Package: hdnom (via r-universe)

October 28, 2026

Type Package

Title Benchmarking and Visualization Toolkit for Penalized Cox Models

Version 6.2.1

Description Creates nomogram visualizations for penalized Cox regression models, with the support of reproducible survival model building, validation, calibration, and comparison for high-dimensional data.

License GPL (>= 3)

LazyData TRUE

URL https://nanx.me/hdnom/, https://github.com/nanxstats/hdnom

BugReports https://github.com/nanxstats/hdnom/issues

Depends R (>= 3.5.0)

Imports foreach, ggplot2, glmnet, gridExtra, ncvreg, penalized, survival

Suggests doParallel, knitr, ragg, rmarkdown

VignetteBuilder knitr

Encoding UTF-8

Config/roxygen2/version 8.0.0

NeedsCompilation yes

Author Nan Xiao [aut, cre] (ORCID: <https://orcid.org/0000-0002-0250-5673>), Qing-Song Xu [aut], Miao-Zhu Li [aut], Frank Harrell [ctb] (rms author), Sergej Potapov [ctb] (survAUC author), Werner Adler [ctb] (survAUC author), Matthias Schmid [ctb] (survAUC author)

Maintainer Nan Xiao <me@nanx.me>

Repository https://cran.r-universe.dev

Date/Publication 2026-07-28 06:50:02 UTC

RemoteUrl https://github.com/cran/hdnom

RemoteRef HEAD

RemoteSha 9ca50ac03af6c201ee52cf4891f35f893bf9d1db

Contents

as_nomogram . . . 3
calibrate . . . 4
calibrate_external . . . 7
compare_by_calibrate . . . 9
compare_by_validate . . . 11
fit_aenet . . . 13
fit_alasso . . . 14
fit_enet . . . 15
fit_flasso . . . 16
fit_lasso . . . 18
fit_mcp . . . 19
fit_mnet . . . 20
fit_scad . . . 21
fit_snet . . . 23
glmnet_basesurv . . . 24
glmnet_survcurve . . . 25
infer_variable_type . . . 25
kmplot . . . 26
logrank_test . . . 27
ncvreg_basesurv . . . 28
ncvreg_survcurve . . . 29
penalized_basesurv . . . 30
penalized_survcurve . . . 30
plot.hdnom.calibrate . . . 31
plot.hdnom.calibrate.external . . . 32
plot.hdnom.compare.calibrate . . . 32
plot.hdnom.compare.validate . . . 33
plot.hdnom.nomogram . . . 34
plot.hdnom.validate . . . 35
plot.hdnom.validate.external . . . 35
predict.hdnom.model . . . 36
print.hdnom.calibrate . . . 37
print.hdnom.calibrate.external . . . 37
print.hdnom.compare.calibrate . . . 38
print.hdnom.compare.validate . . . 38
print.hdnom.model . . . 39
print.hdnom.nomogram . . . 39
print.hdnom.validate . . . 40
print.hdnom.validate.external . . . 40
smart . . . 41
smarto . . . 42
summary.hdnom.calibrate . . . 43
summary.hdnom.calibrate.external . . . 44
summary.hdnom.compare.calibrate . . . 44
summary.hdnom.compare.validate . . . 45
summary.hdnom.validate . . . 45

summary.hdnom.validate.external 46
theme_hdnom 46
validate 47
validate_external 50

Index **54**

`as_nomogram` *Construct nomogram ojects for high-dimensional Cox models*

Description

Construct nomograms ojects for high-dimensional Cox models

Usage

```
as_nomogram(
  object,
  x,
  time,
  event,
  pred.at = NULL,
  fun.at = NULL,
  funlabel = NULL
)
```

Arguments

`object`	Model object fitted by ‘hdnom::fit_*()‘ functions.
`x`	Matrix of training data used for fitting the model.
`time`	Survival time. Must be of the same length with the number of rows as `x`.
`event`	Status indicator, normally 0 = alive, 1 = dead. Must be of the same length with the number of rows as `x`.
`pred.at`	Time point at which to plot nomogram prediction axis.
`fun.at`	Function values to label on axis.
`funlabel`	Label for `fun` axis.

Note

The nomogram visualizes the model under the automatically selected "optimal" hyperparameters (e.g. lambda, alpha, gamma).

Examples

```
data(smart)
x <- as.matrix(smart[, -c(1, 2)])
time <- smart$TEVENT
event <- smart$EVENT
y <- survival::Surv(time, event)

fit <- fit_lasso(x, y, nfolds = 5, rule = "lambda.1se", seed = 1001)

nom <- as_nomogram(
  fit, x, time, event,
  pred.at = 365 * 2,
  funlabel = "2-Year Overall Survival Probability"
)

print(nom)
plot(nom)
```

`calibrate` *Calibrate high-dimensional Cox models*

Description

Calibrate high-dimensional Cox models

Usage

```
calibrate(
  x,
  time,
  event,
 model.type = c("lasso", "alasso", "flasso", "enet", "aenet", "mcp", "mnet", "scad",
    "snet"),
  alpha,
  lambda,
  pen.factor = NULL,
  gamma,
  lambda1,
  lambda2,
  method = c("fitting", "bootstrap", "cv", "repeated.cv"),
  boot.times = NULL,
  nfolds = NULL,
  rep.times = NULL,
  pred.at,
  ngroup = 5,
  cox.ties = c("breslow", "efron"),
  seed = 1001,
  trace = TRUE
)
```

Arguments

x	Matrix of training data used for fitting the model; on which to run the calibration.
time	Survival time. Must be of the same length with the number of rows as x.
event	Status indicator, normally 0 = alive, 1 = dead. Must be of the same length with the number of rows as x.
model.type	Model type to calibrate. Could be one of "lasso", "alasso", "flasso", "enet", "aenet", "mcp", "mnet", "scad", or "snet".
alpha	Value of the elastic-net mixing parameter alpha for enet, aenet, mnet, and snet models. For lasso, alasso, mcp, and scad models, please set alpha = 1. alpha=1: lasso (l1) penalty; alpha=0: ridge (l2) penalty. Note that for mnet and snet models, alpha can be set to very close to 0 but not 0 exactly.
lambda	Value of the penalty parameter lambda to use in the model fits on the resampled data. From the Cox model you have built.
pen.factor	Penalty factors to apply to each coefficient. From the built *adaptive lasso* or *adaptive elastic-net* model.
gamma	Value of the model parameter gamma for MCP/SCAD/Mnet/Snet models.
lambda1	Value of the penalty parameter lambda1 for fused lasso model.
lambda2	Value of the penalty parameter lambda2 for fused lasso model.
method	Calibration method. Options including "fitting", "bootstrap", "cv", and "repeated.cv".
boot.times	Number of repetitions for bootstrap.
nfolds	Number of folds for cross-validation and repeated cross-validation.
rep.times	Number of repeated times for repeated cross-validation.
pred.at	Time point at which calibration should take place.
ngroup	Number of groups to be formed for calibration.
cox.ties	Cox tie-handling method for glmnet model refits.
seed	A random seed for resampling.
trace	Logical. Output the calibration progress or not. Default is TRUE.

Examples

```
data("smart")
x <- as.matrix(smart[, -c(1, 2)])
time <- smart$TEVENT
event <- smart$EVENT
y <- survival::Surv(time, event)

# Fit Cox model with lasso penalty
fit <- fit_lasso(x, y, nfolds = 5, rule = "lambda.1se", seed = 1001)

# Model calibration by fitting the original data directly
cal.fitting <- calibrate(
  x, time, event,
  model.type = "lasso",
```

```
  alpha = 1, lambda = fit$lambda,
  method = "fitting",
  pred.at = 365 * 9, ngroup = 5,
  seed = 1010
)

# Model calibration by 5-fold cross-validation
cal.cv <- calibrate(
  x, time, event,
  model.type = "lasso",
  alpha = 1, lambda = fit$lambda,
  method = "cv", nfolds = 5,
  pred.at = 365 * 9, ngroup = 5,
  seed = 1010
)

print(cal.fitting)
summary(cal.fitting)
plot(cal.fitting)

print(cal.cv)
summary(cal.cv)
plot(cal.cv)

# # Test fused lasso, SCAD, and Mnet models
# data(smart)
# x = as.matrix(smart[, -c(1, 2)])[1:500, ]
# time = smart$TEVENT[1:500]
# event = smart$EVENT[1:500]
# y = survival::Surv(time, event)
#
# set.seed(1010)
# cal.fitting = calibrate(
#   x, time, event, model.type = "flasso",
#   lambda1 = 5, lambda2 = 2,
#   method = "fitting",
#   pred.at = 365 * 9, ngroup = 5,
#   seed = 1010)
#
# cal.boot = calibrate(
#   x, time, event, model.type = "scad",
#   gamma = 3.7, alpha = 1, lambda = 0.03,
#   method = "bootstrap", boot.times = 10,
#   pred.at = 365 * 9, ngroup = 5,
#   seed = 1010)
#
# cal.cv = calibrate(
#   x, time, event, model.type = "mnet",
#   gamma = 3, alpha = 0.3, lambda = 0.03,
#   method = "cv", nfolds = 5,
#   pred.at = 365 * 9, ngroup = 5,
#   seed = 1010)
#
```

```
# cal.repcv = calibrate(
#   x, time, event, model.type = "flasso",
#   lambda1 = 5, lambda2 = 2,
#   method = "repeated.cv", nfolds = 5, rep.times = 3,
#   pred.at = 365 * 9, ngroup = 5,
#   seed = 1010)
#
# print(cal.fitting)
# summary(cal.fitting)
# plot(cal.fitting)
#
# print(cal.boot)
# summary(cal.boot)
# plot(cal.boot)
#
# print(cal.cv)
# summary(cal.cv)
# plot(cal.cv)
#
# print(cal.repcv)
# summary(cal.repcv)
# plot(cal.repcv)
```

`calibrate_external` *Externally calibrate high-dimensional Cox models*

Description

Externally calibrate high-dimensional Cox models

Usage

```
calibrate_external(
  object,
  x,
  time,
  event,
  x_new,
  time_new,
  event_new,
  pred.at,
  ngroup = 5
)
```

Arguments

`object`	Model object fitted by `hdnom::fit_*()`.
`x`	Matrix of training data used for fitting the model.

time	Survival time of the training data. Must be of the same length with the number of rows as x.
event	Status indicator of the training data, normally 0 = alive, 1 = dead. Must be of the same length with the number of rows as x.
x_new	Matrix of predictors for the external validation data.
time_new	Survival time of the external validation data. Must be of the same length with the number of rows as x_new.
event_new	Status indicator of the external validation data, normally 0 = alive, 1 = dead. Must be of the same length with the number of rows as x_new.
pred.at	Time point at which external calibration should take place.
ngroup	Number of groups to be formed for external calibration.

Examples

```
library("survival")

# Load imputed SMART data
data(smart)
# Use the first 1000 samples as training data
# (the data used for internal validation)
x <- as.matrix(smart[, -c(1, 2)])[1:1000, ]
time <- smart$TEVENT[1:1000]
event <- smart$EVENT[1:1000]

# Take the next 1000 samples as external calibration data
# In practice, usually use data collected in other studies
x_new <- as.matrix(smart[, -c(1, 2)])[1001:2000, ]
time_new <- smart$TEVENT[1001:2000]
event_new <- smart$EVENT[1001:2000]

# Fit Cox model with lasso penalty
fit <- fit_lasso(
  x, Surv(time, event),
  nfolds = 5, rule = "lambda.min", seed = 1001
)

# External calibration
cal.ext <- calibrate_external(
  fit, x, time, event,
  x_new, time_new, event_new,
  pred.at = 365 * 5, ngroup = 5
)

print(cal.ext)
summary(cal.ext)
plot(cal.ext, xlim = c(0.6, 1), ylim = c(0.6, 1))
# # Test fused lasso, MCP, and Snet models
# data(smart)
# # Use first 500 samples as training data
# # (the data used for internal validation)
```

```
# x <- as.matrix(smart[, -c(1, 2)])[1:500, ]
# time <- smart$TEVENT[1:500]
# event <- smart$EVENT[1:500]
#
# # Take 1000 samples as external validation data.
# # In practice, usually use data collected in other studies.
# x_new <- as.matrix(smart[, -c(1, 2)])[1001:2000, ]
# time_new <- smart$TEVENT[1001:2000]
# event_new <- smart$EVENT[1001:2000]
#
# flassofit <- fit_flasso(x, survival::Surv(time, event), nfolds = 5, seed = 11)
# scadfit <- fit_mcp(x, survival::Surv(time, event), nfolds = 5, seed = 11)
# mnetfit <- fit_snet(x, survival::Surv(time, event), nfolds = 5, seed = 11)
#
# cal.ext1 <- calibrate_external(
#   flassofit, x, time, event,
#   x_new, time_new, event_new,
#   pred.at = 365 * 5, ngroup = 5)
#
# cal.ext2 <- calibrate_external(
#   scadfit, x, time, event,
#   x_new, time_new, event_new,
#   pred.at = 365 * 5, ngroup = 5)
#
# cal.ext3 <- calibrate_external(
#   mnetfit, x, time, event,
#   x_new, time_new, event_new,
#   pred.at = 365 * 5, ngroup = 5)
#
# print(cal.ext1)
# summary(cal.ext1)
# plot(cal.ext1)
#
# print(cal.ext2)
# summary(cal.ext2)
# plot(cal.ext2)
#
# print(cal.ext3)
# summary(cal.ext3)
# plot(cal.ext3)
```

`compare_by_calibrate` *Compare high-dimensional Cox models by model calibration*

Description

Compare high-dimensional Cox models by model calibration

Usage

```
compare_by_calibrate(
  x,
  time,
  event,
 model.type = c("lasso", "alasso", "flasso", "enet", "aenet", "mcp", "mnet", "scad",
    "snet"),
  method = c("fitting", "bootstrap", "cv", "repeated.cv"),
  boot.times = NULL,
  nfolds = NULL,
  rep.times = NULL,
  pred.at,
  ngroup = 5,
  rule = c("lambda.min", "lambda.1se"),
  cox.ties = c("breslow", "efron"),
  seed = 1001,
  trace = TRUE
)
```

Arguments

x	Matrix of training data used for fitting the model; on which to run the calibration.
time	Survival time. Must be of the same length with the number of rows as x.
event	Status indicator, normally 0 = alive, 1 = dead. Must be of the same length with the number of rows as x.
model.type	Model types to compare. Could be at least two of "lasso", "alasso", "flasso", "enet", "aenet", "mcp", "mnet", "scad", or "snet".
method	Calibration method. Could be "bootstrap", "cv", or "repeated.cv".
boot.times	Number of repetitions for bootstrap.
nfolds	Number of folds for cross-validation and repeated cross-validation.
rep.times	Number of repeated times for repeated cross-validation.
pred.at	Time point at which calibration should take place.
ngroup	Number of groups to be formed for calibration.
rule	Model selection criterion for glmnet models, ‘"lambda.min"‘ or ‘"lambda.1se"‘. Defaults to ‘"lambda.min"‘.
cox.ties	Cox tie-handling method for glmnet model fits and refits.
seed	A random seed for cross-validation fold division.
trace	Logical. Output the calibration progress or not. Default is TRUE.

Examples

```
data(smart)
x <- as.matrix(smart[, -c(1, 2)])
time <- smart$TEVENT
event <- smart$EVENT
```

```
# Compare lasso and adaptive lasso by 5-fold cross-validation
cmp.cal.cv <- compare_by_calibrate(
  x, time, event,
  model.type = c("lasso", "alasso"),
  method = "fitting",
  pred.at = 365 * 9, ngroup = 5, seed = 1001
)

print(cmp.cal.cv)
summary(cmp.cal.cv)
plot(cmp.cal.cv)
```

`compare_by_validate` *Compare high-dimensional Cox models by model validation*

Description

Compare high-dimensional Cox models by model validation

Usage

```
compare_by_validate(
  x,
  time,
  event,
 model.type = c("lasso", "alasso", "flasso", "enet", "aenet", "mcp", "mnet", "scad",
    "snet"),
  method = c("bootstrap", "cv", "repeated.cv"),
  boot.times = NULL,
  nfolds = NULL,
  rep.times = NULL,
  tauc.type = c("CD", "SZ", "UNO"),
  tauc.time,
  rule = c("lambda.min", "lambda.1se"),
  cox.ties = c("breslow", "efron"),
  seed = 1001,
  trace = TRUE
)
```

Arguments

`x`	Matrix of training data used for fitting the model; on which to run the validation.
`time`	Survival time. Must be of the same length with the number of rows as `x`.
`event`	Status indicator, normally 0 = alive, 1 = dead. Must be of the same length with the number of rows as `x`.
`model.type`	Model types to compare. Could be at least two of `"lasso"`, `"alasso"`, `"flasso"`, `"enet"`, `"aenet"`, `"mcp"`, `"mnet"`, `"scad"`, or `"snet"`.

method	Validation method. Could be "bootstrap", "cv", or "repeated.cv".
boot.times	Number of repetitions for bootstrap.
nfolds	Number of folds for cross-validation and repeated cross-validation.
rep.times	Number of repeated times for repeated cross-validation.
tauc.type	Type of time-dependent AUC. Including "CD" proposed by Chambless and Diao (2006)., "SZ" proposed by Song and Zhou (2008)., "UNO" proposed by Uno et al. (2007).
tauc.time	Numeric vector. Time points at which to evaluate the time-dependent AUC.
rule	Model selection criterion for glmnet models, ‘"lambda.min"‘ or ‘"lambda.1se"‘. Defaults to ‘"lambda.min"‘.
cox.ties	Cox tie-handling method for glmnet model fits and refits.
seed	A random seed for cross-validation fold division.
trace	Logical. Output the validation progress or not. Default is TRUE.

References

Chambless, L. E. and G. Diao (2006). Estimation of time-dependent area under the ROC curve for long-term risk prediction. *Statistics in Medicine* 25, 3474–3486.

Song, X. and X.-H. Zhou (2008). A semiparametric approach for the covariate specific ROC curve with survival outcome. *Statistica Sinica* 18, 947–965.

Uno, H., T. Cai, L. Tian, and L. J. Wei (2007). Evaluating prediction rules for t-year survivors with censored regression models. *Journal of the American Statistical Association* 102, 527–537.

Examples

```
data(smart)
x <- as.matrix(smart[, -c(1, 2)])[1:1000, ]
time <- smart$TEVENT[1:1000]
event <- smart$EVENT[1:1000]

# Compare lasso and adaptive lasso by 5-fold cross-validation
cmp.val.cv <- compare_by_validate(
  x, time, event,
  model.type = c("lasso", "alasso"),
  method = "cv", nfolds = 5, tauc.type = "UNO",
  tauc.time = seq(0.25, 2, 0.25) * 365, seed = 1001
)

print(cmp.val.cv)
summary(cmp.val.cv)
plot(cmp.val.cv)
plot(cmp.val.cv, interval = TRUE)
```

`fit_aenet` *Model selection for high-dimensional Cox models with adaptive elastic-net penalty*

Description

Automatic model selection for high-dimensional Cox models with adaptive elastic-net penalty, evaluated by penalized partial-likelihood.

Usage

```
fit_aenet(
  x,
  y,
  nfolds = 5L,
  alphas = seq(0.05, 0.95, 0.05),
  rule = c("lambda.min", "lambda.1se"),
  seed = c(1001, 1002),
  parallel = FALSE,
  cox.ties = c("breslow", "efron")
)
```

Arguments

`x`	Data matrix.
`y`	Response matrix made with `Surv`.
`nfolds`	Fold numbers of cross-validation.
`alphas`	Alphas to tune in `cv.glmnet`.
`rule`	Model selection criterion, `"lambda.min"` or `"lambda.1se"`. See `cv.glmnet` for details.
`seed`	Two random seeds for cross-validation fold division in two estimation steps.
`parallel`	Logical. Enable parallel parameter tuning or not, default is `FALSE`. To enable parallel tuning, load the `doParallel` package and run `registerDoParallel()` with the number of CPU cores before calling this function.
`cox.ties`	Cox tie-handling method passed to `cv.glmnet` and `glmnet`.

Examples

```
data("smart")
x <- as.matrix(smart[, -c(1, 2)])
time <- smart$TEVENT
event <- smart$EVENT
y <- survival::Surv(time, event)

# To enable parallel parameter tuning, first run:
# library("doParallel")
```

```
# registerDoParallel(detectCores())
# then set fit_aenet(..., parallel = TRUE).

fit <- fit_aenet(
  x, y,
  nfolds = 3, alphas = c(0.3, 0.7),
  rule = "lambda.min", seed = c(3, 7)
)

nom <- as_nomogram(
  fit, x, time, event,
  pred.at = 365 * 2,
  funlabel = "2-Year Overall Survival Probability"
)

plot(nom)
```

`fit_alasso` *Model selection for high-dimensional Cox models with adaptive lasso penalty*

Description

Automatic model selection for high-dimensional Cox models with adaptive lasso penalty, evaluated by penalized partial-likelihood.

Usage

```
fit_alasso(
  x,
  y,
  nfolds = 5L,
  rule = c("lambda.min", "lambda.1se"),
  seed = c(1001, 1002),
  cox.ties = c("breslow", "efron")
)
```

Arguments

`x`	Data matrix.
`y`	Response matrix made by `Surv`.
`nfolds`	Fold numbers of cross-validation.
`rule`	Model selection criterion, `"lambda.min"` or `"lambda.1se"`. See `cv.glmnet` for details.
`seed`	Two random seeds for cross-validation fold division in two estimation steps.
`cox.ties`	Cox tie-handling method passed to `cv.glmnet` and `glmnet`.

Examples

```
data("smart")
x <- as.matrix(smart[, -c(1, 2)])
time <- smart$TEVENT
event <- smart$EVENT
y <- survival::Surv(time, event)

fit <- fit_alasso(x, y, nfolds = 3, rule = "lambda.min", seed = c(7, 11))

nom <- as_nomogram(
  fit, x, time, event,
  pred.at = 365 * 2,
  funlabel = "2-Year Overall Survival Probability"
)

plot(nom)
```

`fit_enet` *Model selection for high-dimensional Cox models with elastic-net penalty*

Description

Automatic model selection for high-dimensional Cox models with elastic-net penalty, evaluated by penalized partial-likelihood.

Usage

```
fit_enet(
  x,
  y,
  nfolds = 5L,
  alphas = seq(0.05, 0.95, 0.05),
  rule = c("lambda.min", "lambda.1se"),
  seed = 1001,
  parallel = FALSE,
  cox.ties = c("breslow", "efron")
)
```

Arguments

`x`	Data matrix.
`y`	Response matrix made by `Surv`.
`nfolds`	Fold numbers of cross-validation.
`alphas`	Alphas to tune in `cv.glmnet`.
`rule`	Model selection criterion, `"lambda.min"` or `"lambda.1se"`. See `cv.glmnet` for details.

seed	A random seed for cross-validation fold division.
parallel	Logical. Enable parallel parameter tuning or not, default is FALSE. To enable parallel tuning, load the doParallel package and run registerDoParallel() with the number of CPU cores before calling this function.
cox.ties	Cox tie-handling method passed to cv.glmnet and glmnet.

Examples

```
data("smart")
x <- as.matrix(smart[, -c(1, 2)])
time <- smart$TEVENT
event <- smart$EVENT
y <- survival::Surv(time, event)

# To enable parallel parameter tuning, first run:
# library("doParallel")
# registerDoParallel(detectCores())
# then set fit_enet(..., parallel = TRUE).

fit <- fit_enet(
  x, y,
  nfolds = 3, alphas = c(0.3, 0.7),
  rule = "lambda.min", seed = 3
)

nom <- as_nomogram(
  fit, x, time, event,
  pred.at = 365 * 2,
  funlabel = "2-Year Overall Survival Probability"
)

plot(nom)
```

---

fit_flasso *Model selection for high-dimensional Cox models with fused lasso penalty*

Description

Automatic model selection for high-dimensional Cox models with fused lasso penalty, evaluated by cross-validated likelihood.

Usage

```
fit_flasso(
  x,
  y,
  nfolds = 5L,
```

```
  lambda1 = c(0.001, 0.05, 0.5, 1, 5),
  lambda2 = c(0.001, 0.01, 0.5),
  maxiter = 25,
  epsilon = 0.001,
  seed = 1001,
  trace = FALSE,
  parallel = FALSE,
  ...
)
```

Arguments

x	Data matrix.
y	Response matrix made by Surv.
nfolds	Fold numbers of cross-validation.
lambda1	Vector of lambda1 candidates. Default is 0.001, 0.05, 0.5, 1, 5.
lambda2	Vector of lambda2 candidates. Default is 0.001, 0.01, 0.5.
maxiter	The maximum number of iterations allowed. Default is 25.
epsilon	The convergence criterion. Default is 1e-3.
seed	A random seed for cross-validation fold division.
trace	Output the cross-validation parameter tuning progress or not. Default is FALSE.
parallel	Logical. Enable parallel parameter tuning or not, default is FALSE. To enable parallel tuning, load the doParallel package and run registerDoParallel() with the number of CPU cores before calling this function.
...	other parameters to cvl and penalized.

Note

The cross-validation procedure used in this function is the *approximated cross-validation* provided by the penalized package. Be careful dealing with the results since they might be more optimistic than a traditional CV procedure. This cross-validation method is more suitable for datasets with larger number of observations, and a higher number of cross-validation folds.

Examples

```
data("smart")
x <- as.matrix(smart[, -c(1, 2)])[1:120, ]
time <- smart$TEVENT[1:120]
event <- smart$EVENT[1:120]
y <- survival::Surv(time, event)

fit <- fit_flasso(
  x, y,
  lambda1 = c(1, 10), lambda2 = c(0.01),
  nfolds = 3, seed = 11
)
```

```
nom <- as_nomogram(
  fit, x, time, event,
  pred.at = 365 * 2,
  funlabel = "2-Year Overall Survival Probability"
)

plot(nom)
```

`fit_lasso` *Model selection for high-dimensional Cox models with lasso penalty*

Description

Automatic model selection for high-dimensional Cox models with lasso penalty, evaluated by penalized partial-likelihood.

Usage

```
fit_lasso(
  x,
  y,
  nfolds = 5L,
  rule = c("lambda.min", "lambda.1se"),
  seed = 1001,
  cox.ties = c("breslow", "efron")
)
```

Arguments

`x`	Data matrix.
`y`	Response matrix made by `Surv`.
`nfolds`	Fold numbers of cross-validation.
`rule`	Model selection criterion, `"lambda.min"` or `"lambda.1se"`. See `cv.glmnet` for details.
`seed`	A random seed for cross-validation fold division.
`cox.ties`	Cox tie-handling method passed to `cv.glmnet` and `glmnet`.

Examples

```
data("smart")
x <- as.matrix(smart[, -c(1, 2)])
time <- smart$TEVENT
event <- smart$EVENT
y <- survival::Surv(time, event)

fit <- fit_lasso(x, y, nfolds = 3, rule = "lambda.min", seed = 11)
```

```
nom <- as_nomogram(
  fit, x, time, event,
  pred.at = 365 * 2,
  funlabel = "2-Year Overall Survival Probability"
)

plot(nom)
```

`fit_mcp` *Model selection for high-dimensional Cox models with MCP penalty*

Description

Automatic model selection for high-dimensional Cox models with MCP penalty, evaluated by penalized partial-likelihood.

Usage

```
fit_mcp(
  x,
  y,
  nfolds = 5L,
  gammas = c(1.01, 1.7, 3, 100),
  eps = 1e-04,
  max.iter = 10000L,
  seed = 1001,
  trace = FALSE,
  parallel = FALSE
)
```

Arguments

`x`	Data matrix.
`y`	Response matrix made by `Surv`.
`nfolds`	Fold numbers of cross-validation.
`gammas`	Gammas to tune in `cv.ncvsurv`.
`eps`	Convergence threshhold.
`max.iter`	Maximum number of iterations.
`seed`	A random seed for cross-validation fold division.
`trace`	Output the cross-validation parameter tuning progress or not. Default is `FALSE`.
`parallel`	Logical. Enable parallel parameter tuning or not, default is `FALSE`. To enable parallel tuning, load the `doParallel` package and run `registerDoParallel()` with the number of CPU cores before calling this function.

Examples

```
data("smart")
x <- as.matrix(smart[, -c(1, 2)])
time <- smart$TEVENT
event <- smart$EVENT
y <- survival::Surv(time, event)

fit <- fit_mcp(x, y, nfolds = 3, gammas = c(2.1, 3), seed = 1001)

nom <- as_nomogram(
  fit, x, time, event,
  pred.at = 365 * 2,
  funlabel = "2-Year Overall Survival Probability"
)

plot(nom)
```

`fit_mnet` *Model selection for high-dimensional Cox models with Mnet penalty*

Description

Automatic model selection for high-dimensional Cox models with Mnet penalty, evaluated by penalized partial-likelihood.

Usage

```
fit_mnet(
  x,
  y,
  nfolds = 5L,
  gammas = c(1.01, 1.7, 3, 100),
  alphas = seq(0.05, 0.95, 0.05),
  eps = 1e-04,
  max.iter = 10000L,
  seed = 1001,
  trace = FALSE,
  parallel = FALSE
)
```

Arguments

`x`	Data matrix.
`y`	Response matrix made by `Surv`.
`nfolds`	Fold numbers of cross-validation.
`gammas`	Gammas to tune in `cv.ncvsurv`.

alphas	Alphas to tune in cv.ncvsurv.
eps	Convergence threshhold.
max.iter	Maximum number of iterations.
seed	A random seed for cross-validation fold division.
trace	Output the cross-validation parameter tuning progress or not. Default is FALSE.
parallel	Logical. Enable parallel parameter tuning or not, default is FALSE. To enable parallel tuning, load the doParallel package and run registerDoParallel() with the number of CPU cores before calling this function.

Examples

```
data("smart")
x <- as.matrix(smart[, -c(1, 2)])
time <- smart$TEVENT
event <- smart$EVENT
y <- survival::Surv(time, event)

fit <- fit_mnet(
  x, y,
  nfolds = 3,
  gammas = 3, alphas = c(0.3, 0.6, 0.9),
  max.iter = 15000, seed = 1010
)

nom <- as_nomogram(
  fit, x, time, event,
  pred.at = 365 * 2,
  funlabel = "2-Year Overall Survival Probability"
)

plot(nom)
```

---

fit_scad *Model selection for high-dimensional Cox models with SCAD penalty*

Description

Automatic model selection for high-dimensional Cox models with SCAD penalty, evaluated by penalized partial-likelihood.

Usage

```
fit_scad(
  x,
  y,
  nfolds = 5L,
```

```
  gammas = c(2.01, 2.3, 3.7, 200),
  eps = 1e-04,
  max.iter = 10000L,
  seed = 1001,
  trace = FALSE,
  parallel = FALSE
)
```

Arguments

x	Data matrix.
y	Response matrix made by Surv.
nfolds	Fold numbers of cross-validation.
gammas	Gammas to tune in cv.ncvsurv.
eps	Convergence threshhold.
max.iter	Maximum number of iterations.
seed	A random seed for cross-validation fold division.
trace	Output the cross-validation parameter tuning progress or not. Default is FALSE.
parallel	Logical. Enable parallel parameter tuning or not, default is FALSE. To enable parallel tuning, load the doParallel package and run registerDoParallel() with the number of CPU cores before calling this function.

Examples

```
data("smart")
x <- as.matrix(smart[, -c(1, 2)])
time <- smart$TEVENT
event <- smart$EVENT
y <- survival::Surv(time, event)

fit <- fit_scad(
  x, y,
  nfolds = 3, gammas = c(3.7, 5),
  max.iter = 15000, seed = 1010
)

nom <- as_nomogram(
  fit, x, time, event,
  pred.at = 365 * 2,
  funlabel = "2-Year Overall Survival Probability"
)

plot(nom)
```

fit_snet *Model selection for high-dimensional Cox models with Snet penalty*

Description

Automatic model selection for high-dimensional Cox models with Snet penalty, evaluated by penalized partial-likelihood.

Usage

```
fit_snet(
  x,
  y,
  nfolds = 5L,
  gammas = c(2.01, 2.3, 3.7, 200),
  alphas = seq(0.05, 0.95, 0.05),
  eps = 1e-04,
  max.iter = 10000L,
  seed = 1001,
  trace = FALSE,
  parallel = FALSE
)
```

Arguments

x	Data matrix.
y	Response matrix made by Surv.
nfolds	Fold numbers of cross-validation.
gammas	Gammas to tune in cv.ncvsurv.
alphas	Alphas to tune in cv.ncvsurv.
eps	Convergence threshhold.
max.iter	Maximum number of iterations.
seed	A random seed for cross-validation fold division.
trace	Output the cross-validation parameter tuning progress or not. Default is FALSE.
parallel	Logical. Enable parallel parameter tuning or not, default is FALSE. To enable parallel tuning, load the doParallel package and run registerDoParallel() with the number of CPU cores before calling this function.

Examples

```
data("smart")
x <- as.matrix(smart[, -c(1, 2)])
time <- smart$TEVENT
event <- smart$EVENT
y <- survival::Surv(time, event)
```

```
fit <- fit_snet(
  x, y,
  nfolds = 3,
  gammas = 3.7, alphas = c(0.3, 0.8),
  max.iter = 15000, seed = 1010
)

nom <- as_nomogram(
  fit, x, time, event,
  pred.at = 365 * 2,
  funlabel = "2-Year Overall Survival Probability"
)

plot(nom)
```

`glmnet_basesurv` *Breslow baseline hazard estimator for glmnet objects*

Description

Derived from `peperr:::basesurv` and `gbm::basehaz.gbm`.

Usage

```
glmnet_basesurv(time, event, lp, times.eval = NULL, centered = FALSE)
```

Arguments

`time`	Survival time
`event`	Status indicator
`lp`	Linear predictors
`times.eval`	Survival time to evaluate
`centered`	Should we center the survival curve? See basehaz for details.

Value

list containing cumulative base hazard

Examples

```
NULL
```

glmnet_survcurve *Survival curve prediction for glmnet objects*

Description

Derived from c060::predictProb.coxnet

Usage

```
glmnet_survcurve(object, time, event, x, survtime)
```

Arguments

object	glmnet model object
time	Survival time
event	Status indicator
x	Predictor matrix
survtime	Survival time to evaluate

Value

list containing predicted survival probabilities and linear predictors for all samples

Examples

```
NULL
```

infer_variable_type *Extract information of selected variables from high-dimensional Cox models*

Description

Extract the names and type of selected variables from fitted high-dimensional Cox models.

Usage

```
infer_variable_type(object, x)
```

Arguments

object	Model object.
x	Data matrix used to fit the model.

Value

A list containing the index, name, type and range of the selected variables.

Examples

```
data("smart")
x <- as.matrix(smart[, -c(1, 2)])
time <- smart$TEVENT
event <- smart$EVENT
y <- survival::Surv(time, event)

fit <- fit_lasso(x, y, nfolds = 3, rule = "lambda.min", seed = 11)
infer_variable_type(fit, x)
```

---

kmplot *Kaplan-Meier plot with number at risk table for internal calibration and external calibration results*

Description

Kaplan-Meier plot with number at risk table for internal calibration and external calibration results

Usage

```
kmplot(
  object,
  group.name = NULL,
  time.at = NULL,
  col.pal = c("JCO", "Lancet", "NPG", "AAAS")
)
```

Arguments

object	An object returned by calibrate or calibrate_external.
group.name	Risk group labels. Default is Group 1, Group 2, ..., Group k.
time.at	Time points to evaluate the number at risk.
col.pal	Color palette to use. Possible values are "JCO", "Lancet", "NPG", and "AAAS". Default is "JCO".

Examples

```
data("smart")
# Use the first 1000 samples as training data
# (the data used for internal validation)
x <- as.matrix(smart[, -c(1, 2)])[1:1000, ]
time <- smart$TEVENT[1:1000]
event <- smart$EVENT[1:1000]
```

```
# Take the next 1000 samples as external calibration data
# In practice, usually use data collected in other studies
x_new <- as.matrix(smart[, -c(1, 2)])[1001:2000, ]
time_new <- smart$TEVENT[1001:2000]
event_new <- smart$EVENT[1001:2000]

# Fit Cox model with lasso penalty
fit <- fit_lasso(x, survival::Surv(time, event), nfolds = 5, rule = "lambda.min", seed = 11)

# Internal calibration
cal.int <- calibrate(
  x, time, event,
  model.type = "lasso",
  alpha = 1, lambda = fit$lambda,
  method = "cv", nfolds = 5,
  pred.at = 365 * 9, ngroup = 3
)

kmplot(
  cal.int,
  group.name = c("High risk", "Medium risk", "Low risk"),
  time.at = 1:6 * 365
)

# External calibration
cal.ext <- calibrate_external(
  fit, x, time, event,
  x_new, time_new, event_new,
  pred.at = 365 * 5, ngroup = 3
)

kmplot(
  cal.ext,
  group.name = c("High risk", "Medium risk", "Low risk"),
  time.at = 1:6 * 365
)
```

`logrank_test` *Log-rank test for internal calibration and external calibration results*

Description

Log-rank test for internal calibration and external calibration results

Usage

```
logrank_test(object)
```

Arguments

object	An object returned by calibrate or calibrate_external.

Examples

```
data("smart")
# Use the first 1000 samples as training data
# (the data used for internal validation)
x <- as.matrix(smart[, -c(1, 2)])[1:1000, ]
time <- smart$TEVENT[1:1000]
event <- smart$EVENT[1:1000]

# Take the next 1000 samples as external calibration data
# In practice, usually use data collected in other studies
x_new <- as.matrix(smart[, -c(1, 2)])[1001:2000, ]
time_new <- smart$TEVENT[1001:2000]
event_new <- smart$EVENT[1001:2000]

# Fit Cox model with lasso penalty
fit <- fit_lasso(
  x, survival::Surv(time, event),
  nfolds = 5, rule = "lambda.min", seed = 11
)

# Internal calibration
cal.int <- calibrate(
  x, time, event,
  model.type = "lasso",
  alpha = 1, lambda = fit$lambda,
  method = "cv", nfolds = 5,
  pred.at = 365 * 9, ngroup = 3
)

logrank_test(cal.int)

# External calibration
cal.ext <- calibrate_external(
  fit, x, time, event,
  x_new, time_new, event_new,
  pred.at = 365 * 5, ngroup = 3
)

logrank_test(cal.ext)
```

---

ncvreg_basesurv *Breslow baseline hazard estimator for ncvreg objects*

Description

Derived from peperr:::basesurv and gbm::basehaz.gbm.

Usage

```
ncvreg_basesurv(time, event, lp, times.eval = NULL, centered = FALSE)
```

Arguments

time	Survival time
event	Status indicator
lp	Linear predictors
times.eval	Survival time to evaluate
centered	Should we center the survival curve? See basehaz for details.

Value

list containing cumulative base hazard

Examples

```
NULL
```

---

ncvreg_survcurve *Survival curve prediction for ncvreg objects*

Description

Derived from c060::predictProb.coxnet

Usage

```
ncvreg_survcurve(object, time, event, x, survtime)
```

Arguments

object	ncvreg model object
time	Survival time
event	Status indicator
x	Predictor matrix
survtime	Survival time to evaluate

Value

list containing predicted survival probabilities and linear predictors for all samples

Examples

```
NULL
```

penalized_basesurv *Breslow baseline hazard estimator for penfit objects*

Description

Derived from `peperr:::basesurv` and `gbm::basehaz.gbm`.

Usage

```
penalized_basesurv(time, event, lp, times.eval = NULL, centered = FALSE)
```

Arguments

`time`	Survival time
`event`	Status indicator
`lp`	Linear predictors
`times.eval`	Survival time to evaluate
`centered`	Should we center the survival curve? See basehaz for details.

Value

list containing cumulative base hazard

Examples

```
NULL
```

penalized_survcurve *Survival curve prediction for penfit objects*

Description

Derived from c060::predictProb.coxnet

Usage

```
penalized_survcurve(object, time, event, x, survtime)
```

Arguments

`object`	`penalized` model object
`time`	Survival time
`event`	Status indicator
`x`	Predictor matrix
`survtime`	Survival time to evaluate

Value

list containing predicted survival probabilities and linear predictors for all samples

Examples

```
NULL
```

`plot.hdnom.calibrate` *Plot calibration results*

Description

Plot calibration results

Usage

```
## S3 method for class 'hdnom.calibrate'
plot(
  x,
  xlim = c(0, 1),
  ylim = c(0, 1),
  col.pal = c("JCO", "Lancet", "NPG", "AAAS"),
  ...
)
```

Arguments

`x`	An object returned by `calibrate`.
`xlim`	x axis limits of the plot.
`ylim`	y axis limits of the plot.
`col.pal`	Color palette to use. Possible values are `"JCO"`, `"Lancet"`, `"NPG"`, and `"AAAS"`. Default is `"JCO"`.
`...`	Other parameters for `plot`.

Examples

```
NULL
```

`plot.hdnom.calibrate.external`

Plot external calibration results

Description

Plot external calibration results

Usage

```
## S3 method for class 'hdnom.calibrate.external'
plot(
  x,
  xlim = c(0, 1),
  ylim = c(0, 1),
  col.pal = c("JCO", "Lancet", "NPG", "AAAS"),
  ...
)
```

Arguments

`x`	An object returned by `calibrate_external`.
`xlim`	x axis limits of the plot.
`ylim`	y axis limits of the plot.
`col.pal`	Color palette to use. Possible values are `"JCO"`, `"Lancet"`, `"NPG"`, and `"AAAS"`. Default is `"JCO"`.
`...`	Other parameters for `plot`.

Examples

```
NULL
```

`plot.hdnom.compare.calibrate`

Plot model comparison by calibration results

Description

Plot model comparison by calibration results

Usage

```
## S3 method for class 'hdnom.compare.calibrate'
plot(
  x,
  xlim = c(0, 1),
  ylim = c(0, 1),
  col.pal = c("JCO", "Lancet", "NPG", "AAAS"),
  ...
)
```

Arguments

x	An object returned by compare_by_calibrate.
xlim	x axis limits of the plot.
ylim	y axis limits of the plot.
col.pal	Color palette to use. Possible values are "JCO", "Lancet", "NPG", and "AAAS". Default is "JCO".
...	Other parameters (not used).

Examples

```
NULL
```

---

plot.hdnom.compare.validate

Plot model comparison by validation results

Description

Plot model comparison by validation results

Usage

```
## S3 method for class 'hdnom.compare.validate'
plot(
  x,
  interval = FALSE,
  col.pal = c("JCO", "Lancet", "NPG", "AAAS"),
  ylim = NULL,
  ...
)
```

Arguments

x	An object returned by compare_by_validate.
interval	Show maximum, minimum, 0.25, and 0.75 quantiles of time-dependent AUC as ribbons? Default is FALSE.
col.pal	Color palette to use. Possible values are "JCO", "Lancet", "NPG", and "AAAS". Default is "JCO".
ylim	Range of y coordinates. For example, c(0.5, 1).
...	Other parameters (not used).

Examples

```
NULL
```

---

plot.hdnom.nomogram *Plot nomogram objects*

Description

Plot nomogram objects

Usage

```
## S3 method for class 'hdnom.nomogram'
plot(x, ...)
```

Arguments

x	An object returned by as_nomogram.
...	Other parameters.

Examples

```
NULL
```

plot.hdnom.validate *Plot optimism-corrected time-dependent discrimination curves for validation*

Description

Plot optimism-corrected time-dependent discrimination curves for validation

Usage

```
## S3 method for class 'hdnom.validate'
plot(x, col.pal = c("JCO", "Lancet", "NPG", "AAAS"), ylim = NULL, ...)
```

Arguments

x	An object returned by validate.
col.pal	Color palette to use. Possible values are "JCO", "Lancet", "NPG", and "AAAS". Default is "JCO".
ylim	Range of y coordinates. For example, c(0.5, 1).
...	Other parameters (not used).

Examples

```
NULL
```

plot.hdnom.validate.external *Plot time-dependent discrimination curves for external validation*

Description

Plot time-dependent discrimination curves for external validation

Usage

```
## S3 method for class 'hdnom.validate.external'
plot(x, col.pal = c("JCO", "Lancet", "NPG", "AAAS"), ylim = NULL, ...)
```

Arguments

x	An object returned by validate_external.
col.pal	Color palette to use. Possible values are "JCO", "Lancet", "NPG", and "AAAS". Default is "JCO".
ylim	Range of y coordinates. For example, c(0.5, 1).
...	Other parameters (not used).

Examples

```
NULL
```

`predict.hdnom.model` *Make predictions from high-dimensional Cox models*

Description

Predict overall survival probability at certain time points from fitted Cox models.

Usage

```
## S3 method for class 'hdnom.model'
predict(object, x, y, newx, pred.at, ...)
```

Arguments

`object`	Model object.
`x`	Data matrix used to fit the model.
`y`	Response matrix made with `Surv`.
`newx`	Matrix (with named columns) of new values for `x` at which predictions are to be made.
`pred.at`	Time point at which prediction should take place.
`...`	Other parameters (not used).

Value

A `nrow(newx)` x `length(pred.at)` matrix containing overall survival probablity.

Examples

```
data("smart")
x <- as.matrix(smart[, -c(1, 2)])
time <- smart$TEVENT
event <- smart$EVENT
y <- survival::Surv(time, event)

fit <- fit_lasso(x, y, nfolds = 5, rule = "lambda.min", seed = 11)
predict(fit, x, y, newx = x[101:105, ], pred.at = 1:10 * 365)
```

print.hdnom.calibrate *Print calibration results*

Description

Print calibration results

Usage

```
## S3 method for class 'hdnom.calibrate'
print(x, ...)
```

Arguments

x	An object returned by calibrate.
...	Other parameters (not used).

Examples

```
NULL
```

print.hdnom.calibrate.external *Print external calibration results*

Description

Print external calibration results

Usage

```
## S3 method for class 'hdnom.calibrate.external'
print(x, ...)
```

Arguments

x	An object returned by calibrate_external.
...	Other parameters (not used).

Examples

```
NULL
```

`print.hdnom.compare.calibrate`

Print model comparison by calibration results

Description

Print model comparison by calibration results

Usage

```
## S3 method for class 'hdnom.compare.calibrate'
print(x, ...)
```

Arguments

`x`	An object returned by `compare_by_calibrate`.
`...`	Other parameters (not used).

Examples

```
NULL
```

`print.hdnom.compare.validate`

Print model comparison by validation results

Description

Print model comparison by validation results

Usage

```
## S3 method for class 'hdnom.compare.validate'
print(x, ...)
```

Arguments

`x`	An object returned by `compare_by_validate`.
`...`	Other parameters (not used).

Examples

```
NULL
```

print.hdnom.model *Print high-dimensional Cox model objects*

Description

Print high-dimensional Cox model objects

Usage

```
## S3 method for class 'hdnom.model'
print(x, ...)
```

Arguments

x	Model object.
...	Other parameters (not used).

Examples

```
data("smart")
x <- as.matrix(smart[, -c(1, 2)])
time <- smart$TEVENT
event <- smart$EVENT
y <- survival::Surv(time, event)

fit <- fit_lasso(x, y, nfolds = 5, rule = "lambda.min", seed = 11)
print(fit)
```

print.hdnom.nomogram *Print nomograms objects*

Description

Print nomograms objects

Usage

```
## S3 method for class 'hdnom.nomogram'
print(x, ...)
```

Arguments

x	An object returned by as_nomogram.
...	Other parameters.

Examples

```
NULL
```

print.hdnom.validate *Print validation results*

Description

Print validation results

Usage

```
## S3 method for class 'hdnom.validate'
print(x, ...)
```

Arguments

x	An object returned by validate.
...	Other parameters (not used).

Examples

```
NULL
```

print.hdnom.validate.external *Print external validation results*

Description

Print external validation results

Usage

```
## S3 method for class 'hdnom.validate.external'
print(x, ...)
```

Arguments

x	An object returned by validate_external.
...	Other parameters (not used).

Examples

```
NULL
```

`smart` *Imputed SMART study data*

Description

Imputed SMART study data (no missing values).

Usage

```
data(smart)
```

Format

A numeric matrix with 3873 samples, and 29 variables (27 variables + time variable + event variable):

- Demographics
  - SEX - gender
  - AGE - age in years
- Classical risk factors
  - SMOKING - smoking (never, former, current)
  - PACKYRS - in years
  - ALCOHOL - alcohol use (never, former, current)
  - BMI - Body mass index, in kg/m^2
  - DIABETES
- Blood pressure
  - SYSTH - Systolic, by hand, in mm Hg
  - SYSTBP - Systolic, automatic, in mm Hg
  - DIASTH - Diastolic, by hand, in mm Hg
  - DIASTBP - Diastolic, automatic, in mm Hg
- Lipid levels
  - CHOL - Total cholesterol, in mmol/L
  - HDL - High-density lipoprotein cholesterol, in mmol/L
  - LDL - Low-density lipoprotein cholesterol, in mmol/L
  - TRIG - Triglycerides, in mmol/L
- Previous symptomatic atherosclerosis
  - CEREBRAL - Cerebral
  - CARDIAC - Coronary
  - PERIPH - Peripheral
  - AAA - Abdominal aortic aneurysm
- Markers of atherosclerosis
  - HOMOC - Homocysteine, in μmol/L

  - GLUT - Glutamine, in μmol/L
  - CREAT - Creatinine clearance, in mL/min
  - ALBUMIN - Albumin (no, micro, macro)
  - IMT - Intima media thickness, in mm
  - STENOSIS - Carotid artery stenosis > 50%

Note

See `data-raw/smart.R` for the code to generate this data.

References

Steyerberg, E. W. (2008). Clinical prediction models: a practical approach to development, validation, and updating. Springer Science & Business Media.

Examples

```
data(smart)
dim(smart)
```

`smarto` *Original SMART study data*

Description

Original SMART study data (with missing values) from Steyerberg et, al. 2008.

Usage

```
data(smarto)
```

Format

A numeric matrix with 3873 samples, and 29 variables (27 variables + time variable + event variable):

- Demographics
  - SEX - gender
  - AGE - age in years
- Classical risk factors
  - SMOKING - smoking (never, former, current)
  - PACKYRS - in years
  - ALCOHOL - alcohol use (never, former, current)
  - BMI - Body mass index, in kg/m^2
  - DIABETES
- Blood pressure

  - SYSTH - Systolic, by hand, in mm Hg
  - SYSTBP - Systolic, automatic, in mm Hg
  - DIASTH - Diastolic, by hand, in mm Hg
  - DIASTBP - Diastolic, automatic, in mm Hg
- Lipid levels
  - CHOL - Total cholesterol, in mmol/L
  - HDL - High-density lipoprotein cholesterol, in mmol/L
  - LDL - Low-density lipoprotein cholesterol, in mmol/L
  - TRIG - Triglycerides, in mmol/L
- Previous symptomatic atherosclerosis
  - CEREBRAL - Cerebral
  - CARDIAC - Coronary
  - PERIPH - Peripheral
  - AAA - Abdominal aortic aneurysm
- Markers of atherosclerosis
  - HOMOC - Homocysteine, in μmol/L
  - GLUT - Glutamine, in μmol/L
  - CREAT - Creatinine clearance, in mL/min
  - ALBUMIN - Albumin (no, micro, macro)
  - IMT - Intima media thickness, in mm
  - STENOSIS - Carotid artery stenosis > 50%

References

Steyerberg, E. W. (2008). Clinical prediction models: a practical approach to development, validation, and updating. Springer Science & Business Media.

Examples

```
data(smarto)
dim(smarto)
```

`summary.hdnom.calibrate`

Summary of calibration results

Description

Summary of calibration results

Usage

```
## S3 method for class 'hdnom.calibrate'
summary(object, ...)
```

Arguments

object	An object returned by calibrate.
...	Other parameters (not used).

Examples

```
NULL
```

---

summary.hdnom.calibrate.external

Summary of external calibration results

Description

Summary of external calibration results

Usage

```
## S3 method for class 'hdnom.calibrate.external'
summary(object, ...)
```

Arguments

object	An object returned by calibrate_external.
...	Other parameters (not used).

Examples

```
NULL
```

---

summary.hdnom.compare.calibrate

Summary of model comparison by calibration results

Description

Summary of model comparison by calibration results

Usage

```
## S3 method for class 'hdnom.compare.calibrate'
summary(object, ...)
```

Arguments

object	An object returned by compare_by_calibrate.
...	Other parameters (not used).

Examples

```
NULL
```

---

summary.hdnom.compare.validate

Summary of model comparison by validation results

Description

Summary of model comparison by validation results

Usage

```
## S3 method for class 'hdnom.compare.validate'
summary(object, silent = FALSE, ...)
```

Arguments

object	An object compare_by_validate.
silent	Print summary table header or not, default is FALSE.
...	Other parameters (not used).

Examples

```
NULL
```

---

summary.hdnom.validate

Summary of validation results

Description

Summary of validation results

Usage

```
## S3 method for class 'hdnom.validate'
summary(object, silent = FALSE, ...)
```

Arguments

object	A validate object.
silent	Print summary table header or not, default is FALSE.
...	Other parameters (not used).

Examples

```
NULL
```

---

summary.hdnom.validate.external *Summary of external validation results*

Description

Summary of external validation results

Usage

```
## S3 method for class 'hdnom.validate.external'
summary(object, silent = FALSE, ...)
```

Arguments

object	An object returned by validate_external.
silent	Print summary table header or not, default is FALSE.
...	Other parameters (not used).

Examples

```
NULL
```

---

theme_hdnom *Plot theme (ggplot2) for hdnom*

Description

Plot theme (ggplot2) for hdnom

Usage

```
theme_hdnom(base_size = 14)
```

Arguments

base_size	base font size

validate *Validate high-dimensional Cox models with time-dependent AUC*

Description

Validate high-dimensional Cox models with time-dependent AUC

Usage

```
validate(
  x,
  time,
  event,
 model.type = c("lasso", "alasso", "flasso", "enet", "aenet", "mcp", "mnet", "scad",
    "snet"),
  alpha,
  lambda,
  pen.factor = NULL,
  gamma,
  lambda1,
  lambda2,
  method = c("bootstrap", "cv", "repeated.cv"),
  boot.times = NULL,
  nfolds = NULL,
  rep.times = NULL,
  tauc.type = c("CD", "SZ", "UNO"),
  tauc.time,
  cox.ties = c("breslow", "efron"),
  seed = 1001,
  trace = TRUE
)
```

Arguments

x	Matrix of training data used for fitting the model; on which to run the validation.
time	Survival time. Must be of the same length with the number of rows as x.
event	Status indicator, normally 0 = alive, 1 = dead. Must be of the same length with the number of rows as x.
model.type	Model type to validate. Could be one of "lasso", "alasso", "flasso", "enet", "aenet", "mcp", "mnet", "scad", or "snet".
alpha	Value of the elastic-net mixing parameter alpha for enet, aenet, mnet, and snet models. For lasso, alasso, mcp, and scad models, please set alpha = 1. alpha=1: lasso (l1) penalty; alpha=0: ridge (l2) penalty. Note that for mnet and snet models, alpha can be set to very close to 0 but not 0 exactly.
lambda	Value of the penalty parameter lambda to use in the model fits on the resampled data. From the fitted Cox model.

pen.factor	Penalty factors to apply to each coefficient. From the fitted *adaptive lasso* or *adaptive elastic-net* model.
gamma	Value of the model parameter gamma for MCP/SCAD/Mnet/Snet models.
lambda1	Value of the penalty parameter lambda1 for fused lasso model.
lambda2	Value of the penalty parameter lambda2 for fused lasso model.
method	Validation method. Could be "bootstrap", "cv", or "repeated.cv".
boot.times	Number of repetitions for bootstrap.
nfolds	Number of folds for cross-validation and repeated cross-validation.
rep.times	Number of repeated times for repeated cross-validation.
tauc.type	Type of time-dependent AUC. Including "CD" proposed by Chambless and Diao (2006)., "SZ" proposed by Song and Zhou (2008)., "UNO" proposed by Uno et al. (2007).
tauc.time	Numeric vector. Time points at which to evaluate the time-dependent AUC.
cox.ties	Cox tie-handling method for glmnet model refits.
seed	A random seed for resampling.
trace	Logical. Output the validation progress or not. Default is TRUE.

References

Chambless, L. E. and G. Diao (2006). Estimation of time-dependent area under the ROC curve for long-term risk prediction. *Statistics in Medicine* 25, 3474–3486.

Song, X. and X.-H. Zhou (2008). A semiparametric approach for the covariate specific ROC curve with survival outcome. *Statistica Sinica* 18, 947–965.

Uno, H., T. Cai, L. Tian, and L. J. Wei (2007). Evaluating prediction rules for t-year survivors with censored regression models. *Journal of the American Statistical Association* 102, 527–537.

Examples

```
data(smart)
x <- as.matrix(smart[, -c(1, 2)])[1:500, ]
time <- smart$TEVENT[1:500]
event <- smart$EVENT[1:500]
y <- survival::Surv(time, event)

fit <- fit_lasso(x, y, nfolds = 5, rule = "lambda.min", seed = 11)

# Model validation by bootstrap with time-dependent AUC
# Normally boot.times should be set to 200 or more,
# we set it to 3 here only to save example running time.
val.boot <- validate(
  x, time, event,
  model.type = "lasso",
  alpha = 1, lambda = fit$lambda,
  method = "bootstrap", boot.times = 3,
  tauc.type = "UNO", tauc.time = seq(0.25, 2, 0.25) * 365,
  seed = 1010
```

```
)

# Model validation by 5-fold cross-validation with time-dependent AUC
val.cv <- validate(
  x, time, event,
  model.type = "lasso",
  alpha = 1, lambda = fit$lambda,
  method = "cv", nfolds = 5,
  tauc.type = "UNO", tauc.time = seq(0.25, 2, 0.25) * 365,
  seed = 1010
)

# Model validation by repeated cross-validation with time-dependent AUC
val.repcv <- validate(
  x, time, event,
  model.type = "lasso",
  alpha = 1, lambda = fit$lambda,
  method = "repeated.cv", nfolds = 5, rep.times = 3,
  tauc.type = "UNO", tauc.time = seq(0.25, 2, 0.25) * 365,
  seed = 1010
)

# bootstrap-based discrimination curves has a very narrow band
print(val.boot)
summary(val.boot)
plot(val.boot)

# k-fold cv provides a more strict evaluation than bootstrap
print(val.cv)
summary(val.cv)
plot(val.cv)

# repeated cv provides similar results as k-fold cv
# but more robust than k-fold cv
print(val.repcv)
summary(val.repcv)
plot(val.repcv)
# # Test fused lasso, SCAD, and Mnet models
#
# data(smart)
# x = as.matrix(smart[, -c(1, 2)])[1:500,]
# time = smart$TEVENT[1:500]
# event = smart$EVENT[1:500]
# y = survival::Surv(time, event)
#
# set.seed(1010)
# val.boot = validate(
#   x, time, event, model.type = "flasso",
#   lambda1 = 5, lambda2 = 2,
#   method = "bootstrap", boot.times = 10,
#   tauc.type = "UNO", tauc.time = seq(0.25, 2, 0.25) * 365,
#   seed = 1010)
#
```

```
# val.cv = validate(
#   x, time, event, model.type = "scad",
#   gamma = 3.7, alpha = 1, lambda = 0.05,
#   method = "cv", nfolds = 5,
#   tauc.type = "UNO", tauc.time = seq(0.25, 2, 0.25) * 365,
#   seed = 1010)
#
# val.repcv = validate(
#   x, time, event, model.type = "mnet",
#   gamma = 3, alpha = 0.3, lambda = 0.05,
#   method = "repeated.cv", nfolds = 5, rep.times = 3,
#   tauc.type = "UNO", tauc.time = seq(0.25, 2, 0.25) * 365,
#   seed = 1010)
#
# print(val.boot)
# summary(val.boot)
# plot(val.boot)
#
# print(val.cv)
# summary(val.cv)
# plot(val.cv)
#
# print(val.repcv)
# summary(val.repcv)
# plot(val.repcv)
```

`validate_external` *Externally validate high-dimensional Cox models with time-dependent AUC*

Description

Externally validate high-dimensional Cox models with time-dependent AUC

Usage

```
validate_external(
  object,
  x,
  time,
  event,
  x_new,
  time_new,
  event_new,
  tauc.type = c("CD", "SZ", "UNO"),
  tauc.time
)
```

Arguments

`object`	Model object fitted by `hdnom::fit_*()`.
`x`	Matrix of training data used for fitting the model.
`time`	Survival time of the training data. Must be of the same length with the number of rows as `x`.
`event`	Status indicator of the training data, normally 0 = alive, 1 = dead. Must be of the same length with the number of rows as `x`.
`x_new`	Matrix of predictors for the external validation data.
`time_new`	Survival time of the external validation data. Must be of the same length with the number of rows as `x_new`.
`event_new`	Status indicator of the external validation data, normally 0 = alive, 1 = dead. Must be of the same length with the number of rows as `x_new`.
`tauc.type`	Type of time-dependent AUC. Including `"CD"` proposed by Chambless and Diao (2006)., `"SZ"` proposed by Song and Zhou (2008)., `"UNO"` proposed by Uno et al. (2007).
`tauc.time`	Numeric vector. Time points at which to evaluate the time-dependent AUC.

References

Chambless, L. E. and G. Diao (2006). Estimation of time-dependent area under the ROC curve for long-term risk prediction. *Statistics in Medicine* 25, 3474–3486.

Song, X. and X.-H. Zhou (2008). A semiparametric approach for the covariate specific ROC curve with survival outcome. *Statistica Sinica* 18, 947–965.

Uno, H., T. Cai, L. Tian, and L. J. Wei (2007). Evaluating prediction rules for t-year survivors with censored regression models. *Journal of the American Statistical Association* 102, 527–537.

Examples

```
data(smart)
# Use the first 1000 samples as training data
# (the data used for internal validation)
x <- as.matrix(smart[, -c(1, 2)])[1:1000, ]
time <- smart$TEVENT[1:1000]
event <- smart$EVENT[1:1000]

# Take the next 1000 samples as external validation data
# In practice, usually use data collected in other studies
x_new <- as.matrix(smart[, -c(1, 2)])[1001:2000, ]
time_new <- smart$TEVENT[1001:2000]
event_new <- smart$EVENT[1001:2000]

# Fit Cox model with lasso penalty
fit <- fit_lasso(
  x, survival::Surv(time, event),
  nfolds = 5, rule = "lambda.min", seed = 11
)
```

```
# External validation with time-dependent AUC
val.ext <- validate_external(
  fit, x, time, event,
  x_new, time_new, event_new,
  tauc.type = "UNO",
  tauc.time = seq(0.25, 2, 0.25) * 365
)

print(val.ext)
summary(val.ext)
plot(val.ext)

# # Test fused lasso, MCP, and Snet models
# data(smart)
# # Use first 600 samples as training data
# # (the data used for internal validation)
# x <- as.matrix(smart[, -c(1, 2)])[1:600, ]
# time <- smart$TEVENT[1:600]
# event <- smart$EVENT[1:600]
#
# # Take 500 samples as external validation data.
# # In practice, usually use data collected in other studies.
# x_new <- as.matrix(smart[, -c(1, 2)])[1001:1500, ]
# time_new <- smart$TEVENT[1001:1500]
# event_new <- smart$EVENT[1001:1500]
#
# flassofit <- fit_flasso(x, survival::Surv(time, event), nfolds = 5, seed = 11)
# scadfit <- fit_mcp(x, survival::Surv(time, event), nfolds = 5, seed = 11)
# mnetfit <- fit_snet(x, survival::Surv(time, event), nfolds = 5, seed = 11)
#
# val.ext1 <- validate_external(
#   flassofit, x, time, event,
#   x_new, time_new, event_new,
#   tauc.type = "UNO",
#   tauc.time = seq(0.25, 2, 0.25) * 365)
#
# val.ext2 <- validate_external(
#   scadfit, x, time, event,
#   x_new, time_new, event_new,
#   tauc.type = "CD",
#   tauc.time = seq(0.25, 2, 0.25) * 365)
#
# val.ext3 <- validate_external(
#   mnetfit, x, time, event,
#   x_new, time_new, event_new,
#   tauc.type = "SZ",
#   tauc.time = seq(0.25, 2, 0.25) * 365)
#
# print(val.ext1)
# summary(val.ext1)
# plot(val.ext1)
#
# print(val.ext2)
```

```
# summary(val.ext2)
# plot(val.ext2)
#
# print(val.ext3)
# summary(val.ext3)
# plot(val.ext3)
```

Index

as_nomogram, 3, *34*, *39*

basehaz, *24*, *29, 30*

calibrate, 4, *26*, *28*, *31*, *37*, *44*
calibrate_external, 7, *26*, *28*, *32*, *37*, *44*
compare_by_calibrate, 9, *33*, *38*, *45*
compare_by_validate, 11, *34*, *38*, *45*
cv.glmnet, *13–16*, *18*
cv.ncvsurv, *19–23*
cvl, *17*

fit_aenet, 13
fit_alasso, 14
fit_enet, 15
fit_flasso, 16
fit_lasso, 18
fit_mcp, 19
fit_mnet, 20
fit_scad, 21
fit_snet, 23

glmnet, *13, 14*, *16*, *18*
glmnet_basesurv, 24
glmnet_survcurve, 25

infer_variable_type, 25

kmplot, 26

logrank_test, 27

ncvreg_basesurv, 28
ncvreg_survcurve, 29

penalized, *17*
penalized_basesurv, 30
penalized_survcurve, 30
plot.hdnom.calibrate, 31
plot.hdnom.calibrate.external, 32
plot.hdnom.compare.calibrate, 32
plot.hdnom.compare.validate, 33
plot.hdnom.nomogram, 34
plot.hdnom.validate, 35
plot.hdnom.validate.external, 35
predict.hdnom.model, 36
print.hdnom.calibrate, 37
print.hdnom.calibrate.external, 37
print.hdnom.compare.calibrate, 38
print.hdnom.compare.validate, 38
print.hdnom.model, 39
print.hdnom.nomogram, 39
print.hdnom.validate, 40
print.hdnom.validate.external, 40

smart, 41
smarto, 42
summary.hdnom.calibrate, 43
summary.hdnom.calibrate.external, 44
summary.hdnom.compare.calibrate, 44
summary.hdnom.compare.validate, 45
summary.hdnom.validate, 45
summary.hdnom.validate.external, 46
Surv, *13–15*, *17–20*, *22, 23*, *36*

theme_hdnom, 46

validate, *35*, *40*, *46*, 47
validate_external, *35*, *40*, *46*, 50