

Package: hereR (via r-universe)

November 28, 2024

Type Package

Title 'sf'-Based Interface to the 'HERE' REST APIs

Version 1.0.1

Maintainer Merlin Unterfinger <info@munterfinger.ch>

URL <https://munterfi.github.io/hereR/>,
<https://github.com/munterfi/hereR/>

BugReports <https://github.com/munterfi/hereR/issues/>

Description Interface to the 'HERE' REST APIs

<<https://developer.here.com/develop/rest-apis>>: (1) geocode and autosuggest addresses or reverse geocode POIs using the 'Geocoder' API; (2) route directions, travel distance or time matrices and isolines using the 'Routing', 'Matrix Routing' and 'Isoline Routing' APIs; (3) request real-time traffic flow and incident information from the 'Traffic' API; (4) find request public transport connections and nearby stations from the 'Public Transit' API; (5) request intermodal routes using the 'Intermodal Routing' API; (6) get weather forecasts, reports on current weather conditions, astronomical information and alerts at a specific location from the 'Destination Weather' API. Locations, routes and isolines are returned as 'sf' objects.

Depends R (>= 3.3.0)

Imports crul (>= 1.1.0), curl (>= 4.3), data.table (>= 1.13.0), flexpolyline (>= 0.2.0), jsonlite (>= 1.7.0), sf (>= 0.9-0), stringr (>= 1.4.0)

Suggests covr (>= 3.5.0), ggplot2 (>= 3.3.2), htmlwidgets (>= 1.5.1), knitr (>= 1.29), leafpop (>= 0.0.5), lwgeom (>= 0.2-5), mapview (>= 2.9.0), rmarkdown (>= 2.3), testthat (>= 2.3.2)

License GPL-3

Encoding UTF-8

LazyData true

RoxygenNote 7.3.2

VignetteBuilder knitr**NeedsCompilation** no**Author** Merlin Unterfinger [aut, cre](<<https://orcid.org/0000-0003-2020-2366>>), Daniel Possenriede
[ctb] (<<https://orcid.org/0000-0002-6738-9845>>)**Repository** CRAN**Date/Publication** 2024-11-27 22:20:02 UTC**Config/pak/sysreqs** libgdal-dev gdal-bin libgeos-dev libicu-dev
libssl-dev libproj-dev libsqlite3-dev libudunits2-dev

Contents

aoi	2
autosuggest	3
connection	4
flow	5
geocode	6
incident	7
intermodal_route	8
isoline	9
poi	10
reverse_geocode	11
route	12
route_matrix	13
set_currency	15
set_freemium	15
set_key	16
set_verbose	16
station	17
unset_key	18
weather	18
Index	20

aoi

Example Areas of Interest

Description

Some example Areas of Interest (AOIs): The boundary polygons of the districts of Zurich. The districts serve as the basis for administrative tasks within the City of Zurich.

Usage

```
data(aoi)
```

Format

An object of class "sf", "data.frame".

Source

City of Zurich - Department of Civil Engineering and Waste Management - Geomatics + Surveying
@geocat.ch

Examples

```
data(aoi)
```

autosuggest

HERE Geocoding & Search API: Autosuggest

Description

Completes addresses using the HERE 'Geocoder Autosuggest' API.

Usage

```
autosuggest(address, results = 5, url_only = FALSE)
```

Arguments

address	character, address text to propose suggestions.
results	numeric, maximum number of suggestions (Valid range: 1 and 100).
url_only	boolean, only return the generated URLs (default = FALSE)?

Value

A data.frame object, containing the suggestions for the input addresses.

References

[HERE Geocoder API: Autosuggest](#)

Examples

```
# Provide an API Key for a HERE project
set_key("<YOUR API KEY>")

suggestions <- autosuggest(address = poi$city, url_only = TRUE)
```

 connection

HERE Public Transit API: Transit Route

Description

Route public transport connections with geometries (LINESTRING) between pairs of points using the HERE 'Public Transit' API. Two modes are provided:

- `summary = FALSE`: The public transport connections are returned as multiple sections with the same vehicle and transport mode. Each section has a detailed route geometry.
- `summary = TRUE`: A summary of the connections is retrieved, where each connection is represented as one row with a unified and simplified geometry.

Usage

```
connection(
  origin,
  destination,
  datetime = Sys.time(),
  arrival = FALSE,
  results = 3,
  transfers = -1,
  transport_mode = NULL,
  summary = FALSE,
  url_only = FALSE
)
```

Arguments

<code>origin</code>	sf object, the origin locations of geometry type POINT.
<code>destination</code>	sf object, the destination locations of geometry type POINT.
<code>datetime</code>	POSIXct object, datetime for the departure (or arrival if <code>arrival = TRUE</code>).
<code>arrival</code>	boolean, calculate connections for arrival at the defined time (default = FALSE)?
<code>results</code>	numeric, maximum number of suggested public transport routes (Valid range: 1 and 6).
<code>transfers</code>	numeric, maximum number of transfers allowed per route (Valid range: -1 and 6, whereby the default = -1 allows for unlimited transfers).
<code>transport_mode</code>	character, enable or disable ("-" prefix) transport modes. Note: Do not enable and disable modes at the same time (default = NULL).
<code>summary</code>	boolean, return a summary of the public transport connections instead of the sections of the routes (default = FALSE)?
<code>url_only</code>	boolean, only return the generated URLs (default = FALSE)?

Value

An sf object containing the requested routes.

References

[HERE Public Transit API: Transit Route](#)

Examples

```
# Provide an API Key for a HERE project
set_key("<YOUR API KEY>")

# Connection sections
sections <- connection(
  origin = poi[3:4, ], destination = poi[5:6, ],
  summary = FALSE, url_only = TRUE
)

# Connection summary
summary <- connection(
  origin = poi[3:4, ], destination = poi[5:6, ],
  summary = TRUE, url_only = TRUE
)
```

flow

HERE Traffic API: Flow

Description

Real-time traffic flow from the HERE 'Traffic' API in areas of interest (AOIs). The traffic flow data contains speed and congestion information, which corresponds to the status of the traffic at the time of the query.

Usage

```
flow(aoi, min_jam_factor = 0, url_only = FALSE)
```

Arguments

<code>aoi</code>	sf object, Areas of Interest (POIs) of geometry type POLYGON.
<code>min_jam_factor</code>	numeric, only retrieve flow information with a jam factor greater than the value provided (default = 0).
<code>url_only</code>	boolean, only return the generated URLs (default = FALSE)?

Value

An sf object containing the requested traffic flow information.

Note

The maximum width and height of the bounding box of the input AOIs is 1 degree. This means that each polygon (= one row) in the AOI sf object should fit in a 1 x 1 degree bbox.

References

[HERE Traffic API: Flow](#)

Examples

```
# Provide an API Key for a HERE project
set_key("<YOUR API KEY>")

# Real-time traffic flow
flow_data <- flow(
  aoi = aoi,
  url_only = TRUE
)
```

geocode

HERE Geocoding & Search API: Geocode

Description

Geocodes addresses using the HERE 'Geocoding & Search API' API.

Usage

```
geocode(address, alternatives = FALSE, sf = TRUE, url_only = FALSE)
```

Arguments

address	character, addresses to geocode or a list containing qualified queries with the keys "country", "state", "county", "city", "district", "street", "houseNumber" or "postalCode".
alternatives	boolean, return also alternative results (default = FALSE)?
sf	boolean, return an sf object (default = TRUE) or a data.frame?
url_only	boolean, only return the generated URLs (default = FALSE)?

Value

If `sf = TRUE`, an sf object, containing the position coordinates geocoded addresses as geometry list column and the access coordinates as well-known text (WKT). If `sf = FALSE`, a data.frame containing the coordinates of the geocoded addresses as lng, lat columns.

According to the Geocoding and Search API Reference, the access coordinates are "[c]oordinates of the place you are navigating to (for example, driving or walking). This is a point on a road or in a parking lot." The position coordinates are "[t]he coordinates (latitude, longitude) of a pin on a map corresponding to the searched place."

References

[HERE Geocoding & Search API: Geocode](#)

Examples

```
# Provide an API Key for a HERE project
set_key("<YOUR API KEY>")

locs <- geocode(address = poi$city, url_only = TRUE)
```

incident

*HERE Traffic API: Incidents***Description**

Traffic incident information from the HERE 'Traffic' API in areas of interest (AOIs). The incidents contain information about location, duration, severity, type, description and further details.

Usage

```
incident(aoi, from = NULL, to = NULL, url_only = FALSE)
```

Arguments

aoi	sf object, Areas of Interest (POIs) of geometry type POLYGON.
from	POSIXct object, start time of the earliest traffic incidents (default = NULL).
to	POSIXct object, end time of the latest traffic incidents (default = NULL).
url_only	boolean, only return the generated URLs (default = FALSE)?

Value

An sf object containing the traffic incidents.

Note

The maximum width and height of the bounding box of the input AOIs is 1 degree. This means that each polygon (= one row) in the AOI sf object should fit in a 1 x 1 degree bbox.

References

[HERE Traffic API: Incidents](#)

Examples

```
# Provide an API Key for a HERE project
set_key("<YOUR API KEY>")

# Traffic incidents
incidents <- incident(
  aoi = aoi,
  url_only = TRUE
)
```

intermodal_route *HERE Intermodal Routing API: Calculate Route*

Description

Calculates route geometries (LINESTRING) between given pairs of points using the HERE 'Intermodal Routing' API.

Usage

```
intermodal_route(
  origin,
  destination,
  datetime = Sys.time(),
  results = 3,
  transfers = -1,
  url_only = FALSE
)
```

Arguments

origin	sf object, the origin locations of geometry type POINT.
destination	sf object, the destination locations of geometry type POINT.
datetime	POSIXct object, datetime for the departure (default = Sys.time()).
results	numeric, maximum number of suggested route alternatives (Valid range: 1 and 7, default = 3).
transfers	numeric, maximum number of transfers allowed per route (Valid range: -1 and 6, default = -1).
url_only	boolean, only return the generated URLs (default = FALSE)?

Value

An sf object containing the requested intermodal routes.

References

[HERE Intermodal Routing API: Routes](#)

Examples

```
# Provide an API Key for a HERE project
set_key("<YOUR API KEY>")

# Intermodal routing
routes <- intermodal_route(
  origin = poi[1:3, ],
  destination = poi[4:6, ],
```



```

    url_only = TRUE
  )

```

isoline

HERE Isoline Routing API: Calculate Isoline

Description

Calculates isolines (POLYGON or MULTIPOLYGON) using the HERE 'Isoline Routing' API that connect the end points of all routes leaving from defined centers (POIs) with either a specified length, a specified travel time or consumption (only the default E-car available).

Usage

```

isoline(
  poi,
  datetime = Sys.time(),
  arrival = FALSE,
  range = seq(5, 30, 5) * 60,
  range_type = "time",
  routing_mode = "fast",
  transport_mode = "car",
  traffic = TRUE,
  optimize = "balanced",
  consumption_model = NULL,
  aggregate = FALSE,
  url_only = FALSE
)

```

Arguments

<code>poi</code>	sf object, Points of Interest (POIs) of geometry type POINT.
<code>datetime</code>	POSIXct object, datetime for the departure (or arrival if <code>arrival = TRUE</code>).
<code>arrival</code>	boolean, are the provided Points of Interest (POIs) the origin or destination locations (default = FALSE)?
<code>range</code>	numeric, a vector of type integer containing the breaks for the generation of the isolines: (1) time in seconds; (2) distance in meters; (3) consumption in Wh.
<code>range_type</code>	character, unit of the isolines: "distance", "time" or "consumption".
<code>routing_mode</code>	character, set the routing mode: "fast" or "short".
<code>transport_mode</code>	character, set the transport mode: "car", "pedestrian" or "truck".
<code>traffic</code>	boolean, use real-time traffic or prediction in routing (default = TRUE)? If no traffic is selected, the datetime is set to "any" and the request is processed independently from time.
<code>optimize</code>	character, specifies how isoline calculation is optimized: "balanced", "quality" or "performance" (default = "balanced").

consumption_model	character, specify the consumption model of the vehicle (default = NULL an average electric car is set).
aggregate	boolean, aggregate (with function min) and intersect the isolines from geometry type POLYGON to geometry type MULTIPOLYGON (default = FALSE)?
url_only	boolean, only return the generated URLs (default = FALSE)?

Value

An sf object containing the requested isolines.

References

[HERE Isoline Routing API](#)

Examples

```
# Provide an API Key for a HERE project
set_key("<YOUR API KEY>")

# Isochrone for 5, 10, 15, 20, 25 and 30 minutes driving time
isolines <- isoline(
  poi = poi,
  range = seq(5, 30, 5) * 60,
  url_only = TRUE
)
```

poi

Example Points of Interest

Description

Some example Points of Interest (POIs): Cities in Switzerland and Liechtenstein with more than 100'000 inhabitants.

Usage

```
data(poi)
```

Format

An object of class "sf", "data.frame".

Source

Made with Natural Earth. Free vector and raster map data [@naturalearthdata.com](https://www.naturalearthdata.com)

Examples

```
data(poi)
```

reverse_geocode	<i>HERE Geocoding & Search API: Reverse Geocode</i>
-----------------	---

Description

Get addresses from locations using the HERE 'Geocoder' API. The return value is an `sf` object, containing point geometries with suggestions for addresses near the provided POIs.

Usage

```
reverse_geocode(poi, results = 1, sf = TRUE, url_only = FALSE)
```

Arguments

<code>poi</code>	<code>sf</code> object, Points of Interest (POIs) of geometry type POINT.
<code>results</code>	numeric, maximum number of results (Valid range: 1 and 100).
<code>sf</code>	boolean, return an <code>sf</code> object (default = TRUE) or a <code>data.frame</code> ?
<code>url_only</code>	boolean, only return the generated URLs (default = FALSE)?

Value

If `sf = TRUE`, an `sf` object, containing the position coordinates of the reverse geocoded POIs as geometry list column and the access coordinates as well-known text (WKT). If `sf = FALSE`, a `data.frame` containing the coordinates of the reverse geocoded POIs as `lng`, `lat` columns.

Note

If no addresses are found near a POI, `NULL` for this POI is returned. In this case the rows corresponding to this particular POI are missing and merging the POIs by row is not possible. However, in the returned `sf` object, the column "id" matches the rows of the input POIs. The "id" column can be used to join the original POIs.

References

[HERE Geocoder API: Reverse Geocode](#)

Examples

```
# Provide an API Key for a HERE project
set_key("<YOUR API KEY>")

# Get addresses
addresses <- reverse_geocode(poi = poi, results = 3, url_only = TRUE)
```

 route

HERE Routing API: Calculate Route

Description

Calculates route geometries (LINESTRING) between given pairs of points using the HERE 'Routing' API. Routes can be created for various transport modes, as for example 'car' or 'bicycle', incorporating current traffic information, if available. For routes using the transport mode "car" a vehicle consumption model can be specified, to obtain an estimate of the consumption.

Usage

```
route(
  origin,
  destination,
  datetime = Sys.time(),
  arrival = FALSE,
  results = 1,
  routing_mode = "fast",
  transport_mode = "car",
  traffic = TRUE,
  avoid_area = NULL,
  avoid_feature = NULL,
  consumption_model = NULL,
  vignettes = TRUE,
  url_only = FALSE
)
```

Arguments

origin	sf object, the origin locations of geometry type POINT.
destination	sf object, the destination locations of geometry type POINT.
datetime	POSIXct object, datetime for the departure (or arrival if arrival = TRUE).
arrival	boolean, calculate routes for arrival at the defined time (default = FALSE)?
results	numeric, maximum number of suggested routes (Valid range: 1 and 7).
routing_mode	character, set the routing type: "fast" or "short" (default = "fast").
transport_mode	character, set the transport mode: "car", "truck", "pedestrian", "bicycle", "scooter", "taxi", "bus" or "privateBus" (default = "car").
traffic	boolean, use real-time traffic or prediction in routing (default = TRUE)? If no traffic is selected, the datetime is set to "any" and the request is processed independently from time.
avoid_area	sf object, area (only bounding box is taken) to avoid in routes (default = NULL).
avoid_feature	character, transport network features to avoid, e.g. "tollRoad" or "ferry" (default = NULL).

consumption_model	character, specify the consumption model of the vehicle (default = NULL an average electric car is set).
vignettes	boolean, include vignettes in the total toll cost of routes (default = TRUE).
url_only	boolean, only return the generated URLs (default = FALSE)?

Value

An sf object containing the requested routes.

Tolls are requested for routes with transport mode "car", "truck" "taxi" or "bus". The currency defaults to the current system locale settings. A different currency can be set using `set_currency` and a currency code compliant to ISO 4217.

References

[HERE Routing API: Calculate Route](#)

Examples

```
# Provide an API Key for a HERE project
set_key("<YOUR API KEY>")

# Get all from - to combinations from POIs
to <- poi[rep(seq_len(nrow(poi)), nrow(poi)), ]
from <- poi[rep(seq_len(nrow(poi)), each = nrow(poi)), ]
idx <- apply(to != from, any, MARGIN = 1)
to <- to[idx, ]
from <- from[idx, ]

# Routing
routes <- route(
  origin = from, destination = to, results = 3,
  transport_mode = "car", url_only = TRUE
)
```

route_matrix

HERE Matrix Routing API: Calculate Matrix

Description

Calculates a matrix of M:N, M:1 or 1:N route summaries between given points of interest (POIs) using the HERE 'Matrix Routing' API. Various transport modes and traffic information at a provided timestamp are supported. The requested matrix is split into (sub-)matrices of dimension 15x100 to use the maximum matrix size per request and thereby minimize the number of overall needed requests. The result is one route summary matrix, that fits the order of the provided POIs: `orig_id`, `dest_id`.

Usage

```
route_matrix(
  origin,
  destination = origin,
  datetime = Sys.time(),
  routing_mode = "fast",
  transport_mode = "car",
  traffic = TRUE,
  url_only = FALSE
)
```

Arguments

origin	sf object, the origin locations (M) of geometry type POINT.
destination	sf object, the destination locations (N) of geometry type POINT.
datetime	POSIXct object, datetime for the departure.
routing_mode	character, set the routing type: "fast" or "short" (default = "fast").
transport_mode	character, set the transport mode: "car", "truck", "pedestrian", "bicycle", "scooter", "taxi", "bus" or "privateBus" (default = "car").
traffic	boolean, use real-time traffic or prediction in routing (default = TRUE)? If no traffic is selected, the datetime is set to "any" and the request is processed independently from time.
url_only	boolean, only return the generated URLs (default = FALSE)?

Value

A data.frame, which is an edge list containing the requested M:N route combinations.

Note

This feature is no longer available with new freemium keys on the HERE platform. For more details, refer to the [HERE API documentation](#).

References

[HERE Matrix Routing API](#)

Examples

```
# Provide an API Key for a HERE project
set_key("<YOUR API KEY>")

# Create routes summaries between all POIs
mat <- route_matrix(
  origin = poi,
  url_only = TRUE
)
```

set_currency	<i>Set the currency for HERE API requests</i>
--------------	---

Description

If the currency is not set using this function call, the currency defined in the monetary representations in the current locale is used. If the monetary formatting category "LC_MONETARY" of the C locale is not set, "USD" is set as default.

Usage

```
set_currency(currency = NULL)
```

Arguments

currency	character, the currency code compliant to ISO 4217 to use in the requests (default = NULL, which defaults to the current system locale settings).
----------	---

Value

None.

Examples

```
set_currency("CHF")
```

set_freemium	<i>Set whether plan is freemium or not</i>
--------------	--

Description

If set to TRUE the hereR package limits the requests per second (RPS) sent to the APIs and routing matrices will be chopped up into submatrices of size 15x100. This option is necessary for freemium licenses to avoid hitting the rate limit of the APIs with status code 429. Deactivate this option to increase speed of requests for paid plans.

Usage

```
set_freemium(ans = TRUE)
```

Arguments

ans	boolean, use limits or not (default = TRUE)?
-----	--

Value

None.

Examples

```
set_freemium(FALSE)
```

set_key	<i>Set HERE Application Credentials</i>
---------	---

Description

Provide an API Key for a HERE project of type 'REST'. The key is set for the current R session and is used to authenticate in the requests to the APIs.

Usage

```
set_key(api_key)
```

Arguments

api_key character, the API key from a HERE project.

Details

No login yet? Get a login and key here: [klick](#)

Value

None.

Examples

```
set_key("<YOUR API KEY>")
```

set_verbose	<i>Verbose API usage of hereR</i>
-------------	-----------------------------------

Description

If set to TRUE the hereR package is messaging information about the amount of requests sent to the APIs and data size received.

Usage

```
set_verbose(ans = FALSE)
```

Arguments

ans boolean, verbose or not (default = FALSE)?

Value

None.

Examples

```
set_verbose(TRUE)
```

station	<i>HERE Public Transit API: Find Stations Nearby</i>
---------	--

Description

Retrieve stations with the corresponding line information around given locations using the HERE 'Public Transit' API.

Usage

```
station(poi, radius = 500, results = 50, url_only = FALSE)
```

Arguments

poi	sf object, Points of Interest (POIs) of geometry type POINT.
radius	numeric, the search radius in meters (default = 500).
results	numeric, maximum number of suggested public transport stations (Valid range: 1 and 50, default = 50).
url_only	boolean, only return the generated URLs (default = FALSE)?

Value

An sf object containing the requested stations with the corresponding line information.

References

[HERE Public Transit API: Station Search](#)

Examples

```
# Provide an API Key for a HERE project
set_key("<YOUR API KEY>")

# Stations
stations <- station(poi = poi, url_only = TRUE)
```

unset_key	<i>Remove HERE Application Credentials</i>
-----------	--

Description

Remove previously set HERE API key from the current R session.

Usage

```
unset_key()
```

Value

None.

Examples

```
unset_key()
```

weather	<i>HERE Destination Weather API: Observations, Forecasts, Astronomy and Alerts</i>
---------	--

Description

Weather forecasts, reports on current weather conditions, astronomical information and alerts at a specific location (coordinates or location name) based on the HERE 'Destination Weather' API. The information comes from the nearest available weather station and is not interpolated.

Usage

```
weather(poi, product = "observation", url_only = FALSE)
```

Arguments

poi	sf object or character, Points of Interest (POIs) of geometry type POINT or location names (e.g. cities or regions).
product	character, weather product of the 'Destination Weather API'. Supported products: "observation", "forecastHourly", "forecastAstronomy" and "alerts".
url_only	boolean, only return the generated URLs (default = FALSE)?

Value

An sf object containing the requested weather information at the nearest weather station. The point geometry in the sf object is the location of the weather station.

References

[HERE Destination Weather API](#)

Examples

```
# Provide an API Key for a HERE project
set_key("<YOUR API KEY>")

# Observation
observation <- weather(poi = poi, product = "observation", url_only = TRUE)

# Forecast
forecast <- weather(poi = poi, product = "forecast_hourly", url_only = TRUE)

# Astronomy
astronomy <- weather(poi = poi, product = "forecast_astronomy", url_only = TRUE)

# Alerts
alerts <- weather(poi = poi, product = "alerts", url_only = TRUE)
```

Index

* datasets

aoi, [2](#)
poi, [10](#)

aoi, [2](#)
autosuggest, [3](#)

connection, [4](#)

flow, [5](#)

geocode, [6](#)

incident, [7](#)
intermodal_route, [8](#)
isoline, [9](#)

poi, [10](#)

reverse_geocode, [11](#)
route, [12](#)
route_matrix, [13](#)

set_currency, [13](#), [15](#)
set_freemium, [15](#)
set_key, [16](#)
set_verbose, [16](#)
station, [17](#)

unset_key, [18](#)

weather, [18](#)