Package: iccbeta (via r-universe)

October 27, 2026

Type Package

Title Multilevel Model Intraclass Correlation for Slope Heterogeneity

Version 1.2.1

Description A function and vignettes for computing an intraclass correlation described in Aguinis & Culpepper (2015) <doi:10.1177/1094428114563618>. This package quantifies the share of variance in a dependent variable that is attributed to group heterogeneity in slopes.

URL https://tmsalab.github.io/iccbeta/, https://github.com/tmsalab/iccbeta

BugReports https://github.com/tmsalab/iccbeta/issues

License GPL (>= 2)

Depends R (>= 4.3.0)

Imports Rcpp, lme4, stats, methods

LinkingTo Rcpp (>= 1.1.0), RcppArmadillo (>= 15.0.2-2)

Suggests RLRsim, testthat, covr

RoxygenNote 7.3.3

Encoding UTF-8

LazyData true

NeedsCompilation yes

Author Steven Andrew Culpepper [aut, cph, cre] (ORCID: <https://orcid.org/0000-0003-4226-6176>), Herman Aguinis [aut, cph] (ORCID: <https://orcid.org/0000-0002-3485-9484>)

Maintainer Steven Andrew Culpepper <sculpepp@illinois.edu>

Repository https://cran.r-universe.dev

Date/Publication 2026-03-06 08:00:09 UTC

RemoteUrl https://github.com/cran/iccbeta

RemoteRef HEAD

RemoteSha e575b7ba2a01005284ffbbc265f1a8e2b037726f

Contents

iccbeta-package 2
Hofmann 4
icc_beta 5
simICCdata 8

Index **11**

`iccbeta-package` *iccbeta: Multilevel Model Intraclass Correlation for Slope Heterogeneity*

Description

A function and vignettes for computing an intraclass correlation described in Aguinis & Culpepper (2015) doi:10.1177/1094428114563618. This package quantifies the share of variance in a dependent variable that is attributed to group heterogeneity in slopes.

Author(s)

Maintainer: Steven Andrew Culpepper <sculpepp@illinois.edu> (ORCID) [copyright holder]

Authors:

- Herman Aguinis <haguinis@gwu.edu> (ORCID) [copyright holder]

References

Aguinis, H., & Culpepper, S.A. (2015). An expanded decision making procedure for examining cross-level interaction effects with multilevel modeling. *Organizational Research Methods*. Available at: http://www.hermanaguinis.com/pubs.html

See Also

Useful links:

- https://tmsalab.github.io/iccbeta/
- https://github.com/tmsalab/iccbeta
- Report bugs at https://github.com/tmsalab/iccbeta/issues

Examples

```
## Not run:

if(requireNamespace("lme4") && requireNamespace("RLRsim")){
# Simulated Data Example
data(simICCdata)
library('lme4')
```

```
# computing icca
vy <- var(simICCdata$Y)
lmm0 <- lmer(Y ~ (1|l2id), data = simICCdata, REML = FALSE)
VarCorr(lmm0)$l2id[1,1]/vy

# Create simICCdata2
grp_means = aggregate(simICCdata[c('X1','X2')], simICCdata['l2id'],mean)
colnames(grp_means)[2:3] = c('m_X1','m_X2')
simICCdata2 = merge(simICCdata,grp_means,by='l2id')

# Estimating random slopes model
lmm1  <- lmer(Y ~ I(X1-m_X1) + I(X2-m_X2) + (I(X1-m_X1) + I(X2-m_X2) | l2id),
              data = simICCdata2, REML = FALSE)
X <- model.matrix(lmm1)
p <- ncol(X)
T1 <- VarCorr(lmm1)$l2id[1:p, 1:p]

# computing iccb
# Notice '+1' because icc_beta assumes l2ids are from 1 to 30.
icc_beta(X, simICCdata2$l2id + 1, T1, vy)$rho_beta

# Hofmann 2000 Example
data(Hofmann)
library('lme4')

# Random-Intercepts Model
lmmHofmann0 <- lmer(helping ~ (1|id), data = Hofmann)
vy_Hofmann <- var(Hofmann[,'helping'])
# computing icca
VarCorr(lmmHofmann0)$id[1,1]/vy_Hofmann

# Estimating Group-Mean Centered Random Slopes Model, no level 2 variables
lmmHofmann1  <- lmer(helping ~ mood_grp_cent + (mood_grp_cent | id),
                     data = Hofmann, REML = FALSE)
X_Hofmann <- model.matrix(lmmHofmann1)
P <- ncol(X_Hofmann)
T1_Hofmann <- VarCorr(lmmHofmann1)$id[1:P, 1:P]
# computing iccb
icc_beta(X_Hofmann, Hofmann[,'id'], T1_Hofmann, vy_Hofmann)$rho_beta

# Performing LR test
library('RLRsim')
lmmHofmann1a  <- lmer(helping ~ mood_grp_cent + (1 |id),
                      data = Hofmann, REML = FALSE)
obs.LRT <- 2*(logLik(lmmHofmann1) - logLik(lmmHofmann1a))[1]
X <- getME(lmmHofmann1,"X")
Z <- t(as.matrix(getME(lmmHofmann1,"Zt")))
sim.LRT <- LRTSim(X, Z, 0, diag(ncol(Z)))
(pval <- mean(sim.LRT > obs.LRT))
} else {
 stop("Please install packages `RLRsim` and `lme4` to run the above example.")
}
```

```
## End(Not run)
```

Hofmann *A multilevel dataset from Hofmann, Griffin, and Gavin (2000).*

Description

A multilevel dataset from Hofmann, Griffin, and Gavin (2000).

Usage

```
Hofmann
```

Format

A data frame with 1,000 observations and 7 variables.

`id` a numeric vector of group ids.

`helping` a numeric vector of the helping outcome variable construct.

`mood` a level 1 mood predictor.

`mood_grp_mn` a level 2 variable of the group mean of mood.

`cohesion` a level 2 covariate measuring cohesion.

`mood_grp_cent` group-mean centered mood predictor.

`mood_grd_cent` grand-mean centered mood predictor.

Source

Hofmann, D.A., Griffin, M.A., & Gavin, M.B. (2000). The application of hierarchical linear modeling to management research. In K.J. Klein, & S.W.J. Kozlowski (Eds.), Multilevel theory, research, and methods in organizations: Foundations, extensions, and new directions (pp. 467-511). Hoboken, NJ: Jossey-Bass.

References

Aguinis, H., & Culpepper, S.A. (2015). An expanded decision making procedure for examining cross-level interaction effects with multilevel modeling. *Organizational Research Methods*. Available at: http://hermanaguinis.com/pubs.html

See Also

`lmer`, `model.matrix`, `VarCorr`, `LRTSim`, `simICCdata`

Examples

```
## Not run:

if(requireNamespace("lme4") && requireNamespace("RLRsim")){
data(Hofmann)
library("lme4")

# Random-Intercepts Model
lmmHofmann0 = lmer(helping ~ (1|id), data = Hofmann)
vy_Hofmann = var(Hofmann[,'helping'])

# Computing icca
VarCorr(lmmHofmann0)$id[1,1]/vy_Hofmann

# Estimating Group-Mean Centered Random Slopes Model, no level 2 variables
lmmHofmann1  <- lmer(helping ~ mood_grp_cent + (mood_grp_cent |id),
                     data = Hofmann, REML = FALSE)
X_Hofmann = model.matrix(lmmHofmann1)
P = ncol(X_Hofmann)
T1_Hofmann  = VarCorr(lmmHofmann1)$id[1:P,1:P]

# Computing iccb
icc_beta(X_Hofmann, Hofmann[,'id'], T1_Hofmann, vy_Hofmann)$rho_beta

# Performing LR test
# Need to install 'RLRsim' package
library("RLRsim")
lmmHofmann1a  <- lmer(helping ~ mood_grp_cent + (1 | id),
                      data = Hofmann, REML = FALSE)
obs.LRT <- 2*(logLik(lmmHofmann1) - logLik(lmmHofmann1a))[1]
X <- getME(lmmHofmann1,"X")
Z <- t(as.matrix(getME(lmmHofmann1,"Zt")))
sim.LRT <- LRTSim(X, Z, 0, diag(ncol(Z)))
(pval <- mean(sim.LRT > obs.LRT))
} else {
 stop("Please install packages `RLRsim` and `lme4` to run the above example.")
}

## End(Not run)
```

`icc_beta` *Intraclass correlation used to assess variability of lower-order relationships across higher-order processes/units.*

Description

A function and vignettes for computing the intraclass correlation described in Aguinis & Culpepper (2015). iccbeta quantifies the share of variance in an outcome variable that is attributed to heterogeneity in slopes due to higher-order processes/units.

Usage

```
icc_beta(x, ...)

## S3 method for class 'lmerMod'
icc_beta(x, ...)

## Default S3 method:
icc_beta(x, l2id, T, vy, ...)
```

Arguments

x	A lmer model object or a design matrix with no missing values.
...	Additional parameters...
l2id	A vector that identifies group membership. The vector must be coded as a sequence of integers from 1 to J, the number of groups.
T	A matrix of the estimated variance-covariance matrix of a lmer model fit.
vy	The variance of the outcome variable.

Value

A list with:

- J
- means
- XcpXc
- Nj
- rho_beta

Author(s)

Steven Andrew Culpepper

References

Aguinis, H., & Culpepper, S.A. (2015). An expanded decision making procedure for examining cross-level interaction effects with multilevel modeling. *Organizational Research Methods*. Available at: http://hermanaguinis.com/pubs.html

See Also

lme4::lmer(), model.matrix(), lme4::VarCorr(), RLRsim::LRTSim(), Hofmann, and simICCdata

Examples

```
## Not run:

if(requireNamespace("lme4") && requireNamespace("RLRsim")){

## Example 1: Simulated Data Example from Aguinis & Culpepper (2015) ----
data(simICCdata)
library("lme4")

# Computing icca
vy <- var(simICCdata$Y)
lmm0 <- lmer(Y ~ (1 | l2id), data = simICCdata, REML = FALSE)
VarCorr(lmm0)$l2id[1, 1]/vy

# Create simICCdata2
grp_means = aggregate(simICCdata[c('X1', 'X2')], simICCdata['l2id'], mean)
colnames(grp_means)[2:3] = c('m_X1', 'm_X2')
simICCdata2 = merge(simICCdata, grp_means, by='l2id')

# Estimating random slopes model
lmm1  <- lmer(Y ~ I(X1 - m_X1) + I(X2 - m_X2) +
                 (I(X1 - m_X1) + I(X2 - m_X2) | l2id),
              data = simICCdata2, REML = FALSE)

## iccbeta calculation on `lmer` object
icc_beta(lmm1)

## Manual specification of iccbeta

# Extract components from model.
X <- model.matrix(lmm1)
p <- ncol(X)
T1  <- VarCorr(lmm1)$l2id[1:p,1:p]

# Note: vy was computed under "icca"

# Computing iccb
# Notice '+1' because icc_beta assumes l2ids are from 1 to 30.
icc_beta(X, simICCdata2$l2id + 1, T1, vy)$rho_beta

## Example 2: Hofmann et al. (2000)   ----

data(Hofmann)
library("lme4")

# Random-Intercepts Model
lmmHofmann0 = lmer(helping ~ (1|id), data = Hofmann)
vy_Hofmann = var(Hofmann[,'helping'])

# Computing icca
VarCorr(lmmHofmann0)$id[1,1]/vy_Hofmann
```

```
# Estimating Group-Mean Centered Random Slopes Model, no level 2 variables
lmmHofmann1 <- lmer(helping ~ mood_grp_cent + (mood_grp_cent |id),
                    data = Hofmann, REML = FALSE)

## Automatic calculation of iccbeta using the lmer model
amod = icc_beta(lmmHofmann1)

## Manual calculation of iccbeta

X_Hofmann <- model.matrix(lmmHofmann1)
P <- ncol(X_Hofmann)
T1_Hofmann <- VarCorr(lmmHofmann1)$id[1:P,1:P]

# Computing iccb
bmod = icc_beta(X_Hofmann, Hofmann[,'id'], T1_Hofmann, vy_Hofmann)$rho_beta

# Performing LR test
library("RLRsim")
lmmHofmann1a <- lmer(helping ~ mood_grp_cent + (1 |id),
                     data = Hofmann, REML = FALSE)
obs.LRT <- 2*(logLik(lmmHofmann1) - logLik(lmmHofmann1a))[1]
X <- getME(lmmHofmann1,"X")
Z <- t(as.matrix(getME(lmmHofmann1,"Zt")))
sim.LRT <- LRTSim(X, Z, 0, diag(ncol(Z)))
(pval <- mean(sim.LRT > obs.LRT))
} else {
 stop("Please install packages `RLRsim` and `lme4` to run the above example.")
}


## End(Not run)
```

`simICCdata` *Simulated data example from Aguinis and Culpepper (2015).*

Description

A simulated data example from Aguinis and Culpepper (2015) to demonstrate the `icc_beta` function for computing the proportion of variance in the outcome variable that is attributed to heterogeneity in slopes due to higher-order processes/units.

Usage

```
simICCdata
```

Format

A data frame with 900 observations (i.e., 30 observations nested within 30 groups) on the following 6 variables.

`l1id` A within group ID variable.

`l2id` A group ID variable.

`one` A column of 1's for the intercept.

`X1` A simulated level 1 predictor.

`X2` A simulated level 1 predictor.

`Y` A simulated outcome variable.

Details

See Aguinis and Culpepper (2015) for the model used to simulate the dataset.

Source

Aguinis, H., & Culpepper, S.A. (2015). An expanded decision making procedure for examining cross-level interaction effects with multilevel modeling. *Organizational Research Methods*. Available at: http://www.hermanaguinis.com/pubs.html

See Also

lmer, model.matrix, VarCorr, LRTSim, Hofmann

Examples

```
## Not run:
data(simICCdata)
if(requireNamespace("lme4")){
library("lme4")

# computing icca
vy <- var(simICCdata$Y)
lmm0 <- lmer(Y ~ (1|l2id), data = simICCdata, REML = FALSE)
VarCorr(lmm0)$l2id[1,1]/vy

# Create simICCdata2
grp_means = aggregate(simICCdata[c('X1','X2')], simICCdata['l2id'],mean)
colnames(grp_means)[2:3] = c('m_X1','m_X2')
simICCdata2 = merge(simICCdata, grp_means, by='l2id')

# Estimating random slopes model
lmm1  <- lmer(Y ~ I(X1-m_X1) + I(X2-m_X2) + (I(X1-m_X1) + I(X2-m_X2) | l2id),
              data = simICCdata2, REML = FALSE)
X <- model.matrix(lmm1)
p <- ncol(X)
T1 <- VarCorr(lmm1) $l2id[1:p,1:p]
# computing iccb
# Notice '+1' because icc_beta assumes l2ids are from 1 to 30.
icc_beta(X, simICCdata2$l2id+1, T1, vy)$rho_beta
} else {
 stop("Please install `lme4` to run the above example.")
}
```

```
## End(Not run)
```

Index

∗ **datasets**
Hofmann, 4
simICCdata, 8

Hofmann, 4, *6*, *9*

icc_beta, 5, *8*
iccbeta *(*iccbeta-package*)*, 2
iccbeta-package, 2

lme4::lmer(), *6*
lme4::VarCorr(), *6*
lmer, *4*, *9*
LRTSim, *4*, *9*

model.matrix, *4*, *9*
model.matrix(), *6*

RLRsim::LRTSim(), *6*

simICCdata, *4*, *6*, 8

VarCorr, *4*, *9*