

Package: ieugwasr (via r-universe)

September 30, 2024

Title Interface to the 'OpenGWAS' Database API

Version 1.0.1

Description Interface to the 'OpenGWAS' database API
<<https://gwas-api.mrcieu.ac.uk/>>. Includes a wrapper to make
generic calls to the API, plus convenience functions for
specific queries.

License MIT + file LICENSE

URL <https://github.com/MRCIEU/ieugwasr>,
<https://mrcieu.github.io/ieugwasr/>

BugReports <https://github.com/MRCIEU/ieugwasr/issues>

Depends R (>= 4.0)

Imports dplyr, httr, jsonlite, magrittr, stats

Suggests knitr, utils, rmarkdown, testthat

VignetteBuilder knitr

Encoding UTF-8

RoxygenNote 7.3.1

NeedsCompilation no

Author Gibran Hemani [aut, cre, cph]
(<<https://orcid.org/0000-0003-0920-1055>>), Ben Elsworth [aut]
(<<https://orcid.org/0000-0001-7328-4233>>), Tom Palmer [aut]
(<<https://orcid.org/0000-0003-4655-4511>>), Rita Rasteiro [aut]
(<<https://orcid.org/0000-0002-4217-3060>>)

Maintainer Gibran Hemani <g.hemani@bristol.ac.uk>

Repository CRAN

Date/Publication 2024-07-01 23:10:02 UTC

Contents

afl2_chrpos	2
afl2_list	3
afl2_rsid	4
api_query	4
api_status	5
associations	6
batches	7
batch_from_id	7
check_access_token	8
check_reset	8
editcheck	9
fill_n	9
get_opengwas_jwt	10
get_query_content	10
gwasinfo	11
infer_ancestry	11
ld_clump	12
ld_clump_api	13
ld_clump_local	14
ld_matrix	14
ld_matrix_local	16
ld_reflookup	16
legacy_ids	17
logging_info	17
phewas	18
print.ApiStatus	18
print.GwasInfo	19
select_api	19
set_reset	20
tophits	20
user	21
variants_chrpos	22
variants_gene	22
variants_rsid	23
variants_to_rsid	23

Index	24
--------------	-----------

afl2_chrpos	<i>Look up allele frequencies and LD scores for 1000 genomes populations by chrpos</i>
-------------	--

Description

Look up allele frequencies and LD scores for 1000 genomes populations by chrpos

Usage

```
afl2_chrpos(chrpos, reference = "1000g", opengwas_jwt = get_opengwas_jwt())
```

Arguments

chrpos	list of <chr>:<pos> in build 37, e.g. c("3:46414943", "3:122991235"). Also allows ranges e.g "7:105561135-105563135"
reference	Default="1000g"
opengwas_jwt	Used to authenticate protected endpoints. Login to https://api.opengwas.io to obtain a jwt. Provide the jwt string here, or store in .Renviro under the keyname OPENGWAS_JWT.

Value

Data frame containing ancestry specific LD scores and allele frequencies for each variant

afl2_list	<i>Retrieve a allele frequency and LD scores for pre-defined lists of variants</i>
-----------	--

Description

Data frame includes 1000 genomes metadata including sample sizes, allele frequency and LD score, separated by 5 super populations (EUR = European, AFR = African, EAS = East Asian, AMR = Admixed American, SAS = South Asian)

Usage

```
afl2_list(
  variantlist = c("reduced", "hapmap3")[1],
  opengwas_jwt = get_opengwas_jwt()
)
```

Arguments

variantlist	Choose pre-defined list. reduced = ~20k SNPs that are common in all super populations (default). hapmap3 = ~1.3 million hm3 SNPs
opengwas_jwt	Used to authenticate protected endpoints. Login to https://api.opengwas.io to obtain a jwt. Provide the jwt string here, or store in .Renviro under the keyname OPENGWAS_JWT.

Value

Data frame containing ancestry specific LD scores and allele frequencies for each variant

afl2_rsid	<i>Look up allele frequencies and LD scores for 1000 genomes populations by rsid</i>
-----------	--

Description

Look up allele frequencies and LD scores for 1000 genomes populations by rsid

Usage

```
afl2_rsid(rsid, reference = "1000g", opengwas_jwt = get_opengwas_jwt())
```

Arguments

rsid	Vector of rsids
reference	Default="1000g"
opengwas_jwt	Used to authenticate protected endpoints. Login to https://api.opengwas.io to obtain a jwt. Provide the jwt string here, or store in .Renviron under the keyname OPENGWAS_JWT.

Value

Data frame containing ancestry specific LD scores and allele frequencies for each variant

api_query	<i>Wrapper for sending queries and payloads to API</i>
-----------	--

Description

There are a number of different GET and POST endpoints in the GWAS database API. This is a generic way to access them.

Usage

```
api_query(
  path,
  query = NULL,
  opengwas_jwt = get_opengwas_jwt(),
  method = "GET",
  silent = TRUE,
  encode = "json",
  timeout = 300,
  override_429 = FALSE
)
```

Arguments

path	Either a full query path (e.g. for get) or an endpoint (e.g. for post) queries
query	If post query, provide a list of arguments as the payload. NULL by default
opengwas_jwt	Used to authenticate protected endpoints. Login to https://api.opengwas.io to obtain a jwt. Provide the jwt string here, or store in .Renviron under the keyname OPENGWAS_JWT.
method	"GET" (default) or "POST", "DELETE" etc
silent	TRUE/FALSE to be passed to httr call. TRUE by default
encode	Default = "json", see httr::POST for options
timeout	Default = 300, avoid increasing this, preferentially simplify the query first.
override_429	Default=FALSE. If allowance is exceeded then the query will error before submitting a request to avoid getting blocked. If you are sure you want to submit the request then set this to TRUE.

Value

httr response object

api_status	<i>MR-Base server status</i>
------------	------------------------------

Description

MR-Base server status

Usage

```
api_status()
```

Value

list of values regarding status

associations

Query specific variants from specific GWAS

Description

Every rsid is searched for against each requested GWAS id. To get a list of available GWAS ids, or to find their meta data, use [gwasinfo](#). Can request LD proxies for instances when the requested rsid is not present in a particular GWAS dataset. This currently only uses an LD reference panel composed of Europeans in 1000 genomes version 3. It is also restricted to biallelic single nucleotide polymorphisms (no indels), with European MAF > 0.01.

Usage

```
associations(
  variants,
  id,
  proxies = 1,
  r2 = 0.8,
  align_alleles = 1,
  palindromes = 1,
  maf_threshold = 0.3,
  opengwas_jwt = get_opengwas_jwt()
)
```

Arguments

variants	Array of variants e.g. c("rs234", "7:105561135-105563135")
id	Array of GWAS studies to query. See gwasinfo for available studies
proxies	0 or (default) 1 - indicating whether to look for proxies
r2	Minimum proxy LD rsq value. Default=0.8
align_alleles	Try to align tag alleles to target alleles (if proxies = 1). 1 = yes (default), 0 = no
palindromes	Allow palindromic SNPs (if proxies = 1). 1 = yes (default), 0 = no
maf_threshold	MAF threshold to try to infer palindromic SNPs. Default = 0.3.
opengwas_jwt	Used to authenticate protected endpoints. Login to https://api.opengwas.io to obtain a jwt. Provide the jwt string here, or store in .Renvirom under the keyname OPENGWAS_JWT.

Value

Dataframe

batches	<i>Get list of data batches in IEU GWAS database</i>
---------	--

Description

Get list of data batches in IEU GWAS database

Usage

```
batches(opengwas_jwt = get_opengwas_jwt())
```

Arguments

opengwas_jwt	Used to authenticate protected endpoints. Login to https://api.opengwas.io to obtain a jwt. Provide the jwt string here, or store in .Renviron under the keyname OPENGWAS_JWT.
--------------	--

Value

data frame

batch_from_id	<i>Extract batch name from study ID</i>
---------------	---

Description

Extract batch name from study ID

Usage

```
batch_from_id(id)
```

Arguments

id	Array of study IDs
----	--------------------

Value

Array of batch names

check_access_token	<i>Check if authentication has been maded</i>
--------------------	---

Description

Deprectated. Use `get_opengwas_jwt()` instead. See <https://mrcieu.github.io/ieugwasr/articles/guide.html#authentication> for more information.

Usage

```
check_access_token()
```

Value

NULL or `access_token` depending on current authentication state

check_reset	<i>Check if OpenGWAS allowance needs to be reset</i>
-------------	--

Description

This function checks if a recent query indicated that the OpenGWAS allowance has been used up. To prevent the IP being blocked, it will error if the new query is being submitted before the reset time. If the allowance has been used up, it displays a message indicating the time when the allowance will be reset. By default, the function will throw an error if the allowance has been used up, but this behavior can be overridden by setting `override_429` to TRUE.

Usage

```
check_reset(override_429 = FALSE)
```

Arguments

<code>override_429</code>	Logical value indicating whether to override the allowance reset check (default: FALSE)
---------------------------	---

editcheck	<i>Check datasets that are in process of being uploaded</i>
-----------	---

Description

Check datasets that are in process of being uploaded

Usage

```
editcheck(id, opengwas_jwt = get_opengwas_jwt())
```

Arguments

id	ID
opengwas_jwt	Used to authenticate protected endpoints. Login to https://api.opengwas.io to obtain a jwt. Provide the jwt string here, or store in .Renviron under the keyname OPENGWAS_JWT.

Value

Dataframe

fill_n	<i>Look up sample sizes when meta data is missing from associations</i>
--------	---

Description

Look up sample sizes when meta data is missing from associations

Usage

```
fill_n(d, opengwas_jwt = get_opengwas_jwt())
```

Arguments

d	Output from associations
opengwas_jwt	Used to authenticate protected endpoints. Login to https://api.opengwas.io to obtain a jwt. Provide the jwt string here, or store in .Renviron under the keyname OPENGWAS_JWT.

Value

Updated version of d

get_opengwas_jwt	<i>Retrieve OpenGWAS JSON Web Token from .Renviron file</i>
------------------	---

Description

Retrieve OpenGWAS JSON Web Token from .Renviron file

Usage

```
get_opengwas_jwt()
```

Value

JWT string

get_query_content	<i>Parse out json response from httr object</i>
-------------------	---

Description

Parse out json response from httr object

Usage

```
get_query_content(response)
```

Arguments

response	Output from httr
----------	------------------

Value

Parsed json output from query, often in form of data frame. If status code is not successful then return the actual response

gwasinfo	<i>Get list of studies with available GWAS summary statistics through API</i>
----------	---

Description

Get list of studies with available GWAS summary statistics through API

Usage

```
gwasinfo(id = NULL, opengwas_jwt = get_opengwas_jwt())
```

Arguments

id	List of MR-Base IDs to retrieve. If NULL (default) retrieves all available datasets
opengwas_jwt	Used to authenticate protected endpoints. Login to https://api.opengwas.io to obtain a jwt. Provide the jwt string here, or store in .Renviron under the keyname OPENGWAS_JWT.

Value

Dataframe of details for all available studies

infer_ancestry	<i>Infer ancestry of GWAS dataset by matching against 1000 genomes allele frequencies</i>
----------------	---

Description

Uses ~20k SNPs selected for common frequency across 5 major super populations

Usage

```
infer_ancestry(d, snpinfo = NULL, opengwas_jwt = get_opengwas_jwt())
```

Arguments

d	Data frame containing at least rsid and eaf columns. e.g. output from associations
snpinfo	Output from af12_list , af12_rsid or af12_chrpos . If NULL then af12_list() is used by default
opengwas_jwt	Used to authenticate protected endpoints. Login to https://api.opengwas.io to obtain a jwt. Provide the jwt string here, or store in .Renviron under the keyname OPENGWAS_JWT.

Value

data frame ordered by most likely ancestry, each row represents a super population and cor column represents the correlation between the GWAS dataset and the 1000 genomes super population allele frequencies

ld_clump	<i>Perform LD clumping on SNP data</i>
----------	--

Description

Uses PLINK clumping method, where SNPs in LD within a particular window will be pruned. The SNP with the lowest p-value is retained.

Usage

```
ld_clump(
  dat = NULL,
  clump_kb = 10000,
  clump_r2 = 0.001,
  clump_p = 0.99,
  pop = "EUR",
  opengwas_jwt = get_opengwas_jwt(),
  bfile = NULL,
  plink_bin = NULL
)
```

Arguments

dat	Dataframe. Must have a variant name column (rsid) and pval column called pval. If id is present then clumping will be done per unique id.
clump_kb	Clumping kb window. Default is very strict, 10000
clump_r2	Clumping r2 threshold. Default is very strict, 0.001
clump_p	Clumping sig level for index variants. Default = 1 (i.e. no threshold)
pop	Super-population to use as reference panel. Default = "EUR". Options are "EUR", "SAS", "EAS", "AFR", "AMR". 'legacy' also available - which is a previously used version of the EUR panel with a slightly different set of markers
opengwas_jwt	Used to authenticate protected endpoints. Login to https://api.opengwas.io to obtain a jwt. Provide the jwt string here, or store in .Renvron under the keyname OPENGWAS_JWT.#'
bfile	If this is provided then will use the API. Default = NULL
plink_bin	If NULL and bfile is not NULL then will detect packaged plink binary for specific OS. Otherwise specify path to plink binary. Default = NULL

Details

This function interacts with the OpenGWAS API, which houses LD reference panels for the 5 super-populations in the 1000 genomes reference panel. It includes only bi-allelic SNPs with MAF > 0.01, so it's quite possible that a variant you want to include in the clumping process will be absent. If it is absent, it will be automatically excluded from the results.

You can check if your variants are present in the LD reference panel using `ld_reflookup()`.

This function does put load on the OpenGWAS servers, which makes life more difficult for other users. We have implemented a method and made available the LD reference panels to perform clumping locally, see `ld_clump()` and related vignettes for details.

Value

Data frame

ld_clump_api	<i>Perform clumping on the chosen variants using through API</i>
--------------	--

Description

Perform clumping on the chosen variants using through API

Usage

```
ld_clump_api(
  dat,
  clump_kb = 10000,
  clump_r2 = 0.1,
  clump_p,
  pop = "EUR",
  opengwas_jwt = get_opengwas_jwt()
)
```

Arguments

dat	Dataframe. Must have a variant name column (variant) and pval column called pval. If id is present then clumping will be done per unique id.
clump_kb	Clumping kb window. Default is very strict, 10000
clump_r2	Clumping r2 threshold. Default is very strict, 0.001
clump_p	Clumping sig level for index variants. Default = 1 (i.e. no threshold)
pop	Super-population to use as reference panel. Default = "EUR". Options are "EUR", "SAS", "EAS", "AFR", "AMR"
opengwas_jwt	Used to authenticate protected endpoints. Login to https://api.opengwas.io to obtain a jwt. Provide the jwt string here, or store in .Renviron under the keyname OPENGWAS_JWT.#' @param bfile If this is provided then will use the API. Default = NULL

Value

Data frame of only independent variants

ld_clump_local	<i>Wrapper for clump function using local plink binary and ld reference dataset</i>
----------------	---

Description

Wrapper for clump function using local plink binary and ld reference dataset

Usage

```
ld_clump_local(dat, clump_kb, clump_r2, clump_p, bfile, plink_bin)
```

Arguments

dat	Dataframe. Must have a variant name column (variant) and pval column called pval. If id is present then clumping will be done per unique id.
clump_kb	Clumping kb window. Default is very strict, 10000
clump_r2	Clumping r2 threshold. Default is very strict, 0.001
clump_p	Clumping sig level for index variants. Default = 1 (i.e. no threshold)
bfile	If this is provided then will use the API. Default = NULL
plink_bin	Specify path to plink binary. Default = NULL. See https://github.com/explodecomputer/plinkbin for convenient access to plink binaries

Value

data frame of clumped variants

ld_matrix	<i>Get LD matrix for list of SNPs</i>
-----------	---------------------------------------

Description

This function takes a list of SNPs and searches for them in a specified super-population in the 1000 Genomes phase 3 reference panel. It then creates an LD matrix of r values (signed, and not squared). All LD values are with respect to the major alleles in the 1000G dataset. You can specify whether the allele names are displayed.

Usage

```
ld_matrix(
  variants,
  with_alleles = TRUE,
  pop = "EUR",
  opengwas_jwt = get_opengwas_jwt(),
  bfile = NULL,
  plink_bin = NULL
)
```

Arguments

variants	List of variants (rsids)
with_alleles	Whether to append the allele names to the SNP names. Default: TRUE
pop	Super-population to use as reference panel. Default = "EUR". Options are "EUR", "SAS", "EAS", "AFR", "AMR". 'legacy' also available - which is a previously used version of the EUR panel with a slightly different set of markers
opengwas_jwt	Used to authenticate protected endpoints. Login to https://api.opengwas.io to obtain a jwt. Provide the jwt string here, or store in .Renviro under the keyname OPENGWAS_JWT.#' @param bfile If this is provided then will use the API. Default = NULL
bfile	If this is provided then will use the API. Default = NULL
plink_bin	If NULL and bfile is not NULL then will detect packaged plink binary for specific OS. Otherwise specify path to plink binary. Default = NULL

Details

The data used for generating the LD matrix includes only bi-allelic SNPs with MAF > 0.01, so it's quite possible that a variant you want to include will be absent. If it is absent, it will be automatically excluded from the results.

You can check if your variants are present in the LD reference panel using [ld_reflookup\(\)](#)

This function does put load on the OpenGWAS servers, which makes life more difficult for other users, and has been limited to analyse only up to 500 variants at a time. We have implemented a method and made available the LD reference panels to perform the operation locally, see [ld_matrix\(\)](#) and related vignettes for details.

Value

Matrix of LD r values

ld_matrix_local	<i>Get LD matrix using local plink binary and reference dataset</i>
-----------------	---

Description

Get LD matrix using local plink binary and reference dataset

Usage

```
ld_matrix_local(variants, bfile, plink_bin, with_alleles = TRUE)
```

Arguments

variants	List of variants (rsids)
bfile	Path to bed/bim/fam ld reference panel
plink_bin	Specify path to plink binary. Default = NULL. See https://github.com/explodecomputer/plinkbin for convenient access to plink binaries
with_alleles	Whether to append the allele names to the SNP names. Default: TRUE

Value

data frame

ld_reflookup	<i>Check which rsids are present in a remote LD reference panel</i>
--------------	---

Description

Provide a list of rsids that you may want to perform LD operations on to check if they are present in the LD reference panel. If they are not then some functions e.g. `ld_clump` will exclude them from the analysis, so you may want to consider how to handle those variants in your data.

Usage

```
ld_reflookup(rsid, pop = "EUR", opengwas_jwt = get_opengwas_jwt())
```

Arguments

rsid	Array of rsids to check
pop	Super-population to use as reference panel. Default = "EUR". Options are "EUR", "SAS", "EAS", "AFR", "AMR"
opengwas_jwt	Used to authenticate protected endpoints. Login to https://api.opengwas.io to obtain a jwt. Provide the jwt string here, or store in .Renviron under the keyname OPENGWAS_JWT.#' @param bfile If this is provided then will use the API. Default = NULL

Value

Array of rsids that are present in the LD reference panel

legacy_ids	<i>Convert current IDs to legacy IDs</i>
------------	--

Description

Convert current IDs to legacy IDs

Usage

```
legacy_ids(x)
```

Arguments

x	Vector of ids
---	---------------

Value

vector of back compatible ids

logging_info	<i>Details of how access token logs are used</i>
--------------	--

Description

Details of how access token logs are used

Usage

```
logging_info()
```

Value

No return value, called for side effects

phewas	<i>Perform fast phewas of a specific variants against all available GWAS datasets</i>
--------	---

Description

This is faster than doing it manually through [associations](#)

Usage

```
phewas(variants, pval = 1e-05, batch = c(), opengwas_jwt = get_opengwas_jwt())
```

Arguments

variants	Array of variants e.g. <code>c("rs234", "7:105561135-105563135")</code>
pval	p-value threshold. Default = <code>0.00001</code>
batch	Vector of batch IDs to search across. If <code>c()</code> (default) then returns all batches
opengwas_jwt	Used to authenticate protected endpoints. Login to https://api.opengwas.io to obtain a jwt. Provide the jwt string here, or store in .Renviron under the keyname <code>OPENGWAS_JWT</code> .

Value

Dataframe

print.ApiStatus	<i>Print API status</i>
-----------------	-------------------------

Description

Print API status

Usage

```
## S3 method for class 'ApiStatus'
print(x, ...)
```

Arguments

x	Output from api_status
...	Unused, for extensibility

Value

Print out of API status

print.GwasInfo	<i>Print GWAS information</i>
----------------	-------------------------------

Description

Print GWAS information

Usage

```
## S3 method for class 'GwasInfo'  
print(x, ...)
```

Arguments

x	Output from gwasinfo
...	Unused, for extensibility

Value

Print out of GWAS information

select_api	<i>Toggle API address between development and release</i>
------------	---

Description

Toggle API address between development and release

Usage

```
select_api(where = "public", silent = FALSE)
```

Arguments

where	Which API to use. Choice between "public", "private", "dev1", "dev2". Default = "public".
silent	Silent? Default = FALSE

Value

No return value, called for side effects

set_reset	<i>Set the reset time for OpenGWAS allowance</i>
-----------	--

Description

This function sets the reset time for the OpenGWAS allowance based on the retry-after header returned by the API response. It also displays a warning message indicating the time at which the allowance will reset.

Usage

```
set_reset(r)
```

Arguments

r	The API response object
---	-------------------------

Value

None

tophits	<i>Obtain top hits from a GWAS dataset</i>
---------	--

Description

By default performs clumping on the server side.

Usage

```
tophits(
  id,
  pval = 5e-08,
  clump = 1,
  r2 = 0.001,
  kb = 10000,
  pop = "EUR",
  force_server = FALSE,
  opengwas_jwt = get_opengwas_jwt()
)
```

Arguments

id	Array of GWAS studies to query. See gwasinfo for available studies
pval	use this p-value threshold. Default = 5e-8
clump	whether to clump (1) or not (0). Default = 1
r2	use this clumping r2 threshold. Default is very strict, 0.001
kb	use this clumping kb window. Default is very strict, 10000
pop	Super-population to use as reference panel. Default = "EUR". Options are "EUR", "SAS", "EAS", "AFR", "AMR"
force_server	Logical. By default will return preclumped hits. p-value threshold 5e-8, with r2 threshold 0.001 and kb threshold 10000, using only SNPs with MAF > 0.01 in the European samples in 1000 genomes. If force_server = TRUE then will recompute using server side LD reference panel.
opengwas_jwt	Used to authenticate protected endpoints. Login to https://api.opengwas.io to obtain a jwt. Provide the jwt string here, or store in .Renviron under the keyname OPENGWAS_JWT.

Value

Dataframe

user	<i>Get user details</i>
------	-------------------------

Description

Get user details

Usage

```
user(opengwas_jwt = get_opengwas_jwt())
```

Arguments

opengwas_jwt	Used to authenticate protected endpoints. Login to https://api.opengwas.io to obtain a jwt. Provide the jwt string here, or store in .Renviron under the keyname OPENGWAS_JWT.
--------------	--

Value

user information

variants_chrpos	<i>Obtain information about chr pos and surrounding region</i>
-----------------	--

Description

For a list of chromosome and positions, finds all variants within a given radius

Usage

```
variants_chrpos(chrpos, radius = 0, opengwas_jwt = get_opengwas_jwt())
```

Arguments

chrpos	list of <chr>:<pos> in build 37, e.g. c("3:46414943", "3:122991235"). Also allows ranges e.g. "7:105561135-105563135"
radius	Radius around each chrpos, default = 0
opengwas_jwt	Used to authenticate protected endpoints. Login to https://api.opengwas.io to obtain a jwt. Provide the jwt string here, or store in .Renviron under the keyname OPENGWAS_JWT.

Value

Data frame

variants_gene	<i>Obtain variants around a gene</i>
---------------	--------------------------------------

Description

Provide a gene identified, either Ensembl or Entrez

Usage

```
variants_gene(gene, radius = 0, opengwas_jwt = get_opengwas_jwt())
```

Arguments

gene	Vector of genes, either Ensembl or Entrez, e.g. c("ENSG00000123374", "ENSG00000160791") or 1017
radius	Radius around the gene region to include. Default = 0
opengwas_jwt	Used to authenticate protected endpoints. Login to https://api.opengwas.io to obtain a jwt. Provide the jwt string here, or store in .Renviron under the keyname OPENGWAS_JWT.

Value

data frame with the following columns

variants_rsid	<i>Obtain information about rsid</i>
---------------	--------------------------------------

Description

Obtain information about rsid

Usage

```
variants_rsid(rsid, opengwas_jwt = get_opengwas_jwt())
```

Arguments

rsid	Vector of rsids
opengwas_jwt	Used to authenticate protected endpoints. Login to https://api.opengwas.io to obtain a jwt. Provide the jwt string here, or store in .Renviro under the keyname OPENGWAS_JWT.

Value

data frame

variants_to_rsid	<i>Convert mixed array of rsid and chrpos to list of rsid</i>
------------------	---

Description

Convert mixed array of rsid and chrpos to list of rsid

Usage

```
variants_to_rsid(variants, opengwas_jwt = get_opengwas_jwt())
```

Arguments

variants	Array of variants e.g. c("rs234", "7:105561135-105563135")
opengwas_jwt	Used to authenticate protected endpoints. Login to https://api.opengwas.io to obtain a jwt. Provide the jwt string here, or store in .Renviro under the keyname OPENGWAS_JWT.

Value

list of rsids

Index

afl2_chrpos, [2](#), [11](#)
afl2_list, [3](#), [11](#)
afl2_list(), [11](#)
afl2_rsid, [4](#), [11](#)
api_query, [4](#)
api_status, [5](#), [18](#)
associations, [6](#), [9](#), [18](#)

batch_from_id, [7](#)
batches, [7](#)

check_access_token, [8](#)
check_reset, [8](#)

editcheck, [9](#)

fill_n, [9](#)

get_opengwas_jwt, [10](#)
get_query_content, [10](#)
gwasinfo, [6](#), [11](#), [19](#), [21](#)

http:::POST, [5](#)

infer_ancestry, [11](#)

ld_clump, [12](#), [16](#)
ld_clump(), [13](#)
ld_clump_api, [13](#)
ld_clump_local, [14](#)
ld_matrix, [14](#)
ld_matrix(), [15](#)
ld_matrix_local, [16](#)
ld_reflookup, [16](#)
ld_reflookup(), [13](#), [15](#)
legacy_ids, [17](#)
logging_info, [17](#)

phewas, [18](#)
print.ApiStatus, [18](#)
print.GwasInfo, [19](#)

select_api, [19](#)
set_reset, [20](#)

tophits, [20](#)

user, [21](#)

variants_chrpos, [22](#)
variants_gene, [22](#)
variants_rsid, [23](#)
variants_to_rsid, [23](#)