Package: ijtiff (via r-universe)

October 9, 2026

Type Package

Title Comprehensive TIFF I/O with Full Support for 'ImageJ' TIFF Files

Version 3.2.0

Maintainer Rory Nolan <rorynoolan@gmail.com>

Description General purpose TIFF file I/O for R users. Currently the only such package with read and write support for TIFF files with floating point (real-numbered) pixels, and the only package that can correctly import TIFF files that were saved from 'ImageJ' and write TIFF files than can be correctly read by 'ImageJ' <https://imagej.net/ij/>. Also supports text image I/O.

License GPL-3

URL https://docs.ropensci.org/ijtiff/, https://github.com/ropensci/ijtiff

BugReports https://github.com/ropensci/ijtiff/issues

Depends R (>= 4.2)

Imports checkmate (>= 1.9.3), cli, dplyr, fs (>= 1.5), graphics, grDevices, jsonlite, lubridate, magrittr (>= 1.5), methods, purrr, readr, rlang (>= 1.0), strex (>= 1.5), stringr (>= 1.4)

Suggests abind, covr, EBImage, knitr, rmarkdown, spelling, testthat (>= 3.0), tiff

VignetteBuilder knitr

Biarch TRUE

Config/testthat/edition 3

Encoding UTF-8

Language en-US

RoxygenNote 7.3.3

SystemRequirements fftw3, libtiff, libbz2, libdeflate, libjpeg, liblzma, libwebp, libzstd, X11, zlib

NeedsCompilation yes

Author Rory Nolan [aut, cre] (ORCID: <https://orcid.org/0000-0002-5239-4043>), Kent Johnson [aut], Simon Urbanek [ctb], Sergi Padilla-Parra [ths] (ORCID: <https://orcid.org/0000-0002-8010-9481>), Jeroen Ooms [rev, ctb] (ORCID: <https://orcid.org/0000-0002-4035-0289>), Jon Clayden [rev] (ORCID: <https://orcid.org/0000-0002-6608-0619>)

Config/pak/sysreqs libfftw3-dev libbz2-dev libjpeg-dev liblzma-dev libtiff-dev libwebp-dev libzstd-dev libx11-dev zlib1g-dev

Repository https://cran.r-universe.dev

Date/Publication 2026-01-26 06:30:34 UTC

RemoteUrl https://github.com/cran/ijtiff

RemoteRef HEAD

RemoteSha ddcb9431b18b82901edcc0c2c0dae5c73ea3e362

Contents

as.raster.ijtiff_img . . . 2
as_EBImage . . . 3
count_frames . . . 4
display . . . 5
get_supported_tags . . . 6
ijtiff . . . 6
ijtiff_img . . . 7
linescan-conversion . . . 8
print.ijtiff_img . . . 8
read_tags . . . 9
read_tif . . . 10
text-image-io . . . 11
tif_tags_reference . . . 12
write_tif . . . 13

Index **16**

`as.raster.ijtiff_img` *Convert an ijtiff_img object to a raster object for plotting*

Description

This function converts an ijtiff_img object to a `raster` object that can be used with base R graphics functions. The function extracts the first frame of the image and converts it to an RGB raster representation.

Usage

```
## S3 method for class 'ijtiff_img'
as.raster(x, ...)
```

Arguments

x	An ijtiff_img object. This should be a 4D array with dimensions representing (y, x, channel, frame).
...	Passed to `graphics::plot.raster()`.

Details

The function performs the following operations:

- Extracts the first frame of the image
- Checks for invalid values (all NA or negative values)
- Determines the appropriate color scaling based on the image bit depth
- Creates an RGB representation using the available channels

For single-channel images, a grayscale representation is created. For RGB images (3 channels), a full-color representation is created.

Value

A `raster` object compatible with `graphics::plot.raster()`. The raster will represent the first frame of the input image.

Examples

```
# Read a TIFF image
img <- read_tif(system.file("img", "Rlogo.tif", package = "ijtiff"))

# Convert to raster and plot
raster_img <- as.raster(img)
plot(raster_img)
```

---

as_EBImage *Convert an ijtiff_img to an EBImage::Image.*

Description

This is for interoperability with the the `EBImage` package.

Usage

```
as_EBImage(img, colormode = NULL, scale = TRUE, force = TRUE)
```

Arguments

`img`	An ijtiff_img object (or something coercible to one).
`colormode`	A numeric or a character string containing the color mode which can be either `"Grayscale"` or `"Color"`. If not specified, a guess is made. See 'Details'.
`scale`	Scale values in an integer image to the range `[0, 1]`? Has no effect on floating-point images.
`force`	This function is designed to take ijtiff_imgs as input. To force any old array through this function, use `force = TRUE`, but take care to check that the result is what you'd like it to be.

Details

The guess for the `colormode` is made as follows: * If `img` has an attribute `color_space` with value `"RGB"`, then `colormode` is set to `"Color"`. * Else if `img` has 3 or 4 channels, then `colormode` is set to `"Color"`. * Else `colormode` is set to "Grayscale".

Value

An EBImage::Image.

Examples

```
if (rlang::is_installed("EBImage")) {
  img <- read_tif(system.file("img", "Rlogo.tif", package = "ijtiff"))
  str(img)
  str(as_EBImage(img))
}
```

`count_frames` *Count the number of frames in a TIFF file.*

Description

TIFF files can hold many frames. Often this is sensible, e.g. each frame could be a time-point in a video or a slice of a z-stack.

Usage

```
count_frames(path)

frames_count(path)
```

Arguments

`path`	A string. The path to the tiff file to read.

Details

For those familiar with TIFF files, this function counts the number of directories in a TIFF file. There is an adjustment made for some ImageJ-written TIFF files.

Value

A number, the number of frames in the TIFF file. This has an attribute `n_dirs` which holds the true number of directories in the TIFF file, making no allowance for the way ImageJ may write TIFF files.

Examples

```
count_frames(system.file("img", "Rlogo.tif", package = "ijtiff"))
```

---

display *Basic image display.*

Description

Display an image that has been read in by `read_tif()` as it would look in 'ImageJ'. This function wraps `graphics::plot.raster()`.

Usage

```
display(img, ...)
```

Arguments

`img`	An ijtiff_img object.
`...`	Passed to `graphics::plot.raster()`.

Examples

```
img <- read_tif(system.file("img", "Rlogo.tif", package = "ijtiff"))
display(img)
display(img[, , 1, 1]) # first (red) channel, first frame
display(img[, , 2, ]) # second (green) channel, first frame
display(img[, , 3, ]) # third (blue) channel, first frame
display(img, basic = TRUE) # displays first (red) channel, first frame
```

get_supported_tags *Get supported TIFF tags*

Description

Returns a named integer vector of supported TIFF tags. The names are the human-readable tag names, and the values are the corresponding tag codes.

Usage

```
get_supported_tags()
```

Value

A named integer vector of supported TIFF tags

ijtiff *ijtiff: TIFF I/O for* ImageJ *users*

Description

This is a general purpose TIFF I/O utility for R. The tiff package already exists for this purpose but ijtiff adds some functionality and overcomes some bugs therein.

Details

- ijtiff can write TIFF files whose pixel values are real (floating-point) numbers; tiff cannot.
- ijtiff can read and write *text images*; tiff cannot.
- tiff struggles to interpret channel information and gives cryptic errors when reading TIFF files written by the *ImageJ* software; ijtiff works smoothly with these images.

Author(s)

Maintainer: Rory Nolan <rorynoolan@gmail.com> (ORCID)

Authors:

- Kent Johnson <kjohnson@akoyabio.com>

Other contributors:

- Simon Urbanek <Simon.Urbanek@r-project.org> [contributor]
- Sergi Padilla-Parra <spadilla@well.ox.ac.uk> (ORCID) [thesis advisor]
- Jeroen Ooms (ORCID) [reviewer, contributor]
- Jon Clayden (ORCID) [reviewer]

See Also

Useful links:

- https://docs.ropensci.org/ijtiff/
- https://github.com/ropensci/ijtiff
- Report bugs at https://github.com/ropensci/ijtiff/issues

`ijtiff_img` `ijtiff_img` *class.*

Description

A class for images which are read or to be written by the `ijtiff` package.

Usage

```
ijtiff_img(img, ...)

as_ijtiff_img(img, ...)
```

Arguments

`img`	An array representing the image. • For a single-plane, grayscale image, use a matrix `img[y, x]`. • For a multi-plane, grayscale image, use a 3-dimensional array `img[y, x, plane]`. • For a multi-channel, single-plane image, use a 4-dimensional array with a redundant 4th slot `img[y, x, channel, ]` (see ijtiff_img 'Examples' for an example). • For a multi-channel, multi-plane image, use a 4-dimensional array `img[y, x, channel, plane]`.
`...`	Named arguments which are set as attributes.

Value

A 4 dimensional array representing an image, indexed by `img[y, x, channel, frame]`, with selected attributes.

Examples

```
img <- matrix(1:4, nrow = 2) # to be a single-channel, grayscale image
ijtiff_img(img, description = "single-channel, grayscale")
img <- array(seq_len(2^3), dim = rep(2, 3)) # 1 channel, 2 frame
ijtiff_img(img, description = "blah blah blah")
img <- array(seq_len(2^3), dim = c(2, 2, 2, 1)) #  2 channel, 1 frame
ijtiff_img(img, description = "blah blah")
img <- array(seq_len(2^4), dim = rep(2, 4)) # 2 channel, 2 frame
ijtiff_img(img, software = "R")
```

linescan-conversion *Rejig linescan images.*

Description

ijtiff has the fourth dimension of an ijtiff_img as its time dimension. However, some linescan images (images where a single line of pixels is acquired over and over) have the time dimension as the y dimension, (to avoid the need for an image stack). These functions allow one to convert this type of image into a conventional ijtiff_img (with time in the fourth dimension) and to convert back.

Usage

```
linescan_to_stack(linescan_img)

stack_to_linescan(img)
```

Arguments

linescan_img	A 4-dimensional array in which the time axis is the first axis. Dimension 4 must be 1 i.e. dim(linescan_img)[4] == 1.
img	A conventional ijtiff_img, to be turned into a linescan image. Dimension 1 must be 1 i.e. dim(img)[1] == 1.

Value

The converted image, an object of class ijtiff_img.

Examples

```
linescan <- ijtiff_img(array(rep(1:4, each = 4), dim = c(4, 4, 1, 1)))
print(linescan)
stack <- linescan_to_stack(linescan)
print(stack)
linescan <- stack_to_linescan(stack)
print(linescan)
```

print.ijtiff_img *Print method for an* ijtiff_img.

Description

Print method for an ijtiff_img.

Usage

```
## S3 method for class 'ijtiff_img'
print(x, ...)
```

Arguments

x	An object of class ijtiff_img.
...	Not currently used.

Value

The input (invisibly).

---

read_tags *Read TIFF tag information without actually reading the image array.*

Description

TIFF files contain metadata about images in their *TIFF tags*. This function is for reading this information without reading the actual image.

Usage

```
read_tags(path, frames = "all", translate_tags = TRUE)

tags_read(path, frames = 1)
```

Arguments

path	A string. The path to the tiff file to read.
frames	Which frames do you want to read. Default all. To read the 2nd and 7th frames, use `frames = c(2, 7)`.
translate_tags	Logical. Should the TIFF tags be translated to human-readable strings? E.g. `Compression = 1` becomes `Compression = "none"`.

Value

A list of lists.

Author(s)

Simon Urbanek, Kent Johnson, Rory Nolan.

See Also

read_tif()

Examples

```
read_tags(system.file("img", "Rlogo.tif", package = "ijtiff"))
```

`read_tif` *Read an image stored in the TIFF format*

Description

Reads an image from a TIFF file/content into a numeric array or list.

Usage

```
read_tif(path, frames = "all", list_safety = "error", msg = TRUE)

tif_read(path, frames = "all", list_safety = "error", msg = TRUE)
```

Arguments

`path`	A string. The path to the tiff file to read.
`frames`	Which frames do you want to read. Default all. To read the 2nd and 7th frames, use `frames = c(2, 7)`.
`list_safety`	A string. This is for type safety of this function. Since returning a list is unlikely and probably unexpected, the default is to error. You can instead opt to throw a warning (`list_safety = "warning"`) or to just return the list quietly (`list_safety = "none"`).
`msg`	Print an informative message about the image being read?

Details

TIFF files have the capability to store multiple images, each having multiple channels. Typically, these multiple images represent the sequential frames in a time-stack or z-stack of images and hence each of these images has the same dimension. If this is the case, they are all read into a single 4-dimensional array `img` where `img` is indexed as `img[y, x, channel, frame]` (where we have `y, x` to comply with the conventional `row, col` indexing of a matrix - it means that images displayed as arrays of numbers in the R console will have the correct orientation). However, it is possible that the images in the TIFF file have varying dimensions (most people have never seen this), in which case they are read in as a list of images, where again each element of the list is a 4-dimensional array `img`, indexed as `img[y, x, channel, frame]`.

A (somewhat random) set of TIFF tags are attributed to the read image. These are ImageDepth, BitsPerSample, SamplesPerPixel, SampleFormat, PlanarConfig, Compression, Threshholding, XResolution, YResolution, ResolutionUnit, Indexed and Orientation. More tags should be added in a subsequent version of this package. You can read about TIFF tags at https://www.awaresystems.be/imaging/tiff/tifftags.html.

TIFF images can have a wide range of internal representations, but only the most common in image processing are supported (8-bit, 16-bit and 32-bit integer and 32-bit float samples).

Value

An object of class ijtiff_img or a list of ijtiff_imgs.

Note

- 12-bit TIFFs are not supported.
- There is no standard for packing order for TIFFs beyond 8-bit so we assume big-endian packing

.

Author(s)

Simon Urbanek wrote most of this code for the 'tiff' package. Rory Nolan lifted it from there and changed it around a bit for this 'ijtiff' package. Credit should be directed towards Lord Urbanek.

See Also

`write_tif()`

Examples

```
img <- read_tif(system.file("img", "Rlogo.tif", package = "ijtiff"))
```

---

text-image-io *Read/write an image array to/from disk as text file(s).*

Description

Write images (arrays) as tab-separated `.txt` files on disk. Each channel-frame pair gets its own file.

Usage

```
write_txt_img(img, path, rds = FALSE, msg = TRUE)

read_txt_img(path, msg = TRUE)

txt_img_write(img, path, rds = FALSE, msg = TRUE)

txt_img_read(path, msg = TRUE)
```

Arguments

`img`	An image, represented by a 4-dimensional array, like an ijtiff_img.
`path`	The name of the input/output output file(s), *without* a file extension.
`rds`	In addition to writing a text file, save the image as an RDS (a single R object) file?
`msg`	Print an informative message about the image being read?

Examples

```
img <- read_tif(system.file("img", "Rlogo.tif", package = "ijtiff"))
tmptxt <- tempfile(pattern = "img", fileext = ".txt")
write_txt_img(img, tmptxt)
tmptxt_ch1_path <- paste0(strex::str_before_last_dot(tmptxt), "_ch1.txt")
print(tmptxt_ch1_path)
txt_img <- read_txt_img(tmptxt_ch1_path)
```

`tif_tags_reference` *TIFF tag reference.*

Description

A dataset containing the information on all known baseline and extended TIFF tags.

Usage

```
tif_tags_reference()
```

Details

A data frame with 96 rows and 10 variables:

code_dec decimal numeric code of the TIFF tag

code_hex hexadecimal numeric code of the TIFF tag

name the name of the TIFF tag

short_description a short description of the TIFF tag

tag_type the type of TIFF tag: either "baseline" or "extended"

url the URL of the TIFF tag at https://www.awaresystems.be

libtiff_name the TIFF tag name in the libtiff C library

c_type the C type of the TIFF tag data in libtiff

count the number of elements in the TIFF tag data

default the default value of the data held in the TIFF tag

Source

https://www.awaresystems.be

Examples

```
tif_tags_reference()
```

`write_tif` *Write images in TIFF format*

Description

Write images into a TIFF file.

Usage

```
write_tif(
  img,
  path,
  bits_per_sample = "auto",
  compression = "none",
  overwrite = FALSE,
  msg = TRUE,
  tags_to_write = NULL
)

tif_write(
  img,
  path,
  bits_per_sample = "auto",
  compression = "none",
  overwrite = FALSE,
  msg = TRUE,
  tags_to_write = NULL
)
```

Arguments

`img` An array representing the image.

- For a single-plane, grayscale image, use a matrix `img[y, x]`.
- For a multi-plane, grayscale image, use a 3-dimensional array `img[y, x, plane]`.
- For a multi-channel, single-plane image, use a 4-dimensional array with a redundant 4th slot `img[y, x, channel, ]` (see ijtiff_img 'Examples' for an example).
- For a multi-channel, multi-plane image, use a 4-dimensional array `img[y, x, channel, plane]`.

`path` Path to the TIFF file to write to.

`bits_per_sample`

Number of bits per sample (numeric scalar). Supported values are 8, 16, and 32. The default `"auto"` automatically picks the smallest workable value based on the maximum element in `img`. For example, if the maximum element in `img` is 789, then 16-bit will be chosen because 789 is greater than 2 ^ 8 - 1 but less than or equal to 2 ^ 16 - 1.

`compression` A string, the desired compression algorithm. Must be one of `"none"`, `"LZW"`, `"PackBits"`, `"RLE"`, `"JPEG"`, `"deflate"` or `"Zip"`. If you want compression but don't know which one to go for, I recommend `"Zip"`, it gives a large file size reduction and it's lossless. Note that `"deflate"` and `"Zip"` are the same thing. Avoid using `"JPEG"` compression in a TIFF file if you can; I've noticed it can be buggy.

`overwrite` If writing the image would overwrite a file, do you want to proceed?

`msg` Print an informative message about the image being written?

`tags_to_write` A named list of TIFF tags to write. Tag names are case-insensitive and hyphens/underscores are ignored (e.g., "X_Resolution", "x-resolution", and "xresolution" are all equivalent).

If `NULL` (the default), any supported TIFF tags present as attributes on `img` (e.g., from `read_tif()`) will be automatically extracted and written. If `tags_to_write` is specified, it is merged with auto-detected tags, with explicit tags taking precedence. This enables round-trip editing where metadata from a read image is preserved on re-export unless explicitly overridden.

Supported tags are:

- `xresolution` - Numeric value for horizontal resolution in pixels per unit
- `yresolution` - Numeric value for vertical resolution in pixels per unit
- `resolutionunit` - Integer: 1 (none), 2 (inch), or 3 (centimeter)
- `orientation` - Integer 1-8 for image orientation
- `xposition` - Numeric value for horizontal position in resolution units
- `yposition` - Numeric value for vertical position in resolution units
- `copyright` - Character string for copyright notice
- `artist` - Character string for creator name
- `documentname` - Character string for document name
- `datetime` - Date/time (character, Date, or POSIXct)
- `imagedescription` - Character string for image description

Value

The input `img` (invisibly).

Author(s)

Simon Urbanek wrote most of this code for the 'tiff' package. Rory Nolan lifted it from there and changed it around a bit for this 'ijtiff' package. Credit should be directed towards Lord Urbanek.

See Also

`read_tif()`

Examples

```
img <- read_tif(system.file("img", "Rlogo.tif", package = "ijtiff"))
temp_dir <- tempdir()
```

```
# Basic write
write_tif(img, paste0(temp_dir, "/", "Rlogo"))

# Round-trip with automatic metadata preservation
# Metadata from read_tif is automatically preserved
img_with_metadata <- read_tif(system.file("img", "Rlogo.tif",
                                          package = "ijtiff"))
write_tif(img_with_metadata, paste0(temp_dir, "/", "Rlogo_preserved"))

# Write with additional/overridden tags
write_tif(img_with_metadata, paste0(temp_dir, "/", "Rlogo_with_tags"),
          tags_to_write = list(
            artist = "R Core Team",
            copyright = "(c) 2024",
            imagedescription = "The R logo"
          ))

img <- matrix(1:4, nrow = 2)
write_tif(img, paste0(temp_dir, "/", "tiny2x2"))
list.files(temp_dir, pattern = "tif$")
```

Index

as.raster.ijtiff_img, 2
as_EBImage, 3
as_ijtiff_img *(*ijtiff_img*)*, 7

count_frames, 4

display, 5

EBImage::Image, *3, 4*

frames_count *(*count_frames*)*, 4

get_supported_tags, 6
graphics::plot.raster(), *3*, *5*

ijtiff, 6
ijtiff-package *(*ijtiff*)*, 6
ijtiff_img, *2–5*, 7, *7–9*, *11*, *13*

linescan-conversion, 8
linescan_to_stack
        *(*linescan-conversion*)*, 8

print.ijtiff_img, 8

read_tags, 9
read_tif, 10
read_tif(), *5*, *9*, *14*
read_txt_img *(*text-image-io*)*, 11

stack_to_linescan
        *(*linescan-conversion*)*, 8

tags_read *(*read_tags*)*, 9
text-image-io, 11
tif_read *(*read_tif*)*, 10
tif_tags_reference, 12
tif_write *(*write_tif*)*, 13
txt_img_read *(*text-image-io*)*, 11
txt_img_write *(*text-image-io*)*, 11

write_tif, 13
write_tif(), *11*
write_txt_img *(*text-image-io*)*, 11