

# Package: jenga (via r-universe)

September 9, 2024

**Type** Package

**Title** Fast Extrapolation of Time Features using K-Nearest Neighbors

**Version** 1.3.0

**Author** Giancarlo Vercellino

**Maintainer** Giancarlo Vercellino <giancarlo.vercellino@gmail.com>

**Description** Fast extrapolation of univariate and multivariate time features using K-Nearest Neighbors. The compact set of hyper-parameters is tuned via grid or random search.

**License** GPL-3

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 7.1.1

**Depends** R (>= 4.1)

**Imports** purrr (>= 0.3.4), abind (>= 1.4-5), ggplot2 (>= 3.3.5), readr (>= 2.1.2), lubridate (>= 1.4.0), narray (>= 0.4.1.1), imputeTS (>= 3.2), scales (>= 1.1.1), tictoc (>= 1.0.1), modeest (>= 2.4.0), moments (>= 0.14), philentropy (>= 0.5.0), greybox (>= 1.0.1), Rfast (>= 2.0.6), dplyr (>= 1.0.7), fastDummies (>= 1.6.3), fANCOVA (>= 0.6-1), entropy (>= 1.3.1)

**URL** [https://rpubs.com/giancarlo\\_vercellino/jenga](https://rpubs.com/giancarlo_vercellino/jenga)

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2022-08-18 08:10:02 UTC

## Contents

|                           |   |
|---------------------------|---|
| covid_in_europe . . . . . | 2 |
| jenga . . . . .           | 2 |

|              |          |
|--------------|----------|
| <b>Index</b> | <b>5</b> |
|--------------|----------|

---

|                 |                                 |
|-----------------|---------------------------------|
| covid_in_europe | <i>covid_in_europe data set</i> |
|-----------------|---------------------------------|

---

**Description**

A data frame with with daily and cumulative cases of Covid infections and deaths in Europe since March 2021.

**Usage**

```
covid_in_europe
```

**Format**

A data frame with 5 columns and 163 rows.

**Source**

[www.ecdc.europa.eu](http://www.ecdc.europa.eu)

---

|       |  |
|-------|--|
| jenga | <i>jenga: automatic projections of time features using KNN</i> |
|-------|--|

---

**Description**

Automatic projections of time features using KNN

**Usage**

```
jenga(  
  df,  
  seq_len = NULL,  
  smoother = FALSE,  
  k = NULL,  
  method = NULL,  
  kernel = NULL,  
  ci = 0.8,  
  n_windows = 10,  
  mode = NULL,  
  n_sample = 30,  
  search = "random",  
  dates = NULL,  
  error_scale = "naive",  
  error_benchmark = "naive",  
  seed = 42  
)
```

**Arguments**

|                 |   |
|-----------------|---|
| df              | A data frame with time features on columns (numerical or categorical features, but not both).   |
| seq_len         | Positive integer. Time-step number of the projected sequence  |
| smoother        | Logical. Perform optimal smoothing using standard loess (only for numerical features). Default: FALSE   |
| k               | Positive integer. Number of neighbors to consider when applying kernel average. Min number is 3. Default: NULL (automatic selection).   |
| method          | Positive integer. Distance method for calculating neighbors. Possible options are: "euclidean", "manhattan", "minkowski". Default: NULL (automatic selection).  |
| kernel          | String. Distribution used to calculate kernel densities. Possible options are: "norm", "cauchy", "unif", "t". Default: NULL (automatic selection).  |
| ci              | Confidence interval. Default: 0.8   |
| n_windows       | Positive integer. Number of validation tests to measure/sample error. Default: 10.  |
| mode            | String. Sequencing method: deterministic ("segmented"), or non-deterministic ("sampled"). Default: NULL (automatic selection).  |
| n_sample        | Positive integer. Number of samples for grid or random search. Default: 30.   |
| search          | String. Two option available: "grid", "random". Default: "random".  |
| dates           | Date. Vector with dates for time features.  |
| error_scale     | String. Scale for the scaled error metrics. Two options: "naive" (average of naive one-step absolute error for the historical series) or "deviation" (standard error of the historical series). Default: "naive". |
| error_benchmark | String. Benchmark for the relative error metrics. Two options: "naive" (sequential extension of last value) or "average" (mean value of true sequence). Default: "naive".   |
| seed            | Positive integer. Random seed. Default: 42.   |

**Value**

This function returns a list including:

- exploration: list of all models, complete with predictions, test metrics, prediction stats and plot
- history: a table with the sampled models, hyper-parameters, validation errors
- best\_model: results for the best model, including:
  - predictions: min, max, q25, q50, q75, quantiles at selected ci, and different statics for numerical and categorical variables
  - testing\_errors: training and testing errors for one-step and sequence for each ts feature (different measures for numerical and categorical variables)
- time\_log

**Author(s)**

Giancarlo Vercellino <giancarlo.vercellino@gmail.com>

**See Also**

Useful links:

- [https://rpubs.com/giancarlo\\_vercellino/jenga](https://rpubs.com/giancarlo_vercellino/jenga)

**Examples**

```
jenga(covid_in_europe[, c(2, 3)], n_sample = 1)
jenga(covid_in_europe[, c(4, 5)], n_sample = 1)
```

# Index

## \* datasets

covid\_in\_europe, [2](#)

covid\_in\_europe, [2](#)

jenga, [2](#)

jenga-package (jenga), [2](#)