

# Package: kml3d (via r-universe)

October 24, 2024

**Type** Package

**Title** K-Means for Joint Longitudinal Data

**Description** An implementation of k-means specifically design to cluster joint trajectories (longitudinal data on several variable-trajectories). Like 'kml', it provides facilities to deal with missing value, compute several quality criterion (Calinski and Harabatz, Ray and Turie, Davies and Bouldin, BIC,...) and propose a graphical interface for choosing the 'best' number of clusters. In addition, the 3D graph representing the mean joint-trajectories of each cluster can be exported through LaTeX in a 3D dynamic rotating PDF graph.

**Version** 2.5.0

**Date** 2024-10-21

**Maintainer** Christophe Genolini <christophe.genolini@free.fr>

**Author** Christophe Genolini [cre, aut], Bruno Falissard [ctb], Patrice Kiener [ctb], Jean-Baptiste Pingault [ctb]

**License** GPL (>= 2)

**LazyData** yes

**Collate** global.r distance3d.r clusterLongData3d.r kml3d.r

**Depends** R (>= 2.10), methods, clv, rgl, misc3d, longitudinalData, kml

**Encoding** UTF-8

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2024-10-23 17:20:01 UTC

## Contents

kml3d-package	2
affectIndiv3d	4
calculTrajMean3d	6
clusterLongData3d	7

ClusterLongData3d-class . . . . .	9
dist3d . . . . .	11
generateArtificialLongData3d . . . . .	12
kml3d . . . . .	14
parKml3d . . . . .	16
plot,ClusterLongData3d . . . . .	18
plot3d,ClusterLongData3d . . . . .	20
plot3dPdf . . . . .	21
plotMeans3d,ClusterLongData3d . . . . .	24
plotTraj3d,ClusterLongData3d . . . . .	25
pregnandiol . . . . .	27

<b>Index</b>	<b>28</b>
--------------	-----------

---

kml3d-package                      ~ Overview: KmL3D, K-means for joint Longitudinal data ~

---

## Description

KmL3D is a new implementation of k-means for longitudinal data (or trajectories). Here is an overview of the package.

## Details

Package:    KmL3D  
 Type:        Package  
 Version:    2.4.2  
 Date:        2017-08-01  
 License:    GPL (>= 2)  
 LazyData:    yes  
 Depends:    methods,graphics,rgl,misc3d,longitudinalData(>=2.2),KmL(>=2.2)  
 URL:        <http://www.r-project.org>  
 URL:        <http://christophe.genolini.free.fr/kml>

## Overview

To cluster data, KmL3D go through three steps, each of which is associated to some functions:

1. Data preparation
2. Building "optimal" clusterization.
3. Exporting results
4. Visualizing and exporting 3D object

## 1. Data preparation

kml3d works on object of class `ClusterLongData3d`. Data preparation therefore simply consists in transforming data into an object `ClusterLongData3d`. This can be done via function `clusterLongData3d` (`cld3d` in short) that converts a data.frame or an array into a `ClusterLongData3d`.

Working on several variables measured on different scales can give too much weight to one of the dimensions. So the function `scale` normalizes data.

Instead of working on real data, one can also work on artificial data. Such data can be created with `generateArtificialLongData3d` (`gal3d` in short).

## 2. Building "optimal" clustering

Once an object of class `ClusterLongData3d` has been created, the algorithm `kml3d` can be run.

Starting with a `ClusterLongData3d`, `kml3d` built several `Partitions` (see package `longitudinalData`).

An object of class `Partition` is a partition of trajectories into subgroups. It also contains some information like the percentage of trajectories contained in each group or some quality criterion (like the Calinski & Harabasz).

k-means is a "hill-climbing" algorithm. The specificity of this kind of algorithm is that it always converges towards a maximum, but one cannot know whether it is a local or a global maximum. It offers no guarantee of optimality.

To maximize one's chances of getting a quality `Partition`, it is better to execute the hill climbing algorithm several times, then to choose the best solution. By default, `kml3d` executes the hill climbing algorithm 20 times.

To date, it is not possible to know the optimum number of clusters even if the calculation of some quality criterion can give some clues. `kml3d` computes various of them.

In the end, `kml3d` tests by default 2, 3, 4, 5 et 6 clusters, 20 times each.

## 3. Exporting results

When `kml3d` has constructed some `Partition`, the user can examine them one by one and choose to export some. This can be done via function `choice`. `choice` opens a graphic window showing various information including the trajectories clustered by a specific `Partition`.

When some `Partition` has been selected (the user can select more than 1), it is possible to save them. The clusters are therefore exported towards the file `name-cluster.csv`. Criteria are exported towards `name-criteres.csv`. The graphs are exported according to their extension.

## 4. Visualizing and exporting 3D object

`KmL3D` also propose tools to visualize the trajectories in 3D. `plot3d` using the library `rgl` to plot two variables according to time (either the all set of joint-trajectories, or just the mean joint-trajectories). Then the user can make the graphical representation turn using the mouse. `plot3dPdf` build an `Triangles` object. These kind of object can be include in a pdf file using `saveTrianglesAsASY` and the software `asymptote`. Once again, it is possible to make the image in the pdf file move using the mouse -so the reader gets real 3D-.

### How to get help?

For those who are not familiar with S4 programming: In S4 programming, each function can be adapted for some specific arguments.

- To get help on a function (for example plot), use: `?(plot)`.
- To get help on a function adapted to its argument (for example plot on argument ClusterLongData), used: `?"plot,ClusterLongData"`.

### Examples

```
### Move to tempdir
wd <- getwd()
setwd(tempdir()); getwd()

### 1. Data Preparation
data(pregnandiol)
names(pregnandiol)
cld3dPregTemp <- cld3d(pregnandiol,timeInData=list(temp=1:30*2,preg=1:30*2+1))

### 2. Building "optimal" clusteration (with only 2 redrawings)
### Real analysis needs at least 20 redrawings
kml3d(cld3dPregTemp,3:5,nbRedrawing=2,toPlot="both")

### 3. Exporting results
try(choice(cld3dPregTemp))

### 4. Visualizing in 3D
plotMeans3d(cld3dPregTemp,4)

### Go back to current dir
setwd(wd)
```

---

affectIndiv3d

~ Function: *affectIndiv3d* ~

---

### Description

Given some longitudinal data (trajectories) and  $k$  clusters centers, `affectIndiv3d` affects each individual to the cluster whose center is the closest.

### Usage

```
affectIndiv3d(traj, clustersCenter, distance = dist3d)
```

**Arguments**

traj	[array(numeric)]: longitudinal data. Each line is an individual, each column is a time measurement, each plan of the third dimension is for one variable.
clustersCenter	[array(numeric)]: cluster center. Each line is a cluster centers, each column is a time measurement, each plan of the third dimension is for one variable. .
distance	[numeric <- function(joint-trajectory, joint-trajectory)]: distance between an individual and a clusters centre.

**Details**

Given an array of clusters center `clustersCenter` (each plan of the first dimension is a cluster center, that is `clusterCenter[2,,]` is the second cluster center), the function `affectIndiv3d` affect each individual of the array `traj` to the closest clusters, according to `distance`.

`affectIndiv3d` used with `calculTrajMean3d` simulates one k-means 3D step.

**Value**

Object of class `Partition`.

**Examples**

```
#####
### affectIndiv

### Some trajectories
traj <- gald3d()["traj"]

### 4 clusters centers
center <- traj[runif(4,1,nrow(traj)),,]

### Affectation of each individual
part <- affectIndiv3d(traj,center)

#####
### K-means simulation (3 steps)
plot(clusterLongData3d(traj),parTraj=parTRAJ(col=part+1))
for (i in 1:3){
  center <- calculTrajMean3d(traj,part)
  part <- affectIndiv3d(traj,center)
  plot(clusterLongData3d(traj),parTraj=parTRAJ(col=part+1))
}
```

---

calculTrajMean3d      ~ *Function: calculTrajMean3d* ~

---

### Description

Given some joint longitudinal data and a cluster affectation, calculTrajMean3d computes the mean joint-trajectories of each cluster.

### Usage

```
calculTrajMean3d(traj, clust, centerMethod=function(x){mean(x, na.rm=TRUE)})
```

### Arguments

traj                    [array(numeric)]: joint longitudinal data. Each line is an individual, each column is a time measurement, the third dimension is for variables.

clust                   [vector(numeric)]: affectation of each individual.

centerMethod          [joint-trajectory <- function(array(numeric))]: function used to compute the clusters' centers.

### Details

Given a vector of affectation to a cluster, the function calculTrajMean3d compute the "central" trajectory of each clusters. The "center" can be define using the argument centerMethod.

affectIndiv3d used with [calculTrajMean3d](#) simulates one k-means step.

### Value

An array of dimension  $(k, t, v)$  with  $k$  number of groups,  $t$  number of time mesurement and  $v$  number of variables.

### Examples

```
#####
### calculTrajMean3d

### Some LongitudinalData3d
traj <- gald3d()["traj"]

### A partition
part <- floor(runif(150,1,5))
plot(clusterLongData3d(traj), parTraj=parTRAJ(col=part+1))

### Clusters center
(center <- calculTrajMean3d(traj, part))

#####
```

```

### K-means simulation (4 steps)
plot(clusterLongData3d(traj),parTraj=parTRAJ(col=part+1))
for (i in 1:4){
  part <- affectIndiv3d(traj,center)
  center <- calculTrajMean3d(traj,part)
  plot(clusterLongData3d(traj),parTraj=parTRAJ(col=part+1))
}

```

---

clusterLongData3d ~ Function: clusterLongData3d (or cld3d) ~

---

## Description

clusterLongData3d (or cld3d in short) is the constructor for [ClusterLongData3d](#) object.

## Usage

```

clusterLongData3d(traj, idAll, time, timeInData, varNames, maxNA)
cld3d(traj, idAll, time, timeInData, varNames, maxNA)

```

## Arguments

traj	[array(numeric)] or [data.frame]: structure containing the joint-trajectories. Each line (traj[i, ,]) is a joint-trajectory of an individual ; columns (traj[, j,]) refer to the time during which measures were made ; the third dimensions (traj[, , l]) are for variables.
idAll	[vector(character)]: single identifier for each trajectory (ie each individual). Note that the identifiers are of type character (that allow to deal identifiers like XUK32-612, identifiers that our favorite epidemiologists are so good at providing). If idAll are numeric, they are converted into characters.
time	[vector(numeric)]: time at which measures were made.
timeInData	[list(vector(numeric))]: precise the column containing the trajectories. The list labels are the names of the variables (like list(A=c(2,3,4),B=c(5,7,9))).
varNames	[character]: name of the variable being measured.
maxNA	[numeric] or [vector(numeric)]: maximum number of NA that are tolerates on a trajectory. If a trajectory has more missing than maxNA, then it is remove from the analysis. Note the maxNA can take diffents values for each variable-trajectories. The default value is length(time)-2.

## Details

clusterLongData3d construct a object of class ClusterLongData (from package kml). Two cases can be distinguished:

**traj is an array:** the first dimension (line) are individual. The second dimension (column) are time at which the measurement are made. The third dimension are the differents variable-trajectories. For example, `traj[, , 2]` is the second variable-trajectory.

If `idAll` is missing, the individuals are labelled `i1, i2, i3,...`

If `timeInData` is missing, all the column are used (`1:ncol(traj)`).

**If traj is a data.frame:** lines are individual. Time of measurement and variables should be provide through `timeInData`. `timeInData` is a list. The label of the list are the variable-trajectories names. Elements of the list are the column containing the trajectories. For example, if `timeInData=list(V=c(2,3,4),W=c(6,8,12))`, then the first variable-trajectory is 'V', its mesearment are in column 2,3 and 4. The second variable-trajectory is 'W', its measurement are in column 6,8 and 12.

If `idAll` is missing, the first column of the data.frame is used.

## Value

An object of class `ClusterLongData3d`.

## Examples

```
#####
### Building an array
tr1n <- array(c(1,2,NA, 1,4,NA, 6,1,8, 10,NA,2, 3,NA,NA,
              4,NA,5, 6,3,4, 3,4,4, 4,NA,NA, 5,5,4),
             dim=c(3,5,2))
```

```
#####
### clusterLongData

### With maxNA=3
clusterLongData3d(traj=tr1n,
                  idAll=as.character(c(100,102,104)),
                  time=c(1,2,4,8,16),
                  varNames=c("P","A"),
                  maxNA=3
                 )

### With maxNA=2
### Individual 104 is exclude
clusterLongData3d(traj=tr1n,
                  idAll=as.character(c(100,102,104)),
                  time=c(1,2,4,8,16),
                  varNames=c("P","A"),
                  maxNA=2
                 )
```



---

ClusterLongData3d-class

~ Class: ClusterLongData3d ~

---

## Description

ClusterLongData3d is an object containing joint-trajectories and associated Partition (from package longitudinalData).

## Objects from the Class

`km13d` is an algorithm that builds a set of Partition from joint longitudinal data. ClusterLongData3d is the object containing the original joint longitudinal data and all the Partition that km13d finds.

When created, an ClusterLongData3d object simply contains initial data (the joint-trajectories). After the execution of km13d, it contains the original data and the Partition which has just been found by km13d.

Note that if km13d is executed several times, every new Partition are added to the original ones, no pre-existing Partition is erased.

## Slots

`idAll` [vector(character)]: Single identifier for each of the joint-trajectory (each individual). Usefull for exporting clusters.

`idFewNA` [vector(character)]: Restriction of `idAll` to the trajectories that does not have 'too many' missing value. See `maxNA` for details.

`time` [numeric]: Time at which measures are made.

`varNames` [vector(character)]: Names of the variable measured.

`traj` [array(numeric)]: Contains the joint longitudinal data. Each horizontal plan (first dimension) corresponds to the trajectories of an individual. Vertical plans (second dimension) refer to the time at which measures are made. Transversal plans (the third dimension) are for variables.

`dimTraj` [vector3(numeric)]: size of the array `traj` (ie `c(length(idFewNA), length(time), length(varNames))`).

`maxNA` [numeric] or [vector(numeric)]: Individual whose trajectories contain more missing value than `maxNA` are exclude from `traj` and will no be use in the analysis. Their identifier is preserved in `idAll` but not in `idFewNA`. When `maxNA` is a single number, it is used for all the variables.

`reverse` [matrix(numeric)]: contain the mean (first line) and the standard deviation (second line) used to normalize the data. Usefull to restaure the original data after a scaling operation.

`criterionActif` [character]: Store the criterion name that will be used by functions that need a single criterion (like `plotCriterion` or `ordered`).

`initializationMethod` [vector(chararcter)]: list all the initialization method that has allready been used to find some Partition (usefull to not run several time a deterministic method).

sorted [logical]: are the Partition currently hold in the object sorted in decreasing order ?

c1 [list(Partition)]: list of Partition with 1 clusters.

c2 [list(Partition)]: list of Partition with 2 clusters.

c3 [list(Partition)]: list of Partition with 3 clusters.

...

c26 [list(Partition)]: list of Partition with 26 clusters.

### Extends

Class LongData3d in package longitudinalData, directly. Class ListPartition in package longitudinalData, directly.

### Methods

object[ 'xxx' ] Get the value of the field xxx. Inherit from LongData3d and ListPartition (in package longitudinalData).

object[ 'xxx' ]<-value Set the field xxx to value. xxx. Inherit from ListPartition.

plot Display the ClusterLongData3d, one graph for each variable, according to a Partition.

plot3d Display two variables of the ClusterLongData3d in 3D according to a Partition.

plot3dPdf Export the AZY code for displaying two variables of the ClusterLongData3d in a 3D pdf graph.

### Special thanks

Special thanks to Boris Hejblum for debugging the '[' and '['<- operators (the previous version was not compatible with the matrix package, which is used by lme4).

### Examples

```
### Move to tempdir
wd <- getwd()
setwd(tempdir()); getwd()

### Building longData
traj <- array(c(1,2,3,1,4, 3,6,1,8,10, 1,2,1,3,2, 4,2,5,6,3, 4,3,4,4,4, 7,6,5,5,4),
             dim=c(3,5,2))

myCld <- clusterLongData3d(
  traj=traj,
  idAll=as.character(c(100,102,103)),
  time=c(1,2,4,8,15),
  varNames=c("P", "A"),
  maxNA=3
)

### Show
myCld
```

```

### Get
myCld['varNames']

### Set
myCld['criterionActif']<-"Davies.Bouldin"

### Plot
plot(myCld)

### Go back to current dir
setwd(wd)

```

---

dist3d                      ~ Function: dist3d ~

---

## Description

Compute the distance between two joint trajectories.

## Usage

```
dist3d(x, y, method = "euclidian", power = 2)
```

## Arguments

x	[matrix(numeric)]: first trajectory. The column are time, the line are variables.
y	[matrix(numeric)]: second trajectory. The column are time, the line are variables.
method	[character]: method used. Should be one of the method used by the function <a href="#">dist</a> .
power	[numeric]: if method="minkowski", power is the power used.

## Details

Compute the distance between two joint trajectories, using one of the distance define by [dist](#).

## Value

A numeric

## Examples

```

### Move to tempdir
wd <- getwd()
setwd(tempdir()); getwd()

### Generate artificial data

```

```

myCld <- gald3d()

### Distance between individual 1 and 3 (there are in the same group)
dist3d(myCld['traj'][1,,],myCld['traj'][3,,])

### Distance between individual 1 and 51 (there are in two different groups)
dist3d(myCld['traj'][1,,],myCld['traj'][51,,])

### Go back to current dir
setwd(wd)

```

---

```
generateArtificialLongData3d
```

```
~ Function: generateArtificialLongData3d (or gald3d) ~
```

---

## Description

This function build up an artificial longitudinal data set (joint trajectories) an turn them into an object of class ClusterLongData (from package longitudinalData).

## Usage

```

gald3d(nbEachClusters=50,time=0:10,varNames=c("V","T"),
      meanTrajectories=list(function(t){c(0,0)},
                           function(t){c(10,10)},function(t){c(10-t,10-t)}),
      personalVariation=function(t){c(rnorm(1,0,2),rnorm(1,0,2))},
      residualVariation=function(t){c(rnorm(1,0,2),rnorm(1,0,2))},
      decimal=2,percentOfMissing=0)

generateArtificialLongData3d(nbEachClusters=50,time=0:10,varNames=c("V","T"),
                             meanTrajectories=list(function(t){c(0,0)},
                                                    function(t){c(10,10)},function(t){c(10-t,10-t)}),
                             personalVariation=function(t){c(rnorm(1,0,2),rnorm(1,0,2))},
                             residualVariation=function(t){c(rnorm(1,0,2),rnorm(1,0,2))},
                             decimal=2,percentOfMissing=0)

```

## Arguments

**nbEachClusters** [vector(numeric)]: number of trajectories that each cluster must contain. If a single number is given, it is duplicated for all groups.

**time** [vector(numeric)]: time at which measures are made.

**varNames** [vector(character)]: names of the variables.

**meanTrajectories** [list(function)]: lists the functions that define the average trajectories of each cluster. Each functions shall return a vector containing one value for each variable of varNames.

personalVariation	[function] or [list(function)]: lists the functions defining the personal variation between an individual and the mean trajectories of its cluster. Note that these function should be constant function (the personal variation can not evolve with time). If a single function is given, it is duplicated for all groups (see detail).
residualVariation	[function] or [list(function)]: lists the functions generating the noise of each trajectory within its own cluster. Each functions shall return a vector containing one value for each variable of varNames. If a single function is given, it is duplicated for all groups.
decimal	[numeric]: number of decimals used to round up values.
percentOfMissing	[numeric]: percentage (between 0 and 1) of missing data generated in each cluster. If a single value is given, it is duplicated for all groups. The missing values are Missing Completely At Random (MCAR).

## Details

generateArtificialLongData3d (gald3d in short) is a function that construct a set of artificial joint longitudinal data. Each individual is considered as belonging to a group. This group follows a theoretical trajectory, function of time. These functions (one per group) are given via the argument meanTrajectories.

Within a group, the individual undergoes individual variations. Individual variations are given via the argument residualVariation.

The number of individuals in each group is given by nbEachClusters.

Finally, it is possible to add missing values randomly (MCAR) striking the data thanks to percentOfMissing.

## Value

Object of class ClusterLongData (see package longitudinalData).

## Author

Christophe Genolini

1. UMR U1027, INSERM, Université Paul Sabatier / Toulouse III / France

2. CeRSME, EA 2931, UFR STAPS, Université de Paris Ouest-Nanterre-La Défense / Nanterre / France

## References

[1] C. Genolini and B. Falissard  
 "KmL: k-means for longitudinal data"  
 Computational Statistics, vol 25(2), pp 317-328, 2010

[2] C. Genolini and B. Falissard  
 "KmL: A package to cluster longitudinal data"

Computer Methods and Programs in Biomedicine, 104, pp e112-121, 2011

### See Also

[ClusterLongData3d](#), [clusterLongData3d](#), [generateArtificialLongData](#)

### Examples

```
#####
### Default example

ex1 <- generateArtificialLongData3d()
plot3d(ex1, parTraj=parTRAJ(col=rep(2:4, each=50)))

#####
### 4 lines with unbalanced groups

ex2 <- generateArtificialLongData3d(
  nbEachClusters=c(5,10,20,40),
  meanTrajectories=list(
    function(t)c(t,t^3/100),
    function(t)c(0,t),
    function(t)c(t,t),
    function(t)c(0,t^3/100)
  ),
  residualVariation = function(t){c(rnorm(1,0,1),rnorm(1,0,1))}
)

plot3d(ex2, parTraj=parTRAJ(col=rep(1:4, time=c(5,10,20,40))))
```

---

kml3d

*~ Algorithm kml3d: K-means for Joint Longitudinal data ~*

---

### Description

kml3d is a new implementation of k-means for joint longitudinal data (or joint trajectories). This algorithm is able to deal with missing value and provides an easy way to re roll the algorithm several times, varying the starting conditions and/or the number of clusters looked for.

Here is the description of the algorithm. For an overview of the package, see [kml3d-package](#).

### Usage

```
kml3d(object, nbClusters = 2:6, nbRedrawing = 20, toPlot = "none",
  parAlgo = parKml3d())
```

## Arguments

object	[ClusterLongData3d]: contains trajectories to clusterize and some Partition (see package longitudinalData).
nbClusters	[vector(numeric)]: Vector containing the number of clusters with which kml3d must work. By default, nbClusters is 2:6 which indicates that kml3d must search partitions with respectively 2, then 3, ... up to 6 clusters. Maximum number of cluster is 26.
nbRedrawing	[numeric]: Sets the number of time that k-means must be re-run (with different starting conditions) for each number of clusters.
toPlot	[character]: during computation, kml3d can display some graphes. If toPlot="traj", then the trajectories are plot (like with function plot, ClusterLongData). If toPlot="criterion", the quality criterions are plot (like with function plotCriterion). If toPlot="both", the graphic windows is split in two and both graphs are displayed. If "none", there is no graphical display.
parAlgo	[ParKml] (in package kml): set the option used by kml3d (like the starting condition, the imputation methods, the save frequency, the maximum number of iteration, , the distance used...) See ParKml in package kml for details. The default values are described in parKml3d.

## Details

kml3d works on object of class ClusterLongData. For each number  $i$  included in nbClusters, kml3d computes a Partition then stores it in the field  $cX$  of the object ClusterLongData according to its number of clusters 'X'. The algorithm starts over as many times as it is told in nbRedrawing. By default, it is executed for 2, 3, 4, 5 and 6 clusters 20 times each, namely 100 times.

When a Partition has been found, it is added to the slot  $c1$ ,  $c2$ ,  $c3$ , ... or  $c26$ .  $cX$  stores the all Partition with X clusters. Inside a sublist, the Partition are sorted from the biggest quality criterion to the smallest (the best are stored first, using ordered,ListPartition), or not.

Note that Partition are saved throughout the algorithm. If the user interrupts the execution of kml3d, the result is not lost. If the user run kml3d on an object, then running kml3d again on the same object will add some new Partition to the one already found.

The possible starting conditions are defined in initializePartition.

## Value

A ClusterLongData3d object, after having added some Partition to it.

## Optimisation

Behind kml3d, there are two different procedures :

1. Fast: when the parameter distance is set to "euclidean3d" and toPlot is set to 'none' or 'criterion', kml3d call a C compiled (optimized) procedure.
2. Slow: when the user defines its own distance or if he wants to see the construction of the clusters by setting toPlot to 'traj' or 'both', kml3d uses a R non compiled programmes.

The C procedure is 25 times faster than the R one.

So we advice to use the R procedure 1/ for trying some new method (like using a new distance) or 2/ to "see" the very first clusters construction, in order to check that every thing goes right. Then it is better to switch to the C procedure (like we do in Example section).

If for a specific use, you need a different distance, feel free to contact the author.

### See Also

Overview: [kml3d-package](#)

Classes : [ClusterLongData3d](#), Partition in package longitudinalData

Methods : [clusterLongData3d](#), [choice](#)

### Examples

```
### Move to tempdir
wd <- getwd()
setwd(tempdir()); getwd()

### Generation of some data
cld1 <- generateArtificialLongData3d(15)

### We suspect 2, 3, 4 or 5 clusters, we want 3 redrawing.
### We want to "see" what happen (so toPlot="both")
kml3d(cld1,2:5,3,toPlot="both")

### 3 seems to be the best.
### We don't want to see again, we want to get the result as fast as possible.
### Just, to check the overall process, we plot the criterion evolution
kml3d(cld1,3,10,toPlot="criterion")

### Go back to current dir
setwd(wd)
```

---

parKml3d

~ Function: parKml3d ~

---

### Description

parKml3d is a constructor of object ParKml (from package kml) that provide adequate default value for the use of function [kml3d](#).

### Usage

```
parKml3d(saveFreq = 100, maxIt = 200, imputationMethod = "copyMean",
         distanceName = "euclidean3d", power = 2, distance = function() {
           }, centerMethod = meanNA, startingCond = "nearlyAll", nbCriterion =100,scale=TRUE)
```



**Arguments**

saveFreq	[numeric]: Long computations can take several days. So it is possible to save the object <code>ClusterLongData3d</code> on which works <code>kml3d</code> once in a while. <code>saveFreq</code> defines the frequency of the saving process. The <code>ClusterLongData3d</code> is saved every <code>saveFreq</code> clustering calculations. The object is saved in the file <code>objectName.Rdata</code> in the current folder.
maxIt	[numeric]: Set a limit to the number of iteration if convergence is not reached.
imputationMethod	[character]: the calculation of quality criterion can not be done if some value are missing. <code>imputationMethod</code> define the method use to impute the missing value. See <code>imputation</code> for detail.
distanceName	[character]: name of the distance used by k-means. If the <code>distanceName</code> is "euclidean3d", a compiled optimized version specifically design for joint-trajectories version is used. Otherwise, the function define in the slot <code>distance</code> is used.
power	[numeric]: If <code>distanceName="minkowski"</code> , this define the power that will be used.
distance	[numeric <- function(trajA, trajB)]: function that computes the distance between two trajectories. If no function is specified, the Euclidian distance with Gower adjustment (to deal with missing value) is used.
centerMethod	[numeric <- function(vector(numeric))]: k-means algorithm computes the centers of each cluster. It is possible to personalize the definition of "center" by defining a function "centerMethod". This function should take a vector of numeric as argument and return a single numeric -the center of the vector-.
startingCond	[character]: specifies the starting condition. Should be one of "randomAll", "randomK", "maxDist", "kmeans++", "kmeans+", "kmeans-" or "kmeans-" (see <code>initializePartition</code> for details). It also could take two specific values: "all" stands for c("maxDist", "kmeans-") then an alternance of "kmeans-" and "randomK" while "nearlyAll" stands for "kmeans-" then an alternance of "kmeans-" and "randomK".
nbCriterion	[numeric]: set the maximum number of quality criterion that are display on the graph (since displaying a high criterion number an slow down the overall process, the default value is 100).
scale	[logical]: if TRUE, then the data will be automaticaly scaled (using the function <code>scale</code> with default values) before the execution of k-means on joint trajectories. Then the data will be restore (using the function <code>restoreRealData</code> ) just before the end of the function <code>kml3d</code> . This option has no effect on <code>kml</code> .

**Details**

`parKml3d` is a constructor of object `ParKml` (from package `kml`) that provide adequate default value for the use of function `kml3d`.

**Value**

An object `ParKml` (see package `kml`).

**Examples**

```

### Move to tempdir
wd <- getwd()
setwd(tempdir()); getwd()

### Generation of some data
cld1 <- generateArtificialLongData3d(c(15,15,15))

### Setting two different set of option :
(option1 <- parKml3d())
(option2 <- parKml3d(centerMethod=function(x)median(x,na.rm=TRUE)))

### Running kml. Formaly, the second exemple is 'k-median'
kml3d(cld1,4,1,toPlot="both",parAlgo=option1)
kml3d(cld1,4,1,toPlot="both",parAlgo=option2)

### Go back to current dir
setwd(wd)

```

---

plot, ClusterLongData3d

~ Function: plot for ClusterLongData3d ~

---

**Description**

plot the trajectories of an object ClusterLongData relatively to a Partition. One graph for each variable is displayed.

**Usage**

```

## S4 method for signature 'ClusterLongData3d,ANY'
plot(x,y=NA,parTraj=parTRAJ(),parMean=parMEAN(),
     addLegend=TRUE,adjustLegend=-0.05,toPlot="both",nbCriterion=1000,...)

```

**Arguments**

x	[ClusterLongData3d]: Object containing the joint-trajectories to plot.
y	[numeric] or [vector2(numeric)]: Give the Partition to represent. If y is missing, the Partition with the highest quality criterion (the actif one) is selected. If y is a number, the first Partition of the sublist c-y is selected. If y is a couple of numeric, the y[2]th Partition of the sublist c-y[1] is selected.
parTraj	[ParLongData]: Specification of the plotting parameters of the individual trajectories. Fields that can be changes are 'type','col','pch','xlab' and 'ylab'. In addition to the standard possible values, the option col="clusters" can be use to color the individual trajectories according to their clusters (exemple: parTraj=parTRAJ(type="o", col="clusters")). See ParLongData in package longitudinalData for details.

parMean	[ParLongData]: Specification of the plotting parameters of the mean trajectories (only when y is non missing). Fields that can be changes are 'type', 'col', 'pch', 'pchPeriod' and 'cex'. See ParLongData in package longitudinalData for details.
toPlot	[character]: either 'traj' for plotting trajectories alone, 'criterion' for plotting criterion alone, 'both' for plotting both or 'none' for not display anything.
nbCriterion	[numeric]: if a single criterion is given to criterion (and thus is displayed for 'all' the Partition), this slot allows to fix a limit on the number of points that will be display.
addLegend	[logical]: should the legend be displayed?
adjustLegend	[numeric]: fix the hight of the legend
...	Some other parameters can be passed to the method (like "xlab" or "ylab").

### Details

plot the trajectories of an object `ClusterLongData3d` relatively to the 'best' Partition, or to the Partition define by y.

Graphical option concerning the individual trajectory (col, type, pch and xlab) can be change using `parTraj`. Graphical option concerning the cluster mean trajectory (col, type, pch, pchPeriod and cex) can be change using `parMean`. For more detail on `parTraj` and `parMean`, see object of class `ParLongData` in package `longitudinalData`.

### See Also

Overview: [kml3d-package](#)  
 Classes : `ClusterLongData3d`  
 Plot : `plotTraj`, `plotCriterion`

### Examples

```
### Move to tempdir
wd <- getwd()
setwd(tempdir()); getwd()

#####
### Construction of the data

myCld <- gald3d()

### Basic plotting
plot(myCld)

#####
### Changing graphical parameters 'par'

### No letters on the mean trajectories
kml3d(myCld,2:7,2)
plot(myCld,2,parMean=parMEAN(type="l"))

### Only one letter on the mean trajectories
```

```

plot(myCld,3,parMean=parMEAN(pchPeriod=Inf))

### Color individual according to its clusters (col="clusters")
plot(myCld,4,parTraj=parTRAJ(col="clusters"))

### Mean without individual
plot(myCld,5,parTraj=parTRAJ(type="n"))

### No mean trajectories (type="n")
### Color individual according to its clusters (col="clusters")
plot(myCld,6,parTraj=parTRAJ(col="clusters"),parMean=parMEAN(type="n"))

### Only few trajectories
plot(myCld,7,nbSample=10,parTraj=parTRAJ(col='clusters'),parMean=parMEAN(type="n"))

### Go back to current dir
setwd(wd)

```

---

```
plot3d,ClusterLongData3d
```

```
~ Function: plot3d for ClusterLongData3d ~
```

---

## Description

Plot two variables of a [ClusterLongData3d](#) object in 3D, optionnaly relatively to a [Partition](#).

## Usage

```

## S4 method for signature 'ClusterLongData3d,numeric'
plot3d(x,y,varY=1,varZ=2,
      parTraj=parTRAJ(),parMean=parMEAN(),...)

```

## Arguments

x	[ClusterLongData3d]: Object containing the trajectories to plot.
y	[numeric] or [vector2(numeric)]: Define the <a href="#">Partition</a> P that will be use to plot the object. P is a <a href="#">Partition</a> hold in the field c2, c3, ... c26. If y=c(a,b), then P is the <a href="#">Partition</a> number b with a clusters. If y=a, then P is the partition number 1 with a clusters. If y is missing, P is the <a href="#">Partition</a> with the best criterion.
varY	[numeric] or [character]: either the number or the name of the first variable to display. 1 by default.
varZ	[numeric] or [character]: either the number or the name of the second variable to display. 2 by default.
parTraj	[ParLongData]: Set the graphical parameters used to plot the trajectories of the <a href="#">ClusterLongData3d</a> . See <a href="#">ParLongData</a> in package <a href="#">longitudinalData</a> for details.

parMean [ParLongData]: Set the graphical parameters used to plot the mean trajectories of each clusters ClusterLongData3d (only when y is non missing). See ParLongData in package longitudinalData for details.

... Arguments to be passed to methods, such as graphical parameters.

### Details

Plot two variables of a `ClusterLongData3d` object in 3D. It use the `rgl` library. The user can make the graphical representation turn using its mouse.

### See Also

[ClusterLongData3d](#)

### Examples

```
### Move to tempdir
wd <- getwd()
setwd(tempdir()); getwd()

#####
### Real example on array

time=c(1,2,3,4,8,12,16,20)
id2=1:120
f <- function(id,t)((id-1)%3-1) * t
g <- function(id,t)(id%2+1)*t
h <- function(id,t)(id%4-0.5)*(20-t)
myCld <- clusterLongData3d(array(cbind(outer(id2,time,f),outer(id2,time,g),
  outer(id2,time,h))+rnorm(120*8*3,0,3),dim=c(120,8,3)))

### Basic plot
plot(myCld,parTraj=parTRAJ(col=rep(1:6,20)))

### plot3d, variable 1 and 2
plot3d(myCld,parTraj=parTRAJ(col=rep(1:6,20)))

### plot3d, variable 1 and 3
plot3d(myCld,parTraj=parTRAJ(col=rep(1:6,20)),varZ=3)
plot3d(myCld,parTraj=parTRAJ(col="red"))

### Go back to current dir
setwd(wd)
```

## Description

Given a [ClusterLongData3d](#) and a Partition (from package `longitudinalData`), this function creates Triangle objects representing the 3D plot of two variables of the main trajectories.

## Usage

```
## S4 method for signature 'ClusterLongData3d,missing'
plot3dPdf(x,y,varY=1,varZ=2)
## S4 method for signature 'ClusterLongData3d,numeric'
plot3dPdf(x,y,varY=1,varZ=2)
```

## Arguments

<code>x</code>	[ClusterLongData]: Object containing the trajectories to plot.
<code>y</code>	[numeric]: Define Partition P that will be use to plot the object. P is a Partition hold in the field <code>c2, c3, ... c26</code> . If <code>y=c(a,b)</code> , then P is the Partition number <code>b</code> with <code>a</code> clusters. If <code>y=a</code> , then P is the partition number 1 with <code>a</code> clusters. If <code>y</code> is missing, P is the Partition with the best criterion.
<code>varY</code>	[numeric] or [character]: either the number or the name of the first variable to display. 1 by default.
<code>varZ</code>	[numeric] or [character]: either the number or the name of the second variable to display. 2 by default.

## Details

Create Triangle objects representing the 3D plot of the main trajectories of a `ClusterLongData` (of package `longitudinalData`).

The three functions [plot3dPdf](#), [saveTrianglesAsASY](#) and [makeLatexFile](#) are design to export a 3D graph to a Pdf file. The process is the following:

1. [plot3dPdf](#): Create a scene, that is a collection of Triangle object that represent a 3D images.
2. [saveTrianglesAsASY](#): Export the scene in an `'asy'` file.
3. `'asy'` can not be include in LaTeX file. LaTeX can read only `'pre'` file. So the next step is to use `asympote` to convert `'asy'` tp `'pre'`. This is done by the command `asy -inlineimage -tex pdflatex scene.asy`.
4. The previous step did produce a file `scene+0.prc` that can be include in a LaTeX file. [makeLatexFile](#) create a LaTeX file that is directly compilable (using `pdfLatex`). It produce a pdf file that contain the 3D object.

## Value

A Triangle object.

**Author(s)**

Christophe Genolini  
INSERM U669 / PSIGIAM: Paris Sud Innovation Group in Adolescent Mental Health  
Modal'X / Universite Paris Ouest-Nanterre- La Defense

Contact author : <christophe.genolini@free.fr>

**References**

Article "KmL: K-means for Longitudinal Data", in Computational Statistics, Volume 25, Issue 2 (2010), Page 317.

Web site: <http://christophe.genolini.free.fr/kml/>

**See Also**

[makeTriangles](#)

**Examples**

```
### Move to tempdir
wd <- getwd()
setwd(tempdir()); getwd()

### Generating the data
myCld3d <- gald3d(c(5,5,5))
kml3d(myCld3d,3:4,1)

### Creation of the scene
scene <- plot3dPdf(myCld3d,3)
drawScene.rgl(scene)

### Export in '.azy' file
saveTrianglesAsASY(scene)

### Creation of a '.prc' file
# Open a console window, then run
# asy -inlineimage -tex pdflatex scene.azy

### Creation of the LaTeX main document
makeLatexFile()

### Creation of the '.pdf'
# Open a console window, then run
# pdfLatex main.tex

### Go back to current dir
setwd(wd)
```

---

plotMeans3d, ClusterLongData3d

~ Function: plotMeans3d for ClusterLongData3d ~

---

### Description

Plot the means of two variables of a [ClusterLongData3d](#) object in 3D relatively to a Partition (from package in longitudinalData).

### Usage

```
## S4 method for signature 'ClusterLongData3d,numeric'
plotMeans3d(x,y,varY=1,varZ=2,
            parTraj=parTRAJ(type="n"),parMean=parMEAN(),...)
```

### Arguments

x	[ClusterLongData3d]: Object containing the trajectories to plot.
y	[numeric] or [vector2(numeric)]: Define the Partition P that will be use to plot the object. P is a Partition hold in the field c2, c3, ... c26. If y=c(a,b), then P is the Partition number b with a clusters. If y=a, then P is the partition number 1 with a clusters.
varY	[numeric] or [character]: either the number or the name of the first variable to display. 1 by default.
varZ	[numeric] or [character]: either the number or the name of the second variable to display. 2 by default.
parTraj	[ParLongData]: Set the graphical parameters used to plot the trajectories of the ClusterLongData3d. See ParLongData in package longitudinalData for details.
parMean	[ParLongData]: Set the graphical parameters used to plot the mean trajectories of each clusters ClusterLongData3d (only when y is non missing). See ParLongData in package longitudinalData for details.
...	Arguments to be passed to methods, such as graphical parameters.

### Details

Plot two variables of a [ClusterLongData3d](#) object in 3D. It use the [rgl](#) library. The user can make the graphical representation turn using its mouse.

### See Also

[ClusterLongData3d](#)



**Examples**

```

### Move to tempdir
wd <- getwd()
setwd(tempdir()); getwd()

#####
### Real example on array

time=c(1,2,3,4,8,12,16,20)
id2=1:120
f <- function(id,t)((id-1)%3-1) * t
g <- function(id,t)(id%2+1)*t
h <- function(id,t)(id%4-0.5)*(20-t)
myCld <- clusterLongData3d(array(cbind(outer(id2,time,f),outer(id2,time,g),
  outer(id2,time,h))+rnorm(120*8*3,0,3),dim=c(120,8,3)))
kml3d(myCld,3:4,2)

### Basic plot
plotMeans3d(myCld,3)

### plotMeans3d, variable 1 and 3
plotMeans3d(myCld,4,varZ=3)
plotMeans3d(myCld,3,parTraj=parTRAJ(col="red"))

### Go back to current dir
setwd(wd)

```

---

plotTraj3d, ClusterLongData3d

~ Function: plotTraj3d for ClusterLongData3d ~

---

**Description**

Plot the trajectories of two variables of a [ClusterLongData3d](#) object in 3D relatively to a Partition from package longitudinalData.

**Usage**

```

## S4 method for signature 'ClusterLongData3d,numeric'
plotTraj3d(x,y,varY=1,varZ=2,
  parTraj=parTRAJ(col="clusters"),parMean=parMEAN(type="n"),...)

```

**Arguments**

**x** [ClusterLongData3d]: Object containing the trajectories to plot.

**y** [numeric] or [vector2(numeric)]: Define the Partition P that will be use to plot the object. P is a Partition hold in the field c2, c3, ... c26. If y=c(a,b), then P is the Partition number b with a clusters. If y=a, then P is the partition number 1 with a clusters.

varY	[numeric] or [character]: either the number or the name of the first variable to display. 1 by default.
varZ	[numeric] or [character]: either the number or the name of the second variable to display. 2 by default.
parTraj	[ParLongData]: Set the graphical parameters used to plot the trajectories of the ClusterLongData3d. See ParLongData in package longitudinalData for details.
parMean	[ParLongData]: Set the graphical parameters used to plot the mean trajectories of each clusters ClusterLongData3d (only when y is non missing). See ParLongData in package longitudinalData for details.
...	Arguments to be passed to methods, such as graphical parameters.

### Details

Plot the means trajectories of two variables of a [ClusterLongData3d](#) object in 3D. It use the [rgl](#) library. The user can make the graphical representation turn using its mouse.

### See Also

[ClusterLongData3d](#)

### Examples

```
### Move to tempdir
wd <- getwd()
setwd(tempdir()); getwd()

#####
### Real example on array

time=c(1,2,3,4,8,12,16,20)
id2=1:120
f <- function(id,t)((id-1)%3-1) * t
g <- function(id,t)(id%2+1)*t
h <- function(id,t)(id%4-0.5)*(20-t)
myCld <- clusterLongData3d(array(cbind(outer(id2,time,f),outer(id2,time,g),
  outer(id2,time,h))+rnorm(120*8*3,0,3),dim=c(120,8,3)))
kml3d(myCld,3:4,2)

### Basic plot
plotMeans3d(myCld,3)

### plotTraj3d, variable 1 and 3
plotMeans3d(myCld,4,varZ=3)
plotMeans3d(myCld,3,parMean=parMEAN(col="red"))

### Go back to current dir
setwd(wd)
```

---

pregnandiol

~ *Pregnandiol measure (from QUIDEL database, René Écochard)* ~

---

### Description

These longitudinal data are extract form the QUIDEL database whose aims is to studies hormone profiles among women who have no fertility problem.

### Usage

```
data(pregnandiol)
```

### Format

Some longitudinal data in wide format. It includes 107 women who have been followed during up to 49 days. Each column correspond to a specific time meseasurement. The outcome is the hormone "pregnandiol".

id unique idenfier for each patient.

day1 Measurement of pregnandiol at day 1.

day2 Measurement of pregnandiol at day 2.

day3 Measurement of pregnandiol at day 3.

... ..

day 49 Measurement of pregnandiol at day 49.

### Details

The QUIDEL database aims to gain better knowledge of hormone profiles among women who have no fertility problem. This database has been described as the largest existing database on hormone profiles in the normal human menstrual cycle, involving ultrasound scan of the day of ovulation [eco06]. It involves 107 women and 283 cycles in all, with identification of the day of ovulation and daily titration of the levels of the four main hormones in the ovulation cycle. The database belongs to the laboratory in charge of the analysis of hormone trajectories (CNRS 5558, René Ecochard). It has already been the subject of numerous publications, including [eco00, eco01].

### Source

QUIDEL cohort

### References

[eco00] Ecochard R, Gougeon A. Side of ovulation and cycle characteristics in normally fertile women. *Human reproduction* (Oxford, England). 2000;15(4):752-755.

[eco01] Ecochard R et al. Chronological aspects of ultrasonic, hormonal, and other indirect indices of ovulation. *BJOG : an international journal of obstetrics and gynaecology*. 2001;108(8):822-829.

# Index

- \* **aplot**
  - plot3d, ClusterLongData3d, 20
  - plotMeans3d, ClusterLongData3d, 24
  - plotTraj3d, ClusterLongData3d, 25
- \* **chron**
  - kml3d, 14
  - kml3d-package, 2
  - plot, ClusterLongData3d, 18
- \* **classes**
  - ClusterLongData3d-class, 9
- \* **classif**
  - kml3d, 14
  - kml3d-package, 2
  - plot, ClusterLongData3d, 18
- \* **clusters**
  - pregnandiol, 27
- \* **cluster**
  - generateArtificialLongData3d, 12
  - kml3d, 14
  - kml3d-package, 2
  - plot, ClusterLongData3d, 18
- \* **datagen**
  - generateArtificialLongData3d, 12
- \* **documentation**
  - pregnandiol, 27
- \* **dplot**
  - kml3d, 14
  - kml3d-package, 2
  - plot, ClusterLongData3d, 18
- \* **iplot**
  - kml3d-package, 2
  - plot, ClusterLongData3d, 18
- \* **models**
  - kml3d-package, 2
- \* **nonparametric**
  - kml3d, 14
  - kml3d-package, 2
- \* **package**
  - kml3d-package, 2
  - plot3d, ClusterLongData3d, 20
  - plotMeans3d, ClusterLongData3d, 24
  - plotTraj3d, ClusterLongData3d, 25
- \* **robust**
  - kml3d, 14
  - kml3d-package, 2
- \* **spatial**
  - kml3d, 14
  - kml3d-package, 2
  - plot, ClusterLongData3d, 18
- \* **ts**
  - generateArtificialLongData3d, 12
  - kml3d, 14
  - kml3d-package, 2
  - plot, ClusterLongData3d, 18
  - plot3d, ClusterLongData3d, 20
  - plotMeans3d, ClusterLongData3d, 24
  - plotTraj3d, ClusterLongData3d, 25
  - [, ClusterLongData3d, ANY, missing-method (ClusterLongData3d-class), 9
  - [, ClusterLongData3d-method (ClusterLongData3d-class), 9
  - [, ParChoice-method (kml3d-package), 2
  - [<- , ClusterLongData3d, character, missing, missing-method (ClusterLongData3d-class), 9
  - [<- , ClusterLongData3d-method (ClusterLongData3d-class), 9
  - [<- , ParChoice-method (kml3d-package), 2
  - affectIndiv3d, 4
  - calculTrajMean3d, 5, 6, 6
  - choice, 3, 16
  - cld3d, 3
  - cld3d (clusterLongData3d), 7
  - ClusterLongData3d, 3, 7, 8, 14–17, 19–22, 24–26
  - clusterLongData3d, 3, 7, 14, 16
  - clusterLongData3d, ANY, ANY, ANY, ANY, ANY, ANY (clusterLongData3d), 7

- clusterLongData3d, ANY, ANY, ANY, ANY, ANY, ANY-method (clusterLongData3d), 7
- clusterLongData3d, missing, missing, missing, missing-method (clusterLongData3d), 7
- clusterLongData3d, missing, missing, missing, missing-method (clusterLongData3d), 7
- ClusterLongData3d-class, 9
- dist, 11
- dist3d, 11
- gald3d, 3
- gald3d (generateArtificialLongData3d), 12
- generateArtificialLongData, 14
- generateArtificialLongData3d, 3, 12
- imputation, 17
- initializePartition, 15, 17
- kml, 17
- kml3d, 3, 9, 14, 16, 17
- kml3d, ClusterLongData-method (kml3d), 14
- kml3d-method (kml3d), 14
- kml3d-package, 2, 14
- makeLatexFile, 22
- makeTriangles, 23
- ordered, 9
- parKml3d, 15, 16
- Partition, 5
- plot, 10
- plot (plot, ClusterLongData3d), 18
- plot, ClusterLongData3d, 18
- plot, ClusterLongData3d, ANY-method (plot, ClusterLongData3d), 18
- plot, ClusterLongData3d, missing-method (plot, ClusterLongData3d), 18
- plot, ClusterLongData3d, numeric-method (plot, ClusterLongData3d), 18
- plot3d, 3, 10
- plot3d (plot3d, ClusterLongData3d), 20
- plot3d, ClusterLongData3d, 20
- plot3d, ClusterLongData3d, missing-method (plot3d, ClusterLongData3d), 20
- plot3d, ClusterLongData3d, numeric-method (plot3d, ClusterLongData3d), 20
- plot3dPdf, 3, 10, 21, 22
- plot3dPdf, ClusterLongData3d, missing-method (plot3dPdf), 21
- plot3dPdf, ClusterLongData3d, numeric-method (plot3dPdf), 21
- plot3dPdf, ClusterLongData3d, missing-method (plot3dPdf), 21
- plotCriterion, 9, 15, 19
- plotMeans3d (plotMeans3d, ClusterLongData3d), 24
- plotMeans3d, ClusterLongData3d, 24
- plotMeans3d, ClusterLongData3d, numeric-method (plotMeans3d, ClusterLongData3d), 24
- plotTraj, 19
- plotTraj3d (plotTraj3d, ClusterLongData3d), 25
- plotTraj3d, ClusterLongData3d, 25
- plotTraj3d, ClusterLongData3d, numeric-method (plotTraj3d, ClusterLongData3d), 25
- pregnandiol, 27
- restoreRealData, 17
- rgl, 21, 24, 26
- saveTrianglesAsASY, 3, 22
- scale, 3, 17
- show, ClusterLongData3d-method (ClusterLongData3d-class), 9
- Triangles, 3