

# Package: `kuiper.2samp` (via `r-universe`)

September 5, 2024

**Title** Two-Sample Kuiper Test

**Version** 1.0

**Author** Ying Ruan [aut, cre]

**Maintainer** Ying Ruan <y.ruan.16@ucl.ac.uk>

**Description** This function performs the two-sample Kuiper test to assess the anomaly of continuous, one-dimensional probability distributions. References used for this method are (1). Kuiper, N. H. (1960). <[DOI:10.1016/S1385-7258\(60\)50006-0](https://doi.org/10.1016/S1385-7258(60)50006-0)> and (2). Paltani, S. (2004). <[DOI:10.1051/0004-6361:20034220](https://doi.org/10.1051/0004-6361:20034220)>.

**Depends** R (>= 3.3.1)

**License** AGPL-3

**LazyData** true

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2018-12-18 11:20:09 UTC

## Contents

<code>kuiper.2samp</code> . . . . .	1
<b>Index</b>	<b>3</b>

---

<code>kuiper.2samp</code>	<i>2-sample Kuiper Test Function: performs Kuiper Test for two sets samples of observations</i>
---------------------------	---

---

## Description

2-sample Kuiper Test Function: performs Kuiper Test for two sets samples of observations

## Usage

```
kuiper.2samp(x, y)
```

**Arguments**

x                    an array of sample observations  
y                    the other array of sample observations

**Value**

Kuiper test statistic and p-value

**Note**

The computation of the p-value takes references from Paltani(2004) which states that the functions (in the set of four formulas) never underestimates the false positive probability however it can be a bit high when the sample size in the range of 40 to 50 a factor of 1.5 is quoted at the 1e-7 level

**References**

Kuiper, N. H. (1960). "Tests concerning random points on a circle". Proceedings of the Koninklijke Nederlandse Akademie van Wetenschappen, Series A. 63: 38-47. Paltani, S., "Searching for periods in X-ray observations using Kuiper's test. Application to the ROSAT PSPC archive", Astronomy and Astrophysics, v.240, p.789-790, 2004.

**Examples**

```
kuiper.2samp(rnorm(1e3),rnorm(1e3))
```

# Index

`kuiper.2samp`, [1](#)