

Package: libipldr (via r-universe)

May 27, 2026

Title R Bindings to the 'Rust' 'IPLD' Library

Version 0.1.1

Description Provides R bindings to decode DAG-CBOR (Directed Acyclic Graph Concise Binary Object Representation) encoded data, CIDs (Content Identifiers), and CAR (Content Addressable aRchive) files using the 'Rust' 'IPLD' (InterPlanetary Linked Data) library <<https://github.com/ipld/libipld>>. This is especially useful for working with data from 'IPFS' (InterPlanetary File System) and 'AtProto' (Bluesky) applications.

License MIT + file LICENSE

URL <https://github.com/JBGruber/libipldr>

BugReports <https://github.com/JBGruber/libipldr/issues>

Encoding UTF-8

Config/rextendr/version 0.4.2

SystemRequirements Cargo (Rust's package manager), rustc >= 1.65

Suggests testthat (>= 3.0.0), rextendr (>= 0.2.0), httr2, jsonlite, spelling

Config/testthat/edition 3

Depends R (>= 4.2)

Config/roxygen2/version 8.0.0

Language en-US

NeedsCompilation yes

Author Johannes B. Gruber [aut, cre] (ORCID: <<https://orcid.org/0000-0001-9177-1772>>), Ilya Siamionau [ctb] (Author of the original python-libipld Rust implementation)

Maintainer Johannes B. Gruber <JohannesB.Gruber@gmail.com>

Config/pak/sysreqs libclang-dev

Repository <https://cran.r-universe.dev>

Date/Publication 2026-05-27 19:40:02 UTC

RemoteUrl <https://github.com/cran/libipldr>

RemoteRef HEAD

RemoteSha cb3dae0e6b5548e3c23f38ac3cdf0b578dc4f866

Contents

libipldr-package	2
decode_car	3
decode_cid	3
decode_dag_cbor	4
decode_dag_cbor_multi	4

Index **6**

libipldr-package *libipldr: R Bindings to the 'Rust' 'IPLD' Library*

Description

Provides R bindings to decode DAG-CBOR (Directed Acyclic Graph Concise Binary Object Representation) encoded data, CIDs (Content Identifiers), and CAR (Content Addressable Archive) files using the 'Rust' 'IPLD' (InterPlanetary Linked Data) library <https://github.com/ipld/libipld>. This is especially useful for working with data from 'IPFS' (InterPlanetary File System) and 'AtProto' (Bluesky) applications.

Author(s)

Maintainer: Johannes B. Gruber <JohannesB.Grubergmail.com> ([ORCID](#))

Authors:

- Johannes B. Gruber <JohannesB.Grubergmail.com> ([ORCID](#))

Other contributors:

- Ilya Siamionau (Author of the original python-libipld Rust implementation) [contributor]

See Also

Useful links:

- <https://github.com/JBGruber/libipldr>
- Report bugs at <https://github.com/JBGruber/libipldr/issues>

decode_car	<i>Decode a Content Addressable aRchive (CAR) file</i>
------------	--

Description

This function decodes a CAR file from a raw vector, extracting the header and blocks.

Usage

```
decode_car(data)
```

Arguments

data A raw vector containing a CAR file

Value

A list with header information and decoded blocks

Examples

```
car_file <- system.file("extdata", "sample.car", package = "libipldr")
car_data <- readBin(car_file, what = "raw", n = file.size(car_file))
decode_car(car_data)
```

decode_cid	<i>Decode a Content IDentifier (CID) string</i>
------------	---

Description

This function decodes a CID string into its components (version, codec, and hash).

Usage

```
decode_cid(cid_str)
```

Arguments

cid_str A string containing a valid CID

Value

A list with CID components

Examples

```
# Decode a CID:
cid_info <- decode_cid("bafyreib775pirw4o3rz4iwdjwi3rz7q4z5t4xjyfrwnk2yukhzo2wyr4ye")
```

decode_dag_cbor *Decode DAG-CBOR encoded data to an R object*

Description

This function decodes a raw vector containing DAG-CBOR encoded data into an R object. DAG-CBOR is a deterministic subset of the CBOR format, used by IPFS and AtProto (Bluesky) for data representation.

Usage

```
decode_dag_cbor(data)
```

Arguments

data A raw vector containing DAG-CBOR encoded data

Value

An R object representing the decoded data

Examples

```
# Decode a simple DAG-CBOR map {"a": "Hello", "b": "World!"}
cbor_data <- as.raw(c(
  0xa2, 0x61, 0x61, 0x65, 0x48, 0x65, 0x6c, 0x6c, 0x6f,
  0x61, 0x62, 0x66, 0x57, 0x6f, 0x72, 0x6c, 0x64, 0x21
))
decode_dag_cbor(cbor_data)
```

decode_dag_cbor_multi *Decode multiple DAG-CBOR objects from a byte stream*

Description

This function decodes multiple consecutive DAG-CBOR objects from a single raw vector. The returned list includes a 'bytes_consumed' attribute indicating how many bytes from the beginning of the input were successfully processed. This is useful for streaming applications where you need to know where to continue reading.

Usage

```
decode_dag_cbor_multi(data)
```

Arguments

data A raw vector containing multiple DAG-CBOR encoded objects

Value

A list of R objects, each representing a decoded DAG-CBOR object

Examples

```
# Decode two consecutive DAG-CBOR objects from a single byte stream
cbor_data <- as.raw(c(
  0xa2, 0x61, 0x61, 0x65, 0x48, 0x65, 0x6c, 0x6c, 0x6f,
  0x61, 0x62, 0x66, 0x57, 0x6f, 0x72, 0x6c, 0x64, 0x21,
  0xa1, 0x61, 0x63, 0x01
))
results <- decode_dag_cbor_multi(cbor_data)
attr(results, "bytes_consumed")
```

Index

[decode_car](#), [3](#)
[decode_cid](#), [3](#)
[decode_dag_cbor](#), [4](#)
[decode_dag_cbor_multi](#), [4](#)

[libipldr \(libipldr-package\)](#), [2](#)
[libipldr-package](#), [2](#)