# Package: likelihood.contr (via r-universe)

October 28, 2026

**Type** Package

**Title** Likelihood Contribution Models for Heterogeneous Observation Types

**Version** 0.2.0

**Depends** R (>= 3.5.0)

**Description** Constructs likelihood models from heterogeneous observation types by composing named contributions. Each observation type (exact, left-censored, right-censored, interval-censored, or custom) contributes independently to the total log-likelihood, which is summed under an i.i.d. assumption. Provides contr_name() for standard R distributions and contr_fn() for user-defined contributions, composed via likelihood_contr() into objects compatible with the likelihood.model inference framework.

**License** MIT + file LICENSE

**URL** https://github.com/queelius/likelihood.contr

**BugReports** https://github.com/queelius/likelihood.contr/issues

**Encoding** UTF-8

**Imports** likelihood.model, numDeriv, stats

**Suggests** testthat (>= 3.0.0), knitr, rmarkdown

**VignetteBuilder** knitr

**RoxygenNote** 7.3.3

**Config/testthat/edition** 3

**NeedsCompilation** no

**Author** Alexander Towell [aut, cre] (ORCID: <https://orcid.org/0000-0001-6443-9897>)

**Maintainer** Alexander Towell <lex@metafunctor.com>

**Repository** https://cran.r-universe.dev

**Date/Publication** 2026-10-28 10:10:02 UTC

**RemoteUrl** https://github.com/cran/likelihood.contr

**RemoteRef** HEAD

**RemoteSha** 68602f09c8d95609626d8eb982c7242b68f7e166

# Contents

assumptions.likelihood_contr . . . 2
contr_fn . . . 3
contr_freq . . . 4
contr_name . . . 5
hess_loglik.likelihood_contr . . . 6
likelihood_contr . . . 7
loglik . . . 8
loglik.likelihood_contr . . . 9
print.likelihood_contr . . . 9
rdata.likelihood_contr . . . 10
score.likelihood_contr . . . 11

**Index** **12**

---

`assumptions.likelihood_contr`
*Assumptions for likelihood_contr*

---

## Description

Returns the character vector of model assumptions stored in the `likelihood_contr` object. The `"iid"` assumption is always included.

## Usage

```
## S3 method for class 'likelihood_contr'
assumptions(model, ...)
```

## Arguments

| | |
|---|---|
| `model` | A `likelihood_contr` model. |
| `...` | Additional arguments (currently unused). |

## Value

Character vector of assumptions.

## Examples

```
model <- likelihood_contr(
  obs_type = "status",
  exact = contr_name("exp", "exact", ob_col = "t"),
  assumptions = c("exponential distribution", "non-informative censoring")
)
assumptions(model)
```

---

`contr_fn` *Create a likelihood contribution from user-supplied functions*

---

## Description

Wraps user-provided log-likelihood, score, and Hessian functions into a `"contr"` S3 object suitable for use in `likelihood_contr()`.

## Usage

```
contr_fn(loglik, score = NULL, hess = NULL)
```

## Arguments

| | |
|---|---|
| `loglik` | A function `function(df, par, ...)` returning the log-likelihood contribution (scalar). |
| `score` | Optional function `function(df, par, ...)` returning the score vector. If `NULL`, numerical differentiation via `numDeriv::grad()` is used. |
| `hess` | Optional function `function(df, par, ...)` returning the Hessian matrix. If `NULL`, numerical differentiation via `numDeriv::hessian()` is used. |

## Details

The `loglik` function must have signature `function(df, par, ...)` and return a scalar log-likelihood value. The optional `score` and `hess` functions must have the same signature and return a numeric vector (score) or matrix (Hessian), respectively.

## Value

A `"contr"` S3 object (a list) with elements `$loglik` (function), `$score` (function or `NULL`), and `$hess` (function or `NULL`). Pass this object to `likelihood_contr()` to include it in a composed model.

## Examples

```
# Exponential exact-observation contribution
my_contr <- contr_fn(
  loglik = function(df, par, ...) {
    sum(dexp(df$x, rate = par[1], log = TRUE))
  },
  score = function(df, par, ...) {
    n <- nrow(df)
    c(rate = n / par[1] - sum(df$x))
  }
)
```

---

`contr_freq` *Weight a contribution by observed frequencies*

---

## Description

Wrap an existing contribution to work with counted observations, such as histogram bins. Each row contributes its frequency times its log-likelihood. No expanded data frame is constructed. Analytical derivatives are weighted in the same way; absent derivatives remain available through the model's numerical differentiation fallback.

## Usage

```
contr_freq(contribution, count_col)
```

## Arguments

| | |
|---|---|
| `contribution` | A contribution object created by `contr_fn()` or `contr_name()`. |
| `count_col` | Name of the column containing observed frequencies. |

## Details

Frequencies must be finite, nonnegative integers. This represents repeated independent observations, not survey weights or importance weights. The wrapped contribution must be additive over independent rows. Zero-count rows are skipped, including rows whose likelihood would otherwise be undefined. Multinomial histogram likelihoods differ from this likelihood by a constant independent of the distribution parameters. Rows must describe disjoint bins and counts must be per-bin frequencies, not cumulative histogram counts.

The generic fitting layer counts rows, not expanded observations. Do not use its default BIC or row bootstrap for frequency data: use the sum of frequencies for sample size and resample counts under the sampling design. Direct likelihood optimization is illustrated in the timeout benchmarking vignette.

## Value

A `"contr"` object usable in `likelihood_contr()`.

## Examples

```
bins <- data.frame(lo = c(0, 1, 2), hi = c(1, 2, Inf), count = c(12, 5, 3))
interval <- contr_name("exp", "interval", "lo", "hi")
counted <- contr_freq(interval, "count")
counted$loglik(bins, c(rate = 0.7))
```

---

`contr_name` *Create a likelihood contribution from a named R distribution*

---

## Description

Generates a `"contr"` object for a standard R distribution using the d<name> (PDF) and p<name> (CDF) functions. Exact observations use the PDF, right-censored use the survival function, left-censored use the CDF, and interval-censored use the CDF difference.

## Usage

```
contr_name(dist_name, type, ob_col = "x", ob_col_upper = NULL)
```

## Arguments

| | |
|---|---|
| `dist_name` | The distribution name (e.g., `"norm"`, `"weibull"`, `"exp"`). Must have both d<name> and p<name> functions available. |
| `type` | One of `"exact"`, `"right"`, `"left"`, `"interval"`. |
| `ob_col` | Name of the observation column in the data frame. For interval censoring, this is the lower bound column. |
| `ob_col_upper` | Name of the upper bound column for interval censoring. Required when `type = "interval"`. |

## Details

The log-likelihood form for each contribution type:

- `"exact"`: PDF via d<name>`(x, ..., log = TRUE)`
- `"right"`: Survival function via p<name>`(x, ..., lower.tail = FALSE, log.p = TRUE)`
- `"left"`: CDF via p<name>`(x, ..., log.p = TRUE)`
- `"interval"`: `log(F(upper) - F(lower))` via p<name>, computed in log-space for numerical stability

## Value

A `"contr"` S3 object (a list) with a `$loglik` function derived from the named distribution. The `$score` and `$hess` elements are `NULL`; numerical differentiation is used automatically when the contribution is part of a `likelihood_contr()` model.

## Examples

```
# Exact Weibull contribution
exact <- contr_name("weibull", "exact", ob_col = "t")

# Right-censored Weibull contribution
right <- contr_name("weibull", "right", ob_col = "t")

# Interval-censored normal contribution
interval <- contr_name("norm", "interval", ob_col = "lo", ob_col_upper = "hi")
```

---

# hess_loglik.likelihood_contr

*Hessian of the log-likelihood for likelihood_contr*

---

## Description

Returns a closure that splits the data frame by observation type and sums the per-type Hessian matrices. If a contribution does not provide an analytical Hessian, numerical differentiation via `numDeriv::hessian()` is used.

## Usage

```
## S3 method for class 'likelihood_contr'
hess_loglik(model, ...)
```

## Arguments

| | |
|---|---|
| `model` | A `likelihood_contr` model. |
| `...` | Additional arguments (currently unused). |

## Value

A function `function(df, par, ...)` returning the total Hessian matrix.

## Examples

```
model <- likelihood_contr(
  obs_type = "status",
  exact = contr_name("exp", "exact", ob_col = "t")
)
df <- data.frame(t = c(0.5, 1.0, 1.5), status = "exact")
hess_fn <- hess_loglik(model)
hess_fn(df, par = c(rate = 2))
```

`likelihood_contr` *Compose a likelihood model from heterogeneous observation contributions*

## Description

Constructs a `"likelihood_contr"` model by combining named `"contr"` objects. The model splits a data frame by observation type, evaluates each type's contribution, and sums the results (under the i.i.d. assumption).

## Usage

```
likelihood_contr(obs_type, ..., rdata_fn = NULL, assumptions = character(0))
```

## Arguments

| | |
|---|---|
| `obs_type` | Either a string (column name) or function for determining observation types. See Details. |
| `...` | Named `"contr"` objects, one per observation type. |
| `rdata_fn` | Optional function `function(theta, n, ...)` that generates random data from the model's data-generating process. Required by the default `likelihood.model::fim.likelihood_mod` method. |
| `assumptions` | Character vector of model assumptions. `"iid"` is always included. |

## Details

Observation type dispatch is controlled by `obs_type`:

- If a **string**, it names a column in the data frame whose values are matched against the contribution names.
- If a **function**, it is called as `obs_type(df)` and must return a character vector of the same length as `nrow(df)`.

## Value

A `"likelihood_contr"` S3 object (inheriting from `"likelihood_model"`) containing the contributions, dispatch method, and assumptions. Use `loglik()`, `score()`, `hess_loglik()` to obtain inference closures, or `generics::fit()` from the likelihood.model package to perform maximum likelihood estimation.

## Examples

```
# Weibull model with exact and right-censored observations
model <- likelihood_contr(
  obs_type = "status",
  exact = contr_name("weibull", "exact", ob_col = "t"),
  right = contr_name("weibull", "right", ob_col = "t"),
```

```
  assumptions = c("Weibull distribution", "non-informative censoring")
)
```

---

`loglik` *Re-exported generics from likelihood.model*

---

## Description

These generics are re-exported so that users can call them directly after loading `likelihood.contr`, without loading `likelihood.model` separately.

## Usage

```
loglik(model, ...)
score(model, ...)
hess_loglik(model, ...)
assumptions(model, ...)
rdata(model, ...)
```

## Arguments

| | |
|---|---|
| `model` | A likelihood model object (e.g., a `"likelihood_contr"` object). |
| `...` | Additional arguments passed to methods. |

## Details

`loglik(model, ...)` Returns a closure `function(df, par, ...)` that evaluates the total log-likelihood (a scalar).

`score(model, ...)` Returns a closure `function(df, par, ...)` that evaluates the score vector (gradient of the log-likelihood).

`hess_loglik(model, ...)` Returns a closure `function(df, par, ...)` that evaluates the Hessian matrix of the log-likelihood.

`assumptions(model, ...)` Returns a character vector of model assumptions.

`rdata(model, ...)` Returns a closure `function(theta, n, ...)` that generates a random data frame from the model.

See `loglik` for full documentation.

## Value

The return type depends on the generic; see Details. `loglik`, `score`, `hess_loglik`, and `rdata` each return a **closure** (function). `assumptions` returns a character vector.

## loglik.likelihood_contr

*Log-likelihood for likelihood_contr*

### Description

Returns a closure that splits the data frame by observation type, evaluates each contribution's log-likelihood, and sums them. The data-frame split is cached so repeated calls with the same `df` (e.g., during optimization) skip the split step.

### Usage

```
## S3 method for class 'likelihood_contr'
loglik(model, ...)
```

### Arguments

| | |
|---|---|
| `model` | A `likelihood_contr` model. |
| `...` | Additional arguments (currently unused). |

### Value

A function `function(df, par, ...)` returning the total log-likelihood (scalar).

### Examples

```
model <- likelihood_contr(
  obs_type = "status",
  exact = contr_name("exp", "exact", ob_col = "t"),
  right = contr_name("exp", "right", ob_col = "t")
)
df <- data.frame(t = c(1, 2, 3, 4), status = c("exact", "exact", "right", "right"))
ll_fn <- loglik(model)
ll_fn(df, par = c(rate = 0.5))
```

## print.likelihood_contr

*Print method for likelihood_contr*

### Description

Prints a summary of the model's observation types, dispatch method (column name or function), and assumptions.

### Usage

```
## S3 method for class 'likelihood_contr'
print(x, ...)
```

### Arguments

| | |
|---|---|
| x | A likelihood_contr model. |
| ... | Additional arguments (ignored). |

### Value

The model object, invisibly.

### Examples

```
model <- likelihood_contr(
  obs_type = "status",
  exact = contr_name("weibull", "exact", ob_col = "t"),
  right = contr_name("weibull", "right", ob_col = "t"),
  assumptions = c("Weibull distribution")
)
print(model)
```

---

## rdata.likelihood_contr

*Random data generation for likelihood_contr*

---

### Description

Returns the user-supplied rdata_fn or errors if none was provided.

### Usage

```
## S3 method for class 'likelihood_contr'
rdata(model, ...)
```

### Arguments

| | |
|---|---|
| model | A likelihood_contr model. |
| ... | Additional arguments (currently unused). |

### Value

A function function(theta, n, ...) returning a data frame.

## Examples

```
rdata_fn <- function(theta, n, ...) {
  data.frame(t = rexp(n, rate = theta[1]), status = "exact")
}
model <- likelihood_contr(
  obs_type = "status",
  exact = contr_name("exp", "exact", ob_col = "t"),
  rdata_fn = rdata_fn
)
gen <- rdata(model)
gen(theta = c(rate = 2), n = 5)
```

---

# score.likelihood_contr

*Score for likelihood_contr*

---

## Description

Returns a closure that splits the data frame by observation type and sums the per-type score vectors. If a contribution does not provide an analytical score, numerical differentiation via `numDeriv::grad()` is used.

## Usage

```
## S3 method for class 'likelihood_contr'
score(model, ...)
```

## Arguments

| | |
|---|---|
| `model` | A `likelihood_contr` model. |
| `...` | Additional arguments (currently unused). |

## Value

A function `function(df, par, ...)` returning the total score vector.

## Examples

```
model <- likelihood_contr(
  obs_type = "status",
  exact = contr_name("exp", "exact", ob_col = "t")
)
df <- data.frame(t = c(0.5, 1.0, 1.5), status = "exact")
score_fn <- score(model)
score_fn(df, par = c(rate = 2))
```

# Index


assumptions *(*loglik*)*, 8
assumptions.likelihood_contr, 2

contr_fn, 3
contr_fn(), *4*
contr_freq, 4
contr_name, 5
contr_name(), *4*

generics::fit(), *7*

hess_loglik *(*loglik*)*, 8
hess_loglik(), *7*
hess_loglik.likelihood_contr, 6

likelihood.model::fim.likelihood_model(), *7*
likelihood_contr, 7
likelihood_contr(), *3–5*
loglik, 8, *8*
loglik(), *7*
loglik.likelihood_contr, 9

numDeriv::grad(), *3*, *11*
numDeriv::hessian(), *3*, *6*

print.likelihood_contr, 9

rdata *(*loglik*)*, 8
rdata.likelihood_contr, 10

score *(*loglik*)*, 8
score(), *7*
score.likelihood_contr, 11