

# Package: localsp (via r-universe)

January 27, 2025

**Title** Local Indicator of Stratified Power

**Version** 0.1.0

**Description** Implements a local indicator of stratified power to analyze local spatial stratified association and demonstrate how spatial stratified association changes spatially and in local regions, as outlined in Hu et al. (2024)  
[<doi:10.1080/13658816.2024.2437811>](https://doi.org/10.1080/13658816.2024.2437811).

**License** GPL-3

**Encoding** UTF-8

**RoxygenNote** 7.3.2

**URL** <https://ausgis.github.io/localsp/>,  
<https://github.com/ausgis/localsp>

**BugReports** <https://github.com/ausgis/localsp/issues>

**Depends** R (>= 4.1.0)

**Imports** dplyr, gdverse, purrr, sdsfun, sf, tibble, tidyverse

**Suggests** automap, gstat, knitr, readr, rmarkdown

**VignetteBuilder** knitr

**NeedsCompilation** no

**Author** Jiao Hu [aut, cph] (<<https://orcid.org/0000-0002-9644-9763>>),  
Wenbo Lv [aut, cre] (<<https://orcid.org/0009-0002-6003-3800>>),  
Yongze Song [aut] (<<https://orcid.org/0000-0003-3420-9622>>)

**Maintainer** Wenbo Lv <lyu.geosocial@gmail.com>

**Repository** CRAN

**Date/Publication** 2025-01-27 18:20:08 UTC

**Config/pak/sysreqs** libfontconfig1-dev libfreetype6-dev libgdal-dev  
gdal-bin libgeos-dev make libicu-dev libpng-dev libssl-dev  
libproj-dev python3 libssqlite3-dev libudunits2-dev

## Contents

lisp . . . . .	2
<b>Index</b>	<b>4</b>

---

lisp	<i>local indicator of stratified power</i>
------	--

---

### Description

local indicator of stratified power

### Usage

```
lisp(
  formula,
  data,
  threshold,
  distmat,
  discvar = NULL,
  discnum = 3:8,
  discmethod = c("sd", "equal", "geometric", "quantile", "natural"),
  cores = 1,
  ...
)
```

### Arguments

formula	A formula.
data	The observation data.
threshold	The distance threshold employed to select "local" data.
distmat	The distance matrices.
discvar	(optional) Name of continuous variable columns that need to be discretized. Noted that when formula has discvar, data must have these columns. By default, all independent variables are used as discvar.
discnum	(optional) A vector of number of classes for discretization. Default is 3:8.
discmethod	(optional) A vector of methods for discretization, default is using c("sd", "equal", "geometric", "quantile").
cores	(optional) Positive integer (default is 1). When cores are greater than 1, use multi-core parallel computing.
...	(optional) Other arguments passed to gdverse::gd_optunidisc(). A useful parameter is seed, which is used to set the random number seed.

### Value

A tibble.

**Examples**

```
gtc = readr::read_csv(system.file("extdata/gtc.csv", package = "localsp"))
gtc

# Sample 100 observations from the original data to save runtime;
# This is unnecessary in practice;
set.seed(42)
gtc1 = gtc[sample.int(nrow(gtc), size = 100),]
distmat = as.matrix(dist(gtc1[, c("X", "Y")]))
gtc1 = gtc1[, -c(1,2)]
gtc1

# Use 2 cores for parallel computing;
# Increase cores in practice to speed up;
lisp(GTC ~ ., data = gtc1, threshold = 4.2349, distmat = distmat,
discnum = 3:5, discmethod = "quantile", cores = 2)
```

# **Index**

[lisp, 2](#)