Package: lpirfs (via r-universe)

October 25, 2026

Type Package

Title Local Projections Impulse Response Functions

Version 0.2.5

Maintainer Philipp Adämmer <philipp.adaemmer@uni-greifswald.de>

BugReports https://github.com/adaemmerp/lpirfs/issues

Description Provides functions to estimate and visualize linear as well as nonlinear impulse responses based on local projections by Jordà (2005) <doi:10.1257/0002828053828518>. The methods and the package are explained in detail in Adämmer (2019) <doi:10.32614/RJ-2019-052>.

License GPL (>= 2)

Depends R (>= 3.1.2)

Encoding UTF-8

LazyData true

NeedsCompilation yes

Imports doParallel(>= 1.0.15), dplyr(>= 1.0.0), foreach(>= 1.5.0), ggplot2(>= 3.3.0), gridExtra(>= 2.3), lmtest(>= 0.9-36), plm(>= 2.2-3), sandwich(>= 2.5-1), Rcpp(>= 1.0.4.6)

RoxygenNote 7.3.1

LinkingTo Rcpp, RcppArmadillo

Suggests testthat (>= 3.0.0), AER(>= 1.2-12), readxl, knitr, ggpubr, rmarkdown, zoo, vars

VignetteBuilder knitr

Config/testthat/edition 3

Author Philipp Adämmer [aut, cre] (ORCID: <https://orcid.org/0000-0003-3770-0097>), James P. LeSage [ctb], Mehmet Balcilar [ctb], Jon Danielsson [ctb]

Repository https://cran.r-universe.dev

Date/Publication 2025-10-01 13:20:02 UTC

RemoteUrl https://github.com/cran/lpirfs

RemoteRef HEAD

RemoteSha c96c24266491803f3b3b487070d785ab2c71c139

Contents

lpirfs-package . . . 2
ag_data . . . 3
get_robust_cov_panel . . . 4
hp_filter . . . 4
interest_rules_var_data . . . 6
lp_lin . . . 6
lp_lin_iv . . . 10
lp_lin_panel . . . 15
lp_nl . . . 21
lp_nl_iv . . . 26
lp_nl_panel . . . 31
lpirfs_obj-methods-base . . . 37
monetary_var_data . . . 37
plot.lpirfs_lin_iv_obj . . . 38
plot.lpirfs_lin_obj . . . 39
plot.lpirfs_lin_panel_obj . . . 39
plot.lpirfs_nl_iv_obj . . . 40
plot.lpirfs_nl_obj . . . 40
plot.lpirfs_nl_panel_obj . . . 41
plot_lin . . . 41
plot_nl . . . 42
summary.lpirfs_lin_iv_obj . . . 42
summary.lpirfs_lin_obj . . . 43
summary.lpirfs_lin_panel_obj . . . 43
summary.lpirfs_nl_iv_obj . . . 44
summary.lpirfs_nl_obj . . . 44
summary.lpirfs_nl_panel_obj . . . 45

Index **46**

`lpirfs-package` *Local Projection Impulse Response Functions*

Description

lpirfs provides functions to estimate and plot linear as well as nonlinear impulse responses based on local projections by Jordà (2005) <doi:10.1257/0002828053828518>. The methods and the package are explained in detail in Adämmer (2019) <doi:10.32614/RJ-2019-052>. Please cite the paper when using the package.

Author(s)

Philipp Adämmer

See Also

Useful links:

- Report bugs at https://github.com/adaemmerp/lpirfs/issues

`ag_data` *Data to estimate fiscal multipliers*

Description

A tibble, containing data to estimate fiscal multipliers. This data was originally used by Auerbach and Gorodnichenko (2012). Sarah and Zubairy (2018) use this data to re-evaluate their results with local projections.

Usage

```
ag_data
```

Format

A tibble with 248 quarterly observations (rows) and 7 variables (columns):

Year Year of observation.

Quarter Quarter of observation.

Gov Logs of real government (federal, state, and local) purchases (consumption and investment).

Tax Logs of real government receipts of direct and indirect taxes net of transfers to businesses and individuals.

GDP Logs of real gross domestic product.

GDP_MA 7-quarter moving average growth rate of GDP.

Gov_shock_mean Identified government spending shock. For details see Supplementary Appendix of Ramey and Zubairy (2018).

Sample: 1948:IV - 2008:IV

Source

doi:10.1086/696277

References

Auerbach, A. J., and Gorodnichenko Y. (2012). "Measuring the Output Responses to Fiscal Policy." *American Economic Journal: Economic Policy*, 4 (2): 1-27.

Jordà, Ò. (2005) "Estimation and Inference of Impulse Responses by Local Projections." *American Economic Review*, 95 (1): 161-182.

Ramey, V.A., Zubairy, S. (2018). "Government Spending Multipliers in Good Times and in Bad: Evidence from US Historical Data." *Journal of Political Economy*, 126(2): 850 - 901.

`get_robust_cov_panel` *Function to get robust covariance matrix for panel data*

Description

Function to get robust covariance matrix for panel data

Usage

```
get_robust_cov_panel(panel_results, specs)
```

Arguments

`panel_results`	Plm object from estimation
`specs`	List with specifications

Value

Object with robust covariance matrix

`hp_filter` *Decompose a times series via the Hodrick-Prescott filter*

Description

Estimate cyclical and trend component with filter by Hodrick and Prescott (1997). The function is based on the function *hpfilter* from the archived *mFilter*-package.

Usage

```
hp_filter(x, lambda)
```

Arguments

`x`	One column matrix with numeric values.
`lambda`	Numeric value.

Value

A list. The first element contains the cyclical component and the second element the trend component.

Author(s)

Philipp Adämmer

References

Hodrick, R.J., and Prescott, E. C. (1997). "Postwar U.S. Business Cycles: An Empirical Investigation." *Journal of Money, Credit and Banking*, 29(1), 1-16.

Ravn, M.O., Uhlig, H. (2002). "On Adjusting the Hodrick-Prescott Filter for the Frequency of Observations." *Review of Economics and Statistics*, 84(2), 371-376.

Examples

```
library(lpirfs)


# Decompose the Federal Funds Rate
 data_set     <- as.matrix(interest_rules_var_data$FF)
 hp_results   <- hp_filter(data_set, 1600)

# Extract results and save as data.frame
 hp_cyc    <- as.data.frame(hp_results[[1]])
 hp_trend  <- as.data.frame(hp_results[[2]])

# Make data.frames for plots
 cyc_df     <- data.frame(yy = hp_cyc$V1,   xx = seq(as.Date('1955-01-01'),
                          as.Date('2003-01-01') , "quarter"))
 trend_df   <- data.frame(yy = hp_trend$V1, xx = seq(as.Date('1955-01-01'),
                          as.Date('2003-01-01') , "quarter"))

# Make plots
 library(ggplot2)

# Plot cyclical part
 ggplot(data = cyc_df) +
 geom_line(aes(y = yy, x = xx))

# Plot trend component
 ggplot(trend_df) +
 geom_line(aes(y = yy, x = xx))
```

interest_rules_var_data

Data to estimate the effects of interest rate rules for monetary policy

Description

A tibble, containing data to estimate the effects of interest rate rules for monetary policy. The data are used by Jordà (2005).

Usage

```
interest_rules_var_data
```

Format

A tibble with 193 quarterly observations (rows) and 3 variables (columns):

GDP_gap Percentage difference between real GDP and potential GDP (Congressional Budget Office).

Infl Inflation: Percentage change in the GDP, chain weighted price index at annual rate.

FF Federal funds rate: quarterly average of daily rates.

Sample: 1955:I - 2003:I

Source

https://www.aeaweb.org/articles?id=10.1257/0002828053828518

References

Jordà, Ò. (2005) "Estimation and Inference of Impulse Responses by Local Projections." *American Economic Review*, 95 (1): 161-182.

lp_lin

Compute linear impulse responses

Description

Compute linear impulse responses with local projections by Jordà (2005).

Usage

```
lp_lin(
  endog_data,
  lags_endog_lin = NULL,
  lags_criterion = NaN,
  max_lags = NaN,
  trend = NULL,
  shock_type = NULL,
  confint = NULL,
  use_nw = TRUE,
  nw_lag = NULL,
  nw_prewhite = FALSE,
  adjust_se = FALSE,
  hor = NULL,
  exog_data = NULL,
  lags_exog = NULL,
  contemp_data = NULL,
  num_cores = 1
)
```

Arguments

endog_data	A data.frame, containing the endogenous variables for the VAR. The Cholesky decomposition is based on the column order.
lags_endog_lin	NaN or integer. NaN if lag length criterion is used. Integer for number of lags for *endog_data*.
lags_criterion	NaN or character. NaN (default) means that the number of lags has to be given at *lags_endog_lin*. The character specifies the lag length criterion ('AICc', 'AIC' or 'BIC').
max_lags	NaN or integer. Maximum number of lags if *lags_criterion* is given. NaN (default) otherwise.
trend	Integer. No trend = 0 , include trend = 1, include trend and quadratic trend = 2.
shock_type	Integer. Standard deviation shock = 0, unit shock = 1.
confint	Double. Width of confidence bands. 68% = 1; 90% = 1.65; 95% = 1.96.
use_nw	Boolean. Use Newey-West (1987) standard errors for impulse responses? TRUE (default) or FALSE.
nw_lag	Integer. Specifies the maximum lag with positive weight for the Newey-West estimator. If set to NULL (default), the lag increases with with the number of horizon.
nw_prewhite	Boolean. Should the estimators be pre-whitened? TRUE or FALSE (default).
adjust_se	Boolen. Should a finite sample adjsutment be made to the covariance matrix estimators? TRUE or FALSE (default).
hor	Integer. Number of horizons for impulse responses.

`exog_data` A data.frame, containing exogenous variables for the VAR. The row length has to be the same as *endog_data*. Lag lengths for exogenous variables have to be given and will not be determined via a lag length criterion.

`lags_exog` NULL or Integer. Integer for the number of lags for the exogenous data. The value cannot be 0. If you want to to include exogenous data with contemporaneous impact use *contemp_data*.

`contemp_data` A data.frame, containing exogenous data with contemporaneous impact. This data will not be lagged. The row length has to be the same as *endog_data*.

`num_cores` NULL or Integer. The number of cores to use for the estimation. If NULL, the function will use the maximum number of cores minus one.

Value

A list containing:

`irf_lin_mean` A three 3D array, containing all impulse responses for all endogenous variables. The last dimension denotes the shock variable. The row in each matrix gives the responses of the *ith* variable, ordered as in endog_data. The columns denote the horizons. For example, if *results_lin* contains the list with results, results_lin$irf_lin_mean[, , 1] returns a KXH matrix, where K is the number of variables and H the number of horizons. '1' is the shock variable, corresponding to the first variable in *endog_data*.

`irf_lin_low` A three 3D array containing all lower confidence bands of the responses, based on robust standard errors by Newey and West (1987). Properties are equal to irf_lin_mean.

`irf_lin_up` A three 3D array containing all upper confidence bands of the responses, based on robust standard errors by Newey and West (1987). Properties are equal to *irf_lin_mean*.

`diagnostic_list`
A list OLS diagnostics. To see everything you can simply use summary() or results$diagnostic_list. The first entry the shock variable. The rows of each shown matrix then denotes the endogenous variable that reacts to the shock.

`specs` A list with properties of *endog_data* for the plot function. It also contains lagged data (y_lin and x_lin) used for the irf estimations, and the selected lag lengths when an information criterion has been used.

Author(s)

Philipp Adämmer

References

Akaike, H. (1974). "A new look at the statistical model identification", *IEEE Transactions on Automatic Control*, 19 (6): 716–723.

Hurvich, C. M., and Tsai, C.-L. (1989), "Regression and time series model selection in small samples", *Biometrika*, 76(2): 297–307

Jordà, Ò. (2005). "Estimation and Inference of Impulse Responses by Local Projections." *American Economic Review*, 95 (1): 161-182.

Newey, W.K., and West, K.D. (1987). "A Simple, Positive-Definite, Heteroskedasticity and Autocorrelation Consistent Covariance Matrix." *Econometrica*, 55: 703–708.

Schwarz, Gideon E. (1978). "Estimating the dimension of a model", *Annals of Statistics*, 6 (2): 461–464.

See Also

https://adaemmerp.github.io/lpirfs/README_docs.html

Examples

```
          ## Example without exogenous variables

# Load package
  library(lpirfs)

# Load (endogenous) data
  endog_data <- interest_rules_var_data

# Estimate linear model
  results_lin <- lp_lin(endog_data,
                            lags_endog_lin = 4,
                            trend          = 0,
                            shock_type     = 1,
                            confint        = 1.96,
                            hor            = 12)

# Show all impule responses
# Compare with Figure 5 in Jordà (2005)
 plot(results_lin)

# Make individual plots
 linear_plots <- plot_lin(results_lin)

# Show single plots
 # * The first element of 'linear_plots' shows the response of the first
 #   variable (GDP_gap) to a shock in the first variable (GDP_gap).
 # * The second element of 'linear_plots' shows the response of the first
 #   variable (GDP_gap) to a shock in the second variable (inflation).
 # * ...

  linear_plots[[1]]
  linear_plots[[2]]


# Show diagnostics. The first element correponds to the first shock variable.
 summary(results_lin)


                    ## Example with exogenous variables ##
```

```
# Load (endogenous) data
 endog_data <- interest_rules_var_data

# Create exogenous data and data with contemporaneous impact (for illustration purposes only)
 exog_data   <- endog_data$GDP_gap*endog_data$Infl*endog_data$FF + rnorm(dim(endog_data)[1])
 contemp_data <- endog_data$GDP_gap*endog_data$Infl*endog_data$FF + rnorm(dim(endog_data)[1])

# Exogenous data has to be a data.frame
 exog_data    <- data.frame(xx = exog_data )
 contemp_data <- data.frame(cc =  contemp_data)

# Estimate linear model
  results_lin <- lp_lin(endog_data,
                                lags_endog_lin = 4,
                                trend          = 0,
                                shock_type     = 1,
                                confint        = 1.96,
                                hor            = 12,
                                exog_data      = exog_data,
                                lags_exog      = 4,
                                contemp_data   = contemp_data)

# Show all impulse responses
 plot(results_lin)

# Show diagnostics. The first element correponds to the first shock variable.
 summary(results_lin)
```

`lp_lin_iv` *Compute linear impulse responses with identified shock and/or with 2SLS*

Description

Compute linear impulse responses with identified shock and/or with 2SLS.

Usage

```
lp_lin_iv(
  endog_data,
  shock = NULL,
  cumul_mult = FALSE,
  instr = NULL,
  use_twosls = FALSE,
  instrum = NULL,
  lags_endog_lin = NULL,
  exog_data = NULL,
```

```
  lags_exog = NULL,
  contemp_data = NULL,
  lags_criterion = NaN,
  max_lags = NaN,
  trend = NULL,
  confint = NULL,
  use_nw = TRUE,
  nw_lag = NULL,
  nw_prewhite = FALSE,
  adjust_se = FALSE,
  hor = NULL,
  num_cores = 1
)
```

Arguments

endog_data	A data.frame, containing the values of the dependent variable(s).
shock	A one column data.frame, including the variable to shock with. The row length has to be the same as *endog_data*. When *use_twosls* = *TRUE*, this variable will be approximated/regressed on the instrument variable(s) given in *instrum*.
cumul_mult	Boolean. Estimate cumulative multipliers? TRUE or FALSE (default). If TRUE, cumulative responses are estimated via: $$y_{(t+h)} - y_{(t-1)},$$ where h = 0,..., H-1. This option is only available for *lags_criterion* = *NaN*.
instr	Deprecated input name. Use *shock* instead. See *shock* for details.
use_twosls	Boolean. Use two stage least squares? TRUE or FALSE (default).
instrum	A data.frame, containing the instrument(s) to use for 2SLS. This instrument will be used for the variable in *shock*.
lags_endog_lin	NaN or integer. NaN if lags are chosen by a lag length criterion. Integer for number of lags for *endog_data*.
exog_data	A data.frame, containing exogenous variables. The row length has to be the same as *endog_data*. Lag lengths for exogenous variables have to be given and will not be determined via a lag length criterion.
lags_exog	NULL or Integer. Integer for the number of lags for the exogenous data. The value cannot be 0. If you want to to include exogenous data with contemporaneous impact use 'contemp_data'.
contemp_data	A data.frame, containing exogenous data with contemporaneous impact. The row length has to be the same as *endog_data*.
lags_criterion	NaN or character. NaN means that the number of lags will be given at *lags_endog_lin*. Possible lag length criteria are 'AICc', 'AIC' or 'BIC'. Note that when *use_twosls* = *TRUE*, the lag lengths are chosen based on normal OLS regressions, without using the instruments.
max_lags	NaN or integer. Maximum number of lags if *lags_criterion* is a character denoting the lag length criterion. NaN otherwise.

trend	Integer. No trend = 0 , include trend = 1, include trend and quadratic trend = 2.
confint	Double. Width of confidence bands. 68% = 1; 90% = 1.65; 95% = 1.96.
use_nw	Boolean. Use Newey-West (1987) standard errors for impulse responses? TRUE (default) or FALSE.
nw_lag	Integer. Specifies the maximum lag with positive weight for the Newey-West estimator. If set to NULL (default), the lag increases with with the number of horizon.
nw_prewhite	Boolean. Should the estimators be pre-whitened? TRUE of FALSE (default).
adjust_se	Boolen. Should a finite sample adjsutment be made to the covariance matrix estimators? TRUE or FALSE (default).
hor	Integer. Number of horizons for impulse responses.
num_cores	NULL or Integer. The number of cores to use for the estimation. If NULL, the function will use the maximum number of cores minus one.

Value

A list containing:

irf_lin_mean	A matrix, containing the impulse responses. The row in each matrix denotes the response of the *ith* variable to the shock. The columns are the horizons.
irf_lin_low	A matrix, containing all lower confidence bands of the impulse responses, based on robust standard errors by Newey and West (1987). Properties are equal to *irf_lin_mean*.
irf_lin_up	A matrix, containing all upper confidence bands of the impulse responses, based on robust standard errors by Newey and West (1987). Properties are equal to *irf_lin_mean*.
specs	A list with properties of *endog_data* for the plot function. It also contains lagged data (y_lin and x_lin) used for the estimations of the impulse responses, and the selected lag lengths when an information criterion has been used.

Author(s)

Philipp Adämmer

References

Akaike, H. (1974). "A new look at the statistical model identification", *IEEE Transactions on Automatic Control*, 19 (6): 716–723.

Auerbach, A. J., and Gorodnichenko, Y. (2012). "Measuring the Output Responses to Fiscal Policy." *American Economic Journal: Economic Policy*, 4 (2): 1-27.

Blanchard, O., and Perotti, R. (2002). "An Empirical Characterization of the Dynamic Effects of Changes in Government Spending and Taxes on Output." *Quarterly Journal of Economics*, 117(4): 1329–1368.

Hurvich, C. M., and Tsai, C.-L. (1989), "Regression and time series model selection in small samples", *Biometrika*, 76(2): 297–307

Jordà, Ò. (2005). "Estimation and Inference of Impulse Responses by Local Projections." *American Economic Review*, 95 (1): 161-182.

Jordà, Ò, Schularick, M., Taylor, A.M. (2015), "Betting the house", *Journal of International Economics*, 96, S2-S18.

Newey, W.K., and West, K.D. (1987). "A Simple, Positive-Definite, Heteroskedasticity and Autocorrelation Consistent Covariance Matrix." *Econometrica*, 55: 703–708.

Ramey, V.A., and Zubairy, S. (2018). "Government Spending Multipliers in Good Times and in Bad: Evidence from US Historical Data." *Journal of Political Economy*, 126(2): 850 - 901.

Schwarz, Gideon E. (1978). "Estimating the dimension of a model", *Annals of Statistics*, 6 (2): 461–464.

See Also

https://adaemmerp.github.io/lpirfs/README_docs.html

Examples

```
# This example replicates a result from the Supplementary Appendix
# by Ramey and Zubairy (2018) (RZ-18)

# Load data
 ag_data       <- ag_data
 sample_start  <- 7
 sample_end    <- dim(ag_data)[1]

# Endogenous data
 endog_data    <- ag_data[sample_start:sample_end,3:5]

# Variable to shock with. Here government spending due to
# Blanchard and Perotti (2002) framework
 shock         <- ag_data[sample_start:sample_end, 3]

# Estimate linear model
 results_lin_iv <- lp_lin_iv(endog_data,
                             lags_endog_lin = 4,
                             shock          = shock,
                             trend          = 0,
                             confint        = 1.96,
                             hor            = 20)

# Show all impulse responses
 plot(results_lin_iv)

# Make and save plots
 iv_lin_plots    <- plot_lin(results_lin_iv)

# * The first element of 'iv_lin_plots' shows the response of the first
#   variable (Gov) to the  shock (Gov).
# * The second element of 'iv_lin_plots' shows the response of the second
```

```
#   variable (Tax) to the shock (Gov).
# * ...

# This plot replicates the left plot in the mid-panel of Figure 12 in the
# Supplementary Appendix by RZ-18.
 iv_lin_plots[[1]]


# Show diagnostics. The first element shows the reaction of the first given endogenous variable.
 summary(results_lin_iv)


## Add lags of the identified shock ##

# Endogenous data but now exclude government spending
 endog_data    <- ag_data[sample_start:sample_end, 4:5]

# Variable to shock with (government spending)
 shock         <- ag_data[sample_start:sample_end, 3]

# Add the shock variable to exogenous data
 exog_data     <- shock

# Estimate linear model with lagged shock variable
 results_lin_iv <- lp_lin_iv(endog_data,
                              lags_endog_lin = 4,
                              shock          = shock,
                              exog_data      = exog_data,
                              lags_exog      = 2,
                              trend          = 0,
                              confint        = 1.96,
                              hor            = 20)


# Show all responses
 plot(results_lin_iv)

# Show diagnostics. The first element shows the reaction of the first endogenous variable.
 summary(results_lin_iv)


################################################################################
#####                          Use 2SLS                                 #########
################################################################################

# Set seed
 set.seed(007)

# Load data
 ag_data       <- ag_data
 sample_start  <- 7
 sample_end    <- dim(ag_data)[1]
```

```
# Endogenous data
 endog_data    <- ag_data[sample_start:sample_end,3:5]

# Variable to shock with (government spending)
 shock         <- ag_data[sample_start:sample_end, 3]

# Generate instrument variable that is correlated with government spending
 instrum       <- as.data.frame(0.9*shock$Gov + rnorm(length(shock$Gov), 0, 0.02) )

# Estimate linear model via 2SLS
 results_lin_iv <- lp_lin_iv(endog_data,
                             lags_endog_lin = 4,
                             shock          = shock,
                             instrum        = instrum,
                             use_twosls     = TRUE,
                             trend          = 0,
                             confint        = 1.96,
                             hor            = 20)

# Show all responses
 plot(results_lin_iv)
```

`lp_lin_panel` *Compute linear impulse responses with local projections for panel data*

Description

This function estimates impulse responses with local projections for panel data, either with an identified shock or by an instrument variable approach.

Usage

```
lp_lin_panel(
  data_set = NULL,
  data_sample = "Full",
  endog_data = NULL,
  cumul_mult = TRUE,
  shock = NULL,
  diff_shock = TRUE,
  iv_reg = FALSE,
  instrum = NULL,
  panel_model = "within",
  panel_effect = "individual",
  robust_cov = NULL,
```

```
  robust_method = NULL,
  robust_type = NULL,
  robust_cluster = NULL,
  robust_maxlag = NULL,
  use_gmm = FALSE,
  gmm_model = "onestep",
  gmm_effect = "twoways",
  gmm_transformation = "d",
  c_exog_data = NULL,
  l_exog_data = NULL,
  lags_exog_data = NaN,
  c_fd_exog_data = NULL,
  l_fd_exog_data = NULL,
  lags_fd_exog_data = NaN,
  confint = NULL,
  hor = NULL
)
```

Arguments

data_set	A data.frame, containing the panel data set. The first column has to be the variable denoting the cross section. The second column has to be the variable denoting the time section.
data_sample	Character or numeric. To use the full sample set value to "Full" (default). To estimate a subset, you have to provide a sequence of dates. This sequence has to be in the same format as the second column (time-section).
endog_data	Character. The column name of the endogenous variable. You can only provide one endogenous variable at a time.
cumul_mult	Boolean. Estimate cumulative multipliers? TRUE (default) or FALSE. If TRUE, cumulative responses are estimated via: $$y_{(t+h)} - y_{(t-1)},$$ where h = 0,..., H-1.
shock	Character. The column name of the variable to shock with.
diff_shock	Boolean. Take first differences of the shock variable? TRUE (default) or FALSE. Note that when using this option both shock and instrument are used in first differences
iv_reg	Boolean. Use instrument variable approach? TRUE or FALSE.
instrum	NULL or Character. The name(s) of the instrument variable(s) if iv_reg = TRUE.
panel_model	Character. Type of panel model. The default is "within" (fixed effects). Other options are "random", "ht", "between", "pooling" or "fd". See vignette of the plm package for details.
panel_effect	Character. The effects introduced in the model. Options are "individual" (default), "time", "twoways", or "nested". See the vignette of the plm-package for details.

robust_cov	NULL or Character. The character specifies the method how to estimate robust standard errors: Options are "vcovBK", "vcovDC", "vcovG", "vcovHC", "vcovNW", "vcovSCC". For these options see vignette of plm package. Another option is "Vcxt". For details see Miller (2017) If "use_gmm = TRUE", this option has to be NULL.
robust_method	NULL (default) or Character. The character is an option when robust_cov = "vcovHC". See vignette of the plm package for details.
robust_type	NULL (default) or Character. The character is an option when robust_cov = "vcovBK", "vcovDC", "vcovHC", "vcovNW" or "vcovSCC". See vignette of the plm package for details.
robust_cluster	NULL (default) or Character. The character is an option when robust_cov = "vcovBK", "vcovG" or "vcovHC". See vignette of the plm package for details.
robust_maxlag	NULL (default) or Character. The character is an option when robust_cov = "vcovNW" or "vcovSCC". See vignette of the plm package for details.
use_gmm	Boolean. Use GMM for estimation? TRUE or FALSE (default). See vignette of plm package for details. If TRUE, the option "robust_cov" has to be set to NULL.
gmm_model	Character. Either "onestep" (default) or "twosteps". See vignette of the plm package for details.
gmm_effect	Character. The effects introduced in the model: "twoways" (default) or "individual". See vignette of the plm-package for details.
gmm_transformation	Character. Either "d" (default) for the "difference GMM" model or "ld" for the "system GMM". See vignette of the plm package for details.
c_exog_data	NULL or Character. Name(s) of the exogenous variable(s) with contemporaneous impact.
l_exog_data	NULL or Character. Name(s) of the exogenous variable(s) with lagged impact.
lags_exog_data	Integer. Lag length for the exogenous variable(s) with lagged impact.
c_fd_exog_data	NULL or Character. Name(s) of the exogenous variable(s) with contemporaneous impact of first differences.
l_fd_exog_data	NULL or Character. Name(s) of exogenous variable(s) with lagged impact of first differences.
lags_fd_exog_data	NaN or Integer. Number of lags for variable(s) with impact of first differences.
confint	Double. Width of confidence bands. 68% = 1; 90% = 1.65; 95% = 1.96.
hor	Integer. Number of horizons for impulse responses.

Value

A list containing:

irf_lin_mean	A matrix, containing the impulse responses. The columns are the horizons.
irf_lin_low	A matrix, containing all lower confidence bands. The columns are the horizons.
irf_lin_up	A matrix, containing all upper confidence bands. The columns are the horizons.

reg_outputs	Full regression output (plm object) for each horizon.
reg_summaries	Summary of regression output for each horizon. In case of robust covariance estimators, this only includes the t-tests.
xy_data_sets	Data sets with endogenous and exogenous variables for each horizon.
specs	A list with data properties for e.g. the plot function.

Author(s)

Philipp Adämmer

References

Croissant, Y., Millo, G. (2008). "Panel Data Econometrics in R: The plm Package." *Journal of Statistical Software*, 27(2), 1-43. doi: 10.18637/jss.v027.i02.

Jordà, Ò. (2005). "Estimation and Inference of Impulse Responses by Local Projections." *American Economic Review*, 95 (1): 161-182.

Jordà, Ò., Schualrick, M., Taylor, A.M. (2018). "Large and State-Dependent Effects of Quasi-Random Monetary Experiments", *NBER* working paper 23074, *FRBSF* working paper 2017-02.

Millo G (2017). "Robust Standard Error Estimators for Panel Models: A Unifying Approach." *Journal of Statistical Software*, 82(3), 1-27. doi: 10.18637/jss.v082.i03.

Examples

```
#--- Info
# This example is based on a STATA code that has been provided on
# Òscar Jordà's website (https://sites.google.com/site/oscarjorda/home/local-projections)
# It estimates impulse reponses of the ratio of (mortgage lending/GDP) to a
# +1% change in the short term interest rate

#--- Get data
# Go to the website of the 'The MacroFinance and MacroHistory Lab'
# Download the Excel-Sheet of the 'Jordà-Schularick-Taylor Macrohistory Database':
# URL: https://www.macrohistory.net/database/
# Then uncomment and run the code below...


#--- Code

## Load libraries to download and read excel file from the website
#  library(lpirfs)
#  library(readxl)
#  library(dplyr)
#
# Load JST Macrohistory Database
#  jst_data <- read_excel("JSTdatasetR5.xlsx", sheet = "Data")
#
## Choose years <= 2013. Swap the first two columns so that 'country' is the
## first (cross section) and 'year' the second (time section) column
```

```
#   jst_data <- jst_data                     %>%
#               dplyr::filter(year <= 2013)  %>%
#               dplyr::select(country, year, everything())
#
## Prepare variables
#  data_set <- jst_data %>%
#                 mutate(stir     = stir)                         %>%
#                 mutate(mortgdp  = 100*(tmort/gdp))              %>%
#                 mutate(hpreal   = hpnom/cpi)                    %>%
#                 group_by(country)                               %>%
#                 mutate(hpreal   = hpreal/hpreal[year==1990][1]) %>%
#                 mutate(lhpreal  = log(hpreal))                  %>%
#
#                 mutate(lhpy     = lhpreal - log(rgdppc))        %>%
#                 mutate(lhpy     = lhpy - lhpy[year == 1990][1]) %>%
#                 mutate(lhpreal  = 100*lhpreal)                  %>%
#                 mutate(lhpy     = 100*lhpy)                     %>%
#                 ungroup()                                       %>%
#
#                 mutate(lrgdp    = 100*log(rgdppc))              %>%
#                 mutate(lcpi     = 100*log(cpi))                %>%
#                 mutate(lriy     = 100*log(iy*rgdppc))           %>%
#                 mutate(cay      = 100*(ca/gdp))                 %>%
#                 mutate(tnmort   = tloans - tmort)               %>%
#                 mutate(nmortgdp = 100*(tnmort/gdp))             %>%
#                 dplyr::select(country, year, mortgdp, stir, ltrate,
#                               lhpy, lrgdp, lcpi, lriy, cay, nmortgdp)
#
#
## Use data from 1870 to 2013 and exclude observations during WWI and WWII
#   data_sample <-   seq(1870, 2013)[!(seq(1870, 2016) %in%
#                                    c(seq(1914, 1918), seq(1939, 1947)))]
#
## Estimate panel model
# results_panel <-  lp_lin_panel(data_set          = data_set,
#                                data_sample       = data_sample,
#                                endog_data        = "mortgdp",
#                                cumul_mult        = TRUE,
#
#                                shock             = "stir",
#                                diff_shock        = TRUE,
#                                panel_model       = "within",
#                                panel_effect      = "individual",
#                                robust_cov        = "vcovSCC",
#
#                                c_exog_data       = "cay",
#                                l_exog_data       = "cay",
#                                lags_exog_data    = 2,
#                               c_fd_exog_data    = colnames(data_set)[c(seq(4,9),11)],
#                               l_fd_exog_data    = colnames(data_set)[c(seq(3,9),11)],
#                                lags_fd_exog_data = 2,
#
#                                confint           = 1.67,
```

```
#                                 hor               = 5)
#
## Plot irfs
#   plot(results_panel)
#
#
## Simulate and add instrument to data_set
#   set.seed(123)
#   data_set   <- data_set %>%
#                 group_by(country) %>%
#           mutate(instrument = 0.8*stir + rnorm(length(stir), 0, sd(na.omit(stir))/10)) %>%
#                 ungroup()
#
#
## Estimate panel model with iv approach
#  results_panel <-  lp_lin_panel(data_set          = data_set,
#                                 data_sample       = data_sample,
#                                 endog_data        = "mortgdp",
#                                 cumul_mult        = TRUE,
#
#                                 shock             = "stir",
#                                 diff_shock        = TRUE,
#                                 iv_reg            = TRUE,
#                                 instrum           = "instrument",
#                                 panel_model       = "within",
#                                 panel_effect      = "individual",
#                                 robust_cov        = "vcovSCC",
#
#                                 c_exog_data       = "cay",
#                                 l_exog_data       = "cay",
#                                 lags_exog_data    = 2,
#                                c_fd_exog_data    = colnames(data_set)[c(seq(4,9),11)],
#                                l_fd_exog_data    = colnames(data_set)[c(seq(3,9),11)],
#                                 lags_fd_exog_data = 2,
#
#                                 confint           = 1.67,
#                                 hor               = 5)
#
## Create and plot irfs
#   plot(results_panel)
#
#
################################################################################
###                            Use GMM                                       ###
################################################################################
#
#
## Use a much smaller sample to have fewer T than N
# data_sample <-   seq(2000, 2012)
#
## Estimate panel model with gmm
## This example (please uncomment) gives a warning at each iteration.
## The data set is not well suited for GMM as GMM is based on N-asymptotics
```

```
## and the data set only contains 27 countries
#
# results_panel <-  lp_lin_panel(data_set          = data_set,
#                                data_sample       = data_sample,
#                                endog_data        = "mortgdp",
#                                cumul_mult        = TRUE,
#
#                                shock             = "stir",
#                                diff_shock        = TRUE,
#
#                                use_gmm           = TRUE,
#                                gmm_model         = "onestep",
#                                gmm_effect        = "twoways",
#                                gmm_transformation = "ld",
#
#                                l_exog_data       = "mortgdp",
#                                lags_exog_data    = 2,
#                                l_fd_exog_data    = colnames(data_set)[c(4, 6)],
#                                lags_fd_exog_data  = 1,
#
#                                confint           = 1.67,
#                                hor               = 5)
#
# Create and plot irfs
# plot(results_panel)
#
```

`lp_nl` *Compute nonlinear impulse responses*

Description

Compute nonlinear impulse responses with local projections by Jordà (2005). The data can be separated into two states by a smooth transition function as applied in Auerbach and Gorodnichenko (2012), or by a simple dummy approach.

Usage

```
lp_nl(
  endog_data,
  lags_endog_lin = NULL,
  lags_endog_nl = NULL,
  lags_criterion = NaN,
  max_lags = NaN,
  trend = NULL,
  shock_type = NULL,
```

```
  confint = NULL,
  use_nw = TRUE,
  nw_lag = NULL,
  nw_prewhite = FALSE,
  adjust_se = FALSE,
  hor = NULL,
  switching = NULL,
  lag_switching = TRUE,
  use_logistic = TRUE,
  use_hp = NULL,
  lambda = NULL,
  gamma = NULL,
  exog_data = NULL,
  lags_exog = NULL,
  contemp_data = NULL,
  num_cores = 1
)
```

Arguments

endog_data	A data.frame, containing all endogenous variables for the VAR. The Cholesky decomposition is based on the column order.
lags_endog_lin	NaN or integer. NaN if lag length criterion is used. Integer for number of lags for linear VAR to identify shock.
lags_endog_nl	NaN or integer. Number of lags for nonlinear VAR. NaN if lag length criterion is given.
lags_criterion	NaN or character. NaN (default) means that the number of lags will be given at *lags_endog_nl* and *lags_endog_lin*. The lag length criteria are 'AICc', 'AIC' and 'BIC'.
max_lags	NaN or integer. Maximum number of lags (if *lags_criterion* = 'AICc', 'AIC', 'BIC'). NaN (default) otherwise.
trend	Integer. Include no trend = 0 , include trend = 1, include trend and quadratic trend = 2.
shock_type	Integer. Standard deviation shock = 0, unit shock = 1.
confint	Double. Width of confidence bands. 68% = 1; 90% = 1.65; 95% = 1.96.
use_nw	Boolean. Use Newey-West (1987) standard errors for impulse responses? TRUE (default) or FALSE.
nw_lag	Integer. Specifies the maximum lag with positive weight for the Newey-West estimator. If set to NULL (default), the lag increases with with the number of horizon.
nw_prewhite	Boolean. Should the estimators be pre-whitened? TRUE of FALSE (default).
adjust_se	Boolen. Should a finite sample adjsutment be made to the covariance matrix estimators? TRUE or FALSE (default).
hor	Integer. Number of horizons for impulse responses.

`switching` Numeric vector. A column vector with the same length as *endog_data*. If 'use_logistic = TRUE', this series can either be decomposed via the Hodrick-Prescott filter (see Auerbach and Gorodnichenko, 2013) or directly plugged into the following logistic function:

$$F_{z_t} = \frac{exp(-\gamma z_t)}{1 + exp(-\gamma z_t)}.$$

Important: `F_{z_t}` will be lagged by one and then multiplied with the data. If the variable shall not be lagged, use 'lag_switching = FALSE':
Regime 1 = `(1-F(z_{t-1}))*y_{(t-p)}`,
Regime 2 = `F(z_{t-1})*y_{(t-p)}`.

`lag_switching` Boolean. Use the first lag of the values of the transition function? TRUE (default) or FALSE.

`use_logistic` Boolean. Use logistic function to separate states? TRUE (default) or FALSE. If FALSE, the values of the switching variable have to be binary (0/1).

`use_hp` Boolean. Use HP-filter? TRUE or FALSE.

`lambda` Double. Value of λ for the Hodrick-Prescott filter (if use_hp = TRUE).

`gamma` Double. Positive number which is used in the transition function.

`exog_data` A data.frame, containing exogenous variables for the VAR. The row length has to be the same as *endog_data*. Lag lengths for exogenous variables have to be given and will not be determined via a lag length criterion.

`lags_exog` NULL or Integer. Integer for the number of lags for the exogenous data. The value cannot be 0. If you want to to include exogenous data with contemporaneous impact use *contemp_data*.

`contemp_data` A data.frame, containing exogenous data with contemporaneous impact. This data will not be lagged. The row length has to be the same as *endog_data*.

`num_cores` Integer. The number of cores to use for the estimation. If NULL, the function will use the maximum number of cores minus one.

Value

A list containing:

`irf_s1_mean` A three-dimensional `array`, containing all impulse responses for all endogenous variables of the first state. The last dimension denotes the shock variable. The row in each matrix denotes the responses of the *ith* variable, ordered as in *endog_data*. The columns are the horizons. For example, if the results are saved in *results_nl*, `results_nl\$irf_s1_mean[, , 1]` returns a KxH matrix, where K is the number of variables and H is the number of horizons. '1' is the shock variable, corresponding to the variable in the first column of *endog_data*.

`irf_s1_low` A three-dimensional `array`, containing all lower confidence bands of the impulse responses, based on robust standard errors by Newey and West (1987). Properties are equal to *irf_s1_mean*.

`irf_s1_up` A three-dimensional `array`, containing all upper confidence bands of the impulse responses, based on robust standard errors by Newey and West (1987). Properties are equal to *irf_s1_mean*.

`irf_s2_mean` A three-dimensional `array`, containing all impulse responses for all endogenous variables of the second state. The last dimension denotes the shock variable. The row in each matrix denotes the responses of the *ith* variable, ordered as in *endog_data*. The columns denote the horizon. For example, if the results are saved in *results_nl*, `results_nl\$irf_s2_mean[, , 1]` returns a KxH matrix, where K is the number of variables and H is the number of horizons. '1' is the first shock variable corresponding to the variable in the first column of *endog_data*.

`irf_s2_low` A three-dimensional `array`, containing all lower confidence bands of the responses, based on robust standard errors by Newey and West (1987). Properties are equal to *irf_s2_mean*.

`irf_s2_up` A three-dimensional `array`, containing all upper confidence bands of the responses, based on robust standard errors by Newey and West (1987). Properties are equal to *irf_s2_mean*.

`specs` A list with properties of *endog_data* for the plot function. It also contains lagged data (*y_nl* and *x_nl*) used for the IRF estimations, and the selected lag lengths when an information criterion has been used.

`fz` A vector containing the values of the transition function `F(z\_{t-1})`.

Author(s)

Philipp Adämmer

References

Akaike, H. (1974). "A new look at the statistical model identification", *IEEE Transactions on Automatic Control*, 19 (6): 716–723.

Auerbach, A. J., and Gorodnichenko Y. (2012). "Measuring the Output Responses to Fiscal Policy." *American Economic Journal: Economic Policy*, 4 (2): 1-27.

Auerbach, A. J., and Gorodnichenko Y. (2013). "Fiscal Multipliers in Recession and Expansion." *NBER Working Paper Series*. Nr. 17447.

Hurvich, C. M., and Tsai, C.-L. (1989), "Regression and time series model selection in small samples", *Biometrika*, 76(2): 297–307

Jordà, Ò. (2005) "Estimation and Inference of Impulse Responses by Local Projections." *American Economic Review*, 95 (1): 161-182.

Newey, W.K., and West, K.D. (1987). "A Simple, Positive-Definite, Heteroskedasticity and Autocorrelation Consistent Covariance Matrix." *Econometrica*, 55, 703–708.

Schwarz, Gideon E. (1978). "Estimating the dimension of a model", *Annals of Statistics*, 6 (2): 461–464.

Ravn, M.O., Uhlig, H. (2002). "On Adjusting the Hodrick-Prescott Filter for the Frequency of Observations." *Review of Economics and Statistics*, 84(2), 371-376.

See Also

https://adaemmerp.github.io/lpirfs/README_docs.html

Examples

```
                  ## Example without exogenous variables ##

# Load package
  library(lpirfs)
  library(gridExtra)
  library(ggpubr)


# Load (endogenous) data
  endog_data <- interest_rules_var_data

# Choose data for switching variable (here Federal Funds Rate)
# Important: The switching variable does not have to be used within the VAR!
 switching_data <-  endog_data$Infl

# Estimate model and save results
  results_nl    <- lp_nl(endog_data,
                                lags_endog_lin  = 4,
                                lags_endog_nl   = 3,
                                trend           = 0,
                                shock_type      = 1,
                                confint         = 1.96,
                                hor             = 24,
                                switching       = switching_data,
                                use_hp          = TRUE,
                                lambda          = 1600,
                                gamma           = 3)

# Show all plots
 plot(results_nl)

# Make and save all plots
 nl_plots <- plot_nl(results_nl)

# Save plots based on states
 s1_plots <- sapply(nl_plots$gg_s1, ggplotGrob)
 s2_plots <- sapply(nl_plots$gg_s2, ggplotGrob)

# Show first irf of each state
  plot(s1_plots[[1]])
  plot(s2_plots[[1]])

# Show diagnostics. The first element correponds to the first shock variable.
 summary(results_nl)


                    ## Example with exogenous variables ##

# Load (endogenous) data
 endog_data <- interest_rules_var_data
```

```
# Choose data for switching variable (here Federal Funds Rate)
# Important: The switching variable does not have to be used within the VAR!
 switching_data <-  endog_data$FF

# Create exogenous data and data with contemporaneous impact (for illustration purposes only)
 exog_data   <- endog_data$GDP_gap*endog_data$Infl*endog_data$FF + rnorm(dim(endog_data)[1])
 contemp_data <- endog_data$GDP_gap*endog_data$Infl*endog_data$FF + rnorm(dim(endog_data)[1])

# Exogenous data has to be a data.frame
 exog_data    <- data.frame(xx  = exog_data)
 contemp_data <- data.frame(cc  = contemp_data)

# Estimate model and save results
 results_nl <- lp_nl(endog_data,
                          lags_endog_lin  = 4,
                          lags_endog_nl   = 3,
                          trend           = 0,
                          shock_type      = 1,
                          confint         = 1.96,
                          hor             = 24,
                          switching       = switching_data,
                          use_hp          = TRUE,
                          lambda          = 1600, # Ravn and Uhlig (2002):
                                                  # Anuual data    = 6.25
                                                  # Quarterly data = 1600
                                                  # Monthly data   = 129 600
                          gamma           = 3,
                          exog_data       = exog_data,
                          lags_exog       = 3)


# Show all plots
 plot(results_nl)


# Show diagnostics. The first element correponds to the first shock variable.
 summary(results_nl)
```

---

lp_nl_iv *Compute nonlinear impulse responses with identified shock*

Description

Compute nonlinear impulse responses with local projections and identified shock. The data can be separated into two states by a smooth transition function as applied in Auerbach and Gorodnichenko (2012), or by a simple dummy approach.

Usage

```
lp_nl_iv(
  endog_data,
  lags_endog_nl = NULL,
  shock = NULL,
  cumul_mult = FALSE,
  instr = NULL,
  exog_data = NULL,
  lags_exog = NULL,
  contemp_data = NULL,
  lags_criterion = NaN,
  max_lags = NaN,
  trend = NULL,
  confint = NULL,
  use_nw = TRUE,
  nw_lag = NULL,
  nw_prewhite = FALSE,
  adjust_se = FALSE,
  hor = NULL,
  switching = NULL,
  lag_switching = TRUE,
  use_logistic = TRUE,
  use_hp = NULL,
  lambda = NULL,
  gamma = NULL,
  num_cores = 1
)
```

Arguments

endog_data	A data.frame, containing all endogenous variables for the VAR.
lags_endog_nl	NaN or integer. NaN if lags are chosen by a lag length criterion. Integer for number of lags for *endog_data*.
shock	One column data.frame, including the instrument to shock with. The row length has to be the same as *endog_data*.
cumul_mult	Boolean. Estimate cumulative multipliers? TRUE or FALSE (default). If TRUE, cumulative responses are estimated via: $$y_{(t+h)} - y_{(t-1)},$$ where h = 0,..., H-1. This option is only available for *lags_criterion* = *NaN*.
instr	Deprecated input name. Use *shock* instead. See *shock* for details.
exog_data	A data.frame, containing exogenous variables. The row length has to be the same as *endog_data*. Lag lengths for exogenous variables have to be given and will not be determined via a lag length criterion.
lags_exog	NULL or Integer. Integer for the number of lags for the exogenous data. The value cannot be 0. If you want to to include exogenous data with contemporaneous impact use *contemp_data*.

contemp_data	A data.frame, containing exogenous data with contemporaneous impact. This data will not be lagged. The row length has to be the same as *endog_data*.
lags_criterion	NaN or character. NaN means that the number of lags will be given at *lags_endog_nl*. Possible lag length criteria are 'AICc', 'AIC' or 'BIC'.
max_lags	NaN or integer. Maximum number of lags (if *lags_criterion* = 'AICc', 'AIC', 'BIC'). NaN otherwise.
trend	Integer. Include no trend = 0 , include trend = 1, include trend and quadratic trend = 2.
confint	Double. Width of confidence bands. 68% = 1; 90% = 1.65; 95% = 1.96.
use_nw	Boolean. Use Newey-West (1987) standard errors for impulse responses? TRUE (default) or FALSE.
nw_lag	Integer. Specifies the maximum lag with positive weight for the Newey-West estimator. If set to NULL (default), the lag increases with with the number of horizon.
nw_prewhite	Boolean. Should the estimators be pre-whitened? TRUE of FALSE (default).
adjust_se	Boolen. Should a finite sample adjsutment be made to the covariance matrix estimators? TRUE or FALSE (default).
hor	Integer. Number of horizons for impulse responses.
switching	Numeric vector. A column vector with the same length as *endog_data*. This series can either be decomposed via the Hodrick-Prescott filter (see Auerbach and Gorodnichenko, 2013) or directly plugged into the following smooth transition function: $$F_{z_t} = \frac{exp(-\gamma z_t)}{1 + exp(-\gamma z_t)}.$$ Warning: `F\_{z_t}` will be lagged by one and then multiplied with the data. If the variable shall not be lagged, the vector has to be given with a lead of one. The data for the two regimes are: Regime 1 = `(1-F(z\_{t-1}))*y\_{(t-p)}`, Regime 2 = `F(z\_{t-1})*y\_{(t-p)}`.
lag_switching	Boolean. Use the first lag of the values of the transition function? TRUE (default) or FALSE.
use_logistic	Boolean. Use logistic function to separate states? TRUE (default) or FALSE. If FALSE, the values of the switching variable have to be binary (0/1).
use_hp	Boolean. Use HP-filter? TRUE or FALSE.
lambda	Double. Value of λ for the Hodrick-Prescott filter (if use_hp = TRUE).
gamma	Double. Positive number which is used in the transition function.
num_cores	Integer. The number of cores to use for the estimation. If NULL, the function will use the maximum number of cores minus one.

Value

A list containing:

irf_s1_mean	A matrix, containing the impulse responses of the first regime. The row in each matrix denotes the responses of the *ith* variable to the shock. The columns are the horizons.
irf_s1_low	A matrix, containing all lower confidence bands of the impulse responses, based on robust standard errors by Newey and West (1987). Properties are equal to *irf_s1_mean*.
irf_s1_up	A matrix, containing all upper confidence bands of the impulse responses, based on robust standard errors by Newey and West (1987). Properties are equal to *irf_s1_mean*.
irf_s2_mean	A matrix, containing all impulse responses for the second regime. The row in each matrix denotes the responses of the *ith* variable to the shock. The columns denote the horizon.
irf_s2_low	A matrix, containing all lower confidence bands of the responses, based on robust standard errors by Newey and West (1987). Properties are equal to *irf_s2_mean*.
irf_s2_up	A matrix, containing all upper confidence bands of the responses, based on robust standard errors by Newey and West (1987). Properties are equal to *irf_s2_mean*.
specs	A list with properties of *endog_data* for the plot function. It also contains lagged data (y_nl and x_nl) used for the estimations of the impulse responses, and the selected lag lengths when an information criterion has been used.
fz	A vector, containing the values of the transition function F(z_{t-1}).

Author(s)

Philipp Adämmer

References

Akaike, H. (1974). "A new look at the statistical model identification", *IEEE Transactions on Automatic Control*, 19 (6): 716–723.

Auerbach, A. J., and Gorodnichenko Y. (2012). "Measuring the Output Responses to Fiscal Policy." *American Economic Journal: Economic Policy*, 4 (2): 1-27.

Auerbach, A. J., and Gorodnichenko Y. (2013). "Fiscal Multipliers in Recession and Expansion." *NBER Working Paper Series*. Nr 17447.

Blanchard, O., and Perotti, R. (2002). "An Empirical Characterization of the Dynamic Effects of Changes in Government Spending and Taxes on Output." *Quarterly Journal of Economics*, 117(4): 1329–1368.

Hurvich, C. M., and Tsai, C.-L. (1989), "Regression and time series model selection in small samples", *Biometrika*, 76(2): 297–307

Jordà, Ò. (2005) "Estimation and Inference of Impulse Responses by Local Projections." *American Economic Review*, 95 (1): 161-182.

Jordà, Ò, Schularick, M., Taylor, A.M. (2015), "Betting the house", *Journal of International Economics*, 96, S2-S18.

Newey, W.K., and West, K.D. (1987). "A Simple, Positive-Definite, Heteroskedasticity and Autocorrelation Consistent Covariance Matrix." *Econometrica*, 55, 703–708.

Ramey, V.A., and Zubairy, S. (2018). "Government Spending Multipliers in Good Times and in Bad: Evidence from US Historical Data." *Journal of Political Economy*, 126(2): 850 - 901.

Schwarz, Gideon E. (1978). "Estimating the dimension of a model", *Annals of Statistics*, 6 (2): 461–464.

See Also

https://adaemmerp.github.io/lpirfs/README_docs.html

Examples

```
# This example replicates results from the Supplementary Appendix
# by Ramey and Zubairy (2018) (RZ-18).

# Load and prepare data
 ag_data           <- ag_data
 sample_start      <- 7
 sample_end        <- dim(ag_data)[1]
 endog_data        <- ag_data[sample_start:sample_end, 3:5]

# The shock is estimated by RZ-18
 shock             <- ag_data[sample_start:sample_end, 7]

# Include four lags of the 7-quarter moving average growth rate of GDP
# as exogenous variables (see RZ-18)
 exog_data         <- ag_data[sample_start:sample_end, 6]

# Use the 7-quarter moving average growth rate of GDP as switching variable
# and adjust it to have suffiently long recession periods.
 switching_variable <- ag_data$GDP_MA[sample_start:sample_end] - 0.8

# Estimate local projections
 results_nl_iv <- lp_nl_iv(endog_data,
                           lags_endog_nl     = 3,
                           shock             = shock,
                           exog_data         = exog_data,
                           lags_exog         = 4,
                           trend             = 0,
                           confint           = 1.96,
                           hor               = 20,
                           switching         = switching_variable,
                           use_hp            = FALSE,
                           gamma             = 3)

# Show all impulse responses
plot(results_nl_iv)

# Make and save individual plots
 plots_nl_iv <- plot_nl(results_nl_iv)
```

```
# Show single impulse responses
# Compare with red line of left plot (lower panel) in Figure 12 in Supplementary Appendix of RZ-18.
 plot(plots_nl_iv$gg_s1[[1]])
# Compare with blue line of left plot (lower panel) in Figure 12 in Supplementary Appendix of RZ-18.
 plot(plots_nl_iv$gg_s2[[1]])

# Show diagnostics. The first element shows the reaction of the first endogenous variable.
summary(results_nl_iv)
```

---

lp_nl_panel *Compute nonlinear impulse responses for panel data*

Description

This function estimates nonlinear impulse responses by using local projections for panel data with an identified shock. The data can be separated into two states by a smooth transition function as applied in Auerbach and Gorodnichenko (2012), or by a simple dummy approach.

Usage

```
lp_nl_panel(
  data_set = NULL,
  data_sample = "Full",
  endog_data = NULL,
  cumul_mult = TRUE,
  shock = NULL,
  diff_shock = TRUE,
  panel_model = "within",
  panel_effect = "individual",
  robust_cov = NULL,
  robust_method = NULL,
  robust_type = NULL,
  robust_cluster = NULL,
  robust_maxlag = NULL,
  use_gmm = FALSE,
  gmm_model = "onestep",
  gmm_effect = "twoways",
  gmm_transformation = "d",
  c_exog_data = NULL,
  l_exog_data = NULL,
  lags_exog_data = NaN,
  c_fd_exog_data = NULL,
  l_fd_exog_data = NULL,
  lags_fd_exog_data = NaN,
  switching = NULL,
```

```
  use_logistic = TRUE,
  use_hp = FALSE,
  lag_switching = TRUE,
  lambda = NULL,
  gamma = NULL,
  confint = NULL,
  hor = NULL
)
```

Arguments

data_set	A data.frame, containing the panel data set. The first column has to be the variable denoting the cross section. The second column has to be the variable denoting the time section.
data_sample	Character or numeric. To use the full sample set value to "Full" (default). To estimate a subset, you have to provide a sequence of dates. This sequence has to be in the same format as the second column (time-section).
endog_data	Character. The column name of the endogenous variable. You can only provide one endogenous variable at a time.
cumul_mult	Boolean. Estimate cumulative multipliers? TRUE (default) or FALSE. If TRUE, cumulative responses are estimated via: $$y_{(t+h)} - y_{(t-1)},$$ where h = 0,..., H-1.
shock	Character. The column name of the variable to shock with.
diff_shock	Boolean. Take first differences of the shock variable? TRUE (default) or FALSE. Note that when using this option both shock and instrument are used in first differences
panel_model	Character. Type of panel model. The default is "within" (fixed effects). Other options are "random", "ht", "between", "pooling" or "fd". See vignette of the plm package for details.
panel_effect	Character. The effects introduced in the model. Options are "individual" (default), "time", "twoways", or "nested". See the vignette of the plm-package for details.
robust_cov	NULL or Character. The character specifies the method how to estimate robust standard errors: Options are "vcovBK", "vcovDC", "vcovG", "vcovHC", "vcovNW", "vcovSCC". For these options see vignette of plm package. Another option is "Vcxt". For details see Miller (2017) If "use_gmm = TRUE", this option has to be NULL.
robust_method	NULL (default) or Character. The character is an option when robust_cov = "vcovHC". See vignette of the plm package for details.
robust_type	NULL (default) or Character. The character is an option when robust_cov = "vcovBK", "vcovDC", "vcovHC", "vcovNW" or "vcovSCC". See vignette of the plm package for details.

`robust_cluster` NULL (default) or Character. The character is an option when robust_cov = "vcovBK", "vcovG" or "vcovHC". See vignette of the plm package for details.

`robust_maxlag` NULL (default) or Character. The character is an option when robust_cov = "vcovNW" or "vcovSCC". See vignette of the plm package for details.

`use_gmm` Boolean. Use GMM for estimation? TRUE or FALSE (default). See vignette of plm package for details. If TRUE, the option "robust_cov" has to be set to NULL.

`gmm_model` Character. Either "onestep" (default) or "twosteps". See vignette of the plm package for details.

`gmm_effect` Character. The effects introduced in the model: "twoways" (default) or "individual". See vignette of the plm-package for details.

`gmm_transformation`
Character. Either "d" (default) for the "difference GMM" model or "ld" for the "system GMM". See vignette of the plm package for details.

`c_exog_data` NULL or Character. Name(s) of the exogenous variable(s) with contemporaneous impact.

`l_exog_data` NULL or Character. Name(s) of the exogenous variable(s) with lagged impact.

`lags_exog_data` Integer. Lag length for the exogenous variable(s) with lagged impact.

`c_fd_exog_data` NULL or Character. Name(s) of the exogenous variable(s) with contemporaneous impact of first differences.

`l_fd_exog_data` NULL or Character. Name(s) of exogenous variable(s) with lagged impact of first differences.

`lags_fd_exog_data`
NaN or Integer. Number of lags for variable(s) with impact of first differences.

`switching` Character. Column name of the switching variable. If "use_logistic = TRUE", this series can either be decomposed by the Hodrick-Prescott filter (see Auerbach and Gorodnichenko, 2013) or directly plugged into the following smooth transition function:

$$F_{z_t} = \frac{exp(-\gamma z_t)}{1 + exp(-\gamma z_t)}.$$

The data for the two regimes are lagged by default:
Regime 1 = (1-F(z_{t-1}))*y_{(t-p)},
Regime 2 = F(z_{t-1})*y_{(t-p)}. This option can be suppressed with "lag_switching = FALSE".

`use_logistic` Boolean. Use logistic function to separate states? TRUE (default) or FALSE. If FALSE, the values of the switching variable have to be binary (0/1).

`use_hp` Boolean. Use HP-filter? TRUE or FALSE (default).

`lag_switching` Boolean. Use the first lag of the values of the transition function? TRUE (default) or FALSE.

`lambda` Double. Value of λ for the Hodrick-Prescott filter (if "use_hp = TRUE").

`gamma` Double. Positive value for γ, used in the transition function.

`confint` Double. Width of confidence bands. 68% = 1; 90% = 1.65; 95% = 1.96.

`hor` Integer. Number of horizons for impulse responses.

Value

A list containing:

irf_lin_mean	A matrix, containing the impulse responses. The columns are the horizons.
irf_lin_low	A matrix, containing all lower confidence bands. The columns are the horizons.
irf_lin_up	A matrix, containing all upper confidence bands. The columns are the horizons.
reg_outputs	Full regression output (plm object) for each horizon.
reg_summaries	Summary of regression output for each horizon. In case of robust covariance estimators, this only includes the t-tests.
xy_data_sets	Data sets with endogenous and exogenous variables for each horizon.
specs	A list with data properties for e.g. the plot function.

Author(s)

Philipp Adämmer

References

Croissant, Y., Millo, G. (2008). "Panel Data Econometrics in R: The plm Package." *Journal of Statistical Software*, 27(2), 1-43. doi: 10.18637/jss.v027.i02.

Jordà, Ò. (2005). "Estimation and Inference of Impulse Responses by Local Projections." *American Economic Review*, 95 (1): 161-182.

Jordà, Ò., Schualrick, M., Taylor, A.M. (2018). "Large and State-Dependent Effects of Quasi-Random Monetary Experiments", *NBER* working paper 23074, *FRBSF* working paper 2017-02.

Millo, G. (2017). "Robust Standard Error Estimators for Panel Models: A Unifying Approach." *Journal of Statistical Software*, 82(3), 1-27. doi: 10.18637/jss.v082.i03.

Examples

```
#--- Info
# This example is based on a STATA code that has been provided on
# Òscar Jordà's website (https://sites.google.com/site/oscarjorda/home/local-projections)
# It estimates impulse reponses of the ratio of (mortgage lending/GDP) to a
# +1% change in the short term interest rate

#--- Get data
# Go to the website of the 'The MacroFinance and MacroHistory Lab'
# Download the Excel-Sheet of the 'Jordà-Schularick-Taylor Macrohistory Database':
# URL: https://www.macrohistory.net/database/
# Then uncomment and run the code below...


#--- Code

## Load libraries to download and read excel file from the website
#  library(lpirfs)
```

```
#  library(readxl)
#  library(dplyr)
#
# Load JST Macrohistory Database
#  jst_data <- read_excel("JSTdatasetR5.xlsx", sheet = "Data")
#
## Choose years <= 2013. Swap the first two columns so that 'country' is the
## first (cross section) and 'year' the second (time section) column
#  jst_data <- jst_data                    %>%
#              dplyr::filter(year <= 2013) %>%
#              dplyr::select(country, year, everything())
#
## Prepare variables. This is based on the 'data.do' file
#   data_set <- jst_data %>%
#                mutate(stir     = stir)                          %>%
#                mutate(mortgdp  = 100*(tmort/gdp))               %>%
#                mutate(hpreal   = hpnom/cpi)                     %>%
#                group_by(country)                                %>%
#                mutate(hpreal   = hpreal/hpreal[year==1990][1]) %>%
#                mutate(lhpreal  = log(hpreal))                   %>%
#
#                mutate(lhpy     = lhpreal - log(rgdppc))         %>%
#                mutate(lhpy     = lhpy - lhpy[year == 1990][1]) %>%
#                mutate(lhpreal  = 100*lhpreal)                   %>%
#                mutate(lhpy     = 100*lhpy)                      %>%
#                ungroup()                                        %>%
#
#                mutate(lrgdp    = 100*log(rgdppc))               %>%
#                mutate(lcpi     = 100*log(cpi))                 %>%
#                mutate(lriy     = 100*log(iy*rgdppc))            %>%
#                mutate(cay      = 100*(ca/gdp))                  %>%
#                mutate(tnmort   = tloans - tmort)                %>%
#                mutate(nmortgdp = 100*(tnmort/gdp))              %>%
#                dplyr::select(country, year, mortgdp, stir, ltrate, lhpy,
#                              lrgdp, lcpi, lriy, cay, nmortgdp)
#
#
## Use data_sample from 1870 to 2013 and exclude observations from WWI and WWII
#   data_sample <-   seq(1870, 2016)[!(seq(1870, 2016) %in%
#                                    c(seq(1914, 1918),
#                                    seq(1939, 1947)))]
#
## Estimate panel model
# results_panel <-  lp_nl_panel(data_set           = data_set,
#                               data_sample       = data_sample,
#                               endog_data        = "mortgdp",
#                               cumul_mult        = TRUE,
#
#                               shock             = "stir",
#                               diff_shock        = TRUE,
#                               panel_model       = "within",
#                               panel_effect      = "individual",
#                               robust_cov        = "vcovSCC",
```

```
#
#                                switching         = "lrgdp",
#                                lag_switching     = TRUE,
#                                use_hp            = TRUE,
#                                lambda            = 6.25,
#                                gamma             = 10,
#
#                                c_exog_data       = "cay",
#                                c_fd_exog_data    = colnames(data_set)[c(seq(4,9),11)],
#                                l_fd_exog_data    = colnames(data_set)[c(seq(3,9),11)],
#                                lags_fd_exog_data = 2,
#
#                                confint           = 1.67,
#                                hor               = 5)
#
## Plot irfs
#  plot(results_panel)
#
#
## Plot values of the transition function for USA between 1950 and 2016
#  library(ggplot2)
#
#  data_set %>%
#     mutate(fz = results_panel$fz$fz) %>%
#     select(country, year, fz)     %>%
#     filter(country == "USA" & year > 1950  & year <= 2016) %>%
#     ggplot()+
#     geom_line(aes(x = year, y = fz)) +
#     scale_x_continuous(breaks = seq(1950, 2016, 5))
#
#
################################################################################
###                            Use GMM                                       ###
################################################################################
#
## Use a much smaller sample to have fewer T than N
#  data_sample <-   seq(2000, 2012)
#
#
## Estimate panel model with gmm
## This example (please uncomment) gives a warning at each iteration.
## The data set is not well suited for
## GMM as GMM is based on N-asymptotics and the data set only contains 27 countries
#
# results_panel <-  lp_nl_panel(data_set           = data_set,
#                               data_sample       = data_sample,
#                               endog_data        = "mortgdp",
#                               cumul_mult        = TRUE,
#
#                               shock             = "stir",
#                               diff_shock        = TRUE,
#
#                               use_gmm           = TRUE,
```

```
#                                gmm_model          = "onestep",
#                                gmm_effect         = "twoways",
#                                gmm_transformation = "ld",
#
#                                switching         = "lrgdp",
#                                lag_switching     = TRUE,
#                                use_hp            = TRUE,
#                                lambda            = 6.25,
#                                gamma             = 10,
#
#                                l_exog_data       = "mortgdp",
#                                lags_exog_data    = 1,
#
#                                confint           = 1.67,
#                                hor               = 5)
#
## Create and plot irfs
# plot(results_panel)
```

`lpirfs_obj-methods-base` *Base methods for lpirfs_obj objects*

Description

Base methods for lpirfs_obj objects

`monetary_var_data` *Data to estimate a standard monetary VAR*

Description

A tibble, containing data to estimate a standard monetary VAR.

Usage

```
monetary_var_data
```

Format

A tibble with 494 monthly observations (rows) and 6 variables (columns):

EM Log of non-agricultural payroll employment.

P Log of personal consumption expenditures deflator (1996 = 100).

POCM Annual growth rate of the index of sensitive materials prices issued by the Conference Board.

FF Federal funds rate.

NBRX Ratio of nonborrowed reserves plus extended credit to total reserves.

M2 Annual growth rate of M2 stock.

Sample: 1960:01 - 2001:02.

Source

https://www.aeaweb.org/articles?id=10.1257/0002828053828518

References

Jordà, Ò. (2005) "Estimation and Inference of Impulse Responses by Local Projections." *American Economic Review*, 95 (1): 161-182.

`plot.lpirfs_lin_iv_obj` *Base print() function to plot all impulse responses from linear lpirfs object*

Description

Base print() function to plot all impulse responses from linear lpirfs object

Usage

```
## S3 method for class 'lpirfs_lin_iv_obj'
plot(x, ...)
```

Arguments

x	An object of type 'lpirfs_lin_obj
...	Additional arguments to be consistent with S3 print() function

plot.lpirfs_lin_obj *Base print() function to plot all impulse responses from linear lpirfs object*

Description

Base print() function to plot all impulse responses from linear lpirfs object

Usage

```
## S3 method for class 'lpirfs_lin_obj'
plot(x, ...)
```

Arguments

x	An object of type 'lpirfs_lin_obj
...	Additional arguments to be consistent with S3 print() function

plot.lpirfs_lin_panel_obj *Base print() function to plot all impulse responses from linear lpirfs object*

Description

Base print() function to plot all impulse responses from linear lpirfs object

Usage

```
## S3 method for class 'lpirfs_lin_panel_obj'
plot(x, ...)
```

Arguments

x	An object of type 'lpirfs_lin_panel_obj'
...	Additional arguments to be consistent with S3 print() function

plot.lpirfs_nl_iv_obj *Base print() function to plot all impulse responses from linear lpirfs object*

Description

Base print() function to plot all impulse responses from linear lpirfs object

Usage

```
## S3 method for class 'lpirfs_nl_iv_obj'
plot(x, ...)
```

Arguments

x	An object of type 'lpirfs_nl_iv_obj'
...	Additional arguments to be consistent with S3 print() function

plot.lpirfs_nl_obj *Base print() function to plot all impulse responses from nonlinear lpirfs object*

Description

Base print() function to plot all impulse responses from nonlinear lpirfs object

Usage

```
## S3 method for class 'lpirfs_nl_obj'
plot(x, ...)
```

Arguments

x	An object of type 'lpirfs_nl_obj'
...	Additional arguments to be consistent with S3 print() function

plot.lpirfs_nl_panel_obj *Base print() function to plot all impulse responses from linear lpirfs object*

Description

Base print() function to plot all impulse responses from linear lpirfs object

Usage

```
## S3 method for class 'lpirfs_nl_panel_obj'
plot(x, ...)
```

Arguments

x	An object of type 'lpirfs_lin_panel_obj'
...	Additional arguments to be consistent with S3 print() function

plot_lin *Compute and display plots of linear impulse responses*

Description

Compute and display linear impulse responses, estimated with lp_lin() and lp_lin_iv().

Usage

```
plot_lin(results_lin)
```

Arguments

results_lin	A list created with lp_lin() or lp_lin_iv().

Value

A list with (gg-)plots for linear impulse responses.

Author(s)

Philipp Adämmer

Examples

```
# See examples for lp_lin() and lp_lin_iv().
```

plot_nl *Compute and display plots of nonlinear impulse responses*

Description

Compute and display (nonlinear) impulse responses, estimated with lp_nl() and lp_nl_iv().

Usage

```
plot_nl(results_nl)
```

Arguments

results_nl	A list created with lp_nl() or lp_nl_iv().

Value

A list with (gg-)plots for nonlinear impulse responses.

Author(s)

Philipp Adämmer

Examples

```
# Load package

 # See examples for lp_nl() and lp_nl_iv().
```

summary.lpirfs_lin_iv_obj *Summary for nonlinear lpirfs object*

Description

Summary for nonlinear lpirfs object

Usage

```
## S3 method for class 'lpirfs_lin_iv_obj'
summary(object, ...)
```

Arguments

object	An object of type 'lpirfs_lin_iv_obj'
...	Additional arguments to be consistent with S3 print() function

summary.lpirfs_lin_obj *Summary for linear lpirfs object*

Description

Summary for linear lpirfs object

Usage

```
## S3 method for class 'lpirfs_lin_obj'
summary(object, ...)
```

Arguments

object	An object of type 'lpirfs_lin_obj'
...	Additional arguments to be consistent with S3 print() function

summary.lpirfs_lin_panel_obj *Summary for nonlinear lpirfs object*

Description

Summary for nonlinear lpirfs object

Usage

```
## S3 method for class 'lpirfs_lin_panel_obj'
summary(object, ...)
```

Arguments

object	An object of type 'lpirfs_lin_panel_obj'
...	Additional arguments to be consistent with S3 print() function

summary.lpirfs_nl_iv_obj *Summary for nonlinear lpirfs object*

Description

Summary for nonlinear lpirfs object

Usage

```
## S3 method for class 'lpirfs_nl_iv_obj'
summary(object, ...)
```

Arguments

object	An object of type 'lpirfs_nl_iv_obj'
...	Additional arguments to be consistent with S3 print() function

summary.lpirfs_nl_obj *Summary for nonlinear lpirfs object*

Description

Summary for nonlinear lpirfs object

Usage

```
## S3 method for class 'lpirfs_nl_obj'
summary(object, ...)
```

Arguments

object	An object of type 'lpirfs_nl_obj'
...	Additional arguments to be consistent with S3 print() function

summary.lpirfs_nl_panel_obj *Summary for nonlinear lpirfs object*

Description

Summary for nonlinear lpirfs object

Usage

```
## S3 method for class 'lpirfs_nl_panel_obj'
summary(object, ...)
```

Arguments

object	An object of type 'lpirfs_lin_panel_obj'
...	Additional arguments to be consistent with S3 print() function

Index

∗ **datasets**
    ag_data, 3
    interest_rules_var_data, 6
    monetary_var_data, 37

ag_data, 3
array, *8*

data.frame, *7, 8*, *11*, *16*, *22, 23*, *27, 28*, *32*

get_robust_cov_panel, 4

hp_filter, 4

interest_rules_var_data, 6

list, *41, 42*
lp_lin, 6, *41*
lp_lin_iv, 10, *41*
lp_lin_panel, 15
lp_nl, 21, *42*
lp_nl_iv, 26, *42*
lp_nl_panel, 31
lpirfs *(*lpirfs-package*)*, 2
lpirfs-package, 2
lpirfs_obj-methods-base, 37

matrix, *12*, *17*, *29*, *34*
monetary_var_data, 37

plot.lpirfs_lin_iv_obj, 38
plot.lpirfs_lin_obj, 39
plot.lpirfs_lin_panel_obj, 39
plot.lpirfs_nl_iv_obj, 40
plot.lpirfs_nl_obj, 40
plot.lpirfs_nl_panel_obj, 41
plot_lin, 41
plot_nl, 42

summary.lpirfs_lin_iv_obj, 42
summary.lpirfs_lin_obj, 43
summary.lpirfs_lin_panel_obj, 43
summary.lpirfs_nl_iv_obj, 44
summary.lpirfs_nl_obj, 44
summary.lpirfs_nl_panel_obj, 45