

Package: lvmcomp (via r-universe)

October 26, 2024

Type Package

Title Stochastic EM Algorithms for Latent Variable Models with a High-Dimensional Latent Space

Version 1.2

Date 2018-12-19

Author Siliang Zhang [aut, cre], Yunxiao Chen [aut], Jorge Nocedal [cph], Naoaki Okazaki [cph]

Description Provides stochastic EM algorithms for latent variable models with a high-dimensional latent space. So far, we provide functions for confirmatory item factor analysis based on the multidimensional two parameter logistic (M2PL) model and the generalized multidimensional partial credit model. These functions scale well for problems with many latent traits (e.g., thirty or even more) and are virtually tuning-free. The computation is facilitated by multiprocessing 'OpenMP' API. For more information, please refer to: Zhang, S., Chen, Y., & Liu, Y. (2018). An Improved Stochastic EM Algorithm for Large-scale Full-information Item Factor Analysis. *British Journal of Mathematical and Statistical Psychology*. <doi:10.1111/bmsp.12153>.

Maintainer Siliang Zhang <zhangsiliang123@gmail.com>

URL <https://github.com/slzhang-fd/lvmcomp>

BugReports <https://github.com/slzhang-fd/lvmcomp/issues>

License GPL-3

LazyData true

Depends R (>= 3.1)

Imports Rcpp (>= 0.12.17), coda (>= 0.19-1), stats

LinkingTo Rcpp, RcppArmadillo

RoxygenNote 6.1.0

Encoding UTF-8

NeedsCompilation yes

Repository CRAN

Date/Publication 2018-12-30 23:00:02 UTC

Contents

data_sim_mirt	2
data_sim_pcirt	2
StEM_mirt	3
StEM_pcirt	4

Index	6
--------------	----------

data_sim_mirt	<i>Simulated dataset for multivariate item response theory model.</i>
---------------	---

Description

The dataset contains the simulation setting and the response data.

Usage

data_sim_mirt

Format

An object of class list of length 9.

data_sim_pcirt	<i>Simulated dataset for generalized partial credit model.</i>
----------------	--

Description

The dataset contains the simulation setting and the response data.

Usage

data_sim_pcirt

Format

An object of class list of length 10.

StEM_mirt	<i>Stochastic EM algorithm for solving multivariate item response theory model</i>
-----------	--

Description

Stochastic EM algorithm for solving multivariate item response theory model

Usage

```
StEM_mirt(response, Q, A0, d0, theta0, sigma0, m = 200, TT = 20,
max_attempt = 40, tol = 1.5, precision = 0.01, parallel = FALSE)
```

Arguments

response	N by J matrix containing 0/1 responses, where N is the number of respondents and J is the number of items.
Q	J by K matrix containing 0/1 entries, where J is the number of items and K is the number of latent traits. Each entry indicates whether an item measures a certain latent trait.
A0	J by K matrix, the initial value of loading matrix, satisfying the constraints given by Q.
d0	Length J vector, the initial value of intercept parameters.
theta0	N by K matrix, the initial value of latent traits for each respondent.
sigma0	K by K matrix, the initial value of correlations among the latent traits.
m	The length of Markov chain window for choosing burn-in size with a default value 200.
TT	The batch size with a default value 20.
max_attempt	The maximum number of batches before stopping.
tol	The tolerance of geweke statistic used for determining burn-in size with a default value 1.5.
precision	The precision value for determining the stopping of the algorithm with a default value 1e-2.
parallel	Whether or not enable the parallel computing with a default value FALSE.

Value

The function returns a list with the following components:

A_hat The estimated loading matrix.
d_hat The estimated value of intercept parameters.
sigma_hat The estimated value of correlation matrix of latent traits.
burn_in_T The length of burn-in size.

References

Zhang, S., Chen, Y. and Liu, Y. (2018). An Improved Stochastic EM Algorithm for Large-Scale Full-information Item Factor Analysis. *British Journal of Mathematical and Statistical Psychology*. To appear. D.C. Liu and J. Nocedal. On the Limited Memory Method for Large Scale Optimization (1989), *Mathematical Programming B*, 45, 3, pp. 503-528.

Examples

```
# run a toy example based on the M2PL model

# load a simulated dataset
attach(data_sim_mirt)

# generate starting values for the algorithm
A0 <- Q
d0 <- rep(0, J)
theta0 <- matrix(rnorm(N*K, 0, 1),N)
sigma0 <- diag(1, K)

# do the confirmatory MIRT analysis
# to enable multicore processing, set parallel = T
mirt_res <- StEM_mirt(response, Q, A0, d0, theta0, sigma0)
```

StEM_pcirt

Stochastic EM algorithm for solving generalized partial credit model

Description

Stochastic EM algorithm for solving generalized partial credit model

Usage

```
StEM_pcirt(response, Q, A0, D0, theta0, sigma0, m = 200, TT = 20,
  max_attempt = 40, tol = 1.5, precision = 0.015, parallel = F)
```

Arguments

response	N by J matrix containing 0,1,...,M-1 responses, where N is the number of respondents and J is the number of items.
Q	J by K matrix containing 0/1 entries, where J is the number of items and K is the number of latent traits. Each entry indicates whether an item measures a certain latent trait.
A0	J by K matrix, the initial value of loading matrix.
D0	J by M matrix containing the initial value of intercept parameters, where M is the number of response categories.
theta0	N by K matrix, the initial value of latent traits for each respondent

<code>sigma0</code>	K by K matrix, the initial value of correlations among latent traits.
<code>m</code>	The length of Markov chain window for choosing burn-in size with a default value 200.
<code>TT</code>	The batch size with a default value 20.
<code>max_attempt</code>	The maximum attempt times if the precision criterion is not meet.
<code>tol</code>	The tolerance of geweke statistic used for determining burn in size, default value is 1.5.
<code>precision</code>	The pre-set precision value for determining the length of Markov chain, default value is 0.015.
<code>parallel</code>	Whether or not enable the parallel computing with a default value FALSE.

Value

The function returns a list with the following components:

A_hat The estimated loading matrix

D_hat The estimated value of intercept parameters.

sigma_hat The estimated value of correlation matrix of latent traits.

burn_in_T The length of burn in size.

References

Zhang, S., Chen, Y. and Liu, Y. (2018). An Improved Stochastic EM Algorithm for Large-Scale Full-information Item Factor Analysis. *British Journal of Mathematical and Statistical Psychology*. To appear. D.C. Liu and J. Nocedal. On the Limited Memory Method for Large Scale Optimization (1989), *Mathematical Programming B*, 45, 3, pp. 503-528.

Examples

```
# run a toy example based on the partial credit model

# load a simulated dataset
attach(data_sim_pcirt)

# generate starting values for the algorithm
A0 <- Q
D0 <- matrix(1, J, M)
D0[,1] <- 0
theta0 <- matrix(rnorm(N*K), N, K)
sigma0 <- diag(1, K)

# do the confirmatory partial credit model analysis
# to enable multicore processing, set parallel = T
pcirt_res <- StEM_pcirt(response, Q, A0, D0, theta0, sigma0)
```

Index

* datasets

data_sim_mirt, [2](#)

data_sim_pcirt, [2](#)

data_sim_mirt, [2](#)

data_sim_pcirt, [2](#)

StEM_mirt, [3](#)

StEM_pcirt, [4](#)