

# Package: mand (via r-universe)

August 28, 2024

**Type** Package

**Title** Multivariate Analysis for Neuroimaging Data

**Version** 2.0

**Date** 2023-09-14

**Maintainer** Atsushi Kawaguchi <kawa\_a24@yahoo.co.jp>

**Depends** R (>= 3.5), msma

**Imports** oro.nifti, oro.dicom, imager, caret

**Description** Several functions can be used to analyze neuroimaging data using multivariate methods based on the 'msma' package. The functions used in the book entitled ``Multivariate Analysis for Neuroimaging Data'' (2021, ISBN-13: 978-0367255329) are contained.

**License** GPL (>= 2)

**Suggests** knitr, rmarkdown

**VignetteBuilder** knitr

**RoxygenNote** 7.2.3

**NeedsCompilation** no

**Author** Atsushi Kawaguchi [aut, cre]

**Repository** CRAN

**Date/Publication** 2023-09-12 22:10:06 UTC

## Contents

mand-package . . . . .	2
atlas . . . . .	2
atlasdatasets . . . . .	3
atlastable . . . . .	3
baseimg . . . . .	4
basisprod . . . . .	4
coat . . . . .	5
diffimg . . . . .	7

exbrain . . . . .	7
imgdatamat . . . . .	8
mask . . . . .	9
multicoat . . . . .	9
multicompplot . . . . .	10
multirec . . . . .	11
ptest . . . . .	12
rbfunc . . . . .	13
rec . . . . .	14
sdevimg . . . . .	15
simbrain . . . . .	15
sizechange . . . . .	16
template . . . . .	17

<b>Index</b>	<b>18</b>
--------------	-----------

---

mand-package	<i>Multivariate Analysis for Neuroimaging Data Package</i>
--------------	--

---

### Description

A Package for implementation of multivariate data analysis for neuroimaging data.

### Author(s)

Atsushi Kawaguchi. <kawa\_a24@yahoo.co.jp>

### References

Kawaguchi, A. (2021). *Multivariate Analysis for Neuroimaging Data*. CRC Press.

---

atlas	<i>Atlas set</i>
-------	------------------

---

### Description

The data is the atlas image data. An image whose element is "ROIid" is stored for each atlas.

### Usage

```
data(atlas)
```

### Format

A list of array

---

atlasdatasets	<i>Atlas data set</i>
---------------	-----------------------

---

**Description**

The data is the atlas data. Various atlases are stored. Each matrix has "ROIid" and "ROIname" as column names.

**Usage**

```
data(atlasdatasets)
```

**Format**

A list of matrix

---

atlastable	<i>Result report with atlas data</i>
------------	--------------------------------------

---

**Description**

This function refers to the results obtained by the analysis in an atlas image, and reports a summary of the results for each anatomical region.

**Usage**

```
atlastable(x, y, atlasdataset = NULL, ROIids = NULL, ...)
```

```
## S3 method for class 'atlastable'
print(x, ...)
```

**Arguments**

x	an array for the atlas image.
y	an array for the result image.
atlasdataset	a matrix or data.frame. The colnames should include "ROIid" and "ROIname".
ROIids	a vector indicating ROI id shown in the result.
...	further arguments passed to or from other methods.

**Details**

atlastable requires the atlas image and data frame including the ROI id and the name.

**Examples**

```

data(diffimg)
data(atlasdatasets)
data(atlas)
atlasname = "aal3"
atlasdataset = atlasdatasets[[atlasname]]
tmpatlas = atlas[[atlasname]]
atlastable(tmpatlas, diffimg, atlasdataset=atlasdataset, ROIids = c(1:2, 41:44))

```

---

baseimg

*Base Brain Data*


---

**Description**

The data is the base brain data. This is an average image of a healthy person, and is used when generating artificial data.

**Usage**

```
data(baseimg)
```

**Format**

A array

---

basisprod

*Product Radial Basis Function*


---

**Description**

This is a function to product the output for the rbfunc function with data matrix for a dimension reduction.

**Usage**

```
basisprod(A, B)
```

**Arguments**

A a list or a matrix corresponding to the output for the rbfunc function with the argument hispec=FALSE or data matrix, respectively.

B a list or a matrix.

**Details**

basisprod requires one list and one matrix.

**Examples**

```

imagedim1=c(10,10,10)

B1 = rbfunc(imagedim=imagedim1, seppix=4, hispec=TRUE)
B2 = rbfunc(imagedim=imagedim1, seppix=4, hispec=FALSE)

n = 50
S = matrix(rnorm(n*prod(imagedim1)), nrow = n, ncol = prod(imagedim1))

SB1 = S %%% B1
SB12 = tcrossprod(S, t(B1))
all(SB1-SB12 == 0)

SB2 = basisprod(S, B2)
all(SB1-SB2 == 0)

BS1 = t(B1) %%% t(S)
BS2 = basisprod(B2, S)
all(BS1-t(BS2) == 0)

```

---

coat

*Coat Function*


---

**Description**

This is a function for plotting an image. The analysis result can be overcoated on the template.

**Usage**

```

coat(
  x,
  y = NULL,
  pseq = NULL,
  xyz = NULL,
  col.x = gray(0:64/64),
  col.y = NULL,
  breaks.y = NULL,
  zlim.x = NULL,
  zlim.y = NULL,
  rownum = 5,
  colnum = NULL,
  plane = c("axial", "coronal", "sagittal", "all")[1],
  xlab = "",
  ylab = "",
  axes = FALSE,
  oma = rep(0, 4),
  mar = rep(0, 4),

```

```

    bg = "black",
    paron = TRUE,
    cross.hair = FALSE,
    chxy = NULL,
    color.bar = TRUE,
    regionplot = FALSE,
    atlasdataset = NULL,
    regionname = c("atlas", "stat")[1],
    regionlegend = FALSE,
    atlasname = "",
    ROIids = 1:9,
    ...
)

```

### Arguments

x	image1. Base image.
y	image2 to be overcoated.
pseq	a vector plot sequence.
xyz	a vector position to be plotted.
col.x	a color vector for image1.
col.y	a color vector for image2.
breaks.y	a vector breaks value for y.
zlim.x	a vector plot limitation values for z of x.
zlim.y	a vector plot limitation values for z of y.
rownum	a numeric, the number of row for the plot.
colnum	a numeric, the number of colnum for the plot.
plane	a vector plot sequence.
xlab	a character for a label in the x axis.
ylab	a character for a label in the y axis.
axes	a logical. TRUE presents the axes.
oma	a vector for outer margin area.
mar	a vector for margin.
bg	a character for color of background.
paron	a logical. TRUE means par is used.
cross.hair	a logical.
chxy	a vector cross hair position to be plotted.
color.bar	a logical.
regionplot	a logical.
atlasdataset	a matrix or data.frame. colnames shold include "ROIid" and "ROIname".
regionname	a character.

regionlegend a logical.  
atlasname a character.  
ROIids a vector  
... further arguments passed to or from other methods.

### Details

coat requires a image array.

### Examples

```
data(exbrain)  
coat(exbrain)
```

---

diffimg *Difference Brain Data*

---

### Description

The data is the difference brain data. This represents the difference between the average images of healthy subjects and patients with Alzheimer's disease, and is used when generating artificial data.

### Usage

```
data(diffimg)
```

### Format

A array

---

exbrain *Example Brain Data*

---

### Description

The data are from a MRI gray matter brain data for one subject.

### Usage

```
data(exbrain)
```

### Format

A array

imgdatamat

*Creat Data Matrix Function***Description**

This is a function that creates a data matrix for analysis from a file saved in image format.

**Usage**

```
imgdatamat(
  imgfnames,
  mask = NULL,
  ROI = FALSE,
  atlas = NULL,
  atlasdataset = NULL,
  ROIids = NULL,
  zeromask = FALSE,
  schange = FALSE,
  ...
)
```

**Arguments**

imgfnames	a vector for (nifti) file names to be used.
mask	a vector for brain mask data.
ROI	a logical for roi data set.
atlas	an array for the atlas.
atlasdataset	a matrix or data.frame. colnames shold include "ROIid" and "ROIname".
ROIids	a vector
zeromask	a logical for masking voxel with all zeros.
schange	a logical for change dimension.
...	further arguments passed to or from other methods.

**Details**

imgdatamat requires image file names.

**Value**

S	data matrix
brainpos	binary brain position.
imagedim	three dimensional vector for image dimension



**Examples**

```
# imgfnames1 = c("img1.nii", "img2.nii")
# imgdata = imgdatamat(imgfnames1)
```

---

mask

*Brain Mask*


---

**Description**

The data is the brain mask. This is used to exclude extra-brain regions from the analysis.

**Usage**

```
data(mask)
```

**Format**

A array

---

multicoat

*Multi Coat Function*


---

**Description**

This is a function for plotting an image. The analysis result can be overcoated on the template.

**Usage**

```
multicoat(imgs, y = NULL, row4imp = 6, col4imp = 1, trm = NULL, ...)
```

**Arguments**

imgs	list of images. Base images.
y	image2 to be overcoated.
row4imp	the number of rows per a image
col4imp	the number of columns per a image
trm	the index to trim the top and bottom of the slice
...	further arguments passed to or from other methods.

**Details**

multicoat requires a image array.

**Examples**

```
data(exbrain)
```

---

multicompplot                      *Multi components plot*

---

### Description

This is a function that plots the vectorized image returned to its original dimensions by the multirec function.

### Usage

```
multicompplot(
  object,
  x,
  comps = NULL,
  row4comp = 6,
  col4comp = 1,
  pseq4comp = NULL,
  ...
)
```

### Arguments

object	an object of class "multirec." Usually, a result of a call to multirec
x	template image
comps	a component sequence to be plotted.
row4comp	the number of rows per a component
col4comp	the number of columns per a component
pseq4comp	the number of images per a component
...	further arguments passed to or from other methods.

### Details

multicompplot requires the output result of msma function.

### Examples

```
data(baseimg)
data(diffimg)
data(mask)
data(template)
img1 = simbrain(baseimg = baseimg, diffimg = diffimg, mask=mask)
B1 = rbfunc(imagedim=img1$imagedim, seppix=2, hispec=FALSE, mask=img1$brainpos)
SB1 = basisprod(img1$S, B1)
fit111 = msma(SB1, comp=2)
ws = multirec(fit111, imagedim=img1$imagedim, B=B1, mask=img1$brainpos)
multicompplot(ws, template)
```

---

multirec *Multi components reconstruction*

---

**Description**

This is a function that returns the weight vector of multiple components obtained by the msma function applied after dimension reduction by the radial basis function to the same dimension as the original image.

**Usage**

```
multirec(
  object,
  imagedim,
  B = NULL,
  mask = NULL,
  midx = 1,
  comps = NULL,
  XY = c("X", "Y", "XY")[1],
  signflip = FALSE
)
```

**Arguments**

object	an object of class msma. Usually, a result of a call to msma
imagedim	a vector for original dimension.
B	a list or a matrix.
mask	a list or a matrix.
midx	a block number.
comps	a component sequence to be plotted.
XY	a character, indicating "X" or "Y". "XY" for the scatter plots using X and Y scores from msma.
signflip	a logical if the sign in the block is flipped to pose the super as positive.

**Details**

multirec requires the output result of msma function.

**Examples**

```
data(baseimg)
data(diffimg)
data(mask)
img1 = simbrain(baseimg = baseimg, diffimg = diffimg, mask=mask)
B1 = rbfunc(imagedim=img1$imagedim, seppix=2, hispec=FALSE, mask=img1$brainpos)
SB1 = basisprod(img1$S, B1)
```

```
fit111 = msma(SB1, comp=2)
ws = multirec(fit111, imagedim=img1$imagedim, B=B1, mask=img1$brainpos)
```

---

ptest

*Prediction Model Function*

---

## Description

This is the function that creates and evaluates the predictive model.

## Usage

```
ptest(
  object,
  Z = Z,
  newdata = NULL,
  testZ = NULL,
  regmethod = "glm",
  methods1 = c("boot", "boot632", "cv", "repeatedcv", "L00CV", "LGOCV")[4],
  metric = "ROC",
  number1 = 10,
  repeats1 = 5,
  params = NULL
)
```

## Arguments

object	a matrix indicating the explanatory variable(s), or an object of class msma, which is a result of a call to msma .
Z	a vector, response variable(s) for the construction of the prediction model. The length of Z is the number of subjects for the training.
newdata	a matrix for the prediction.
testZ	a vector, response variable(s) for the prediction evaluation. The length of testZ is the number of subjects for the validation.
regmethod	a character for the name of the prediction model. This corresponds to the method argument of the train function in the caret package.
methods1	a character for the name of the evaluation method.
metric	a character for the name of summary metric to select the optimal model.
number1	a number of folds or number of resampling iterations
repeats1	a number of repeats for the repeated cross-validation
params	a data frame with possible tuning values.

## Details

ptest requires the output result of msma function.

**Value**

object	an object of class "msma", usually, a result of a call to msma
trainout	a predictive model output from the train function in the caret package with scores computed by the msma function as predictors
scorecvroc	the training evaluation measure and values of the tuning parameters
evalmeasure	evaluation measures and information criterion for the msma model
traincnfmat	a confusion matrix in training data
predcnfmat	a confusion matrix in test data

**Examples**

```

data(baseimg)
data(diffimg)
data(mask)
data(template)
img1 = simbrain(baseimg = baseimg, diffimg = diffimg, mask=mask)
B1 = rbfunc(imagedim=img1$imagedim, seppix=2, hispec=FALSE, mask=img1$brainpos)
SB1 = basisprod(img1$S, B1)
fit111 = msma(SB1, comp=2)
predmodel = ptest(fit111, Z=img1$Z)

```

---

rbfunc

*Radial Basis Function*


---

**Description**

This makes a radial basis function.

**Usage**

```
rbfunc(imagedim, seppix, hispec = FALSE, mask = NULL, brainpos = NULL)
```

**Arguments**

imagedim	a vector indicating image three dimension.
seppix	a numeric. distance between knots.
hispec	a logical. TRUE produces a matrix output. FALSE produces a list output to reduce the data memory.
mask	a vector.
brainpos	a logical vector.

**Details**

rbfunc requires the dimensions of the original image to be applied and the knot interval. The output is obtained as a matrix, with the number of rows corresponding to the number of voxels in the original image and the number of columns determined by the knot spacing. By setting hispec = TRUE, you can get the output in list format with a smaller memory.

**Examples**

```
imagedim1=c(10,10,10)
```

```
B1 = rbfunc(imagedim=imagedim1, seppix=4, hispec=TRUE)
```

```
B2 = rbfunc(imagedim=imagedim1, seppix=4, hispec=FALSE)
```

---

 rec

---

*Reconstruction*


---

**Description**

This is a function that restores the vectorized image to its original dimensions, reduced in dimension by the radial basis function.

**Usage**

```
rec(Q, imagedim, B = NULL, mask = NULL)
```

**Arguments**

Q	a vector for reduced data.
imagedim	a vector for original dimension.
B	a list or a matrix indicating the basis function used in the dimension reduction.
mask	a list or a matrix indicating the mask image used in the dimension reduction.

**Details**

rec requires a vector to be converted to a array.

**Examples**

```
imagedim1=c(10,10,10)
```

```
recvec = rec(rnorm(prod(imagedim1)), imagedim1)
```

---

`sdevimg`*Standard Deviation Brain Data*

---

**Description**

The data is the standard deviation brain data. This represents the common standard deviation between the average images of healthy subjects and patients with Alzheimer's disease, and is used when generating artificial data.

**Usage**

```
data(sdevimg)
```

**Format**

A array

---

`simbrain`*Generate simulation data Function*

---

**Description**

This is a function for simulation data based on the real base brain image data and difference in brain between healthy and disease groups.

**Usage**

```
simbrain(  
  baseimg,  
  diffimg,  
  sdevimg = NULL,  
  mask = NULL,  
  n0 = 10,  
  c1 = 0.5,  
  sd1 = 0.01,  
  rho = NULL,  
  zeromask = FALSE,  
  reduce = c("no", "rd1", "rd2")[1],  
  output = c("rdata", "nifti")[1],  
  seed = 1  
)
```

**Arguments**

baseimg	an array for the basis image.
diffimg	an array for the difference image.
sdevimg	an array for the standard deviation image.
mask	an array for the mask image.
n0	a numeric, which is a sample size per group.
c1	a numeric, the strength of the difference
sd1	a numeric, standard deviation for the individual variation.
rho	a numeric, correlation coefficient in the noise
zeromask	a logical, whether mask the position with zero values for all subjects.
reduce	a vector.
output	a vector.
seed	a numeric for seed for random variables.

**Details**

simbrain requires a base brain image data and mean difference image data.

**Value**

S	data matrix
Z	binary group variable
brainpos	binary brain position.
imagedim	three dimensional vector for image dimension

**Examples**

```
data(baseimg)
data(diffimg)
sim1 = simbrain(baseimg = baseimg, diffimg = diffimg)
```

---

sizechange

*Size change Function*


---

**Description**

This is a function that changes the resolution of the image.

**Usage**

```
sizechange(img1, simscale = NULL, refsize = NULL, ...)
```



**Arguments**

img1	a array or nifti class, which is a image data to be changed the size.
simscale	a numeric.
resize	a vector with length 3, which is a size to be changed.
...	further arguments passed to or from other methods.

**Details**

sizechange requires the array data.

**Examples**

```
data(exbrain)
exbrain2 = sizechange(exbrain, simscale=1/2)
```

---

template

*Brain Template*

---

**Description**

The data is the brain tempalte. This is an average brain image, and is mainly used for overlaying analysis results.

**Usage**

```
data(template)
```

**Format**

A array

# Index

- \* **datasets**
  - atlas, 2
  - atlasdatasets, 3
  - baseimg, 4
  - diffimg, 7
  - exbrain, 7
  - mask, 9
  - sdevimg, 15
  - template, 17
- \* **documentation**
  - mand-package, 2
- \* **print**
  - atlastable, 3

atlas, 2

atlasdatasets, 3

atlastable, 3

baseimg, 4

basisprod, 4

coat, 5

diffimg, 7

exbrain, 7

imgdatamat, 8

mand-package, 2

mask, 9

multicoat, 9

multicomplot, 10

multirec, 11

print.atlastable (atlastable), 3

pctest, 12

rbfunc, 13

rec, 14

sdevimg, 15

simbrain, 15

sizechange, 16

template, 17