Package: metalcor (via r-universe)

October 30, 2026

Title Meta-Analysis of Correlated Genetic Association Studies

Version 1.0.5

Description The main function performs meta-analysis of genetic association study summary statistics that may be correlated due to cryptic relatedness or other confounders, generalizing inverse variance weighted methods. The function that estimates the correlation structure is also provided standalone. Another key innovation, the estimation of the correlation parameter from the median product of correlated standard normal variables, is provided, as well as a complete set of functions for their underlying distribution: density, cumulative, quantile, and random deviates. Described in Tu and Ochoa (2026) <doi:10.1016/j.xhgg.2026.100657>.

License GPL (>= 3)

Encoding UTF-8

Suggests knitr, rmarkdown, testthat (>= 3.0.0)

Imports stats, dplyr, rlang, tibble, tidyselect

Config/testthat/edition 3

VignetteBuilder knitr

URL https://github.com/OchoaLab/metalcor

BugReports https://github.com/OchoaLab/metalcor/issues

Config/roxygen2/version 8.1.1

NeedsCompilation no

Author Alejandro Ochoa [aut, cre] (ORCID: <https://orcid.org/0000-0003-4928-3403>), Tiffany Tu [aut] (ORCID: <https://orcid.org/0000-0002-9357-6660>)

Maintainer Alejandro Ochoa <alejandro.ochoa@duke.edu>

Repository https://cran.r-universe.dev

Date/Publication 2026-10-29 20:40:22 UTC

RemoteUrl https://github.com/cran/metalcor

RemoteRef HEAD

RemoteSha 0078797dfd2b22af9bad32581cebc927f7155016

Contents

estimate_R 2
metalcor 3
prodcor 5
rho_from_median 6

Index **8**

`estimate_R` *Estimate Covariance Matrix of Study Z-scores*

Description

The default "median" estimator is expected to be more robust to outliers (present due to causal variants and linkage disequilibrium). For completeness, the more standard "mean" estimator is also implemented, which is better when there are no outliers. The determinant is also tested, and if its absolute value is less than `tol` an error is triggered, warning the user that perhaps the same study was included multiple times (as this is otherwise expected to be extremely rare).

Usage

```
estimate_R(Z, median = TRUE, tol = 1e-08)
```

Arguments

`Z`	Matrix of z-scores, loci along rows, `S` studies along columns. Missing values can be present and are appropriately ignored.
`median`	If `TRUE`, uses `rho_from_median()` to calculate covariance values from sample medians; otherwise, sample means are used.
`tol`	Determinant tolerance for singularity test

Value

The `S`-by-`S` covariance matrix.

See Also

`rho_from_median()`

Examples

```
# simulate some correlated Z-scores for 3 studies and `m` loci
m <- 10000
# true correlation matrix
R <- matrix(
  c( 1.0, 0.2, 0.0,
     0.2, 1.0, 0.1,
     0.0, 0.1, 1.0 ),
  nrow = 3, ncol = 3
)
# use Cholesky decomposition to simulate via affine transform
L <- chol( R )
Z <- matrix( rnorm( m * 3 ), nrow = m, ncol = 3 ) %*% L

# calulate estimates
estimate_R( Z )
estimate_R( Z, median = FALSE )
# compare to naive covariance estimate, which does not assume zero mean for z-scores
cov( Z, use = 'pairwise.complete.obs' )
```

`metalcor` *Meta-Analysis of Correlated Genetic Association Studies*

Description

This function accepts the summary statistics from several studies, estimates their z-score correlation matrix, and performs the meta-analysis taking those correlations into account.

Usage

```
metalcor(
  studies,
  median = TRUE,
  df = 1,
  tol = 1e-08,
  useid = FALSE,
  noswitch = FALSE
)
```

Arguments

`studies`	A list of `S` studies, each of which is a data frame with the following required columns: `chr`, `pos`, `ref`, `alt`, `beta`, `se`, `n`. Column names have to match exactly. `chr`, `pos`, `ref` and `alt` are jointly used to match variants between studies (they must be unique for different variants, and be the same for the same variant), except if `noswitch` = `FALSE` (default) then `ref` and `alt` values may be switched in different studies. `chr` and `pos` are also used to sort variants after the studies

have been merged (please have numeric chr for best results). beta and se are required to perform meta-analysis. n is used to report locus-specific total sample sizes under missingness.

median — If TRUE (default), estimates correlations from sample medians instead of means. Passed to estimate_R().

df — Degree of freedom for calculating the p-values from the z-scores (default of 1 is best practically always).

tol — Determinant tolerance for singularity test of R estimate

useid — Additionally use IDs for matching and in outputs. If FALSE (default), IDs are totally ignored, even if inputs had them. If TRUE, id will be used to match variants (together with chr, pos, ref, alt), and there will be id in the output. IDs can be useful when ref/alt switches are allowed, to better disambiguate matching allele pairs, especially for unstandardized indels.

noswitch — Do not allow ref and alt switching. Default is to attempt to switch them for a locus and study if matching failed otherwise. noswitch = TRUE can be a good idea if you're sure most or all of your data is aligned to reference, or when insertions and deletions both appear and are symmetric (for example, in one allele pair "A/AB" and another "AB/A"), which can result in confusion.

Value

A list with two named elements:

- assoc: the meta-analyzed study, a tibble with columns id (if useid = TRUE), chr, pos, ref, alt, n, n_studies, beta, se, z, and p; sorted by chr and pos. If noswitch = FALSE (default), ref and alt values are those of the first study in which each variant appears, and if a subsequent study has then switched, the variant is aligned by changing the sign of its beta prior to meta-analysis.
- R: the S-by-S estimated z-score covariance matrix

See Also

estimate_R()

Examples

```
# construct two toy studies just to run example, with minimal columns
study1 <- data.frame(
  chr = 1,
  pos = 1:5,
  ref = 'A',
  alt = 'G',
  n = 2000,
  beta = rnorm( 5 ),
  se = abs( rnorm( 5 ) )
)
# note the second study is missing the 5th SNP, this is fine
# also, the 4th SNP is has switched ref/alt values
study2 <- data.frame(
```

```
  chr = 1,
  pos = 1:4,
  ref = c( 'A', 'A', 'A', 'G' ),
  alt = c( 'G', 'G', 'G', 'A' ),
  n = 5000,
  beta = rnorm( 4 ),
  se = abs( rnorm( 4 ) )
)

# gather the studies in a list
studies <- list( study1, study2 )
# this performs the meta-analysis modeling covariance!
out <- metalcor( studies )
# this is the meta-analyzed association table
out$assoc
# and this is the estimated study covariance matrix
out$R
```

`prodcor` *The Correlated Standard Normal Product Distribution*

Description

Density, cumulative, quantile, and random generation for the product of two correlated standard normal variables with correlation parameter `rho`.

Usage

```
dprodcor(x, rho)

pprodcor(x, rho, eps = 1e-08)

qprodcor(p, rho)

rprodcor(n, rho)
```

Arguments

`x`	Vector of quantiles.
`rho`	Correlation parameter, must be a scalar in [-1, 1].
`eps`	Near zero value to use for integrating around the divergence at `x=0`.
`p`	Vector of probabilities.
`n`	Number of observations. If `length(n) > 1`, the length is taken to be the number required.

Details

pprodcor does not have a closed form, so it is calculated by numerical integration of dprodcor. Furthermore, dprodcor(0) is infinite, so in order for numerical integration to succeed, we exclude the window c(-eps, eps) for arguments near zero. eps is the initial value, but if failure is still encountered, eps is incremented by factors of 10 until successful. (For positive arguments integration from above is used instead, subtracted from 1.) qprodcor also does not have a closed form, so it is calculated using a root finder on pprodcor, which makes it very slow.

Value

dprodcor gives the density, pprodcor the cumulative, and qprodcor the quantile function. rprodcor generates random deviates. The length of the result is determined by n for rnorm, and it is the length of x or p for the other functions.

References

Nadarajah, Saralees, and Tibor K. Pogány. "On the Distribution of the Product of Correlated Normal Random Variables." Comptes Rendus Mathematique 354, no. 2 (2016): 201–4. doi:10.1016/j.crma.2015.10.019.

Gaunt, Robert E. "The Basic Distributional Theory for the Product of Zero Mean Correlated Normal Random Variables." Statistica Neerlandica 76, no. 4 (2022): 450–70. doi:10.1111/stan.12267.

Examples

```
n <- 10
x <- rnorm( n )
p <- runif( n )
rho <- 0.8
dprodcor( x, rho )
pprodcor( x, rho )
qprodcor( p, rho )
rprodcor( n, rho )
```

---

rho_from_median — *Estimated Correlations from Sample Medians of the Correlated Standard Normal Product Distribution*

Description

This code implements estimation from the sample median of the correlation of a product of two correlated standard normal variables. While this estimation is straightforward from the mean, using the median requires the transformation implemented here because the distribution has heavy tails, so for positive correlations the median is much smaller than the mean. The median version is desired due to its robustness to outliers.

Usage

```
rho_from_median(x)
```

Arguments

x	vector of sample medians

Details

The highest correlation of `rho = 1` results in a median of only `q~0.455`. To permit application to arbitrary data, including data that does not satisfy assumptions and is therefore inflated, the function returns `x/q` for elements whose absolute values of `x/q` exceed 1, and can therefore return values that exceed [-1, 1].

Value

Vector of estimated correlations, extended for inflated cases.

See Also

`qprodcor()`

Examples

```
# a large number of samples is required for the median to yield an accurate estimate
n <- 10000
rho <- 0.3
x <- median( rprodcor( n, rho ) )
rho_from_median( x )
```

Index

dprodcor *(prodcor)*, 5

estimate_R, 2
estimate_R(), *4*

metalcor, 3

pprodcor *(prodcor)*, 5
prodcor, 5

qprodcor *(prodcor)*, 5
qprodcor(), *7*

rho_from_median, 6
rho_from_median(), *2*
rprodcor *(prodcor)*, 5