

Package: mlr3forecast (via r-universe)

July 22, 2026

Title Extending 'mlr3' to Time Series Forecasting

Version 0.1.0

Description Extends the 'mlr3' package and ecosystem to time series forecasting. Provides forecasting tasks, learners, resampling strategies, performance measures, and 'mlr3pipelines' operators for time-series feature engineering. Machine learning regression learners can be turned into forecasters through recursive and direct multi-step strategies.

License LGPL-3

URL <https://mlr3forecast.mlr-org.com>,
<https://github.com/mlr-org/mlr3forecast>

BugReports <https://github.com/mlr-org/mlr3forecast/issues>

Depends mlr3 (>= 1.7.0), R (>= 3.6.0)

Imports backports (>= 1.5.0), checkmate (>= 2.0.0), cli, data.table (>= 1.18.0), generics (>= 0.1.2), lgr, mlr3misc (>= 0.22.0), mlr3pipelines (>= 0.11.0), paradox (>= 1.0.1), R6 (>= 2.4.1), stats, utils

Suggests distributional, fabletools, feasts, forecast (>= 9.0.2), ggplot2 (>= 3.4.0), greybox, mlr3tuning, nnfor (>= 0.9.9), prophet (>= 1.1.7), Rcatch22, Rlgt (>= 0.2.3), rpart, smooth (>= 4.4.0), testthat (>= 3.2.0), tidyselect, timeSeries, tsbox, tscount (>= 1.4.3), tsfeatures, tsibble, tsibbledata, vctrs, vdiffir (>= 1.0.0), withr (>= 3.0.0), xts, zoo

Config/roxygen2/markdown TRUE

Config/roxygen2/r6 TRUE

Config/roxygen2/version 8.0.0

Config/testthat/edition 3

Config/testthat/parallel true

Encoding UTF-8

Collate 'DirectForecaster.R' 'LearnerFcst.R' 'zzz.R'
 'LearnerFcstAdam.R' 'LearnerFcstArfima.R' 'LearnerFcstArima.R'
 'LearnerFcstAutoAdam.R' 'LearnerFcstAutoArima.R'
 'LearnerFcstAutoCes.R' 'LearnerFcstAutoGum.R'
 'LearnerFcstAutoMsarima.R' 'LearnerFcstAutoSsarima.R'
 'LearnerFcstBaggedModel.R' 'LearnerFcstBats.R'
 'LearnerFcstCes.R' 'LearnerFcstCroston.R' 'LearnerFcstElm.R'
 'LearnerFcstEs.R' 'LearnerFcstEts.R' 'LearnerFcstForecast.R'
 'LearnerFcstGum.R' 'LearnerFcstHoltWinters.R'
 'LearnerFcstMean.R' 'LearnerFcstMlp.R' 'LearnerFcstMsarima.R'
 'LearnerFcstNnetar.R' 'LearnerFcstProphet.R'
 'LearnerFcstRandomWalk.R' 'LearnerFcstRlgt.R'
 'LearnerFcstSma.R' 'LearnerFcstSmooth.R' 'LearnerFcstSpline.R'
 'LearnerFcstSsarima.R' 'LearnerFcstStlm.R'
 'LearnerFcstStructTS.R' 'LearnerFcstTbats.R'
 'LearnerFcstTheta.R' 'LearnerFcstTscout.R' 'LearnerFcstTslm.R'
 'MeasureACF1.R' 'MeasureCoverage.R' 'MeasureDirectional.R'
 'MeasureMPE.R' 'MeasureMSIS.R' 'MeasurePinball.R'
 'MeasureScaled.R' 'MeasureWAPE.R' 'MeasureWinkler.R'
 'PipeOpFcstAvg.R' 'PipeOpFcstCatch22.R' 'PipeOpFcstFeasts.R'
 'PipeOpFcstFourier.R' 'PipeOpFcstLags.R' 'PipeOpFcstRolling.R'
 'PipeOpFcstSplitKey.R' 'PipeOpFcstTsfeats.R'
 'PipeOpFcstUniteKey.R' 'PipeOpTargetTrafo.R'
 'PipeOpTargetTrafoBoxCox.R' 'PredictionDataFcst.R'
 'PredictionFcst.R' 'RecursiveForecaster.R' 'ResamplingFcstCV.R'
 'ResamplingFcstHoldout.R' 'TaskFcst.R'
 'TaskFcstAirpassengers.R' 'TaskFcstElectricity.R'
 'TaskFcstLivestock.R' 'TaskFcstLynx.R' 'TaskFcstUsaccdeaths.R'
 'as_task_fcst.R' 'assertions.R' 'autoplot.R' 'bibentries.R'
 'direct_forecaster.R' 'forecast.R' 'helper.R'
 'helper_data_table.R' 'helper_freq.R' 'helper_key.R'
 'partition.R' 'pipeline_fcst_local.R' 'recursive_forecaster.R'
 'reexports.R' 'selector.R' 'tsf.R'

NeedsCompilation no

Author Maximilian Mücke [aut, cre] (ORCID:
 <<https://orcid.org/0009-0000-9432-9795>>), Marc Becker [aut]
 (ORCID: <<https://orcid.org/0000-0002-8115-0400>>), Bernd Bischl
 [aut] (ORCID: <<https://orcid.org/0000-0001-6002-6980>>)

Maintainer Maximilian Mücke <muecke.maximilian@gmail.com>

Repository <https://cran.r-universe.dev>

Date/Publication 2026-07-22 07:10:15 UTC

RemoteUrl <https://github.com/cran/mlr3forecast>

RemoteRef HEAD

RemoteSha 93d74da454e9af8e32e501885e4ac499f4140c66

Contents

mlr3forecast-package	4
as_task_fcst	5
autoplot.PredictionFcst	8
autoplot.TaskFcst	9
direct_forecaster	10
DirectForecaster	11
download_zenodo_record	14
forecast.Learner	15
generate_newdata	16
LearnerFcst	16
mlr_graphs_fcst.local	19
mlr_learners_fcst.adam	20
mlr_learners_fcst.arfima	23
mlr_learners_fcst.arima	26
mlr_learners_fcst.auto_adam	29
mlr_learners_fcst.auto_arima	32
mlr_learners_fcst.auto_ces	35
mlr_learners_fcst.auto_gum	38
mlr_learners_fcst.auto_msarima	40
mlr_learners_fcst.auto_ssarima	43
mlr_learners_fcst.bagged	45
mlr_learners_fcst.bats	48
mlr_learners_fcst.ces	51
mlr_learners_fcst.croston	53
mlr_learners_fcst.elm	56
mlr_learners_fcst.es	59
mlr_learners_fcst.ets	61
mlr_learners_fcst.gum	64
mlr_learners_fcst.holt_winters	67
mlr_learners_fcst.mean	70
mlr_learners_fcst.mlp	72
mlr_learners_fcst.msarima	75
mlr_learners_fcst.nnetar	77
mlr_learners_fcst.prophet	80
mlr_learners_fcst.random_walk	83
mlr_learners_fcst.rlg	85
mlr_learners_fcst.sma	88
mlr_learners_fcst.spline	90
mlr_learners_fcst.ssarima	93
mlr_learners_fcst.stlm	96
mlr_learners_fcst.struct_ts	98
mlr_learners_fcst.tbats	101
mlr_learners_fcst.theta	104
mlr_learners_fcst.tscount	106
mlr_learners_fcst.tslm	109
mlr_measures_fcst.acf1	111

mlr_measures_fcst.coverage	113
mlr_measures_fcst.mase	115
mlr_measures_fcst.mda	117
mlr_measures_fcst.mdpv	119
mlr_measures_fcst.mdv	121
mlr_measures_fcst.mpe	123
mlr_measures_fcst.msis	124
mlr_measures_fcst.pinball	127
mlr_measures_fcst.rmsse	129
mlr_measures_fcst.wape	131
mlr_measures_fcst.winkler	133
mlr_pipeops_fcst.catch22	135
mlr_pipeops_fcst.feasts	136
mlr_pipeops_fcst.fourier	137
mlr_pipeops_fcst.lags	139
mlr_pipeops_fcst.rolling	140
mlr_pipeops_fcst.splitkey	141
mlr_pipeops_fcst.targetboxcox	142
mlr_pipeops_fcst.targetdiff	144
mlr_pipeops_fcst.tsfeats	146
mlr_pipeops_fcst.unitekey	147
mlr_pipeops_fcstavg	148
mlr_resamplings_fcst.cv	150
mlr_resamplings_fcst.holdout	152
mlr_tasks_airpassengers	153
mlr_tasks_electricity	155
mlr_tasks_livestock	156
mlr_tasks_lynx	157
mlr_tasks_usaccdeaths	158
partition.TaskFcst	159
PredictionFcst	160
read_tsf	162
recursive_forecaster	163
RecursiveForecaster	164
selector_fcst_lags	167
selector_fcst_rolling	168
TaskFcst	168

Index**173**

Description

Extends the 'mlr3' package and ecosystem to time series forecasting. Provides forecasting tasks, learners, resampling strategies, performance measures, and 'mlr3pipelines' operators for time-series feature engineering. Machine learning regression learners can be turned into forecasters through recursive and direct multi-step strategies.

Author(s)

Maintainer: Maximilian Mücke <muecke.maximilian@gmail.com> ([ORCID](#))

Authors:

- Maximilian Mücke <muecke.maximilian@gmail.com> ([ORCID](#))
- Marc Becker <marcbecker@posteo.de> ([ORCID](#))
- Bernd Bischl <bernd.bischl@gmail.com> ([ORCID](#))

See Also

Useful links:

- <https://mlr3forecast.mlr-org.com>
- <https://github.com/mlr-org/mlr3forecast>
- Report bugs at <https://github.com/mlr-org/mlr3forecast/issues>

as_task_fcst

Convert to a Forecast Task

Description

Convert object to a [TaskFcst](#). This is a S3 generic. mlr3forecast ships with methods for the following objects:

1. [TaskFcst](#): ensure the identity
2. [data.frame\(\)](#) and [mlr3::DataBackend](#): provides an alternative to the constructor of [TaskFcst](#).
3. ts: from base R time series objects (univariate and multivariate).
4. zoo and xts: from zoo/xts time series objects.
5. timeSeries: from Rmetrics timeSeries objects.
6. tsf: from tsf format data.
7. tbl_ts: from tsibble objects.

Usage

```
as_task_fcst(x, ...)

as_tasks_fcst(x, ...)

## Default S3 method:
as_tasks_fcst(x, ...)

## S3 method for class 'list'
as_tasks_fcst(x, ...)

## S3 method for class 'TaskFcst'
as_task_fcst(x, clone = FALSE, ...)

## S3 method for class 'DataBackend'
as_task_fcst(
  x,
  target,
  order,
  key = character(),
  freq = NULL,
  id = deparse1(substitute(x)),
  label = NA_character_,
  ...
)

## S3 method for class 'data.frame'
as_task_fcst(
  x,
  target,
  order,
  key = character(),
  freq = NULL,
  id = deparse1(substitute(x)),
  label = NA_character_,
  ...
)

## S3 method for class 'tsf'
as_task_fcst(x, id = deparse1(substitute(x)), label = NA_character_, ...)

## S3 method for class 'ts'
as_task_fcst(
  x,
  freq = NULL,
  id = deparse1(substitute(x)),
  label = NA_character_,
  ...
)
```

```

)

## S3 method for class 'zoo'
as_task_fcst(
  x,
  freq = NULL,
  id = deparse1(substitute(x)),
  label = NA_character_,
  ...
)

## S3 method for class 'timeSeries'
as_task_fcst(
  x,
  freq = NULL,
  id = deparse1(substitute(x)),
  label = NA_character_,
  ...
)

## S3 method for class 'tbl_ts'
as_task_fcst(
  x,
  target,
  freq = NULL,
  id = deparse1(substitute(x)),
  label = NA_character_,
  ...
)

```

Arguments

x	(any) Object to convert.
...	(any) Additional arguments.
clone	(logical(1)) If TRUE, ensures that the returned object is not the same as the input x.
target	(character(1)) Name of the target column.
order	(character(1)) Name of the order column.
key	(character()) Name of the key column.
freq	(character(1) numeric(1) NULL) Frequency of the time series. Either a positive number or a seq()-compatible string, e.g.: "1 month", "day", "3 months", "1 hour", "week".

id	(character(1)) Id for the new task. Defaults to the (deparsed and substituted) name of the data argument.
label	(character(1)) Label for the new instance.

Value[TaskFcst](#).**Examples**

```
library(data.table)
airpassengers = tsbox::ts_dt(AirPassengers)
setnames(airpassengers, c("month", "passengers"))
as_task_fcst(airpassengers, target = "passengers", order = "month", freq = "month")
```

 autoplot.PredictionFcst

Plot for Forecast Predictions

Description

Generates a forecast plot for [PredictionFcst](#). The point forecast is drawn over the time index. When a task is supplied, the historical series is overlaid and the forecast region is drawn in a distinct colour, connected to the last historical observation for visual continuity.

For quantile forecasts, symmetric quantile pairs (e.g. the 10% and 90% quantiles) are drawn as shaded central prediction interval ribbons over the forecast region, shaded darker for narrower intervals and labelled by their level (e.g. 80, 95) in a legend. Quantiles without a symmetric partner are not drawn.

Usage

```
## S3 method for class 'PredictionFcst'
autoplot(
  object,
  task = NULL,
  theme = ggplot2::theme_minimal(),
  facets = FALSE,
  ...
)
```

Arguments

object	(PredictionFcst).
task	(TaskFcst NULL) Optional task providing the historical series to overlay. When NULL, only the forecast region is drawn.
theme	(ggplot2::theme()) The ggplot2::theme_minimal() is applied by default to all plots.
facets	(logical(1)) For keyed tasks, draw one panel per series instead of one coloured line per series. Default FALSE.
...	(any) Additional argument, passed down to the underlying geom or plot functions.

Value

[ggplot2::ggplot\(\)](#) object.

Examples

```
task = tsk("airpassengers")
learner = lrn("fcst.auto_arima")$train(task)
p = forecast(learner, task, h = 12)
ggplot2::autoplot(p, task = task)
```

autoplot.TaskFcst	<i>Plot for Forecast Tasks</i>
-------------------	--------------------------------

Description

Generates plots for [TaskFcst](#).

Usage

```
## S3 method for class 'TaskFcst'
autoplot(object, theme = ggplot2::theme\_minimal\(\), facets = FALSE, ...)
```

Arguments

object	(TaskFcst).
theme	(ggplot2::theme()) The ggplot2::theme_minimal() is applied by default to all plots.
facets	(logical(1)) For keyed tasks, draw one panel per series instead of one coloured line per series. Default FALSE.
...	(any) Additional argument, passed down to the underlying geom or plot functions.

Value

`ggplot2::ggplot()` object.

Examples

```
task = tsk("airpassengers")
ggplot2::autoplot(task)
```

direct_forecaster	Create a Direct Forecast Learner
-------------------	----------------------------------

Description

Function to create a [DirectForecaster](#) object. This is the recommended way to construct a direct forecaster. It is a thin wrapper around `DirectForecaster$new()`.

A direct forecaster trains a separate regression model per forecast horizon, so predictions never feed back into one another (no error accumulation). For the recursive strategy (a single iterated model) see [recursive_forecaster\(\)](#).

Usage

```
direct_forecaster(
  learner,
  lags,
  horizons,
  id = NULL,
  param_vals = list(),
  predict_type = NULL
)
```

Arguments

learner	(mlr3::Learner mlr3pipelines::Graph mlr3pipelines::PipeOp) A regression learner or a graph/PipeOp (without PipeOpFcstLags).
lags	(integer()) The base lag values. Exposed in <code>\$param_set</code> as <code>lags</code> , so it can be tuned via mlr3tuning::AutoTuner .
horizons	(integer()) Either a single integer <code>H</code> (expanded to <code>1:H</code>) or an integer vector of specific horizons. One model is trained per horizon.
id	(character(1) <code>NULL</code>) Identifier, default <code>NULL</code> (auto-generated from the learner id).
param_vals	(named list()) Hyperparameter values applied to every horizon model. Per-horizon hyperparameters are not currently supported.

`predict_type` (character(1) | NULL)
The predict type, default NULL.

Value

[DirectForecaster](#).

Examples

```
library(mlr3pipelines)

task = tsk("airpassengers")
split = partition(task, ratio = 0.8)

# one model per horizon
flrn = direct_forecaster(lrn("regr.rpart"), lags = 1:3, horizons = length(split$test))
flrn$train(task, split$train)
flrn$predict(task, split$test)
```

DirectForecaster	<i>Direct Multi-Step Forecast Learner</i>
------------------	---

Description

Trains a separate model for each forecast horizon. For horizon h with base lags $1:p$, model h uses lags $h:(h+p-1)$, so that at prediction time only observed values are needed. Unlike [RecursiveForecaster](#), predictions do not feed back into subsequent steps (no error accumulation).

Lag features are managed internally via lags. Do not add iterative feature PipeOps (property "fcst_iterative", e.g. [PipeOpFcstLags](#), [PipeOpFcstRolling](#)), which are rejected at construction.

Super class

[mlr3::Learner](#) -> DirectForecaster

Active bindings

`learner` ([mlr3::Learner](#))
The base regression learner.

`native_model` (named list())
The fitted models.

`lags` (integer())
The base lags.

`horizons` (integer())
The forecast horizons.

`param_set` ([paradox::ParamSet](#))
Set of hyperparameters.

marshaled (logical(1))

Whether the learner's model is currently in marshaled form.

predict_type (character(1))

Stores the currently active predict type.

Methods

Public methods:

- [DirectForecaster\\$new\(\)](#)
- [DirectForecaster\\$print\(\)](#)
- [DirectForecaster\\$marshal\(\)](#)
- [DirectForecaster\\$unmarshal\(\)](#)
- [DirectForecaster\\$clone\(\)](#)

[DirectForecaster\\$new\(\)](#): Creates a new instance of this [R6](#) class.

Usage:

```
DirectForecaster$new(
  learner,
  lags,
  horizons,
  id = NULL,
  param_vals = list(),
  predict_type = NULL
)
```

Arguments:

learner ([mlr3::Learner](#) | [mlr3pipelines::Graph](#) | [mlr3pipelines::PipeOp](#))

A regression learner or a graph/PipeOp (without [PipeOpFcstLags](#)).

lags (integer())

The base lag values. Exposed in `$param_set` as lags, so it can be tuned via [mlr3tuning::AutoTuner](#).

horizons (integer())

Either a single integer H (expanded to 1:H) or an integer vector of specific horizons. One model is trained per horizon. At predict time each test row is routed to the model matching its step-distance from the end of training, so with specific horizons (e.g. `c(2L, 4L, 6L)`) the test set may only contain rows at those exact steps ahead.

id (character(1) | NULL)

Identifier, default NULL (auto-generated from the learner id).

param_vals (named list())

Hyperparameter values applied to every horizon model. Per-horizon hyperparameters are not currently supported.

predict_type (character(1) | NULL)

The predict type, default NULL.

[DirectForecaster\\$print\(\)](#): Printer.

Usage:

```
DirectForecaster$print(...)
```

Arguments:

... (ignored).

`DirectForecaster$marshal()`: Marshal the learner's model.

Usage:

`DirectForecaster$marshal(...)`

Arguments:

... (any)

Additional arguments passed to `mlr3::marshal_model()`.

`DirectForecaster$unmarshal()`: Unmarshal the learner's model.

Usage:

`DirectForecaster$unmarshal(...)`

Arguments:

... (any)

Additional arguments passed to `mlr3::unmarshal_model()`.

`DirectForecaster$clone()`: The objects of this class are cloneable with this method.

Usage:

`DirectForecaster$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

Examples

```
library(mlr3pipelines)

task = tsk("airpassengers")
split = partition(task, ratio = 0.8)

# simple: one model per horizon
flrn = DirectForecaster$new(lrn("regr.rpart"), lags = 1:3, horizons = length(split$test))
flrn$train(task, split$train)
flrn$predict(task, split$test)

# or use the direct_forecaster() helper
flrn = direct_forecaster(lrn("regr.rpart"), lags = 1:3, horizons = length(split$test))
flrn$train(task, split$train)
flrn$predict(task, split$test)
```

download_zenodo_record

Download tsf file from Zenodo

Description

Downloads a tsf file from Zenodo using the provided record ID and dataset name.

Usage

```
download_zenodo_record(record_id = 4656222, dataset_name = "m3_yearly_dataset")
```

Arguments

record_id	(integer(1)) The Zenodo record ID.
dataset_name	(character(1)) The name of the dataset to download.

Value

([data.table::data.table\(\)](#)) with class "tsf". If the file contains a frequency or horizon, the "frequency" and "horizon" attributes are set, respectively.

References

Godaheva R, Bergmeir C, Webb GI, Hyndman RJ, Montero-Manso P (2021). "Monash time series forecasting archive." *arXiv preprint arXiv:2105.06643*.

Examples

```
## Not run:
library(data.table)
dt = download_zenodo_record(record_id = 4656222, dataset_name = "m3_yearly_dataset")

# optional renaming
setnames(dt, c("id", "date", "value"))

# transform into single task
task = as_task_fcst(dt)

# or split up for forecast learners that don't allow key columns
tasks = as_tasks_fcst(split(dt, by = "id", keep.by = FALSE))

# benchmark
learners = lrns(c("fcst.auto_arima", "fcst.ets", "fcst.random_walk"))
resampling = rsmpl("fcst.holdout", ratio = 0.8)
design = benchmark_grid(tasks, learners, resampling)
bmr = benchmark(design)
```

```
bmr$aggregate(msr("regr.rmse"))[, .(rmse = mean(regr.rmse)), by = learner_id]

## End(Not run)
```

forecast.Learner	<i>Forecast from a Trained Learner</i>
------------------	--

Description

Generates h future rows from the task's skeleton (using [generate_newdata\(\)](#)), optionally overlays user-supplied newdata onto those rows, and predicts with the trained learner via [mlr3::Learner\\$predict_newdata\(\)](#). Works with [RecursiveForecaster](#), [DirectForecaster](#), and classic `LearnerFcst*` forecasters.

Usage

```
## S3 method for class 'Learner'
forecast(object, task, h = 12L, newdata = NULL, ...)
```

Arguments

object	(mlr3::Learner) A trained forecast learner.
task	(TaskFcst) Provides the metadata needed to construct future rows: the order column (to extend the time index), key columns (for keyed tasks), freq, and the column-type schema expected by <code>predict_newdata()</code> . The task's data values are not used. Pass the training task or any other schema-compatible TaskFcst .
h	(<code>integer(1)</code>) Forecast horizon — number of future time steps per key.
newdata	(<code>data.frame()</code> <code>NULL</code>) Optional exogenous features for future rows. Must contain the order column (and any key columns for keyed tasks), and every row must match a row of the generated future grid. Columns other than those are overlaid onto the generated skeleton, while skeleton rows without a match keep NA.
...	(any) Ignored.

Value

[mlr3::Prediction](#).

generate_newdata	<i>Generate new data for a forecast task</i>
------------------	--

Description

Generate new data for a forecast task

Usage

```
generate_newdata(task, n = 1L)
```

Arguments

task	TaskFcst Task.
n	(integer(1)) Number of new data points to generate. Default 1L.

Details

Future dates are extrapolated by stepping the order column. For calendar freq (month/quarter/year), the origin's day-of-month is carried forward and clamped to each target month's last valid day. Other freqs use [base::seq\(\)](#). Month-end is not inferred, so use a first-of-month or period-style index for genuine month-end series.

Value

A [data.table::data.table\(\)](#) with n new data points.

LearnerFcst	<i>Forecast Learner</i>
-------------	-------------------------

Description

This Learner specializes [mlr3::LearnerRegr](#) for forecast problems:

- task_type is set to "fcst".
- Creates [mlr3::Predictions](#) of class [PredictionFcst](#).
- Possible values for predict_types are:
 - "response": Predicts a numeric response for each observation in the test set.
 - "se": Predicts the standard error for each value of response for each observation in the test set.
 - "distr": Probability distribution as [VectorDistribution](#) object (requires package [distr6](#), available via repository <https://raphaels1.r-universe.dev>).

- "quantiles": Predicts quantile estimates for each observation in the test set. Set `$quantiles` to specify the quantiles to predict and `$quantile_response` to specify the response quantile. See the [mlr3book](#) on quantile regression for more details.

Predefined learners can be found in the [dictionary mlr3::mlr_learners](#).

Super classes

`mlr3::Learner` -> `mlr3::LearnerRegr` -> `LearnerFcst`

Active bindings

`native_model` (any)
The fitted model.

Methods

Public methods:

- `LearnerFcst$new()`
- `LearnerFcst$clone()`

`LearnerFcst$new()`: Creates a new instance of this [R6](#) class.

Usage:

```
LearnerFcst$new(
  id,
  param_set = ps(),
  predict_types = "response",
  feature_types = character(),
  properties = character(),
  packages = character(),
  label = NA_character_,
  man = NA_character_
)
```

Arguments:

`id` (`character(1)`)

Identifier for the new instance.

`param_set` (`paradox::ParamSet`)

Set of hyperparameters.

`predict_types` (`character()`)

Supported predict types. Must be a subset of `mlr_reflections$learner_predict_types`.

`feature_types` (`character()`)

Feature types the learner operates on. Must be a subset of `mlr_reflections$task_feature_types`.

`properties` (`character()`)

Set of properties of the `mlr3::Learner`. Must be a subset of `mlr_reflections$learner_properties`. The following properties are currently standardized and understood by learners in [mlr3](#):

- "missings": The learner can handle missing values in the data.
- "weights": The learner supports observation weights.

- "offset": The learner can incorporate offset values to adjust predictions.
- "importance": The learner supports extraction of importance scores, i.e. comes with an `$importance()` extractor function (see section on optional extractors in [mlr3::Learner](#)).
- "selected_features": The learner supports extraction of the set of selected features, i.e. comes with a `$selected_features()` extractor function (see section on optional extractors in [mlr3::Learner](#)).
- "oob_error": The learner supports extraction of estimated out of bag error, i.e. comes with a `$oob_error()` extractor function (see section on optional extractors in [mlr3::Learner](#)).
- "validation": The learner can use a validation task during training.
- "internal_tuning": The learner is able to internally optimize hyperparameters (those are also tagged with "internal_tuning").
- "marshal": To save learners with this property, you need to call `$marshal()` first. If a learner is in a marshaled state, you call first need to call `$unmarshal()` to use its model, e.g. for prediction.
- "hotstart_forward": The learner supports to hotstart a model forward.
- "hotstart_backward": The learner supports hotstarting a model backward.
- "featureless": The learner does not use features.

`packages` (character())

Set of required packages. A warning is signaled by the constructor if at least one of the packages is not installed, but loaded (not attached) later on-demand via [requireNamespace\(\)](#).

`label` (character(1))

Label for the new instance.

`man` (character(1))

String in the format `[pkg]::[topic]` pointing to a manual page for this object. The referenced help package can be opened via method `$help()`.

`LearnerFcst$clone()`: The objects of this class are cloneable with this method.

Usage:

`LearnerFcst$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

See Also

- Chapter in the [mlr3book](https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners): https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners
- Package [mlr3learners](#) for a solid collection of essential learners.
- Package [mlr3extralearners](#) for more learners.
- Dictionary of Learners: [mlr3::mlr_learners](#)
- `as.data.table(mlr_learners)` for a table of available [Learners](#) in the running session (depending on the loaded packages).
- [mlr3pipelines](#) to combine learners with pre- and postprocessing steps.
- Package [mlr3viz](#) for some generic visualizations.
- Extension packages for additional task types:

- **mlr3proba** for probabilistic supervised regression and survival analysis.
- **mlr3cluster** for unsupervised clustering.
- **mlr3tuning** for tuning of hyperparameters, **mlr3tuningspaces** for established default tuning spaces.

Other Learner: `mlr_learners_fcst.adam`, `mlr_learners_fcst.arfima`, `mlr_learners_fcst.arima`, `mlr_learners_fcst.auto_adam`, `mlr_learners_fcst.auto_arima`, `mlr_learners_fcst.auto_ces`, `mlr_learners_fcst.auto_gum`, `mlr_learners_fcst.auto_msarima`, `mlr_learners_fcst.auto_ssarima`, `mlr_learners_fcst.bagged`, `mlr_learners_fcst.bats`, `mlr_learners_fcst.ces`, `mlr_learners_fcst.croston`, `mlr_learners_fcst.elm`, `mlr_learners_fcst.es`, `mlr_learners_fcst.ets`, `mlr_learners_fcst.gum`, `mlr_learners_fcst.holt_winters`, `mlr_learners_fcst.mean`, `mlr_learners_fcst.mlp`, `mlr_learners_fcst.msarima`, `mlr_learners_fcst.nnetar`, `mlr_learners_fcst.prophet`, `mlr_learners_fcst.random_walk`, `mlr_learners_fcst.rlgt`, `mlr_learners_fcst.sma`, `mlr_learners_fcst.spline`, `mlr_learners_fcst.ssarima`, `mlr_learners_fcst.stlm`, `mlr_learners_fcst.struct_ts`, `mlr_learners_fcst.tbats`, `mlr_learners_fcst.theta`, `mlr_learners_fcst.tscount`, `mlr_learners_fcst.tslm`

Examples

```
# get all forecast learners from mlr_learners:
lrns = mlr_learners$mget(mlr_learners$keys("^fcst"))
names(lrns)

# get a specific learner from mlr_learners:
mlr_learners$get("fcst.ets")
lrn("fcst.auto_arima")
```

`mlr_graphs_fcst.local` *Create a Graph to Fit Local Per-Series Forecast Models*

Description

Create a new [Graph](#) that wraps graph between `po("fcst.splitkey")` and `po("fcst.unitekey")`, fitting one local model per series of a keyed [TaskFcst](#) instead of one global model pooled across series.

All input arguments are cloned and have no references in common with the returned [Graph](#).

Usage

```
pipeline_fcst_local(graph, key = "key")
```

Arguments

`graph` ([Graph](#))
 Graph being wrapped between `po("fcst.splitkey")` and `po("fcst.unitekey")`.
 The graph should return NULL during training and a [PredictionFcst](#) during prediction.

key (character(1))
 Name of the rebuilt series-identity column in the united prediction's extra slot, default "key". Set it to the task's key column name to get predictions column-compatible with global forecasters such as [RecursiveForecaster](#).

Value

[Graph](#)

Examples

```
library(mlr3pipelines)
library(data.table)
dt = CJ(
  month = seq(as.Date("2024-01-01"), by = "month", length.out = 36L),
  id = factor(c("a", "b"))
)
dt[, value := rnorm(.N, mean = fifelse(id == "a", 10, 20))]
task = as_task_fcst(dt, target = "value", order = "month", key = "id", freq = "month")
flrn = as_learner(ppl("fcst.local", lrn("fcst.ets")))$train(task)
forecast(flrn, task, 12L)
```

mlr_learners_fcst.adam

ADAM Forecast Learner

Description

Augmented Dynamic Adaptive Model (ADAM) Forecast Learner model. Calls `smooth::adam()` from package **smooth**.

Dictionary

This `mlr3::Learner` can be instantiated via the dictionary `mlr3::mlr_learners` or with the associated sugar function `mlr3::lrn()`:

```
mlr_learners$get("fcst.adam")
lrn("fcst.adam")
```

Meta Information

- Task type: "fcst"
- Predict Types: "response", "quantiles"
- Feature Types: "logical", "integer", "numeric"
- Required Packages: **mlr3**, **mlr3forecast**, **smooth**

Parameters

Id	Type	Default	Levels
model	untyped	"ZZZ"	
lags	untyped	-	
orders	untyped	list(ar = 0, i = 0, ma = 0, select = FALSE)	
constant	logical	FALSE	TRUE, FALSE
regressors	character	use	use, select, adapt
occurrence	character	none	none, auto, fixed, general, odds-ratio, inverse-odds-ratio
distribution	character	default	default, dnorm, dlaplace, ds, dgnorm, dlnorm, dinvgaus
loss	character	likelihood	likelihood, MSE, MAE, HAM, LASSO, RIDGE, MSE
outliers	character	ignore	ignore, use, select
holdout	logical	FALSE	TRUE, FALSE
persistence	untyped	NULL	
phi	numeric	NULL	
initial	character	backcasting	backcasting, optimal, two-stage, complete
arma	untyped	NULL	
ic	character	AICc	AICc, AIC, BIC, BICc
bounds	character	usual	usual, admissible, none
silent	logical	TRUE	TRUE, FALSE
ets	character	conventional	conventional, adam

Super classes

```
mlr3::Learner -> mlr3::LearnerRegr -> LearnerFcst -> LearnerFcstSmooth -> LearnerFcstAdam
```

Methods**Public methods:**

- `LearnerFcstAdam$new()`
- `LearnerFcstAdam$clone()`

`LearnerFcstAdam$new()`: Creates a new instance of this [R6](#) class.

Usage:

```
LearnerFcstAdam$new()
```

`LearnerFcstAdam$clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerFcstAdam$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

References

Svetunkov I (2023). “Smooth forecasting with the smooth package in R.” 2301.01790, <https://arxiv.org/abs/2301.01790>.

Svetunkov I (2023). *Forecasting and Analytics with the Augmented Dynamic Adaptive Model (ADAM)*, 1st edition. Chapman and Hall/CRC. doi:10.1201/9781003452652. <https://openforecast.org/adam/>.

See Also

- Chapter in the **mlr3book**: https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners
- Package **mlr3learners** for a solid collection of essential learners.
- Package **mlr3extralearners** for more learners.
- **Dictionary of Learners**: `mlr3::mlr_learners`
- `as.data.table(mlr_learners)` for a table of available **Learners** in the running session (depending on the loaded packages).
- **mlr3pipelines** to combine learners with pre- and postprocessing steps.
- Package **mlr3viz** for some generic visualizations.
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.
- **mlr3tuning** for tuning of hyperparameters, **mlr3tuningpaces** for established default tuning spaces.

Other Learner: `LearnerFcst`, `mlr_learners_fcst.arfima`, `mlr_learners_fcst.arima`, `mlr_learners_fcst.auto_adam`, `mlr_learners_fcst.auto_arima`, `mlr_learners_fcst.auto_ces`, `mlr_learners_fcst.auto_gum`, `mlr_learners_fcst.auto_msarima`, `mlr_learners_fcst.auto_ssarima`, `mlr_learners_fcst.bagged`, `mlr_learners_fcst.bats`, `mlr_learners_fcst.ces`, `mlr_learners_fcst.croston`, `mlr_learners_fcst.elm`, `mlr_learners_fcst.es`, `mlr_learners_fcst.ets`, `mlr_learners_fcst.gum`, `mlr_learners_fcst.holt_winters`, `mlr_learners_fcst.mean`, `mlr_learners_fcst.mlp`, `mlr_learners_fcst.msarima`, `mlr_learners_fcst.nnetar`, `mlr_learners_fcst.prophet`, `mlr_learners_fcst.random_walk`, `mlr_learners_fcst.rlg`, `mlr_learners_fcst.sma`, `mlr_learners_fcst.spline`, `mlr_learners_fcst.ssarima`, `mlr_learners_fcst.stlm`, `mlr_learners_fcst.struct_ts`, `mlr_learners_fcst.tbats`, `mlr_learners_fcst.theta`, `mlr_learners_fcst.tscou`, `mlr_learners_fcst.tslm`

Examples

```
# Define the Learner and set parameter values
learner = lrn("fcst.adam")
print(learner)

# Define a Task
task = tsk("airpassengers")

# Create train and test set
ids = partition(task)
```

```

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)

# Print the model
print(learner$model)

# Importance method
if ("importance" %in% learner$properties) print(learner$importance())

# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()

```

mlr_learners_fcst.arfima

ARFIMA Forecast Learner

Description

ARFIMA model. Calls `forecast::arfima()` from package **forecast**.

Dictionary

This `mlr3::Learner` can be instantiated via the dictionary `mlr3::mlr_learners` or with the associated sugar function `mlr3::lrn()`:

```

mlr_learners$get("fcst.arfima")
lrn("fcst.arfima")

```

Meta Information

- Task type: “fcst”
- Predict Types: “response”, “quantiles”
- Feature Types: “logical”, “integer”, “numeric”
- Required Packages: **mlr3**, **mlr3forecast**, **forecast**

Parameters

Id	Type	Default	Levels	Range
drange	untyped	c(0, 0.5)		-
estim	character	mle	mle, ls	-
lambda	untyped	NULL		-
biasadj	logical	FALSE	TRUE, FALSE	-
simulate	logical	FALSE	TRUE, FALSE	-

bootstrap	logical	FALSE	TRUE, FALSE	-
npaths	integer	5000		[1, ∞)
max.p	integer	5		[0, ∞)
max.q	integer	5		[0, ∞)
max.order	integer	5		[0, ∞)
start.p	integer	2		[0, ∞)
start.q	integer	2		[0, ∞)
ic	character	aicc	aicc, aic, bic	-
stepwise	logical	TRUE	TRUE, FALSE	-
nmodels	integer	94		[0, ∞)
trace	logical	FALSE	TRUE, FALSE	-
approximation	logical	-	TRUE, FALSE	-
method	character	NULL	CSS-ML, ML, CSS	-
truncate	integer	NULL		[1, ∞)
parallel	logical	FALSE	TRUE, FALSE	-
num.cores	integer	2		[1, ∞)
transform.pars	logical	TRUE	TRUE, FALSE	-
fixed	untyped	NULL		-
init	untyped	NULL		-
SSinit	character	Gardner1980	Gardner1980, Rossignol2011	-
n.cond	integer	-		[1, ∞)
optim.method	character	BFGS	Nelder-Mead, BFGS, CG, L-BFGS-B, SANN, Brent	-
optim.control	untyped	list()		-
kappa	numeric	1e+06		$(-\infty, \infty)$

Super classes

`mlr3::Learner -> mlr3::LearnerRegr -> LearnerFcst -> LearnerFcstForecast -> LearnerFcstArfima`

Methods

Public methods:

- `LearnerFcstArfima$new()`
- `LearnerFcstArfima$clone()`

`LearnerFcstArfima$new()`: Creates a new instance of this [R6](#) class.

Usage:

```
LearnerFcstArfima$new()
```

`LearnerFcstArfima$clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerFcstArfima$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

References

- Haslett J, Raftery AE (1989). “Space-time Modelling with Long-memory Dependence: Assessing Ireland’s Wind Power Resource.” *Journal of the Royal Statistical Society: Series C (Applied Statistics)*, **38**(1), 1–21.
- Hyndman RJ, Khandakar Y (2008). “Automatic Time Series Forecasting: The forecast Package for R.” *Journal of Statistical Software*, **27**(3), 1–22. doi:10.18637/jss.v027.i03.

See Also

- Chapter in the **mlr3book**: https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners
- Package **mlr3learners** for a solid collection of essential learners.
- Package **mlr3extralearners** for more learners.
- **Dictionary of Learners**: `mlr3::mlr_learners`
- `as.data.table(mlr_learners)` for a table of available **Learners** in the running session (depending on the loaded packages).
- **mlr3pipelines** to combine learners with pre- and postprocessing steps.
- Package **mlr3viz** for some generic visualizations.
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.
- **mlr3tuning** for tuning of hyperparameters, **mlr3tuningpaces** for established default tuning spaces.

Other Learner: `LearnerFcst`, `mlr_learners_fcst.adam`, `mlr_learners_fcst.arima`, `mlr_learners_fcst.auto_adam`, `mlr_learners_fcst.auto_arima`, `mlr_learners_fcst.auto_ces`, `mlr_learners_fcst.auto_gum`, `mlr_learners_fcst.auto_msarima`, `mlr_learners_fcst.auto_ssarima`, `mlr_learners_fcst.bagged`, `mlr_learners_fcst.bats`, `mlr_learners_fcst.ces`, `mlr_learners_fcst.croston`, `mlr_learners_fcst.elm`, `mlr_learners_fcst.es`, `mlr_learners_fcst.ets`, `mlr_learners_fcst.gum`, `mlr_learners_fcst.holt_winters`, `mlr_learners_fcst.mean`, `mlr_learners_fcst.mlp`, `mlr_learners_fcst.msarima`, `mlr_learners_fcst.nnetar`, `mlr_learners_fcst.prophet`, `mlr_learners_fcst.random_walk`, `mlr_learners_fcst.rlg`, `mlr_learners_fcst.sma`, `mlr_learners_fcst.spline`, `mlr_learners_fcst.ssarima`, `mlr_learners_fcst.stlm`, `mlr_learners_fcst.struct_ts`, `mlr_learners_fcst.tbats`, `mlr_learners_fcst.theta`, `mlr_learners_fcst.tscou`, `mlr_learners_fcst.tslm`

Examples

```
# Define the Learner and set parameter values
learner = lrn("fcst.arfima")
print(learner)

# Define a Task
task = tsk("airpassengers")

# Create train and test set
ids = partition(task)
```

```
# Train the learner on the training ids
learner$train(task, row_ids = ids$train)

# Print the model
print(learner$model)

# Importance method
if ("importance" %in% learner$properties) print(learner$importance())

# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()
```

mlr_learners_fcst.arma
<i>ARIMA Forecast Learner</i>

Description

Autoregressive Integrated Moving Average Forecast (ARIMA) model. Calls `forecast::Arima()` from package **forecast**.

Dictionary

This `mlr3::Learner` can be instantiated via the dictionary `mlr3::mlr_learners` or with the associated sugar function `mlr3::lrn()`:

```
mlr_learners$get("fcst.arma")
lrn("fcst.arma")
```

Meta Information

- Task type: “fcst”
- Predict Types: “response”, “quantiles”
- Feature Types: “logical”, “integer”, “numeric”
- Required Packages: **mlr3**, **mlr3forecast**, **forecast**

Parameters

Id	Type	Default	Levels	Range
order	untyped	c(0L, 0L, 0L)		-
seasonal	untyped	c(0L, 0L, 0L)		-
include.mean	logical	TRUE	TRUE, FALSE	-
include.drift	logical	FALSE	TRUE, FALSE	-

include.constant	logical	FALSE	TRUE, FALSE	-
lambda	untyped	NULL		-
biasadj	logical	FALSE	TRUE, FALSE	-
method	character	CSS-ML	CSS-ML, ML, CSS	-
simulate	logical	FALSE	TRUE, FALSE	-
bootstrap	logical	FALSE	TRUE, FALSE	-
npaths	integer	5000		$[1, \infty)$
transform.pars	logical	TRUE	TRUE, FALSE	-
fixed	untyped	NULL		-
init	untyped	NULL		-
SSinit	character	Gardner1980	Gardner1980, Rossignol2011	-
n.cond	integer	-		$[1, \infty)$
optim.method	character	BFGS	Nelder-Mead, BFGS, CG, L-BFGS-B, SANN, Brent	-
optim.control	untyped	list()		-
kappa	numeric	1e+06		$(-\infty, \infty)$

Super classes

```
mlr3::Learner -> mlr3::LearnerRegr -> LearnerFcst -> LearnerFcstForecast -> LearnerFcstArima
```

Methods

Public methods:

- `LearnerFcstArima$new()`
- `LearnerFcstArima$clone()`

`LearnerFcstArima$new()`: Creates a new instance of this [R6](#) class.

Usage:

```
LearnerFcstArima$new()
```

`LearnerFcstArima$clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerFcstArima$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

References

Hyndman RJ, Athanasopoulos G (2018). *Forecasting: principles and practice*, 2nd edition. OTexts, Melbourne, Australia. <https://OTexts.com/fpp2/>.

See Also

- Chapter in the **mlr3book**: https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners
- Package **mlr3learners** for a solid collection of essential learners.
- Package **mlr3extralearners** for more learners.
- Dictionary of Learners: `mlr3::mlr_learners`
- `as.data.table(mlr_learners)` for a table of available **Learners** in the running session (depending on the loaded packages).
- **mlr3pipelines** to combine learners with pre- and postprocessing steps.
- Package **mlr3viz** for some generic visualizations.
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.
- **mlr3tuning** for tuning of hyperparameters, **mlr3tuningspaces** for established default tuning spaces.

Other Learner: `LearnerFcst`, `mlr_learners_fcst.adam`, `mlr_learners_fcst.arfima`, `mlr_learners_fcst.auto_adam`, `mlr_learners_fcst.auto_arma`, `mlr_learners_fcst.auto_ces`, `mlr_learners_fcst.auto_gum`, `mlr_learners_fcst.auto_msarima`, `mlr_learners_fcst.auto_ssarima`, `mlr_learners_fcst.bagged`, `mlr_learners_fcst.bats`, `mlr_learners_fcst.ces`, `mlr_learners_fcst.croston`, `mlr_learners_fcst.elm`, `mlr_learners_fcst.es`, `mlr_learners_fcst.ets`, `mlr_learners_fcst.gum`, `mlr_learners_fcst.holt_winters`, `mlr_learners_fcst.mean`, `mlr_learners_fcst.mlp`, `mlr_learners_fcst.msarima`, `mlr_learners_fcst.nnetar`, `mlr_learners_fcst.prophet`, `mlr_learners_fcst.random_walk`, `mlr_learners_fcst.rlg`, `mlr_learners_fcst.sma`, `mlr_learners_fcst.spline`, `mlr_learners_fcst.ssarima`, `mlr_learners_fcst.stlm`, `mlr_learners_fcst.struct_ts`, `mlr_learners_fcst.tbats`, `mlr_learners_fcst.theta`, `mlr_learners_fcst.tscou`, `mlr_learners_fcst.tsml`

Examples

```
# Define the Learner and set parameter values
learner = lrn("fcst.arma")
print(learner)

# Define a Task
task = tsk("airpassengers")

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)

# Print the model
print(learner$model)

# Importance method
if ("importance" %in% learner$properties) print(learner$importance())
```

```
# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()
```

mlr_learners_fcst.auto_adam
<i>Auto ADAM Forecast Learner</i>

Description

Auto Augmented Dynamic Adaptive Model (ADAM) model. Calls `smooth::auto.adam()` from package **smooth**.

Dictionary

This `mlr3::Learner` can be instantiated via the dictionary `mlr3::mlr_learners` or with the associated sugar function `mlr3::lrn()`:

```
mlr_learners$get("fcst.auto_adam")
lrn("fcst.auto_adam")
```

Meta Information

- Task type: “fcst”
- Predict Types: “response”, “quantiles”
- Feature Types: “logical”, “integer”, “numeric”
- Required Packages: **mlr3**, **mlr3forecast**, **smooth**

Parameters

Id	Type	Default	Levels
model	untyped	"ZZZ"	
lags	untyped	-	
orders	untyped	list(ar = c(3, 3), i = c(2, 1), ma = c(3, 3), select = TRUE)	
regressors	character	use	use, select, adapt
occurrence	character	none	none, auto, fixed, general, odds-ratio, inv
distribution	character	dnorm	dnorm, dlaplace, ds, dgnorm, dlnorm, di
outliers	character	ignore	ignore, use, select
holdout	logical	FALSE	TRUE, FALSE
persistence	untyped	NULL	
phi	numeric	NULL	
initial	character	backcasting	backcasting, optimal, two-stage, comple
arma	untyped	NULL	

ic	character	AICc	AICc, AIC, BIC, BICc
bounds	character	usual	usual, admissible, none
silent	logical	TRUE	TRUE, FALSE
parallel	logical	FALSE	TRUE, FALSE
ets	character	conventional	conventional, adam

Super classes

`mlr3::Learner -> mlr3::LearnerRegr -> LearnerFcst -> LearnerFcstSmooth -> LearnerFcstAutoAdam`

Methods

Public methods:

- `LearnerFcstAutoAdam$new()`
- `LearnerFcstAutoAdam$clone()`

`LearnerFcstAutoAdam$new()`: Creates a new instance of this [R6](#) class.

Usage:

```
LearnerFcstAutoAdam$new()
```

`LearnerFcstAutoAdam$clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerFcstAutoAdam$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

References

Svetunkov I (2023). “Smooth forecasting with the smooth package in R.” 2301.01790, <https://arxiv.org/abs/2301.01790>.

Svetunkov I (2023). *Forecasting and Analytics with the Augmented Dynamic Adaptive Model (ADAM)*, 1st edition. Chapman and Hall/CRC. doi:10.1201/9781003452652. <https://openforecast.org/adam/>.

See Also

- Chapter in the [mlr3book](https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners): https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners
- Package **mlr3learners** for a solid collection of essential learners.
- Package **mlr3extralearners** for more learners.
- Dictionary of [Learners](#): `mlr3::mlr_learners`
- `as.data.table(mlr_learners)` for a table of available [Learners](#) in the running session (depending on the loaded packages).

- **mlr3pipelines** to combine learners with pre- and postprocessing steps.
- Package **mlr3viz** for some generic visualizations.
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.
- **mlr3tuning** for tuning of hyperparameters, **mlr3tuningspaces** for established default tuning spaces.

Other Learner: `LearnerFcst`, `mlr_learners_fcst.adam`, `mlr_learners_fcst.arfima`, `mlr_learners_fcst.arima`, `mlr_learners_fcst.auto_arima`, `mlr_learners_fcst.auto_ces`, `mlr_learners_fcst.auto_gum`, `mlr_learners_fcst.auto_msarima`, `mlr_learners_fcst.auto_ssarima`, `mlr_learners_fcst.bagged`, `mlr_learners_fcst.bats`, `mlr_learners_fcst.ces`, `mlr_learners_fcst.croston`, `mlr_learners_fcst.elm`, `mlr_learners_fcst.es`, `mlr_learners_fcst.ets`, `mlr_learners_fcst.gum`, `mlr_learners_fcst.holt_winters`, `mlr_learners_fcst.mean`, `mlr_learners_fcst.mlp`, `mlr_learners_fcst.msarima`, `mlr_learners_fcst.nnetar`, `mlr_learners_fcst.prophet`, `mlr_learners_fcst.random_walk`, `mlr_learners_fcst.rlg`, `mlr_learners_fcst.sma`, `mlr_learners_fcst.spline`, `mlr_learners_fcst.ssarima`, `mlr_learners_fcst.stlm`, `mlr_learners_fcst.struct_ts`, `mlr_learners_fcst.tbats`, `mlr_learners_fcst.theta`, `mlr_learners_fcst.tscou`, `mlr_learners_fcst.tslm`

Examples

```
# Define the Learner and set parameter values
learner = lrn("fcst.auto_adam")
print(learner)

# Define a Task
task = tsk("airpassengers")

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)

# Print the model
print(learner$model)

# Importance method
if ("importance" %in% learner$properties) print(learner$importance())

# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()
```

```
mlr_learners_fcst.auto_arima
```

Auto ARIMA Forecast Learner

Description

Auto ARIMA model. Calls `forecast::auto.arima()` from package **forecast**.

Dictionary

This `mlr3::Learner` can be instantiated via the dictionary `mlr3::mlr_learners` or with the associated sugar function `mlr3::lrn()`:

```
mlr_learners$get("fcst.auto_arima")
lrn("fcst.auto_arima")
```

Meta Information

- Task type: “fcst”
- Predict Types: “response”, “quantiles”
- Feature Types: “logical”, “integer”, “numeric”
- Required Packages: **mlr3**, **mlr3forecast**, **forecast**

Parameters

Id	Type	Default	Levels	Range
d	integer	NA		$[0, \infty)$
D	integer	NA		$[0, \infty)$
max.p	integer	5		$[0, \infty)$
max.q	integer	5		$[0, \infty)$
max.P	integer	2		$[0, \infty)$
max.Q	integer	2		$[0, \infty)$
max.order	integer	5		$[0, \infty)$
max.d	integer	2		$[0, \infty)$
max.D	integer	1		$[0, \infty)$
start.p	integer	2		$[0, \infty)$
start.q	integer	2		$[0, \infty)$
start.P	integer	1		$[0, \infty)$
start.Q	integer	1		$[0, \infty)$
stationary	logical	FALSE	TRUE, FALSE	-
seasonal	logical	TRUE	TRUE, FALSE	-
ic	character	aicc	aicc, aic, bic	-
stepwise	logical	TRUE	TRUE, FALSE	-
nmodels	integer	94		$[0, \infty)$
trace	logical	FALSE	TRUE, FALSE	-

approximation	logical	-	TRUE, FALSE	-
method	character	NULL	CSS-ML, ML, CSS	-
truncate	integer	NULL		$[1, \infty)$
test	character	kpss	kpss, adf, pp	-
test.args	untyped	list()		-
seasonal.test	character	seas	seas, ocsb, hegy, ch	-
seasonal.test.args	untyped	list()		-
allowdrift	logical	TRUE	TRUE, FALSE	-
allowmean	logical	TRUE	TRUE, FALSE	-
biasadj	logical	FALSE	TRUE, FALSE	-
parallel	logical	FALSE	TRUE, FALSE	-
num.cores	integer	2		$[1, \infty)$
lambda	untyped	NULL		-
simulate	logical	FALSE	TRUE, FALSE	-
bootstrap	logical	FALSE	TRUE, FALSE	-
npaths	integer	5000		$[1, \infty)$
transform.pars	logical	TRUE	TRUE, FALSE	-
fixed	untyped	NULL		-
init	untyped	NULL		-
SSinit	character	Gardner1980	Gardner1980, Rossignol2011	-
n.cond	integer	-		$[1, \infty)$
optim.method	character	BFGS	Nelder-Mead, BFGS, CG, L-BFGS-B, SANN, Brent	-
optim.control	untyped	list()		-
kappa	numeric	1e+06		$(-\infty, \infty)$

Super classes

`mlr3::Learner -> mlr3::LearnerRegr -> LearnerFcst -> LearnerFcstForecast -> LearnerFcstAutoArima`

Methods

Public methods:

- `LearnerFcstAutoArima$new()`
- `LearnerFcstAutoArima$clone()`

`LearnerFcstAutoArima$new()`: Creates a new instance of this [R6](#) class.

Usage:

```
LearnerFcstAutoArima$new()
```

`LearnerFcstAutoArima$clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerFcstAutoArima$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

References

- Hyndman RJ, Khandakar Y (2008). “Automatic Time Series Forecasting: The forecast Package for R.” *Journal of Statistical Software*, **27**(3), 1–22. doi:10.18637/jss.v027.i03.
- Wang X, Smith K, Hyndman R (2006). “Characteristic-based clustering for time series data.” *Data Mining and Knowledge Discovery*, **13**, 335–364.

See Also

- Chapter in the **mlr3book**: https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners
- Package **mlr3learners** for a solid collection of essential learners.
- Package **mlr3extralearners** for more learners.
- **Dictionary of Learners**: `mlr3::mlr_learners`
- `as.data.table(mlr_learners)` for a table of available **Learners** in the running session (depending on the loaded packages).
- **mlr3pipelines** to combine learners with pre- and postprocessing steps.
- Package **mlr3viz** for some generic visualizations.
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.
- **mlr3tuning** for tuning of hyperparameters, **mlr3tuningspaces** for established default tuning spaces.

Other Learner: `LearnerFcst`, `mlr_learners_fcst.adam`, `mlr_learners_fcst.arfima`, `mlr_learners_fcst.arima`, `mlr_learners_fcst.auto_adam`, `mlr_learners_fcst.auto_ces`, `mlr_learners_fcst.auto_gum`, `mlr_learners_fcst.auto_msarima`, `mlr_learners_fcst.auto_ssarima`, `mlr_learners_fcst.bagged`, `mlr_learners_fcst.bats`, `mlr_learners_fcst.ces`, `mlr_learners_fcst.croston`, `mlr_learners_fcst.elm`, `mlr_learners_fcst.es`, `mlr_learners_fcst.ets`, `mlr_learners_fcst.gum`, `mlr_learners_fcst.holt_winters`, `mlr_learners_fcst.mean`, `mlr_learners_fcst.mlp`, `mlr_learners_fcst.msarima`, `mlr_learners_fcst.nnetar`, `mlr_learners_fcst.prophet`, `mlr_learners_fcst.random_walk`, `mlr_learners_fcst.rlg`, `mlr_learners_fcst.sma`, `mlr_learners_fcst.spline`, `mlr_learners_fcst.ssarima`, `mlr_learners_fcst.stlm`, `mlr_learners_fcst.struct_ts`, `mlr_learners_fcst.tbats`, `mlr_learners_fcst.theta`, `mlr_learners_fcst.tscou`, `mlr_learners_fcst.tslm`

Examples

```
# Define the Learner and set parameter values
learner = lrn("fcst.auto_arima")
print(learner)

# Define a Task
task = tsk("airpassengers")

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
```

```
learner$train(task, row_ids = ids$train)

# Print the model
print(learner$model)

# Importance method
if ("importance" %in% learner$properties) print(learner$importance())

# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()
```

mlr_learners_fcst.auto_ces
Auto CES Forecast Learner

Description

Auto Complex Exponential Smoothing (CES) model. Calls `smooth::auto.ces()` from package **smooth**.

Dictionary

This `mlr3::Learner` can be instantiated via the dictionary `mlr3::mlr_learners` or with the associated sugar function `mlr3::lrn()`:

```
mlr_learners$get("fcst.auto_ces")
lrn("fcst.auto_ces")
```

Meta Information

- Task type: “fcst”
- Predict Types: “response”, “quantiles”
- Feature Types: “logical”, “integer”, “numeric”
- Required Packages: **mlr3**, **mlr3forecast**, **smooth**

Parameters

Id	Type	Default	Levels
seasonality	character	none	none, simple, partial, full
lags	untyped	-	
initial	character	backcasting	backcasting, optimal, two-stage, complete
ic	character	AICc	AICc, AIC, BIC, BICc
loss	character	likelihood	likelihood, MSE, MAE, HAM, MSEh, TMSE, GTMSE, MSCE, GPL

holdout	logical	FALSE	TRUE, FALSE
bounds	character	admissible	admissible, none
silent	logical	TRUE	TRUE, FALSE
regressors	character	use	use, select, adapt

Super classes

`mlr3::Learner -> mlr3::LearnerRegr -> LearnerFcst -> LearnerFcstSmooth -> LearnerFcstAutoCes`

Methods

Public methods:

- `LearnerFcstAutoCes$new()`
- `LearnerFcstAutoCes$clone()`

`LearnerFcstAutoCes$new()`: Creates a new instance of this [R6](#) class.

Usage:

```
LearnerFcstAutoCes$new()
```

`LearnerFcstAutoCes$clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerFcstAutoCes$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

References

Svetunkov I (2023). “Smooth forecasting with the smooth package in R.” 2301.01790, <https://arxiv.org/abs/2301.01790>.

Svetunkov I (2023). *Forecasting and Analytics with the Augmented Dynamic Adaptive Model (ADAM)*, 1st edition. Chapman and Hall/CRC. doi:10.1201/9781003452652. <https://openforecast.org/adam/>.

See Also

- Chapter in the [mlr3book](https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners): https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners
- Package [mlr3learners](#) for a solid collection of essential learners.
- Package [mlr3extralearners](#) for more learners.
- Dictionary of [Learners](#): `mlr3::mlr_learners`
- `as.data.table(mlr_learners)` for a table of available [Learners](#) in the running session (depending on the loaded packages).

- **mlr3pipelines** to combine learners with pre- and postprocessing steps.
- Package **mlr3viz** for some generic visualizations.
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.
- **mlr3tuning** for tuning of hyperparameters, **mlr3tuningspaces** for established default tuning spaces.

Other Learner: `LearnerFcst`, `mlr_learners_fcst.adam`, `mlr_learners_fcst.arfima`, `mlr_learners_fcst.arima`, `mlr_learners_fcst.auto_adam`, `mlr_learners_fcst.auto_arima`, `mlr_learners_fcst.auto_gum`, `mlr_learners_fcst.auto_msarima`, `mlr_learners_fcst.auto_ssarima`, `mlr_learners_fcst.bagged`, `mlr_learners_fcst.bats`, `mlr_learners_fcst.ces`, `mlr_learners_fcst.croston`, `mlr_learners_fcst.elm`, `mlr_learners_fcst.es`, `mlr_learners_fcst.ets`, `mlr_learners_fcst.gum`, `mlr_learners_fcst.holt_winters`, `mlr_learners_fcst.mean`, `mlr_learners_fcst.mlp`, `mlr_learners_fcst.msarima`, `mlr_learners_fcst.nnetar`, `mlr_learners_fcst.prophet`, `mlr_learners_fcst.random_walk`, `mlr_learners_fcst.rlg`, `mlr_learners_fcst.sma`, `mlr_learners_fcst.spline`, `mlr_learners_fcst.ssarima`, `mlr_learners_fcst.stlm`, `mlr_learners_fcst.struct_ts`, `mlr_learners_fcst.tbats`, `mlr_learners_fcst.theta`, `mlr_learners_fcst.tscou`, `mlr_learners_fcst.tslm`

Examples

```
# Define the Learner and set parameter values
learner = lrn("fcst.auto_ces")
print(learner)

# Define a Task
task = tsk("airpassengers")

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)

# Print the model
print(learner$model)

# Importance method
if ("importance" %in% learner$properties) print(learner$importance())

# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()
```

mlr_learners_fcst.auto_gum

Auto GUM Forecast Learner

Description

Automatic selection over Generalised Univariate Model (GUM) specifications via an information criterion. Calls `smooth::auto.gum()` from package **smooth**.

Dictionary

This `mlr3::Learner` can be instantiated via the dictionary `mlr3::mlr_learners` or with the associated sugar function `mlr3::lrn()`:

```
mlr_learners$get("fcst.auto_gum")
lrn("fcst.auto_gum")
```

Meta Information

- Task type: “fcst”
- Predict Types: “response”, “quantiles”
- Feature Types: “logical”, “integer”, “numeric”
- Required Packages: **mlr3**, **mlr3forecast**, **smooth**

Parameters

Id	Type	Default	Levels	Range
orders	integer	3		$[1, \infty)$
lags	integer	-		$[1, \infty)$
type	character	additive	additive, multiplicative, select	-
initial	character	backcasting	backcasting, optimal, two-stage, complete	-
ic	character	AICc	AICc, AIC, BIC, BICc	-
loss	character	likelihood	likelihood, MSE, MAE, HAM, MSEh, TMSE, GTMSE, MSCE, GPL	-
holdout	logical	FALSE	TRUE, FALSE	-
bounds	character	usual	usual, admissible, none	-
silent	logical	TRUE	TRUE, FALSE	-
regressors	character	use	use, select, adapt, integrate	-

Super classes

```
mlr3::Learner -> mlr3::LearnerRegr -> LearnerFcst -> LearnerFcstSmooth -> LearnerFcstAutoGum
```

Methods

Public methods:

- `LearnerFcstAutoGum$new()`
- `LearnerFcstAutoGum$clone()`

`LearnerFcstAutoGum$new()`: Creates a new instance of this [R6](#) class.

Usage:

```
LearnerFcstAutoGum$new()
```

`LearnerFcstAutoGum$clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerFcstAutoGum$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

References

Svetunkov I (2023). “Smooth forecasting with the smooth package in R.” 2301.01790, <https://arxiv.org/abs/2301.01790>.

See Also

- Chapter in the [mlr3book](https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners): https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners
- Package **mlr3learners** for a solid collection of essential learners.
- Package **mlr3extralearners** for more learners.
- [Dictionary of Learners](#): `mlr3::mlr_learners`
- `as.data.table(mlr_learners)` for a table of available [Learners](#) in the running session (depending on the loaded packages).
- **mlr3pipelines** to combine learners with pre- and postprocessing steps.
- Package **mlr3viz** for some generic visualizations.
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.
- **mlr3tuning** for tuning of hyperparameters, **mlr3tuningpaces** for established default tuning spaces.

Other Learner: `LearnerFcst`, `mlr_learners_fcst.adam`, `mlr_learners_fcst.arfima`, `mlr_learners_fcst.arima`, `mlr_learners_fcst.auto_adam`, `mlr_learners_fcst.auto_arima`, `mlr_learners_fcst.auto_ces`, `mlr_learners_fcst.auto_msarima`, `mlr_learners_fcst.auto_ssarima`, `mlr_learners_fcst.bagged`, `mlr_learners_fcst.bats`, `mlr_learners_fcst.ces`, `mlr_learners_fcst.croston`, `mlr_learners_fcst.elm`, `mlr_learners_fcst.es`, `mlr_learners_fcst.ets`, `mlr_learners_fcst.gum`, `mlr_learners_fcst.holt_winters`, `mlr_learners_fcst.mean`, `mlr_learners_fcst.mlp`, `mlr_learners_fcst.msarima`, `mlr_learners_fcst.nnetar`, `mlr_learners_fcst.prophet`, `mlr_learners_fcst.random_walk`, `mlr_learners_fcst.rlg`, `mlr_learners_fcst.sma`, `mlr_learners_fcst.spline`, `mlr_learners_fcst.ssarima`, `mlr_learners_fcst.stlm`, `mlr_learners_fcst.struct_ts`, `mlr_learners_fcst.tbats`, `mlr_learners_fcst.theta`, `mlr_learners_fcst.tscou`, `mlr_learners_fcst.ts`, `mlr_learners_fcst.tsml`

Examples

```
# Define the Learner and set parameter values
learner = lrn("fcst.auto_gum")
print(learner)

# Define a Task
task = tsk("airpassengers")

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)

# Print the model
print(learner$model)

# Importance method
if ("importance" %in% learner$properties) print(learner$importance())

# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()
```

```
mlr_learners_fcst.auto_msarima
```

Auto Multiple-Seasonal ARIMA Forecast Learner

Description

Automatic order selection for Multiple-Seasonal ARIMA. Picks orders minimising the chosen information criterion. Calls `smooth::auto.msarima()` from package **smooth**.

Dictionary

This `mlr3::Learner` can be instantiated via the dictionary `mlr3::mlr_learners` or with the associated sugar function `mlr3::lrn()`:

```
mlr_learners$get("fcst.auto_msarima")
lrn("fcst.auto_msarima")
```

Meta Information

- Task type: “fcst”
- Predict Types: “response”, “quantiles”
- Feature Types: “logical”, “integer”, “numeric”
- Required Packages: **mlr3**, **mlr3forecast**, **smooth**

Parameters

Id	Type	Default	Levels
orders	untyped	list(ar = c(3, 3), i = c(2, 1), ma = c(3, 3))	
lags	untyped	-	
initial	character	backcasting	backcasting, optimal, two-stage, complete
ic	character	AICc	AICc, AIC, BIC, BICc
loss	character	likelihood	likelihood, MSE, MAE, HAM, MSEh, TMSE, GTMSE, M
holdout	logical	FALSE	TRUE, FALSE
bounds	character	usual	usual, admissible, none
silent	logical	TRUE	TRUE, FALSE
regressors	character	use	use, select, adapt

Super classes

```
mlr3::Learner -> mlr3::LearnerRegr -> LearnerFcst -> LearnerFcstSmooth -> LearnerFcstAutoMsarima
```

Methods**Public methods:**

- `LearnerFcstAutoMsarima$new()`
- `LearnerFcstAutoMsarima$clone()`

`LearnerFcstAutoMsarima$new()`: Creates a new instance of this [R6](#) class.

Usage:

```
LearnerFcstAutoMsarima$new()
```

`LearnerFcstAutoMsarima$clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerFcstAutoMsarima$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

References

Svetunkov I (2023). “Smooth forecasting with the smooth package in R.” 2301.01790, <https://arxiv.org/abs/2301.01790>.

Svetunkov I (2023). *Forecasting and Analytics with the Augmented Dynamic Adaptive Model (ADAM)*, 1st edition. Chapman and Hall/CRC. doi:10.1201/9781003452652. <https://openforecast.org/adam/>.

See Also

- Chapter in the **mlr3book**: https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners
- Package **mlr3learners** for a solid collection of essential learners.
- Package **mlr3extralearners** for more learners.
- Dictionary of Learners: `mlr3::mlr_learners`
- `as.data.table(mlr_learners)` for a table of available **Learners** in the running session (depending on the loaded packages).
- **mlr3pipelines** to combine learners with pre- and postprocessing steps.
- Package **mlr3viz** for some generic visualizations.
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.
- **mlr3tuning** for tuning of hyperparameters, **mlr3tuningspaces** for established default tuning spaces.

Other Learner: `LearnerFcst`, `mlr_learners_fcst.adam`, `mlr_learners_fcst.arfima`, `mlr_learners_fcst.arima`, `mlr_learners_fcst.auto_adam`, `mlr_learners_fcst.auto_arima`, `mlr_learners_fcst.auto_ces`, `mlr_learners_fcst.auto_gum`, `mlr_learners_fcst.auto_ssarima`, `mlr_learners_fcst.bagged`, `mlr_learners_fcst.bats`, `mlr_learners_fcst.ces`, `mlr_learners_fcst.croston`, `mlr_learners_fcst.elm`, `mlr_learners_fcst.es`, `mlr_learners_fcst.ets`, `mlr_learners_fcst.gum`, `mlr_learners_fcst.holt_winters`, `mlr_learners_fcst.mean`, `mlr_learners_fcst.mlp`, `mlr_learners_fcst.msarima`, `mlr_learners_fcst.nnetar`, `mlr_learners_fcst.prophet`, `mlr_learners_fcst.random_walk`, `mlr_learners_fcst.rlg`, `mlr_learners_fcst.sma`, `mlr_learners_fcst.spline`, `mlr_learners_fcst.ssarima`, `mlr_learners_fcst.stlm`, `mlr_learners_fcst.struct_ts`, `mlr_learners_fcst.tbats`, `mlr_learners_fcst.theta`, `mlr_learners_fcst.tscou`, `mlr_learners_fcst.tsml`

Examples

```
# Define the Learner and set parameter values
learner = lrn("fcst.auto_msarima")
print(learner)

# Define a Task
task = tsk("airpassengers")

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)

# Print the model
print(learner$model)

# Importance method
if ("importance" %in% learner$properties) print(learner$importance())
```

```
# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()
```

mlr_learners_fcst.auto_ssarima
<i>Auto State-Space ARIMA Forecast Learner</i>

Description

Automatic order selection for State-Space ARIMA. Picks orders minimising the chosen information criterion. Calls `smooth::auto.ssarima()` from package **smooth**.

Dictionary

This `mlr3::Learner` can be instantiated via the dictionary `mlr3::mlr_learners` or with the associated sugar function `mlr3::lrn()`:

```
mlr_learners$get("fcst.auto_ssarima")
lrn("fcst.auto_ssarima")
```

Meta Information

- Task type: “fcst”
- Predict Types: “response”, “quantiles”
- Feature Types: “logical”, “integer”, “numeric”
- Required Packages: **mlr3**, **mlr3forecast**, **smooth**

Parameters

Id	Type	Default	Levels
orders	untyped	list(ar = c(3, 3), i = c(2, 1), ma = c(3, 3))	
lags	untyped	-	
fast	logical	TRUE	TRUE, FALSE
constant	logical	NULL	TRUE, FALSE
initial	character	backcasting	backcasting, optimal, two-stage, complete
ic	character	AICc	AICc, AIC, BIC, BICc
loss	character	likelihood	likelihood, MSE, MAE, HAM, MSEh, TMSE, GTMSE, M
holdout	logical	FALSE	TRUE, FALSE
bounds	character	admissible	admissible, usual, none
silent	logical	TRUE	TRUE, FALSE
regressors	character	use	use, select, adapt

Super classes

`mlr3::Learner -> mlr3::LearnerRegr -> LearnerFcst -> LearnerFcstSmooth -> LearnerFcstAutoSsarima`

Methods

Public methods:

- `LearnerFcstAutoSsarima$new()`
- `LearnerFcstAutoSsarima$clone()`

`LearnerFcstAutoSsarima$new()`: Creates a new instance of this [R6](#) class.

Usage:

`LearnerFcstAutoSsarima$new()`

`LearnerFcstAutoSsarima$clone()`: The objects of this class are cloneable with this method.

Usage:

`LearnerFcstAutoSsarima$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

References

Svetunkov I (2023). “Smooth forecasting with the smooth package in R.” 2301.01790, <https://arxiv.org/abs/2301.01790>.

Svetunkov I (2023). *Forecasting and Analytics with the Augmented Dynamic Adaptive Model (ADAM)*, 1st edition. Chapman and Hall/CRC. doi:10.1201/9781003452652. <https://openforecast.org/adam/>.

See Also

- Chapter in the [mlr3book](https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners): https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners
- Package [mlr3learners](#) for a solid collection of essential learners.
- Package [mlr3extralearners](#) for more learners.
- Dictionary of Learners: [mlr3::mlr_learners](#)
- `as.data.table(mlr_learners)` for a table of available [Learners](#) in the running session (depending on the loaded packages).
- [mlr3pipelines](#) to combine learners with pre- and postprocessing steps.
- Package [mlr3viz](#) for some generic visualizations.
- Extension packages for additional task types:
 - [mlr3proba](#) for probabilistic supervised regression and survival analysis.
 - [mlr3cluster](#) for unsupervised clustering.

- **mlr3tuning** for tuning of hyperparameters, **mlr3tuningspaces** for established default tuning spaces.

Other Learner: `LearnerFcst`, `mlr_learners_fcst.adam`, `mlr_learners_fcst.arfima`, `mlr_learners_fcst.arima`, `mlr_learners_fcst.auto_adam`, `mlr_learners_fcst.auto_arima`, `mlr_learners_fcst.auto_ces`, `mlr_learners_fcst.auto_gum`, `mlr_learners_fcst.auto_msarima`, `mlr_learners_fcst.bagged`, `mlr_learners_fcst.bats`, `mlr_learners_fcst.ces`, `mlr_learners_fcst.croston`, `mlr_learners_fcst.elm`, `mlr_learners_fcst.es`, `mlr_learners_fcst.ets`, `mlr_learners_fcst.gum`, `mlr_learners_fcst.holt_winters`, `mlr_learners_fcst.mean`, `mlr_learners_fcst.mlp`, `mlr_learners_fcst.msarima`, `mlr_learners_fcst.nnetar`, `mlr_learners_fcst.prophet`, `mlr_learners_fcst.random_walk`, `mlr_learners_fcst.rlg`, `mlr_learners_fcst.sma`, `mlr_learners_fcst.spline`, `mlr_learners_fcst.ssarima`, `mlr_learners_fcst.stlm`, `mlr_learners_fcst.struct_ts`, `mlr_learners_fcst.tbats`, `mlr_learners_fcst.theta`, `mlr_learners_fcst.tscou`, `mlr_learners_fcst.tsml`

Examples

```
# Define the Learner and set parameter values
learner = lrn("fcst.auto_ssarima")
print(learner)

# Define a Task
task = tsk("airpassengers")

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)

# Print the model
print(learner$model)

# Importance method
if ("importance" %in% learner$properties) print(learner$importance())

# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()
```

`mlr_learners_fcst.bagged`

Bagged Model Forecast Learner

Description

Bootstrap-aggregated forecasts. The series is resampled via the Box-Cox/Loess moving block bootstrap of Bergmeir, Hyndman, and Benítez and `fn` is fit on each replicate. The forecast averages across the ensemble. Calls `forecast::baggedModel()` from package **forecast**.

fn is the model-fitting function applied to each bootstrap replicate (defaults to `forecast::ets()`). Any function returning an object compatible with `forecast::forecast()` may be passed, e.g. `forecast::auto.arima()` or `forecast::Arima()` with fixed orders via a wrapper. The number of bootstrap replicates is controlled by num, and block_size configures the moving block length in `forecast::bld.mbb.bootstrap()`. Prediction intervals from `forecast::forecast.baggedModel()` are the empirical bootstrap range (not configurable by level), so only "response" is offered as a predict_type.

Dictionary

This `mlr3::Learner` can be instantiated via the dictionary `mlr3::mlr_learners` or with the associated sugar function `mlr3::lrn()`:

```
mlr_learners$get("fcst.bagged")
lrn("fcst.bagged")
```

Meta Information

- Task type: "fcst"
- Predict Types: "response"
- Feature Types: "logical", "integer", "numeric", "character", "factor", "ordered", "POSIXct", "Date"
- Required Packages: **mlr3**, **mlr3forecast**, **forecast**

Parameters

Id	Type	Default	Range
fn	untyped	-	-
num	integer	100	$[1, \infty)$
block_size	integer	NULL	$[1, \infty)$

Super classes

```
mlr3::Learner -> mlr3::LearnerRegr -> LearnerFcst -> LearnerFcstForecast -> LearnerFcstBaggedModel
```

Methods

Public methods:

- `LearnerFcstBaggedModel$new()`
- `LearnerFcstBaggedModel$clone()`

`LearnerFcstBaggedModel$new()`: Creates a new instance of this **R6** class.

Usage:

```
LearnerFcstBaggedModel$new()
```

`LearnerFcstBaggedModel$clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerFcstBaggedModel$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

References

Bergmeir C, Hyndman RJ, Benítez JM (2016). “Bagging exponential smoothing methods using STL decomposition and Box-Cox transformation.” *International Journal of Forecasting*, **32**(2), 303–312. doi:10.1016/j.ijforecast.2015.07.002.

See Also

- Chapter in the **mlr3book**: https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners
- Package **mlr3learners** for a solid collection of essential learners.
- Package **mlr3extralearners** for more learners.
- [Dictionary of Learners](#): `mlr3::mlr_learners`
- `as.data.table(mlr_learners)` for a table of available [Learners](#) in the running session (depending on the loaded packages).
- **mlr3pipelines** to combine learners with pre- and postprocessing steps.
- Package **mlr3viz** for some generic visualizations.
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.
- **mlr3tuning** for tuning of hyperparameters, **mlr3tuningspaces** for established default tuning spaces.

Other Learner: `LearnerFcst`, `mlr_learners_fcst.adam`, `mlr_learners_fcst.arfima`, `mlr_learners_fcst.arima`, `mlr_learners_fcst.auto_adam`, `mlr_learners_fcst.auto_arima`, `mlr_learners_fcst.auto_ces`, `mlr_learners_fcst.auto_gum`, `mlr_learners_fcst.auto_msarima`, `mlr_learners_fcst.auto_ssarima`, `mlr_learners_fcst.bats`, `mlr_learners_fcst.ces`, `mlr_learners_fcst.croston`, `mlr_learners_fcst.elm`, `mlr_learners_fcst.es`, `mlr_learners_fcst.ets`, `mlr_learners_fcst.gum`, `mlr_learners_fcst.holt_winters`, `mlr_learners_fcst.mean`, `mlr_learners_fcst.mlp`, `mlr_learners_fcst.msarima`, `mlr_learners_fcst.nnetar`, `mlr_learners_fcst.prophet`, `mlr_learners_fcst.random_walk`, `mlr_learners_fcst.rlg`, `mlr_learners_fcst.sma`, `mlr_learners_fcst.spline`, `mlr_learners_fcst.ssarima`, `mlr_learners_fcst.stlm`, `mlr_learners_fcst.struct_ts`, `mlr_learners_fcst.tbats`, `mlr_learners_fcst.theta`, `mlr_learners_fcst.tscou`, `mlr_learners_fcst.tslm`

Examples

```
# Define the Learner and set parameter values
learner = lrn("fcst.bagged")
print(learner)
```

```

# Define a Task
task = tsk("airpassengers")

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)

# Print the model
print(learner$model)

# Importance method
if ("importance" %in% learner$properties) print(learner$importance())

# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()

```

mlr_learners_fcst.bats

BATS Forecast Learner

Description

Exponential smoothing state space model with Box-Cox transformation, ARMA errors, Trend and Seasonal components (BATS) model. Calls `forecast::bats()` from package **forecast**.

Dictionary

This `mlr3::Learner` can be instantiated via the dictionary `mlr3::mlr_learners` or with the associated sugar function `mlr3::lrn()`:

```

mlr_learners$get("fcst.bats")
lrn("fcst.bats")

```

Meta Information

- Task type: “fcst”
- Predict Types: “response”, “quantiles”
- Feature Types: “logical”, “integer”, “numeric”, “character”, “factor”, “ordered”, “POSIXct”, “Date”
- Required Packages: **mlr3**, **mlr3forecast**, **forecast**

Parameters

Id	Type	Default	Levels	Range
use.box.cox	logical	NULL	TRUE, FALSE	-
use.trend	logical	NULL	TRUE, FALSE	-
use.damped.trend	logical	NULL	TRUE, FALSE	-
seasonal.periods	untyped	NULL		-
use.arma.errors	logical	TRUE	TRUE, FALSE	-
use.parallel	logical	-	TRUE, FALSE	-
num.cores	integer	2		$[1, \infty)$
bc.lower	numeric	0		$(-\infty, \infty)$
bc.upper	numeric	1		$(-\infty, \infty)$
biasadj	logical	FALSE	TRUE, FALSE	-

Super classes

`mlr3::Learner` -> `mlr3::LearnerRegr` -> `LearnerFcst` -> `LearnerFcstForecast` -> `LearnerFcstBats`

Methods

Public methods:

- `LearnerFcstBats$new()`
- `LearnerFcstBats$clone()`

`LearnerFcstBats$new()`: Creates a new instance of this [R6](#) class.

Usage:

```
LearnerFcstBats$new()
```

`LearnerFcstBats$clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerFcstBats$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

References

De Livera AM, Hyndman RJ, Snyder RD (2011). “Forecasting time series with complex seasonal patterns using exponential smoothing.” *Journal of the American Statistical Association*, **106**(496), 1513–1527.

See Also

- Chapter in the **mlr3book**: https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners
- Package **mlr3learners** for a solid collection of essential learners.
- Package **mlr3extralearners** for more learners.
- Dictionary of Learners: `mlr3::mlr_learners`
- `as.data.table(mlr_learners)` for a table of available **Learners** in the running session (depending on the loaded packages).
- **mlr3pipelines** to combine learners with pre- and postprocessing steps.
- Package **mlr3viz** for some generic visualizations.
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.
- **mlr3tuning** for tuning of hyperparameters, **mlr3tuningspaces** for established default tuning spaces.

Other Learner: `LearnerFcst`, `mlr_learners_fcst.adam`, `mlr_learners_fcst.arfima`, `mlr_learners_fcst.arima`, `mlr_learners_fcst.auto_adam`, `mlr_learners_fcst.auto_arima`, `mlr_learners_fcst.auto_ces`, `mlr_learners_fcst.auto_gum`, `mlr_learners_fcst.auto_msarima`, `mlr_learners_fcst.auto_ssarima`, `mlr_learners_fcst.bagged`, `mlr_learners_fcst.ces`, `mlr_learners_fcst.croston`, `mlr_learners_fcst.elm`, `mlr_learners_fcst.es`, `mlr_learners_fcst.ets`, `mlr_learners_fcst.gum`, `mlr_learners_fcst.holt_winters`, `mlr_learners_fcst.mean`, `mlr_learners_fcst.mlp`, `mlr_learners_fcst.msarima`, `mlr_learners_fcst.nnetar`, `mlr_learners_fcst.prophet`, `mlr_learners_fcst.random_walk`, `mlr_learners_fcst.rlg`, `mlr_learners_fcst.sma`, `mlr_learners_fcst.spline`, `mlr_learners_fcst.ssarima`, `mlr_learners_fcst.stlm`, `mlr_learners_fcst.struct_ts`, `mlr_learners_fcst.tbats`, `mlr_learners_fcst.theta`, `mlr_learners_fcst.tscou`, `mlr_learners_fcst.tsml`

Examples

```
# Define the Learner and set parameter values
learner = lrn("fcst.bats")
print(learner)

# Define a Task
task = tsk("airpassengers")

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)

# Print the model
print(learner$model)

# Importance method
if ("importance" %in% learner$properties) print(learner$importance())
```

```
# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()
```

mlr_learners_fcst.ces *CES Forecast Learner*

Description

Complex Exponential Smoothing (CES) model. Calls `smooth::ces()` from package **smooth**.

Dictionary

This `mlr3::Learner` can be instantiated via the dictionary `mlr3::mlr_learners` or with the associated sugar function `mlr3::lrn()`:

```
mlr_learners$get("fcst.ces")
lrn("fcst.ces")
```

Meta Information

- Task type: “fcst”
- Predict Types: “response”, “quantiles”
- Feature Types: “logical”, “integer”, “numeric”
- Required Packages: **mlr3**, **mlr3forecast**, **smooth**

Parameters

Id	Type	Default	Levels
seasonality	character	none	none, simple, partial, full
lags	untyped	-	
initial	character	backcasting	backcasting, optimal, two-stage, complete
a	untyped	NULL	
b	untyped	NULL	
loss	character	likelihood	likelihood, MSE, MAE, HAM, MSEh, TMSE, GTMSE, MSCE, GPL
holdout	logical	FALSE	TRUE, FALSE
bounds	character	admissible	admissible, none
silent	logical	TRUE	TRUE, FALSE
regressors	character	use	use, select, adapt

Super classes

`mlr3::Learner` -> `mlr3::LearnerRegr` -> `LearnerFcst` -> `LearnerFcstSmooth` -> `LearnerFcstCes`

Methods

Public methods:

- `LearnerFcstCes$new()`
- `LearnerFcstCes$clone()`

`LearnerFcstCes$new()`: Creates a new instance of this [R6](#) class.

Usage:

`LearnerFcstCes$new()`

`LearnerFcstCes$clone()`: The objects of this class are cloneable with this method.

Usage:

`LearnerFcstCes$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

References

Svetunkov I (2023). “Smooth forecasting with the smooth package in R.” 2301.01790, <https://arxiv.org/abs/2301.01790>.

Svetunkov I (2023). *Forecasting and Analytics with the Augmented Dynamic Adaptive Model (ADAM)*, 1st edition. Chapman and Hall/CRC. doi:10.1201/9781003452652. <https://openforecast.org/adam/>.

See Also

- Chapter in the [mlr3book](https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners): https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners
- Package [mlr3learners](#) for a solid collection of essential learners.
- Package [mlr3extralearners](#) for more learners.
- Dictionary of Learners: [mlr3::mlr_learners](#)
- `as.data.table(mlr_learners)` for a table of available [Learners](#) in the running session (depending on the loaded packages).
- [mlr3pipelines](#) to combine learners with pre- and postprocessing steps.
- Package [mlr3viz](#) for some generic visualizations.
- Extension packages for additional task types:
 - [mlr3proba](#) for probabilistic supervised regression and survival analysis.
 - [mlr3cluster](#) for unsupervised clustering.

- **mlr3tuning** for tuning of hyperparameters, **mlr3tuningspaces** for established default tuning spaces.

Other Learner: `LearnerFcst`, `mlr_learners_fcst.adam`, `mlr_learners_fcst.arfima`, `mlr_learners_fcst.arima`, `mlr_learners_fcst.auto_adam`, `mlr_learners_fcst.auto_arima`, `mlr_learners_fcst.auto_ces`, `mlr_learners_fcst.auto_gum`, `mlr_learners_fcst.auto_msarima`, `mlr_learners_fcst.auto_ssarima`, `mlr_learners_fcst.bagged`, `mlr_learners_fcst.bats`, `mlr_learners_fcst.croston`, `mlr_learners_fcst.elm`, `mlr_learners_fcst.es`, `mlr_learners_fcst.ets`, `mlr_learners_fcst.gum`, `mlr_learners_fcst.holt_winters`, `mlr_learners_fcst.mean`, `mlr_learners_fcst.mlp`, `mlr_learners_fcst.msarima`, `mlr_learners_fcst.nnetar`, `mlr_learners_fcst.prophet`, `mlr_learners_fcst.random_walk`, `mlr_learners_fcst.rlg`, `mlr_learners_fcst.sma`, `mlr_learners_fcst.spline`, `mlr_learners_fcst.ssarima`, `mlr_learners_fcst.stlm`, `mlr_learners_fcst.struct_ts`, `mlr_learners_fcst.tbats`, `mlr_learners_fcst.theta`, `mlr_learners_fcst.tscou`, `mlr_learners_fcst.tslm`

Examples

```
# Define the Learner and set parameter values
learner = lrn("fcst.ces")
print(learner)

# Define a Task
task = tsk("airpassengers")

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)

# Print the model
print(learner$model)

# Importance method
if ("importance" %in% learner$properties) print(learner$importance())

# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()
```

`mlr_learners_fcst.croston`

Croston Forecast Learner

Description

Croston model. Calls `forecast::croston_model()` from package **forecast**.

Dictionary

This `mlr3::Learner` can be instantiated via the dictionary `mlr3::mlr_learners` or with the associated sugar function `mlr3::lrn()`:

```
mlr_learners$get("fcst.croston")
lrn("fcst.croston")
```

Meta Information

- Task type: “fcst”
- Predict Types: “response”
- Feature Types: “logical”, “integer”, “numeric”
- Required Packages: **mlr3**, **mlr3forecast**, **forecast**

Parameters

Id	Type	Default	Levels	Range
alpha	numeric	0.1		[0, 1]
type	character	croston	croston, sba, sbj	-

Super classes

`mlr3::Learner` -> `mlr3::LearnerRegr` -> `LearnerFcst` -> `LearnerFcstForecast` -> `LearnerFcstCroston`

Methods

Public methods:

- `LearnerFcstCroston$new()`
- `LearnerFcstCroston$clone()`

`LearnerFcstCroston$new()`: Creates a new instance of this [R6](#) class.

Usage:

```
LearnerFcstCroston$new()
```

`LearnerFcstCroston$clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerFcstCroston$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

References

- Croston JD (1972). “Forecasting and stock control for intermittent demands.” *Journal of the Operational Research Society*, **23**(3), 289–303.
- Shale EA, Boylan JE, Johnston F (2006). “Forecasting for intermittent demand: the estimation of an unbiased average.” *Journal of the Operational Research Society*, **57**(5), 588–592.
- Shenstone L, Hyndman RJ (2005). “Stochastic models underlying Croston’s method for intermittent demand forecasting.” *Journal of Forecasting*, **24**(6), 389–402.
- Syntetos AA, Boylan JE (2001). “On the bias of intermittent demand estimates.” *International Journal of Production Economics*, **71**(1-3), 457–466.

See Also

- Chapter in the **mlr3book**: https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners
- Package **mlr3learners** for a solid collection of essential learners.
- Package **mlr3extralearners** for more learners.
- **Dictionary of Learners**: `mlr3::mlr_learners`
- `as.data.table(mlr_learners)` for a table of available **Learners** in the running session (depending on the loaded packages).
- **mlr3pipelines** to combine learners with pre- and postprocessing steps.
- Package **mlr3viz** for some generic visualizations.
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.
- **mlr3tuning** for tuning of hyperparameters, **mlr3tuningspaces** for established default tuning spaces.

Other Learner: `LearnerFcst`, `mlr_learners_fcst.adam`, `mlr_learners_fcst.arfima`, `mlr_learners_fcst.arima`, `mlr_learners_fcst.auto_adam`, `mlr_learners_fcst.auto_arima`, `mlr_learners_fcst.auto_ces`, `mlr_learners_fcst.auto_gum`, `mlr_learners_fcst.auto_msarima`, `mlr_learners_fcst.auto_ssarima`, `mlr_learners_fcst.bagged`, `mlr_learners_fcst.bats`, `mlr_learners_fcst.ces`, `mlr_learners_fcst.elm`, `mlr_learners_fcst.es`, `mlr_learners_fcst.ets`, `mlr_learners_fcst.gum`, `mlr_learners_fcst.holt_winters`, `mlr_learners_fcst.mean`, `mlr_learners_fcst.mlp`, `mlr_learners_fcst.msarima`, `mlr_learners_fcst.nnetar`, `mlr_learners_fcst.prophet`, `mlr_learners_fcst.random_walk`, `mlr_learners_fcst.rlgt`, `mlr_learners_fcst.sma`, `mlr_learners_fcst.spline`, `mlr_learners_fcst.ssarima`, `mlr_learners_fcst.stlm`, `mlr_learners_fcst.struct_ts`, `mlr_learners_fcst.tbats`, `mlr_learners_fcst.theta`, `mlr_learners_fcst.tscou`, `mlr_learners_fcst.tslm`

Examples

```
# Define the Learner and set parameter values
learner = lrn("fcst.croston")
print(learner)

# Define a Task
task = tsk("airpassengers")
```

```
# Create train and test set
ids = partition(task)

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)

# Print the model
print(learner$model)

# Importance method
if ("importance" %in% learner$properties) print(learner$importance())

# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()
```

mlr_learners_fcst.elm *Extreme Learning Machine Forecast Learner*

Description

Automatic time series forecasting with an extreme learning machine neural network, including automatic input lag selection, deterministic seasonality handling, and ensemble combination across multiple training repetitions. Calls `nnfor::elm()` from package **nnfor**.

Dictionary

This `mlr3::Learner` can be instantiated via the dictionary `mlr3::mlr_learners` or with the associated sugar function `mlr3::lrn()`:

```
mlr_learners$get("fcst.elm")
lrn("fcst.elm")
```

Meta Information

- Task type: “fcst”
- Predict Types: “response”
- Feature Types: “logical”, “integer”, “numeric”, “character”, “factor”, “ordered”, “POSIXct”, “Date”
- Required Packages: **mlr3**, **mlr3forecast**, **nnfor**, **forecast**

Parameters

Id	Type	Default	Levels	Range
m	integer	-		$[1, \infty)$
hd	untyped	NULL		-
type	character	lasso	lasso, ridge, step, lm	-
reps	integer	20		$[1, \infty)$
comb	character	median	median, mean, mode	-
lags	untyped	NULL		-
keep	untyped	NULL		-
difforder	untyped	NULL		-
sel.lag	logical	TRUE	TRUE, FALSE	-
direct	logical	FALSE	TRUE, FALSE	-
allow.det.season	logical	TRUE	TRUE, FALSE	-
det.type	character	auto	auto, bin, trg	-
barebone	logical	FALSE	TRUE, FALSE	-
retrain	logical	FALSE	TRUE, FALSE	-

Super classes

`mlr3::Learner` -> `mlr3::LearnerRegr` -> `LearnerFcst` -> `LearnerFcstForecast` -> `LearnerFcstElm`

Methods

Public methods:

- `LearnerFcstElm$new()`
- `LearnerFcstElm$clone()`

`LearnerFcstElm$new()`: Creates a new instance of this [R6](#) class.

Usage:

```
LearnerFcstElm$new()
```

`LearnerFcstElm$clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerFcstElm$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

References

Kourentzes N, Barrow DK, Crone SF (2014). “Neural network ensemble operators for time series forecasting.” *Expert Systems with Applications*, **41**(9), 4235–4244. doi:10.1016/j.eswa.2013.12.011.

See Also

- Chapter in the **mlr3book**: https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners
- Package **mlr3learners** for a solid collection of essential learners.
- Package **mlr3extralearners** for more learners.
- Dictionary of Learners: `mlr3::mlr_learners`
- `as.data.table(mlr_learners)` for a table of available **Learners** in the running session (depending on the loaded packages).
- **mlr3pipelines** to combine learners with pre- and postprocessing steps.
- Package **mlr3viz** for some generic visualizations.
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.
- **mlr3tuning** for tuning of hyperparameters, **mlr3tuningspaces** for established default tuning spaces.

Other Learner: `LearnerFcst`, `mlr_learners_fcst.adam`, `mlr_learners_fcst.arfima`, `mlr_learners_fcst.arima`, `mlr_learners_fcst.auto_adam`, `mlr_learners_fcst.auto_arima`, `mlr_learners_fcst.auto_ces`, `mlr_learners_fcst.auto_gum`, `mlr_learners_fcst.auto_msarima`, `mlr_learners_fcst.auto_ssarima`, `mlr_learners_fcst.bagged`, `mlr_learners_fcst.bats`, `mlr_learners_fcst.ces`, `mlr_learners_fcst.croston`, `mlr_learners_fcst.es`, `mlr_learners_fcst.ets`, `mlr_learners_fcst.gum`, `mlr_learners_fcst.holt_winters`, `mlr_learners_fcst.mean`, `mlr_learners_fcst.mlp`, `mlr_learners_fcst.msarima`, `mlr_learners_fcst.nnetar`, `mlr_learners_fcst.prophet`, `mlr_learners_fcst.random_walk`, `mlr_learners_fcst.rlg`, `mlr_learners_fcst.sma`, `mlr_learners_fcst.spline`, `mlr_learners_fcst.ssarima`, `mlr_learners_fcst.stlm`, `mlr_learners_fcst.struct_ts`, `mlr_learners_fcst.tbats`, `mlr_learners_fcst.theta`, `mlr_learners_fcst.tscou`, `mlr_learners_fcst.tsml`

Examples

```
# Define the Learner and set parameter values
learner = lrn("fcst.elm")
print(learner)

# Define a Task
task = tsk("airpassengers")

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)

# Print the model
print(learner$model)

# Importance method
if ("importance" %in% learner$properties) print(learner$importance())
```

```
# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()
```

mlr_learners_fcst.es *Exponential Smoothing Forecast Learner*

Description

Exponential smoothing (ETS) model in state-space form. Supports multiple seasonal lags natively (e.g. `lags = c(1, 24, 168)` for hourly data with daily and weekly cycles). Calls `smooth::es()` from package **smooth**.

Dictionary

This `mlr3::Learner` can be instantiated via the dictionary `mlr3::mlr_learners` or with the associated sugar function `mlr3::lrn()`:

```
mlr_learners$get("fcst.es")
lrn("fcst.es")
```

Meta Information

- Task type: “fcst”
- Predict Types: “response”, “quantiles”
- Feature Types: “logical”, “integer”, “numeric”
- Required Packages: **mlr3**, **mlr3forecast**, **smooth**

Parameters

Id	Type	Default	Levels	Range
model	untyped	"ZXZ"		-
lags	untyped	-		-
persistence	untyped	NULL		-
phi	numeric	NULL		$(-\infty, \infty)$
initial	character	backcasting	backcasting, optimal, two-stage, complete	-
initialSeason	untyped	NULL		-
ic	character	AICc	AICc, AIC, BIC, BICc	-
loss	character	likelihood	likelihood, MSE, MAE, HAM, MSEh, TMSE, GTMSE, MSCE, GPL	-
holdout	logical	FALSE	TRUE, FALSE	-
bounds	character	usual	usual, admissible, none	-
silent	logical	TRUE	TRUE, FALSE	-
regressors	character	use	use, select	-

Super classes

`mlr3::Learner -> mlr3::LearnerRegr -> LearnerFcst -> LearnerFcstSmooth -> LearnerFcstEs`

Methods

Public methods:

- `LearnerFcstEs$new()`
- `LearnerFcstEs$clone()`

`LearnerFcstEs$new()`: Creates a new instance of this [R6](#) class.

Usage:

`LearnerFcstEs$new()`

`LearnerFcstEs$clone()`: The objects of this class are cloneable with this method.

Usage:

`LearnerFcstEs$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

References

Svetunkov I (2023). “Smooth forecasting with the smooth package in R.” 2301.01790, <https://arxiv.org/abs/2301.01790>.

Svetunkov I (2023). *Forecasting and Analytics with the Augmented Dynamic Adaptive Model (ADAM)*, 1st edition. Chapman and Hall/CRC. doi:10.1201/9781003452652. <https://openforecast.org/adam/>.

See Also

- Chapter in the [mlr3book](https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners): https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners
- Package **mlr3learners** for a solid collection of essential learners.
- Package **mlr3extralearners** for more learners.
- Dictionary of Learners: [mlr3::mlr_learners](#)
- `as.data.table(mlr_learners)` for a table of available [Learners](#) in the running session (depending on the loaded packages).
- **mlr3pipelines** to combine learners with pre- and postprocessing steps.
- Package **mlr3viz** for some generic visualizations.
- Extension packages for additional task types:

- **mlr3proba** for probabilistic supervised regression and survival analysis.
- **mlr3cluster** for unsupervised clustering.
- **mlr3tuning** for tuning of hyperparameters, **mlr3tuningspaces** for established default tuning spaces.

Other Learner: `LearnerFcst`, `mlr_learners_fcst.adam`, `mlr_learners_fcst.arfima`, `mlr_learners_fcst.arma`, `mlr_learners_fcst.auto_adam`, `mlr_learners_fcst.auto_arma`, `mlr_learners_fcst.auto_ces`, `mlr_learners_fcst.auto_gum`, `mlr_learners_fcst.auto_msarima`, `mlr_learners_fcst.auto_ssarima`, `mlr_learners_fcst.bagged`, `mlr_learners_fcst.bats`, `mlr_learners_fcst.ces`, `mlr_learners_fcst.croston`, `mlr_learners_fcst.elm`, `mlr_learners_fcst.ets`, `mlr_learners_fcst.gum`, `mlr_learners_fcst.holt_winters`, `mlr_learners_fcst.mean`, `mlr_learners_fcst.mlp`, `mlr_learners_fcst.msarima`, `mlr_learners_fcst.nnetar`, `mlr_learners_fcst.prophet`, `mlr_learners_fcst.random_walk`, `mlr_learners_fcst.rlg`, `mlr_learners_fcst.sma`, `mlr_learners_fcst.spline`, `mlr_learners_fcst.ssarima`, `mlr_learners_fcst.stlm`, `mlr_learners_fcst.struct_ts`, `mlr_learners_fcst.tbats`, `mlr_learners_fcst.theta`, `mlr_learners_fcst.tscou`, `mlr_learners_fcst.tslm`

Examples

```
# Define the Learner and set parameter values
learner = lrn("fcst.es")
print(learner)

# Define a Task
task = tsk("airpassengers")

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)

# Print the model
print(learner$model)

# Importance method
if ("importance" %in% learner$properties) print(learner$importance())

# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()
```

`mlr_learners_fcst.ets` *ETS Forecast Learner*

Description

Exponential Smoothing State Space (ETS) model. Calls `forecast::ets()` from package **forecast**.

Dictionary

This `mlr3::Learner` can be instantiated via the dictionary `mlr3::mlr_learners` or with the associated sugar function `mlr3::lrn()`:

```
mlr_learners$get("fcst.ets")
lrn("fcst.ets")
```

Meta Information

- Task type: “fcst”
- Predict Types: “response”, “quantiles”
- Feature Types: “logical”, “integer”, “numeric”, “character”, “factor”, “ordered”, “POSIXct”, “Date”
- Required Packages: **mlr3**, **mlr3forecast**, **forecast**

Parameters

Id	Type	Default	Levels	Range
model	untyped	"ZZZ"		-
damped	logical	NULL	TRUE, FALSE	-
alpha	numeric	NULL		$(-\infty, \infty)$
beta	numeric	NULL		$(-\infty, \infty)$
gamma	numeric	NULL		$(-\infty, \infty)$
phi	numeric	NULL		$(-\infty, \infty)$
additive.only	logical	FALSE	TRUE, FALSE	-
lambda	untyped	NULL		-
biasadj	logical	FALSE	TRUE, FALSE	-
lower	untyped	<code>c(rep.int(1e-04, 3), 0.8)</code>		-
upper	untyped	<code>c(rep.int(0.9999, 3), 0.98)</code>		-
opt.crit	character	lik	lik, amse, mse, sigma, mae	-
nmse	integer	3		[0, 30]
bounds	character	both	both, usual, admissible	-
ic	character	aicc	aicc, aic, bic	-
restrict	logical	TRUE	TRUE, FALSE	-
allow.multiplicative.trend	logical	FALSE	TRUE, FALSE	-
simulate	logical	FALSE	TRUE, FALSE	-
bootstrap	logical	FALSE	TRUE, FALSE	-
npaths	integer	5000		[1, ∞)

Super classes

```
mlr3::Learner -> mlr3::LearnerRegr -> LearnerFcst -> LearnerFcstForecast -> LearnerFcstEts
```

Methods

Public methods:

- `LearnerFcstEts$new()`
- `LearnerFcstEts$clone()`

`LearnerFcstEts$new()`: Creates a new instance of this [R6](#) class.

Usage:

```
LearnerFcstEts$new()
```

`LearnerFcstEts$clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerFcstEts$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

References

Hyndman RJ, Koehler AB, Snyder RD, Grose S (2002). “A state space framework for automatic forecasting using exponential smoothing methods.” *International Journal of Forecasting*, **18**(3), 439–454.

Hyndman RJ, Akram M, Archibald B (2008). “The admissible parameter space for exponential smoothing models.” *Annals of the Institute of Statistical Mathematics*, **60**(2), 407–426.

Hyndman RJ, Koehler AB, Ord JK, Snyder RD (2008). *Forecasting with exponential smoothing: the state space approach*. Springer-Verlag. <https://robjhyndman.com/expsmooth/>.

See Also

- Chapter in the [mlr3book](https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners): https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners
- Package **mlr3learners** for a solid collection of essential learners.
- Package **mlr3extralearners** for more learners.
- [Dictionary of Learners](#): `mlr3::mlr_learners`
- `as.data.table(mlr_learners)` for a table of available [Learners](#) in the running session (depending on the loaded packages).
- **mlr3pipelines** to combine learners with pre- and postprocessing steps.
- Package **mlr3viz** for some generic visualizations.
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.
- **mlr3tuning** for tuning of hyperparameters, **mlr3tuningspaces** for established default tuning spaces.

Other Learner: `LearnerFcst`, `mlr_learners_fcst.adam`, `mlr_learners_fcst.arfima`, `mlr_learners_fcst.arima`, `mlr_learners_fcst.auto_adam`, `mlr_learners_fcst.auto_arima`, `mlr_learners_fcst.auto_ces`,

```
mlr_learners_fcst.auto_gum, mlr_learners_fcst.auto_msarima, mlr_learners_fcst.auto_ssarima,
mlr_learners_fcst.bagged, mlr_learners_fcst.bats, mlr_learners_fcst.ces, mlr_learners_fcst.croston,
mlr_learners_fcst.elm, mlr_learners_fcst.es, mlr_learners_fcst.gum, mlr_learners_fcst.holt_winters,
mlr_learners_fcst.mean, mlr_learners_fcst.mlp, mlr_learners_fcst.msarima, mlr_learners_fcst.nnetar,
mlr_learners_fcst.prophet, mlr_learners_fcst.random_walk, mlr_learners_fcst.rlg,
mlr_learners_fcst.sma, mlr_learners_fcst.spline, mlr_learners_fcst.ssarima, mlr_learners_fcst.stlm,
mlr_learners_fcst.struct_ts, mlr_learners_fcst.tbats, mlr_learners_fcst.theta, mlr_learners_fcst.tscou,
mlr_learners_fcst.tslm
```

Examples

```
# Define the Learner and set parameter values
learner = lrn("fcst.ets")
print(learner)

# Define a Task
task = tsk("airpassengers")

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)

# Print the model
print(learner$model)

# Importance method
if ("importance" %in% learner$properties) print(learner$importance())

# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()
```

mlr_learners_fcst.gum *GUM Forecast Learner*

Description

Generalised Univariate Model (GUM): a single-source-of-error state-space model with a user-defined transition matrix, persistence vector and measurement vector. Generalises exponential smoothing beyond the ETS structural template. Calls `smooth::gum()` from package **smooth**.

Dictionary

This `mlr3::Learner` can be instantiated via the dictionary `mlr3::mlr_learners` or with the associated sugar function `mlr3::lrn()`:

```
mlr_learners$get("fcst.gum")
lrn("fcst.gum")
```

Meta Information

- Task type: “fcst”
- Predict Types: “response”, “quantiles”
- Feature Types: “logical”, “integer”, “numeric”
- Required Packages: **mlr3**, **mlr3forecast**, **smooth**

Parameters

Id	Type	Default	Levels
orders	untyped	c(1, 1)	
lags	untyped	-	
type	character	additive	additive, multiplicative
initial	character	backcasting	backcasting, optimal, two-stage, complete
persistence	untyped	NULL	
transition	untyped	NULL	
measurement	untyped	NULL	
loss	character	likelihood	likelihood, MSE, MAE, HAM, MSEh, TMSE, GTMSE, MSCE, GPL
holdout	logical	FALSE	TRUE, FALSE
bounds	character	usual	usual, admissible, none
silent	logical	TRUE	TRUE, FALSE
regressors	character	use	use, select, adapt, integrate

Super classes

```
mlr3::Learner -> mlr3::LearnerRegr -> LearnerFcst -> LearnerFcstSmooth -> LearnerFcstGum
```

Methods

Public methods:

- [LearnerFcstGum\\$new\(\)](#)
- [LearnerFcstGum\\$clone\(\)](#)

[LearnerFcstGum\\$new\(\)](#): Creates a new instance of this [R6](#) class.

Usage:

```
LearnerFcstGum$new()
```

[LearnerFcstGum\\$clone\(\)](#): The objects of this class are cloneable with this method.

Usage:

```
LearnerFcstGum$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

References

Svetunkov I (2023). “Smooth forecasting with the smooth package in R.” 2301.01790, <https://arxiv.org/abs/2301.01790>.

See Also

- Chapter in the **mlr3book**: https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners
- Package **mlr3learners** for a solid collection of essential learners.
- Package **mlr3extralearners** for more learners.
- **Dictionary of Learners**: `mlr3::mlr_learners`
- `as.data.table(mlr_learners)` for a table of available **Learners** in the running session (depending on the loaded packages).
- **mlr3pipelines** to combine learners with pre- and postprocessing steps.
- Package **mlr3viz** for some generic visualizations.
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.
- **mlr3tuning** for tuning of hyperparameters, **mlr3tuningspaces** for established default tuning spaces.

Other Learner: `LearnerFcst`, `mlr_learners_fcst.adam`, `mlr_learners_fcst.arfima`, `mlr_learners_fcst.arima`, `mlr_learners_fcst.auto_adam`, `mlr_learners_fcst.auto_arima`, `mlr_learners_fcst.auto_ces`, `mlr_learners_fcst.auto_gum`, `mlr_learners_fcst.auto_msarima`, `mlr_learners_fcst.auto_ssarima`, `mlr_learners_fcst.bagged`, `mlr_learners_fcst.bats`, `mlr_learners_fcst.ces`, `mlr_learners_fcst.croston`, `mlr_learners_fcst.elm`, `mlr_learners_fcst.es`, `mlr_learners_fcst.ets`, `mlr_learners_fcst.holt_winters`, `mlr_learners_fcst.mean`, `mlr_learners_fcst.mlp`, `mlr_learners_fcst.msarima`, `mlr_learners_fcst.nnetar`, `mlr_learners_fcst.prophet`, `mlr_learners_fcst.random_walk`, `mlr_learners_fcst.rlg`, `mlr_learners_fcst.sma`, `mlr_learners_fcst.spline`, `mlr_learners_fcst.ssarima`, `mlr_learners_fcst.stlm`, `mlr_learners_fcst.struct_ts`, `mlr_learners_fcst.tbats`, `mlr_learners_fcst.theta`, `mlr_learners_fcst.tscout`, `mlr_learners_fcst.tslm`

Examples

```
# Define the Learner and set parameter values
learner = lrn("fcst.gum")
print(learner)

# Define a Task
task = tsk("airpassengers")

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)
```

```
# Print the model
print(learner$model)

# Importance method
if ("importance" %in% learner$properties) print(learner$importance())

# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()
```

```
mlr_learners_fcst.holt_winters
      Holt-Winters Forecast Learner
```

Description

Holt-Winters exponential smoothing with optional trend and additive or multiplicative seasonal component. Smoothing parameters are estimated by minimizing the squared one-step prediction error. Calls `stats::HoltWinters()` from package **stats** and forecasts via `forecast::forecast()`.

Setting `beta = FALSE` fits a simple exponential smoothing model (no trend). Setting `gamma = FALSE` fits a non-seasonal model.

Dictionary

This `mlr3::Learner` can be instantiated via the dictionary `mlr3::mlr_learners` or with the associated sugar function `mlr3::lrn()`:

```
mlr_learners$get("fcst.holt_winters")
lrn("fcst.holt_winters")
```

Meta Information

- Task type: “fcst”
- Predict Types: “response”, “quantiles”
- Feature Types: “logical”, “integer”, “numeric”, “character”, “factor”, “ordered”, “POSIXct”, “Date”
- Required Packages: **mlr3**, **mlr3forecast**, **forecast**

Parameters

Id	Type	Default	Levels	Range
alpha	numeric	NULL		[0, 1]
beta	numeric	NULL		[0, 1]

gamma	numeric	NULL		[0, 1]
seasonal	character	additive	additive, multiplicative	-
start.periods	integer	2		$[2, \infty)$
l.start	numeric	NULL		$(-\infty, \infty)$
b.start	numeric	NULL		$(-\infty, \infty)$
s.start	untyped	NULL		-
optim.start	untyped	c(alpha = 0.3, beta = 0.1, gamma = 0.1)		-
optim.control	untyped	list()		-
lambda	untyped	NULL		-
biasadj	logical	FALSE	TRUE, FALSE	-

Super classes

```
mlr3::Learner -> mlr3::LearnerRegr -> LearnerFcst -> LearnerFcstForecast -> LearnerFcstHoltWinters
```

Methods

Public methods:

- `LearnerFcstHoltWinters$new()`
- `LearnerFcstHoltWinters$clone()`

`LearnerFcstHoltWinters$new()`: Creates a new instance of this R6 class.

Usage:

```
LearnerFcstHoltWinters$new()
```

`LearnerFcstHoltWinters$clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerFcstHoltWinters$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

References

- Holt CC (2004). “Forecasting seasonals and trends by exponentially weighted moving averages.” *International Journal of Forecasting*, **20**(1), 5–10. doi:10.1016/j.ijforecast.2003.09.015.
- Winters PR (1960). “Forecasting Sales by Exponentially Weighted Moving Averages.” *Management Science*, **6**(3), 324–342. doi:10.1287/mnsc.6.3.324.

See Also

- Chapter in the `mlr3book`: https://mlr3book.ml-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners
- Package **mlr3learners** for a solid collection of essential learners.

- Package **mlr3extralearners** for more learners.
- Dictionary of Learners: `mlr3::mlr_learners`
- `as.data.table(mlr_learners)` for a table of available Learners in the running session (depending on the loaded packages).
- **mlr3pipelines** to combine learners with pre- and postprocessing steps.
- Package **mlr3viz** for some generic visualizations.
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.
- **mlr3tuning** for tuning of hyperparameters, **mlr3tuningspaces** for established default tuning spaces.

Other Learner: `LearnerFcst`, `mlr_learners_fcst.adam`, `mlr_learners_fcst.arfima`, `mlr_learners_fcst.arima`, `mlr_learners_fcst.auto_adam`, `mlr_learners_fcst.auto_arima`, `mlr_learners_fcst.auto_ces`, `mlr_learners_fcst.auto_gum`, `mlr_learners_fcst.auto_msarima`, `mlr_learners_fcst.auto_ssarima`, `mlr_learners_fcst.bagged`, `mlr_learners_fcst.bats`, `mlr_learners_fcst.ces`, `mlr_learners_fcst.croston`, `mlr_learners_fcst.elm`, `mlr_learners_fcst.es`, `mlr_learners_fcst.ets`, `mlr_learners_fcst.gum`, `mlr_learners_fcst.mean`, `mlr_learners_fcst.mlp`, `mlr_learners_fcst.msarima`, `mlr_learners_fcst.nnetar`, `mlr_learners_fcst.prophet`, `mlr_learners_fcst.random_walk`, `mlr_learners_fcst.rlg`, `mlr_learners_fcst.sma`, `mlr_learners_fcst.spline`, `mlr_learners_fcst.ssarima`, `mlr_learners_fcst.stlm`, `mlr_learners_fcst.struct_ts`, `mlr_learners_fcst.tbats`, `mlr_learners_fcst.theta`, `mlr_learners_fcst.tscou`, `mlr_learners_fcst.tslm`

Examples

```
# Define the Learner and set parameter values
learner = lrn("fcst.holt_winters")
print(learner)

# Define a Task
task = tsk("airpassengers")

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)

# Print the model
print(learner$model)

# Importance method
if ("importance" %in% learner$properties) print(learner$importance())

# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()
```

mlr_learners_fcst.mean

Mean Forecast Learner

Description

Mean model. Calls `forecast::mean_model()` from package **forecast**.

Dictionary

This `mlr3::Learner` can be instantiated via the dictionary `mlr3::mlr_learners` or with the associated sugar function `mlr3::lrn()`:

```
mlr_learners$get("fcst.mean")
lrn("fcst.mean")
```

Meta Information

- Task type: “fcst”
- Predict Types: “response”, “quantiles”
- Feature Types: “logical”, “integer”, “numeric”, “character”, “factor”, “ordered”, “POSIXct”, “Date”
- Required Packages: **mlr3**, **mlr3forecast**, **forecast**

Parameters

Id	Type	Default	Levels
lambda	untyped	NULL	
biasadj	logical	FALSE	TRUE, FALSE

Super classes

```
mlr3::Learner -> mlr3::LearnerRegr -> LearnerFcst -> LearnerFcstForecast -> LearnerFcstMean
```

Methods

Public methods:

- `LearnerFcstMean$new()`
- `LearnerFcstMean$clone()`

`LearnerFcstMean$new()`: Creates a new instance of this [R6](#) class.

Usage:

```
LearnerFcstMean$new()
```

`LearnerFcstMean$clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerFcstMean$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

References

Hyndman RJ, Athanasopoulos G (2018). *Forecasting: principles and practice*, 2nd edition. OTexts, Melbourne, Australia. <https://OTexts.com/fpp2/>.

See Also

- Chapter in the **mlr3book**: https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners
- Package **mlr3learners** for a solid collection of essential learners.
- Package **mlr3extralearners** for more learners.
- Dictionary of Learners: **mlr3::mlr_learners**
- `as.data.table(mlr_learners)` for a table of available **Learners** in the running session (depending on the loaded packages).
- **mlr3pipelines** to combine learners with pre- and postprocessing steps.
- Package **mlr3viz** for some generic visualizations.
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.
- **mlr3tuning** for tuning of hyperparameters, **mlr3tuningspaces** for established default tuning spaces.

Other Learner: `LearnerFcst`, `mlr_learners_fcst.adam`, `mlr_learners_fcst.arfima`, `mlr_learners_fcst.arima`, `mlr_learners_fcst.auto_adam`, `mlr_learners_fcst.auto_arima`, `mlr_learners_fcst.auto_ces`, `mlr_learners_fcst.auto_gum`, `mlr_learners_fcst.auto_msarima`, `mlr_learners_fcst.auto_ssarima`, `mlr_learners_fcst.bagged`, `mlr_learners_fcst.bats`, `mlr_learners_fcst.ces`, `mlr_learners_fcst.croston`, `mlr_learners_fcst.elm`, `mlr_learners_fcst.es`, `mlr_learners_fcst.ets`, `mlr_learners_fcst.gum`, `mlr_learners_fcst.holt_winters`, `mlr_learners_fcst.mlp`, `mlr_learners_fcst.msarima`, `mlr_learners_fcst.nnetar`, `mlr_learners_fcst.prophet`, `mlr_learners_fcst.random_walk`, `mlr_learners_fcst.rlg`, `mlr_learners_fcst.sma`, `mlr_learners_fcst.spline`, `mlr_learners_fcst.ssarima`, `mlr_learners_fcst.stlm`, `mlr_learners_fcst.struct_ts`, `mlr_learners_fcst.tbats`, `mlr_learners_fcst.theta`, `mlr_learners_fcst.tscount`, `mlr_learners_fcst.tslm`

Examples

```
# Define the Learner and set parameter values
learner = lrn("fcst.mean")
print(learner)
```

```

# Define a Task
task = tsk("airpassengers")

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)

# Print the model
print(learner$model)

# Importance method
if ("importance" %in% learner$properties) print(learner$importance())

# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()

```

mlr_learners_fcst.mlp *Multilayer Perceptron Forecast Learner*

Description

Automatic time series forecasting with a multilayer perceptron neural network, including automatic input lag selection, deterministic seasonality handling, and ensemble combination across multiple training repetitions. Calls `nnfor::mlp()` from package **nnfor**.

Dictionary

This `mlr3::Learner` can be instantiated via the dictionary `mlr3::mlr_learners` or with the associated sugar function `mlr3::lrn()`:

```

mlr_learners$get("fcst.mlp")
lrn("fcst.mlp")

```

Meta Information

- Task type: “fcst”
- Predict Types: “response”
- Feature Types: “logical”, “integer”, “numeric”, “character”, “factor”, “ordered”, “POSIXct”, “Date”
- Required Packages: **mlr3**, **mlr3forecast**, **nnfor**, **forecast**

Parameters

Id	Type	Default	Levels	Range
m	integer	-		$[1, \infty)$
hd	untyped	NULL		-
reps	integer	20		$[1, \infty)$
comb	character	median	median, mean, mode	-
lags	untyped	NULL		-
keep	untyped	NULL		-
difforder	untyped	NULL		-
sel.lag	logical	TRUE	TRUE, FALSE	-
allow.det.season	logical	TRUE	TRUE, FALSE	-
det.type	character	auto	auto, bin, trg	-
hd.auto.type	character	set	set, valid, cv, elm	-
hd.max	integer	NULL		$[1, \infty)$
retrain	logical	FALSE	TRUE, FALSE	-

Super classes

`mlr3::Learner` -> `mlr3::LearnerRegr` -> `LearnerFcst` -> `LearnerFcstForecast` -> `LearnerFcstMlp`

Methods**Public methods:**

- `LearnerFcstMlp$new()`
- `LearnerFcstMlp$clone()`

`LearnerFcstMlp$new()`: Creates a new instance of this [R6](#) class.

Usage:

```
LearnerFcstMlp$new()
```

`LearnerFcstMlp$clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerFcstMlp$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

References

Kourentzes N, Barrow DK, Crone SF (2014). “Neural network ensemble operators for time series forecasting.” *Expert Systems with Applications*, **41**(9), 4235–4244. doi:10.1016/j.eswa.2013.12.011.

See Also

- Chapter in the **mlr3book**: https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners
- Package **mlr3learners** for a solid collection of essential learners.
- Package **mlr3extralearners** for more learners.
- Dictionary of Learners: `mlr3::mlr_learners`
- `as.data.table(mlr_learners)` for a table of available **Learners** in the running session (depending on the loaded packages).
- **mlr3pipelines** to combine learners with pre- and postprocessing steps.
- Package **mlr3viz** for some generic visualizations.
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.
- **mlr3tuning** for tuning of hyperparameters, **mlr3tuningspaces** for established default tuning spaces.

Other Learner: `LearnerFcst`, `mlr_learners_fcst.adam`, `mlr_learners_fcst.arfima`, `mlr_learners_fcst.arima`, `mlr_learners_fcst.auto_adam`, `mlr_learners_fcst.auto_arima`, `mlr_learners_fcst.auto_ces`, `mlr_learners_fcst.auto_gum`, `mlr_learners_fcst.auto_msarima`, `mlr_learners_fcst.auto_ssarima`, `mlr_learners_fcst.bagged`, `mlr_learners_fcst.bats`, `mlr_learners_fcst.ces`, `mlr_learners_fcst.croston`, `mlr_learners_fcst.elm`, `mlr_learners_fcst.es`, `mlr_learners_fcst.ets`, `mlr_learners_fcst.gum`, `mlr_learners_fcst.holt_winters`, `mlr_learners_fcst.mean`, `mlr_learners_fcst.msarima`, `mlr_learners_fcst.nnetar`, `mlr_learners_fcst.prophet`, `mlr_learners_fcst.random_walk`, `mlr_learners_fcst.rlgt`, `mlr_learners_fcst.sma`, `mlr_learners_fcst.spline`, `mlr_learners_fcst.ssarima`, `mlr_learners_fcst.stlm`, `mlr_learners_fcst.struct_ts`, `mlr_learners_fcst.tbats`, `mlr_learners_fcst.theta`, `mlr_learners_fcst.tscount`, `mlr_learners_fcst.tslm`

Examples

```
# Define the Learner and set parameter values
learner = lrn("fcst.mlp")
print(learner)

# Define a Task
task = tsk("airpassengers")

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)

# Print the model
print(learner$model)

# Importance method
if ("importance" %in% learner$properties) print(learner$importance())
```

```
# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()
```

mlr_learners_fcst.msarima

Multiple-Seasonal ARIMA Forecast Learner

Description

Multiple-Seasonal ARIMA model in state-space form. Supports multiple seasonal lags natively (e.g. lags = c(1, 24, 168) for hourly data with daily and weekly cycles). Calls `smooth::msarima()` from package **smooth**.

Dictionary

This `mlr3::Learner` can be instantiated via the dictionary `mlr3::mlr_learners` or with the associated sugar function `mlr3::lrn()`:

```
mlr_learners$get("fcst.msarima")
lrn("fcst.msarima")
```

Meta Information

- Task type: “fcst”
- Predict Types: “response”, “quantiles”
- Feature Types: “logical”, “integer”, “numeric”
- Required Packages: **mlr3**, **mlr3forecast**, **smooth**

Parameters

Id	Type	Default	Levels
orders	untyped	list(ar = 0, i = 1, ma = 1)	
lags	untyped	1	
constant	logical	FALSE	TRUE, FALSE
arma	untyped	NULL	
initial	character	backcasting	backcasting, optimal, two-stage, complete
ic	character	AICc	AICc, AIC, BIC, BICc
loss	character	likelihood	likelihood, MSE, MAE, HAM, MSEh, TMSE, GTMSE, MSCE, GPL
holdout	logical	FALSE	TRUE, FALSE
bounds	character	usual	usual, admissible, none
silent	logical	TRUE	TRUE, FALSE
regressors	character	use	use, select, adapt

Super classes

`mlr3::Learner -> mlr3::LearnerRegr -> LearnerFcst -> LearnerFcstSmooth -> LearnerFcstMsarima`

Methods

Public methods:

- `LearnerFcstMsarima$new()`
- `LearnerFcstMsarima$clone()`

`LearnerFcstMsarima$new()`: Creates a new instance of this R6 class.

Usage:

`LearnerFcstMsarima$new()`

`LearnerFcstMsarima$clone()`: The objects of this class are cloneable with this method.

Usage:

`LearnerFcstMsarima$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

References

Svetunkov I (2023). “Smooth forecasting with the smooth package in R.” 2301.01790, <https://arxiv.org/abs/2301.01790>.

Svetunkov I (2023). *Forecasting and Analytics with the Augmented Dynamic Adaptive Model (ADAM)*, 1st edition. Chapman and Hall/CRC. doi:10.1201/9781003452652. <https://openforecast.org/adam/>.

See Also

- Chapter in the `mlr3book`: https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners
- Package `mlr3learners` for a solid collection of essential learners.
- Package `mlr3extralearners` for more learners.
- Dictionary of Learners: `mlr3::mlr_learners`
- `as.data.table(mlr_learners)` for a table of available Learners in the running session (depending on the loaded packages).
- `mlr3pipelines` to combine learners with pre- and postprocessing steps.
- Package `mlr3viz` for some generic visualizations.
- Extension packages for additional task types:

- **mlr3proba** for probabilistic supervised regression and survival analysis.
- **mlr3cluster** for unsupervised clustering.
- **mlr3tuning** for tuning of hyperparameters, **mlr3tuningspaces** for established default tuning spaces.

Other Learner: `LearnerFcst`, `mlr_learners_fcst.adam`, `mlr_learners_fcst.arfima`, `mlr_learners_fcst.arima`, `mlr_learners_fcst.auto_adam`, `mlr_learners_fcst.auto_arima`, `mlr_learners_fcst.auto_ces`, `mlr_learners_fcst.auto_gum`, `mlr_learners_fcst.auto_msarima`, `mlr_learners_fcst.auto_ssarima`, `mlr_learners_fcst.bagged`, `mlr_learners_fcst.bats`, `mlr_learners_fcst.ces`, `mlr_learners_fcst.croston`, `mlr_learners_fcst.elm`, `mlr_learners_fcst.es`, `mlr_learners_fcst.ets`, `mlr_learners_fcst.gum`, `mlr_learners_fcst.holt_winters`, `mlr_learners_fcst.mean`, `mlr_learners_fcst.mlp`, `mlr_learners_fcst.nnetar`, `mlr_learners_fcst.prophet`, `mlr_learners_fcst.random_walk`, `mlr_learners_fcst.rlg`, `mlr_learners_fcst.sma`, `mlr_learners_fcst.spline`, `mlr_learners_fcst.ssarima`, `mlr_learners_fcst.stlm`, `mlr_learners_fcst.struct_ts`, `mlr_learners_fcst.tbats`, `mlr_learners_fcst.theta`, `mlr_learners_fcst.tscou`, `mlr_learners_fcst.tslm`

Examples

```
# Define the Learner and set parameter values
learner = lrn("fcst.msarima")
print(learner)

# Define a Task
task = tsk("airpassengers")

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)

# Print the model
print(learner$model)

# Importance method
if ("importance" %in% learner$properties) print(learner$importance())

# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()
```

Description

Single Layer Neural Network. Calls `forecast::nnetar()` from package **forecast**.

Dictionary

This `mlr3::Learner` can be instantiated via the dictionary `mlr3::mlr_learners` or with the associated sugar function `mlr3::lrn()`:

```
mlr_learners$get("fcst.nnetar")
lrn("fcst.nnetar")
```

Meta Information

- Task type: “fcst”
- Predict Types: “response”
- Feature Types: “logical”, “integer”, “numeric”
- Required Packages: **mlr3**, **mlr3forecast**, **forecast**

Parameters

Id	Type	Default	Levels	Range
p	integer	-		$[0, \infty)$
P	integer	1		$[0, \infty)$
size	integer	NULL		$[1, \infty)$
repeats	integer	20		$(-\infty, \infty)$
lambda	untyped	NULL		-
scale.inputs	logical	TRUE	TRUE, FALSE	-
parallel	logical	FALSE	TRUE, FALSE	-
num.cores	integer	2		$[1, \infty)$
bootstrap	logical	FALSE	TRUE, FALSE	-
npaths	integer	1000		$[1, \infty)$
innov	untyped	NULL		-

Super classes

```
mlr3::Learner -> mlr3::LearnerRegr -> LearnerFcst -> LearnerFcstForecast -> LearnerFcstNnetar
```

Methods

Public methods:

- `LearnerFcstNnetar$new()`
- `LearnerFcstNnetar$clone()`

`LearnerFcstNnetar$new()`: Creates a new instance of this **R6** class.

Usage:

```
LearnerFcstNnetar$new()
```

`LearnerFcstNnetar$clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerFcstNnetar$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

References

Ripley BD (1996). *Pattern Recognition and Neural Networks*. Cambridge University Press. doi:10.1017/cbo9780511812651.

See Also

- Chapter in the **mlr3book**: https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners
- Package **mlr3learners** for a solid collection of essential learners.
- Package **mlr3extralearners** for more learners.
- **Dictionary of Learners**: `mlr3::mlr_learners`
- `as.data.table(mlr_learners)` for a table of available **Learners** in the running session (depending on the loaded packages).
- **mlr3pipelines** to combine learners with pre- and postprocessing steps.
- Package **mlr3viz** for some generic visualizations.
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.
- **mlr3tuning** for tuning of hyperparameters, **mlr3tuningspaces** for established default tuning spaces.

Other Learner: `LearnerFcst`, `mlr_learners_fcst.adam`, `mlr_learners_fcst.arfima`, `mlr_learners_fcst.arima`, `mlr_learners_fcst.auto_adam`, `mlr_learners_fcst.auto_arima`, `mlr_learners_fcst.auto_ces`, `mlr_learners_fcst.auto_gum`, `mlr_learners_fcst.auto_msarima`, `mlr_learners_fcst.auto_ssarima`, `mlr_learners_fcst.bagged`, `mlr_learners_fcst.bats`, `mlr_learners_fcst.ces`, `mlr_learners_fcst.croston`, `mlr_learners_fcst.elm`, `mlr_learners_fcst.es`, `mlr_learners_fcst.ets`, `mlr_learners_fcst.gum`, `mlr_learners_fcst.holt_winters`, `mlr_learners_fcst.mean`, `mlr_learners_fcst.mlp`, `mlr_learners_fcst.msarima`, `mlr_learners_fcst.prophet`, `mlr_learners_fcst.random_walk`, `mlr_learners_fcst.rlg`, `mlr_learners_fcst.sma`, `mlr_learners_fcst.spline`, `mlr_learners_fcst.ssarima`, `mlr_learners_fcst.stlm`, `mlr_learners_fcst.struct_ts`, `mlr_learners_fcst.tbats`, `mlr_learners_fcst.theta`, `mlr_learners_fcst.tscou`, `mlr_learners_fcst.tsml`

Examples

```
# Define the Learner and set parameter values
learner = lrn("fcst.nnetar")
print(learner)

# Define a Task
task = tsk("airpassengers")

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)

# Print the model
print(learner$model)

# Importance method
if ("importance" %in% learner$properties) print(learner$importance())

# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()
```

mlr_learners_fcst.prophet

Prophet Forecast Learner

Description

Prophet model. Calls `prophet::prophet()` from package **prophet**.

Dictionary

This `mlr3::Learner` can be instantiated via the dictionary `mlr3::mlr_learners` or with the associated sugar function `mlr3::lrn()`:

```
mlr_learners$get("fcst.prophet")
lrn("fcst.prophet")
```

Meta Information

- Task type: “fcst”
- Predict Types: “response”
- Feature Types: “logical”, “integer”, “numeric”
- Required Packages: **mlr3**, **mlr3forecast**, **prophet**

Parameters

Id	Type	Default	Levels	Range
growth	character	linear	linear, logistic, flat	-
changepoints	untyped	NULL		-
n.changepoints	integer	25		$[0, \infty)$
changepoint.range	numeric	0.8		$[0, 1]$
yearly.seasonality	untyped	"auto"	additive, multiplicative	-
weekly.seasonality	untyped	"auto"		-
daily.seasonality	untyped	"auto"		-
holidays	untyped	NULL		-
seasonality.mode	character	additive		-
seasonality.prior.scale	numeric	10		$[0, \infty)$
holidays.prior.scale	numeric	10		$[0, \infty)$
changepoint.prior.scale	numeric	0.05		$[0, \infty)$
mcmc.samples	integer	0		$[0, \infty)$
interval.width	numeric	0.8		$[0, 1]$
uncertainty.samples	integer	1000		$[0, \infty)$
backend	character	NULL	rstan, cmdstanr	-

Super classes

```
mlr3::Learner -> mlr3::LearnerRegr -> LearnerFcst -> LearnerFcstProphet
```

Methods**Public methods:**

- `LearnerFcstProphet$new()`
- `LearnerFcstProphet$clone()`

`LearnerFcstProphet$new()`: Creates a new instance of this R6 class.

Usage:

```
LearnerFcstProphet$new()
```

`LearnerFcstProphet$clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerFcstProphet$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

References

Taylor SJ, Letham B (2018). "Forecasting at Scale." *The American Statistician*, **72**(1), 37–45.
[doi:10.1080/00031305.2017.1380080](https://doi.org/10.1080/00031305.2017.1380080).

See Also

- Chapter in the **mlr3book**: https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners
- Package **mlr3learners** for a solid collection of essential learners.
- Package **mlr3extralearners** for more learners.
- Dictionary of Learners: `mlr3::mlr_learners`
- `as.data.table(mlr_learners)` for a table of available Learners in the running session (depending on the loaded packages).
- **mlr3pipelines** to combine learners with pre- and postprocessing steps.
- Package **mlr3viz** for some generic visualizations.
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.
- **mlr3tuning** for tuning of hyperparameters, **mlr3tuningspaces** for established default tuning spaces.

Other Learner: `LearnerFcst`, `mlr_learners_fcst.adam`, `mlr_learners_fcst.arfima`, `mlr_learners_fcst.arima`, `mlr_learners_fcst.auto_adam`, `mlr_learners_fcst.auto_arima`, `mlr_learners_fcst.auto_ces`, `mlr_learners_fcst.auto_gum`, `mlr_learners_fcst.auto_msarima`, `mlr_learners_fcst.auto_ssarima`, `mlr_learners_fcst.bagged`, `mlr_learners_fcst.bats`, `mlr_learners_fcst.ces`, `mlr_learners_fcst.croston`, `mlr_learners_fcst.elm`, `mlr_learners_fcst.es`, `mlr_learners_fcst.ets`, `mlr_learners_fcst.gum`, `mlr_learners_fcst.holt_winters`, `mlr_learners_fcst.mean`, `mlr_learners_fcst.mlp`, `mlr_learners_fcst.msarima`, `mlr_learners_fcst.nnetar`, `mlr_learners_fcst.random_walk`, `mlr_learners_fcst.rlgt`, `mlr_learners_fcst.sma`, `mlr_learners_fcst.spline`, `mlr_learners_fcst.ssarima`, `mlr_learners_fcst.stlm`, `mlr_learners_fcst.struct_t`, `mlr_learners_fcst.tbats`, `mlr_learners_fcst.theta`, `mlr_learners_fcst.tscount`, `mlr_learners_fcst.tslm`

Examples

```
# Define the Learner and set parameter values
learner = lrn("fcst.prophet")
print(learner)

# Define a Task
task = tsk("airpassengers")

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)

# Print the model
print(learner$model)

# Importance method
if ("importance" %in% learner$properties) print(learner$importance())

# Make predictions for the test rows
```

```

predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()

```

```
mlr_learners_fcst.random_walk
```

Random Walk Forecast Learner

Description

Random walk model. Calls `forecast::rw_model()` from package **forecast**.

Dictionary

This `mlr3::Learner` can be instantiated via the dictionary `mlr3::mlr_learners` or with the associated sugar function `mlr3::lrn()`:

```

mlr_learners$get("fcst.random_walk")
lrn("fcst.random_walk")

```

Meta Information

- Task type: “fcst”
- Predict Types: “response”, “quantiles”
- Feature Types: “logical”, “integer”, “numeric”
- Required Packages: **mlr3**, **mlr3forecast**, **forecast**

Parameters

Id	Type	Default	Levels	Range
lag	integer	1		$[1, \infty)$
drift	logical	FALSE	TRUE, FALSE	-
lambda	untyped	NULL		-
biasadj	logical	FALSE	TRUE, FALSE	-
simulate	logical	FALSE	TRUE, FALSE	-
bootstrap	logical	FALSE	TRUE, FALSE	-
npaths	integer	5000		$[1, \infty)$

Super classes

```
mlr3::Learner -> mlr3::LearnerRegr -> LearnerFcst -> LearnerFcstForecast -> LearnerFcstRandomWalk
```

Methods

Public methods:

- `LearnerFcstRandomWalk$new()`
- `LearnerFcstRandomWalk$clone()`

`LearnerFcstRandomWalk$new()`: Creates a new instance of this R6 class.

Usage:

```
LearnerFcstRandomWalk$new()
```

`LearnerFcstRandomWalk$clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerFcstRandomWalk$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

- Chapter in the [mlr3book](https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners): https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners
- Package **mlr3learners** for a solid collection of essential learners.
- Package **mlr3extralearners** for more learners.
- Dictionary of Learners: `mlr3::mlr_learners`
- `as.data.table(mlr_learners)` for a table of available Learners in the running session (depending on the loaded packages).
- **mlr3pipelines** to combine learners with pre- and postprocessing steps.
- Package **mlr3viz** for some generic visualizations.
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.
- **mlr3tuning** for tuning of hyperparameters, **mlr3tuningpaces** for established default tuning spaces.

Other Learner: `LearnerFcst`, `mlr_learners_fcst.adam`, `mlr_learners_fcst.arfima`, `mlr_learners_fcst.arima`, `mlr_learners_fcst.auto_adam`, `mlr_learners_fcst.auto_arima`, `mlr_learners_fcst.auto_ces`, `mlr_learners_fcst.auto_gum`, `mlr_learners_fcst.auto_msarima`, `mlr_learners_fcst.auto_ssarima`, `mlr_learners_fcst.bagged`, `mlr_learners_fcst.bats`, `mlr_learners_fcst.ces`, `mlr_learners_fcst.croston`, `mlr_learners_fcst.elm`, `mlr_learners_fcst.es`, `mlr_learners_fcst.ets`, `mlr_learners_fcst.gum`, `mlr_learners_fcst.holt_winters`, `mlr_learners_fcst.mean`, `mlr_learners_fcst.mlp`, `mlr_learners_fcst.msarima`, `mlr_learners_fcst.nnetar`, `mlr_learners_fcst.prophet`, `mlr_learners_fcst.rlg`, `mlr_learners_fcst.sma`, `mlr_learners_fcst.spline`, `mlr_learners_fcst.ssarima`, `mlr_learners_fcst.stlm`, `mlr_learners_fcst.struct`, `mlr_learners_fcst.tbats`, `mlr_learners_fcst.theta`, `mlr_learners_fcst.tscount`, `mlr_learners_fcst.tslm`

Examples

```
# Define the Learner and set parameter values
learner = lrn("fcst.random_walk")
print(learner)

# Define a Task
task = tsk("airpassengers")

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)

# Print the model
print(learner$model)

# Importance method
if ("importance" %in% learner$properties) print(learner$importance())

# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()
```

mlr_learners_fcst.rlgt

Local and Global Trend Forecast Learner

Description

Bayesian exponential smoothing with a nonlinear global trend (LGT/SGT), Student-t errors, and optional heteroscedasticity, fitted via MCMC. The seasonal period is taken from the frequency of the series. Calls `Rlgt::rlgt()` from package **Rlgt**.

Dictionary

This `mlr3::Learner` can be instantiated via the dictionary `mlr3::mlr_learners` or with the associated sugar function `mlr3::lrn()`:

```
mlr_learners$get("fcst.rlgt")
lrn("fcst.rlgt")
```

Meta Information

- Task type: “fcst”
- Predict Types: “response”, “quantiles”
- Feature Types: “logical”, “integer”, “numeric”
- Required Packages: **mlr3**, **mlr3forecast**, **Rlgt**

Parameters

Id	Type	Default	Levels	Range
seasonality	integer	1		$[1, \infty)$
seasonality2	integer	1		$[1, \infty)$
seasonality.type	character	multiplicative	multiplicative, generalized	-
error.size.method	character	std	std, innov	-
level.method	character	HW	HW, seasAvg, HW_sAvg	-
method	character	Gibbs	Gibbs, Stan	-
homoscedastic	logical	FALSE	TRUE, FALSE	-
control	untyped	NULL		-
verbose	logical	FALSE	TRUE, FALSE	-
NUM_OF_TRIALS	integer	2000		$[1, \infty)$

Super classes

`mlr3::Learner -> mlr3::LearnerRegr -> LearnerFcst -> LearnerFcstForecast -> LearnerFcstRlgt`

Methods

Public methods:

- `LearnerFcstRlgt$new()`
- `LearnerFcstRlgt$clone()`

`LearnerFcstRlgt$new()`: Creates a new instance of this [R6](#) class.

Usage:

```
LearnerFcstRlgt$new()
```

`LearnerFcstRlgt$clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerFcstRlgt$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

References

Smyl S, Bergmeir C, Wibowo E, Ng TW, Long X, Dokumentov A, Schmidt D (2025). *Rlgt: Bayesian Exponential Smoothing Models with Trend Modifications*. R package version 0.2-3, <https://github.com/cbergmeir/Rlgt>.

See Also

- Chapter in the **mlr3book**: https://mlr3book.ml-r.org/chapters/chapter2/data_and_basic_modeling.html#sec-learners
- Package **mlr3learners** for a solid collection of essential learners.
- Package **mlr3extralearners** for more learners.
- **Dictionary of Learners**: `mlr3::mlr_learners`
- `as.data.table(mlr_learners)` for a table of available **Learners** in the running session (depending on the loaded packages).
- **mlr3pipelines** to combine learners with pre- and postprocessing steps.
- Package **mlr3viz** for some generic visualizations.
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.
- **mlr3tuning** for tuning of hyperparameters, **mlr3tuningpaces** for established default tuning spaces.

Other Learner: `LearnerFcst`, `mlr_learners_fcst.adam`, `mlr_learners_fcst.arfima`, `mlr_learners_fcst.arima`, `mlr_learners_fcst.auto_adam`, `mlr_learners_fcst.auto_arima`, `mlr_learners_fcst.auto_ces`, `mlr_learners_fcst.auto_gum`, `mlr_learners_fcst.auto_msarima`, `mlr_learners_fcst.auto_ssarima`, `mlr_learners_fcst.bagged`, `mlr_learners_fcst.bats`, `mlr_learners_fcst.ces`, `mlr_learners_fcst.croston`, `mlr_learners_fcst.elm`, `mlr_learners_fcst.es`, `mlr_learners_fcst.ets`, `mlr_learners_fcst.gum`, `mlr_learners_fcst.holt_winters`, `mlr_learners_fcst.mean`, `mlr_learners_fcst.mlp`, `mlr_learners_fcst.msarima`, `mlr_learners_fcst.nnetar`, `mlr_learners_fcst.prophet`, `mlr_learners_fcst.random_walk`, `mlr_learners_fcst.sma`, `mlr_learners_fcst.spline`, `mlr_learners_fcst.ssarima`, `mlr_learners_fcst.stlm`, `mlr_learners_fcst.struct_ts`, `mlr_learners_fcst.tbats`, `mlr_learners_fcst.theta`, `mlr_learners_fcst.tscou`, `mlr_learners_fcst.tslm`

Examples

```
# Define the Learner and set parameter values
learner = lrn("fcst.rlgt")
print(learner)

# Define a Task
task = ts("airpassengers")

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
```

```
learner$train(task, row_ids = ids$train)

# Print the model
print(learner$model)

# Importance method
if ("importance" %in% learner$properties) print(learner$importance())

# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()
```

mlr_learners_fcst.sma	<i>Simple Moving Average Forecast Learner</i>
-----------------------	---

Description

Simple moving average. The forecast is the mean of the last order observations. If order is NULL (the default), the optimal window is selected automatically according to the chosen information criterion i.e. Calls `smooth::sma()` from package **smooth**.

Dictionary

This `mlr3::Learner` can be instantiated via the dictionary `mlr3::mlr_learners` or with the associated sugar function `mlr3::lrn()`:

```
mlr_learners$get("fcst.sma")
lrn("fcst.sma")
```

Meta Information

- Task type: “fcst”
- Predict Types: “response”
- Feature Types: “logical”, “integer”, “numeric”, “character”, “factor”, “ordered”, “POSIXct”, “Date”
- Required Packages: **mlr3**, **mlr3forecast**, **smooth**

Parameters

Id	Type	Default	Levels	Range
order	integer	NULL		$[1, \infty)$
ic	character	AICc	AICc, AIC, BIC, BICc	-
holdout	logical	FALSE	TRUE, FALSE	-

silent	logical	TRUE	TRUE, FALSE	-
fast	logical	TRUE	TRUE, FALSE	-

Super classes

```
mlr3::Learner -> mlr3::LearnerRegr -> LearnerFcst -> LearnerFcstSma
```

Methods

Public methods:

- `LearnerFcstSma$new()`
- `LearnerFcstSma$clone()`

`LearnerFcstSma$new()`: Creates a new instance of this [R6](#) class.

Usage:

```
LearnerFcstSma$new()
```

`LearnerFcstSma$clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerFcstSma$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

References

Svetunkov I (2023). “Smooth forecasting with the smooth package in R.” 2301.01790, <https://arxiv.org/abs/2301.01790>.

See Also

- Chapter in the [mlr3book](https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners): https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners
- Package **mlr3learners** for a solid collection of essential learners.
- Package **mlr3extralearners** for more learners.
- [Dictionary of Learners](#): `mlr3::mlr_learners`
- `as.data.table(mlr_learners)` for a table of available [Learners](#) in the running session (depending on the loaded packages).
- **mlr3pipelines** to combine learners with pre- and postprocessing steps.
- Package **mlr3viz** for some generic visualizations.
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.

- **mlr3cluster** for unsupervised clustering.
- **mlr3tuning** for tuning of hyperparameters, **mlr3tuningspaces** for established default tuning spaces.

Other Learner: `LearnerFcst`, `mlr_learners_fcst.adam`, `mlr_learners_fcst.arfima`, `mlr_learners_fcst.arima`, `mlr_learners_fcst.auto_adam`, `mlr_learners_fcst.auto_arima`, `mlr_learners_fcst.auto_ces`, `mlr_learners_fcst.auto_gum`, `mlr_learners_fcst.auto_msarima`, `mlr_learners_fcst.auto_ssarima`, `mlr_learners_fcst.bagged`, `mlr_learners_fcst.bats`, `mlr_learners_fcst.ces`, `mlr_learners_fcst.croston`, `mlr_learners_fcst.elm`, `mlr_learners_fcst.es`, `mlr_learners_fcst.ets`, `mlr_learners_fcst.gum`, `mlr_learners_fcst.holt_winters`, `mlr_learners_fcst.mean`, `mlr_learners_fcst.mlp`, `mlr_learners_fcst.msarima`, `mlr_learners_fcst.nnetar`, `mlr_learners_fcst.prophet`, `mlr_learners_fcst.random_walk`, `mlr_learners_fcst.rlgt`, `mlr_learners_fcst.spline`, `mlr_learners_fcst.ssarima`, `mlr_learners_fcst.stlm`, `mlr_learners_fcst.struct_ts`, `mlr_learners_fcst.tbats`, `mlr_learners_fcst.theta`, `mlr_learners_fcst.tscou`, `mlr_learners_fcst.tslm`

Examples

```
# Define the Learner and set parameter values
learner = lrn("fcst.sma")
print(learner)

# Define a Task
task = tsk("airpassengers")

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)

# Print the model
print(learner$model)

# Importance method
if ("importance" %in% learner$properties) print(learner$importance())

# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()
```

`mlr_learners_fcst.spline`

Spline Forecast Learner

Description

Cubic spline stochastic model. Calls `forecast::spline_model()` from package **forecast**.

Dictionary

This `mlr3::Learner` can be instantiated via the dictionary `mlr3::mlr_learners` or with the associated sugar function `mlr3::lrn()`:

```
mlr_learners$get("fcst.spline")
lrn("fcst.spline")
```

Meta Information

- Task type: “fcst”
- Predict Types: “response”, “quantiles”
- Feature Types: “logical”, “integer”, “numeric”
- Required Packages: **mlr3**, **mlr3forecast**, **forecast**

Parameters

Id	Type	Default	Levels	Range
method	character	gcv	gcv, mle	-
lambda	untyped	NULL		-
biasadj	logical	FALSE	TRUE, FALSE	-
simulate	logical	FALSE	TRUE, FALSE	-
bootstrap	logical	FALSE	TRUE, FALSE	-
npaths	integer	5000		$[1, \infty)$

Super classes

```
mlr3::Learner -> mlr3::LearnerRegr -> LearnerFcst -> LearnerFcstForecast -> LearnerFcstSpline
```

Methods

Public methods:

- `LearnerFcstSpline$new()`
- `LearnerFcstSpline$clone()`

`LearnerFcstSpline$new()`: Creates a new instance of this [R6](#) class.

Usage:

```
LearnerFcstSpline$new()
```

`LearnerFcstSpline$clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerFcstSpline$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

References

Hyndman RJ, King ML, Pitrun I, Billah B (2005). “Local linear forecasts using cubic smoothing splines.” *Australian & New Zealand Journal of Statistics*, **47**(1), 87–99.

See Also

- Chapter in the **mlr3book**: https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners
- Package **mlr3learners** for a solid collection of essential learners.
- Package **mlr3extralearners** for more learners.
- **Dictionary of Learners**: `mlr3::mlr_learners`
- `as.data.table(mlr_learners)` for a table of available **Learners** in the running session (depending on the loaded packages).
- **mlr3pipelines** to combine learners with pre- and postprocessing steps.
- Package **mlr3viz** for some generic visualizations.
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.
- **mlr3tuning** for tuning of hyperparameters, **mlr3tuningpaces** for established default tuning spaces.

Other Learner: `LearnerFcst`, `mlr_learners_fcst.adam`, `mlr_learners_fcst.arfima`, `mlr_learners_fcst.arima`, `mlr_learners_fcst.auto_adam`, `mlr_learners_fcst.auto_arima`, `mlr_learners_fcst.auto_ces`, `mlr_learners_fcst.auto_gum`, `mlr_learners_fcst.auto_msarima`, `mlr_learners_fcst.auto_ssarima`, `mlr_learners_fcst.bagged`, `mlr_learners_fcst.bats`, `mlr_learners_fcst.ces`, `mlr_learners_fcst.croston`, `mlr_learners_fcst.elm`, `mlr_learners_fcst.es`, `mlr_learners_fcst.ets`, `mlr_learners_fcst.gum`, `mlr_learners_fcst.holt_winters`, `mlr_learners_fcst.mean`, `mlr_learners_fcst.mlp`, `mlr_learners_fcst.msarima`, `mlr_learners_fcst.nnetar`, `mlr_learners_fcst.prophet`, `mlr_learners_fcst.random_walk`, `mlr_learners_fcst.rlgt`, `mlr_learners_fcst.sma`, `mlr_learners_fcst.ssarima`, `mlr_learners_fcst.stlm`, `mlr_learners_fcst.struct_ts`, `mlr_learners_fcst.tbats`, `mlr_learners_fcst.theta`, `mlr_learners_fcst.tscou`, `mlr_learners_fcst.tslm`

Examples

```
# Define the Learner and set parameter values
learner = lrn("fcst.spline")
print(learner)

# Define a Task
task = tsk("airpassengers")

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)
```

```
# Print the model
print(learner$model)

# Importance method
if ("importance" %in% learner$properties) print(learner$importance())

# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()
```

mlr_learners_fcst.ssarima
State-Space ARIMA Forecast Learner

Description

State-Space ARIMA model. Supports multiple seasonal lags natively (e.g. lags = c(1, 24, 168) for hourly data with daily and weekly cycles). Calls `smooth::ssarima()` from package **smooth**.

Dictionary

This `mlr3::Learner` can be instantiated via the dictionary `mlr3::mlr_learners` or with the associated sugar function `mlr3::lrn()`:

```
mlr_learners$get("fcst.ssarima")
lrn("fcst.ssarima")
```

Meta Information

- Task type: “fcst”
- Predict Types: “response”, “quantiles”
- Feature Types: “logical”, “integer”, “numeric”
- Required Packages: **mlr3**, **mlr3forecast**, **smooth**

Parameters

Id	Type	Default	Levels
orders	untyped	list(ar = 0, i = 1, ma = 1)	
lags	untyped	-	
constant	logical	FALSE	TRUE, FALSE
arma	untyped	NULL	
initial	character	backcasting	backcasting, optimal, two-stage, complete
loss	character	likelihood	likelihood, MSE, MAE, HAM, MSEh, TMSE, GTMSE, MSCE, GPL

holdout	logical	FALSE	TRUE, FALSE
bounds	character	admissible	admissible, usual, none
silent	logical	TRUE	TRUE, FALSE
regressors	character	use	use, select, adapt

Super classes

`mlr3::Learner -> mlr3::LearnerRegr -> LearnerFcst -> LearnerFcstSmooth -> LearnerFcstSsarima`

Methods

Public methods:

- `LearnerFcstSsarima$new()`
- `LearnerFcstSsarima$clone()`

`LearnerFcstSsarima$new()`: Creates a new instance of this [R6](#) class.

Usage:

```
LearnerFcstSsarima$new()
```

`LearnerFcstSsarima$clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerFcstSsarima$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

References

Svetunkov I (2023). “Smooth forecasting with the smooth package in R.” 2301.01790, <https://arxiv.org/abs/2301.01790>.

Svetunkov I (2023). *Forecasting and Analytics with the Augmented Dynamic Adaptive Model (ADAM)*, 1st edition. Chapman and Hall/CRC. doi:10.1201/9781003452652. <https://openforecast.org/adam/>.

See Also

- Chapter in the [mlr3book](https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners): https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners
- Package [mlr3learners](#) for a solid collection of essential learners.
- Package [mlr3extralearners](#) for more learners.
- [Dictionary of Learners: mlr3::mlr_learners](#)
- `as.data.table(mlr_learners)` for a table of available [Learners](#) in the running session (depending on the loaded packages).

- **mlr3pipelines** to combine learners with pre- and postprocessing steps.
- Package **mlr3viz** for some generic visualizations.
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.
- **mlr3tuning** for tuning of hyperparameters, **mlr3tuningspaces** for established default tuning spaces.

Other Learner: `LearnerFcst`, `mlr_learners_fcst.adam`, `mlr_learners_fcst.arfima`, `mlr_learners_fcst.arima`, `mlr_learners_fcst.auto_adam`, `mlr_learners_fcst.auto_arima`, `mlr_learners_fcst.auto_ces`, `mlr_learners_fcst.auto_gum`, `mlr_learners_fcst.auto_msarima`, `mlr_learners_fcst.auto_ssarima`, `mlr_learners_fcst.bagged`, `mlr_learners_fcst.bats`, `mlr_learners_fcst.ces`, `mlr_learners_fcst.croston`, `mlr_learners_fcst.elm`, `mlr_learners_fcst.es`, `mlr_learners_fcst.ets`, `mlr_learners_fcst.gum`, `mlr_learners_fcst.holt_winters`, `mlr_learners_fcst.mean`, `mlr_learners_fcst.mlp`, `mlr_learners_fcst.msarima`, `mlr_learners_fcst.nnetar`, `mlr_learners_fcst.prophet`, `mlr_learners_fcst.random_walk`, `mlr_learners_fcst.rlgt`, `mlr_learners_fcst.sma`, `mlr_learners_fcst.spline`, `mlr_learners_fcst.stlm`, `mlr_learners_fcst.struct_ts`, `mlr_learners_fcst.tbats`, `mlr_learners_fcst.theta`, `mlr_learners_fcst.tscout`, `mlr_learners_fcst.tslm`

Examples

```
# Define the Learner and set parameter values
learner = lrn("fcst.ssarima")
print(learner)

# Define a Task
task = tsk("airpassengers")

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)

# Print the model
print(learner$model)

# Importance method
if ("importance" %in% learner$properties) print(learner$importance())

# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()
```

mlr_learners_fcst.stlm
<i>STL + ETS/ARIMA Forecast Learner</i>

Description

Forecasts of seasonal time series using STL decomposition. The seasonal component is forecast naively and the seasonally-adjusted series is forecast with either an ETS or ARIMA model. Calls `forecast::stlm()` from package **forecast**.
The task must provide a seasonal time series (frequency > 1).

Dictionary

This `mlr3::Learner` can be instantiated via the dictionary `mlr3::mlr_learners` or with the associated sugar function `mlr3::lrn()`:

```
mlr_learners$get("fcst.stlm")
lrn("fcst.stlm")
```

Meta Information

- Task type: “fcst”
- Predict Types: “response”, “quantiles”
- Feature Types: “logical”, “integer”, “numeric”
- Required Packages: **mlr3**, **mlr3forecast**, **forecast**

Parameters

Id	Type	Default	Levels	Range
s.window	untyped	7L + 4L * seq_len(6L)		-
t.window	integer	NULL		[1, ∞)
robust	logical	FALSE	TRUE, FALSE	-
method	character	ets	ets, arima	-
modelfunction	untyped	NULL		-
etsmodel	untyped	"ZZN"		-
lambda	untyped	NULL		-
biasadj	logical	FALSE	TRUE, FALSE	-
allow.multiplicative.trend	logical	FALSE	TRUE, FALSE	-

Super classes

```
mlr3::Learner -> mlr3::LearnerRegr -> LearnerFcst -> LearnerFcstForecast -> LearnerFcstStlm
```

Methods

Public methods:

- `LearnerFcstStlm$new()`
- `LearnerFcstStlm$clone()`

`LearnerFcstStlm$new()`: Creates a new instance of this [R6](#) class.

Usage:

```
LearnerFcstStlm$new()
```

`LearnerFcstStlm$clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerFcstStlm$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

References

Cleveland RB, Cleveland WS, McRae JE, Terpenning I (1990). “STL: A Seasonal-Trend Decomposition Procedure Based on Loess.” *Journal of Official Statistics*, **6**(1), 3–73.

Hyndman RJ, Athanasopoulos G (2018). *Forecasting: principles and practice*, 2nd edition. OTexts, Melbourne, Australia. <https://OTexts.com/fpp2/>.

See Also

- Chapter in the [mlr3book](https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners): https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners
- Package **mlr3learners** for a solid collection of essential learners.
- Package **mlr3extralearners** for more learners.
- [Dictionary of Learners](#): `mlr3::mlr_learners`
- `as.data.table(mlr_learners)` for a table of available [Learners](#) in the running session (depending on the loaded packages).
- **mlr3pipelines** to combine learners with pre- and postprocessing steps.
- Package **mlr3viz** for some generic visualizations.
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.
- **mlr3tuning** for tuning of hyperparameters, **mlr3tuningspaces** for established default tuning spaces.

Other Learner: `LearnerFcst`, `mlr_learners_fcst.adam`, `mlr_learners_fcst.arfima`, `mlr_learners_fcst.arima`, `mlr_learners_fcst.auto_adam`, `mlr_learners_fcst.auto_arima`, `mlr_learners_fcst.auto_ces`, `mlr_learners_fcst.auto_gum`, `mlr_learners_fcst.auto_msarima`, `mlr_learners_fcst.auto_ssarima`, `mlr_learners_fcst.bagged`, `mlr_learners_fcst.bats`, `mlr_learners_fcst.ces`, `mlr_learners_fcst.croston`, `mlr_learners_fcst.elm`, `mlr_learners_fcst.es`, `mlr_learners_fcst.ets`, `mlr_learners_fcst.gum`,

```
mlr_learners_fcst.holt_winters,mlr_learners_fcst.mean,mlr_learners_fcst.mlp,mlr_learners_fcst.msarima,
mlr_learners_fcst.nnetar,mlr_learners_fcst.prophet,mlr_learners_fcst.random_walk,
mlr_learners_fcst.rlg,mlr_learners_fcst.sma,mlr_learners_fcst.spline,mlr_learners_fcst.ssarima,
mlr_learners_fcst.struct_ts,mlr_learners_fcst.tbats,mlr_learners_fcst.theta,mlr_learners_fcst.tscout,
mlr_learners_fcst.tslm
```

Examples

```
# Define the Learner and set parameter values
learner = lrn("fcst.stlm")
print(learner)

# Define a Task
task = tsk("airpassengers")

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)

# Print the model
print(learner$model)

# Importance method
if ("importance" %in% learner$properties) print(learner$importance())

# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()
```

```
mlr_learners_fcst.struct_ts
```

Structural Time Series Forecast Learner

Description

Structural time series model fit by maximum likelihood. Three model types are supported: local level, local linear trend, and basic structural model (level + trend + seasonal). Calls `stats::StructTS()` from package **stats**.

type = "BSM" requires a seasonal time series (frequency > 1). Prediction is performed via `forecast::forecast.StructTS()` which yields point forecasts and predictive intervals from the Kalman filter.

Dictionary

This `mlr3::Learner` can be instantiated via the dictionary `mlr3::mlr_learners` or with the associated sugar function `mlr3::lrn()`:

```
mlr_learners$get("fcst.struct_ts")
lrn("fcst.struct_ts")
```

Meta Information

- Task type: “fcst”
- Predict Types: “response”, “quantiles”
- Feature Types: “logical”, “integer”, “numeric”, “character”, “factor”, “ordered”, “POSIXct”, “Date”
- Required Packages: **mlr3**, **mlr3forecast**, **forecast**

Parameters

Id	Type	Default	Levels
type	character	level	level, trend, BSM
init	untyped	NULL	
fixed	untyped	NULL	
optim.control	untyped	NULL	
lambda	untyped	NULL	
biasadj	logical	FALSE	TRUE, FALSE

Super classes

```
mlr3::Learner -> mlr3::LearnerRegr -> LearnerFcst -> LearnerFcstForecast -> LearnerFcstStructTS
```

Methods

Public methods:

- `LearnerFcstStructTS$new()`
- `LearnerFcstStructTS$clone()`

`LearnerFcstStructTS$new()`: Creates a new instance of this [R6](#) class.

Usage:

```
LearnerFcstStructTS$new()
```

`LearnerFcstStructTS$clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerFcstStructTS$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

References

Harvey AC (1989). *Forecasting, Structural Time Series Models and the Kalman Filter*. Cambridge University Press, Cambridge.

See Also

- Chapter in the **mlr3book**: https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners
- Package **mlr3learners** for a solid collection of essential learners.
- Package **mlr3extralearners** for more learners.
- **Dictionary of Learners**: `mlr3::mlr_learners`
- `as.data.table(mlr_learners)` for a table of available **Learners** in the running session (depending on the loaded packages).
- **mlr3pipelines** to combine learners with pre- and postprocessing steps.
- Package **mlr3viz** for some generic visualizations.
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.
- **mlr3tuning** for tuning of hyperparameters, **mlr3tuningspaces** for established default tuning spaces.

Other Learner: `LearnerFcst`, `mlr_learners_fcst.adam`, `mlr_learners_fcst.arfima`, `mlr_learners_fcst.arima`, `mlr_learners_fcst.auto_adam`, `mlr_learners_fcst.auto_arima`, `mlr_learners_fcst.auto_ces`, `mlr_learners_fcst.auto_gum`, `mlr_learners_fcst.auto_msarima`, `mlr_learners_fcst.auto_ssarima`, `mlr_learners_fcst.bagged`, `mlr_learners_fcst.bats`, `mlr_learners_fcst.ces`, `mlr_learners_fcst.croston`, `mlr_learners_fcst.elm`, `mlr_learners_fcst.es`, `mlr_learners_fcst.ets`, `mlr_learners_fcst.gum`, `mlr_learners_fcst.holt_winters`, `mlr_learners_fcst.mean`, `mlr_learners_fcst.mlp`, `mlr_learners_fcst.msarima`, `mlr_learners_fcst.nnetar`, `mlr_learners_fcst.prophet`, `mlr_learners_fcst.random_walk`, `mlr_learners_fcst.rlgt`, `mlr_learners_fcst.sma`, `mlr_learners_fcst.spline`, `mlr_learners_fcst.ssarima`, `mlr_learners_fcst.stlm`, `mlr_learners_fcst.tbats`, `mlr_learners_fcst.theta`, `mlr_learners_fcst.tscount`, `mlr_learners_fcst.tslm`

Examples

```
# Define the Learner and set parameter values
learner = lrn("fcst.struct_ts")
print(learner)

# Define a Task
task = tsk("airpassengers")

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)
```

```
# Print the model
print(learner$model)

# Importance method
if ("importance" %in% learner$properties) print(learner$importance())

# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()
```

```
mlr_learners_fcst.tbats
      TBATS Forecast Learner
```

Description

Exponential smoothing state space model with Box-Cox transformation, ARMA errors, Trend and Seasonal components (TBATS) model. Calls `forecast::tbats()` from package **forecast**.

Dictionary

This `mlr3::Learner` can be instantiated via the dictionary `mlr3::mlr_learners` or with the associated sugar function `mlr3::lrn()`:

```
mlr_learners$get("fcst.tbats")
lrn("fcst.tbats")
```

Meta Information

- Task type: “fcst”
- Predict Types: “response”, “quantiles”
- Feature Types: “logical”, “integer”, “numeric”, “character”, “factor”, “ordered”, “POSIXct”, “Date”
- Required Packages: **mlr3**, **mlr3forecast**, **forecast**

Parameters

Id	Type	Default	Levels	Range
use.box.cox	logical	NULL	TRUE, FALSE	-
use.trend	logical	NULL	TRUE, FALSE	-
use.damped.trend	logical	NULL	TRUE, FALSE	-
seasonal.periods	untyped	NULL		-
use.arma.errors	logical	TRUE	TRUE, FALSE	-

use.parallel	logical	-	TRUE, FALSE	-
num.cores	integer	2		$[1, \infty)$
bc.lower	numeric	0		$(-\infty, \infty)$
bc.upper	numeric	1		$(-\infty, \infty)$
biasadj	logical	FALSE	TRUE, FALSE	-
simulate	logical	FALSE	TRUE, FALSE	-
bootstrap	logical	FALSE	TRUE, FALSE	-
npaths	integer	5000		$[1, \infty)$

Super classes

`mlr3::Learner` -> `mlr3::LearnerRegr` -> `LearnerFcst` -> `LearnerFcstForecast` -> `LearnerFcstTbats`

Methods

Public methods:

- `LearnerFcstTbats$new()`
- `LearnerFcstTbats$clone()`

`LearnerFcstTbats$new()`: Creates a new instance of this R6 class.

Usage:

```
LearnerFcstTbats$new()
```

`LearnerFcstTbats$clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerFcstTbats$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

References

De Livera AM, Hyndman RJ, Snyder RD (2011). “Forecasting time series with complex seasonal patterns using exponential smoothing.” *Journal of the American Statistical Association*, **106**(496), 1513–1527.

See Also

- Chapter in the `mlr3book`: https://mlr3book.ml-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners
- Package `mlr3learners` for a solid collection of essential learners.
- Package `mlr3extralearners` for more learners.
- Dictionary of Learners: `mlr3::mlr_learners`

- `as.data.table(mlr_learners)` for a table of available [Learners](#) in the running session (depending on the loaded packages).
- **mlr3pipelines** to combine learners with pre- and postprocessing steps.
- Package **mlr3viz** for some generic visualizations.
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.
- **mlr3tuning** for tuning of hyperparameters, **mlr3tuningspaces** for established default tuning spaces.

Other Learner: `LearnerFcst`, `mlr_learners_fcst.adam`, `mlr_learners_fcst.arfima`, `mlr_learners_fcst.arima`, `mlr_learners_fcst.auto_adam`, `mlr_learners_fcst.auto_arima`, `mlr_learners_fcst.auto_ces`, `mlr_learners_fcst.auto_gum`, `mlr_learners_fcst.auto_msarima`, `mlr_learners_fcst.auto_ssarima`, `mlr_learners_fcst.bagged`, `mlr_learners_fcst.bats`, `mlr_learners_fcst.ces`, `mlr_learners_fcst.croston`, `mlr_learners_fcst.elm`, `mlr_learners_fcst.es`, `mlr_learners_fcst.ets`, `mlr_learners_fcst.gum`, `mlr_learners_fcst.holt_winters`, `mlr_learners_fcst.mean`, `mlr_learners_fcst.mlp`, `mlr_learners_fcst.msarima`, `mlr_learners_fcst.nnetar`, `mlr_learners_fcst.prophet`, `mlr_learners_fcst.random_walk`, `mlr_learners_fcst.rlgt`, `mlr_learners_fcst.sma`, `mlr_learners_fcst.spline`, `mlr_learners_fcst.ssarima`, `mlr_learners_fcst.stlm`, `mlr_learners_fcst.struct_ts`, `mlr_learners_fcst.theta`, `mlr_learners_fcst.tscount`, `mlr_learners_fcst.tslm`

Examples

```
# Define the Learner and set parameter values
learner = lrn("fcst.tbats")
print(learner)

# Define a Task
task = tsk("airpassengers")

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)

# Print the model
print(learner$model)

# Importance method
if ("importance" %in% learner$properties) print(learner$importance())

# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()
```

mlr_learners_fcst.theta

Theta Forecast Learner

Description

Theta model. Calls `forecast::theta_model()` from package **forecast**.

Dictionary

This `mlr3::Learner` can be instantiated via the dictionary `mlr3::mlr_learners` or with the associated sugar function `mlr3::lrn()`:

```
mlr_learners$get("fcst.theta")
lrn("fcst.theta")
```

Meta Information

- Task type: “fcst”
- Predict Types: “response”, “quantiles”
- Feature Types: “logical”, “integer”, “numeric”
- Required Packages: **mlr3**, **mlr3forecast**, **forecast**

Parameters

Id	Type	Default	Levels
lambda	untyped	NULL	
biasadj	logical	FALSE	TRUE, FALSE

Super classes

```
mlr3::Learner -> mlr3::LearnerRegr -> LearnerFcst -> LearnerFcstForecast -> LearnerFcstTheta
```

Methods

Public methods:

- `LearnerFcstTheta$new()`
- `LearnerFcstTheta$clone()`

`LearnerFcstTheta$new()`: Creates a new instance of this **R6** class.

Usage:

```
LearnerFcstTheta$new()
```

LearnerFcstTheta\$clone(): The objects of this class are cloneable with this method.

Usage:

```
LearnerFcstTheta$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

References

Assimakopoulos V, Nikolopoulos K (2000). “The theta model: a decomposition approach to forecasting.” *International Journal of Forecasting*, **16**(4), 521–530.

Hyndman RJ, Billah B (2003). “Unmasking the Theta method.” *International Journal of Forecasting*, **19**(2), 287–290.

See Also

- Chapter in the **mlr3book**: https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners
- Package **mlr3learners** for a solid collection of essential learners.
- Package **mlr3extralearners** for more learners.
- **Dictionary of Learners**: `mlr3::mlr_learners`
- `as.data.table(mlr_learners)` for a table of available **Learners** in the running session (depending on the loaded packages).
- **mlr3pipelines** to combine learners with pre- and postprocessing steps.
- Package **mlr3viz** for some generic visualizations.
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.
- **mlr3tuning** for tuning of hyperparameters, **mlr3tuningspaces** for established default tuning spaces.

Other Learner: `LearnerFcst`, `mlr_learners_fcst.adam`, `mlr_learners_fcst.arfima`, `mlr_learners_fcst.arima`, `mlr_learners_fcst.auto_adam`, `mlr_learners_fcst.auto_arima`, `mlr_learners_fcst.auto_ces`, `mlr_learners_fcst.auto_gum`, `mlr_learners_fcst.auto_msarima`, `mlr_learners_fcst.auto_ssarima`, `mlr_learners_fcst.bagged`, `mlr_learners_fcst.bats`, `mlr_learners_fcst.ces`, `mlr_learners_fcst.croston`, `mlr_learners_fcst.elm`, `mlr_learners_fcst.es`, `mlr_learners_fcst.ets`, `mlr_learners_fcst.gum`, `mlr_learners_fcst.holt_winters`, `mlr_learners_fcst.mean`, `mlr_learners_fcst.mlp`, `mlr_learners_fcst.msarima`, `mlr_learners_fcst.nnetar`, `mlr_learners_fcst.prophet`, `mlr_learners_fcst.random_walk`, `mlr_learners_fcst.rlgt`, `mlr_learners_fcst.sma`, `mlr_learners_fcst.spline`, `mlr_learners_fcst.ssarima`, `mlr_learners_fcst.stlm`, `mlr_learners_fcst.struct_ts`, `mlr_learners_fcst.tbats`, `mlr_learners_fcst.tscount`, `mlr_learners_fcst.tsml`

Examples

```
# Define the Learner and set parameter values
learner = lrn("fcst.theta")
print(learner)

# Define a Task
task = tsk("airpassengers")

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)

# Print the model
print(learner$model)

# Importance method
if ("importance" %in% learner$properties) print(learner$importance())

# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()
```

```
mlr_learners_fcst.tscount
```

Count Time Series Forecast Learner

Description

Generalized linear model for count time series (INGARCH). Calls `tscount::tsglm()` from package **tscount**.

Dictionary

This `mlr3::Learner` can be instantiated via the dictionary `mlr3::mlr_learners` or with the associated sugar function `mlr3::lrn()`:

```
mlr_learners$get("fcst.tscount")
lrn("fcst.tscount")
```

Meta Information

- Task type: “fcst”
- Predict Types: “response”, “quantiles”
- Feature Types: “logical”, “integer”, “numeric”
- Required Packages: **mlr3**, **mlr3forecast**, **tscount**

Parameters

Id	Type	Default	Levels	Range
past_obs	untyped	NULL		-
past_mean	untyped	NULL		-
external	untyped	FALSE		-
link	character	identity	identity, log	-
distr	character	poisson	poisson, nbinom	-
B	integer	1000		$[10, \infty)$

Super classes

```
mlr3::Learner -> mlr3::LearnerRegr -> LearnerFcst -> LearnerFcstTscount
```

Methods**Public methods:**

- `LearnerFcstTscount$new()`
- `LearnerFcstTscount$clone()`

`LearnerFcstTscount$new()`: Creates a new instance of this [R6](#) class.

Usage:

```
LearnerFcstTscount$new()
```

`LearnerFcstTscount$clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerFcstTscount$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

References

Liboschik T, Fokianos K, Fried R (2017). “tscount: An R Package for Analysis of Count Time Series Following Generalized Linear Models.” *Journal of Statistical Software*, **82**(5), 1–51. doi:[10.18637/jss.v082.i05](https://doi.org/10.18637/jss.v082.i05).

See Also

- Chapter in the [mlr3book](https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners): https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners
- Package [mlr3learners](#) for a solid collection of essential learners.
- Package [mlr3extralearners](#) for more learners.
- Dictionary of Learners: [mlr3::mlr_learners](#)

- `as.data.table(mlr_learners)` for a table of available [Learners](#) in the running session (depending on the loaded packages).
- **mlr3pipelines** to combine learners with pre- and postprocessing steps.
- Package **mlr3viz** for some generic visualizations.
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.
- **mlr3tuning** for tuning of hyperparameters, **mlr3tuningspaces** for established default tuning spaces.

Other Learner: `LearnerFcst`, `mlr_learners_fcst.adam`, `mlr_learners_fcst.arfima`, `mlr_learners_fcst.arima`, `mlr_learners_fcst.auto_adam`, `mlr_learners_fcst.auto_arima`, `mlr_learners_fcst.auto_ces`, `mlr_learners_fcst.auto_gum`, `mlr_learners_fcst.auto_msarima`, `mlr_learners_fcst.auto_ssarima`, `mlr_learners_fcst.bagged`, `mlr_learners_fcst.bats`, `mlr_learners_fcst.ces`, `mlr_learners_fcst.croston`, `mlr_learners_fcst.elm`, `mlr_learners_fcst.es`, `mlr_learners_fcst.ets`, `mlr_learners_fcst.gum`, `mlr_learners_fcst.holt_winters`, `mlr_learners_fcst.mean`, `mlr_learners_fcst.mlp`, `mlr_learners_fcst.msarima`, `mlr_learners_fcst.nnetar`, `mlr_learners_fcst.prophet`, `mlr_learners_fcst.random_walk`, `mlr_learners_fcst.rlgt`, `mlr_learners_fcst.sma`, `mlr_learners_fcst.spline`, `mlr_learners_fcst.ssarima`, `mlr_learners_fcst.stlm`, `mlr_learners_fcst.struct_ts`, `mlr_learners_fcst.tbats`, `mlr_learners_fcst.theta`, `mlr_learners_fcst.tslm`

Examples

```
# Define the Learner and set parameter values
learner = lrn("fcst.tscount")
print(learner)

# Define a Task
task = tsk("airpassengers")

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)

# Print the model
print(learner$model)

# Importance method
if ("importance" %in% learner$properties) print(learner$importance())

# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()
```

mlr_learners_fcst.tslm

Time Series Linear Model Forecast Learner

Description

Time series linear model. Calls `forecast::tslm()` from package **forecast**.

If formula is not set, the model is fit with the trend and season terms of `forecast::tslm()` plus all features, i.e. `<target> ~ trend + season + <features>`.

Dictionary

This `mlr3::Learner` can be instantiated via the dictionary `mlr3::mlr_learners` or with the associated sugar function `mlr3::lrn()`:

```
mlr_learners$get("fcst.tslm")
lrn("fcst.tslm")
```

Meta Information

- Task type: “fcst”
- Predict Types: “response”, “quantiles”
- Feature Types: “logical”, “integer”, “numeric”
- Required Packages: **mlr3**, **mlr3forecast**, **forecast**

Parameters

Id	Type	Default	Levels
formula	untyped	-	
lambda	untyped	NULL	
biasadj	logical	FALSE	TRUE, FALSE

Super classes

```
mlr3::Learner -> mlr3::LearnerRegr -> LearnerFcst -> LearnerFcstForecast -> LearnerFcstTslm
```

Methods

Public methods:

- `LearnerFcstTslm$new()`
- `LearnerFcstTslm$clone()`

`LearnerFcstTslm$new()`: Creates a new instance of this R6 class.

Usage:

`LearnerFcstTslm$new()`

`LearnerFcstTslm$clone()`: The objects of this class are cloneable with this method.

Usage:

`LearnerFcstTslm$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

References

Hyndman RJ, Athanasopoulos G (2018). *Forecasting: principles and practice*, 2nd edition. OTexts, Melbourne, Australia. <https://OTexts.com/fpp2/>.

See Also

- Chapter in the `mlr3book`: https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-learners
- Package `mlr3learners` for a solid collection of essential learners.
- Package `mlr3extralearners` for more learners.
- Dictionary of Learners: `mlr3::mlr_learners`
- `as.data.table(mlr_learners)` for a table of available Learners in the running session (depending on the loaded packages).
- `mlr3pipelines` to combine learners with pre- and postprocessing steps.
- Package `mlr3viz` for some generic visualizations.
- Extension packages for additional task types:
 - `mlr3proba` for probabilistic supervised regression and survival analysis.
 - `mlr3cluster` for unsupervised clustering.
- `mlr3tuning` for tuning of hyperparameters, `mlr3tuningspaces` for established default tuning spaces.

Other Learner: `LearnerFcst`, `mlr_learners_fcst.adam`, `mlr_learners_fcst.arfima`, `mlr_learners_fcst.arima`, `mlr_learners_fcst.auto_adam`, `mlr_learners_fcst.auto_arima`, `mlr_learners_fcst.auto_ces`, `mlr_learners_fcst.auto_gum`, `mlr_learners_fcst.auto_msarima`, `mlr_learners_fcst.auto_ssarima`, `mlr_learners_fcst.bagged`, `mlr_learners_fcst.bats`, `mlr_learners_fcst.ces`, `mlr_learners_fcst.croston`, `mlr_learners_fcst.elm`, `mlr_learners_fcst.es`, `mlr_learners_fcst.ets`, `mlr_learners_fcst.gum`, `mlr_learners_fcst.holt_winters`, `mlr_learners_fcst.mean`, `mlr_learners_fcst.mlp`, `mlr_learners_fcst.msarima`, `mlr_learners_fcst.nnetar`, `mlr_learners_fcst.prophet`, `mlr_learners_fcst.random_walk`, `mlr_learners_fcst.rlgt`, `mlr_learners_fcst.sma`, `mlr_learners_fcst.spline`, `mlr_learners_fcst.ssarima`, `mlr_learners_fcst.stlm`, `mlr_learners_fcst.struct_ts`, `mlr_learners_fcst.tbats`, `mlr_learners_fcst.theta`, `mlr_learners_fcst.tscount`

Examples

```
# Define the Learner and set parameter values
learner = lrn("fcst.tslm")
print(learner)

# Define a Task
task = tsk("airpassengers")

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)

# Print the model
print(learner$model)

# Importance method
if ("importance" %in% learner$properties) print(learner$importance())

# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()
```

mlr_measures_fcst.acf1

Autocorrelation at Lag 1

Description

Measures the autocorrelation of the forecast residuals at lag 1. Values close to zero indicate that residuals are uncorrelated, while values far from zero suggest the model is not capturing all available information.

Details

Computed as the sample autocorrelation of the residuals at lag 1 using `stats::acf()`.

Dictionary

This `mlr3::Measure` can be instantiated via the dictionary `mlr3::mlr_measures` or with the associated sugar function `mlr3::msr()`:

```
mlr_measures$get("fcst.acf1")
msr("fcst.acf1")
```

Task type

Forecast measures are registered with `task_type = "regr"` so they compose with the standard regression measures (e.g. `mlr3::mlr_measures_regr.rmse`) on the `PredictionFcst` that forecast learners produce. List them via the key prefix, not the task type, as the latter returns nothing:

```
as.data.table(mlr_measures)[grep1("^fcst", key)]
```

Meta Information

- Task type: “regr”
- Range: $[-1, 1]$
- Minimize: NA
- Average: macro
- Required Prediction: “response”
- Required Packages: **mlr3**, **mlr3forecast**

Parameters

Empty ParamSet

Super classes

```
mlr3::Measure -> mlr3::MeasureRegr -> MeasureACF1
```

Methods

Public methods:

- `MeasureACF1$new()`
- `MeasureACF1$clone()`

`MeasureACF1$new()`: Creates a new instance of this [R6](#) class.

Usage:

```
MeasureACF1$new()
```

`MeasureACF1$clone()`: The objects of this class are cloneable with this method.

Usage:

```
MeasureACF1$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

- Chapter in the **mlr3book**: https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-eval
- Package **mlr3measures** for the scoring functions.
- **Dictionary** of Measures: `mlr3::mlr_measures`
- `as.data.table(mlr_measures)` for a table of available **Measures** in the running session (depending on the loaded packages).
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.

Other Measure: `mlr_measures_fcst.coverage`, `mlr_measures_fcst.mase`, `mlr_measures_fcst.mda`, `mlr_measures_fcst.mdvp`, `mlr_measures_fcst.mdv`, `mlr_measures_fcst.mpe`, `mlr_measures_fcst.msis`, `mlr_measures_fcst.pinball`, `mlr_measures_fcst.rmsse`, `mlr_measures_fcst.wape`, `mlr_measures_fcst.winkler`

`mlr_measures_fcst.coverage`

Empirical Coverage

Description

Measures the proportion of true values that fall within the prediction interval. A well-calibrated prediction interval at level $1 - \alpha$ should have coverage close to $1 - \alpha$.

Details

$$\text{Coverage} = \frac{1}{n} \sum_{i=1}^n \mathbf{1}\{l_i \leq y_i \leq u_i\}$$

where l_i and u_i are the lower and upper bounds of the prediction interval and y_i is the observed value.

Dictionary

This `mlr3::Measure` can be instantiated via the **dictionary** `mlr3::mlr_measures` or with the associated sugar function `mlr3::msr()`:

```
mlr_measures$get("fcst.coverage")
msr("fcst.coverage")
```

Task type

Forecast measures are registered with `task_type = "regr"` so they compose with the standard regression measures (e.g. `mlr3::mlr_measures_regr.rmse`) on the **PredictionFcst** that forecast learners produce. List them via the key prefix, not the task type, as the latter returns nothing:

```
as.data.table(mlr_measures)[grep1("^fcst", key)]
```

Meta Information

- Task type: “regr”
- Range: [0, 1]
- Minimize: NA
- Average: macro
- Required Prediction: “quantiles”
- Required Packages: **mlr3**, **mlr3forecast**

Parameters

Id	Type	Default	Range
alpha	numeric	-	[0, 1]

Super classes

```
mlr3::Measure -> mlr3::MeasureRegr -> MeasureCoverage
```

Methods**Public methods:**

- `MeasureCoverage$new()`
- `MeasureCoverage$clone()`

`MeasureCoverage$new()`: Creates a new instance of this [R6](#) class.

Usage:

```
MeasureCoverage$new()
```

`MeasureCoverage$clone()`: The objects of this class are cloneable with this method.

Usage:

```
MeasureCoverage$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

- Chapter in the **mlr3book**: https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-eval
- Package **mlr3measures** for the scoring functions.
- Dictionary of **Measures**: `mlr3::mlr_measures`
- `as.data.table(mlr_measures)` for a table of available **Measures** in the running session (depending on the loaded packages).

- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.

Other Measure: [mlr_measures_fcst.acf1](#), [mlr_measures_fcst.mase](#), [mlr_measures_fcst.mda](#), [mlr_measures_fcst.mdpv](#), [mlr_measures_fcst.mdv](#), [mlr_measures_fcst.mpe](#), [mlr_measures_fcst.msis](#), [mlr_measures_fcst.pinball](#), [mlr_measures_fcst.rmsse](#), [mlr_measures_fcst.wape](#), [mlr_measures_fcst.winkler](#)

mlr_measures_fcst.mase

Mean Absolute Scaled Error

Description

Measures the mean absolute error of the forecast scaled by the in-sample mean absolute error of the naive (or seasonal naive) forecast. Values less than one indicate the forecast is better than the naive baseline.

Details

$$\text{MASE} = \frac{1}{n} \sum_{i=1}^n \frac{|y_i - \hat{y}_i|}{\frac{1}{T-m} \sum_{t=m+1}^T |z_t - z_{t-m}|}$$

where z is the training series, m is the seasonal period, and T is the length of the training series.

Dictionary

This [mlr3::Measure](#) can be instantiated via the [dictionary mlr3::mlr_measures](#) or with the associated sugar function [mlr3::msr\(\)](#):

```
mlr_measures$get("fcst.mase")
msr("fcst.mase")
```

Task type

Forecast measures are registered with `task_type = "regr"` so they compose with the standard regression measures (e.g. [mlr3::mlr_measures_regr.rmse](#)) on the [PredictionFcst](#) that forecast learners produce. List them via the key prefix, not the task type, as the latter returns nothing:

```
as.data.table(mlr_measures)[grep1("^fcst", key)]
```

Meta Information

- Task type: "regr"
- Range: $[0, \infty)$
- Minimize: TRUE
- Average: macro
- Required Prediction: "response"
- Required Packages: **mlr3**, **mlr3forecast**

Parameters

Id	Type	Default	Range
period	integer	-	$[1, \infty)$

Super classes

`mlr3::Measure` -> `mlr3::MeasureRegr` -> `MeasureMASE`

Methods

Public methods:

- `MeasureMASE$new()`
- `MeasureMASE$clone()`

`MeasureMASE$new()`: Creates a new instance of this [R6](#) class.

Usage:

```
MeasureMASE$new()
```

`MeasureMASE$clone()`: The objects of this class are cloneable with this method.

Usage:

```
MeasureMASE$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

References

Hyndman RJ, Koehler AB (2006). “Another look at measures of forecast accuracy.” *International Journal of Forecasting*, **22**(4), 679–688.

See Also

- Chapter in the [mlr3book](https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-eval): https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-eval
- Package **mlr3measures** for the scoring functions.
- Dictionary of Measures: [mlr3::mlr_measures](#)
- `as.data.table(mlr_measures)` for a table of available Measures in the running session (depending on the loaded packages).
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.

Other Measure: [mlr_measures_fcst.acf1](#), [mlr_measures_fcst.coverage](#), [mlr_measures_fcst.mda](#), [mlr_measures_fcst.mdvp](#), [mlr_measures_fcst.mdv](#), [mlr_measures_fcst.mpe](#), [mlr_measures_fcst.msis](#), [mlr_measures_fcst.pinball](#), [mlr_measures_fcst.rmsse](#), [mlr_measures_fcst.wape](#), [mlr_measures_fcst.winkler](#)

mlr_measures_fcst.mda *Mean Directional Accuracy*

Description

Measure of the proportion of correctly predicted directions between successive observations in forecast tasks.

Details

$$\text{MDA} = (a - b) \frac{1}{n - 1} \sum_{i=2}^n \mathbf{1}\{\text{sign}(y_i - y_{i-1}) = \text{sign}(\hat{y}_i - y_{i-1})\} + b$$

where a is the reward for a correct direction (default 1), b is the penalty for an incorrect direction (default 0), and n is the number of observations.

Dictionary

This `mlr3::Measure` can be instantiated via the [dictionary `mlr3::mlr\_measures`](#) or with the associated sugar function `mlr3::msr()`:

```
mlr_measures$get("fcst.mda")
msr("fcst.mda")
```

Task type

Forecast measures are registered with `task_type = "regr"` so they compose with the standard regression measures (e.g. [mlr3::mlr_measures_regr.rmse](#)) on the [PredictionFcst](#) that forecast learners produce. List them via the key prefix, not the task type, as the latter returns nothing:

```
as.data.table(mlr_measures)[grep("^fcst", key)]
```

Meta Information

- Task type: "regr"
- Range: $(-\infty, \infty)$
- Minimize: FALSE
- Average: macro
- Required Prediction: "response"
- Required Packages: **mlr3**, **mlr3forecast**

Parameters

Id	Type	Default	Range
reward	numeric	-	$(-\infty, \infty)$
penalty	numeric	-	$(-\infty, \infty)$

Super classes

`mlr3::Measure -> mlr3::MeasureRegr -> MeasureMDA`

Methods

Public methods:

- `MeasureMDA$new()`
- `MeasureMDA$clone()`

`MeasureMDA$new()`: Creates a new instance of this [R6](#) class.

Usage:

```
MeasureMDA$new()
```

`MeasureMDA$clone()`: The objects of this class are cloneable with this method.

Usage:

```
MeasureMDA$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

References

Blaskowitz O, Herwartz H (2011). “On economic evaluation of directional forecasts.” *International Journal of Forecasting*, **27**(4), 1058–1065.

See Also

- Chapter in the [mlr3book](https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-eval): https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-eval
- Package **mlr3measures** for the scoring functions.
- Dictionary of Measures: [mlr3::mlr_measures](#)
- `as.data.table(mlr_measures)` for a table of available Measures in the running session (depending on the loaded packages).
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.

Other Measure: `mlr_measures_fcst.acf1`, `mlr_measures_fcst.coverage`, `mlr_measures_fcst.mase`, `mlr_measures_fcst.mdvp`, `mlr_measures_fcst.mdv`, `mlr_measures_fcst.mpe`, `mlr_measures_fcst.msis`, `mlr_measures_fcst.pinball`, `mlr_measures_fcst.rmsse`, `mlr_measures_fcst.wape`, `mlr_measures_fcst.winkler`

mlr_measures_fcst.mdpv

Mean Directional Percentage Value

Description

Measure of average percentage-weighted directional accuracy in forecast tasks.

Details

$$\text{MDPV} = \frac{1}{n-1} \sum_{i=2}^n \left| \frac{y_i - y_{i-1}}{y_{i-1}} \right| \times \begin{cases} +1, & \text{if } \text{sign}(y_i - y_{i-1}) = \text{sign}(\hat{y}_i - y_{i-1}), \\ -1, & \text{otherwise.} \end{cases}$$

Dictionary

This `mlr3::Measure` can be instantiated via the [dictionary](#) `mlr3::mlr_measures` or with the associated sugar function `mlr3::msr()`:

```
mlr_measures$get("fcst.mdpv")
msr("fcst.mdpv")
```

Task type

Forecast measures are registered with `task_type = "regr"` so they compose with the standard regression measures (e.g. `mlr3::mlr_measures_regr.rmse`) on the [PredictionFcst](#) that forecast learners produce. List them via the key prefix, not the task type, as the latter returns nothing:

```
as.data.table(mlr_measures)[grep1("^fcst", key)]
```

Meta Information

- Task type: "regr"
- Range: $(-\infty, \infty)$
- Minimize: FALSE
- Average: macro
- Required Prediction: "response"
- Required Packages: **mlr3**, **mlr3forecast**

Parameters

Empty ParamSet

Super classes

```
mlr3::Measure -> mlr3::MeasureRegr -> MeasureMDPV
```

Methods

Public methods:

- [MeasureMDPV\\$new\(\)](#)
- [MeasureMDPV\\$clone\(\)](#)

[MeasureMDPV\\$new\(\)](#): Creates a new instance of this [R6](#) class.

Usage:

```
MeasureMDPV$new()
```

[MeasureMDPV\\$clone\(\)](#): The objects of this class are cloneable with this method.

Usage:

```
MeasureMDPV$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

References

Blaskowitz O, Herwartz H (2011). “On economic evaluation of directional forecasts.” *International Journal of Forecasting*, **27**(4), 1058–1065.

See Also

- Chapter in the [mlr3book](#): https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-eval
- Package **mlr3measures** for the scoring functions.
- Dictionary of Measures: [mlr3::mlr_measures](#)
- `as.data.table(mlr_measures)` for a table of available [Measures](#) in the running session (depending on the loaded packages).
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.

Other Measure: [mlr_measures_fcst.acf1](#), [mlr_measures_fcst.coverage](#), [mlr_measures_fcst.mase](#), [mlr_measures_fcst.mda](#), [mlr_measures_fcst.mdv](#), [mlr_measures_fcst.mpe](#), [mlr_measures_fcst.msis](#), [mlr_measures_fcst.pinball](#), [mlr_measures_fcst.rmsse](#), [mlr_measures_fcst.wape](#), [mlr_measures_fcst.winkler](#)

mlr_measures_fcst.mdv *Mean Directional Value*

Description

Measure of average magnitude-weighted directional accuracy in forecast tasks.

Details

$$\text{MDV} = \frac{1}{n-1} \sum_{i=2}^n |y_i - y_{i-1}| \times \begin{cases} +1, & \text{if } \text{sign}(y_i - y_{i-1}) = \text{sign}(\hat{y}_i - y_{i-1}), \\ -1, & \text{otherwise.} \end{cases}$$

where n is the number of observations.

Dictionary

This `mlr3::Measure` can be instantiated via the [dictionary `mlr3::mlr\_measures`](#) or with the associated sugar function `mlr3::msr()`:

```
mlr_measures$get("fcst.mdv")
msr("fcst.mdv")
```

Task type

Forecast measures are registered with `task_type = "regr"` so they compose with the standard regression measures (e.g. [mlr3::mlr_measures_regr.rmse](#)) on the [PredictionFcst](#) that forecast learners produce. List them via the key prefix, not the task type, as the latter returns nothing:

```
as.data.table(mlr_measures)[grepl("^fcst", key)]
```

Meta Information

- Task type: “regr”
- Range: $(-\infty, \infty)$
- Minimize: FALSE
- Average: macro
- Required Prediction: “response”
- Required Packages: **mlr3**, **mlr3forecast**

Parameters

Empty ParamSet

Super classes

```
mlr3::Measure -> mlr3::MeasureRegr -> MeasureMDV
```

Methods

Public methods:

- `MeasureMDV$new()`
- `MeasureMDV$clone()`

`MeasureMDV$new()`: Creates a new instance of this [R6](#) class.

Usage:

```
MeasureMDV$new()
```

`MeasureMDV$clone()`: The objects of this class are cloneable with this method.

Usage:

```
MeasureMDV$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

References

Blaskowitz O, Herwartz H (2011). “On economic evaluation of directional forecasts.” *International Journal of Forecasting*, **27**(4), 1058–1065.

See Also

- Chapter in the [mlr3book](https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-eval): https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-eval
- Package **mlr3measures** for the scoring functions.
- Dictionary of Measures: [mlr3::mlr_measures](#)
- `as.data.table(mlr_measures)` for a table of available [Measures](#) in the running session (depending on the loaded packages).
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.

Other Measure: [mlr_measures_fcst.acf1](#), [mlr_measures_fcst.coverage](#), [mlr_measures_fcst.mase](#), [mlr_measures_fcst.mda](#), [mlr_measures_fcst.mdpv](#), [mlr_measures_fcst.mpe](#), [mlr_measures_fcst.msis](#), [mlr_measures_fcst.pinball](#), [mlr_measures_fcst.rmsse](#), [mlr_measures_fcst.wape](#), [mlr_measures_fcst.winkler](#)

mlr_measures_fcst.mpe *Mean Percentage Error*

Description

Measure of the average signed percentage error of forecasts. Positive values indicate systematic under-forecasting, negative values indicate over-forecasting.

Details

$$\text{MPE} = \frac{100}{n} \sum_{i=1}^n \frac{y_i - \hat{y}_i}{y_i}$$

Dictionary

This `mlr3::Measure` can be instantiated via the [dictionary `mlr3::mlr\_measures`](#) or with the associated sugar function `mlr3::msr()`:

```
mlr_measures$get("fcst.mpe")
msr("fcst.mpe")
```

Task type

Forecast measures are registered with `task_type = "regr"` so they compose with the standard regression measures (e.g. [mlr3::mlr_measures_regr.rmse](#)) on the [PredictionFcst](#) that forecast learners produce. List them via the key prefix, not the task type, as the latter returns nothing:

```
as.data.table(mlr_measures)[grepl("^fcst", key)]
```

Meta Information

- Task type: "regr"
- Range: $(-\infty, \infty)$
- Minimize: NA
- Average: macro
- Required Prediction: "response"
- Required Packages: **mlr3**, **mlr3forecast**

Parameters

Empty ParamSet

Super classes

```
mlr3::Measure -> mlr3::MeasureRegr -> MeasureMPE
```

Methods

Public methods:

- `MeasureMPE$new()`
- `MeasureMPE$clone()`

`MeasureMPE$new()`: Creates a new instance of this [R6](#) class.

Usage:

```
MeasureMPE$new()
```

`MeasureMPE$clone()`: The objects of this class are cloneable with this method.

Usage:

```
MeasureMPE$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

- Chapter in the [mlr3book](https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-eval): https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-eval
- Package **mlr3measures** for the scoring functions.
- Dictionary of Measures: `mlr3::mlr_measures`
- `as.data.table(mlr_measures)` for a table of available Measures in the running session (depending on the loaded packages).
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.

Other Measure: `mlr_measures_fcst.acf1`, `mlr_measures_fcst.coverage`, `mlr_measures_fcst.mase`, `mlr_measures_fcst.mda`, `mlr_measures_fcst.mdpv`, `mlr_measures_fcst.mdv`, `mlr_measures_fcst.msis`, `mlr_measures_fcst.pinball`, `mlr_measures_fcst.rmsse`, `mlr_measures_fcst.wape`, `mlr_measures_fcst.winkler`

`mlr_measures_fcst.msis`

Mean Scaled Interval Score

Description

Measures the quality of central prediction intervals, scaling the interval (Winkler) score by the in-sample mean absolute error of the naive (or seasonal naive) forecast. The interval score rewards narrow intervals and penalizes observations falling outside them, and the scaling makes the measure comparable across series of different magnitudes. This is the prediction-interval metric used in the M4 competition. Smaller scores indicate better calibrated and narrower intervals.

Details

For a central interval at level $1 - \alpha$ with lower and upper bounds l_i and u_i (the $\alpha/2$ and $1 - \alpha/2$ quantiles):

$$\text{MSIS} = \frac{\frac{1}{n} \sum_{i=1}^n (u_i - l_i) + \frac{2}{\alpha} (l_i - y_i) \mathbf{1}\{y_i < l_i\} + \frac{2}{\alpha} (y_i - u_i) \mathbf{1}\{y_i > u_i\}}{\frac{1}{T-m} \sum_{t=m+1}^T |z_t - z_{t-m}|}$$

where z is the training series, m is the seasonal period, and T is the length of the training series. For keyed tasks the score is computed per series and averaged.

Dictionary

This `mlr3::Measure` can be instantiated via the `dictionary mlr3::mlr_measures` or with the associated sugar function `mlr3::msr()`:

```
mlr_measures$get("fcst.ms")
msr("fcst.ms")
```

Task type

Forecast measures are registered with `task_type = "regr"` so they compose with the standard regression measures (e.g. `mlr3::mlr_measures_regr.rmse`) on the `PredictionFcst` that forecast learners produce. List them via the key prefix, not the task type, as the latter returns nothing:

```
as.data.table(mlr_measures)[grepl("^fcst", key)]
```

Meta Information

- Task type: "regr"
- Range: $[0, \infty)$
- Minimize: TRUE
- Average: macro
- Required Prediction: "quantiles"
- Required Packages: **mlr3**, **mlr3forecast**

Parameters

Id	Type	Default	Range
alpha	numeric	-	$[0, 1]$
period	integer	-	$[1, \infty)$

Super classes

```
mlr3::Measure -> mlr3::MeasureRegr -> MeasureMSIS
```

Methods

Public methods:

- `MeasureMSIS$new()`
- `MeasureMSIS$clone()`

`MeasureMSIS$new()`: Creates a new instance of this [R6](#) class.

Usage:

```
MeasureMSIS$new()
```

`MeasureMSIS$clone()`: The objects of this class are cloneable with this method.

Usage:

```
MeasureMSIS$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

References

Gneiting T, Raftery AE (2007). “Strictly Proper Scoring Rules, Prediction, and Estimation.” *Journal of the American Statistical Association*, **102**(477), 359–378.

Makridakis S, Spiliotis E, Assimakopoulos V (2020). “The M4 Competition: 100,000 time series and 61 forecasting methods.” *International Journal of Forecasting*, **36**(1), 54–74.

See Also

- Chapter in the [mlr3book](https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-eval): https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-eval
- Package **mlr3measures** for the scoring functions.
- Dictionary of Measures: [mlr3::mlr_measures](#)
- `as.data.table(mlr_measures)` for a table of available [Measures](#) in the running session (depending on the loaded packages).
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.

Other Measure: [mlr_measures_fcst.acf1](#), [mlr_measures_fcst.coverage](#), [mlr_measures_fcst.mase](#), [mlr_measures_fcst.mda](#), [mlr_measures_fcst.mdpv](#), [mlr_measures_fcst.mdv](#), [mlr_measures_fcst.mpe](#), [mlr_measures_fcst.pinball](#), [mlr_measures_fcst.rmsse](#), [mlr_measures_fcst.wape](#), [mlr_measures_fcst.winkler](#)

```
mlr_measures_fcst.pinball
```

Pinball Loss

Description

Measures the quality of quantile (probabilistic) forecasts using the pinball loss, also known as the quantile loss. The loss is averaged over all observations and all predicted quantile levels. Smaller scores indicate better calibrated quantile forecasts.

Details

For a single quantile level τ with forecast q_i and observation y_i the pinball loss is

$$L_\tau(y_i, q_i) = \begin{cases} \tau (y_i - q_i), & \text{if } y_i \geq q_i \\ (1 - \tau) (q_i - y_i), & \text{if } y_i < q_i \end{cases}$$

The reported score is twice the mean of L_τ over all observations and all quantile levels τ , matching the convention used by **fabletools** so that the median ($\tau = 0.5$) pinball loss equals the mean absolute error.

Dictionary

This `mlr3::Measure` can be instantiated via the [dictionary](#) `mlr3::mlr_measures` or with the associated sugar function `mlr3::msr()`:

```
mlr_measures$get("fcst.pinball")
msr("fcst.pinball")
```

Task type

Forecast measures are registered with `task_type = "regr"` so they compose with the standard regression measures (e.g. `mlr3::mlr_measures_regr.rmse`) on the [PredictionFcst](#) that forecast learners produce. List them via the key prefix, not the task type, as the latter returns nothing:

```
as.data.table(mlr_measures)[grepl("^fcst", key)]
```

Meta Information

- Task type: "regr"
- Range: $[0, \infty)$
- Minimize: TRUE
- Average: macro
- Required Prediction: "quantiles"
- Required Packages: **mlr3**, **mlr3forecast**

Parameters

Empty ParamSet

Super classes

`mlr3::Measure -> mlr3::MeasureRegr -> MeasurePinball`

Methods**Public methods:**

- `MeasurePinball$new()`
- `MeasurePinball$clone()`

`MeasurePinball$new()`: Creates a new instance of this [R6](#) class.

Usage:

`MeasurePinball$new()`

`MeasurePinball$clone()`: The objects of this class are cloneable with this method.

Usage:

`MeasurePinball$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

References

Koenker R, Bassett G (1978). “Regression Quantiles.” *Econometrica*, **46**(1), 33–50.

See Also

- Chapter in the [mlr3book](https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-eval): https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-eval
- Package **mlr3measures** for the scoring functions.
- Dictionary of Measures: [mlr3::mlr_measures](#)
- `as.data.table(mlr_measures)` for a table of available Measures in the running session (depending on the loaded packages).
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.

Other Measure: [mlr_measures_fcst.acf1](#), [mlr_measures_fcst.coverage](#), [mlr_measures_fcst.mase](#), [mlr_measures_fcst.mda](#), [mlr_measures_fcst.mdpv](#), [mlr_measures_fcst.mdv](#), [mlr_measures_fcst.mpe](#), [mlr_measures_fcst.msis](#), [mlr_measures_fcst.rmsse](#), [mlr_measures_fcst.wape](#), [mlr_measures_fcst.winkler](#)

mlr_measures_fcst.rmsse

Root Mean Squared Scaled Error

Description

Measures the root mean squared error of the forecast scaled by the in-sample mean squared error of the naive (or seasonal naive) forecast. Values less than one indicate the forecast is better than the naive baseline.

Details

$$\text{RMSSE} = \sqrt{\frac{1}{n} \sum_{i=1}^n \frac{(y_i - \hat{y}_i)^2}{\frac{1}{T-m} \sum_{t=m+1}^T (z_t - z_{t-m})^2}}$$

where z is the training series, m is the seasonal period, and T is the length of the training series.

Dictionary

This [mlr3::Measure](#) can be instantiated via the [dictionary mlr3::mlr_measures](#) or with the associated sugar function [mlr3::msr\(\)](#):

```
mlr_measures$get("fcst.rmsse")
msr("fcst.rmsse")
```

Task type

Forecast measures are registered with `task_type = "regr"` so they compose with the standard regression measures (e.g. [mlr3::mlr_measures_regr.rmse](#)) on the [PredictionFcst](#) that forecast learners produce. List them via the key prefix, not the task type, as the latter returns nothing:

```
as.data.table(mlr_measures)[grepl("^fcst", key)]
```

Meta Information

- Task type: "regr"
- Range: $[0, \infty)$
- Minimize: TRUE
- Average: macro
- Required Prediction: "response"
- Required Packages: **mlr3**, **mlr3forecast**

Parameters

Id	Type	Default	Range
period	integer	-	$[1, \infty)$

Super classes

`mlr3::Measure` -> `mlr3::MeasureRegr` -> `MeasureRMSSE`

Methods

Public methods:

- `MeasureRMSSE$new()`
- `MeasureRMSSE$clone()`

`MeasureRMSSE$new()`: Creates a new instance of this [R6](#) class.

Usage:

```
MeasureRMSSE$new()
```

`MeasureRMSSE$clone()`: The objects of this class are cloneable with this method.

Usage:

```
MeasureRMSSE$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

References

Hyndman RJ, Koehler AB (2006). “Another look at measures of forecast accuracy.” *International Journal of Forecasting*, **22**(4), 679–688.

See Also

- Chapter in the `mlr3book`: https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-eval
- Package **`mlr3measures`** for the scoring functions.
- Dictionary of Measures: `mlr3::mlr_measures`
- `as.data.table(mlr_measures)` for a table of available Measures in the running session (depending on the loaded packages).
- Extension packages for additional task types:
 - **`mlr3proba`** for probabilistic supervised regression and survival analysis.
 - **`mlr3cluster`** for unsupervised clustering.

Other Measure: `mlr_measures_fcst.acf1`, `mlr_measures_fcst.coverage`, `mlr_measures_fcst.mase`, `mlr_measures_fcst.mda`, `mlr_measures_fcst.mdpv`, `mlr_measures_fcst.mdv`, `mlr_measures_fcst.mpe`, `mlr_measures_fcst.msis`, `mlr_measures_fcst.pinball`, `mlr_measures_fcst.wape`, `mlr_measures_fcst.winkler`

mlr_measures_fcst.wape

Weighted Absolute Percentage Error

Description

Measure of the total absolute error of forecasts as a percentage of the total absolute truth. It weights each error by the magnitude of the series, making it robust to individual observations close to zero where the ordinary percentage error is undefined.

Details

$$\text{WAPE} = 100 \cdot \frac{\sum_{i=1}^n |y_i - \hat{y}_i|}{\sum_{i=1}^n |y_i|}$$

Dictionary

This `mlr3::Measure` can be instantiated via the [dictionary `mlr3::mlr\_measures`](#) or with the associated sugar function `mlr3::msr()`:

```
mlr_measures$get("fcst.wape")
msr("fcst.wape")
```

Task type

Forecast measures are registered with `task_type = "regr"` so they compose with the standard regression measures (e.g. `mlr3::mlr_measures_regr.rmse`) on the [PredictionFcst](#) that forecast learners produce. List them via the key prefix, not the task type, as the latter returns nothing:

```
as.data.table(mlr_measures)[grep1("^fcst", key)]
```

Meta Information

- Task type: “regr”
- Range: $[0, \infty)$
- Minimize: TRUE
- Average: macro
- Required Prediction: “response”
- Required Packages: **mlr3**, **mlr3forecast**

Parameters

Empty ParamSet

Super classes

`mlr3::Measure` -> `mlr3::MeasureRegr` -> `MeasureWAPE`

Methods

Public methods:

- `MeasureWAPE$new()`
- `MeasureWAPE$clone()`

`MeasureWAPE$new()`: Creates a new instance of this [R6](#) class.

Usage:

```
MeasureWAPE$new()
```

`MeasureWAPE$clone()`: The objects of this class are cloneable with this method.

Usage:

```
MeasureWAPE$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

- Chapter in the [mlr3book](https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-eval): https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-eval
- Package **mlr3measures** for the scoring functions.
- Dictionary of Measures: [mlr3::mlr_measures](#)
- `as.data.table(mlr_measures)` for a table of available Measures in the running session (depending on the loaded packages).
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.

Other Measure: `mlr_measures_fcst.acf1`, `mlr_measures_fcst.coverage`, `mlr_measures_fcst.mase`, `mlr_measures_fcst.mda`, `mlr_measures_fcst.mdpv`, `mlr_measures_fcst.mdv`, `mlr_measures_fcst.mpe`, `mlr_measures_fcst.msis`, `mlr_measures_fcst.pinball`, `mlr_measures_fcst.rmsse`, `mlr_measures_fcst.winkler`

```
mlr_measures_fcst.winkler
```

Winkler Score

Description

Measures the quality of prediction intervals by combining their width with a penalty for observations falling outside the interval. Smaller scores indicate better calibrated and narrower intervals.

Details

$$W_i = \begin{cases} (u_i - l_i) + \frac{2}{\alpha}(l_i - y_i), & \text{if } y_i < l_i \\ (u_i - l_i), & \text{if } l_i \leq y_i \leq u_i \\ (u_i - l_i) + \frac{2}{\alpha}(y_i - u_i), & \text{if } y_i > u_i \end{cases}$$

where l_i and u_i are the lower and upper bounds of the prediction interval, y_i is the observed value, and $\alpha = 1 - \text{level}/100$ is the significance level. The Winkler score is then the mean of W_i over all observations.

Dictionary

This `mlr3::Measure` can be instantiated via the [dictionary `mlr3::mlr\_measures`](#) or with the associated sugar function `mlr3::msr()`:

```
mlr_measures$get("fcst.winkler")
msr("fcst.winkler")
```

Task type

Forecast measures are registered with `task_type = "regr"` so they compose with the standard regression measures (e.g. `mlr3::mlr_measures_regr.rmse`) on the [PredictionFcst](#) that forecast learners produce. List them via the key prefix, not the task type, as the latter returns nothing:

```
as.data.table(mlr_measures)[grepl("^fcst", key)]
```

Meta Information

- Task type: “regr”
- Range: $[0, \infty)$
- Minimize: TRUE
- Average: macro
- Required Prediction: “quantiles”
- Required Packages: **mlr3**, **mlr3forecast**

Parameters

Id	Type	Default	Range
alpha	numeric	-	[0, 1]

Super classes

```
mlr3::Measure -> mlr3::MeasureRegr -> MeasureWinkler
```

Methods

Public methods:

- `MeasureWinkler$new()`
- `MeasureWinkler$clone()`

`MeasureWinkler$new()`: Creates a new instance of this [R6](#) class.

Usage:

```
MeasureWinkler$new()
```

`MeasureWinkler$clone()`: The objects of this class are cloneable with this method.

Usage:

```
MeasureWinkler$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

References

Winkler RL (1972). “A Decision-Theoretic Approach to Interval Estimation.” *Journal of the American Statistical Association*, **67**(337), 187–191.

See Also

- Chapter in the [mlr3book](https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-eval): https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html#sec-eval
- Package **mlr3measures** for the scoring functions.
- Dictionary of Measures: [mlr3::mlr_measures](#)
- `as.data.table(mlr_measures)` for a table of available Measures in the running session (depending on the loaded packages).
- Extension packages for additional task types:
 - **mlr3proba** for probabilistic supervised regression and survival analysis.
 - **mlr3cluster** for unsupervised clustering.

Other Measure: [mlr_measures_fcst.acf1](#), [mlr_measures_fcst.coverage](#), [mlr_measures_fcst.mase](#), [mlr_measures_fcst.mda](#), [mlr_measures_fcst.mdpv](#), [mlr_measures_fcst.mdv](#), [mlr_measures_fcst.mpe](#), [mlr_measures_fcst.msis](#), [mlr_measures_fcst.pinball](#), [mlr_measures_fcst.rmsse](#), [mlr_measures_fcst.wape](#)

mlr_pipeops_fcst.catch22

Time Series Feature Extraction (catch22)

Description

This PipeOp extracts the 22 (or 24) canonical time series characteristics (catch22) from the target variable. For more details, see [Rcatch22::catch22_all\(\)](#), which is called internally on the ordered target vector.

For other time series feature extractors, see [PipeOpFcstTsfeats](#) and [PipeOpFcstFeasts](#).

Parameters

The parameters are the parameters inherited from [mlr3pipelines::PipeOpTaskPreproc](#), as well as:

- `catch24 :: logical(1)`
If TRUE, additionally compute the mean and standard deviation (the catch24 set). Default FALSE.

Naming

The new columns are named `{target}_catch22_{feature}`. If the target was called "y" and the feature is "DN_HistogramMode_5", the corresponding new column will be called "y_catch22_DN_HistogramMode_5".

Super classes

[mlr3pipelines::PipeOp](#) -> [mlr3pipelines::PipeOpTaskPreproc](#) -> [PipeOpFcstCatch22](#)

Methods

Public methods:

- [PipeOpFcstCatch22\\$new\(\)](#)
- [PipeOpFcstCatch22\\$clone\(\)](#)

[PipeOpFcstCatch22\\$new\(\)](#): Initializes a new instance of this Class.

Usage:

```
PipeOpFcstCatch22$new(id = "fcst.catch22", param_vals = list())
```

Arguments:

`id` (character(1))

Identifier of resulting object, default "fcst.catch22".

`param_vals` (named list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction. Default list().

[PipeOpFcstCatch22\\$clone\(\)](#): The objects of this class are cloneable with this method.

Usage:

```
PipeOpFcstCatch22$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```
library(mlr3pipelines)
task = tsk("airpassengers")
po = po("fcst.catch22")
out = po$train(list(task))[[1L]]
out$head()
```

```
mlr_pipeops_fcst.feasts
```

Time Series Feature Extraction (feasts)

Description

Computes per-series summary features from the target variable via `fabletools::features()` with feature functions from the **feasts** package, and broadcasts them as constant columns to every row of the corresponding series. For an unkeyed task the features are broadcast to every row. For a keyed task each key contributes one feature vector.

This is the **feasts** (tidyverts) counterpart of `PipeOpFcstTsfeats`. Predicting on a key that was not seen during training is an error.

Parameters

The parameters are the parameters inherited from `mlr3pipelines::PipeOpTaskPreproc`, as well as:

- `features :: list()`
A list of **feasts** feature functions (e.g. `feasts::feat_acf`, `feasts::feat_stl`) or a `fabletools::feature_set()`.
Default `list(feasts::feat_acf, feasts::feat_stl)`.

Super classes

```
mlr3pipelines::PipeOp -> mlr3pipelines::PipeOpTaskPreproc -> PipeOpFcstFeasts
```

Methods

Public methods:

- `PipeOpFcstFeasts$new()`
- `PipeOpFcstFeasts$clone()`

`PipeOpFcstFeasts$new()`: Initializes a new instance of this Class.

Usage:

```
PipeOpFcstFeasts$new(id = "fcst.feasts", param_vals = list())
```

Arguments:

id (character(1))

Identifier of resulting object, default "fcst.feasts".

param_vals (named list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction. Default list().

PipeOpFcstFeasts\$clone(): The objects of this class are cloneable with this method.

Usage:

PipeOpFcstFeasts\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Examples

```
library(mlr3pipelines)
task = tsk("airpassengers")
po = po("fcst.feasts", features = list(feasts::feat_acf))
out = po$train(list(task))[[1L]]
out$head()

# select features by tag via fabletools::feature_set() (requires feasts to be attached so its
# feature registry is populated)
library(feasts)
features = fabletools::feature_set(pkgs = "feasts", tags = "autocorrelation")
po = po("fcst.feasts", features = features)
po$train(list(task))[[1L]]$head()
```

mlr_pipeops_fcst.fourier

*Create Fourier Features for Seasonality***Description**

Creates pairs of Fourier (harmonic) terms $\sin(2 * \pi * k * t / \text{period})$ and $\cos(2 * \pi * k * t / \text{period})$ as new feature columns, for $k = 1, \dots, K$ harmonics per seasonal period, where t is the per-series time position. They encode seasonality as a flexible alternative to seasonal lags, in particular for long or non-integer periods and multiple seasonalities at once.

Parameters

The parameters are the parameters inherited from [mlr3pipelines::PipeOpTaskPreprocSimple](#), as well as the following parameters:

- `period::numeric() | NULL`
Seasonal period(s), in number of observations per cycle. May be non-integer and may contain multiple periods for multiple seasonalities. If NULL (default), the period is derived from the task's frequency (`task$freq`).

- `K :: integer()`
Number of Fourier harmonics per period. Either a single value recycled to all periods, or one value per period. Each K must satisfy $2 * K \leq \text{period}$. Default 1L.

Super classes

```
mlr3pipelines::PipeOp -> mlr3pipelines::PipeOpTaskPreproc -> mlr3pipelines::PipeOpTaskPreprocSimple
-> PipeOpFcstFourier
```

Methods

Public methods:

- `PipeOpFcstFourier$new()`
- `PipeOpFcstFourier$clone()`

`PipeOpFcstFourier$new()`: Initializes a new instance of this Class.

Usage:

```
PipeOpFcstFourier$new(id = "fcst.fourier", param_vals = list())
```

Arguments:

`id` (`character(1)`)

Identifier of resulting object, default "fcst.fourier".

`param_vals` (`named list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction. Default `list()`.

`PipeOpFcstFourier$clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpFcstFourier$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

References

De Livera AM, Hyndman RJ, Snyder RD (2011). "Forecasting time series with complex seasonal patterns using exponential smoothing." *Journal of the American Statistical Association*, **106**(496), 1513–1527.

Hyndman RJ, Khandakar Y (2008). "Automatic Time Series Forecasting: The forecast Package for R." *Journal of Statistical Software*, **27**(3), 1–22. doi:10.18637/jss.v027.i03.

Examples

```
library(mlr3pipelines)
task = tsk("airpassengers")
po = po("fcst.fourier", period = 12, K = 3L)
new_task = po$train(list(task))[[1L]]
new_task$head()
```

mlr_pipeops_fcst.lags *Create Lags of Target Variable*

Description

Creates lagged versions of the target variable as new feature columns.

At train time the first rows of each series have no history for the requested lags. These incomplete rows are dropped (the autoregressive-fit convention), so the base learner never sees NA lags. A keyed series shorter than the largest lag is dropped entirely, with a warning.

At predict time lags are computed from the full series history.

Parameters

The parameters are the parameters inherited from `mlr3pipelines::PipeOpTaskPreproc`, as well as the following parameters:

- `lags :: integer()`
The lags to create.

Super classes

`mlr3pipelines::PipeOp -> mlr3pipelines::PipeOpTaskPreproc -> PipeOpFcstLags`

Methods**Public methods:**

- `PipeOpFcstLags$new()`
- `PipeOpFcstLags$clone()`

`PipeOpFcstLags$new()`: Initializes a new instance of this Class.

Usage:

```
PipeOpFcstLags$new(id = "fcst.lags", param_vals = list())
```

Arguments:

`id` (character(1))

Identifier of resulting object, default "fcst.lags".

`param_vals` (named list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction. Default list().

`PipeOpFcstLags$clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpFcstLags$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
library(mlr3pipelines)
task = tsk("airpassengers")
po = po("fcst.lags", lags = 1:3)
new_task = po$train(list(task))[[1L]]
new_task$head()
```

```
mlr_pipeops_fcst.rolling
```

Create Rolling Window Features of Target Variable

Description

Creates rolling-window summary statistics of the target variable as new feature columns. The window ends at position $t - \text{lag}$ (exclusive of the current and $\text{lag} - 1$ most recent values) and has size `window_size`. Use `window_size = Inf` for an expanding window that grows to include all history up to $t - \text{lag}$.

At train time rows whose window has insufficient history are NA and are dropped, matching [PipeOpFcstLags](#). Predict keeps all rows.

At predict time rolling features are computed from the full series history.

Parameters

The parameters are the parameters inherited from [mlr3pipelines::PipeOpTaskPreproc](#), as well as the following parameters:

- `funs :: character()`
Aggregation functions. Subset of `c("mean", "median", "sd", "min", "max", "sum")`. Default "mean".
- `window_sizes :: numeric()`
Window sizes. Every combination of `funs` and `window_sizes` produces one output column. Finite sizes must be whole numbers. `Inf` requests an expanding window (all history up to $t - \text{lag}$). Default 3L.
- `lag :: integer(1)`
Minimum lag before the window starts. Must be ≥ 1 to avoid leakage. Default 1L.

Super classes

```
mlr3pipelines::PipeOp -> mlr3pipelines::PipeOpTaskPreproc -> PipeOpFcstRolling
```

Methods**Public methods:**

- [PipeOpFcstRolling\\$new\(\)](#)
- [PipeOpFcstRolling\\$clone\(\)](#)

`PipeOpFcstRolling$new()`: Initializes a new instance of this Class.

Usage:

```
PipeOpFcstRolling$new(id = "fcst.rolling", param_vals = list())
```

Arguments:

`id` (character(1))

Identifier of resulting object, default "fcst.rolling".

`param_vals` (named list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction. Default list().

`PipeOpFcstRolling$clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpFcstRolling$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
library(mlr3pipelines)
task = tsk("airpassengers")
po = po("fcst.rolling", funs = c("mean", "sd"), window_sizes = c(3L, 12L))
new_task = po$train(list(task))[[1L]]
new_task$head()
```

mlr_pipeops_fcst.splitkey

Split a Forecast Task into Per-Series Tasks

Description

Splits a keyed (multi-series) [TaskFcst](#) into a [Multiplicity](#) of single-series tasks, one per key combination. Subsequent PipeOps are executed once per series until a [po\("fcst.unitekey"\)](#) is reached, fitting one local model per series instead of one global model pooled across series.

The per-series tasks carry no key columns, so classical univariate learners (e.g. `lrn("fcst.ets")`) compose as well. The key groups observed during training are stored in the `$state` and the task must contain exactly the same key groups at predict time.

Parameters

This PipeOp has no parameters.

Super class

```
mlr3pipelines::PipeOp -> PipeOpFcstSplitKey
```

Methods

Public methods:

- `PipeOpFcstSplitKey$new()`
- `PipeOpFcstSplitKey$clone()`

`PipeOpFcstSplitKey$new()`: Initializes a new instance of this Class.

Usage:

```
PipeOpFcstSplitKey$new(id = "fcst.splitkey", param_vals = list())
```

Arguments:

`id` (character(1))

Identifier of resulting object, default "fcst.splitkey".

`param_vals` (named list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction. Default list().

`PipeOpFcstSplitKey$clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpFcstSplitKey$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
library(mlr3pipelines)
library(data.table)
dt = CJ(
  month = seq(as.Date("2024-01-01"), by = "month", length.out = 36L),
  id = factor(c("a", "b"))
)
dt[, value := rnorm(.N, mean = fifelse(id == "a", 10, 20))]
task = as_task_fcst(dt, target = "value", order = "month", key = "id", freq = "month")
graph = po("fcst.splitkey") %>% lrn("fcst.ets") %>% po("fcst.unitekey")
flrn = as_learner(graph)$train(task)
forecast(flrn, task, 12L)
```

Description

Applies a Box-Cox transformation to the target variable to stabilize the variance, producing the new target `BoxCox(y, lambda)`. The transformation is pointwise and monotonic, so no rows are dropped and predictions are inverted via `forecast::InvBoxCox()`. `lambda = 0` is the log transformation. When `lambda` is `NULL` (default) it is estimated from the training data, per series on keyed tasks. Predicting a series not seen during training is an error.

Box-Cox and log transformations require strictly positive target values. Non-positive values produce `NaN` or an error. A negative estimated `lambda` can make `forecast::InvBoxCox()` return `NA` for upper quantiles. Set `lower = 0` to avoid this.

Parameters

The parameters are the parameters inherited from `mlr3pipelines::PipeOpTargetTrafo`, as well as the following:

- `lambda :: numeric(1) | NULL`
Box-Cox transformation parameter. `NULL` (default) estimates it from the training data, `0` is the log transformation, any other numeric is used as a fixed value.
- `method :: character(1)`
Method used to estimate `lambda` when `lambda = NULL`, one of `"guerrero"` (default) or `"loglik"`. See `forecast::BoxCox.lambda()`.
- `lower :: numeric(1)`
Lower bound for the estimated `lambda`. Default `-1`.
- `upper :: numeric(1)`
Upper bound for the estimated `lambda`. Default `2`.

Limitations

This `PipeOp` must not be placed *inside* a `RecursiveForecaster` or `DirectForecaster` graph and is rejected at construction. Use it inside a plain `mlr3pipelines::GraphLearner` via `ppl("targettrafo", ...)`, or wrap the forecaster itself with `ppl("targettrafo", ...)` so all horizons are inverted together.

Super classes

```
mlr3pipelines::PipeOp -> mlr3pipelines::PipeOpTargetTrafo -> PipeOpTargetTrafoBoxCox
```

Methods

Public methods:

- `PipeOpTargetTrafoBoxCox$new()`
- `PipeOpTargetTrafoBoxCox$clone()`

`PipeOpTargetTrafoBoxCox$new()`: Initializes a new instance of this Class.

Usage:

```
PipeOpTargetTrafoBoxCox$new(id = "fcst.targetboxcox", param_vals = list())
```

Arguments:

`id` (character(1))
 Identifier of resulting object, default "fcst.targetboxcox".

`param_vals` (named list())
 List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction. Default list().

`PipeOpTargetTrafoBoxCox$clone()`: The objects of this class are cloneable with this method.

Usage:

`PipeOpTargetTrafoBoxCox$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

Examples

```
library(mlr3pipelines)
task = tsk("airpassengers")
split = partition(task, ratio = 0.8)
flrn = as_learner(ppl("targettrafo",
  graph = DirectForecaster$new(lrn("regr.rpart"), lags = 1:3, horizons = length(split$test)),
  trafo_pipeop = po("fcst.targetboxcox")
))
flrn$train(task, split$train)
flrn$predict(task, split$test)
```

mlr_pipeops_fcst.targetdiff

Difference the Target Variable

Description

Differences the target variable with lag `lag`, producing the new target $y'_t = y_t - y_{t-lag}$. The first `lag` rows are dropped during training and predictions are inverted back to the original scale. On keyed (multi-series) tasks this happens within each series. Series too short for the requested lag are dropped with a warning, and predicting a series not seen during training is an error.

Use `lag = 1` to remove a trend and `lag = 12` (or the seasonal period) to remove seasonality.

Parameters

The parameters are the parameters inherited from `mlr3pipelines::PipeOpTargetTrafo`, as well as the following:

- `lag` :: integer(1)
 Lag to difference at. Default 1L.

Limitations

This PipeOp must not be placed *inside* a [RecursiveForecaster](#) or [DirectForecaster](#) graph and is rejected at construction. Use it inside a plain [mlr3pipelines::GraphLearner](#) via `ppl("targettrafo", ...)`, or wrap the forecaster itself with `ppl("targettrafo", ...)` so all horizons are inverted together.

Quantile predictions cannot be inverted and are rejected.

Super classes

`mlr3pipelines::PipeOp -> mlr3pipelines::PipeOpTargetTrafo -> PipeOpTargetTrafoDifference`

Methods

Public methods:

- `PipeOpTargetTrafoDifference$new()`
- `PipeOpTargetTrafoDifference$clone()`

`PipeOpTargetTrafoDifference$new()`: Initializes a new instance of this Class.

Usage:

```
PipeOpTargetTrafoDifference$new(id = "fcst.targetdiff", param_vals = list())
```

Arguments:

`id` (character(1))

Identifier of resulting object, default "fcst.targetdiff".

`param_vals` (named list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction. Default list().

`PipeOpTargetTrafoDifference$clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTargetTrafoDifference$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
library(mlr3pipelines)
task = tsk("airpassengers")
split = partition(task, ratio = 0.8)
flrn = as_learner(ppl("targettrafo",
  graph = DirectForecaster$new(lrn("regr.rpart"), lags = 1:3, horizons = length(split$test)),
  trafo_pipeop = po("fcst.targetdiff", lag = 1L)
))
flrn$train(task, split$train)
flrn$predict(task, split$test)
```

mlr_pipeops_fcst.tsfeats

Time Series Feature Extraction

Description

Computes per-series summary features from the target variable via `tsfeatures::tsfeatures()` and broadcasts them as constant columns to every row of the corresponding series. For an unkeyed task the features are broadcast to every row. For a keyed task each key contributes one feature vector.

Predicting on a key that was not seen during training is an error.

Parameters

The parameters are the parameters inherited from `mlr3pipelines::PipeOpTaskPreproc`, as well as:

- `features :: character()`
Function names from the `tsfeatures` namespace that return numeric feature vectors. Default `c("frequency", "stl_features", "entropy", "acf_features")`.
- `scale :: logical(1)`
If TRUE, scale each series to mean 0 and sd 1 before feature extraction. Default TRUE.
- `trim :: logical(1)`
If TRUE, trim values outside $\pm \text{trim_amount}$ before feature extraction. Default FALSE.
- `trim_amount :: numeric(1)`
Trimming threshold. Default 0.1.
- `parallel :: logical(1)`
If TRUE, compute features in parallel via a `future::plan()`. Default FALSE.
- `multiprocess :: function`
Function from the `future` package used when `parallel = TRUE`. Default `future::multisession()`.
- `na.action :: function`
Missing-value handler. Default `stats::na.pass()`.

Super classes

`mlr3pipelines::PipeOp` -> `mlr3pipelines::PipeOpTaskPreproc` -> `PipeOpFcstTsfeats`

Methods

Public methods:

- `PipeOpFcstTsfeats$new()`
- `PipeOpFcstTsfeats$clone()`

`PipeOpFcstTsfeats$new()`: Initializes a new instance of this Class.

Usage:

```
PipeOpFcstTsfeats$new(id = "fcst.tsfeats", param_vals = list())
```

Arguments:`id` (character(1))

Identifier of resulting object, default "fcst.tsfeats".

`param_vals` (named list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction. Default list().

`PipeOpFcstTsfeats$clone()`: The objects of this class are cloneable with this method.*Usage:*`PipeOpFcstTsfeats$clone(deep = FALSE)`*Arguments:*`deep` Whether to make a deep clone.**Examples**

```
library(mlr3pipelines)
task = tsk("airpassengers")
po = po("fcst.tsfeats", features = c("entropy", "acf_features"))
out = po$train(list(task))[[1L]]
out$head()
```

mlr_pipeops_fcst.unitekey

Unite Per-Series Forecasts into One Prediction

Description

Row-binds a [Multiplicity](#) of per-series [PredictionFcsts](#), as created downstream of `po("fcst.splitkey")`, into a single [PredictionFcst](#).

The series identity is rebuilt from the multiplicity names as a factor column in the prediction's extra slot, so `$key`, `as.data.table()`, and `autoplot.PredictionFcst()` keep working. Set `key` to the task's key column name to get predictions column-compatible with global forecasters such as [RecursiveForecaster](#), which attach the original key column.

Parameters

- `key` :: character(1)

Name of the rebuilt series-identity column in the prediction's extra slot. Default "key".

Super class`mlr3pipelines::PipeOp -> PipeOpFcstUniteKey`

Methods

Public methods:

- [PipeOpFcstUniteKey\\$new\(\)](#)
- [PipeOpFcstUniteKey\\$clone\(\)](#)

[PipeOpFcstUniteKey\\$new\(\)](#): Initializes a new instance of this Class.

Usage:

```
PipeOpFcstUniteKey$new(id = "fcst.unitekey", param_vals = list())
```

Arguments:

id (character(1))

Identifier of resulting object, default "fcst.unitekey".

param_vals (named list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction. Default list().

[PipeOpFcstUniteKey\\$clone\(\)](#): The objects of this class are cloneable with this method.

Usage:

```
PipeOpFcstUniteKey$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```
library(mlr3pipelines)
library(data.table)
dt = CJ(
  month = seq(as.Date("2024-01-01"), by = "month", length.out = 36L),
  id = factor(c("a", "b"))
)
dt[, value := rnorm(.N, mean = fifelse(id == "a", 10, 20))]
task = as_task_fcst(dt, target = "value", order = "month", key = "id", freq = "month")
graph = po("fcst.splitkey") %>% lrn("fcst.ets") %>% po("fcst.unitekey")
flrn = as_learner(graph)$train(task)
forecast(flrn, task, 12L)
```

mlr_pipeops_fcstavg *Weighted Prediction Averaging for Forecasts*

Description

Performs (weighted) averaging of forecast [PredictionFcsts](#), mirroring [mlr3pipelines::PipeOpRegrAvg](#) but preserving the forecast prediction type, which plain regravg would drop. The output is a [PredictionFcst](#) that keeps the time index and key columns (carried in the extra slot), so `$order`, `$key`, [autoplot.PredictionFcst\(\)](#), and forecast task_type inference keep working through the ensemble.

Connect it to several [PipeOpLearner](#) outputs (classical forecast learners or [RecursiveForecaster](#) / [DirectForecaster](#)) to average their forecasts.

Parameters

The parameters are the parameters inherited from `mlr3pipelines::PipeOpRegrAvg`.

Super classes

```
mlr3pipelines::PipeOp -> mlr3pipelines::PipeOpEnsemble -> mlr3pipelines::PipeOpRegrAvg
-> PipeOpFcstAvg
```

Methods

Public methods:

- `PipeOpFcstAvg$new()`
- `PipeOpFcstAvg$clone()`

`PipeOpFcstAvg$new()`: Initializes a new instance of this Class.

Usage:

```
PipeOpFcstAvg$new(
  innum = 0L,
  collect_multiplicity = FALSE,
  id = "fcstavg",
  param_vals = list()
)
```

Arguments:

`innum` (numeric(1))

Number of input channels. Default 0 creates a vararg channel taking an arbitrary number of inputs.

`collect_multiplicity` (logical(1))

If TRUE, the single input is a [Multiplicity](#) collecting channel. Requires `innum = 0`. Default FALSE.

`id` (character(1))

Identifier of resulting object, default "fcstavg".

`param_vals` (named list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction. Default `list()`.

`PipeOpFcstAvg$clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpFcstAvg$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
library(mlr3pipelines)
task = tsk("airpassengers")
graph = gunion(list(
```

```

    po("learner", lrn("fcst.auto_arma"), id = "arma"),
    po("learner", lrn("fcst.ets"), id = "ets")
  )) %>>%
  po("fcstavg")
flrn = as_learner(graph)$train(task)
forecast(flrn, task, 12L)

```

mlr_resamplings_fcst.cv

Forecast Cross-Validation Resampling

Description

Splits data using a folds-folds (default: 5 folds) rolling window cross-validation.

Dictionary

This [Resampling](#) can be instantiated via the [dictionary mlr_resamplings](#) or with the associated sugar function [rsmp\(\)](#):

```

mlr_resamplings$get("fcst.cv")
rsmp("fcst.cv")

```

Parameters

- `horizon (integer(1))`
Forecasting horizon in the test sets, i.e. number of test samples for each fold.
- `folds (integer(1))`
Number of folds.
- `step_size (integer(1))`
Step size between windows.
- `window_size (integer(1))`
Size of the rolling window. For `fixed_window = TRUE`, this is the exact training window size. For `fixed_window = FALSE` (expanding window), this is the minimum number of training observations in the first fold.
- `fixed_window (logical(1))`
Should a fixed sized window be used? If `FALSE` an expanding window is used.

Super class

[mlr3::Resampling](#) -> `ResamplingFcstCV`

Active bindings

```

iters (integer(1))
  Returns the number of resampling iterations, depending on the values stored in the param_set.

```

Methods

Public methods:

- [ResamplingFcstCV\\$new\(\)](#)
- [ResamplingFcstCV\\$clone\(\)](#)

[ResamplingFcstCV\\$new\(\)](#): Creates a new instance of this [R6](#) class.

Usage:

```
ResamplingFcstCV$new()
```

[ResamplingFcstCV\\$clone\(\)](#): The objects of this class are cloneable with this method.

Usage:

```
ResamplingFcstCV$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

References

Tashman LJ (2000). “Out-of-sample tests of forecasting accuracy: an analysis and review.” *International Journal of Forecasting*, **16**(4), 437–450.

Bergmeir C, Hyndman RJ, Koo B (2018). “A note on the validity of cross-validation for evaluating autoregressive time series prediction.” *Computational Statistics & Data Analysis*, **120**, 70–83.

See Also

- Chapter in the [mlr3book](#): https://mlr3book.mlr-org.com/chapters/chapter3/evaluation_and_benchmarking.html#sec-resampling
- Package [mlr3spatiotempcv](#) for spatio-temporal resamplings.
- Dictionary of [Resamplings](#): [mlr3::mlr_resamplings](#)
- `as.data.table(mlr_resamplings)` for a table of available [Resamplings](#) in the running session (depending on the loaded packages).
- [mlr3spatiotempcv](#) for additional [mlr3::Resamplings](#) for spatio-temporal tasks.

Other Resampling: [mlr_resamplings_fcst.holdout](#)

Examples

```
# Create a task with 20 observations
task = tsk("airpassengers")
task$filter(1:20)

# Instantiate Resampling
cv = rspm("fcst.cv", folds = 3, fixed_window = FALSE)
cv$instantiate(task)

# Individual sets:
cv$train_set(1)
cv$test_set(1)
```

```
intersect(cv$train_set(1), cv$test_set(1))

# Internal storage:
cv$instance # list
```

```
mlr_resamplings_fcst.holdout
```

Forecast Holdout Resampling

Description

Splits data into a training set and a test set. Parameter `ratio` determines the ratio of observation going into the training set.

Dictionary

This [Resampling](#) can be instantiated via the [dictionary mlr_resamplings](#) or with the associated sugar function `rsmp()`:

```
mlr_resamplings$get("fcst.holdout")
rsmp("fcst.holdout")
```

Parameters

- `ratio` (`numeric(1)`)
Ratio of observations to put into the training set. Mutually exclusive with parameter `n`.
- `n` (`integer(1)`)
Number of observations to put into the training set. If negative, the absolute value determines the number of observations in the test set. Mutually exclusive with parameter `ratio`.

Super class

```
mlr3::Resampling -> ResamplingFcstHoldout
```

Active bindings

```
iters (integer(1))
Returns the number of resampling iterations, depending on the values stored in the param_set.
```

Methods

Public methods:

- [ResamplingFcstHoldout\\$new\(\)](#)
- [ResamplingFcstHoldout\\$clone\(\)](#)

`ResamplingFcstHoldout$new()`: Creates a new instance of this [R6](#) class.

Usage:

```
ResamplingFcstHoldout$new()
```

`ResamplingFcstHoldout$clone()`: The objects of this class are cloneable with this method.

Usage:

```
ResamplingFcstHoldout$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

- Chapter in the [mlr3book](https://mlr3book.mlr-org.com/chapters/chapter3/evaluation_and_benchmarking.html#sec-resampling): https://mlr3book.mlr-org.com/chapters/chapter3/evaluation_and_benchmarking.html#sec-resampling
- Package **mlr3spatiotempcv** for spatio-temporal resamplings.
- Dictionary of Resamplings: [mlr3::mlr_resamplings](#)
- `as.data.table(mlr_resamplings)` for a table of available Resamplings in the running session (depending on the loaded packages).
- **mlr3spatiotempcv** for additional [mlr3::Resamplings](#) for spatio-temporal tasks.

Other Resampling: [mlr_resamplings_fcst.cv](#)

Examples

```
# Create a task with 10 observations
task = tsk("airpassengers")
task$filter(1:10)

# Instantiate Resampling
holdout = rsm("fcst.holdout", ratio = 0.5)
holdout$instantiate(task)

# Individual sets:
holdout$train_set(1)
holdout$test_set(1)

# Disjunct sets:
intersect(holdout$train_set(1), holdout$test_set(1))

# Internal storage:
holdout$instance # simple list
```

mlr_tasks_airpassengers

Air Passengers Forecast Task

Description

A forecast task for the popular [datasets::AirPassengers](#) data set. The task represents the monthly totals of international airline passengers from 1949 to 1960.

Format

`R6::R6Class` inheriting from `TaskFcst`.

Dictionary

This `Task` can be instantiated via the dictionary `mlr_tasks` or with the associated sugar function `tsk()`:

```
mlr_tasks$get("airpassengers")
tsk("airpassengers")
```

Meta Information

- Task type: “fcst”
- Dimensions: 144x1
- Properties: “ordered”
- Has Missings: FALSE
- Target: “passengers”
- Features: -

Source

Box GEP, Jenkins GM (1976). *Time Series Analysis: Forecasting and Control*, Revised edition. Holden-Day, San Francisco.

See Also

- Chapter in the `mlr3book`: https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html
- Package **mlr3data** for more toy tasks.
- Package **mlr3oml** for downloading tasks from <https://www.openml.org>.
- Package **mlr3viz** for some generic visualizations.
- Dictionary of Tasks: `mlr3::mlr_tasks`
- `as.data.table(mlr_tasks)` for a table of available `Tasks` in the running session (depending on the loaded packages).
- **mlr3fselect** and **mlr3filters** for feature selection and feature filtering.
- Extension packages for additional task types:
 - Unsupervised clustering: **mlr3cluster**
 - Probabilistic supervised regression and survival analysis: <https://mlr3proba.mlr-org.com/>.

Other Task: `TaskFcst`, `mlr_tasks_electricity`, `mlr_tasks_livestock`, `mlr_taskslynx`, `mlr_tasks_usaccdeaths`

mlr_tasks_electricity *Daily electricity demand for Victoria, Australia Forecast Task*

Description

A forecast task for the `tsibbledata::vic_elec` data set. The task represents a daily time series and is ordered by date.

Format

`R6::R6Class` inheriting from `TaskFest`.

Dictionary

This `Task` can be instantiated via the dictionary `mlr_tasks` or with the associated sugar function `tsk()`:

```
mlr_tasks$get("electricity")
tsk("electricity")
```

Meta Information

- Task type: “fcst”
- Dimensions: 1096x3
- Properties: “ordered”
- Has Missings: FALSE
- Target: “demand”
- Features: “holiday”, “temperature”

See Also

- Chapter in the `mlr3book`: https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html
- Package `mlr3data` for more toy tasks.
- Package `mlr3oml` for downloading tasks from <https://www.openml.org>.
- Package `mlr3viz` for some generic visualizations.
- Dictionary of Tasks: `mlr3::mlr_tasks`
- `as.data.table(mlr_tasks)` for a table of available `Tasks` in the running session (depending on the loaded packages).
- `mlr3fselect` and `mlr3filters` for feature selection and feature filtering.
- Extension packages for additional task types:
 - Unsupervised clustering: `mlr3cluster`

- Probabilistic supervised regression and survival analysis: <https://mlr3proba.mlr-org.com/>.

Other Task: [TaskFcst](#), [mlr_tasks_airpassengers](#), [mlr_tasks_livestock](#), [mlr_tasks_lynx](#), [mlr_tasks_usaccdeaths](#)

mlr_tasks_livestock	<i>Australian Livestock Slaughter Forecast Task</i>
---------------------	---

Description

A forecast task for the [tsibbledata::aus_livestock](#) data set. The task represents a monthly time series and is ordered by month.

Format

[R6::R6Class](#) inheriting from [TaskFcst](#).

Dictionary

This [Task](#) can be instantiated via the [dictionary mlr_tasks](#) or with the associated sugar function [tsk\(\)](#):

```
mlr_tasks$get("livestock")
tsk("livestock")
```

Meta Information

- Task type: “fcst”
- Dimensions: 29364x3
- Properties: “ordered”, “keys”
- Has Missings: FALSE
- Target: “count”
- Features: “animal”, “state”

See Also

- Chapter in the [mlr3book](#): https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html
- Package [mlr3data](#) for more toy tasks.
- Package [mlr3oml](#) for downloading tasks from <https://www.openml.org>.
- Package [mlr3viz](#) for some generic visualizations.
- [Dictionary of Tasks](#): [mlr3::mlr_tasks](#)
- `as.data.table(mlr_tasks)` for a table of available [Tasks](#) in the running session (depending on the loaded packages).

- **mlr3fselect** and **mlr3filters** for feature selection and feature filtering.
- Extension packages for additional task types:
 - Unsupervised clustering: **mlr3cluster**
 - Probabilistic supervised regression and survival analysis: <https://mlr3proba.mlr-org.com/>.

Other Task: [TaskFcst](#), [mlr_tasks_airpassengers](#), [mlr_tasks_electricity](#), [mlr_tasks_lynx](#), [mlr_tasks_usaccdeaths](#)

mlr_tasks_lynx

Annual Canadian Lynx Trappings Forecast Task

Description

A forecast task for the popular [datasets::lynx](#) data set. The task represents the annual numbers of lynx trappings in Canada from 1821 to 1934.

Format

R6::R6Class inheriting from [TaskFcst](#).

Dictionary

This [Task](#) can be instantiated via the [dictionary mlr_tasks](#) or with the associated sugar function [tsk\(\)](#):

```
mlr_tasks$get("lynx")
tsk("lynx")
```

Meta Information

- Task type: “fcst”
- Dimensions: 114x1
- Properties: “ordered”
- Has Missings: FALSE
- Target: “count”
- Features: -

Source

Brockwell PJ, Davis RA (1991). *Time Series: Theory and Methods*, 2nd edition. Springer, New York.

References

Campbell MJ, Walker AM (1977). “A Survey of Statistical Work on the Mackenzie River Series of Annual Canadian Lynx Trappings for the Years 1821-1934 and a New Analysis.” *Journal of the Royal Statistical Society. Series A (General)*, **140**(4), 411–431. doi:10.2307/2345277.

Becker RA, Chambers JM, Wilks AR (1988). *The New S Language*. Chapman and Hall/CRC, London.

See Also

- Chapter in the **mlr3book**: https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html
- Package **mlr3data** for more toy tasks.
- Package **mlr3oml** for downloading tasks from <https://www.openml.org>.
- Package **mlr3viz** for some generic visualizations.
- **Dictionary of Tasks**: `mlr3::mlr_tasks`
- `as.data.table(mlr_tasks)` for a table of available **Tasks** in the running session (depending on the loaded packages).
- **mlr3fselect** and **mlr3filters** for feature selection and feature filtering.
- Extension packages for additional task types:
 - Unsupervised clustering: **mlr3cluster**
 - Probabilistic supervised regression and survival analysis: <https://mlr3proba.mlr-org.com/>.

Other Task: `TaskFcst`, `mlr_tasks_airpassengers`, `mlr_tasks_electricity`, `mlr_tasks_livestock`, `mlr_tasks_usaccdeaths`

`mlr_tasks_usaccdeaths` *Accidental Deaths in the US Forecast Task*

Description

A forecast task for the popular `datasets::USAccDeaths` data set. The task represents the monthly totals of accidental deaths in the US from 1973 to 1978.

Format

`R6::R6Class` inheriting from `TaskFcst`.

Dictionary

This **Task** can be instantiated via the **dictionary** `mlr_tasks` or with the associated sugar function `tsk()`:

```
mlr_tasks$get("usaccdeaths")
tsk("usaccdeaths")
```

Meta Information

- Task type: “fcst”
- Dimensions: 72x1
- Properties: “ordered”
- Has Missings: FALSE
- Target: “deaths”
- Features: -

Source

Brockwell PJ, Davis RA (1991). *Time Series: Theory and Methods*, 2nd edition. Springer, New York.

See Also

- Chapter in the **mlr3book**: https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html
- Package **mlr3data** for more toy tasks.
- Package **mlr3oml** for downloading tasks from <https://www.openml.org>.
- Package **mlr3viz** for some generic visualizations.
- **Dictionary of Tasks**: `mlr3::mlr_tasks`
- `as.data.table(mlr_tasks)` for a table of available **Tasks** in the running session (depending on the loaded packages).
- **mlr3select** and **mlr3filters** for feature selection and feature filtering.
- Extension packages for additional task types:
 - Unsupervised clustering: **mlr3cluster**
 - Probabilistic supervised regression and survival analysis: <https://mlr3proba.mlr-org.com/>.

Other Task: `TaskFcst`, `mlr_tasks_airpassengers`, `mlr_tasks_electricity`, `mlr_tasks_livestock`, `mlr_tasks_lynx`

partition.TaskFcst	<i>Manually Partition into Training, Test and Validation Set</i>
--------------------	--

Description

Creates a split of the row ids of a **Task** into a training and a test set, and optionally a validation set.

Usage

```
## S3 method for class 'TaskFcst'
partition(task, ratio = 0.67)
```

Arguments

task	(Task) Task to operate on.
ratio	(numeric()) Ratio of observations to put into the training set. If a 2 element vector is provided, the first element is the ratio for the training set, the second element is the ratio for the test set. The validation set will contain the remaining observations.

Examples

```
task = tsk("airpassengers")
split = partition(task, ratio = 0.8)
```

PredictionFcst

Prediction Object for Forecasting

Description

This object wraps the predictions returned by a forecast learner ([LearnerFcst](#), [RecursiveForecaster](#), [DirectForecaster](#)). It subclasses [mlr3::PredictionRegr](#), so forecasting is treated as regression: the response, se, quantiles and distr fields and all regression measures continue to work.

In addition, the prediction carries the time index (and any key columns) of the forecast horizon in its `$data$extra` slot. These are exposed via the `$order` and `$key` fields, lead the `as.data.table()` output, and are used by [autoplot.PredictionFcst\(\)](#) to draw a forecast plot.

The `task_type` is kept as "regr" so that regression measures remain compatible: forecasting is scored as regression.

Super classes

```
mlr3::Prediction -> mlr3::PredictionRegr -> PredictionFcst
```

Active bindings

`order` ([data.table::data.table\(\)](#) | NULL)

The forecast time index, recovered from `$data$extra`. A table with two columns:

- `row_id` ([integer\(\)](#)), and
- `order` ([Date\(\)](#) | [POSIXct\(\)](#) | [integer\(\)](#) | [numeric\(\)](#)).

Returns NULL if no extra data is stored.

`key` ([data.table::data.table\(\)](#) | NULL)

The series identity columns of the forecast horizon, recovered from `$data$extra`. A table with two or more columns:

- `row_id` ([integer\(\)](#)), and
- key variable(s) ([factor\(\)](#) | [ordered\(\)](#)).

If there is only one key column, it is named `key`. Returns NULL if there are no key columns.

Methods

Public methods:

- `PredictionFcst$new()`
- `PredictionFcst$clone()`

`PredictionFcst$new()`: Creates a new instance of this [R6](#) class.

Usage:

```
PredictionFcst$new(
  task = NULL,
  row_ids = task$row_ids,
  truth = task$truth(),
  response = NULL,
  se = NULL,
  quantiles = NULL,
  distr = NULL,
  weights = NULL,
  check = TRUE,
  extra = NULL,
  raw = NULL
)
```

Arguments:

`task` ([TaskFcst](#))

Task, used to extract defaults for `row_ids` and `truth`.

`row_ids` (`integer()`)

Row ids of the predicted observations, i.e. the row ids of the test set.

`truth` (`numeric()`)

True (observed) response.

`response` (`numeric()`)

Vector of numeric response values. One element for each observation in the test set.

`se` (`numeric()`)

Numeric vector of predicted standard errors. One element for each observation in the test set.

`quantiles` (`matrix()`)

Numeric matrix of predicted quantiles. One row per observation, one column per quantile.

`distr` (`VectorDistribution`)

`VectorDistribution` from package `distr6` (in repository <https://raphaels1.r-universe.dev>).

`weights` (`numeric()`)

Vector of measure weights for each observation.

`check` (`logical(1)`)

If TRUE, performs some argument checks and predict type conversions.

`extra` (`list()`)

Named list carrying the order (time) column and any key columns of the forecast horizon. The list names are the original task column names.

`raw` (`any`)

Raw prediction object from the upstream model. Stored as-is without validation.

PredictionFcst\$clone(): The objects of this class are cloneable with this method.

Usage:

```
PredictionFcst$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

Package **mlr3viz** for some generic visualizations.

Examples

```
task = tsk("airpassengers")
learner = lrn("fcst.auto_arma")$train(task)
p = forecast(learner, task, h = 12)
p$predict_types
head(as.data.table(p))
```

read_tsf

Read tsf files

Description

Parses a file located at file and returns a `data.table::data.table()`.

Usage

```
read_tsf(file)
```

Arguments

file (character(1))
The path to the TSF file.

Value

(`data.table::data.table()`) with class "tsf". If the file contains a frequency or horizon, the "frequency" and "horizon" attributes are set, respectively.

References

Godahewa R, Bergmeir C, Webb GI, Hyndman RJ, Montero-Manso P (2021). "Monash time series forecasting archive." *arXiv preprint arXiv:2105.06643*.

Examples

```
file = system.file("extdata", "m3_yearly_dataset.tsf", package = "mlr3forecast")
dt = read_tsf(file)
head(dt)
```

recursive_forecaster *Create a Recursive Forecast Learner*

Description

Function to create a [RecursiveForecaster](#) object. This is the recommended way to construct a recursive forecaster. It is a thin wrapper around `RecursiveForecaster$new()`.

A recursive forecaster trains a single regression model and forecasts iteratively one step ahead, feeding each prediction back as a lag/rolling feature for the next step. For the direct strategy (one model per horizon) see [direct_forecaster\(\)](#).

Usage

```
recursive_forecaster(
  learner,
  lags = NULL,
  id = NULL,
  param_vals = list(),
  predict_type = NULL,
  clone_graph = TRUE
)
```

Arguments

learner	(mlr3::Learner mlr3pipelines::Graph mlr3pipelines::PipeOp) A regression learner (when lags is provided) or a graph/PipeOp.
lags	(<code>integer()</code> <code>NULL</code>) The lag values to use for creating lag features. If provided, learner is wrapped with <code>po("fcst.lags", lags = lags)</code> . If <code>NULL</code> , learner must be a mlr3pipelines::Graph or mlr3pipelines::PipeOp .
id	(<code>character(1)</code> <code>NULL</code>) Identifier, default <code>NULL</code> (auto-generated).
param_vals	(named <code>list()</code>) List of hyperparameter settings.
predict_type	(<code>character(1)</code> <code>NULL</code>) The predict type, default <code>NULL</code> .
clone_graph	(<code>logical(1)</code>) Whether to clone the graph, default <code>TRUE</code> .

Value

[RecursiveForecaster](#).

Examples

```
library(mlr3pipelines)

task = tsk("airpassengers")
split = partition(task, ratio = 0.8)

# simple: wrap a regression learner with lag features
flrn = recursive_forecaster(lrn("regr.rpart"), lags = 1:3)
flrn$train(task, split$train)
flrn$predict(task, split$test)

# graph: custom preprocessing pipeline
graph = po("fcst.lags", lags = 1:3) %>% lrn("regr.rpart")
flrn = recursive_forecaster(graph)
```

RecursiveForecaster *Recursive Forecast Learner*

Description

A [mlr3::Learner](#) for iterative one-step-ahead forecasting: a single model is fit, then applied recursively, feeding each prediction back as a lag/rolling feature for the next step.

Can be constructed in two ways:

- **Simple:** `RecursiveForecaster$new(learner, lags = 1:3)` – internally builds `po("fcst.lags", lags = lags) %>% learner`.
- **Graph:** `RecursiveForecaster$new(graph)` – takes an arbitrary [mlr3pipelines::Graph](#) or [mlr3pipelines::PipeOp](#).

Target transformations

A target transformation (e.g. [mlr_pipeops_fcst.targetdiff](#), [mlr3pipelines::PipeOpTargetMutate](#)) must *wrap* the forecaster, not be placed *inside* its graph. Wrap it with [mlr3pipelines::ppl\("targettrafo"\)](#) so the whole series is transformed once up front, the recursion runs entirely on the transformed scale, and predictions are inverted once at the end:

```
flrn = as_learner(ppl("targettrafo",
  graph = RecursiveForecaster$new(lrn("regr.rpart"), lags = 1:12),
  trafo_pipeop = po("fcst.targetdiff", lag = 1L)
))
flrn$train(task, split$train)
flrn$predict(task, split$test) # predictions are on the original scale
```

Placing a [mlr3pipelines::PipeOpTargetTrafo](#) *inside* the graph is not supported and is rejected at construction.

Prediction uncertainty

Only the point forecast is fed back between steps, so se/distr uncertainty does not accumulate across horizons and intervals are too narrow for $h > 1$. For calibrated multi-step intervals, prefer [DirectForecaster](#).

Super class

`mlr3::Learner` -> RecursiveForecaster

Active bindings

`learner` (`mlr3::Learner`)
The base regression learner.

`native_model` (any)
The fitted model.

`lags` (`integer()` | `NULL`)
The lags used, or `NULL` if no [PipeOpFcstLags](#) is in the graph.

`param_set` (`paradox::ParamSet`)
Set of hyperparameters.

`marshaled` (`logical(1)`)
Whether the learner's model is currently in marshaled form.

`predict_type` (`character(1)`)
Stores the currently active predict type.

Methods**Public methods:**

- [RecursiveForecaster\\$new\(\)](#)
- [RecursiveForecaster\\$print\(\)](#)
- [RecursiveForecaster\\$marshal\(\)](#)
- [RecursiveForecaster\\$unmarshal\(\)](#)
- [RecursiveForecaster\\$clone\(\)](#)

`RecursiveForecaster$new()`: Creates a new instance of this [R6](#) class.

Usage:

```
RecursiveForecaster$new(
  learner,
  lags = NULL,
  id = NULL,
  param_vals = list(),
  predict_type = NULL,
  clone_graph = TRUE
)
```

Arguments:

`learner` (`mlr3::Learner` | `mlr3pipelines::Graph` | `mlr3pipelines::PipeOp`)
A regression learner (when `lags` is provided) or a graph/PipeOp.

lags (integer() | NULL)
 The lag values to use for creating lag features. If provided, learner is wrapped with `po("fcst.lags", lags = lags)`. If NULL, learner must be a [mlr3pipelines::Graph](#) or [mlr3pipelines::PipeOp](#).

id (character(1) | NULL)
 Identifier, default NULL (auto-generated).

param_vals (named list())
 List of hyperparameter settings.

predict_type (character(1) | NULL)
 The predict type, default NULL.

clone_graph (logical(1))
 Whether to clone the graph, default TRUE.

`RecursiveForecaster$print()`: Printer.

Usage:

`RecursiveForecaster$print(...)`

Arguments:

... (ignored).

`RecursiveForecaster$marshal()`: Marshal the learner's model.

Usage:

`RecursiveForecaster$marshal(...)`

Arguments:

... (any)

Additional arguments passed to [mlr3::marshal_model\(\)](#).

`RecursiveForecaster$unmarshal()`: Unmarshal the learner's model.

Usage:

`RecursiveForecaster$unmarshal(...)`

Arguments:

... (any)

Additional arguments passed to [mlr3::unmarshal_model\(\)](#).

`RecursiveForecaster$clone()`: The objects of this class are cloneable with this method.

Usage:

`RecursiveForecaster$clone(deep = FALSE)`

Arguments:

deep Whether to make a deep clone.

Examples

```
library(mlr3pipelines)
```

```
task = tsk("airpassengers")
```

```
flrn = RecursiveForecaster$new(lrn("regr.rpart"), lags = 1:3)
```

```
split = partition(task, ratio = 0.8)
flrn$train(task, split$train)
flrn$predict(task, split$test)

# graph: custom preprocessing pipeline
graph = po("fcst.lags", lags = 1:3) %>% lrn("regr.rpart")
flrn = RecursiveForecaster$new(graph)
flrn$train(task, split$train)
flrn$predict(task, split$test)
```

selector_fcst_lags	Select Forecast Lag Features
--------------------	------------------------------

Description

[mlr3pipelines::Selector](#) that selects lag features created by [PipeOpFcstLags](#). Matches features named `{target}_lag_{i}` where `{target}` is the task's target variable.

Usage

```
selector_fcst_lags()
```

Value

function: A [mlr3pipelines::Selector](#) function.

See Also

Other Selectors: [selector_fcst_rolling\(\)](#)

Examples

```
library(mlr3pipelines)
task = tsk("airpassengers")
pop = po("fcst.lags", lags = 1:3)
new_task = pop$train(list(task))[[1L]]
selector_fcst_lags()(new_task)
```

`selector_fcst_rolling` *Select Forecast Rolling Features*

Description

[mlr3pipelines::Selector](#) that selects rolling-window features created by [PipeOpFcstRolling](#). Matches features named `{target}_roll_{fun}_{size}` where `{target}` is the task's target variable and `{fun}` is one of the aggregation functions supported by [PipeOpFcstRolling](#).

Usage

```
selector_fcst_rolling()
```

Value

function: A [mlr3pipelines::Selector](#) function.

See Also

Other Selectors: [selector_fcst_lags\(\)](#)

Examples

```
library(mlr3pipelines)
task = tsk("airpassengers")
pop = po("fcst.rolling", funs = c("mean", "sd"), window_sizes = c(3L, 12L))
new_task = pop$train(list(task))[[1L]]
selector_fcst_rolling()(new_task)
```

TaskFcst

Forecast Task

Description

This task specializes [mlr3::Task](#), [mlr3::TaskSupervised](#) and [mlr3::TaskRegr](#) for forecasting problems. The target column is assumed to be numeric. The `task_type` is set to "fcst".

It is recommended to use [as_task_fcst\(\)](#) for construction. Predefined tasks are stored in the dictionary [mlr3::mlr_tasks](#).

Series identity and keys

A task may have one or more key columns whose combination identifies each series. The key role drives all per-series operations: target lags and rolling windows ([PipeOpFcstLags](#), [PipeOpFcstRolling](#)) are computed within each series, and the future forecast grid is built per series.

Key columns are **also** features by default, which lets a global model specialize per series. Drop a key's feature role while keeping the grouping when it carries no signal beyond identifying the series:

```
task$set_col_roles("series_id", remove_from = "feature")
```

For a high-cardinality key, encode it inside the learner graph (e.g. `po("encodeimpact")` or `po("encode1mer")`) rather than passing the raw factor to the model.

Super classes

```
mlr3::Task -> mlr3::TaskSupervised -> mlr3::TaskRegr -> TaskFcst
```

Active bindings

`freq` (`character(1) | numeric(1) | NULL`)

The frequency of the time series.

`properties` (`character()`)

Set of task properties. Possible properties are stored in [mlr_reflections\\$task_properties](#). The following properties are currently standardized and understood by tasks in **mlr3**:

- "strata": The task is resampled using one or more stratification variables (role "stratum").
- "groups": The task comes with grouping/blocking information (role "group").
- "weights_learner": The task comes with observation weights for the learner (role "weights_learner").
- "weights_measure": The task comes with observation weights for the measure (role "weights_measure").
- "offset": The task comes with offset information (role "offset").
- "ordered": The task has columns which define the row order (role "order").
- "keys": The task has columns which define the time series "key".

Note that above listed properties are calculated from the `$col_roles` and may not be set explicitly.

`order` ([data.table::data.table\(\)](#))

A table with two columns:

- `row_id` (`integer()`), and
- `order` (`Date() | POSIXct() | integer() | numeric()`).

`key` ([data.table::data.table\(\)](#) | `NULL`)

If the task has a column with designated role "key", a table with two or more columns:

- `row_id` (`integer()`), and
- `key variable(s)` (`factor() | ordered()`).

If there is only one key column, it will be named as `key`. Returns `NULL` if there are no key columns.

Methods

Public methods:

- [TaskFcst\\$new\(\)](#)
- [TaskFcst\\$view\(\)](#)
- [TaskFcst\\$print\(\)](#)
- [TaskFcst\\$clone\(\)](#)

TaskFcst\$new(): Creates a new instance of this [R6](#) class. The function [as_task_fcst\(\)](#) provides an alternative way to construct forecast tasks.

Usage:

```
TaskFcst$new(
  id,
  backend,
  target,
  order,
  key = character(),
  freq = NULL,
  label = NA_character_,
  extra_args = list()
)
```

Arguments:

id ([character\(1\)](#))

Identifier for the new instance.

backend ([mlr3::DataBackend](#))

Either a [mlr3::DataBackend](#), or any object which is convertible to a [mlr3::DataBackend](#) with [as_data_backend\(\)](#). E.g., a `data.frame()` will be converted to a [mlr3::DataBackendDataTable](#).

target ([character\(1\)](#))

Name of the target column.

order ([character\(1\)](#))

Name of the order column.

key ([character\(\)](#))

Name of the key column.

freq ([character\(1\)](#) | [numeric\(1\)](#) | [NULL](#))

Frequency of the time series. Either a positive number or a `seq()`-compatible string, e.g.: "1 month", "day", "3 months", "1 hour", "week".

label ([character\(1\)](#))

Label for the new instance.

extra_args ([named list\(\)](#))

Named list of constructor arguments, required for converting task types via [mlr3::convert_task\(\)](#).

TaskFcst\$view(): Returns a slice of the data from the [mlr3::DataBackend](#) as a [data.table::data.table\(\)](#). Rows default to observations with role "use", and columns default to features with roles "target", "order", "key" or "feature". If rows or cols are specified which do not exist in the [mlr3::DataBackend](#), an exception is raised.

Rows and columns are returned in the order specified via the arguments rows and cols. If rows is NULL, rows are returned in the order of `task$row_ids`. If cols is NULL, the column order defaults

to `c(task$target_names, task$feature_names, task$col_roles$key, task$col_roles$order)`.
 Note that it is recommended to **not** rely on the order of columns, and instead always address columns with their respective column name.

Usage:

```
TaskFcst$view(rows = NULL, cols = NULL, ordered = FALSE)
```

Arguments:

`rows` (positive integer() | NULL)

Vector or row indices.

`cols` (character() | NULL)

Vector of column names.

`ordered` (logical(1))

If TRUE, data is ordered according to the columns with column role "order" and "key".

Returns: A `data.table::data.table()`.

`TaskFcst$print()`: Printer.

Usage:

```
TaskFcst$print(...)
```

Arguments:

... (ignored).

`TaskFcst$clone()`: The objects of this class are cloneable with this method.

Usage:

```
TaskFcst$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

- Chapter in the `mlr3book`: https://mlr3book.mlr-org.com/chapters/chapter2/data_and_basic_modeling.html
- Package **mlr3data** for more toy tasks.
- Package **mlr3oml** for downloading tasks from <https://www.openml.org>.
- Package **mlr3viz** for some generic visualizations.
- Dictionary of Tasks: `mlr3::mlr_tasks`
- `as.data.table(mlr_tasks)` for a table of available Tasks in the running session (depending on the loaded packages).
- **mlr3fselect** and **mlr3filters** for feature selection and feature filtering.
- Extension packages for additional task types:
 - Unsupervised clustering: **mlr3cluster**
 - Probabilistic supervised regression and survival analysis: <https://mlr3proba.mlr-org.com/>.

Other Task: `mlr_tasks_airpassengers`, `mlr_tasks_electricity`, `mlr_tasks_livestock`, `mlr_tasks_lynx`, `mlr_tasks_usaccdeaths`

Examples

```
library(data.table)
airpassengers = tsbox::ts_dt(AirPassengers)
setnames(airpassengers, c("month", "passengers"))
task = as_task_fcst(airpassengers, target = "passengers", order = "month", freq = "month")
task$task_type
task$formula()
task$truth()
```

Index

* Learner

- LearnerFcst, 16
- mlr_learners_fcst.adam, 20
- mlr_learners_fcst.arfima, 23
- mlr_learners_fcst.arima, 26
- mlr_learners_fcst.auto_adam, 29
- mlr_learners_fcst.auto_arima, 32
- mlr_learners_fcst.auto_ces, 35
- mlr_learners_fcst.auto_gum, 38
- mlr_learners_fcst.auto_msarima, 40
- mlr_learners_fcst.auto_ssarima, 43
- mlr_learners_fcst.bagged, 45
- mlr_learners_fcst.bats, 48
- mlr_learners_fcst.ces, 51
- mlr_learners_fcst.croston, 53
- mlr_learners_fcst.elm, 56
- mlr_learners_fcst.es, 59
- mlr_learners_fcst.ets, 61
- mlr_learners_fcst.gum, 64
- mlr_learners_fcst.holt_winters, 67
- mlr_learners_fcst.mean, 70
- mlr_learners_fcst.mlp, 72
- mlr_learners_fcst.msarima, 75
- mlr_learners_fcst.nnetar, 77
- mlr_learners_fcst.prophet, 80
- mlr_learners_fcst.random_walk, 83
- mlr_learners_fcst.rlg, 85
- mlr_learners_fcst.sma, 88
- mlr_learners_fcst.spline, 90
- mlr_learners_fcst.ssarima, 93
- mlr_learners_fcst.stlm, 96
- mlr_learners_fcst.struct_ts, 98
- mlr_learners_fcst.tbats, 101
- mlr_learners_fcst.theta, 104
- mlr_learners_fcst.tscount, 106
- mlr_learners_fcst.tslm, 109

* Measure

- mlr_measures_fcst.acf1, 111
- mlr_measures_fcst.coverage, 113

- mlr_measures_fcst.mase, 115
- mlr_measures_fcst.mda, 117
- mlr_measures_fcst.mdpv, 119
- mlr_measures_fcst.mdv, 121
- mlr_measures_fcst.mpe, 123
- mlr_measures_fcst.msis, 124
- mlr_measures_fcst.pinball, 127
- mlr_measures_fcst.rmsse, 129
- mlr_measures_fcst.wape, 131
- mlr_measures_fcst.winkler, 133

* Resampling

- mlr_resamplings_fcst.cv, 150
- mlr_resamplings_fcst.holdout, 152

* Selectors

- selector_fcst_lags, 167
- selector_fcst_rolling, 168

* Task

- mlr_tasks_airpassengers, 153
- mlr_tasks_electricity, 155
- mlr_tasks_livestock, 156
- mlr_tasks_lynx, 157
- mlr_tasks_usaccdeaths, 158
- TaskFcst, 168

..., 21

- as_task_fcst, 5
- as_task_fcst(), 168, 170
- as_tasks_fcst(as_task_fcst), 5
- autoplot.PredictionFcst, 8
- autoplot.PredictionFcst(), 147, 148, 160
- autoplot.TaskFcst, 9

base::seq(), 16

- data.frame(), 5, 15
- data.table::data.table(), 14, 16, 160, 162, 169–171

datasets::AirPassengers, 153

datasets::lynx, 157

datasets::USAccDeaths, 158

- Dictionary, [18](#), [22](#), [25](#), [28](#), [30](#), [34](#), [36](#), [39](#), [42](#),
[44](#), [47](#), [50](#), [52](#), [55](#), [58](#), [60](#), [63](#), [66](#), [69](#),
[71](#), [74](#), [76](#), [79](#), [82](#), [84](#), [87](#), [89](#), [92](#), [94](#),
[97](#), [100](#), [102](#), [105](#), [107](#), [110](#), [113](#),
[114](#), [116](#), [118](#), [120](#), [122](#), [124](#), [126](#),
[128](#), [130](#), [132](#), [134](#), [151](#), [153–156](#),
[158](#), [159](#), [171](#)
- dictionary, [17](#), [20](#), [23](#), [26](#), [29](#), [32](#), [35](#), [38](#), [40](#),
[43](#), [46](#), [48](#), [51](#), [54](#), [56](#), [59](#), [62](#), [64](#), [67](#),
[70](#), [72](#), [75](#), [78](#), [80](#), [83](#), [85](#), [88](#), [91](#), [93](#),
[96](#), [99](#), [101](#), [104](#), [106](#), [109](#), [111](#), [113](#),
[115](#), [117](#), [119](#), [121](#), [123](#), [125](#), [127](#),
[129](#), [131](#), [133](#), [150](#), [152](#), [154–158](#),
[168](#)
- direct_forecaster, [10](#)
- direct_forecaster(), [163](#)
- DirectForecaster, [10](#), [11](#), [11](#), [15](#), [143](#), [145](#),
[148](#), [160](#), [165](#)
- download_zenodo_record, [14](#)
- fabletools::feature_set(), [136](#)
- fabletools::features(), [136](#)
- feasts::feat_acf, [136](#)
- feasts::feat_stl, [136](#)
- forecast.Learner, [15](#)
- forecast::arfima(), [23](#)
- forecast::Arima(), [26](#), [46](#)
- forecast::auto.arima(), [32](#), [46](#)
- forecast::baggedModel(), [45](#)
- forecast::bats(), [48](#)
- forecast::bld.mbb.bootstrap(), [46](#)
- forecast::BoxCox.lambda(), [143](#)
- forecast::croston_model(), [53](#)
- forecast::ets(), [46](#), [61](#)
- forecast::forecast(), [46](#), [67](#)
- forecast::forecast.baggedModel(), [46](#)
- forecast::forecast.StructTS(), [98](#)
- forecast::InvBoxCox(), [143](#)
- forecast::mean_model(), [70](#)
- forecast::nnetar(), [78](#)
- forecast::rw_model(), [83](#)
- forecast::spline_model(), [90](#)
- forecast::stlm(), [96](#)
- forecast::tbats(), [101](#)
- forecast::theta_model(), [104](#)
- forecast::tslm(), [109](#)
- future::multisession(), [146](#)
- future::plan(), [146](#)
- generate_newdata, [16](#)
- generate_newdata(), [15](#)
- ggplot2::ggplot(), [9](#), [10](#)
- ggplot2::theme(), [9](#)
- ggplot2::theme_minimal(), [9](#)
- Graph, [19](#), [20](#)
- LearnerFcst, [16](#), [21](#), [22](#), [24](#), [25](#), [27](#), [28](#), [30](#),
[31](#), [33](#), [34](#), [36–39](#), [41](#), [42](#), [44–47](#), [49](#),
[50](#), [52–55](#), [57](#), [58](#), [60–63](#), [65](#), [66](#),
[68–71](#), [73](#), [74](#), [76–79](#), [81–84](#), [86](#), [87](#),
[89–92](#), [94–97](#), [99](#), [100](#), [102–105](#),
[107–110](#), [160](#)
- LearnerFcstAdam
(mlr_learners_fcst.adam), [20](#)
- LearnerFcstArfima
(mlr_learners_fcst.arfima), [23](#)
- LearnerFcstArima
(mlr_learners_fcst.arima), [26](#)
- LearnerFcstAutoAdam
(mlr_learners_fcst.auto_adam),
[29](#)
- LearnerFcstAutoArima
(mlr_learners_fcst.auto_arima),
[32](#)
- LearnerFcstAutoCes
(mlr_learners_fcst.auto_ces),
[35](#)
- LearnerFcstAutoGum
(mlr_learners_fcst.auto_gum),
[38](#)
- LearnerFcstAutoMsarima
(mlr_learners_fcst.auto_msarima),
[40](#)
- LearnerFcstAutoSsarima
(mlr_learners_fcst.auto_ssarima),
[43](#)
- LearnerFcstBaggedModel
(mlr_learners_fcst.bagged), [45](#)
- LearnerFcstBats
(mlr_learners_fcst.bats), [48](#)
- LearnerFcstCes (mlr_learners_fcst.ces),
[51](#)
- LearnerFcstCroston
(mlr_learners_fcst.croston), [53](#)
- LearnerFcstElm (mlr_learners_fcst.elm),
[56](#)
- LearnerFcstEs (mlr_learners_fcst.es), [59](#)

- LearnerFcstEts (mlr_learners_fcst.ets),
61
- LearnerFcstForecast, [24](#), [27](#), [33](#), [46](#), [49](#), [54](#),
[57](#), [62](#), [68](#), [70](#), [73](#), [78](#), [83](#), [86](#), [91](#), [96](#),
[99](#), [102](#), [104](#), [109](#)
- LearnerFcstGum (mlr_learners_fcst.gum),
64
- LearnerFcstHoltWinters
(mlr_learners_fcst.holt_winters),
67
- LearnerFcstMean
(mlr_learners_fcst.mean), [70](#)
- LearnerFcstMlp (mlr_learners_fcst.mlp),
72
- LearnerFcstMsarima
(mlr_learners_fcst.msarima), [75](#)
- LearnerFcstNnetar
(mlr_learners_fcst.nnetar), [77](#)
- LearnerFcstProphet
(mlr_learners_fcst.prophet), [80](#)
- LearnerFcstRandomWalk
(mlr_learners_fcst.random_walk),
83
- LearnerFcstRlgt
(mlr_learners_fcst.rlgt), [85](#)
- LearnerFcstSma (mlr_learners_fcst.sma),
88
- LearnerFcstSmooth, [21](#), [30](#), [36](#), [38](#), [41](#), [44](#),
[52](#), [60](#), [65](#), [76](#), [94](#)
- LearnerFcstSpline
(mlr_learners_fcst.spline), [90](#)
- LearnerFcstSsarima
(mlr_learners_fcst.ssarima), [93](#)
- LearnerFcstStlm
(mlr_learners_fcst.stlm), [96](#)
- LearnerFcstStructTS
(mlr_learners_fcst.struct_ts),
98
- LearnerFcstTbats
(mlr_learners_fcst.tbats), [101](#)
- LearnerFcstTheta
(mlr_learners_fcst.theta), [104](#)
- LearnerFcstTscount
(mlr_learners_fcst.tscount),
106
- LearnerFcstTslm
(mlr_learners_fcst.tslm), [109](#)
- Learners, [18](#), [22](#), [25](#), [28](#), [30](#), [34](#), [36](#), [39](#), [42](#),
[44](#), [47](#), [50](#), [52](#), [55](#), [58](#), [60](#), [63](#), [66](#), [69](#),
[71](#), [74](#), [76](#), [79](#), [82](#), [84](#), [87](#), [89](#), [92](#), [94](#),
[97](#), [100](#), [102](#), [103](#), [105](#), [107](#), [108](#), [110](#)
- MeasureACF1 (mlr_measures_fcst.acf1),
111
- MeasureCoverage
(mlr_measures_fcst.coverage),
113
- MeasureMASE (mlr_measures_fcst.mase),
115
- MeasureMDA (mlr_measures_fcst.mda), [117](#)
- MeasureMDPV (mlr_measures_fcst.mdpv),
119
- MeasureMDV (mlr_measures_fcst.mdv), [121](#)
- MeasureMPE (mlr_measures_fcst.mpe), [123](#)
- MeasureMSIS (mlr_measures_fcst.msis),
124
- MeasurePinball
(mlr_measures_fcst.pinball),
127
- MeasureRMSSE (mlr_measures_fcst.rmsse),
129
- Measures, [113](#), [114](#), [116](#), [118](#), [120](#), [122](#), [124](#),
[126](#), [128](#), [130](#), [132](#), [134](#)
- MeasureWAPE (mlr_measures_fcst.wape),
131
- MeasureWinkler
(mlr_measures_fcst.winkler),
133
- mlr3::convert_task(), [170](#)
- mlr3::DataBackend, [5](#), [170](#)
- mlr3::DataBackendDataTable, [170](#)
- mlr3::Learner, [10–12](#), [15](#), [17](#), [18](#), [20](#), [21](#), [23](#),
[24](#), [26](#), [27](#), [29](#), [30](#), [32](#), [33](#), [35](#), [36](#), [38](#),
[40](#), [41](#), [43](#), [44](#), [46](#), [48](#), [49](#), [51](#), [52](#), [54](#),
[56](#), [57](#), [59](#), [60](#), [62](#), [64](#), [65](#), [67](#), [68](#), [70](#),
[72](#), [73](#), [75](#), [76](#), [78](#), [80](#), [81](#), [83](#), [85](#), [86](#),
[88](#), [89](#), [91](#), [93](#), [94](#), [96](#), [99](#), [101](#), [102](#),
[104](#), [106](#), [107](#), [109](#), [163–165](#)
- mlr3::LearnerRegr, [16](#), [17](#), [21](#), [24](#), [27](#), [30](#),
[33](#), [36](#), [38](#), [41](#), [44](#), [46](#), [49](#), [52](#), [54](#), [57](#),
[60](#), [62](#), [65](#), [68](#), [70](#), [73](#), [76](#), [78](#), [81](#), [83](#),
[86](#), [89](#), [91](#), [94](#), [96](#), [99](#), [102](#), [104](#), [107](#),
[109](#)
- mlr3::lrn(), [20](#), [23](#), [26](#), [29](#), [32](#), [35](#), [38](#), [40](#),
[43](#), [46](#), [48](#), [51](#), [54](#), [56](#), [59](#), [62](#), [64](#), [67](#),
[70](#), [72](#), [75](#), [78](#), [80](#), [83](#), [85](#), [88](#), [91](#), [93](#),
[96](#), [99](#), [101](#), [104](#), [106](#), [109](#)

- `mlr3::marshal_model()`, [13](#), [166](#)
- `mlr3::Measure`, [111–119](#), [121](#), [123](#), [125](#), [127–134](#)
- `mlr3::MeasureRegr`, [112](#), [114](#), [116](#), [118](#), [119](#), [121](#), [123](#), [125](#), [128](#), [130](#), [132](#), [134](#)
- `mlr3::mlr_learners`, [17](#), [18](#), [20](#), [22](#), [23](#), [25](#), [26](#), [28–30](#), [32](#), [34–36](#), [38–40](#), [42–44](#), [46–48](#), [50–52](#), [54–56](#), [58–60](#), [62–64](#), [66](#), [67](#), [69–72](#), [74–76](#), [78–80](#), [82–85](#), [87–89](#), [91–94](#), [96](#), [97](#), [99–102](#), [104–107](#), [109](#), [110](#)
- `mlr3::mlr_measures`, [111](#), [113–134](#)
- `mlr3::mlr_measures_regr.rmse`, [112](#), [113](#), [115](#), [117](#), [119](#), [121](#), [123](#), [125](#), [127](#), [129](#), [131](#), [133](#)
- `mlr3::mlr_resamplings`, [151](#), [153](#)
- `mlr3::mlr_tasks`, [154–156](#), [158](#), [159](#), [168](#), [171](#)
- `mlr3::msr()`, [111](#), [113](#), [115](#), [117](#), [119](#), [121](#), [123](#), [125](#), [127](#), [129](#), [131](#), [133](#)
- `mlr3::Prediction`, [15](#), [16](#), [160](#)
- `mlr3::PredictionRegr`, [160](#)
- `mlr3::Resampling`, [150–153](#)
- `mlr3::Task`, [168](#), [169](#)
- `mlr3::TaskRegr`, [168](#), [169](#)
- `mlr3::TaskSupervised`, [168](#), [169](#)
- `mlr3::unmarshal_model()`, [13](#), [166](#)
- `mlr3forecast` (`mlr3forecast`-package), [4](#)
- `mlr3forecast`-package, [4](#)
- `mlr3pipelines::Graph`, [10](#), [12](#), [163–166](#)
- `mlr3pipelines::GraphLearner`, [143](#), [145](#)
- `mlr3pipelines::PipeOp`, [10](#), [12](#), [135](#), [136](#), [138–141](#), [143](#), [145–147](#), [149](#), [163–166](#)
- `mlr3pipelines::PipeOpEnsemble`, [149](#)
- `mlr3pipelines::PipeOpRegrAvg`, [148](#), [149](#)
- `mlr3pipelines::PipeOpTargetMutate`, [164](#)
- `mlr3pipelines::PipeOpTargetTrafo`, [143–145](#), [164](#)
- `mlr3pipelines::PipeOpTaskPreproc`, [135](#), [136](#), [138–140](#), [146](#)
- `mlr3pipelines::PipeOpTaskPreprocSimple`, [137](#), [138](#)
- `mlr3pipelines::ppl`, [164](#)
- `mlr3pipelines::Selector`, [167](#), [168](#)
- `mlr3tuning::AutoTuner`, [10](#), [12](#)
- `mlr_graphs_fcst.local`, [19](#)
- `mlr_learners_fcst.adam`, [19](#), [20](#), [25](#), [28](#), [31](#), [34](#), [37](#), [39](#), [42](#), [45](#), [47](#), [50](#), [53](#), [55](#), [58](#), [61](#), [63](#), [66](#), [69](#), [71](#), [74](#), [77](#), [79](#), [82](#), [84](#), [87](#), [90](#), [92](#), [95](#), [97](#), [100](#), [103](#), [105](#), [108](#), [110](#)
- `mlr_learners_fcst.arfima`, [19](#), [22](#), [23](#), [28](#), [31](#), [34](#), [37](#), [39](#), [42](#), [45](#), [47](#), [50](#), [53](#), [55](#), [58](#), [61](#), [63](#), [66](#), [69](#), [71](#), [74](#), [77](#), [79](#), [82](#), [84](#), [87](#), [90](#), [92](#), [95](#), [97](#), [100](#), [103](#), [105](#), [108](#), [110](#)
- `mlr_learners_fcst.arima`, [19](#), [22](#), [25](#), [26](#), [31](#), [34](#), [37](#), [39](#), [42](#), [45](#), [47](#), [50](#), [53](#), [55](#), [58](#), [61](#), [63](#), [66](#), [69](#), [71](#), [74](#), [77](#), [79](#), [82](#), [84](#), [87](#), [90](#), [92](#), [95](#), [97](#), [100](#), [103](#), [105](#), [108](#), [110](#)
- `mlr_learners_fcst.auto_adam`, [19](#), [22](#), [25](#), [28](#), [29](#), [34](#), [37](#), [39](#), [42](#), [45](#), [47](#), [50](#), [53](#), [55](#), [58](#), [61](#), [63](#), [66](#), [69](#), [71](#), [74](#), [77](#), [79](#), [82](#), [84](#), [87](#), [90](#), [92](#), [95](#), [97](#), [100](#), [103](#), [105](#), [108](#), [110](#)
- `mlr_learners_fcst.auto_arima`, [19](#), [22](#), [25](#), [28](#), [31](#), [32](#), [37](#), [39](#), [42](#), [45](#), [47](#), [50](#), [53](#), [55](#), [58](#), [61](#), [63](#), [66](#), [69](#), [71](#), [74](#), [77](#), [79](#), [82](#), [84](#), [87](#), [90](#), [92](#), [95](#), [97](#), [100](#), [103](#), [105](#), [108](#), [110](#)
- `mlr_learners_fcst.auto_ces`, [19](#), [22](#), [25](#), [28](#), [31](#), [34](#), [35](#), [39](#), [42](#), [45](#), [47](#), [50](#), [53](#), [55](#), [58](#), [61](#), [63](#), [66](#), [69](#), [71](#), [74](#), [77](#), [79](#), [82](#), [84](#), [87](#), [90](#), [92](#), [95](#), [97](#), [100](#), [103](#), [105](#), [108](#), [110](#)
- `mlr_learners_fcst.auto_gum`, [19](#), [22](#), [25](#), [28](#), [31](#), [34](#), [37](#), [38](#), [42](#), [45](#), [47](#), [50](#), [53](#), [55](#), [58](#), [61](#), [64](#), [66](#), [69](#), [71](#), [74](#), [77](#), [79](#), [82](#), [84](#), [87](#), [90](#), [92](#), [95](#), [97](#), [100](#), [103](#), [105](#), [108](#), [110](#)
- `mlr_learners_fcst.auto_msarima`, [19](#), [22](#), [25](#), [28](#), [31](#), [34](#), [37](#), [39](#), [40](#), [45](#), [47](#), [50](#), [53](#), [55](#), [58](#), [61](#), [64](#), [66](#), [69](#), [71](#), [74](#), [77](#), [79](#), [82](#), [84](#), [87](#), [90](#), [92](#), [95](#), [97](#), [100](#), [103](#), [105](#), [108](#), [110](#)
- `mlr_learners_fcst.auto_ssarima`, [19](#), [22](#), [25](#), [28](#), [31](#), [34](#), [37](#), [39](#), [42](#), [43](#), [47](#), [50](#), [53](#), [55](#), [58](#), [61](#), [64](#), [66](#), [69](#), [71](#), [74](#), [77](#), [79](#), [82](#), [84](#), [87](#), [90](#), [92](#), [95](#), [97](#), [100](#), [103](#), [105](#), [108](#), [110](#)
- `mlr_learners_fcst.bagged`, [19](#), [22](#), [25](#), [28](#), [31](#), [34](#), [37](#), [39](#), [42](#), [45](#), [45](#), [50](#), [53](#), [55](#), [58](#), [61](#), [64](#), [66](#), [69](#), [71](#), [74](#), [77](#), [79](#), [82](#), [84](#), [87](#), [90](#), [92](#), [95](#), [97](#), [100](#), [103](#), [105](#), [108](#), [110](#)

- 108, 110
- `mlr_learners_fcst.bats`, 19, 22, 25, 28, 31, 34, 37, 39, 42, 45, 47, 48, 53, 55, 58, 61, 64, 66, 69, 71, 74, 77, 79, 82, 84, 87, 90, 92, 95, 97, 100, 103, 105, 108, 110
- `mlr_learners_fcst.ces`, 19, 22, 25, 28, 31, 34, 37, 39, 42, 45, 47, 50, 51, 55, 58, 61, 64, 66, 69, 71, 74, 77, 79, 82, 84, 87, 90, 92, 95, 97, 100, 103, 105, 108, 110
- `mlr_learners_fcst.croston`, 19, 22, 25, 28, 31, 34, 37, 39, 42, 45, 47, 50, 53, 53, 58, 61, 64, 66, 69, 71, 74, 77, 79, 82, 84, 87, 90, 92, 95, 97, 100, 103, 105, 108, 110
- `mlr_learners_fcst.elm`, 19, 22, 25, 28, 31, 34, 37, 39, 42, 45, 47, 50, 53, 55, 56, 61, 64, 66, 69, 71, 74, 77, 79, 82, 84, 87, 90, 92, 95, 97, 100, 103, 105, 108, 110
- `mlr_learners_fcst.es`, 19, 22, 25, 28, 31, 34, 37, 39, 42, 45, 47, 50, 53, 55, 58, 59, 64, 66, 69, 71, 74, 77, 79, 82, 84, 87, 90, 92, 95, 97, 100, 103, 105, 108, 110
- `mlr_learners_fcst.ets`, 19, 22, 25, 28, 31, 34, 37, 39, 42, 45, 47, 50, 53, 55, 58, 61, 61, 66, 69, 71, 74, 77, 79, 82, 84, 87, 90, 92, 95, 97, 100, 103, 105, 108, 110
- `mlr_learners_fcst.gum`, 19, 22, 25, 28, 31, 34, 37, 39, 42, 45, 47, 50, 53, 55, 58, 61, 64, 64, 69, 71, 74, 77, 79, 82, 84, 87, 90, 92, 95, 97, 100, 103, 105, 108, 110
- `mlr_learners_fcst.holt_winters`, 19, 22, 25, 28, 31, 34, 37, 39, 42, 45, 47, 50, 53, 55, 58, 61, 64, 66, 67, 71, 74, 77, 79, 82, 84, 87, 90, 92, 95, 98, 100, 103, 105, 108, 110
- `mlr_learners_fcst.mean`, 19, 22, 25, 28, 31, 34, 37, 39, 42, 45, 47, 50, 53, 55, 58, 61, 64, 66, 69, 70, 74, 77, 79, 82, 84, 87, 90, 92, 95, 98, 100, 103, 105, 108, 110
- `mlr_learners_fcst.mlp`, 19, 22, 25, 28, 31, 34, 37, 39, 42, 45, 47, 50, 53, 55, 58, 61, 64, 66, 69, 71, 72, 77, 79, 82, 84, 87, 90, 92, 95, 98, 100, 103, 105, 108, 110
- `mlr_learners_fcst.msarima`, 19, 22, 25, 28, 31, 34, 37, 39, 42, 45, 47, 50, 53, 55, 58, 61, 64, 66, 69, 71, 74, 75, 79, 82, 84, 87, 90, 92, 95, 98, 100, 103, 105, 108, 110
- `mlr_learners_fcst.nnetar`, 19, 22, 25, 28, 31, 34, 37, 39, 42, 45, 47, 50, 53, 55, 58, 61, 64, 66, 69, 71, 74, 77, 77, 82, 84, 87, 90, 92, 95, 98, 100, 103, 105, 108, 110
- `mlr_learners_fcst.prophet`, 19, 22, 25, 28, 31, 34, 37, 39, 42, 45, 47, 50, 53, 55, 58, 61, 64, 66, 69, 71, 74, 77, 79, 80, 84, 87, 90, 92, 95, 98, 100, 103, 105, 108, 110
- `mlr_learners_fcst.random_walk`, 19, 22, 25, 28, 31, 34, 37, 39, 42, 45, 47, 50, 53, 55, 58, 61, 64, 66, 69, 71, 74, 77, 79, 82, 83, 87, 90, 92, 95, 98, 100, 103, 105, 108, 110
- `mlr_learners_fcst.rlg`, 19, 22, 25, 28, 31, 34, 37, 39, 42, 45, 47, 50, 53, 55, 58, 61, 64, 66, 69, 71, 74, 77, 79, 82, 84, 85, 90, 92, 95, 98, 100, 103, 105, 108, 110
- `mlr_learners_fcst.sma`, 19, 22, 25, 28, 31, 34, 37, 39, 42, 45, 47, 50, 53, 55, 58, 61, 64, 66, 69, 71, 74, 77, 79, 82, 84, 87, 88, 92, 95, 98, 100, 103, 105, 108, 110
- `mlr_learners_fcst.spline`, 19, 22, 25, 28, 31, 34, 37, 39, 42, 45, 47, 50, 53, 55, 58, 61, 64, 66, 69, 71, 74, 77, 79, 82, 84, 87, 90, 90, 95, 98, 100, 103, 105, 108, 110
- `mlr_learners_fcst.ssarima`, 19, 22, 25, 28, 31, 34, 37, 39, 42, 45, 47, 50, 53, 55, 58, 61, 64, 66, 69, 71, 74, 77, 79, 82, 84, 87, 90, 92, 93, 98, 100, 103, 105, 108, 110
- `mlr_learners_fcst.stlm`, 19, 22, 25, 28, 31, 34, 37, 39, 42, 45, 47, 50, 53, 55, 58, 61, 64, 66, 69, 71, 74, 77, 79, 82, 84, 87, 90, 92, 95, 96, 100, 103, 105, 108, 110

- mlr_learners_fcst.struct_ts, [19](#), [22](#), [25](#),
[28](#), [31](#), [34](#), [37](#), [39](#), [42](#), [45](#), [47](#), [50](#), [53](#),
[55](#), [58](#), [61](#), [64](#), [66](#), [69](#), [71](#), [74](#), [77](#), [79](#),
[82](#), [84](#), [87](#), [90](#), [92](#), [95](#), [98](#), [98](#), [103](#),
[105](#), [108](#), [110](#)
- mlr_learners_fcst.tbats, [19](#), [22](#), [25](#), [28](#),
[31](#), [34](#), [37](#), [39](#), [42](#), [45](#), [47](#), [50](#), [53](#), [55](#),
[58](#), [61](#), [64](#), [66](#), [69](#), [71](#), [74](#), [77](#), [79](#), [82](#),
[84](#), [87](#), [90](#), [92](#), [95](#), [98](#), [100](#), [101](#), [105](#),
[108](#), [110](#)
- mlr_learners_fcst.theta, [19](#), [22](#), [25](#), [28](#),
[31](#), [34](#), [37](#), [39](#), [42](#), [45](#), [47](#), [50](#), [53](#), [55](#),
[58](#), [61](#), [64](#), [66](#), [69](#), [71](#), [74](#), [77](#), [79](#), [82](#),
[84](#), [87](#), [90](#), [92](#), [95](#), [98](#), [100](#), [103](#), [104](#),
[108](#), [110](#)
- mlr_learners_fcst.tscount, [19](#), [22](#), [25](#), [28](#),
[31](#), [34](#), [37](#), [39](#), [42](#), [45](#), [47](#), [50](#), [53](#), [55](#),
[58](#), [61](#), [64](#), [66](#), [69](#), [71](#), [74](#), [77](#), [79](#), [82](#),
[84](#), [87](#), [90](#), [92](#), [95](#), [98](#), [100](#), [103](#), [105](#),
[106](#), [110](#)
- mlr_learners_fcst.tslm, [19](#), [22](#), [25](#), [28](#), [31](#),
[34](#), [37](#), [39](#), [42](#), [45](#), [47](#), [50](#), [53](#), [55](#), [58](#),
[61](#), [64](#), [66](#), [69](#), [71](#), [74](#), [77](#), [79](#), [82](#), [84](#),
[87](#), [90](#), [92](#), [95](#), [98](#), [100](#), [103](#), [105](#),
[108](#), [109](#)
- mlr_measures_fcst.acf1, [111](#), [115](#), [116](#),
[118](#), [120](#), [122](#), [124](#), [126](#), [128](#), [130](#),
[132](#), [134](#)
- mlr_measures_fcst.coverage, [113](#), [113](#),
[116](#), [118](#), [120](#), [122](#), [124](#), [126](#), [128](#),
[130](#), [132](#), [134](#)
- mlr_measures_fcst.mase, [113](#), [115](#), [115](#),
[118](#), [120](#), [122](#), [124](#), [126](#), [128](#), [130](#),
[132](#), [134](#)
- mlr_measures_fcst.mda, [113](#), [115](#), [116](#), [117](#),
[120](#), [122](#), [124](#), [126](#), [128](#), [130](#), [132](#),
[134](#)
- mlr_measures_fcst.mdvpv, [113](#), [115](#), [116](#),
[118](#), [119](#), [122](#), [124](#), [126](#), [128](#), [130](#),
[132](#), [134](#)
- mlr_measures_fcst.mdv, [113](#), [115](#), [116](#), [118](#),
[120](#), [121](#), [124](#), [126](#), [128](#), [130](#), [132](#),
[134](#)
- mlr_measures_fcst.mpe, [113](#), [115](#), [116](#), [118](#),
[120](#), [122](#), [123](#), [126](#), [128](#), [130](#), [132](#),
[134](#)
- mlr_measures_fcst.msis, [113](#), [115](#), [116](#),
[118](#), [120](#), [122](#), [124](#), [124](#), [128](#), [130](#),
[132](#), [134](#)
- mlr_measures_fcst.pinball, [113](#), [115](#), [116](#),
[118](#), [120](#), [122](#), [124](#), [126](#), [127](#), [130](#),
[132](#), [134](#)
- mlr_measures_fcst.rmse, [113](#), [115](#), [116](#),
[118](#), [120](#), [122](#), [124](#), [126](#), [128](#), [129](#),
[132](#), [134](#)
- mlr_measures_fcst.wape, [113](#), [115](#), [116](#),
[118](#), [120](#), [122](#), [124](#), [126](#), [128](#), [130](#),
[131](#), [134](#)
- mlr_measures_fcst.winkler, [113](#), [115](#), [116](#),
[118](#), [120](#), [122](#), [124](#), [126](#), [128](#), [130](#),
[132](#), [133](#)
- mlr_pipeops_fcst.catch22, [135](#)
- mlr_pipeops_fcst.feasts, [136](#)
- mlr_pipeops_fcst.fourier, [137](#)
- mlr_pipeops_fcst.lags, [139](#)
- mlr_pipeops_fcst.rolling, [140](#)
- mlr_pipeops_fcst.splitkey, [141](#)
- mlr_pipeops_fcst.targetboxcox, [142](#)
- mlr_pipeops_fcst.targetdiff, [144](#), [164](#)
- mlr_pipeops_fcst.tsfeats, [146](#)
- mlr_pipeops_fcst.unitekey, [147](#)
- mlr_pipeops_fcstavg, [148](#)
- mlr_reflections\$learner_predict_types,
[17](#)
- mlr_reflections\$learner_properties, [17](#)
- mlr_reflections\$task_feature_types, [17](#)
- mlr_reflections\$task_properties, [169](#)
- mlr_resamplings, [150](#), [152](#)
- mlr_resamplings_fcst.cv, [150](#), [153](#)
- mlr_resamplings_fcst.holdout, [151](#), [152](#)
- mlr_tasks, [154–158](#)
- mlr_tasks_airpassengers, [153](#), [156–159](#),
[171](#)
- mlr_tasks_electricity, [154](#), [155](#), [157–159](#),
[171](#)
- mlr_tasks_livestock, [154](#), [156](#), [156](#), [158](#),
[159](#), [171](#)
- mlr_tasks_lynx, [154](#), [156](#), [157](#), [157](#), [159](#), [171](#)
- mlr_tasks_usaccdeaths, [154](#), [156](#), [157](#), [158](#),
[158](#), [171](#)
- Multiplicity, [141](#), [147](#), [149](#)
- nnfor::elm(), [56](#)
- nnfor::mlp(), [72](#)
- paradox::ParamSet, [11](#), [17](#), [165](#)
- partition.TaskFcst, [159](#)

- pipeline_fcst_local
 - (mlr_graphs_fcst.local), 19
- PipeOpFcstAvg (mlr_pipeops_fcstavg), 148
- PipeOpFcstCatch22
 - (mlr_pipeops_fcst.catch22), 135
- PipeOpFcstFeasts, 135
- PipeOpFcstFeasts
 - (mlr_pipeops_fcst.feasts), 136
- PipeOpFcstFourier
 - (mlr_pipeops_fcst.fourier), 137
- PipeOpFcstLags, 10–12, 140, 165, 167, 169
- PipeOpFcstLags (mlr_pipeops_fcst.lags), 139
- PipeOpFcstRolling, 11, 168, 169
- PipeOpFcstRolling
 - (mlr_pipeops_fcst.rolling), 140
- PipeOpFcstSplitKey
 - (mlr_pipeops_fcst.splitkey), 141
- PipeOpFcstTsfeats, 135, 136
- PipeOpFcstTsfeats
 - (mlr_pipeops_fcst.tsfeats), 146
- PipeOpFcstUniteKey
 - (mlr_pipeops_fcst.unitekey), 147
- PipeOpLearner, 148
- PipeOpTargetTrafoBoxCox
 - (mlr_pipeops_fcst.targetboxcox), 142
- PipeOpTargetTrafoDifference
 - (mlr_pipeops_fcst.targetdiff), 144
- po(fcst.splitkey), 19, 147
- po(fcst.unitekey), 19, 141
- PredictionFcst, 8, 9, 16, 19, 112, 113, 115, 117, 119, 121, 123, 125, 127, 129, 131, 133, 147, 148, 160
- prophet::prophet(), 80
- R6, 12, 17, 21, 24, 27, 30, 33, 36, 39, 41, 44, 46, 49, 52, 54, 57, 60, 63, 65, 68, 70, 73, 76, 78, 81, 84, 86, 89, 91, 94, 97, 99, 102, 104, 107, 110, 112, 114, 116, 118, 120, 122, 124, 126, 128, 130, 132, 134, 151, 152, 161, 165, 170
- R6::R6Class, 154–158
- Rcatch22::catch22_all(), 135
- read_tsf, 162
- recursive_forecaster, 163
- recursive_forecaster(), 10
- RecursiveForecaster, 11, 15, 20, 143, 145, 147, 148, 160, 163, 164
- requireNamespace(), 18
- Resampling, 150, 152
- ResamplingFcstCV
 - (mlr_resamplings_fcst.cv), 150
- ResamplingFcstHoldout
 - (mlr_resamplings_fcst.holdout), 152
- Resamplings, 151, 153
- Rlgt::rlgt(), 85
- rsmp(), 150, 152
- selector_fcst_lags, 167
- selector_fcst_lags(), 168
- selector_fcst_rolling, 168
- selector_fcst_rolling(), 167
- smooth::adam(), 20
- smooth::auto.adam(), 29
- smooth::auto.ces(), 35
- smooth::auto.gum(), 38
- smooth::auto.msarima(), 40
- smooth::auto.ssarima(), 43
- smooth::ces(), 51
- smooth::es(), 59
- smooth::gum(), 64
- smooth::msarima(), 75
- smooth::sma(), 88
- smooth::ssarima(), 93
- stats::acf(), 111
- stats::HoltWinters(), 67
- stats::na.pass(), 146
- stats::StructTS(), 98
- Task, 154–160
- TaskFcst, 5, 8, 9, 15, 16, 19, 141, 154–159, 161, 168
- Tasks, 154–156, 158, 159, 171
- tscount::tsglm(), 106
- tsfeatures::tsfeatures(), 146
- tsibbledata::aus_livestock, 156
- tsibbledata::vic_elec, 155
- tsk(), 154–158