

Package: modesto (via r-universe)

October 13, 2024

Type Package

Title Modeling and Analysis of Stochastic Systems

Version 0.1.4

Author Carlos Alberto Cardozo Delgado

Maintainer Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>

Description Compute important quantities when we consider stochastic systems that are observed continuously. Such as, Cost model, Limiting distribution, Transition matrix, Transition distribution and Occupancy matrix. The methods are described, for example, Ross S. (2014), Introduction to Probability Models. Eleven Edition. Academic Press.

License GPL-3

Encoding UTF-8

NeedsCompilation yes

RoxygenNote 7.1.2

Suggests testthat

Imports methods, markovchain, Rcpp

LinkingTo Rcpp

Repository CRAN

Date/Publication 2022-05-31 22:50:04 UTC

Contents

ETCt	2
LimDist	3
LRC	3
Mt	4
Pt2	5
PXt	6
summary.modesto	7

Index

8

ETCt

Tool to computate the Expected Total Cost vector for a Continuous Time Markov Chain, CTMC.

Description

ETCt is used to obtain the Expected Total Cost vector up to t of a homogeneous continuous time Markov chain.

Usage

```
ETCt(R, c, t, epsilon = 0.001)
```

Arguments

R	numeric, represents the rate matrix of a CTMC.
c	vector, represents the costs of the states of a CTMC.
t	numeric, represents the length of time.
epsilon	numeric, represents the error bound of the approximation of M(t). Default value is 0.001.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Ross, S, Introduction to Probability Models, Eleven Edition. Academic Press, 2014.

Kulkarni V, Introduction to modeling and analysis of stochastic systems. Second Edition. Springer-Verlag, 2011.

Examples

```
library(modesto)
# A four states CTMC example
R <- matrix(c(0,1,0,0,0, 1/72,0,1,0,0, 0,2/72,0,1,0, 0,0,3/72,0,1/2, 0,0,0,4/72,0),5,5,byrow=TRUE)
ETCt(R,c(-80,-15,50,125,200),t=24,epsilon=0.001)
```

LimDist

Tool to computate the limiting distribution for a Continuous Time Markov Chain, CTMC.

Description

LimDist is used to obtain the limiting distribution of a homogeneous continuous time Markov chain.

Usage

```
LimDist(X, rate, epsilon = 0.01, iter)
```

Arguments

X	matrix, represents a rate matrix of a CTMC or the transition probability matrix of the DTMC associated to the CTMC.
rate	boolean, if rate is equal to TRUE then the argument X represents the rate matrix of the CTMC. If rate is equal to FALSE then the argument X represents the probability transition matrix of the CTMC.
epsilon	numeric, represents the error of approximation.
iter	integer, represents the maximum of iterations.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

Ross, S, Introduction to Probability Models, Eleven Edition. Academic Press, 2014.

Kulkarni V, Introduction to modeling and analysis of stochastic systems. Second Edition. Springer-Verlag, 2011.

LRC

Tool to computate the Long-Run Cost Rate for a Continuous Time Markov Chain, CTMC.

Description

LRC is used to obtain the Long-Run Cost Rate of a homogeneous continuous time Markov chain.

Usage

```
LRC(X, costs)
```

Arguments

- X matrix, represents the rate matrix of a CTMC.
 costs vector, represents the costs of the states of a CTMC.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

- Ross, S, Introduction to Probability Models, Eleven Edition. Academic Press, 2014.
 Kulkarni V, Introduction to modeling and analysis of stochastic systems. Second Edition. Springer-Verlag, 2011.

Examples

```
## Not run: library(modesto)
# A five states CTMC example
R <- matrix(c(0,1,0,0,0, 1/72,0,1,0,0, 0,2/72,0,1,0, 0,0,3/72,0,1/2, 0,0,0,4/72,0),5,5,byrow=TRUE)
LRC(X=R,costs=c(-80,-15,50,125,200))

## End(Not run)
```

Mt

Tool to computate the Occupancy Matrix for a Continuous Time Markov Chain, CTMC.

Description

Mt is used to obtain the Occupancy matrix of a homogeneous continuous time Markov chain for a period of time [0,t].

Usage

```
Mt(R, t, epsilon = 0.001)
```

Arguments

- R numeric, represents the rate matrix of a CTMC.
 t numeric, represents the length of time.
 epsilon numeric, represents the error bound of the approximation of M(t). Default value is 0.001.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

- Ross, S, Introduction to Probability Models, Eleven Edition. Academic Press, 2014.
 Kulkarni V, Introduction to modeling and analysis of stochastic systems. Second Edition. Springer-Verlag, 2011.

Examples

```
library(modesto)
# A five states CTMC example
R <- matrix(c(0,1,0,0,0, 1/72,0,1,0,0, 0,2/72,0,1,0, 0,0,3/72,0,1/2, 0,0,0,4/72,0),5,5,byrow=TRUE)
Mt(R,t=24,epsilon=0.005)
```

Pt2

Tool to compute the transition matrix for a Continuous Time Markov Chain, CTMC.

Description

Pt2 is used to obtain the transition matrix of a homogeneous continuous time Markov chain for a period of time of t.

Usage

```
Pt2(R, t, epsilon = 0.001)
```

Arguments

- | | |
|---------|--|
| R | numeric, represents the rate matrix of a CTMC. |
| t | numeric, represents the length of time. |
| epsilon | numeric, represents the error bound of the approximation of P(t). Default values is 0.001. |

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

- Ross, S, Introduction to Probability Models, Eleven Edition. Academic Press, 2014.
 Kulkarni V, Introduction to modeling and analysis of stochastic systems. Second Edition. Springer-Verlag, 2011.

Examples

```
library(modesto)
# A two states CTMC example
Pt2(matrix(c(0,2,3,0),2,2,byrow=TRUE),t=0.7,epsilon=0.005)
# A four states CTMC example
R <- matrix(c(0,2,3,0,4,0,2,0,0,2,0,2,1,0,3,0),4,4,byrow=TRUE)
Pt2(R,t=0.7,epsilon=0.005)
# require(microbenchmark)
# microbenchmark(Pt(R,t=0.7,epsilon=0.005),Pt2(R,t=0.7,epsilon=0.005),times=1000L)
```

P Xt

Tool to compute the transient probability distribution for a Continuous Time Markov Chain, CTMC.

Description

Pt is used to obtain the transient probability distribution of a homogeneous continuous time Markov chain at a point of time t.

Usage

```
P Xt(X0, R, t, epsilon = 0.001)
```

Arguments

X0	numeric vector, represents the probability distribution of the initial state.
R	numeric, represents the rate matrix of a CTMC.
t	numeric, represents the length of time.
epsilon	numeric, represents the error bound of the approximation of P(t). Default values is 0.001.

Author(s)

Carlos Alberto Cardozo Delgado <cardozorpackages@gmail.com>.

References

- Ross, S, Introduction to Probability Models, Eleven Edition. Academic Press, 2014.
- Kulkarni V, Introduction to modeling and analysis of stochastic systems. Second Edition. Springer-Verlag, 2011.

Examples

```
library(modesto)
# A three states CTMC example
R <- matrix(c(0,2,0,3,0,1,0,6,0),3,3,byrow=TRUE)
X0 <- c(1,0,0)
P Xt(X0,R,t=0.5,epsilon=0.005)
X0 <- c(0,0,1)
P Xt(X0,R,t=0.5,epsilon=0.005)
```

summary.modesto

summary.modesto

Description

summary.modesto displays the summary of calculated quantities from an object of class 'modesto'.

Usage

```
## S3 method for class 'modesto'
summary(object, ...)
```

Arguments

- | | |
|--------|--|
| object | an object of the class 'modesto'. This object is returned from the call to LimDist() function. |
| ... | other arguments. |

Examples

```
# A two states CTMC example
model <- LimDist(matrix(c(0,2,3,0),2,2,byrow=TRUE),rate=TRUE,epsilon=0.005)
summary(model)
```

Index

ETCt, 2

LimDist, 3

LRC, 3

Mt, 4

Pt2, 5

PXt, 6

summary.modesto, 7