

Package: msce (via r-universe)

May 16, 2026

Type Package

Title Hazard of Multi-Stage Clonal Expansion Models

Version 1.0.2

Date 2025-12-05

Author Cristoforo Simonetto [aut, cre] (ORCID:
<<https://orcid.org/0000-0003-4816-3514>>), Jan Christian Kaiser
[ctb]

Maintainer Cristoforo Simonetto <cristoforo.simonetto@ph.tum.de>

Description Functions to calculate hazard and survival function of
Multi-Stage Clonal Expansion Models used in cancer
epidemiology. For the Two-Stage Clonal Expansion Model an exact
solution is implemented assuming piecewise constant parameters,
see Heidenreich, Luebeck, Moolgavkar (1997)
<[doi:10.1111/j.1539-6924.1997.tb00878.x](https://doi.org/10.1111/j.1539-6924.1997.tb00878.x)>. Numerical solutions
are provided for its extensions, see also Little, Vineis, Li
(2008) <[doi:10.1016/j.jtbi.2008.05.027](https://doi.org/10.1016/j.jtbi.2008.05.027)>.

License GPL (>= 2)

Imports Rcpp (>= 1.0.3), RcppParallel (>= 5.0.0)

LinkingTo Rcpp, RcppParallel

Encoding UTF-8

RoxygenNote 7.3.3

Suggests knitr, rmarkdown, testthat

VignetteBuilder knitr

NeedsCompilation yes

Repository <https://cran.r-universe.dev>

Date/Publication 2025-12-17 02:21:06 UTC

RemoteUrl <https://github.com/cran/msce>

RemoteRef HEAD

RemoteSha 826601c801598234a155928326e8c47bc28badf1

Contents

lungCancerRadon	2
lungCancerSmoking	2
msce_numerical	3
tsce	5

Index	7
--------------	----------

lungCancerRadon	<i>Exemplary person year table</i>
-----------------	------------------------------------

Description

Data set of fatal lung cancer in rats exposed to Radon at Pacific Northwest National Laboratory. For each rat, the age at start of Radon exposure, the age at end of exposure and the age at end of follow-up/death is provided in weeks. The Radon dose rate is given in WL (working level).

Usage

```
data(lungCancerRadon)
```

Format

Data frame with 5 variables.

Source

Pacific Northwest National Laboratory, see Heidenreich, W, Jacob P, Paretzke H., et al. (1999). Radiation research, 151 2, 209-17 DOI:10.2307/3579772.

Examples

```
data(lungCancerRadon)
lungCancerRadon[1000,]
```

lungCancerSmoking	<i>Exemplary person year table</i>
-------------------	------------------------------------

Description

Fictitious data set providing the number of lung cancer cases and person years in some population stratified according to age, age of smoking start, age of smoking cessation, and average number of cigarettes per day during the active smoking period.

Usage

```
data(lungCancerSmoking)
```

Format

Data frame with 6 variables.

Source

Fictitious data set, only for illustration and test.

Examples

```
data(lungCancerSmoking)
lungCancerSmoking[1000,]
```

msce_numerical

Numerical solution of the Multi-Stage Clonal Expansion Model

Description

This function aims to solve the general multi-stage model with piecewise constant parameters approximately by integrating the characteristic equations with Euler's method. For sufficiently small time intervals, this approximation often yields reasonable results. Small time intervals can either be provided explicitly with many columns in argument `t`. An alternative is the optional parameter `innerSteps`.

Usage

```
msce_numerical(t, parameterList, innerSteps = 1000L)
```


Arguments

- | | |
|----------------------------|--|
| <code>t</code> | Each element in a row of <code>t</code> defines the endpoint of a time interval. The first time interval starts at time 0. The last element is the time point for which hazard and survival function are evaluated. Elements in a row have to be in monotonously increasing order. In order to achieve a different number of time intervals for different rows, rows may start with an arbitrary number of zeros (i.e. time intervals of length zero). |
| <code>parameterList</code> | List of Matrices. Each list member has to be named. Allowed names are <code>Nnu0</code> , <code>alphaX</code> , <code>gammaX</code> , and <code>nuX</code> where <code>X</code> can be any positive integer value. The number of stages is deduced from <code>nuX</code> with the highest <code>X</code> . Matrices <code>Nnu0</code> and successive <code>nuX</code> must be provided. Missing other matrices are assumed to be zero. For each matrix it has to hold that the number of columns must be equal to the ones in <code>t</code> . The number of rows can either equal to the number of rows in <code>t</code> , or only one row is provided, which then is applied to all rows of <code>t</code> .

Values in matrices <code>Nnu0</code> , <code>alphaX</code> , <code>gammaX</code> , <code>nuX</code> correspond to parameters for each time interval, see the figure and explanations in the package vignette. Here, <code>Nnu0</code> is the product of N and ν_0 and γ_X is defined by $\alpha_X - \beta_X$. |

innerSteps Positive integer. To improve accuracy, each time interval is internally divided into `innerSteps` time intervals of equal length. Defaults to 1000. Note, however, that even in the limit of infinite `innerSteps`, there will always be a finite discrepancy to the exact result.

Details



Value

The output list contains all used arguments of the `parameterList` and vectors of the model results for hazard and logarithm of the survival function for each row of the input.

See Also

[tsce](#)

Examples

```
t <- matrix(data=c(10,20,65,10,20,70),nrow=2,byrow=TRUE)
Nnu0 <- matrix(c(0.3,0.7,1),nrow = 1)
nu1 <- matrix(1e-6,nrow=1,ncol=3)
alpha1<- matrix(1,nrow=1,ncol=3)
gamma1<- matrix(c(0.13,0.13,0.13, 0.15,0.15,0.15),nrow=2,byrow=TRUE)
pars = list(Nnu0=Nnu0, nu1=nu1,alpha1=alpha1,gamma1=gamma1)

msce_numerical(t,pars)
```

 tsce

Exact solution of the Two-Stage Clonal Expansion Model

Description

For piecewise constant parameters `tsce(t, parameterList)` returns the exact hazard and logarithm of the survival function of the Two-Stage Clonal Expansion Model. All arguments are matrices. Evaluation is performed separately for each row.

Usage


```
tsce(t, parameterList)
```

Arguments

`t` Each element in a row of `t` defines the endpoint of a time interval. The first time interval starts at time 0 . The last element is the time point for which hazard and survival function are evaluated. Elements in a row have to be in monotonously increasing order. In order to achieve a different number of time intervals for different rows, rows may start with an arbitrary number of zeros (i.e. time intervals of length zero).

`parameterList` List of Matrices. Each list member has to be named. Allowed names are `Nnu0`, `alpha`, `gamma`, and `nu1`. Matrices `Nnu0` and `nu1` must be provided. If `alpha` or `gamma` are missing, they are assumed to be zero. For each matrix it has to hold that the number of columns must be equal to the ones in `t`. The number of rows can either equal to the number of rows in `t`, or only one row is provided, which then is applied to all rows of `t`.

Values in matrices `Nnu0`, `alpha`, `gamma`, `nu1` correspond to parameters for each time interval, see the figure and explanations in the package vignette. Here, `Nnu0` is the product of N and ν_0 and γ is defined by $\alpha - \beta$.

Details**Value**

Returns a list. Besides the parameters of the parameterList, it contains two named components: hazard the exact hazard and lnSurvival the logarithm of the survival function of the Two-Stage Clonal Expansion Model.

See Also

[msce_numerical](#)

Examples

```
t <- matrix(data=c(10,20,65,10,20,70),nrow=2,byrow=TRUE)
Nnu0 <- matrix(c(0.3,0.7,1),nrow = 1)
alpha<- matrix(1,nrow=1,ncol=3)
gamma<- matrix(c(0.13,0.13,0.13, 0.15,0.15,0.15),nrow=2,byrow=TRUE)
nu1 <- matrix(1e-6,nrow=1,ncol=3)
pars = list(Nnu0=Nnu0, alpha=alpha,gamma=gamma,nu1=nu1)

tsce(t,pars)
```

Index

* datasets

lungCancerRadon, [2](#)

lungCancerSmoking, [2](#)

lungCancerRadon, [2](#)

lungCancerSmoking, [2](#)

msce_numerical, [3](#), [6](#)

tsce, [4](#), [5](#)