Package: multbxxc (via r-universe)

October 6, 2026

Type Package

Title Auxiliary Routines for Influx Software

Version 1.0.3

Date 2024-06-26

Author Serguei Sokol

Maintainer Serguei Sokol <sokol@insa-toulouse.fr>

Description Contains auxiliary routines for influx software. This packages is not intended to be used directly. Influx was published here: Sokol et al. (2012) <doi:10.1093/bioinformatics/btr716>.

License GPL (>= 2)

Imports Rcpp (>= 1.0.0)

LinkingTo Rcpp, RcppArmadillo, rmumps

Depends R (>= 3.4), rmumps (>= 5.2.1-6)

URL https://github.com/sgsokol/influx/

RoxygenNote 7.3.1

Encoding UTF-8

Suggests slam, testthat

NeedsCompilation yes

Repository https://cran.r-universe.dev

Date/Publication 2024-06-27 02:43:06 UTC

RemoteUrl https://github.com/cran/multbxxc

RemoteRef HEAD

RemoteSha a929150c98f8dc4c75316cb81109685441b6f819

Contents

bop . . . 2
ij2ijv_i . . . 3
iv2v . . . 3
jrhs_ff . . . 4
match_ij . . . 4
mm_xpf . . . 5
mult_bxxc . . . 5
multbxxc . . . 6
redim . . . 6
solve_ieu . . . 7

Index **8**

---

bop *Bloc Operation in Place*

Description

src array is added (if sop=="+=") to dst[...] or any other manipulation is made according to sop parameter Both arrays are supposed to be of type 'double' The operation is done 'in place' without new memory allocation for dst src is reshaped and possibly replicated to fit the designated block of dst. mv can be:

- a 1 or 3 component vector describing the block: 1-margin number of dst, 2-offset, 3-length if only the margin is present than offest is 0 and length is the total length of this margin
- a matrix of indexes. Its column number must be equal to the length(dim(dst))) each row of this matrix is a multidimensional index in dst array.

sop is one off: "=" (copy src to dst[]), "+=", "-=", "*=", "/="

Usage

```
bop(dst, mv, sop, src)
```

Arguments

`dst`	A numeric array, destination
`mv`	An integer vector or matrix, describe margins to operate on
`sop`	A string, describes an operator to apply
`src`	A numeric array, source (may be replicated to fit the size of dst)

Value

None

Examples

```
a=matrix(1, 3, 3) # 3x3 matrix of 1's
b=1:3
bop(a, 2, "+=", b) # a += b, here b will be repeated
a
#      [,1] [,2] [,3]
# [1,]    2    2    2
# [2,]    3    3    3
# [3,]    4    4    4
```

---

ij2ijv_i *Transform Repeated Matrix Indexes*

Description

Transforms a couple of index vectors ir and jc (ij of a sparse matrix) with possibly repeated values into sparse indexes i,j and a vector of 1d indexes of non zero values. The response can be then used for repeated creation of sparse matrices with the same pattern by calling `iv2v()` ir and jc are supposed to be sorted in increasing order, column-wise (ic runs first)

Usage

```
ij2ijv_i(ir, jc)
```

Arguments

`ir`	An integer vector, row indexes
`jc`	An integer vector, column indexes

Value

A list with fields i, j and iv

---

iv2v *Sum non Zero Repeated Values*

Description

sum values in v according to possibly repeated indexes in iv

Usage

```
iv2v(iv, v)
```

Arguments

iv	An integer vector, obtained with ij2ijv_i(...)$iv
v	A numeric vector

Value

Numeric vector

---

jrhs_ff *Update Matrix by a Cascade of Dot Product*

Description

Update Matrix by a Cascade of Dot Product

Usage

```
jrhs_ff(jrhs, ff, xpfw)
```

Arguments

jrhs	A sparse matrix of type slam
ff	A sparse matrix of type slam
xpfw	A numeric matrix

---

match_ij *Fast Match for Matrix Indexes*

Description

Match ix,jx-couple in ti,tj-table and return their 1-based positions (0 for non matched couples)

Usage

```
match_ij(ix, jx, ti, tj)
```

Arguments

ix	An integer vector
jx	An integer vector
ti	An integer vector
tj	An integer vector

Value

An integer vector

Examples

```
match_ij(1:2, 1:2, 0:4, 0:4)
# [1] 2 3
```

---

mm_xpf *Dot Product SparseMatrix*DenseArray*

Description

Dot product of simple triplet matrix x (m x n) (measurement matrix) and a dense array y (n x k x l). Only slices of y_ from lsel vector are used.

Usage

```
mm_xpf(x, y_, lsel)
```

Arguments

x	A list, sparse matrix of type slam
y_	A numeric 3d array
lsel	An integer vector

Value

An array with dimensions (m x len(lsel) x k), i.e. it is permuted on the fly.

---

mult_bxxc *Calculate Inplace a Series of Dot Product*

Description

Calculate Inplace a Series of Dot Product

Usage

```
mult_bxxc(a, b, c)
```

Arguments

a	A dense array, the size of a is (nr_b, nc_c, ntico)
b	A sparse matrix (cf. simple_triplet_matrix) of size (nr_b*ntico, nc_b) given by its fields v, i, and j describing triplet storage.
c	A dense array, the size of c is (ldc, nc_c, ntico), ldc must be >= ncol(b)

Value

None

---

multbxxc *multbxxc: Auxiliary Routines for Influx Software*

Description

The multbxxc package provides a series C++ function most often operating inplace

keyword

metabolic flux analysis (MFA)

Author(s)

Serguei Sokol

References

Sokol et al. (2012) <doi:10.1093/bioinformatics/btr716>

---

redim *New Dimensions*

Description

Write new dimension vector while keeping the old memory

Usage

```
redim(x, di)
```

Arguments

x	A numeric array
di	An integer vector, new dimensions

Value

None

Examples

```
a=matrix(as.double(1:12), 6, 2)
redim(a, c(3, 4))
dim(a)
# [1] 3 4
```

`solve_ieu` *Solve ODE System by Implicite Euler Scheme*

Description

The system is defined as $M * dx/dt = a * x + s$ where M is a diagonal matrix given by its diagonal vector M (which has a form of matrix for term-by-term multiplication with x0) In discrete terms $(M/dt_i - a) * x_i = (M/dt_i) * x_(i - 1) + s_i$ The rmumps matrix $(M/dt_i - a)$ is stored in list ali as XPtr<Rmumps> or a plain dense inverted matrix. Calculations are done in-place so s is modified and contains the solution on exit. The others parameters are not modified.

Usage

```
solve_ieu(invdt, x0_, M, ali, s, ilua)
```

Arguments

`invdt`	A numeric vactor, represents 1/dt
`x0_`	A numeric matrix or NULL, is the starting value at t0 (NULL means 0)
`M`	A numeric matrix representing diagonal terms (masses)
`ali`	A list of matrices or Rmumps objects
`s`	A 3d numeric array, is the source term, its last margin corresponds to time. `s[,,i]` can be a matrix or a vector(== 1-column matrix)
`ilua`	An integer vector, `ilua[i]` gives the list index in `ali` for a given dt_i. In such a way, `ali` may be shorter than time points.

Value

None

Index

bop, 2

ij2ijv_i, 3
iv2v, 3

jrhs_ff, 4

match_ij, 4
mm_xpf, 5
mult_bxxc, 5
multbxxc, 6
multbxxc-package *(multbxxc)*, 6

redim, 6

simple_triplet_matrix, *6*
solve_ieu, 7