Package: ndjson (via r-universe)

October 28, 2026

Type Package

Title Wicked-Fast Streaming 'JSON' ('ndjson') Reader

Version 0.9.1

Date 2025-03-06

Maintainer Bob Rudis <bob@rud.is>

Description Streaming 'JSON' ('ndjson') has one 'JSON' record per-line and many modern 'ndjson' files contain large numbers of records. These constructs may not be columnar in nature, but it is often useful to read in these files and ``flatten'' the structure out to enable working with the data in an R 'data.frame'-like context. Functions are provided that make it possible to read in plain 'ndjson' files or compressed ('gz') 'ndjson' files and either validate the format of the records or create ``flat'' 'data.table' structures from them.

URL https://github.com/hrbrmstr/ndjson

BugReports https://github.com/hrbrmstr/ndjson/issues

SystemRequirements zlib, C++17

NeedsCompilation yes

License MIT + file LICENSE

Encoding UTF-8

Suggests tinytest, covr

Depends R (>= 3.2.0)

Imports Rcpp, data.table, tibble

LinkingTo Rcpp

RoxygenNote 7.3.2

Author Bob Rudis [aut, cre] (<https://orcid.org/0000-0001-5670-2640>), Niels Lohmann [aut] (C++ json parser), Deepak Bandyopadhyay [aut] (C++ gzstream), Lutz Kettner [aut] (C++ gzstream), Neal Fultz [ctb] (Rcpp integration), Maarten Demeyer [ctb] (dtplyr cleanup)

Config/pak/sysreqs zlib1g-dev

Repository https://cran.r-universe.dev

Date/Publication 2025-03-06 22:20:02 UTC

RemoteUrl https://github.com/cran/ndjson

RemoteRef HEAD

RemoteSha 928a5905a1ff44510c29cd53a6682dfcbc6a4c24

Contents

flatten 2
ndjson 3
stream_in 3
validate 4

Index **5**

`flatten` *Flatten a character vector of individual JSON lines into a* `data.table`

Description

Flatten a character vector of individual JSON lines into a `data.table`

Usage

```
flatten(x, cls = c("dt", "tbl"))
```

Arguments

`x`	character vector of individual JSON lines to flatten
`cls`	the package uses `data.table::rbindlist` for speed but that's not always the best return type for everyone, so you have option of keeping it a `data.table` or converting it to a `tbl`

Value

`data.table` or `tbl`

Examples

```
flatten('{"top":{"next":{"final":1,"end":true},"another":"yes"},"more":"no"}')
```

ndjson *Wicked-fast Streaming JSON ('ndjson) Reader*

Description

Streaming 'JSON' ('ndjson') has one 'JSON' record per-line and many modern 'ndjson' files contain large numbers of records. These constructs may not be columnar in nature, but it is often useful to read in these files and "flatten" the structure out to enable working with the data in an R 'data.frame'-like context. Functions are provided that make it possible to read in plain ndjson' files or compressed ('gz') 'ndjson' files and either validate the format of the records or create "flat" 'data.table' structures from them.

Author(s)

Bob Rudis (bob@rud.is)

See Also

Useful links:

- https://github.com/hrbrmstr/ndjson
- Report bugs at https://github.com/hrbrmstr/ndjson/issues

stream_in *Stream in & flatten an ndjson file into a* data.table

Description

Given a file of streaming JSON (ndjson) this function reads in the records and creates a flat `data.table` / `tbl` from it.

Usage

```
stream_in(path, cls = c("dt", "tbl"))
```

Arguments

path	path to file (supports "gz" files)
cls	the package uses `data.table::rbindlist` for speed but that's not always the best return type for everyone, so you have option of keeping it a `data.table` or converting it to a `tbl`

Value

`data.table` or `tbl`

References

https://ndjson.org/

Examples

```
f <- system.file("extdata", "test.json", package="ndjson")
nrow(stream_in(f))

gzf <- system.file("extdata", "testgz.json.gz", package="ndjson")
nrow(stream_in(gzf))
```

---

validate *Validate ndjson file*

Description

Given a file of streaming JSON (ndjson) this function reads in the records and validates that they are all legal JSON records. If the `verbose` parameter is `TRUE` and errors are found, the line numbers of the errant records will be displayed.

Usage

```
validate(path, verbose = FALSE)
```

Arguments

`path`	path to file (supports "gz" files)
`verbose`	display verbose information (filename and line numbers with bad records)

Value

logical

References

https://ndjson.org/

Examples

```
f <- system.file("extdata", "test.json", package="ndjson")
validate(f)

gzf <- system.file("extdata", "testgz.json.gz", package="ndjson")
validate(gzf)
```

Index

flatten, 2

ndjson, 3
ndjson-package (ndjson), 3

stream_in, 3

validate, 4