

Package: netmatchRI (via r-universe)

October 15, 2026

Title Network-Constrained Matching and Randomization-Based Inference

Version 0.1.0

Author Zhejia Dong [aut, cre]

Maintainer Zhejia Dong <zhejia_dong@brown.edu>

Description Provides network-constrained matching and randomization-based inference for observational network data with dependence and interference. Dual-penalty matching minimizes total covariate dissimilarity while enforcing penalties on network proximity between and within treatment arms in matched sets. Randomization-based inference combines evidence from correlated matched sets based on this design. The package also provides covariate-balance and network-distance diagnostics, sensitivity analysis, and simulated example data. The open-source 'HiGHS' solver is used by default to solve the matching problem. An optional interface to the commercial 'Gurobi Optimizer' is available. Eligible academic users can request a free license at <<https://www.gurobi.com/academics/>>. The optimizer can be downloaded from <<https://www.gurobi.com/product/download-center>>. The associated 'gurobi' R package is not available from CRAN; it is distributed with the optimizer and can be installed by following the official instructions at <<https://docs.gurobi.com/projects/optimizer/en/current/reference/r/setup.html>>.

License MIT + file LICENSE

URL <https://github.com/zhejiadong/netmatchRI>

BugReports <https://github.com/zhejiadong/netmatchRI/issues>

Encoding UTF-8

RoxygenNote 7.3.3

Depends R (>= 4.1.0)

Imports ggplot2, graphics, highs, igraph, Matrix, mvtnorm, optmatch, Rglpk, slam, stats, utils

Suggests knitr, MASS, rmarkdown, testthat (>= 3.2.0)
Enhances gurobi
VignetteBuilder knitr
Config/testthat/edition 3
NeedsCompilation no
Repository https://cran.r-universe.dev
Date/Publication 2026-10-15 10:20:02 UTC
RemoteUrl https://github.com/cran/netmatchRI
RemoteRef HEAD
RemoteSha 920824778233f386472528a36f6efb601023cf02

Contents

netmatchRI-package	2
critical_sensitivity	3
diagnose_match	4
matched_data	5
netmatch	6
netmatch_example	7
plot_covariate_balance	8
plot_covariate_similarity	9
plot_sensitivity	9
RI_adjusted	10
RI_design	11
RI_unadjusted	12
sensitivity_grid	13
simulate_netmatch_example	14
Index	16

netmatchRI-package	<i>netmatchRI: Network-Constrained Matching and Randomization-Based Inference</i>
--------------------	---

Description

netmatchRI provides network-constrained matching and randomization-based inference for observational network data. Dual-penalty matching minimizes total covariate dissimilarity while enforcing penalties on network proximity between and within treatment arms in matched sets. Randomization-based inference combines evidence from correlated matched sets based on this design.

Details

Use `netmatch()` to construct a dual-penalty, single-penalty, or covariate-only matched design. Inspect the result with `summary()`, `matched_data()`, and `diagnose_match()`, which checks covariate balance and within-set network distances. Compare selected matching designs with `plot_covariate_balance()` and `plot_covariate_similarity()`. Use `RI_unadjusted()`, `RI_adjusted()`, or `RI_design()` for inference, and use `sensitivity_grid()`, `critical_sensitivity()`, and `plot_sensitivity()` to examine sensitivity to residual network dependence.

Dual-penalty matching uses the open-source HiGHS solver by default. The solver argument can select HiGHS, Gurobi, or GLPK; `solver = "auto"` tries them in that order of availability.

`netmatch_example` contains the fixed data and network used in the guide. `simulate_netmatch_example()` generates new simulated network data.

`critical_sensitivity` *Critical Sensitivity Curve and Critical Ratio*

Description

Computes critical eta values where the p-value equals alpha, together with critical eta at rho = 1 and the critical ratio.

Usage

```
critical_sensitivity(match, outcome, rho = seq(0, 1, by = 0.01),
  alpha = 0.05, kappa = NULL, weight_type = c("ns", "ntc"))
```

Arguments

<code>match</code>	A netmatch object. Critical-curve interpretation is intended for dual-penalty matching.
<code>outcome</code>	Name of the numeric outcome column.
<code>rho</code>	Sensitivity-decay values in $[0, 1]$. Default: <code>seq(0, 1, by = 0.01)</code> .
<code>alpha</code>	Test level. Default: <code>0.05</code> .
<code>kappa</code>	Network distance threshold. NULL uses <code>match\$kappa</code> .
<code>weight_type</code>	Matched-set weighting. "ns" uses $1/(n_s + 1)$, where n_s is the set size; "ntc" uses $1/(n_{st}n_{sc})$, where n_{st} and n_{sc} are the treated and control counts. Default: "ns".

Details

Let $h_{s,l}$ be the minimum network distance between units in matched sets s and l . For pairs with $h_{s,l} \leq \kappa$, the sensitivity bound is $M_{sl}^*(\eta, \rho) = \eta \rho^{h_{s,l}-1} M_{sl}$. At a critical contour point, its value is the critical sensitivity bound $M_{sl}^{\text{crit}}(\rho) = M_{sl}^*(\eta^*(\rho), \rho)$. Within the parameter range, eta values below the critical curve retain rejection and values above it do not. On the curve, the p-value equals alpha.

Let S be the number of matched sets and N_κ the number of relevant matched-set pairs. The critical ratio is

$$R_{\text{crit}} = \frac{N_\kappa^{-1} \sum_{s < l: l \in \mathcal{I}_\kappa(s)} w_s w_l M_{sl}^{\text{crit}}(\rho)}{S^{-1} \sum_{s=1}^S w_s^2 \sigma_{ss}}.$$

Here, w_s is the matched-set weight and σ_{ss} is the variance of its Mann–Whitney U statistic. The numerator averages the weighted covariance bounds over pairs with minimum distance at most kappa; the denominator averages the weighted within-set variances. The ratio is constant along the critical curve.

The summary's `critical_ratio` is NA when no critical contour is attained within the range. If the baseline p-value is greater than alpha, critical eta is NA. If the baseline p-value equals alpha and the sensitivity denominator is positive, critical eta and the ratio are zero.

Value

A `netmatch_critical_sensitivity` object. `summary` reports the critical eta at $\rho = 1$ and the critical ratio; `curve` contains the critical eta over the requested rho values; `detail` contains the supporting counts and averages. The object also retains the analysis settings and matched design.

Examples

```
data("netmatch_example", package = "netmatchRI")
sim <- netmatch_example
m <- netmatch(sim$data, "Z", c("X1", "X2", "X3"), sim$net_dist,
  method = "dual", kappa = 2)
crit <- critical_sensitivity(m, "Y", rho = seq(0, 1, by = 0.25))
crit
crit$summary
crit$curve
```

diagnose_match

Diagnose a Matched Design

Description

Checks covariate balance and network distance within matched sets.

Usage

```
diagnose_match(match)
```

Arguments

`match` A `netmatch` object.

Details

Each factor level is represented by an indicator. For every reported covariate, the before and after absolute standardized mean differences use one fixed pooled original-sample standard deviation,

$$\sqrt{\{(n_1 - 1)s_1^2 + (n_0 - 1)s_0^2\}/(n_1 + n_0 - 2)}.$$

The before difference uses unweighted original-sample treatment-group means. The after difference uses the unit matching weights among matched units.

Value

A list containing covariate-balance results, a network-distance summary, and the within-matched-set distance table.

Examples

```
data("netmatch_example", package = "netmatchRI")
sim <- netmatch_example
m <- netmatch(sim$data, "Z", c("X1", "X2", "X3"), sim$net_dist,
             method = "dual", kappa = 2, solver = "auto")
diag <- diagnose_match(m)
diag$covariate_balance
diag$network_summary
diag$within_distance_table
```

matched_data

Extract Data from a Matched Design

Description

Returns the original unit-level data with matched-set membership and matching weights.

Usage

```
matched_data(object, drop_unmatched = TRUE)
```

Arguments

object A netmatch object.
drop_unmatched If TRUE, omit unmatched units. Default: TRUE.

Value

The unit-level data with subclass and weights.

Description

Provides three matching methods for observational network data: dual-penalty, single-penalty, and covariate-only matching. Dual-penalty matching minimizes total covariate dissimilarity while restricting network-close pairs both between and within treatment arms in matched sets. Single-penalty matching restricts network-close pairs across treatment arms; covariate-only matching has no network-distance restriction.

Usage

```
netmatch(data, treat, covariates, network,
  method = c("dual", "single", "covariate"), kappa = 2,
  solver = c(" highs", "auto", "gurobi", "glpk"), min_controls = 0.01,
  max_controls = 100, caliper = Inf, timelimit = 90, mipgap = 0.01,
  threads = 1, estimand = c("ATT", "ATC", "ATE"),
  network_type = c("auto", "adjacency", "distance"),
  include_solver = FALSE)
```

Arguments

data	Data frame with one row per unit. The names subclass and weights are reserved.
treat	Name of the binary treatment column.
covariates	Names of the numeric or factor covariates used for matching.
network	Symmetric adjacency or network-distance matrix aligned with data.
method	Matching method: dual-penalty, single-penalty, or covariate-only. Default: dual-penalty ("dual").
kappa	Network distance threshold used by designs with network restrictions. Default: 2.
solver	Solver for dual-penalty matching. "auto" tries HiGHS, then Gurobi, then GLPK. Default: " highs".
min_controls	Minimum control-to-treated ratio. Default: 0.01.
max_controls	Maximum control-to-treated ratio; use Inf for no upper limit. Default: 100.
caliper	Mahalanobis-distance caliper for treated-control pairs in dual-penalty matching, analogous to a propensity-score caliper; use Inf for no caliper. Default: Inf.
timelimit	Solver time limit in seconds. Default: 90.
mipgap	Target relative MIP gap. Default: 0.01.
threads	Requested solver threads. Default: 1.

estimand	Unit matching weights used in summaries and balance diagnostics: "ATT", "ATC", or "ATE". Default: "ATT". This choice does not change the sharp-null RI test.
network_type	Format of network: "auto", "adjacency", or "distance". Default: "auto".
include_solver	If TRUE, retain the complete solver result. Default: FALSE.

Details

Dual-penalty matching requires every pair of units in a matched set to have network distance greater than kappa. Single-penalty matching imposes this restriction only on treated-control pairs.

Covariate dissimilarity is the square root of the Mahalanobis quadratic form, using the pooled within-treatment-group covariance matrix.

Dual-penalty matching is formulated and solved as a mixed-integer program. Covariate-only and single-penalty comparison designs use `optmatch::fullmatch()`.

Value

`netmatch()` returns a `netmatch` object containing the matched data, full-sample subclasses and unit weights, design settings, network distances, and solver summary. The complete solver result is included only when requested.

`summary()` returns sample, balance, network, and solver summaries. `plot()` draws the within-matched-set matching diagnostic.

Examples

```
data("netmatch_example", package = "netmatchRI")
sim <- netmatch_example
m <- netmatch(
  data = sim$data,
  treat = "Z",
  covariates = c("X1", "X2", "X3"),
  network = sim$net_dist,
  method = "dual",
  kappa = 2,
  solver = "highs",
  estimand = "ATT"
)
m
summary(m)
```

netmatch_example

Simulated Network Data for the Analysis Workflow

Description

Simulated data with no treatment effect and network-dependent covariates, treatment assignment, and outcomes. The dataset was selected to illustrate how sensitivity to network dependence can change the inferential conclusion.

Usage

```
data(netmatch_example)
```

Format

A list containing data, a data frame with 300 rows and columns Z, X1, X2, X3, and Y; Adj, the aligned 300 by 300 undirected adjacency matrix; and net_dist, the corresponding shortest-path distances (infinite between disconnected nodes). Rows of the matrices follow the data frame's row order.

Source

Generated with `simulate_netmatch_example(seed = 17, n = 300, beta_z = 0, alpha1 = 0.9, alpha2 = 0.3, edge_prob = 4 / 299)`. The repository data-generation script records the construction.

Examples

```
data(netmatch_example)
dim(netmatch_example$data)
```

```
plot_covariate_balance
```

Plot Covariate Balance

Description

Compares absolute standardized mean differences before matching and across selected matching designs.

Usage

```
plot_covariate_balance(designs, include_before = TRUE)
```

Arguments

`designs` Named list of comparable netmatch objects.
`include_before` Include the unmatched sample. Default: TRUE.

Value

A ggplot object.

Examples

```
data("netmatch_example", package = "netmatchRI")
sim <- netmatch_example
m <- netmatch(sim$data, "Z", c("X1", "X2", "X3"), sim$net_dist,
              method = "dual", kappa = 2)
plot_covariate_balance(list("Dual-penalty" = m))
```

plot_covariate_similarity
Plot Covariate Similarity

Description

Compares average treated-control Mahalanobis distance before matching and within matched sets across selected matching designs. Smaller values indicate greater covariate similarity.

Usage

```
plot_covariate_similarity(designs, include_before = TRUE)
```

Arguments

`designs` Named list of comparable netmatch objects.
`include_before` Include the unmatched sample. Default: TRUE.

Value

A ggplot object.

Examples

```
data("netmatch_example", package = "netmatchRI")
sim <- netmatch_example
m <- netmatch(sim$data, "Z", c("X1", "X2", "X3"), sim$net_dist,
              method = "dual", kappa = 2)
plot_covariate_similarity(list("Dual-penalty" = m))
```

plot_sensitivity *Plot Sensitivity Results*

Description

Plots a p-value grid or a critical sensitivity curve. Stored analysis choices, including the weighting method, are reused for conversions and unadjusted reference lines.

Usage

```
plot_sensitivity(x, type = NULL, alpha = 0.05, unadjusted = NULL,
               critical_ylim = NULL)
```

Arguments

<code>x</code>	A sensitivity-grid or critical-sensitivity object.
<code>type</code>	"pvalue" or "critical". The default follows the class of <code>x</code> .
<code>alpha</code>	Reference or test level. Default: 0.05.
<code>unadjusted</code>	Optional unadjusted p-value or test result for the p-value plot.
<code>critical_ylim</code>	Optional y-axis limits for the critical plot. Default: NULL, which scales to the curve within [0, 1].

Details

A p-value plot shows how the p-value changes with ρ for each selected value of η . A critical plot shows the boundary value of η ; values below the curve retain rejection at the selected α , and values above it do not. If no finite boundary exists on the requested grid, the function returns an error with the reason rather than drawing a curve. Algebraic crossings outside the displayed range remain in the plot data but are not critical contour points within the parameter range.

Value

A ggplot object.

Examples

```
data("netmatch_example", package = "netmatchRI")
sim <- netmatch_example
m <- netmatch(sim$data, "Z", c("X1", "X2", "X3"), sim$net_dist,
             method = "dual", kappa = 2, solver = "auto")
sens <- sensitivity_grid(m, "Y", eta = c(0, 0.01, 0.05, 0.10, 0.15, 0.20),
                       rho = seq(0, 0.5, by = 0.05))
plot_sensitivity(sens)

crit <- critical_sensitivity(m, "Y")
plot_sensitivity(crit)
```

RI_adjusted

Randomization-Based Inference Adjusting for Covariance

Description

Tests the sharp null that no unit's outcome is affected by any unit's treatment, including both direct effects and treatment interference. The adjusted test scales the design-based covariance bounds between matched sets using η and ρ .

Usage

```
RI_adjusted(match, outcome, eta = 0.03, rho = 0.10, kappa = NULL,
            weight_type = c("ns", "ntc"))
```

Arguments

match	A netmatch object.
outcome	Name of the numeric outcome column.
eta	Relative magnitude of the design-based covariance bound in $[0, 1]$. Default: 0.03.
rho	Decay parameter in $[0, 1]$. Default: 0.10.
kappa	Network distance threshold. NULL uses match\$kappa.
weight_type	Matched-set weighting. "ns" uses $1/(n_s + 1)$, where n_s is the set size; "ntc" uses $1/(n_{st}n_{sc})$, where n_{st} and n_{sc} are the treated and control counts. Default: "ns".

Details

The test uses a weighted sum of Mann-Whitney U statistics from matched sets and a normal approximation to obtain a two-sided p-value. The design-based covariance bound between matched sets is scaled by eta and decays with the minimum network distance between sets according to rho. Smaller rho gives faster decay, and rho = 1 gives no decay. These are sensitivity parameters, not estimated covariances. The adjusted bound must cover the cross-matched-set covariance for the conservative inference described in the paper to apply. The null moments assume no within-matched-set ties.

Value

A netmatch_test object containing the test result, matched-set details, covariance and distance matrices, analysis settings, and original matched design.

Examples

```
data("netmatch_example", package = "netmatchRI")
sim <- netmatch_example
m <- netmatch(sim$data, "Z", c("X1", "X2", "X3"), sim$net_dist,
  method = "dual", kappa = 2, solver = "auto")
RI_adjusted(m, "Y", eta = 0.05, rho = 0.20)
```

RI_design	<i>Randomization-Based Inference with Design-Based Covariance Bounds</i>
-----------	--

Description

Tests the sharp null that no unit's outcome is affected by any unit's treatment, including both direct effects and treatment interference. The design-based test accounts for dependence using covariance bounds between matched sets.

Usage

```
RI_design(match, outcome, kappa = NULL, weight_type = c("ns", "ntc"))
```

Arguments

match	A netmatch object.
outcome	Name of the numeric outcome column.
kappa	Network distance threshold. NULL uses match\$kappa.
weight_type	Matched-set weighting. "ns" uses $1/(n_s + 1)$, where n_s is the set size; "ntc" uses $1/(n_{st}n_{sc})$, where n_{st} and n_{sc} are the treated and control counts. Default: "ns".

Details

The test uses a weighted sum of Mann-Whitney U statistics from matched sets and a normal approximation to obtain a two-sided p-value. It uses the design-based covariance bounds without scaling or decay for pairs of matched sets whose minimum network distance is at most kappa. The null moments assume no within-matched-set ties.

Value

A netmatch_test object containing the test result, matched-set details, covariance and distance matrices, analysis settings, and original matched design.

Examples

```
data("netmatch_example", package = "netmatchRI")
sim <- netmatch_example
m <- netmatch(sim$data, "Z", c("X1", "X2", "X3"), sim$net_dist,
              method = "dual", kappa = 2, solver = "auto")
RI_design(m, "Y")
```

RI_unadjusted

Randomization-Based Inference Without Covariance Adjustment

Description

Tests the sharp null that no unit's outcome is affected by any unit's treatment, including both direct effects and treatment interference. The unadjusted test proceeds without adjusting for covariance between matched sets.

Usage

```
RI_unadjusted(match, outcome, kappa = NULL, weight_type = c("ns", "ntc"))
```

Arguments

match	A netmatch object.
outcome	Name of the numeric outcome column.
kappa	Network distance threshold. NULL uses match\$kappa.
weight_type	Matched-set weighting. "ns" uses $1/(n_s + 1)$, where n_s is the set size; "ntc" uses $1/(n_{st}n_{sc})$, where n_{st} and n_{sc} are the treated and control counts. Default: "ns".

Details

The test uses a weighted sum of Mann-Whitney U statistics from matched sets and a normal approximation to obtain a two-sided p-value. It uses only within-matched-set variances. The null moments assume no within-matched-set ties.

Value

A netmatch_test object containing the test result, matched-set details, covariance and distance matrices, analysis settings, and original matched design.

Examples

```
data("netmatch_example", package = "netmatchRI")
sim <- netmatch_example
m <- netmatch(sim$data, "Z", c("X1", "X2", "X3"), sim$net_dist,
              method = "dual", kappa = 2, solver = "auto")
RI_unadjusted(m, "Y")
```

sensitivity_grid

Sensitivity Grid for Inferential Results

Description

Evaluates how the p-value changes over a grid of eta and rho values. Eta scales the design-based covariance bound between matched sets. Rho controls how that bound decays with the minimum network distance between sets: for distance d, the multiplier is $\eta * \rho^{(d - 1)}$.

Usage

```
sensitivity_grid(match, outcome, eta = seq(0, 0.10, by = 0.01),
                 rho = seq(0, 0.50, by = 0.05), kappa = NULL,
                 weight_type = c("ns", "ntc"))
```

Arguments

match	A netmatch object.
outcome	Name of the numeric outcome column.
eta	Sensitivity-scale values in $[0, 1]$. Default: <code>seq(0, 0.10, by = 0.01)</code> .
rho	Sensitivity-decay values in $[0, 1]$. Default: <code>seq(0, 0.50, by = 0.05)</code> .
kappa	Network distance threshold. NULL uses <code>match\$kappa</code> .
weight_type	Matched-set weighting. "ns" uses $1/(n_s + 1)$, where n_s is the set size; "ntc" uses $1/(n_{st}n_{sc})$, where n_{st} and n_{sc} are the treated and control counts. Default: "ns".

Details

The set statistic counts a treated outcome only when it is strictly greater than a control outcome. The null moments assume no tied outcomes within a matched set.

Value

A `netmatch_sensitivity` object containing the p-value grid, original matched design, and analysis settings.

Examples

```
data("netmatch_example", package = "netmatchRI")
sim <- netmatch_example
m <- netmatch(sim$data, "Z", c("X1", "X2", "X3"), sim$net_dist,
             method = "dual", kappa = 2, solver = "auto")
sens <- sensitivity_grid(m, "Y", eta = c(0, 0.01, 0.05, 0.10, 0.15, 0.20),
                       rho = seq(0, 0.5, by = 0.05))
sens$grid
```

```
simulate_netmatch_example
```

Generate Example Network Data

Description

Generates a random network and a data frame with three covariates, a binary treatment, and an outcome. Covariates, treatment, and outcome may be correlated across connected units.

Usage

```
simulate_netmatch_example(seed = NULL, beta_z = 0, n = 200,
                          alpha1 = 0.9, alpha2 = 0.1, edge_prob = 0.02)
```

Arguments

seed	Simulation seed. Default: NULL, which uses the current RNG state.
beta_z	Treatment effect in the outcome model. Default: 0.
n	Number of units. Default: 200.
alpha1	Network-related covariance coefficient in $[0, 1]$. Default: 0.9.
alpha2	Unit-specific covariance coefficient in $[0, 1]$. Default: 0.1.
edge_prob	Edge probability. Default: 0.02.

Value

A list containing the simulated data, adjacency matrix Adj, network-distance matrix net_dist, covariance matrix V, and the simulation settings.

Examples

```
sim <- simulate_netmatch_example(seed = 2, n = 200, beta_z = 0,  
                                alpha1 = 0.9, alpha2 = 0.1, edge_prob = 0.02)  
dim(sim$data)  
table(sim$data$Z)
```

Index

* datasets

- netmatch_example, [7](#)
- critical_sensitivity, [3, 3](#)
- diagnose_match, [3, 4](#)
- matched_data, [3, 5](#)
- netmatch, [3, 6](#)
- netmatch_example, [3, 7](#)
- netmatchRI (netmatchRI-package), [2](#)
- netmatchRI-package, [2](#)
- plot_covariate_balance, [3, 8](#)
- plot_covariate_similarity, [3, 9](#)
- plot_sensitivity, [3, 9](#)
- RI_adjusted, [3, 10](#)
- RI_design, [3, 11](#)
- RI_unadjusted, [3, 12](#)
- sensitivity_grid, [3, 13](#)
- simulate_netmatch_example, [3, 14](#)