

Package: normalize (via r-universe)

July 2, 2026

Type Package

Title Centering and Scaling of Numeric Data

Version 0.1.3

Description Provides simple methods for centering and scaling of numeric data. Columns or rows can be ignored when normalizing or be normalized jointly.

License GPL (>= 3)

Encoding UTF-8

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

Imports stats

URL <https://github.com/loelschlaeger/normalize>

BugReports <https://github.com/loelschlaeger/normalize/issues>

Config/roxygen2/version 8.0.0

NeedsCompilation no

Author Lennart Oelschläger [aut, cre]

Maintainer Lennart Oelschläger <oelschlaeger.lennart@gmail.com>

Repository <https://cran.r-universe.dev>

Date/Publication 2026-07-02 03:50:02 UTC

RemoteUrl <https://github.com/cran/normalize>

RemoteRef HEAD

RemoteSha 971c2f33ac68093574795b5ecf29924ea356d935

Contents

normalize	2
Index	4

normalize	<i>Normalize numeric data</i>
-----------	-------------------------------

Description

Center and scale vectors, matrices, data frames, or lists of these objects.

Usage

```
normalize(x, center = TRUE, scale = TRUE, ...)
```

```
## Default S3 method:
```

```
normalize(x, ...)
```

```
## S3 method for class 'numeric'
```

```
normalize(x, center = TRUE, scale = TRUE, ...)
```

```
## S3 method for class 'matrix'
```

```
normalize(  
  x,  
  center = TRUE,  
  scale = TRUE,  
  byrow = FALSE,  
  ignore = integer(),  
  jointly = list(),  
  ...  
)
```

```
## S3 method for class 'data.frame'
```

```
normalize(  
  x,  
  center = TRUE,  
  scale = TRUE,  
  byrow = FALSE,  
  ignore = integer(),  
  jointly = list(),  
  ...  
)
```

```
## S3 method for class 'list'
```

```
normalize(x, center = TRUE, scale = TRUE, ...)
```

Arguments

x	An object to be normalized.
center	[logical(1)] Should values be centered to zero mean?

scale	[logical(1)] Should values be scaled to unit variance?
...	Further arguments to be passed to or from other methods.
byrow	[logical(1)] Only relevant if x has two dimensions (rows and columns). In this case, set to TRUE to normalize row-wise or FALSE to normalize column-wise (default).
ignore	[integer()] Only relevant if x has two dimensions (rows and columns). Indices to leave unchanged. With byrow = TRUE, these are row indices. With byrow = FALSE, these are column indices. This is useful, for example, to keep identifier or non-numeric columns in a data frame.
jointly	[list()] Only relevant if x has two dimensions (rows and columns). A list of disjoint index groups to normalize jointly. With byrow = TRUE, these are row indices. With byrow = FALSE, these are column indices.

Value

A normalized version of x, preserving attributes where possible. Lists return a list with each element normalized. The centering and scaling values used are stored in the "center" and "scale" attributes where relevant.

Examples

```
# can normalize vectors, matrices, data.frames, and lists of such types
normalize(
  list(
    c(-3, 0, 3),
    matrix(1:12, nrow = 3, ncol = 4),
    data.frame(a = 1:3, b = 4:6, c = 7:9, d = 10:12)
  )
)

# can ignore columns (or rows)
normalize(
  data.frame(a = 1:3, b = c("A", "B", "C"), c = 7:9, d = 10:12),
  ignore = 2
)

# can normalize columns (or rows) jointly
normalize(
  matrix(1:12, nrow = 3, ncol = 4),
  jointly = list(1:2, 3:4)
)
```

Index

normalize, [2](#)