Package: odbc (via r-universe)

November 1, 2026

Title Connect to ODBC Compatible Databases (using the DBI Interface)

Version 1.7.2

Description A DBI-compatible interface to ODBC databases.

License MIT + file LICENSE

URL https://odbc.r-dbi.org, https://github.com/r-dbi/odbc, https://solutions.posit.co/connections/db/

BugReports https://github.com/r-dbi/odbc/issues

Depends R (>= 4.2.0)

Imports bit64, blob (>= 1.2.0), cli, DBI (>= 1.0.0), hms, lifecycle, methods, Rcpp (>= 0.12.11), rlang (>= 1.1.0), vctrs

Suggests connectcreds (>= 0.2.0), covr, DBItest, httr2, knitr, magrittr, paws.common (>= 0.7.1), rmarkdown, RSQLite, snowflakeauth, testthat (>= 3.0.0), tibble, withr

LinkingTo Rcpp

VignetteBuilder knitr

ByteCompile true

Config/Needs/check pkgbuild

Config/Needs/website tidyverse/tidytemplate

Config/roxygen2/version 8.1.0

Config/testthat/edition 3

Encoding UTF-8

SystemRequirements GNU make, An ODBC3 driver manager and drivers.

Collate 'RcppExports.R' 'aaa-odbc-data-type.R' 'connection-pane.R' 'dbi-connection.R' 'odbc-connection.R' 'db.R' 'dbi-driver.R' 'dbi-result.R' 'dbi-table.R' 'dbi.R' 'driver-access.R' 'driver-bigquery.R' 'driver-databricks.R' 'driver-db2.R' 'driver-hana.R' 'driver-hive.R' 'driver-impala.R' 'driver-mysql.R' 'driver-netezza.R' 'driver-oracle.R' 'driver-postgres.R' 'driver-redshift.R' 'driver-snowflake.R'

'driver-spark.R' 'driver-sql-server.R' 'driver-sqlite.R'
'driver-teradata.R' 'driver-vertica.R'
'import-standalone-obj-type.R'
'import-standalone-types-check.R' 'odbc-config.R'
'odbc-data-sources.R' 'odbc-drivers.R' 'odbc-package.R'
'odbc.R' 'utils.R' 'zzz.R'

NeedsCompilation yes

Author Jim Hester [aut], Hadley Wickham [aut, cre], Oliver Gjoneski [aut], Simon Couch [aut], lexicalunit [cph] (nanodbc library), Google Inc. [cph] (cctz library), Posit Software, PBC [cph, fnd]

Maintainer Hadley Wickham <hadley@posit.co>

Config/pak/sysreqs make unixodbc-dev

Repository https://cran.r-universe.dev

Date/Publication 2026-10-02 18:33:04 UTC

RemoteUrl https://github.com/cran/odbc

RemoteRef HEAD

RemoteSha fc74c1ed0220f23f1ceb5f981885815d31188119

Contents

databricks . . . 3
DBI-tables . . . 5
dbListTables,OdbcConnection-method . . . 7
isTempTable . . . 8
odbc . . . 9
odbcConnectionColumns,Snowflake,character-method . . . 12
odbcDataType . . . 12
odbcListColumns . . . 14
odbcListConfig . . . 14
odbcListDataSources . . . 15
odbcListDrivers . . . 17
odbcListObjects . . . 18
odbcListObjectTypes . . . 19
odbcPreviewObject . . . 20
odbcSetTransactionIsolationLevel . . . 20
quote_value . . . 21
redshift . . . 22
snowflake . . . 23

Index **26**

`databricks` *Helper for Connecting to Databricks via ODBC*

Description

Connect to Databricks clusters and SQL warehouses via the Databricks ODBC driver.

In particular, the custom `dbConnect()` method for the Databricks ODBC driver implements a variant of Databricks's unified authentication model when no `uid` or `pwd` is supplied, checking for ambient credentials in the following order:

- Viewer-based or service principal credentials supplied by Posit Connect (requires the **connectcreds** package).
- Personal access tokens.
- Workload identity federation.
- OAuth machine-to-machine credentials.
- OAuth user-to-machine credentials suplied via Posit Workbench or the Databricks CLI on desktop.

This aims to provide broad compatibility between **odbc** and the standard environment variables used by Databricks SDKs in R and other languages.

In addition, on macOS platforms, the `dbConnect()` method will check for irregularities with how the driver is configured, and attempt to fix in-situ, unless the `odbc.no_config_override` environment variable is set.

String truncation:

The Databricks ODBC driver reports `STRING` columns to clients as `VARCHAR(n)`, where `n` is the value of its `DefaultStringColumnLength` connection attribute. This reported size determines the allocated string buffer, and the driver can silently truncate values that do not fit. Because the driver's own default of 255 is easy to hit in practice, `dbConnect()` sets this attribute to 65535 by default. Pass `defaultStringColumnLength` to `dbConnect()` to choose another limit.

Usage

```
databricks()

## S4 method for signature 'DatabricksOdbcDriver'
dbConnect(
  drv,
  httpPath,
  workspace = Sys.getenv("DATABRICKS_HOST"),
  useNativeQuery = TRUE,
  driver = NULL,
  HTTPPath,
  uid = NULL,
  pwd = NULL,
  ...
)
```

Arguments

drv	an object that inherits from DBI::DBIDriver, or an existing DBI::DBIConnection object (in order to clone an existing connection).
httpPath, HTTPPath	To query a cluster, use the HTTP Path value found under Advanced Options > JDBC/ODBC in the Databricks UI. For SQL warehouses, this is found under Connection Details instead.
workspace	The URL of a Databricks workspace, e.g. "https://example.cloud.databricks.com".
useNativeQuery	Suppress the driver's conversion from ANSI SQL 92 to HiveSQL. When set to true, we also set the following related flags: EnableNativeParameterizedQuery, and PopulateParametersForNativeQuery. The default (TRUE), gives greater performance but could cause issues with paramterised queries (and hence dbWriteTable()).
driver	The name of the Databricks ODBC driver, or NULL to use the default name.
uid, pwd	Manually specify a username and password for authentication. Specifying these options will disable automated credential discovery.
...	Further arguments passed on to dbConnect().

Value

An OdbcConnection object with an active connection to a Databricks cluster or SQL warehouse.

Examples

```
## Not run:
DBI::dbConnect(
  odbc::databricks(),
  httpPath = "sql/protocolv1/o/4425955464597947/1026-023828-vn51jugj"
)

# Use credentials from the viewer or a service principal (when possible) in
# a Shiny app deployed to Posit Connect.
library(connectcreds)
server <- function(input, output, session) {
  conn <- DBI::dbConnect(
    odbc::databricks(),
    workspace = "https://example.cloud.databricks.com",
    httpPath = "sql/protocolv1/o/4425955464597947/1026-023828-vn51jugj"
  )
}

## End(Not run)
```

DBI-tables *Convenience functions for reading/writing DBMS tables*

Description

Convenience functions for reading/writing DBMS tables

Usage

```
## S4 method for signature 'OdbcConnection,character,data.frame'
dbWriteTable(
  conn,
  name,
  value,
  overwrite = FALSE,
  append = FALSE,
  temporary = FALSE,
  row.names = NULL,
  field.types = NULL,
  batch_rows = getOption("odbc.batch_rows", NA),
  ...
)

## S4 method for signature 'OdbcConnection,Id,data.frame'
dbWriteTable(
  conn,
  name,
  value,
  overwrite = FALSE,
  append = FALSE,
  temporary = FALSE,
  row.names = NULL,
  field.types = NULL,
  batch_rows = getOption("odbc.batch_rows", NA),
  ...
)

## S4 method for signature 'OdbcConnection,SQL,data.frame'
dbWriteTable(
  conn,
  name,
  value,
  overwrite = FALSE,
  append = FALSE,
  temporary = FALSE,
  row.names = NULL,
  field.types = NULL,
```

```
  batch_rows = getOption("odbc.batch_rows", NA),
  ...
)

## S4 method for signature 'OdbcConnection'
dbAppendTable(
  conn,
  name,
  value,
  batch_rows = getOption("odbc.batch_rows", NA),
  ...,
  row.names = NULL
)

## S4 method for signature 'OdbcConnection'
sqlCreateTable(
  con,
  table,
  fields,
  row.names = NA,
  temporary = FALSE,
  ...,
  field.types = NULL
)
```

Arguments

conn	An OdbcConnection object, produced by DBI::dbConnect().
name	a character string specifying a table name. Names will be automatically quoted so you can use any sequence of characters, not just any valid bare table name.
value	A data.frame to write to the database.
overwrite	Allow overwriting the destination table. Cannot be TRUE if append is also TRUE.
append	Allow appending to the destination table. Cannot be TRUE if overwrite is also TRUE.
temporary	If TRUE, will generate a temporary table.
row.names	Either TRUE, FALSE, NA or a string. If TRUE, always translate row names to a column called "row_names". If FALSE, never translate row names. If NA, translate rownames only if they're a character vector. A string is equivalent to TRUE, but allows you to override the default name. For backward compatibility, NULL is equivalent to FALSE.
field.types	Additional field types used to override derived types.
batch_rows	The number of rows to retrieve. Defaults to NA, which is set dynamically to the minimum of 1024 and the size of the input. Depending on the database, driver, dataset and free memory, setting this to a lower value may improve performance.
...	Other arguments used by individual methods.

con	A database connection.
table	The table name, passed on to dbQuoteIdentifier(). Options are: • a character string with the unquoted DBMS table name, e.g. "table_name", • a call to Id() with components to the fully qualified table name, e.g. Id(schema = "my_schema", table = "table_name") • a call to SQL() with the quoted and fully qualified table name given verbatim, e.g. SQL('"my_schema"."table_name"')
fields	Either a character vector or a data frame. A named character vector: Names are column names, values are types. Names are escaped with dbQuoteIdentifier(). Field types are unescaped. A data frame: field types are generated using dbDataType().

Examples

```
## Not run:
library(DBI)
con <- dbConnect(odbc::odbc())
dbListTables(con)
dbWriteTable(con, "mtcars", mtcars, temporary = TRUE)
dbReadTable(con, "mtcars")

dbListTables(con)
dbExistsTable(con, "mtcars")

# A zero row data frame just creates a table definition.
dbWriteTable(con, "mtcars2", mtcars[0, ], temporary = TRUE)
dbReadTable(con, "mtcars2")

dbDisconnect(con)

## End(Not run)
```

---

dbListTables,OdbcConnection-method

List remote tables and fields for an ODBC connection

Description

dbListTables() provides names of remote tables accessible through this connection; dbListFields() provides names of columns within a table.

Usage

```
## S4 method for signature 'OdbcConnection'
dbListTables(
  conn,
  catalog_name = NULL,
```

```
  schema_name = NULL,
  table_name = NULL,
  table_type = NULL,
  ...
)
```

Arguments

conn	A DBI::DBIConnection object, as returned by dbConnect().
catalog_name, schema_name, table_name	Catalog, schema, and table names. By default, catalog_name, schema_name and table_name will automatically escape underscores to ensure that you match exactly one table. If you want to search for multiple tables using wild cards, you will need to use odbcConnectionTables() directly instead.
table_type	The type of the table to return, the default returns all table types.
...	Other parameters passed on to methods.

Value

A character vector of table or field names respectively.

---

isTempTable *Helper method used to determine if a table identifier is that of a temporary table.*

Description

Currently implemented only for select back-ends where we have a use for it (SQL Server, for example). Generic, in case we develop a broader use case.

Usage

```
isTempTable(conn, name, ...)

## S4 method for signature 'OdbcConnection,Id'
isTempTable(conn, name, ...)

## S4 method for signature 'OdbcConnection,SQL'
isTempTable(conn, name, ...)
```

Arguments

conn	OdbcConnection
name	Table name
...	additional parameters to methods

odbc *Connect to a database via an ODBC driver*

Description

The dbConnect() method documented here is invoked when DBI::dbConnect() is called with the first argument odbc(). Connecting to a database via an ODBC driver is likely the first step in analyzing data using the odbc package; for an overview of package concepts, see the *Overview* section below.

Usage

```
odbc()

## S4 method for signature 'OdbcDriver'
dbConnect(
  drv,
  dsn = NULL,
  ...,
  timezone = "UTC",
  timezone_out = "UTC",
  encoding = "",
  name_encoding = "",
  bigint = c("integer64", "integer", "numeric", "character"),
  timeout = 10,
  driver = NULL,
  server = NULL,
  database = NULL,
  uid = NULL,
  pwd = NULL,
  dbms.name = NULL,
  attributes = NULL,
  interruptible = getOption("odbc.interruptible", interactive()),
  .connection_string = NULL
)
```

Arguments

drv	An OdbcDriver, from odbc().
dsn	The data source name. For currently available options, see the name column of odbcListDataSources() output.
...	Additional ODBC keywords. These will be joined with the other arguments to form the final connection string. Note that ODBC parameter names are case-insensitive so that (e.g.) DRV and drv are equivalent. Since this is different to R and a possible source of confusion, odbc will error if you supply multiple arguments that have the same name when case is ignored.

Any values containing a leading or trailing space, a =, ;, {, or } are likely to require quoting. Use quote_value() for a fairly standard approach or see your driver documentation for specifics.

timezone — The server time zone. Useful if the database has an internal timezone that is *not* 'UTC'. If the database is in your local timezone, set this argument to Sys.timezone(). See OlsonNames() for a complete list of available time zones on your system. Note, if the datatype itself carries timezone information, as is the case, for example, with SQL Server::DATETIMEOFFSET, package:odbc will make an effort to respect the timezone declared therein. In those cases, this parameter is not used - the timezone that is part of the datatype takes precedence.

timezone_out — The time zone returned to R. If you want to display datetime values in the local timezone, set to Sys.timezone().

encoding — The text encoding used on the Database. If the database is not using UTF-8 you will need to set the encoding to get accurate re-encoding. See iconvlist() for a complete list of available encodings on your system. Note strings are always returned UTF-8 encoded.

name_encoding — The text encoding for column names used on the Database. May be different than the encoding argument. Defaults to empty string which is equivalent to returning the column names without performing any conversion.

bigint — The R type that SQL_BIGINT types should be mapped to. Default is bit64::integer64, which allows the full range of 64 bit integers.

timeout — Time in seconds to timeout the connection attempt. Setting a timeout of Inf or NA indicates no timeout. Defaults to 10 seconds.

driver — The ODBC driver name or a path to a driver. For currently available options, see the name column of odbcListDrivers() output.

server — The server hostname. Some drivers use Servername as the name for this argument. Not required when configured for the supplied dsn.

database — The database on the server. Not required when configured for the supplied dsn.

uid — The user identifier. Some drivers use username as the name for this argument. Not required when configured for the supplied dsn.

pwd — The password. Some drivers use password as the name for this argument. Not required when configured for the supplied dsn.

dbms.name — The database management system name. This should normally be queried automatically by the ODBC driver. This name is used as the class name for the OdbcConnection object returned from dbConnect(). However, if the driver does not return a valid value, it can be set manually with this parameter.

attributes — A list of connection attributes that are passed prior to the connection being established. See ConnectionAttributes.

interruptible — Logical. If TRUE calls to SQLExecute and SQLExecuteDirect can be interrupted when the user sends SIGINT (ctrl-c). Otherwise, they block. Defaults to TRUE in interactive sessions, and FALSE otherwise. It can be set explicitly either by manipulating this argument, or by setting the global option odbc.interruptible.

`.connection_string`
: A complete connection string, useful if you are copy pasting it from another source. If this argument is used, any additional arguments will be appended to this string.

Connection strings

Internally, `dbConnect()` creates a connection string using the supplied arguments. Connection string keywords are driver-dependent; the arguments documented here are common, but some drivers may not accept them.

Alternatively to configuring DSNs and driver names with the driver manager, you can pass a complete connection string directly as the `.connection_string` argument. The Connection Strings Reference is a useful resource that has example connection strings for a large variety of databases.

Overview

The odbc package is one piece of the R interface to databases with support for ODBC:



The package supports any **Database Management System (DBMS)** with ODBC support. Support for a given DBMS is provided by an **ODBC driver**, which defines how to interact with that DBMS using the standardized syntax of ODBC and SQL. Drivers can be downloaded from the DBMS vendor or, if you're a Posit customer, using the professional drivers. To manage information about each driver and the data sources they provide access to, our computers use a **driver manager**. Windows is bundled with a driver manager, while MacOS and Linux require installation of one; this package supports the unixODBC driver manager.

In the **R interface**, the DBI package provides a front-end while odbc implements a back-end to communicate with the driver manager. The odbc package is built on top of the nanodbc C++ library.

Interfacing with DBMSs using R and odbc involves three high-level steps:

1. *Configure drivers and data sources*: the functions `odbcListDrivers()`, `odbcListDataSources()`, and `odbcListConfig()` help to interface with the driver manager.
2. *Connect to a database*: The `dbConnect()` function, called with the first argument odbc(), connects to a database using the specified ODBC driver to create a connection object.
3. *Interface with connections*: The resulting connection object can be passed to various functions to retrieve information on database structure ([DBI::dbListTables()][]), iteratively develop queries (`DBI::dbSendQuery()`, `DBI::dbColumnInfo()`), and query data objects (`DBI::dbFetch()`).

Learn more

To learn more about databases:

- "Best Practices in Working with Databases" documents how to use the odbc package with various popular databases.

- The pyodbc "Drivers and Driver Managers" Wiki provides further context on drivers and driver managers.
- Microsoft's "Introduction to ODBC" is a thorough resource on the ODBC interface.

`odbcConnectionColumns,Snowflake,character-method`
Connecting to Snowflake via ODBC

Description

`odbcConnectionColumns()`:

If the catalog, or the schema arguments are NULL, attempt to infer by querying for CURRENT_DATABASE() and CURRENT_SCHEMA(). We do this to aid with performance, as the SQLColumns method is more performant when restricted to a particular DB/schema.

Usage

```
## S4 method for signature 'Snowflake,character'
dbExistsTableForWrite(conn, name, ..., catalog_name = NULL, schema_name = NULL)
```

Arguments

`conn`	A DBI::DBIConnection object, as returned by `dbConnect()`.
`name`	The table name, passed on to `dbQuoteIdentifier()`. Options are: • a character string with the unquoted DBMS table name, e.g. `"table_name"`, • a call to `Id()` with components to the fully qualified table name, e.g. `Id(schema = "my_schema", table = "table_name")` • a call to `SQL()` with the quoted and fully qualified table name given verbatim, e.g. `SQL('"my_schema"."table_name"')`
`...`	Other parameters passed on to methods.
`catalog_name, schema_name`	Catalog and schema names.

`odbcDataType` *Return the corresponding ODBC data type for an R object*

Description

This is used when creating a new table with `dbWriteTable()`. Databases with default methods defined are:

- MySQL
- PostgreSQL
- SQL Server
- Oracle
- SQLite
- Spark
- Hive
- Impala
- Redshift
- Vertica
- BigQuery
- Teradata
- Access
- Snowflake

Usage

```
odbcDataType(con, obj, ...)
```

Arguments

`con`	A driver connection object, as returned by `dbConnect()`.
`obj`	An R object.
`...`	Additional arguments passed to methods.

Details

If you are using a different database and `dbWriteTable()` fails with a SQL parsing error the default method is not appropriate, you will need to write a new method. The object type for your method will be the database name retrieved by `dbGetInfo(con)$dbms.name`. Use the documentation provided with your database to determine appropriate values for each R data type.

Value

Corresponding SQL type for the `obj`.

odbcListColumns *List columns in an object.*

Description

Lists the names and types of each column (field) of a specified object.

Usage

```
odbcListColumns(connection, ...)
```

Arguments

connection	A connection object, as returned by dbConnect().
...	Parameters specifying the object.

Details

The object to inspect must be specified as one of the arguments (e.g. `table = "employees"`); depending on the driver and underlying data store, additional specification arguments may be required.

Value

A data frame with `name` and `type` columns, listing the object's fields.

odbcListConfig *List locations of ODBC configuration files*

Description

On MacOS and Linux, odbc uses the unixODBC driver manager to manage information about driver and data sources. This helper returns the filepaths where the driver manager will look for that information.

`odbcListConfig()` is a wrapper around the command line call `odbcinst -j`. The `odbcEditDrivers()`, `odbcEditSystemDSN()`, and `odbcEditUserDSN()` helpers provide a shorthand for `file.edit(odbcListConfig()[[i]])`.

Windows does not use `.ini` configuration files; on Windows, `odbcListConfig()` will return a 0-length vector and `odbcEdit*()` will raise an error.

Usage

```
odbcListConfig()

odbcEditDrivers()

odbcEditSystemDSN()

odbcEditUserDSN()
```

See Also

The odbcListDrivers() and odbcListDataSources() helpers return information on the contents of odbcinst.ini and odbc.ini files, respectively. odbcListDataSources() collates entries from both the System and User odbc.ini files.

Learn more about unixODBC and the odbcinst utility here.

Examples

```
configs <- odbcListConfig()

configs

# shorthand for file.edit(configs[[1]])
odbcEditDrivers()
```

---

odbcListDataSources *List Configured Data Source Names*

Description

Collect information about the available data source names (DSNs). A DSN must be both installed and configured with the driver manager to be included in this list. Configuring a DSN just sets up a lookup table (e.g. in odbc.ini) to allow users to pass only the DSN to dbConnect().

DSNs that are not configured with the driver manager can still be connected to with dbConnect() by providing DSN metadata directly.

Usage

```
odbcListDataSources()
```

Value

A data frame with two columns:

name Name of the data source. The entries in this column can be passed to the dsn argument of dbConnect().

description Data source description.

Configuration

This function interfaces with the driver manager to collect information about the available data source names.

For **MacOS and Linux**, the odbc package supports the unixODBC driver manager. unixODBC looks to the odbc.ini *configuration file* for information on DSNs. Find the location(s) of your odbc.ini file(s) with odbcinst -j.

In this example odbc.ini file:

```
[MySQL]
Driver = MySQL Driver
Database = test
Server = 127.0.0.1
User = root
password = root
Port = 3306
```

...the data source name is `MySQL`, which will appear in the `name` column of this function's output. To pass the DSN as the `dsn` argument to `dbConnect()`, pass it as a string, like `"MySQL"`. `Driver = MySQL Driver` references the driver `name` in `odbcListDrivers()` output.

Windows is bundled with an ODBC driver manager.

When a DSN is configured with a driver manager, information on the DSN will be automatically passed on to `dbConnect()` when its `dsn` argument is set.

For example, with the `MySQL` data source name configured, and the driver name `MySQL Driver` appearing in `odbcListDrivers()` output, the code:

```
con <-
  dbConnect(
    odbc::odbc(),
    Driver = "MySQL Driver",
    Database = "test",
    Server = "127.0.0.1",
    User = "root",
    password = "root",
    Port = 3306
  )
```

...can be written:

```
con <- dbConnect(odbc::odbc(), dsn = "MySQL")
```

In this case, `dbConnect()` will look up the information defined for `MySQL` in the driver manager (in our example, `odbc.ini`) and automatically pass the needed arguments.

See Also

`odbcListDrivers()`

odbcListDrivers *List Configured ODBC Drivers*

Description

Collect information about the configured driver names. A driver must be both installed and configured with the driver manager to be included in this list. Configuring a driver name just sets up a lookup table (e.g. in `odbcinst.ini`) to allow users to pass only the driver name to `dbConnect()`.

Driver names that are not configured with the driver manager (and thus do not appear in this function's output) can still be used in `dbConnect()` by providing a path to a driver directly.

Usage

```
odbcListDrivers(
  keep = getOption("odbc.drivers_keep"),
  filter = getOption("odbc.drivers_filter")
)
```

Arguments

`keep`, `filter`	A character vector of driver names to keep in or remove from the results, respectively. If `NULL`, all driver names will be kept, or none will be removed, respectively. The `odbc.drivers_keep` and `odbc.drivers_filter` options control the argument defaults. Driver names are first processed with `keep`, then `filter`. Thus, if a driver name is in both `keep` and `filter`, it won't appear in output.

Value

A data frame with three columns.

name Name of the driver. The entries in this column can be passed to the `driver` argument of `dbConnect()` (as long as the driver accepts the argument).

attribute Driver attribute name.

value Driver attribute value.

If a driver has multiple attributes, there will be one row per attribute, each with the same driver `name`. If a given driver name does not have any attributes, the function will return one row with the driver `name`, but the last two columns will be `NA`.

Configuration

This function interfaces with the driver manager to collect information about the available driver names.

For **MacOS and Linux**, the odbc package supports the unixODBC driver manager. unixODBC looks to the `odbcinst.ini` *configuration file* for information on driver names. Find the location(s) of your `odbcinst.ini` file(s) with `odbcinst -j`.

In this example `odbcinst.ini` file:

```
[MySQL Driver]
Driver=/opt/homebrew/Cellar/mysql/8.2.0_1/lib/libmysqlclient.dylib
```

Then the driver name is `MySQL Driver`, which will appear in the `name` column of this function's output. To pass the driver name as the `driver` argument to `dbConnect()`, pass it as a string, like `"MySQL Driver"`.

Windows is bundled with an ODBC driver manager.

In this example, function output would include 1 row: the `name` column would read `"MySQL Driver"`, `attribute` would be `"Driver"`, and `value` would give the file path to the driver. Additional key-value pairs under the driver name would add additional rows with the same `name` entry.

When a driver is configured with a driver manager, information on the driver will be automatically passed on to `dbConnect()` when its `driver` argument is set. For an example, see the same section in the `odbcListDataSources()` help-file. Instead of configuring driver information with a driver manager, it is also possible to provide a path to a driver directly to `dbConnect()`.

See Also

`odbcListDataSources()`

Examples

```
odbcListDrivers()
```

`odbcListObjects` *List objects in a connection.*

Description

Lists all of the objects in the connection, or all the objects which have specific attributes.

Usage

```
odbcListObjects(connection, ...)
```

Arguments

`connection`	A connection object, as returned by `dbConnect()`.
`...`	Attributes to filter by.

Details

When used without parameters, this function returns all of the objects known by the connection. Any parameters passed will filter the list to only objects which have the given attributes; for instance, passing `schema = "foo"` will return only objects matching the schema `foo`.

Value

A data frame with `name` and `type` columns, listing the objects.

`odbcListObjectTypes` *Return the object hierarchy supported by a connection.*

Description

Lists the object types and metadata known by the connection, and how those object types relate to each other.

Usage

```
odbcListObjectTypes(connection)
```

Arguments

`connection`	A connection object, as returned by `dbConnect()`.

Details

The returned hierarchy takes the form of a nested list, in which each object type supported by the connection is a named list with the following attributes:

contains A list of other object types contained by the object, or "data" if the object contains data

icon An optional path to an icon representing the type

For instance, a connection in which the top-level object is a schema that contains tables and views, the function will return a list like the following:

```
list(schema = list(contains = list(
                   list(name = "table", contains = "data")
                   list(name = "view", contains = "data"))))
```

Value

The hierarchy of object types supported by the connection.

odbcPreviewObject *Preview the data in an object.*

Description

Return the data inside an object as a data frame.

Usage

```
odbcPreviewObject(connection, rowLimit, ...)
```

Arguments

connection	A connection object, as returned by dbConnect().
rowLimit	The maximum number of rows to display.
...	Parameters specifying the object.

Details

The object to previewed must be specified as one of the arguments (e.g. table = "employees"); depending on the driver and underlying data store, additional specification arguments may be required.

Value

A data frame containing the data in the object.

odbcSetTransactionIsolationLevel *Set the Transaction Isolation Level for a Connection*

Description

Set the Transaction Isolation Level for a Connection

Usage

```
odbcSetTransactionIsolationLevel(conn, levels)
```

Arguments

conn	A DBI::DBIConnection object, as returned by dbConnect().
levels	One or more of 'read_uncommitted', 'read_committed', 'repeatable_read', 'serializable'.

See Also

https://learn.microsoft.com/en-us/sql/odbc/reference/develop-app/setting-the-transaction-isolation-

Examples

```
## Not run:
# Can use spaces or underscores in between words.
odbcSetTransactionIsolationLevel(con, "read uncommitted")

# Can also use the full constant name.
odbcSetTransactionIsolationLevel(con, "SQL_TXN_READ_UNCOMMITTED")

## End(Not run)
```

---

quote_value *Quote special character when connecting*

Description

When connecting to a database using odbc, all the arguments are concatenated into a single connection string that looks like `name1=value1;name2=value2`. That means if your value contains `=` or `;` then it needs to be quoted. Other rules mean that you need to quote any values that starts or ends with white space, or contains `{` or `}`.

This function quotes a string in a way that should work for most drivers, but unfortunately there doesn't seem to be an approach that works everywhere. If this function doesn't work for you, you'll need to carefully read the docs for your driver.

Usage

```
quote_value(x)
```

Arguments

x	A string to quote.

Value

A quoted string, wrapped in `I()`.

Examples

```
quote_value("abc")
quote_value("ab'c")

# Real usage is more likely to look like:
## Not run:
library(DBI)
```

```
con <- dbConnect(
  odbc::odbc(),
  dsn = "reallycooldatabase"
  password = odbc::quote_value(Sys.getenv("MY_PASSWORD"))
)

## End(Not run)
```

`redshift` *Helper for Connecting to Redshift via ODBC*

Description

Connect to Redshift clusters via ODBC.

In particular, the custom `dbConnect()` method for Redshift ODBC drivers automatically determines whether IAM-based credentials are available, much like other AWS SDKs and tools. This requires the **paws.common** package.

Usage

```
redshift()

## S4 method for signature 'RedshiftOdbcDriver'
dbConnect(
  drv,
  clusterId,
  server,
  database,
  region = NULL,
  driver = NULL,
  uid = NULL,
  pwd = NULL,
  dbUser = uid,
  ...
)
```

Arguments

`drv`	an object that inherits from DBI::DBIDriver, or an existing DBI::DBIConnection object (in order to clone an existing connection).
`clusterId`	The Redshift cluster identifier. Only one of `clusterId` or the more verbose `server` is required.
`server`	The full hostname of the Redshift cluster.
`database`	The name of the Redshift database to connect to.
`region`	The AWS region the Redshift cluster runs in. Ignored when `server` is provided. Defaults to the value of the environment variable `AWS_REGION`, then `AWS_REGION`, or uses `us-east-1` if both are unset.

driver	The name of or path to a Redshift ODBC driver, or NULL to locate one automatically.
uid, pwd	Disable IAM credentials and manually specify a username and password for authentication.
dbUser	The Redshift database account.
...	Further arguments passed on to dbConnect().

Value

An OdbcConnection object with an active connection to a Redshift cluster or SQL warehouse.

Examples

```
## Not run:
# Connect to Redshift using IAM credentials.
DBI::dbConnect(
  odbc::redshift(),
  clusterId = "my-testing-cluster",
  database = "dev",
  dbUser = "me"
)

## End(Not run)
```

---

snowflake *Helper for connecting to Snowflake via ODBC*

Description

Connect to a Snowflake account via the Snowflake ODBC driver.

In particular, the custom dbConnect() method for the Snowflake ODBC driver supports the connections.toml and config.toml files used by the Snowflake Connector for Python and the Snowflake CLI via the **snowflakeauth** package. It also detects ambient OAuth credentials on platforms like Snowpark Container Services or Posit Workbench. Finally, it can detect viewer-based or service account credentials on Posit Connect if the **connectcreds** package is installed.

In addition, on macOS platforms, the dbConnect method will check and warn if it detects irregularities with how the driver is configured, unless the odbc.no_config_override environment variable is set.

Usage

```
snowflake()

## S4 method for signature 'SnowflakeOdbcDriver'
dbConnect(
  drv,
  account = Sys.getenv("SNOWFLAKE_ACCOUNT"),
```

```
  driver = NULL,
  warehouse = NULL,
  database = NULL,
  schema = NULL,
  uid = NULL,
  pwd = NULL,
  connection_name = NULL,
  ...
)
```

Arguments

drv	an object that inherits from DBI::DBIDriver, or an existing DBI::DBIConnection object (in order to clone an existing connection).
account	A Snowflake account identifier, e.g. "testorg-test_account".
driver	The name of the Snowflake ODBC driver, or NULL to use the default name.
warehouse	The name of a Snowflake compute warehouse, or NULL to use the default.
database	The name of a Snowflake database, or NULL to use the default.
schema	The name of a Snowflake database schema, or NULL to use the default.
uid, pwd	Manually specify a username and password for authentication. Specifying these options will disable ambient credential discovery.
connection_name	The name of a connection defined in your Snowflake connections.toml file, or NULL to use the default connection.
...	Further arguments passed on to dbConnect().

Value

An OdbcConnection object with an active connection to a Snowflake account.

Examples

```
## Not run:
# Use ambient credentials.
DBI::dbConnect(odbc::snowflake())

# Use browser-based SSO (if configured). Only works on desktop.
DBI::dbConnect(
  odbc::snowflake(),
  account = "testorg-test_account",
  authenticator = "externalbrowser"
)

# Use a traditional username & password.
DBI::dbConnect(
  odbc::snowflake(),
  account = "testorg-test_account",
  uid = "me",
```

```
  pwd = rstudioapi::askForPassword()
)

# Use a named connection from a connections.toml file.
DBI::dbConnect(odbc::snowflake(), connection_name = "test")

# Use credentials from the viewer or a service account (when possible) in
# content deployed to Posit Connect.
library(connectcreds)
server <- function(input, output, session) {
  conn <- DBI::dbConnect(odbc::snowflake())
}

## End(Not run)
```

Index

bit64::integer64, *10*

ConnectionAttributes, *10*

databricks, 3
DatabricksOdbcDriver-class *(databricks)*, 3
dbAppendTable,OdbcConnection-method *(DBI-tables)*, 5
dbConnect *(odbc)*, 9
dbConnect(), *4*, *10*, *11*, *15–18*, *23*, *24*
dbConnect,DatabricksOdbcDriver-method *(databricks)*, 3
dbConnect,OdbcDriver-method *(odbc)*, 9
dbConnect,RedshiftOdbcDriver-method *(redshift)*, 22
dbConnect,SnowflakeOdbcDriver-method *(snowflake)*, 23
dbDataType(), *7*
dbExistsTableForWrite,Snowflake,character-method *(odbcConnectionColumns,Snowflake,character-method)*, 12
DBI-tables, 5
DBI::dbColumnInfo(), *11*
DBI::dbConnect(), *6*, *9*
DBI::dbFetch(), *11*
DBI::DBIConnection, *4*, *8*, *12*, *20*, *22*, *24*
DBI::DBIDriver, *4*, *22*, *24*
DBI::dbSendQuery(), *11*
dbListTables,OdbcConnection-method, 7
dbQuoteIdentifier(), *7*, *12*
dbWriteTable,OdbcConnection,character,data.frame-method *(DBI-tables)*, 5
dbWriteTable,OdbcConnection,Id,data.frame-method *(DBI-tables)*, 5
dbWriteTable,OdbcConnection,SQL,data.frame-method *(DBI-tables)*, 5

iconvlist(), *10*
Id(), *7*, *12*

isTempTable, 8
isTempTable,OdbcConnection,Id-method *(isTempTable)*, 8
isTempTable,OdbcConnection,SQL-method *(isTempTable)*, 8

odbc, 9
OdbcConnection, *6*
odbcConnectionColumns,Snowflake,character-method, 12
odbcConnectionColumns,Snowflake,SQL-method *(odbcConnectionColumns,Snowflake,character-method)*, 12
odbcDataType, 12
odbcDataType,ACCESS-method *(odbcDataType)*, 12
odbcDataType,ANY-method *(odbcDataType)*, 12
odbcDataType,BigQuery-method *(odbcDataType)*, 12
odbcDataType,Hive-method *(odbcDataType)*, 12
odbcDataType,Impala-method *(odbcDataType)*, 12
odbcDataType,Microsoft SQL Server-method *(odbcDataType)*, 12
odbcDataType,MySQL-method *(odbcDataType)*, 12
odbcDataType,NetezzaSQL-method *(odbcDataType)*, 12
odbcDataType,Oracle-method *(odbcDataType)*, 12
odbcDataType,PostgreSQL-method *(odbcDataType)*, 12
odbcDataType,Redshift-method *(odbcDataType)*, 12
odbcDataType,Snowflake-method *(odbcDataType)*, 12
odbcDataType,Spark SQL-method *(odbcDataType)*, 12

odbcDataType,SQLite-method
(odbcDataType), 12
odbcDataType,Teradata-method
(odbcDataType), 12
odbcDataType,Vertica Database-method
(odbcDataType), 12
odbcEditDrivers (odbcListConfig), 14
odbcEditDrivers(), *14*
odbcEditSystemDSN (odbcListConfig), 14
odbcEditSystemDSN(), *14*
odbcEditUserDSN (odbcListConfig), 14
odbcEditUserDSN(), *14*
odbcListColumns, 14
odbcListConfig, 14
odbcListConfig(), *11*
odbcListDataSources, 15
odbcListDataSources(), *9*, *11*, *15*, *18*
odbcListDrivers, 17
odbcListDrivers(), *10, 11*, *15, 16*
odbcListObjects, 18
odbcListObjectTypes, 19
odbcPreviewObject, 20
odbcSetTransactionIsolationLevel, 20
OlsonNames(), *10*

quote_value, 21
quote_value(), *10*

redshift, 22
RedshiftOdbcDriver-class (redshift), 22

snowflake, 23
SnowflakeOdbcDriver-class (snowflake),
23
SQL(), *7*, *12*
sqlCreateTable,OdbcConnection-method
(DBI-tables), 5
Sys.timezone(), *10*