Package: openNLP (via r-universe)

October 16, 2026

Encoding UTF-8

Version 0.2-8

Title Apache OpenNLP Tools Interface

Description An interface to the Apache OpenNLP tools (version 1.5.3). The Apache OpenNLP library is a machine learning based toolkit for the processing of natural language text written in Java. It supports the most common NLP tasks, such as tokenization, sentence segmentation, part-of-speech tagging, named entity extraction, chunking, parsing, and coreference resolution. See <https://opennlp.apache.org/> for more information.

Imports NLP (>= 0.1-6.3), openNLPdata (>= 1.5.3-1), rJava (>= 0.6-3)

Suggests openNLPmodels.en

Additional_repositories https://datacube.wu.ac.at

SystemRequirements Java (>= 5.0)

License GPL-3

NeedsCompilation no

Author Kurt Hornik [aut, cre] (ORCID: <https://orcid.org/0000-0003-4198-9911>)

Maintainer Kurt Hornik <Kurt.Hornik@R-project.org>

Config/pak/sysreqs default-jdk

Repository https://cran.r-universe.dev

Date/Publication 2026-07-13 11:33:33 UTC

RemoteUrl https://github.com/cran/openNLP

RemoteRef HEAD

RemoteSha d34bb58f4366cad82de73f32dc51f96ab969c0b7

Contents

Maxent_Chunk_Annotator 2
Maxent_Entity_Annotator 3

Maxent_POS_Tag_Annotator 5
Maxent_Sent_Token_Annotator 6
Maxent_Word_Token_Annotator 7
Parse_Annotator 9

Index **11**

`Maxent_Chunk_Annotator` *Apache OpenNLP based chunk annotators*

Description

Generate an annotator which computes chunk annotations using the Apache OpenNLP Maxent chunker.

Usage

```
Maxent_Chunk_Annotator(language = "en", probs = FALSE, model = NULL)
```

Arguments

`language`	a character string giving the ISO-639 code of the language being processed by the annotator.
`probs`	a logical indicating whether the computed annotations should provide the token probabilities obtained from the Maxent model as their 'chunk_prob' feature.
`model`	a character string giving the path to the Maxent model file to be used, or `NULL` indicating to use a default model file for the given language (if available, see **Details**).

Details

See https://opennlp.sourceforge.net/models-1.5/ for available model files. These can conveniently be made available to R by installing the respective **openNLPmodels.***language* packages from the repository at https://datacube.wu.ac.at.

Value

An `Annotator` object giving the generated chunk annotator.

See Also

https://opennlp.apache.org for more information about Apache OpenNLP.

Examples

```
## Requires package 'openNLPmodels.en' from the repository at
## <https://datacube.wu.ac.at>.
if(nzchar(system.file(package = "openNLPmodels.en"))) {
    use("NLP")
    ## Some text.
    s <- paste(c("Pierre Vinken, 61 years old, will join the board as a ",
                 "nonexecutive director Nov. 29.\n",
                 "Mr. Vinken is chairman of Elsevier N.V., ",
                 "the Dutch publishing group."),
               collapse = "")
    s <- as.String(s)

    ## Chunking needs word token annotations with POS tags.
    sent_token_annotator <- Maxent_Sent_Token_Annotator()
    word_token_annotator <- Maxent_Word_Token_Annotator()
    pos_tag_annotator <- Maxent_POS_Tag_Annotator()
    a3 <- annotate(s,
                   list(sent_token_annotator,
                        word_token_annotator,
                        pos_tag_annotator))

    annotate(s, Maxent_Chunk_Annotator(), a3)
    annotate(s, Maxent_Chunk_Annotator(probs = TRUE), a3)
}
```

Maxent_Entity_Annotator

Apache OpenNLP based entity annotators

Description

Generate an annotator which computes entity annotations using the Apache OpenNLP Maxent name finder.

Usage

```
Maxent_Entity_Annotator(language = "en", kind = "person", probs = FALSE,
                        model = NULL)
```

Arguments

language	a character string giving the ISO-639 code of the language being processed by the annotator.
kind	a character string giving the 'kind' of entity to be annotated (person, date, ...).
probs	a logical indicating whether the computed annotations should provide the token probabilities obtained from the Maxent model as their 'prob' feature.

`model` a character string giving the path to the Maxent model file to be used, or `NULL` indicating to use a default model file for the given language (if available, see **Details**).

Details

See https://opennlp.sourceforge.net/models-1.5/ for available model files. These can conveniently be made available to R by installing the respective **openNLPmodels.***language* package from the repository at https://datacube.wu.ac.at.

Value

An `Annotator` object giving the generated entity annotator.

See Also

https://opennlp.apache.org for more information about Apache OpenNLP.

Examples

```
## Requires package 'openNLPmodels.en' from the repository at
## <https://datacube.wu.ac.at>.
if(nzchar(system.file(package = "openNLPmodels.en"))) {
    use("NLP")
    ## Some text.
    s <- paste(c("Pierre Vinken, 61 years old, will join the board as a ",
                 "nonexecutive director Nov. 29.\n",
                 "Mr. Vinken is chairman of Elsevier N.V., ",
                 "the Dutch publishing group."),
               collapse = "")
    s <- as.String(s)

    ## Need sentence and word token annotations.
    sent_token_annotator <- Maxent_Sent_Token_Annotator()
    word_token_annotator <- Maxent_Word_Token_Annotator()
    a2 <- annotate(s, list(sent_token_annotator, word_token_annotator))

    ## Entity recognition for persons.
    entity_annotator <- Maxent_Entity_Annotator()
    entity_annotator
    annotate(s, entity_annotator, a2)
    ## Directly:
    entity_annotator(s, a2)
    ## And slice ...
    s[entity_annotator(s, a2)]
    ## Variant with sentence probabilities as features.
    annotate(s, Maxent_Entity_Annotator(probs = TRUE), a2)
}
```

`Maxent_POS_Tag_Annotator` *Apache OpenNLP based POS tag annotators*

Description

Generate an annotator which computes POS tag annotations using the Apache OpenNLP Maxent Part of Speech tagger.

Usage

```
Maxent_POS_Tag_Annotator(language = "en", probs = FALSE, model = NULL)
```

Arguments

`language`	a character string giving the ISO-639 code of the language being processed by the annotator.
`probs`	a logical indicating whether the computed annotations should provide the token probabilities obtained from the Maxent model as their 'POS_prob' feature.
`model`	a character string giving the path to the Maxent model file to be used, or `NULL` indicating to use a default model file for the given language (if available, see **Details**).

Details

See https://opennlp.sourceforge.net/models-1.5/ for available model files. For languages other than English, these can conveniently be made available to R by installing the respective **openNLPmodels.***language* package from the repository at https://datacube.wu.ac.at. For English, no additional installation is required.

Value

An `Annotator` object giving the generated POS tag annotator.

See Also

https://opennlp.apache.org for more information about Apache OpenNLP.

Examples

```
use("NLP")
## Some text.
s <- paste(c("Pierre Vinken, 61 years old, will join the board as a ",
             "nonexecutive director Nov. 29.\n",
             "Mr. Vinken is chairman of Elsevier N.V., ",
             "the Dutch publishing group."),
           collapse = "")
s <- as.String(s)
```

```
## Need sentence and word token annotations.
sent_token_annotator <- Maxent_Sent_Token_Annotator()
word_token_annotator <- Maxent_Word_Token_Annotator()
a2 <- annotate(s, list(sent_token_annotator, word_token_annotator))

pos_tag_annotator <- Maxent_POS_Tag_Annotator()
pos_tag_annotator
a3 <- annotate(s, pos_tag_annotator, a2)
a3
## Variant with POS tag probabilities as (additional) features.
head(annotate(s, Maxent_POS_Tag_Annotator(probs = TRUE), a2))

## Determine the distribution of POS tags for word tokens.
a3w <- subset(a3, type == "word")
tags <- sapply(a3w$features, `[[`, "POS")
tags
table(tags)
## Extract token/POS pairs (all of them): easy.
sprintf("%s/%s", s[a3w], tags)

## Extract pairs of word tokens and POS tags for second sentence:
a3ws2 <- annotations_in_spans(subset(a3, type == "word"),
                              subset(a3, type == "sentence")[2L])[[1L]]
sprintf("%s/%s", s[a3ws2], sapply(a3ws2$features, `[[`, "POS"))
```

`Maxent_Sent_Token_Annotator` *Apache OpenNLP based sentence token annotators*

Description

Generate an annotator which computes sentence annotations using the Apache OpenNLP Maxent sentence detector.

Usage

```
Maxent_Sent_Token_Annotator(language = "en", probs = FALSE, model = NULL)
```

Arguments

`language`	a character string giving the ISO-639 code of the language being processed by the annotator.
`probs`	a logical indicating whether the computed annotations should provide the token probabilities obtained from the Maxent model as their 'prob' feature.
`model`	a character string giving the path to the Maxent model file to be used, or `NULL` indicating to use a default model file for the given language (if available, see **Details**).

Details

See https://opennlp.sourceforge.net/models-1.5/ for available model files. For languages other than English, these can conveniently be made available to R by installing the respective **openNLPmodels.***language* package from the repository at https://datacube.wu.ac.at. For English, no additional installation is required.

Value

An Annotator object giving the generated sentence token annotator.

See Also

https://opennlp.apache.org for more information about Apache OpenNLP.

Examples

```
use("NLP")
## Some text.
s <- paste(c("Pierre Vinken, 61 years old, will join the board as a ",
             "nonexecutive director Nov. 29.\n",
             "Mr. Vinken is chairman of Elsevier N.V., ",
             "the Dutch publishing group."),
           collapse = "")
s <- as.String(s)

sent_token_annotator <- Maxent_Sent_Token_Annotator()
sent_token_annotator
a1 <- annotate(s, sent_token_annotator)
a1
## Extract sentences.
s[a1]
## Variant with sentence probabilities as features.
annotate(s, Maxent_Sent_Token_Annotator(probs = TRUE))
```

Maxent_Word_Token_Annotator

Apache OpenNLP based word token annotators

Description

Generate an annotator which computes word token annotations using the Apache OpenNLP Maxent tokenizer.

Usage

```
Maxent_Word_Token_Annotator(language = "en", probs = FALSE, model = NULL)
```

Arguments

language	a character string giving the ISO-639 code of the language being processed by the annotator.
probs	a logical indicating whether the computed annotations should provide the token probabilities obtained from the Maxent model as their 'prob' feature.
model	a character string giving the path to the Maxent model file to be used, or NULL indicating to use a default model file for the given language (if available, see **Details**).

Details

See https://opennlp.sourceforge.net/models-1.5/ for available model files. For languages other than English, these can conveniently be made available to R by installing the respective **openNLPmodels.***language* package from the repository at https://datacube.wu.ac.at. For English, no additional installation is required.

Value

An Annotator object giving the generated word token annotator.

See Also

https://opennlp.apache.org for more information about Apache OpenNLP.

Examples

```
use("NLP")
## Some text.
s <- paste(c("Pierre Vinken, 61 years old, will join the board as a ",
             "nonexecutive director Nov. 29.\n",
             "Mr. Vinken is chairman of Elsevier N.V., ",
             "the Dutch publishing group."),
           collapse = "")
s <- as.String(s)

## Need sentence token annotations.
sent_token_annotator <- Maxent_Sent_Token_Annotator()
a1 <- annotate(s, sent_token_annotator)

word_token_annotator <- Maxent_Word_Token_Annotator()
word_token_annotator
a2 <- annotate(s, word_token_annotator, a1)
a2
## Variant with word token probabilities as features.
head(annotate(s, Maxent_Word_Token_Annotator(probs = TRUE), a1))

## Can also perform sentence and word token annotations in a pipeline:
a <- annotate(s, list(sent_token_annotator, word_token_annotator))
head(a)
```

Parse_Annotator *Apache OpenNLP based parse annotator*

Description

Generate an annotator which computes Penn Treebank parse annotations using the Apache OpenNLP chunking parser for English.

Usage

```
Parse_Annotator()
```

Details

Using the generated annotator requires installing package **openNLPmodels.en** from the repository at https://datacube.wu.ac.at (which provides the Maxent model file used by the parser).

Value

An Annotator object giving the generated parse annotator.

See Also

https://opennlp.apache.org for more information about Apache OpenNLP.

Examples

```
## Requires package 'openNLPmodels.en' from the repository at
## <https://datacube.wu.ac.at>.
if(nzchar(system.file(package = "openNLPmodels.en"))) {
    use("NLP")
    ## Some text.
    s <- paste(c("Pierre Vinken, 61 years old, will join the board as a ",
                 "nonexecutive director Nov. 29.\n",
                 "Mr. Vinken is chairman of Elsevier N.V., ",
                 "the Dutch publishing group."),
               collapse = "")
    s <- as.String(s)

    ## Need sentence and word token annotations.
    sent_token_annotator <- Maxent_Sent_Token_Annotator()
    word_token_annotator <- Maxent_Word_Token_Annotator()
    a2 <- annotate(s, list(sent_token_annotator, word_token_annotator))

    parse_annotator <- Parse_Annotator()
    ## Compute the parse annotations only.
    p <- parse_annotator(s, a2)
    ## Extract the formatted parse trees.
    ptexts <- sapply(p$features, `[[`, "parse")
```

```
    ptexts
    ## Read into NLP Tree objects.
    ptrees <- lapply(ptexts, Tree_parse)
    ptrees
}
```

Index

Annotator, *2*, *4*, *5*, *7–9*

Maxent_Chunk_Annotator, 2
Maxent_Entity_Annotator, 3
Maxent_POS_Tag_Annotator, 5
Maxent_Sent_Token_Annotator, 6
Maxent_Word_Token_Annotator, 7

Parse_Annotator, 9