

Package: **optimsimplex** (via r-universe)

October 14, 2024

Type Package

Title R Port of the 'Scilab' Optimsimplex Module

Version 1.0-8

Date 2022-01-28

Description Provides a building block for optimization algorithms based on a simplex. The 'optimsimplex' package may be used in the following optimization methods: the simplex method of Spendley et al. (1962) <[doi:10.1080/00401706.1962.10490033](https://doi.org/10.1080/00401706.1962.10490033)>, the method of Nelder and Mead (1965) <[doi:10.1093/comjnl/7.4.308](https://doi.org/10.1093/comjnl/7.4.308)>, Box's algorithm for constrained optimization (1965) <[doi:10.1093/comjnl/8.1.42](https://doi.org/10.1093/comjnl/8.1.42)>, the multi-dimensional search by Torczon (1989) <<https://www.cs.wm.edu/~va/research/thesis.pdf>>, etc...

Depends optimbase (>= 1.0-8),methods

Suggests knitr (>= 1.28),rmarkdown (>= 2.2)

License CeCILL-2

Encoding UTF-8

VignetteBuilder knitr

LazyLoad yes

NeedsCompilation no

Author Sebastien Bihorel [aut, cre], Michael Baudin [aut]

Maintainer Sebastien Bihorel <sb.pmlab@gmail.com>

Repository CRAN

Date/Publication 2022-01-28 21:10:06 UTC

Contents

optimsimplex-package	2
Function evaluations	3
Get functions	4
optimsimplex	6

optimsimplex.destroy	9
optimsimplex.log	10
optimsimplex.reflect	10
optimsimplex.shrink	11
optimsimplex.utils	12
osimplex	14
Set functions	16
Simplex gradient	17

Index	19
--------------	-----------

optimsimplex-package *R port of the Scilab optimsimplex module*

Description

The goal of this package is to provide a building block for optimization algorithms based on a simplex. The **optimsimplex** package may be used in the following optimization methods:

- the simplex method of Spendley et al.,
- the method of Nelder and Mead,
- the Box's algorithm for constrained optimization,
- the multi-dimensional search by Torczon,
- etc ...

Features The following is a list of features currently provided:

- Manage various simplex initializations
 - initial simplex given by user,
 - initial simplex computed with a length and along the coordinate axes,
 - initial regular simplex computed with Spendley et al. formula,
 - initial simplex computed by a small perturbation around the initial guess point,
 - initial simplex computed from randomized bounds.
- sort the vertices by increasing function values,
- compute the standard deviation of the function values in the simplex,
- compute the simplex gradient with forward or centered differences,
- shrink the simplex toward the best vertex,
- etc...

Details

Package: optimsimplex
 Type: Package
 Version: 1.0-8
 Date: 2022-01-28
 License: CeCILL-2
 LazyLoad: yes

See `vignette('optimsimplex', package='optimsimplex')` for more information.

Author(s)

Author of Scilab optimsimplex module: Michael Baudin (INRIA - Digiteo)

Author of R adaptation: Sebastien Bihorel (<sb.pmlab@gmail.com>)

Function evaluations *Computation of Function Value(s)*

Description

These functions compute the value of the function at the vertices points stored in the current simplex object and stored them back into the simplex object. `optimsimplex.computefv` determines how many vertices are stored in the simplex object and delegates the calculation of the function values to `optimsimplex.compsomefv`.

Usage

```
optimsimplex.computefv(this = NULL, fun = NULL, data = NULL)
optimsimplex.compsomefv(this = NULL, fun = NULL, indices = NULL, data = NULL)
```

Arguments

<code>this</code>	The current simplex object, containing the <code>nbve x n</code> matrix of vertice coordinates (i.e. <code>x</code> element), where <code>n</code> is the dimension of the space and <code>nbve</code> the number of vertices.
<code>fun</code>	The function to compute at vertices. The function is expected to have the following input and output arguments:

```
myfunction <- function(x, this){
  ...
  return(list(f=f,this=this))
}
```

where `x` is a row vector and `this` a user-defined data, i.e. the data argument.

<code>data</code>	A user-defined data passed to the function. If data is provided, it is passed to the callback function both as an input and output argument. <code>data</code> may be used if the function uses some additional parameters. It is returned as an output parameter because the function may modify the data while computing the function value. This feature may be used, for example, to count the number of times that the function has been called.
<code>indices</code>	A vector of increasing integers from 1 to <code>nbve</code> .

Value

`optimsimplex.compute fv` and `optimsimplex.compsome fv` return a list with the following elements:

this The updated simplex object.

data The updated user-defined data.

Author(s)

Author of Scilab `optimsimplex` module: Michael Baudin (INRIA - Digiteo)

Author of R adaptation: Sebastien Bihorel (<sb.pmlab@gmail.com>)

See Also

[optimsimplex](#)

Get functions

Optimsimplex Get Function Class

Description

The functions extract the content to various elements of a simplex object:

`optimsimplex.getall` Get all the coordinates and the function values of all the vertices.

`optimsimplex.getallfv` Get all the function values of all the vertices.

`optimsimplex.getallx` Get all the coordinates of all the vertices.

`optimsimplex.getfv` Get the function value at a given index.

`optimsimplex.getn` Get the dimension of the space of the simplex.

`optimsimplex.getnbve` Get the number of vertices of the simplex.

`optimsimplex.getve` Get the vertex at a given index in the current simplex.

`optimsimplex.getx` Get the coordinates of the vertex at a given index in the current simplex.

Usage

```

optimsimplex.getall(this = NULL)
optimsimplex.getallfv(this = NULL)
optimsimplex.getallx(this = NULL)
optimsimplex.getfv(this = NULL, ive = NULL)
optimsimplex.getn(this = NULL)
optimsimplex.getnbve(this = NULL)
optimsimplex.getve(this = NULL, ive = NULL)
optimsimplex.getx(this = NULL, ive = NULL)

```

Arguments

<code>this</code>	A simplex object.
<code>ive</code>	Vertex index.

Value

`optimsimplex.getall` Return a `nbve` x `n+1` matrix, where `n` is the dimension of the space, `nbve` is the number of vertices and with the following content:

- `simplex[k, 1]` is the function value of the vertex `k`, with `k = 1` to `nbve`,
- `simplex[k, 2:(n+1)]` is the coordinates of the vertex `k`, with `k = 1` to `nbve`.

`optimsimplex.getallfv` Return a row vector of function values, which `k`th element is the function value for the vertex `k`, with `k = 1` to `nbve`.

`optimsimplex.getallx` Return a `nbve` x `n` matrix of vertice coordinates; any given vertex is expected to be stored at row `k`, with `k = 1` to `nbve`.

`optimsimplex.getfv` Return a numeric scalar.

`optimsimplex.getn` Return a numeric scalar.

`optimsimplex.getnbve` Return a numeric scalar.

`optimsimplex.getve` Return an object of class 'vertex', i.e. a list with the following elements:

- n** The dimension of the space of the simplex.
- x** The coordinates of the vertex at index `ive`.
- fv** The value of the function at index `ive`.

`optimsimplex.getx` Return a row vector, representing the coordinates of the vertex at index `ive`.

Author(s)

Author of Scilab `optimsimplex` module: Michael Baudin (INRIA - Digiteo)

Author of R adaptation: Sebastien Bihorel (<sb.pmlab@gmail.com>)

See Also

[optimsimplex](#)

optimsimplex	<i>S3 optimsimplex class</i>
--------------	------------------------------

Description

These functions support the S3 class 'optimsimplex' and are intended to either create objects of this class or check if an object is of this class.

Usage

```
optimsimplex(coords = NULL, fun = NULL, data = NULL, method = NULL,
            x0 = NULL, len = NULL, deltausual = NULL, deltazero = NULL,
            boundsmax = NULL, boundsmin = NULL, nbve = NULL,
            simplex0 = NULL)
```

```
optimsimplex.tostring(x)
```

```
## S3 method for class 'optimsimplex'
print(x,...)
```

```
## S3 method for class 'optimsimplex'
is(x)
```

Arguments

coords The matrix of point estimate coordinates in the simplex. The coords matrix is expected to be a nbve x n matrix, where n is the dimension of the space and nbve is the number of vertices in the simplex, with nbve >= n+1. Only used if method is set to NULL.

fun The function to compute at vertices. The function is expected to have the following input and output arguments:

```
myfunction <- function(x, this){
  ...
  return(list(f=f,this=this))
}
```

where x is a row vector and this a user-defined data, i.e. the data argument.

data A user-defined data passed to the function. If data is provided, it is passed to the callback function both as an input and output argument. data may be used if the function uses some additional parameters. It is returned as an output parameter because the function may modify the data while computing the function value. This feature may be used, for example, to count the number of times that the function has been called.

method	The method used to create the new optimsimplex object, either 'axes', 'pfeffer', 'randbounds', 'spendley' or 'oriented'.
x0	The initial point estimates, as a row vector of length n.
len	The dimension of the simplex. If length is a value, that unique length is used in all directions. If length is a vector with n values, each length is used with the corresponding direction. Only used if method is set to 'axes' or 'spendley'.
deltausal	The absolute delta for non-zero values. Only used if method is set to 'pfeffer'.
deltazero	The absolute delta for zero values. Only used if method is set to 'pfeffer'.
boundsmmin	A vector of minimum bounds. Only used if method is set to 'randbounds'.
boundsmmax	A vector of maximum bounds. Only used if method is set to 'randbounds'.
nbve	The total number of vertices in the simplex. Only used if method is set to 'randbounds'.
simplex0	The initial simplex. Only used if method is set to 'oriented'.
x	An object of class 'optimsimplex'.
...	optional arguments to 'print' or 'plot' methods.

Details

All arguments of optimsimplex are optional. If no input is provided, the new optimsimplex object is empty.

If method is NULL, the new optimsimplex object is created by optimsimplex.coords. If coords is NULL, the optimsimplex object is empty; otherwise, coords is used as the initial vertice coordinates in the new simplex.

If method is set to 'axes', the initial vertice coordinates are stored in a nbve x n matrix built as follows:

$$\begin{array}{ccccccc}
 [,1] & | & x0[1] & \dots & x0[n] & | & \dots & | & len[1] & \dots & 0 & | \\
 [,.] & | & \dots & \dots & \dots & | & + & | & \dots & \dots & \dots & | \\
 [,nbve] & | & x0[1] & \dots & x0[n] & | & \dots & | & 0 & \dots & len[n] & |
 \end{array}$$

If method is set to 'pfeffer', the new optimsimplex object is created using the Pfeffer's method, i.e. a relative delta for non-zero values and an absolute delta for zero values.

If method is set to 'randbounds', the initial vertice coordinates are stored in a nbve x n matrix consisting of the initial point estimates (on the first row) and a (nbve-1) x n matrix of randomly sampled numbers between the specified the bounds. The number of vertices nbve in the optimsimplex is arbitrary.

If method is set to 'spendley', the new optimsimplex object is created using the Spendley's method, i.e. a regular simplex made of nbve = n+1 vertices.

If method is set to 'oriented', the new optimsimplex object is created in sorted order. The new simplex has the same sigma- length of the base simplex, but is "oriented" depending on the function value. The created optimsimplex may be used, as Kelley suggests, for a restart of Nelder-Mead algorithm.

The optimsimplex.tostring function is a utility function, which formats the content of a optimsimplex object into a single string of characters.

Value

The `optimsimplex` function returns a list with the following elements:

newobj An object of class 'simplex', i.e. a list with the following elements:

- verbose** The verbose option, controlling the amount of messages. Set to FALSE.
- x** The coordinates of the vertices, with size `nbve x n`.
- n** The dimension of the space.
- fv** The values of the function at given vertices. It is a column matrix of length `nbve`.
- nbve** The number of vertices.

data The updated data input argument.

Author(s)

Author of Scilab `optimsimplex` module: Michael Baudin (INRIA - Digiteo)

Author of R adaptation: Sebastien Bihorel (<sb.pmlab@gmail.com>)

References

"A Simplex Method for Function Minimization", Nelder, J. A. and Mead, R. The Computer Journal, January, 1965, 308-313

"Sequential Application of Simplex Designs in Optimisation and Evolutionary Operation", W. Spendley, G. R. Hext, F. R. Himsforth, Technometrics, Vol. 4, No. 4 (Nov., 1962), pp. 441-461, Section 3.1

"A New Method of Constrained Optimization and a Comparison With Other Methods", M. J. Box, The Computer Journal 1965 8(1):42-52, 1965 by British Computer Society

"Detection and Remediation of Stagnation in the Nelder-Mead Algorithm Using a Sufficient Decrease Condition", SIAM J. on Optimization, Kelley C.T., 1999

"Multi-Directional Search: A Direct Search Algorithm for Parallel Machines", by E. Boyd, Kenneth W. Kennedy, Richard A. Tapia, Virginia Joanne Torczon, Virginia Joanne Torczon, 1989, Phd Thesis, Rice University

"Grid Restrained Nelder-Mead Algorithm", Arpad Burmen, Janez Puhon, Tadej Tuma, Computational Optimization and Applications, Volume 34 , Issue 3 (July 2006), Pages: 359 - 375

"A convergent variant of the Nelder-Mead algorithm", C. J. Price, I. D. Coope, D. Byatt, Journal of Optimization Theory and Applications, Volume 113 , Issue 1 (April 2002), Pages: 5 - 19,

"Global Optimization Of Lennard-Jones Atomic Clusters", Ellen Fan, Thesis, February 26, 2002, McMaster University

Examples

```
myfun <- function(x, this){return(list(f=sum(x^2), this=this))}
mat <- matrix(c(0,1,0,0,0,1), ncol=2)
```

```
optimsimplex()
optimsimplex(coords=mat, x0=1:4, fun=myfun)
optimsimplex(method='axes', x0=1:4, fun=myfun)
optimsimplex(method='pfeffer', x0=1:6, fun=myfun)
```

```
opt <- optimsimplex(method='randbounds',x0=1:6,boundsmin=rep(0,6),
                   boundsmax=rep(10,6),fun=myfun)
opt
optimsimplex(method='spendley',x0=1:6,fun=myfun,len=10)
optimsimplex(method='oriented',simplex=opt$newobj,fun=myfun)
```

optimsimplex.destroy *Erase Simplex Object*

Description

This function erases the coordinates of the vertices (x) and the function values (fv) in a simplex object

Usage

```
optimsimplex.destroy(this = NULL)
```

Arguments

this A simplex object.

Value

Return an updated simplex object for which the content of the x and fv elements were set to NULL.

Author(s)

Author of Scilab optimsimplex module: Michael Baudin (INRIA - Digiteo)

Author of R adaptation: Sebastien Bihorel (<sb.pmlab@gmail.com>)

See Also

[optimsimplex](#)

optimsimplex.log *Optimsimplex Logging*

Description

This function prints a message to screen (or log file).

Usage

```
optimsimplex.log(this = NULL, msg = NULL)
```

Arguments

<code>this</code>	An simplex object.
<code>msg</code>	A message to print.

Value

Do not return any value but print `msg` to screen if the `verbose` in `this` is set to 1.

Author(s)

Author of Scilab `optimsimplex` module: Michael Baudin (INRIA - Digiteo)

Author of R adaptation: Sebastien Bihorel (<sb.pmlab@gmail.com>)

See Also

[optimsimplex](#)

optimsimplex.reflect *Simplex Reflection*

Description

This function returns a new simplex by reflection of the current simplex with respect to the first vertex in the simplex. This move is used in the centered simplex gradient.

Usage

```
optimsimplex.reflect(this = NULL, fun = NULL, data = NULL)
```

Arguments

this An simplex object.
fun The function to compute at vertices. The function is expected to have the following input and output arguments:

```
myfunction <- function(x, this){
  ...
  return(list(f=f,this=this))
}
```

where x is a row vector and this a user-defined data, i.e. the data argument.

data A user-defined data passed to the function. If data is provided, it is passed to the callback function both as an input and output argument. data may be used if the function uses some additional parameters. It is returned as an output parameter because the function may modify the data while computing the function value. This feature may be used, for example, to count the number of times that the function has been called.

Value

Return a list with the following elements:

- r** The reflected simplex object.
- data** The updated user-defined data.

Author(s)

Author of Scilab optimsimplex module: Michael Baudin (INRIA - Digiteo)
 Author of R adaptation: Sebastien Bihorel (<sb.pmlab@gmail.com>)

See Also

[optimsimplex](#)

optimsimplex.shrink *Simplex Shrink*

Description

This function shrinks the simplex with given coefficient sigma and returns an updated simplex. The shrink is performed with respect to the first point in the simplex.

Usage

```
optimsimplex.shrink(this = NULL, fun = NULL, sigma = 0.5, data = NULL)
```

Arguments

this An simplex object

fun The function to compute at vertices. The function is expected to have the following input and output arguments:

```
myfunction <- function(x, this){
  ...
  return(list(f=f,this=this))
}
```

where x is a row vector and $this$ a user-defined data, i.e. the data.

sigma The shrinkage coefficient. The default value is 0.5.

data A user-defined data passed to the function. If data is provided, it is passed to the callback function both as an input and output argument. `data` may be used if the function uses some additional parameters. It is returned as an output parameter because the function may modify the data while computing the function value. This feature may be used, for example, to count the number of times that the function has been called.

Value

Return a list with the following elements:

this The updated simplex object.

data The updated user-defined data.

Author(s)

Author of Scilab optimsimplex module: Michael Baudin (INRIA - Digiteo)

Author of R adaptation: Sebastien Bihorel (<sb.pmlab@gmail.com>)

See Also

[optimsimplex](#)

optimsimplex.utils *Optimsimplex Utility Functions*

Description

These functions enable various calculations and checks on the current simplex:

`optimsimplex.center` Compute the center of the current simplex.

`optimsimplex.check` Check the consistency of the data in the current simplex.

`optimsimplex.deltafv` Compute the vector of function value differences with respect to the function value at the first vertex (the lowest).

- optimsimplex.deltafvmax Compute the difference of function value between the lowest and the highest vertices. It is expected that the first vertex (`this$x[1,]`) is associated with the smallest function value and that the last vertex (`this$x[nbve,]`) is associated with the highest function value.
- optimsimplex.dirmat Compute the matrix of simplex direction, i.e. the matrix of differences of vertice coordinates with respect to the first vertex.
- optimsimplex.fvmean Compute the mean of the function values in the current simplex.
- optimsimplex.fvstdev Compute the standard deviation of the function values in the current simplex.
- optimsimplex.fvvariance Compute the variance of the function values in the current simplex.
- optimsimplex.size Determines the size of the simplex.
- optimsimplex.sort Sort the simplex by increasing order of function value, so the smallest function is at the first vertex.
- optimsimplex.xbar Compute the center of n vertices, by excluding the vertex with index `iexcl`. The default of `iexcl` is the number of vertices: in that case, if the simplex is sorted in increasing function value order, the worst vertex is excluded.

Usage

```

optimsimplex.center(this = NULL)
optimsimplex.check(this = NULL)
optimsimplex.deltafv(this = NULL)
optimsimplex.deltafvmax(this = NULL)
optimsimplex.dirmat(this = NULL)
optimsimplex.fvmean(this = NULL)
optimsimplex.fvstdev(this = NULL)
optimsimplex.fvvariance(this = NULL)
optimsimplex.size(this = NULL, method = NULL)
optimsimplex.sort(this = NULL)
optimsimplex.xbar(this = NULL, iexcl = NULL)

```

Arguments

- | | |
|---------------------|---|
| <code>this</code> | The current simplex. |
| <code>method</code> | The method to use to compute the size of the simplex. The available methods are the following:
<ul style="list-style-type: none"> 'sigmaplus' (this is the default) The sigmamplus size is the maximum 2-norm length of the vector from each vertex to the first vertex. It requires one loop over the vertices. 'sigmaminus' The sigmaminus size is the minimum 2-norm length of the vector from each vertex to the first vertex. It requires one loop over the vertices. 'Nash' The 'Nash' size is the sum of the norm of the norm-1 length of the vector from the given vertex to the first vertex. It requires one loop over the vertices. 'diameter' The diameter is the maximum norm-2 length of all the edges of the simplex. It requires 2 nested loops over the vertices. |
| <code>iexcl</code> | The index of the vertex to exclude in center computation. |

Value

- optimsimplex.center Return a vector of length nbve, where nbve is the number of vertices in the current simplex.
- optimsimplex.check Return an error message if the dimensions of the various elements of the current simplex do not match.
- optimsimplex.deltafv Return a column vector of length nbve-1.
- optimsimplex.deltafvmax Return a numeric scalar.
- optimsimplex.dirmat Return a n x n numeric matrix, where n is the dimension of the space of the simplex.
- optimsimplex.fvmean Return a numeric scalar.
- optimsimplex.fvstdev Return a numeric scalar.
- optimsimplex.fvvariance Return a numeric scalar.
- optimsimplex.size Return a numeric scalar.
- optimsimplex.sort Return an updated simplex object.
- optimsimplex.xbar Return a row vector of length n.

Author(s)

Author of Scilab optimsimplex module: Michael Baudin (INRIA - Digiteo)

Author of R adaptation: Sebastien Bihorel (<sb.pmlab@gmail.com>)

References

"Compact Numerical Methods For Computers - Linear Algebra and Function Minimization", J.C. Nash, 1990, Chapter 14. Direct Search Methods

"Iterative Methods for Optimization", C.T. Kelley, 1999, Chapter 6., section 6.2

See Also

[optimsimplex](#)

osimplex

S3 osimplex and vertex classes

Description

These functions support the S3 classes 'osimplex' and 'vertex'. They are intended to either create objects of these classes or check if an object is of these classes

Usage

```
osimplex(verbose,x,n,fv,nbve)

vertex(x,n,fv)

## S3 method for class 'osimplex'
print(x,...)

## S3 method for class 'vertex'
print(x,...)

## S3 method for class 'osimplex'
is(x)

## S3 method for class 'vertex'
is(x)
```

Arguments

verbose	The verbose option, controlling the amount of messages
x	The coordinates of the vertices, with size nbve x n in a simplex object or 1 x n in a vertex.
n	The dimension of the space.
fv	The values of the function at given vertices. It is a column matrix of length nbve in a simplex or a single value in a vertex.
nbve	The number of vertices in a simplex.
...	optional arguments to 'print' or 'plot' methods.

Details

A simplex of size n x nbve is essentially a collection of vertex of size n.

Value

osimplex returns a list with the following elements: verbose, x, n, fv, and nbve. vertex returns a list with the following elements: x, n, and fv.

Author(s)

Author of Scilab optimsimplex module: Michael Baudin (INRIA - Digiteo)

Author of R adaptation: Sebastien Bihorel (<sb.pmlab@gmail.com>)

Description

The functions assign content to various elements of a simplex object:

`optimsimplex.setall` Set all the coordinates and the function values of all the vertices.

`optimsimplex.setallfv` Set all the function values of all the vertices.

`optimsimplex.setallx` Set all the coordinates of all the vertices.

`optimsimplex.setfv` Set the function value at a given index.

`optimsimplex.setn` Set the dimension of the space of the simplex.

`optimsimplex.setnbve` Set the number of vertices of the simplex.

`optimsimplex.setve` Set the coordinates of the vertex and the function values at a given index in the current simplex.

`optimsimplex.setx` Set the coordinates of the vertex at a given index in the current simplex.

Usage

```
optimsimplex.setall(this = NULL, simplex = NULL)
optimsimplex.setallfv(this = NULL, fv = NULL)
optimsimplex.setallx(this = NULL, x = NULL)
optimsimplex.setfv(this = NULL, ive = NULL, fv = NULL)
optimsimplex.setn(this = NULL, n = NULL)
optimsimplex.setnbve(this = NULL, nbve = NULL)
optimsimplex.setve(this = NULL, ive = NULL, fv = NULL, x = NULL)
optimsimplex.setx(this = NULL, ive = NULL, x = NULL)
```

Arguments

<code>this</code>	A simplex object.
<code>simplex</code>	The simplex to set. It is expected to be a <code>nbve x n+1</code> matrix where <code>n</code> is the dimension of the space, <code>nbve</code> is the number of vertices and with the following content: <ul style="list-style-type: none"> <code>simplex[k,1]</code> is the function value of the vertex <code>k</code>, with <code>k = 1</code> to <code>nbve</code>, <code>simplex[k,2:(n+1)]</code> is the coordinates of the vertex <code>k</code>, with <code>k = 1</code> to <code>nbve</code>.
<code>fv</code>	A row vector of function values; <code>fv[k]</code> is expected to be the function value for the vertex <code>k</code> , with <code>k = 1</code> to <code>nbve</code> . For <code>optimsimplex.setfv</code> , <code>fv</code> is expected to be a numerical scalar.
<code>x</code>	The <code>nbve x n</code> matrix of vertice coordinates; the vertex is expected to be stored in <code>x[k,1:n]</code> , with <code>k = 1</code> to <code>nbve</code> . For <code>optimsimplex.setve</code> and <code>optimsimplex.setx</code> , <code>x</code> is expected to be a row matrix.
<code>ive</code>	Vertex index.
<code>n</code>	The dimension of the space of the simplex.
<code>nbve</code>	The number of vertices of the simplex.

Value

Return a updated simplex object `this`.

Author(s)

Author of Scilab `optimsimplex` module: Michael Baudin (INRIA - Digiteo)

Author of R adaptation: Sebastien Bihorel (<sb.pmlab@gmail.com>)

See Also

[optimsimplex](#)

Simplex gradient *Simplex Gradient*

Description

`optimsimplex.gradientfv` determines the simplex gradient of the function which is computed by the secondary functions `optimsimplex.gradcenter` and `optimsimplex.gradforward`.

Usage

```
optimsimplex.gradientfv(this = NULL, fun = NULL, method = "forward",
                        data = NULL)
optimsimplex.gradcenter(this = NULL, fun = NULL, data = NULL)
optimsimplex.gradforward(this = NULL)
```

Arguments

<code>this</code>	An simplex object
<code>fun</code>	The function to compute at vertices. The function is expected to have the following input and output arguments:

```
myfunction <- function(x, this){
  ...
  return(list(f=f,this=this))
}
```

where `x` is a row vector and `this` a user-defined data, i.e. the data argument.

<code>method</code>	The method used to compute the simplex gradient. Two methods are available: 'forward' and 'centered'. The 'forward' method uses the current simplex to compute the gradient (using <code>optimsimplex.dirmat</code> and <code>optimsimplex.deltafv</code>). The 'centered' method creates an intermediate simplex and computes the average.
---------------------	--

data A user-defined data passed to the function. If data is provided, it is passed to the callback function both as an input and output argument. `data` may be used if the function uses some additional parameters. It is returned as an output parameter because the function may modify the data while computing the function value. This feature may be used, for example, to count the number of times that the function has been called.

Value

`optimsimplex.gradientfv` returns a list with the following elements:

g A column vector of function gradient (with length `this$n`).

data The updated user-defined data.

`optimsimplex.gradcenter` returns a list with the following elements:

g A column vector of function gradient (with length `this$n`).

data The updated user-defined data.

`optimsimplex.gradforward` returns a column vector of function gradient (with length `this$n`).

Author(s)

Author of Scilab `optimsimplex` module: Michael Baudin (INRIA - Digiteo)

Author of R adaptation: Sebastien Bihorel (<sb.pmlab@gmail.com>)

See Also

[optimsimplex](#), [optimsimplex.dirmat](#), [optimsimplex.deltafv](#)

Index

* **method**

- Function evaluations, [3](#)
- Get functions, [4](#)
- optimsimplex, [6](#)
- optimsimplex.destroy, [9](#)
- optimsimplex.log, [10](#)
- optimsimplex.reflect, [10](#)
- optimsimplex.shrink, [11](#)
- optimsimplex.utils, [12](#)
- osimplex, [14](#)
- Set functions, [16](#)
- Simplex gradient, [17](#)

* **package**

- optimsimplex-package, [2](#)

Function evaluations, [3](#)

Get functions, [4](#)

is.optimsimplex (optimsimplex), [6](#)

is.osimplex (osimplex), [14](#)

is.vertex (osimplex), [14](#)

optimsimplex, [4](#), [5](#), [6](#), [9–12](#), [14](#), [17](#), [18](#)

optimsimplex-package, [2](#)

optimsimplex.center
(optimsimplex.utils), [12](#)

optimsimplex.check
(optimsimplex.utils), [12](#)

optimsimplex.compsomefv (Function
evaluations), [3](#)

optimsimplex.compute fv (Function
evaluations), [3](#)

optimsimplex.deltafv, [18](#)

optimsimplex.deltafv
(optimsimplex.utils), [12](#)

optimsimplex.deltafvmax
(optimsimplex.utils), [12](#)

optimsimplex.destroy, [9](#)

optimsimplex.dirmat, [18](#)

optimsimplex.dirmat
(optimsimplex.utils), [12](#)

optimsimplex.fvmean
(optimsimplex.utils), [12](#)

optimsimplex.fvstdev
(optimsimplex.utils), [12](#)

optimsimplex.fvvariance
(optimsimplex.utils), [12](#)

optimsimplex.getall (Get functions), [4](#)

optimsimplex.getallfv (Get functions), [4](#)

optimsimplex.getallx (Get functions), [4](#)

optimsimplex.getfv (Get functions), [4](#)

optimsimplex.getn (Get functions), [4](#)

optimsimplex.getnbve (Get functions), [4](#)

optimsimplex.getve (Get functions), [4](#)

optimsimplex.getx (Get functions), [4](#)

optimsimplex.gradcenter (Simplex
gradient), [17](#)

optimsimplex.gradforward (Simplex
gradient), [17](#)

optimsimplex.gradientfv (Simplex
gradient), [17](#)

optimsimplex.log, [10](#)

optimsimplex.reflect, [10](#)

optimsimplex.setall (Set functions), [16](#)

optimsimplex.setallfv (Set functions),
[16](#)

optimsimplex.setallx (Set functions), [16](#)

optimsimplex.setfv (Set functions), [16](#)

optimsimplex.setn (Set functions), [16](#)

optimsimplex.setnbve (Set functions), [16](#)

optimsimplex.setve (Set functions), [16](#)

optimsimplex.setx (Set functions), [16](#)

optimsimplex.shrink, [11](#)

optimsimplex.size (optimsimplex.utils),
[12](#)

optimsimplex.sort (optimsimplex.utils),
[12](#)

optimsimplex.utils, [12](#)

`optimsimplex.xbar (optimsimplex.utils),`
[12](#)

`osimplex, 14`

`print.optimsimplex (optimsimplex), 6`

`print.osimplex (osimplex), 14`

`print.vertex (osimplex), 14`

Set functions, [16](#)

Simplex gradient, [17](#)

`vertex (osimplex), 14`