

Package: parade (via r-universe)

August 25, 2024

Type Package

Title Pen's Income Parades

Version 0.1

Date 2019-07-19

Author Marek Hlavac <mhlavac@alumni.princeton.edu>

Maintainer Marek Hlavac <mhlavac@alumni.princeton.edu>

Description Tool for producing Pen's parade graphs, useful for visualizing inequalities in income, wages or other variables, as proposed by Pen (1971, ISBN: 978-0140212594). Income or another economic variable is captured by the vertical axis, while the population is arranged in ascending order of income along the horizontal axis. Pen's income parades provide an easy-to-interpret visualization of economic inequalities.

License GPL (>= 2)

Imports methods, stats

LazyData yes

Collate 'parade-internal.R' 'parade.R'

NeedsCompilation no

Repository CRAN

Date/Publication 2019-07-23 09:40:05 UTC

Contents

chicago	2
parade	3

Index	5
--------------	----------

 chicago

Labor market and demographic data for employed Hispanic workers in metropolitan Chicago

Description

Data from a 2013 sample of employed Hispanic workers in metropolitan Chicago. It is a subset of the 2013 Current Population Survey (CPS) Outgoing Rotation Groups (ORG) data set provided by the Center for Economic and Policy Research in Washington, DC (CEPR, 2014).

Usage

```
data("chicago")
```

Format

A data frame containing 712 observations on 9 variables. The 9 variables contain labor market and demographic information on a sample of employed Hispanic workers in the Chicago metropolitan area.

[, 1]	age	the worker's age, expressed in years
[, 2]	female	an indicator for female gender
[, 3]	foreign.born	an indicator for foreign-born status
[, 4]	LTHS	an indicator for having completed less than a high school (LTHS) education
[, 5]	high.school	an indicator for having completed a high school education
[, 6]	some.college	an indicator for having completed some college education
[, 7]	college	an indicator for having completed a college education
[, 8]	advanced.degree	an indicator for having completed an advanced degree
[, 9]	ln.real.wage	the natural logarithm of the worker's real wage (in 2013 U.S. dollars)

Source

Center for Economic and Policy Research (CEPR). 2014. CPS ORG Uniform Extracts, Version 1.9 . Washington, DC.

Examples

```
data("chicago")
summary(chicago)
```

parade

Pen's Income Parades

Description

parade produces Pen's parade graphs, useful for visualizing inequalities in income, wages or other variables. They were first proposed by Jan Pen in his well-known story of the "parade of dwarfs and a few giants" (Pen, 1971). In this story, income is captured by the vertical axis, while the population is arranged in ascending order of income ("height") along the horizontal axis. As such, Pen's income parades provide an easy-to-interpret visualization of economic inequalities (Cowell, 2000).

Usage

```
parade(height, line.fun = NULL, line.col = "red", line.lty = 1, line.lwd = 2, ...)
```

Arguments

height	a vector of numerical values (e.g., incomes, wages) describing the vertical bars which make up the plot.
line.fun	a function whose result, when applied to the data in height, will determine the position of the horizontal line. If NULL, the horizontal line will occur at the value of the arithmetic mean of the height data.
line.col	a specification for the horizontal line color. This can be a character string giving the color name (e.g., "blue"). Colors can also be specified in terms of their RGB components with a string of the form "#RRGGBB", in which RR, GG and BB correspond to two hexadecimal digits.
line.lty	the horizontal line type. It can be specified as an integer (0=blank, 1=solid (default), 2=dashed, 3=dotted, 4=dotdash, 5=longdash, 6=twodash) or as one of the character strings "blank", "solid", "dashed", "dotted", "dotdash", "longdash", or "twodash", where "blank" uses 'invisible lines' (i.e., does not draw them).
line.lwd	the horizontal line widths (a positive number).
...	additional (e.g., graphical) arguments that will be passed on to the barplot function.

Note:

No horizontal line will be drawn if any of the arguments `line.col`, `line.lty` or `line.lwd` are set to NULL.

Please cite as:

Hlavac, Marek (2019). parade: Pen's Income Parades in R.
R package version 0.1. <https://CRAN.R-project.org/package=parade>

Author(s)

Marek Hlavac < mhlavac at alumni.princeton.edu >
Research Fellow, Central European Labour Studies Institute (CELSI), Bratislava, Slovakia

References

Cowell, Frank A. (2000). Measurement of Inequality. In: Atkinson, Anthony B. and Francois Bourguignon, *Handbook of Income Distribution*. North Holland, 87-166.
Pen, Jan. (1971). *Income Distribution*. Harmondsworth: Allen Lane.

Examples

```
# load data set of Hispanic workers in Chicago
data("chicago")

# generate real wages from their logged versions
chicago$real.wage <- exp(chicago$ln.real.wage)

# simple Pen's parade with a blue, dashed, thin horizontal line at the mean
parade(chicago$real.wage, line.col = "blue", line.lwd = 1, line.lty = "dashed")
```

Index

- * **datasets**
 - chicago, [2](#)
 - * **income**
 - parade, [3](#)
 - * **inequality**
 - parade, [3](#)
 - * **visualization**
 - parade, [3](#)
- chicago, [2](#)
- parade, [3](#)