Package: pcFactorStan (via r-universe)

October 29, 2026

Title Stan Models for the Paired Comparison Factor Model

Version 1.5.4

Description Provides convenience functions and pre-programmed Stan models related to the paired comparison factor model. Its purpose is to make fitting paired comparison data using Stan easy. This package is described in Pritikin (2020) <doi:10.1016/j.heliyon.2020.e04821>.

License GPL (>= 3)

URL https://github.com/jpritikin/pcFactorStan

BugReports https://github.com/jpritikin/pcFactorStan/issues

Depends R (>= 3.4), methods, Rcpp (>= 0.12.0)

Imports rstan (>= 2.26.0), rstantools (>= 2.1.1), reshape2, mvtnorm, igraph, loo, lifecycle

Suggests knitr, rmarkdown, testthat, shiny, ggplot2, covr, qgraph, Matrix

LinkingTo Rcpp (>= 0.12.0), RcppEigen (>= 0.3.3.3.0), RcppParallel (>= 5.0.2), StanHeaders (>= 2.26.0), BH (>= 1.66.0), rstan (>= 2.26.0)

VignetteBuilder knitr

RdMacros lifecycle

Encoding UTF-8

LazyData true

NeedsCompilation yes

RoxygenNote 7.2.3

SystemRequirements GNU make

Author Joshua N. Pritikin [aut, cre] (<https://orcid.org/0000-0002-9862-5484>), Daniel C. Furr [ctb], Trustees of Columbia University [cph]

Maintainer Joshua N. Pritikin <jpritikin@pobox.com>

Config/pak/sysreqs make

Repository https://cran.r-universe.dev

Date/Publication 2023-09-13 19:30:22 UTC

RemoteUrl https://github.com/cran/pcFactorStan

RemoteRef HEAD

RemoteSha ceeed125c343d51ddff158f721eddb3034e243ba

Contents

pcFactorStan-package . . . 2
calibrateItems . . . 3
cmp_probs . . . 4
filterGraph . . . 6
findModel . . . 7
generateCovItems . . . 8
generateFactorItems . . . 9
generateItem . . . 11
generateSingleFactorItems . . . 12
itemModelExplorer . . . 13
normalizeData . . . 14
outlierTable . . . 14
parDistributionCustom . . . 15
parInterval . . . 16
pcStan . . . 17
phyActFlowPropensity . . . 18
prepCleanData . . . 19
prepData . . . 20
prepFactorModel . . . 20
prepSingleFactorModel . . . 21
responseCurve . . . 22
roundRobinGraph . . . 23
toLoo . . . 24
twoLevelGraph . . . 25
unfactor . . . 26
withoutIndex . . . 26

Index **28**

`pcFactorStan-package` *Stan Models for the Pairwise Comparison Factor Model*

Description

pcFactorStan makes it easy to fit the paired comparison factor model using **rstan**.

A user will generally want to use `prepData` and `pcStan` to fit a model.

The package includes a number of Stan models (see `findModel` for a list) and an example dataset `phyActFlowPropensity`.

After gaining some experience with the pre-defined models, we anticipate that users may write their own Stan models and fit them with `stan`, for which `pcStan` is a wrapper.

`calibrateItems` *Determine the optimal scale constant for a set of items*

Description

Data are passed through `filterGraph` and `normalizeData`. Then the 'unidim_adapt' model is fit to each item individually. A larger `varCorrection` will obtain a more accurate `scale`, but is also more likely to produce an intractable model. A good compromise is between 5.0 and 9.0.

Usage

```
calibrateItems(
  df,
  iter = 2000L,
  chains = 4L,
  varCorrection = 5,
  maxAttempts = 5L,
  ...
)
```

Arguments

`df`	a data frame with pairs of vertices given in columns `pa1` and `pa2`, and item response data in other columns
`iter`	A positive integer specifying the number of iterations for each chain (including warmup).
`chains`	A positive integer specifying the number of Markov chains.
`varCorrection`	A correction factor greater than or equal to 1.0
`maxAttempts`	How many times to try re-running a model with more iterations.
`...`	Additional options passed to `stan`.

Value

A data.frame (one row per item) with the following columns:

item Name of the item

iter Number of iterations per chain

divergent Number of divergent transitions observed after warmup

treedepth Number of times the treedepth was exceeded

low_bfmi Number of chains with low E-BFMI

n_eff Minimum effective number of samples across all parameters

Rhat Maximum Rhat across all parameters

scale Median marginal posterior of `scale`

thetaVar Median variance of theta (latent scores)

References

Vehtari, A., Gelman, A., Simpson, D., Carpenter, B., & Bürkner, P. C. (2019). Rank-normalization, folding, and localization: An improved $\widehat{R}$ for assessing convergence of MCMC. arXiv preprint arXiv:1903.08008.

See Also

`check_hmc_diagnostics`

Examples

```
result <- calibrateItems(phyActFlowPropensity)  # takes more than 5 seconds
print(result)
```

`cmp_probs` *Item response function for pairwise comparisons*

Description

Use `itemModelExplorer` to explore the item model. In this **shiny** app, the *discrimination* parameter does what is customary in item response models. However, it is not difficult to show that discrimination is a function of thresholds and scale. That is, discrimination is not an independent parameter. In paired comparison models, discrimination and measurement error are confounded.

Usage

```
cmp_probs(alpha, scale, pa1, pa2, thRaw)
```

Arguments

alpha	discrimination parameter
scale	scale correction factor
pa1	first latent worth
pa2	second latent worth
thRaw	vector of positive thresholds

Details

The thresholds are parameterized as the difference from the previous threshold. For example, thresholds c(0.5, 0.6) are not at the same location but are at locations c(0.5, 1.1). Thresholds are symmetric. If there is one threshold then the model admits three possible response outcomes (e.g. *win*, *tie*, and *lose*). Responses are always stored centered with zero representing a tie. Therefore, it is necessary to add one plus the number of thresholds to response data to index into the vector returned by `cmp_probs`. For example, if our response data is (-1, 0, 1) and has one threshold then we would add 2 (1 + 1 threshold) to obtain the indices (1, 2, 3).

Value

A vector of probabilities of observing each outcome

Math

Up until version 1.4, the item response model was based on the partial credit model (Masters, 1982). In version 1.5, the graded response model is used instead (Samejima, 1969). The advantage of the graded response model is greater independence among threshold parameters and the ability to compute only the parts of the model that are actually needed given particular observations. The curves predicted by both models are similar and should obtain similar results in data analyses.

References

Samejima, F. (1969). Estimation of latent ability using a response pattern of graded scores. *Psychometrika Monograph Supplement, 34*(4, Pt. 2), 100.

Masters, G. N. (1982). A Rasch model for partial credit scoring. *Psychometrika, 47*, 149–174. doi: 10.1007/BF02296272

Examples

```
# Returns probabilities of
# c(pa1 > pa2, pa1 = pa2, pa1 < pa2)
cmp_probs(1,1,0,1,.8)

# Add another threshold for a symmtric 3 point Likert scale
cmp_probs(1,1,0,.5,c(.8, 1.6))
```

`filterGraph` *Filter graph to remove vertices that are not well connected*

Description

Vertices not part of the largest connected component are excluded (Hopcroft & Tarjan, 1973). Vertices that have fewer than `minAny` edges and are not connected to `minDifferent` or more different vertices are excluded. For example, vertex 'a' connected to vertices 'b' and 'c' will be include so long as these vertices are part of the largest connected component.

Usage

```
filterGraph(df, minAny = 11L, minDifferent = 2L)
```

Arguments

`df`	a data frame with pairs of vertices given in columns `pa1` and `pa2`, and item response data in other columns
`minAny`	the minimum number of edges
`minDifferent`	the minimum number of vertices

Details

Given that `minDifferent` defaults to 2, if activity A was compared to at least two other activities, B and C, then A is retained. The rationale is that, although little may be learned about A, there may be a transitive relationship, such as $B < A < C$, by which the model can infer that $B < C$. Therefore, per-activity sample size is less of a concern when the graph is densely connected.

A young novice asked the wise master, "Why is 11 the default `minAny` instead of 10?" The master answered, "Because 11 is a prime number."

Value

The same graph excluding some vertices.

References

Hopcroft, J., & Tarjan, R. (1973). Algorithm 447: Efficient algorithms for graph manipulation. *Communications of the ACM, 16*(6), 372–378. doi:10.1145/362248.362272

Examples

```
df <- filterGraph(phyActFlowPropensity[,c(paste0('pa',1:2),'predict')])
head(df)
```

`findModel` *Given a model name, return stanmodel object*

Description

This is a convenience function to help you look up the path to an appropriate model for your data.

Usage

```
findModel(model = NULL)
```

Arguments

`model`	the name of a model

Details

There are essentially three models: 'unidim', 'covariance', and 'factor'. 'unidim' analyzes a single item. 'covariance' is suitable for two or more items. Once you have vetted your items with the 'unidim' and 'covariance' models, then you can try the 'factor' model. For each model, there is a '_ll' variation. This model includes row-wise log likelihoods suitable for feeding to **loo** for efficient approximate leave-one-out cross-validation (Vehtari, Gelman, & Gabry, 2017).

There is also a special model 'unidim_adapt'. Except for this model, the other models require a scaling constant. To find an appropriate scaling constant, we recommend fitting 'unidim_adapt' to each item separately and then take the median of median point estimates to set the scale. 'unidim_adapt' requires a varCorrection constant. In general, a varCorrection of 2.0 or 3.0 should provide optimal results.

Since version 1.1.0, the factor model permits an arbitrary number of factors and arbitrary factor-to-item paths. If you were using the old factor model, you'll need to update your code to call prepSingleFactorModel. Arbitrary factor model structure should be specified using prepFactorModel. The single factor model is called 'factor1' and the general factor model is called 'factor'.

Value

An instance of S4 class `stanmodel` that can be passed to `pcStan`.

References

Vehtari A, Gelman A, Gabry J (2017). "Practical Bayesian model evaluation using leave-one-out cross-validation and WAIC." *Statistics and Computing, 27*, 1413-1432. doi: 10.1007/s11222-016-9696-4

See Also

`toLoo`

Examples

```
findModel()  # shows available models
findModel('unidim')
```

`generateCovItems` *Generate paired comparison data with random correlations between items*

Description

If you need access to the correlation matrix used to generate the absolute latent scores then you will need to generate them yourself. This is not difficult. See how in the example.

Usage

```
generateCovItems(df, numItems, th = 0.5, name, ..., scale = 1, alpha = 1)
```

Arguments

`df`	a data frame with pairs of vertices given in columns `pa1` and `pa2`, and item response data in other columns
`numItems`	how many items to create
`th`	a vector of thresholds
`name`	a vector of item names
`...`	Not used. Forces remaining arguments to be specified by name.
`scale`	a vector of scaling constants
`alpha`	a vector of item discriminations

Value

The given data.frame `df` with additional columns for each item. In addition, you can obtain the correlation matrix used to generate the latent worths from `attr(df, "cor")` and and latent worths from `attr(df, "worth")`.

Response model

See cmp_probs for details.

See Also

Other item generators: `generateFactorItems()`, `generateItem()`, `generateSingleFactorItems()`

Examples

```
library(mvtnorm)
df <- twoLevelGraph(letters[1:10], 100)
df <- generateCovItems(df, 3)

# generateCovItems essentially does the same thing as:
numItems <- 3
palist <- letters[1:10]
trueCor <- cov2cor(rWishart(1, numItems, diag(numItems))[,,1])
theta <- rmvnorm(length(palist), sigma=trueCor)
dimnames(theta) <- list(palist, paste0('i', 3 + 1:numItems))
df <- generateItem(df, theta)
attr(df, "cor")
```

---

generateFactorItems *Generate paired comparison data for a factor model*

Description

Generate paired comparison data given a mapping from factors to items.

Usage

```
generateFactorItems(
  df,
  path,
  factorScalePrior = deprecated(),
  th = 0.5,
  name,
  ...,
  scale = 1,
  alpha = 1
)
```

Arguments

df	a data frame with pairs of vertices given in columns pa1 and pa2, and item response data in other columns
path	a named list of item names
factorScalePrior	a named numeric vector (deprecated)
th	a vector of thresholds
name	a vector of item names
...	Not used. Forces remaining arguments to be specified by name.
scale	a vector of scaling constants
alpha	a vector of item discriminations

Details

For each factor, you need to specify its name and which items it predicts. The connections from factors to items is specified by the 'path' argument. Both factors and items are specified by name (not index).

Path proportions (factor-to-item loadings) are sampled from a logistic transformed normal distribution with scale 0.6. A few attempts are made to resample path proportions if any of the item proportions sum to more than 1.0. An exception will be raised if repeated attempts fail to produce viable proportion assignments.

Value

The given data.frame `df` with additional columns for each item. In addition, you can obtain path proportions (factor-to-item loadings) from `attr(df, "pathProp")`, the factor scores from `attr(df, "score")`, and latent worths from `attr(df, "worth")`.

Response model

See cmp_probs for details.

Backward incompatibility

The function generateFactorItems was renamed to `generateSingleFactorItems` (version 1.1.0) to make space for a more flexible factor model with an arbitrary number of factors and arbitrary factor-to-item loading pattern. If you don't need this flexibility, you can call the old function generateSingleFactorItems.

References

Silver, D., Hubert, T., Schrittwieser, J., Antonoglou, I., Lai, M., Guez, A., ... & Lillicrap, T. (2018). A general reinforcement learning algorithm that masters chess, shogi, and Go through self-play. *Science, 362*(6419), 1140-1144.

See Also

To fit a factor model: prepFactorModel

Other item generators: `generateCovItems()`, `generateItem()`, `generateSingleFactorItems()`

Examples

```
df <- twoLevelGraph(letters[1:10], 100)
df <- generateFactorItems(df, list(f1=paste0('i',1:4),
                          f2=paste0('i',2:4)),
                      c(f1=0.9, f2=0.5))
head(df)
attr(df, "pathProp")
attr(df, "score")
attr(df, "worth")
```

`generateItem` *Generate paired comparison data for one or more items given absolute latent scores*

Description

To add a single item, `theta` should be a vector of latent scores. To add multiple items at a time, `theta` should be a matrix with one item in each column. Item names can be given as the colnames of `theta`.

The interpretation of `theta` depends on the context where the data were generated. For example, in chess, `theta` represents unobserved chess skill that is partially revealed by match outcomes.

The graph can be regarded as undirected, but data are generated relative to the order of vertices within each row. Vertices do not commute. For example, a `-1` for vertices 'a' and 'b' is the same as `1` for vertices 'b' and 'a'.

Usage

```
generateItem(df, theta, th = 0.5, name, ..., scale = 1, alpha = 1)
```

Arguments

`df`	a data frame with pairs of vertices given in columns `pa1` and `pa2`, and item response data in other columns
`theta`	a vector or matrix of absolute latent scores. See details below.
`th`	a vector of thresholds
`name`	a vector of item names
`...`	Not used. Forces remaining arguments to be specified by name.
`scale`	a vector of scaling constants
`alpha`	a vector of item discriminations

Value

The given data.frame `df` with additional columns for each item.

Response model

See cmp_probs for details.

See Also

Other item generators: `generateCovItems()`, `generateFactorItems()`, `generateSingleFactorItems()`

Examples

```
df <- roundRobinGraph(letters[1:5], 40)
df <- generateItem(df)
```

`generateSingleFactorItems` *Generate paired comparison data with a common factor that accounts for some proportion of the variance*

Description

Imagine that there are people that play in tournaments of more than one board game. For example, the computer player AlphaZero (Silver et al. 2018) has trained to play chess, shogi, and Go. We can take the tournament match outcome data and find rankings among the players for each of these games. We may also suspect that there is a latent board game skill that accounts for some proportion of the variance in the per-board game rankings.

Usage

```
generateSingleFactorItems(df, prop, th = 0.5, name, ..., scale = 1, alpha = 1)
```

Arguments

`df`	a data frame with pairs of vertices given in columns `pa1` and `pa2`, and item response data in other columns
`prop`	the number of items or a vector of signed proportions of variance
`th`	a vector of thresholds
`name`	a vector of item names
`...`	Not used. Forces remaining arguments to be specified by name.
`scale`	a vector of scaling constants
`alpha`	a vector of item discriminations

Value

The given data.frame `df` with additional columns for each item.

Response model

See cmp_probs for details.

Backward incompatibility

The function generateFactorItems was renamed to `generateSingleFactorItems` (version 1.1.0) to make space for a more flexible factor model with an arbitrary number of factors and arbitrary factor-to-item loading pattern. If you don't need this flexibility, you can call the old function generateSingleFactorItems.

References

Silver, D., Hubert, T., Schrittwieser, J., Antonoglou, I., Lai, M., Guez, A., ... & Lillicrap, T. (2018). A general reinforcement learning algorithm that masters chess, shogi, and Go through self-play. *Science, 362*(6419), 1140-1144.

See Also

Other item generators: `generateCovItems()`, `generateFactorItems()`, `generateItem()`

Examples

```
df <- twoLevelGraph(letters[1:10], 100)
df <- generateSingleFactorItems(df, 3)
```

`itemModelExplorer` *A Shiny app to experiment with the item response model*

Description

When data `dl` and fitted model `fit` are provided, the item parameters associated with `item` are loaded for inspection.

Usage

```
itemModelExplorer(dl = NULL, fit = NULL, item = NULL)
```

Arguments

`dl`	a data list prepared by `prepData`
`fit`	a `stanfit` object
`item`	name of the item to visualize

Response model

See cmp_probs for details.

Examples

```
itemModelExplorer()  # will launch a browser in RStudio
```

normalizeData *Normalize data according to a canonical order*

Description

Pairwise comparison data are not commutative. Alice beating Bob in chess is equivalent to Bob losing to Alice. `normalizeData` assigns an arbitrary order to all vertices and reorders vertices column-wise to match, flipping signs as needed.

Usage

```
normalizeData(df, ..., .palist = NULL, .sortRows = TRUE)
```

Arguments

`df`	a data frame with pairs of vertices given in columns `pa1` and `pa2`, and item response data in other columns
`...`	Not used. Forces remaining arguments to be specified by name.
`.palist`	a character vector giving an order to use instead of the default
`.sortRows`	logical. Using the same order, sort rows in addition to vertex pairs.

Examples

```
df <- data.frame(pa1=NA, pa2=NA, i1=c(1, -1))
df[1,paste0('pa',1:2)] <- c('a','b')
df[2,paste0('pa',1:2)] <- c('b','a')
normalizeData(df)
```

outlierTable *List observations with Pareto values larger than a given threshold*

Description

The function `prepCleanData` compresses observations into the most efficient format for evaluation by Stan. This function maps indices of observations back to the actual observations, filtering by the largest Pareto k values. It is assumed that `data` was processed by `normalizeData` or is in the same order as seen by `prepCleanData`.

Usage

```
outlierTable(data, x, threshold = 0.5)
```

Arguments

data	a data list prepared for processing by Stan
x	An object created by loo
threshold	threshold is the minimum k value to include

Value

A data.frame (one row per observation) with the following columns:

pa1 Name of object 1

pa2 Name of object 2

item Name of item

pick Observed response

k Associated Pareto k value

See Also

toLoo, pareto_k_ids

Examples

```
palist <- letters[1:10]
df <- twoLevelGraph(palist, 300)
theta <- rnorm(length(palist))
names(theta) <- palist
df <- generateItem(df, theta, th=rep(0.5, 4))

df <- filterGraph(df)
df <- normalizeData(df)
dl <- prepCleanData(df)
dl$scale <- 1.5


m1 <- pcStan("unidim_ll", dl)

loo1 <- toLoo(m1, cores=1)
ot <- outlierTable(dl, loo1, threshold=.2)
df[df$pa1==ot[1,'pa1'] & df$pa2==ot[1,'pa2'], 'i1']
```

---

parDistributionCustom *Produce data suitable for plotting parameter distributions*

Description

Produce data suitable for plotting parameter distributions

Usage

```
parDistributionCustom(
  fit,
  pars,
  nameVec,
  label = withoutIndex(pars[1]),
  samples = 500
)

parDistributionFor(fit, pi, samples = 500)
```

Arguments

fit	a stanfit object
pars	a vector of parameter names
nameVec	a vector of explanatory parameters names
label	column name for nameVec
samples	number of posterior samples
pi	a data.frame returned by parInterval

Value

A data.frame with the following columns:

sample Sample index

label A name from *nameVec*

value A single sample of the associated parameter

See Also

Other data extractor: parInterval(), responseCurve()

Examples

```
vignette('manual', 'pcFactorStan')
```

---

parInterval *Produce data suitable for plotting parameter estimates*

Description

Produce data suitable for plotting parameter estimates

Usage

```
parInterval(fit, pars, nameVec, label = withoutIndex(pars[1]), width = 0.8)
```

Arguments

fit	a stanfit object
pars	a vector of parameter names
nameVec	a vector of explanatory parameters names
label	column name for nameVec
width	a width in probability units for the uncertainty interval

Value

A data.frame with the following columns:

L Lower quantile

M Median

U Upper quantile

label *nameVec*

See Also

Other data extractor: parDistributionCustom(), responseCurve()

Examples

```
vignette('manual', 'pcFactorStan')
```

---

pcStan *Fit a paired comparison Stan model*

Description

Uses findModel to find the appropriate model and then invokes sampling.

Usage

```
pcStan(model, data, ...)
```

Arguments

model	the name of a model
data	a data list prepared for processing by Stan
...	Additional options passed to stan.

Value

A stanfit object.

An object of S4 class stanfit.

See Also

See sampling, for which this function is a wrapper, for additional options. See prepData to create a suitable data list. See print.stanfit for ways of getting tables summarizing parameter posteriors.

calibrateItems, outlierTable

Examples

```
dl <- prepData(phyActFlowPropensity[,c(1,2,3)])
dl$varCorrection <- 5.0
pcStan('unidim_adapt', data=dl)  # takes more than 5 seconds
```

---

phyActFlowPropensity *Physical activity flow propensity*

Description

A dataset containing paired comparisons of 87 physical activities on 16 flow-related facets. Participants submitted two activities using free-form input. These activities were substitute into item templates. For example, the 'predict' item asked, "How predictable is the action?" with response options:

- A1 is much more predictable than A2.
- A1 is somewhat more predictable than A2.
- Both offer roughly equal predictability.
- A2 is somewhat more predictable than A1.
- A2 is much more predictable than A1.

Most items were adapted from Jackson & Eklund (2002).

Usage

```
phyActFlowPropensity
```

Format

A data.frame with one row per activity comparison and items in the columns. All item responses are between -2 and 2. Zero indicates that both activities were judged equal on the trait.

Source

A manuscript fully describing the study is in preparation. Data are made available under the Community Data License Agreement - Sharing - Version 1.0

References

Jackson, S. A., & Eklund, R. C. (2002). Assessing flow in physical activity: The flow state scale-2 and dispositional flow scale-2. *Journal of Sport and Exercise Psychology, 24*(2), 133-150. doi:10.1123/jsep.24.2.133

prepCleanData *Transforms data into a form tailored for efficient evaluation by Stan*

Description

Vertex names, if not already factors, are converted to factors. The number of thresholds per item is determined by the largest absolute response value. Missing responses are filtered out. Responses on the same pair of vertices on the same item are grouped together. Within a vertex pair and item, responses are ordered from negative to positive.

Usage

```
prepCleanData(df)
```

Arguments

df	a data frame with pairs of vertices given in columns pa1 and pa2, and item response data in other columns

Details

Note: Reordering of responses is likely unless something like normalizeData has been used with .sortRows=TRUE.

Value

a data list suitable for passing as the data argument to pcStan or stan

See Also

Other data preppers: prepData(), prepFactorModel(), prepSingleFactorModel()

Examples

```
df <- prepCleanData(phyActFlowPropensity)
str(df)
```

prepData *Transforms data into a form tailored for efficient evaluation by Stan*

Description

Invokes `filterGraph` and `normalizeData`. Vertex names, if not already factors, are converted to factors. The number of thresholds per item is determined by the largest absolute response value. Missing responses are filtered out. Responses on the same pair of vertices on the same item are grouped together. Within a vertex pair and item, responses are ordered from negative to positive.

Usage

```
prepData(df)
```

Arguments

`df`	a data frame with pairs of vertices given in columns `pa1` and `pa2`, and item response data in other columns

Value

a data list suitable for passing as the `data` argument to `pcStan` or `stan`

See Also

Other data preppers: `prepCleanData()`, `prepFactorModel()`, `prepSingleFactorModel()`

Examples

```
df <- prepData(phyActFlowPropensity)
str(df)
```

prepFactorModel *Specify a factor model*

Description

Specify a factor model with an arbitrary number of factors and arbitrary factor-to-item structure.

Usage

```
prepFactorModel(
  data,
  path,
  factorScalePrior = deprecated(),
  psiScalePrior = deprecated()
)
```

Arguments

data	a data list prepared for processing by Stan
path	a named list of item names
factorScalePrior	a named numeric vector (deprecated)
psiScalePrior	matrix of priors for factor correlations (deprecated)

Details

For each factor, you need to specify its name and which items it predicts. The connections from factors to items is specified by the 'path' argument. Both factors and items are specified by name (not index).

Value

a data list suitable for passing as the data argument to pcStan or stan

See Also

To simulate data from a factor model: generateFactorItems

Other factor model: prepSingleFactorModel()

Other data preppers: prepCleanData(), prepData(), prepSingleFactorModel()

Examples

```
pa <- phyActFlowPropensity[,setdiff(colnames(phyActFlowPropensity),
                                    c('goal1','feedback1'))]
dl <- prepData(pa)
dl <- prepFactorModel(dl,
                      list(flow=c('complex','skill','predict',
                                  'creative', 'novelty', 'stakes',
                                  'present', 'reward', 'chatter',
                                  'body'),
                           f2=c('waiting','control','evaluated','spont'),
                           rc=c('novelty', 'waiting')))
str(dl)
```

---

prepSingleFactorModel *Specify a single factor model*

Description

Specify a single latent factor with a path to each item.

Usage

```
prepSingleFactorModel(data, factorScalePrior = deprecated())
```

Arguments

data	a data list prepared for processing by Stan
factorScalePrior	a named numeric vector (deprecated)

Value

a data list suitable for passing as the data argument to pcStan or stan

See Also

Other factor model: prepFactorModel()

Other data preppers: prepCleanData(), prepData(), prepFactorModel()

Examples

```
dl <- prepData(phyActFlowPropensity)
dl <- prepSingleFactorModel(dl)
str(dl)
```

---

responseCurve *Produce data suitable for plotting item response curves*

Description

Selects samples random draws from the posterior and evaluates the item response curve on the grid given by seq(from,to,by). All items use the same responseNames. If you have some items with a different number of thresholds or different response names then you can call responseCurve for each item separately and rbind the results together.

Usage

```
responseCurve(
  dl,
  fit,
  responseNames,
  item = dl$nameInfo$item,
  samples = 100,
  from = qnorm(0.1),
  to = -from,
  by = 0.02
)
```

Arguments

dl	a data list prepared by prepData
fit	a stanfit object
responseNames	a vector of labels for the possible responses
item	a vector of item names
samples	number of posterior samples
from	the starting latent difference value
to	the ending latent difference value
by	the grid increment

Value

A data.frame with the following columns:

response Which response

worthDiff Difference in worth

item Which item

sample Which sample

prob Associated probability

responseSample A grouping index for independent item response samples

Response model

See cmp_probs for details.

See Also

Other data extractor: parDistributionCustom(), parInterval()

Examples

```
vignette('manual', 'pcFactorStan')
```

---

roundRobinGraph *Create an edge list with round-robin connectivity*

Description

Create an edge list with round-robin connectivity

Usage

```
roundRobinGraph(name, N)
```

Arguments

name	vector of vertex names
N	number of comparisons

Value

An undirected graph represented as a data frame with each row describing an edge.

See Also

Other graph generators: twoLevelGraph()

Examples

```
roundRobinGraph(letters[1:5], 10)
```

---

toLoo *Compute approximate leave-one-out (LOO) cross-validation for Bayesian models using Pareto smoothed importance sampling (PSIS)*

Description

You must use an '_ll' model variation (see findModel).

Usage

```
toLoo(fit, ...)
```

Arguments

fit	a stanfit object
...	Additional options passed to loo.

Value

a loo object

See Also

outlierTable, loo

Examples

```
palist <- letters[1:10]
df <- twoLevelGraph(palist, 300)
theta <- rnorm(length(palist))
names(theta) <- palist
df <- generateItem(df, theta, th=rep(0.5, 4))

df <- filterGraph(df)
df <- normalizeData(df)
dl <- prepCleanData(df)
dl$scale <- 1.5


m1 <- pcStan("unidim_ll", dl)

loo1 <- toLoo(m1, cores=1)
print(loo1)
```

`twoLevelGraph` *Create an edge list with a random two level connectivity*

Description

Initially, edges are added from the first vertex to all the other vertices. Thereafter, the first vertex is drawn from a Beta(shape1, 1.0) distribution and the second vertex is drawn from a Beta(shape2, 1.0) distribution. The idea is that the edges will tend to connect a small subset of vertices from the top of the tree to leaf vertices. These vertex connections are similar to the pairs that you might observe in an elimination tournament. The selected vertices are sorted so it doesn't matter whether `shape1 > shape2` or `shape1 < shape2`.

Usage

```
twoLevelGraph(name, N, shape1 = 0.8, shape2 = 0.5)
```

Arguments

`name`	vector of vertex names
`N`	number of comparisons
`shape1`	beta distribution parameter for first edge
`shape2`	beta distribution parameter for second edge

Value

An undirected graph represented as a data frame with each row describing an edge.

See Also

Other graph generators: `roundRobinGraph()`

Examples

```
twoLevelGraph(letters[1:5], 20)
```

`unfactor` *Turn a factor back into a vector of integers*

Description

Factors store values as integers and use a 'levels' attribute to map the integers to labels. This function removes the 'factor' class and levels attribute, leaving the vector of integers.

Usage

```
unfactor(f)
```

Arguments

`f`	a factor

Examples

```
f <- factor(letters[1:3])
print(f)
print(unfactor(f))
```

`withoutIndex` *Remove the array indexing from a parameter name*

Description

Remove the array indexing from a parameter name

Usage

```
withoutIndex(name)
```

Arguments

`name`	a parameter name

Value

the name without the square bracket parameter indexing

Examples

```
withoutIndex("foo[1,2]")
```

Index

∗ **data extractor**
  parDistributionCustom, 15
  parInterval, 16
  responseCurve, 22
∗ **data preppers**
  prepCleanData, 19
  prepData, 20
  prepFactorModel, 20
  prepSingleFactorModel, 21
∗ **datasets**
  phyActFlowPropensity, 18
∗ **factor model**
  prepFactorModel, 20
  prepSingleFactorModel, 21
∗ **graph generators**
  roundRobinGraph, 23
  twoLevelGraph, 25
∗ **item generators**
  generateCovItems, 8
  generateFactorItems, 9
  generateItem, 11
  generateSingleFactorItems, 12

calibrateItems, 3, *18*
check_hmc_diagnostics, *4*
cmp_probs, 4, *8*, *10–13*, *23*

filterGraph, *3*, 6, *20*
findModel, *3*, 7, *17*, *24*

generateCovItems, 8, *10, 11*, *13*
generateFactorItems, *8*, 9, *10–13*, *21*
generateItem, *8*, *10*, 11, *13*
generateSingleFactorItems, *8*, *10, 11*, 12, *12*

itemModelExplorer, *4*, 13

loo, *15*, *24*

normalizeData, *3*, 14, *14*, *19, 20*

outlierTable, 14, *18*, *24*

parDistributionCustom, 15, *17*, *23*
parDistributionFor *(*parDistributionCustom*)*, 15
pareto_k_ids, *15*
parInterval, 16, *16*, *23*
pcFactorStan *(*pcFactorStan-package*)*, 2
pcFactorStan-package, 2
pcStan, *3*, *7*, 17, *19–22*
phyActFlowPropensity, *3*, 18
prepCleanData, *14*, 19, *20–22*
prepData, *3*, *13*, *18, 19*, 20, *21–23*
prepFactorModel, *7*, *10*, *19*, 20, *20*, *22*
prepSingleFactorModel, *7*, *19, 20*, 21, *21*
print.stanfit, *18*

responseCurve, *16, 17*, 22
roundRobinGraph, 23, *26*

sampling, *17, 18*
stan, *3*, *17*, *19–22*
stanfit, *13*, *16, 17*, *23, 24*
stanmodel, *7*

toLoo, *7*, *15*, 24
twoLevelGraph, *24*, 25

unfactor, 26

withoutIndex, 26