

# Package: phenoCDM (via r-universe)

September 20, 2024

**Title** Continuous Development Models for Incremental Time-Series Analysis

**Version** 0.1.3

**Date** 2018-05-01

**Author** Bijan Seyednasrollah, Jennifer J. Swenson, Jean-Christophe Domec, James S. Clark

**Maintainer** Bijan Seyednasrollah <[bi.jan.s.nasr@gmail.com](mailto:bi.jan.s.nasr@gmail.com)>

**Description** Using the Bayesian state-space approach, we developed a continuous development model to quantify dynamic incremental changes in the response variable. While the model was originally developed for daily changes in forest green-up, the model can be used to predict any similar process. The CDM can capture both timing and rate of nonlinear processes. Unlike statics methods, which aggregate variations into a single metric, our dynamic model tracks the changing impacts over time. The CDM accommodates nonlinear responses to variation in predictors, which changes throughout development.

**Depends** R (>= 3.3.0)

**Imports** rjags

**License** MIT + file LICENSE

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 6.0.1.9000

**BugReports** <https://github.com/bnasr/phenoCDM/issues>

**Suggests** knitr, rmarkdown

**VignetteBuilder** knitr

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2018-05-02 03:45:15 UTC

## Contents

fitCDM	2
getGibbsSummary	3
phenoSim	4
phenoSimPlot	5
plotPOGibbs	6
plotPost	7
<b>Index</b>	<b>9</b>

---

fitCDM	<i>Fit a CDM Model</i>
--------	------------------------

---

### Description

This function fits a CDM model on the input data as it is described by the phenoSim function.

### Usage

```
fitCDM(x, z, connect = NULL, nGibbs = 1000, nBurnin = 1, n.adapt = 100,
       n.chains = 4, quiet = FALSE, calcLatentGibbs = FALSE, trend = +1)
```

### Arguments

x	Matrix of predictors [N x p].
z	Vector of response values [N x 1].
connect	The connectivity matrix for the z vector [n x 2]. Each row contains the last and next elements of the time-series. NA values indicate not connected.
nGibbs	Number of MCMC iterations
nBurnin	Number of burn-in iterations.
n.adapt	Number of iterations for adaptive sampling
n.chains	Number of MCMC chains
quiet	logical value indicating whether to report the progress
calcLatentGibbs	logical value indicating whether to calculate the latent states
trend	time-series expected trend as -1:decreasing, +1:increasing, 0: not constrained

### Examples

```
#Summarize CDM Model Output

ssSim <- phenoSim(nSites = 2, #number of sites
                 nTSet = 30, #number of Time steps
                 beta = c(1, 2), #beta coefficients
                 sig = .01, #process error)
```

```

        tau = .1, #observation error
        plotFlag = TRUE, #whether plot the data or not
        miss = 0.05, #fraction of missing data
        ymax = c(6, 3) #maximum of saturation trajectory
    )

    ssOut <- fitCDM(x = ssSim$x, #predictors
                  nGibbs = 200,
                  nBurnin = 100,
                  z = ssSim$z, #response
                  connect = ssSim$connect, #connectivity of time data
                  quiet=TRUE)

    summ <- getGibbsSummary(ssOut, burnin = 100, sigmaPerSeason = FALSE)

    colMeans(summ$ymax)
    colMeans(summ$betas)
    colMeans(summ$tau)
    colMeans(summ$sigma)

```

---

getGibbsSummary

*Summarize Output of the CDM Model*


---

## Description

This function return a summary of the output from the Gibbs-Sampling of the CDM model.

## Usage

```

getGibbsSummary(ssOut, burnin = NULL, colNames = NULL,
                sigmaPerSeason = TRUE)

```

## Arguments

ssOut	CDM output list.
burnin	Number of burnin iterations .
colNames	vector of characters includes names of each variable in the output.
sigmaPerSeason	logical value indicating whether each site/season has a separate process error

## Examples

```

#Summarize CDM Model Ouput

ssSim <- phenoSim(nSites = 2, #number of sites
                 nTSet = 30, #number of Time steps
                 beta = c(1, 2), #beta coefficients
                 sig = .01, #process error
                 tau = .1, #observation error

```

```

        plotFlag = TRUE, #whether plot the data or not
        miss = 0.05, #fraction of missing data
        ymax = c(6, 3) #maximum of saturation trajectory
    )

    ssOut <- fitCDM(x = ssSim$x, #predictors
                  nGibbs = 200,
                  nBurnin = 100,
                  z = ssSim$z, #response
                  connect = ssSim$connect, #connectivity of time data
                  quiet=TRUE)

    summ <- getGibbsSummary(ssOut, burnin = 100, sigmaPerSeason = FALSE)

    colMeans(summ$ymax)
    colMeans(summ$betas)
    colMeans(summ$tau)
    colMeans(summ$sigma)

```

---

 phenoSim

*Simulate Green-up Phenology Data*


---

## Description

This function return a set of simulated data for multiple green-up phenology time-series.

## Usage

```

phenoSim(nSites = 1000, nTSet = c(3:6), p = 2, beta = NULL, sig = 0.1,
         tau = 0.01, miss = 0, plotFlag = FALSE, ymax = 1, trend = +1)

```

## Arguments

nSites	Number of sites/seasons
nTSet	A vector of integer values. Length of each time-series will be randomly sampled from this vector.
p	Number of predictors in the model.
beta	Beta coefficients
sig	Process error.
tau	Observation error.
miss	Fraction of missing data.
plotFlag	logical value indicating whether to plot the resulted time-series.
ymax	Asymptotic maximum values.
trend	time-series expected trend as -1:decreasing, +1:increasing, 0: not constrained

**Examples**

```
#Simulate Phenology Data
ssSim <- phenoSim(nSites = 2, #number of sites
                 nTSet = 30, #number of time steps
                 beta = c(1, 2), #beta coefficients
                 sig = .01, #process error
                 tau = .1, #observation error
                 plotFlag = TRUE, #whether plot the data or not
                 miss = 0.05, #fraction of missing data
                 ymax = c(6, 3) #maximum of saturation trajectory
)
```

---

phenoSimPlot

*Plot Simulated Phenology Data*


---

**Description**

This function plots the time-series data described with a connectivity matrix.

**Usage**

```
phenoSimPlot(z, connect, add = FALSE, col = "blue", ylim = range(z, na.rm
= TRUE), pch = 1, lwd = 1)
```

**Arguments**

<code>z</code>	A vector of time-series data [n x 1]
<code>connect</code>	The connectivity matrix for the z vector [n x 2]. Each row contains the last and next elements of the time-series. NA values means not connected.
<code>add</code>	logical value indicating whether the plot should be overlaid on the current panel.
<code>col</code>	The color variable as character
<code>ylim</code>	Range of the y axis
<code>pch</code>	pch value for the symbols
<code>lwd</code>	lwd value for line tickness

**Examples**

```
#Simulate Phenology Data
ssSim <- phenoSim(nSites = 2, #number of sites
                 nTSet = 30, #number of time steps
                 beta = c(1, 2), #beta coefficients
                 sig = .01, #process error
                 tau = .1, #observation error
                 plotFlag = TRUE, #whether plot the data or not
                 miss = 0.05, #fraction of missing data
                 ymax = c(6, 3) #maximum of saturation trajectory
)
```

```
)
#Plot Simulated Data
phenoSimPlot(ssSim$z, ssSim$connect)
```

---

plotPOGibbs

*Plot Observed vs Predicted*


---

## Description

This function plot posterior distributions of the parameters.

## Usage

```
plotPOGibbs(o, p, nburnin = NULL, xlim = range(o, na.rm = TRUE),
  ylim = range(p, na.rm = TRUE), xlab = "Observed", ylab = "Predicted",
  colSet = c("#fb8072", "#80b1d3", "black"), cex = 1, lwd = 2, pch = 19)
```

## Arguments

o	Observed vector
p	Predicted Gibbs samples
nburnin	numbe of burn-in itterations
xlim	x-axis range
ylim	y-axis range
xlab	x-axis label
ylab	y-axis label
colSet	vector of colors for points, bars and the 1:1 line
cex	cex value for size
lwd	line width
pch	pch value for symbols

## Examples

```
ssSim <- phenoSim(nSites = 2, #number of sites
  nTSet = 30, #number of Time steps
  beta = c(1, 2), #beta coefficients
  sig = .01, #process error
  tau = .1, #observation error
  plotFlag = TRUE, #whether plot the data or not
  miss = 0.05, #fraction of missing data
  ymax = c(6, 3) #maximum of saturation trajectory
)

ssOut <- fitCDM(x = ssSim$x, #predictors
```

```

nGibbs = 200,
nBurnin = 100,
z = ssSim$z,#response
connect = ssSim$connect, #connectivity of time data
quiet=TRUE)

summ <- getGibbsSummary(ssOut, burnin = 100, sigmaPerSeason = FALSE)

colMeans(summ$ymax)
colMeans(summ$betas)
colMeans(summ$tau)
colMeans(summ$sigma)

par(mfrow = c(1,3), oma = c(1,1,3,1), mar=c(2,2,0,1), font.axis=2)

plotPost(chains = ssOut$chains[,c("beta.1", "beta.2")], trueValues = ssSim$beta)
plotPost(chains = ssOut$chains[,c("ymax.1", "ymax.2")], trueValues = ssSim$ymax)
plotPost(chains = ssOut$chains[,c("sigma", "tau")], trueValues = c(ssSim$sig, ssSim$tau))

mtext('Posterior distributions of the parameters', side = 3, outer = TRUE, line = 1, font = 2)
legend('topleft', legend = c('posterior', 'true value'),
      col = c('black', 'red'), lty = 1, bty = 'n', cex=1.5, lwd =2)

yGibbs <- ssOut$latentGibbs
zGibbs <- ssOut$zpred
o <- ssOut$data$z
p <- apply(ssOut$rawsamples$y, 1, mean)
R2 <- cor(na.omit(cbind(o, p)))[1,2]^2
#Plot Observed vs Predicted
par( mar=c(4,4,1,1), font.axis=2)
plotPOGibbs(o = o , p = zGibbs,
            xlim = c(0,10), ylim=c(0,10),
            cex = .7, nburnin = 1000)
points(o, p, pch = 3)

mtext(paste0('R2 = ', signif(R2, 3)), line = -1, cex = 2, font = 2, side = 1, adj = .9)
legend('topleft', legend = c('mean', '95th percentile', '1:1 line', 'latent states'),
      col = c('#fb8072', '#80b1d3', 'black', 'black'),
      bty = 'n', cex=1.5,
      lty = c(NA, 1, 2, NA), lwd =c(NA, 2, 2, 2), pch = c(16, NA, NA, 3))

```

---

plotPost

*Plot Posterior Distributions*


---

### Description

This function plot posterior distributions of the parameters.

**Usage**

```
plotPost(chains, trueValues = NULL, outline = FALSE)
```

**Arguments**

chains	Gibbs sampling chains
trueValues	numeric vector of true values
outline	logical value whether showing outliers

**Examples**

```
ssSim <- phenoSim(nSites = 2, #number of sites
                 nTSet = 30, #number of Time steps
                 beta = c(1, 2), #beta coefficients
                 sig = .01, #process error
                 tau = .1, #observation error
                 plotFlag = TRUE, #whether plot the data or not
                 miss = 0.05, #fraction of missing data
                 ymax = c(6, 3) #maximum of saturation trajectory
                 )

ssOut <- fitCDM(x = ssSim$x, #predictors
               nGibbs = 200,
               nBurnin = 100,
               z = ssSim$z, #response
               connect = ssSim$connect, #connectivity of time data
               quiet=TRUE)

summ <- getGibbsSummary(ssOut, burnin = 100, sigmaPerSeason = FALSE)

colMeans(summ$ymax)
colMeans(summ$betas)
colMeans(summ$tau)
colMeans(summ$sigma)

par(mfrow = c(1,3), oma = c(1,1,3,1), mar=c(2,2,0,1), font.axis=2)

plotPost(chains = ssOut$chains[,c("beta.1", "beta.2")], trueValues = ssSim$beta)
plotPost(chains = ssOut$chains[,c("ymax.1", "ymax.2")], trueValues = ssSim$ymax)
plotPost(chains = ssOut$chains[,c("sigma", "tau")], trueValues = c(ssSim$sig, ssSim$tau))

mtext('Posterior distributions of the parameters', side = 3, outer = TRUE, line = 1, font = 2)
legend('topleft', legend = c('posterior', 'true value'), col = c('black', 'red'),
      lty = 1, bty = 'n', cex=1.5, lwd =2)
```



# Index

- \* **CDM**
    - fitCDM, 2
  - \* **Data**
    - phenoSim, 4
    - phenoSimPlot, 5
  - \* **Distributions**
    - plotPost, 7
  - \* **Fit**
    - fitCDM, 2
  - \* **Gibbs**
    - getGibbsSummary, 3
  - \* **Model**
    - fitCDM, 2
  - \* **Observed**
    - plotPOGibbs, 6
  - \* **Output**
    - getGibbsSummary, 3
  - \* **Phenology**
    - phenoSim, 4
    - phenoSimPlot, 5
  - \* **Plot**
    - phenoSimPlot, 5
    - plotPOGibbs, 6
    - plotPost, 7
  - \* **Posterior**
    - plotPost, 7
  - \* **Predicted**
    - plotPOGibbs, 6
  - \* **Summary**
    - getGibbsSummary, 3
  - \* **Sampling**
    - getGibbsSummary, 3
  - \* **Simulated**
    - phenoSimPlot, 5
  - \* **Simulate**
    - phenoSim, 4
  - \* **vs**
    - plotPOGibbs, 6
- fitCDM, 2
- getGibbsSummary, 3
- phenoSim, 4
- phenoSimPlot, 5
- plotPOGibbs, 6
- plotPost, 7