Package: pubmedR (via r-universe)

November 22, 2026

Title Gathering Metadata About Publications, Grants, Clinical Trials from 'PubMed' Database

Version 1.1.0

Description A set of tools to extract bibliographic content from 'PubMed' database using 'NCBI' REST API <https://www.ncbi.nlm.nih.gov/home/develop/api/>. It includes functions to search, download, and convert 'PubMed' bibliographic records into data frames compatible with the 'bibliometrix' package. Features include programmatic query building, batch downloading by PMID, citation enrichment via 'NCBI' E-Link and 'NIH iCite', and robust error handling with automatic retry logic.

License GPL-3

URL https://massimoaria.github.io/pubmedR/, https://github.com/massimoaria/pubmedR

BugReports https://github.com/massimoaria/pubmedR/issues

Encoding UTF-8

Imports jsonlite, rentrez, XML

Suggests bibliometrix, knitr, rmarkdown, testthat (>= 3.0.0), withr

Config/testthat/edition 3

VignetteBuilder knitr

Config/roxygen2/version 8.1.0

NeedsCompilation no

Author Massimo Aria [aut, cre] (ORCID: <https://orcid.org/0000-0002-8517-9411>)

Maintainer Massimo Aria <massimo.aria@gmail.com>

Repository https://cran.r-universe.dev

Date/Publication 2026-11-21 19:30:02 UTC

RemoteUrl https://github.com/cran/pubmedR

RemoteRef HEAD

RemoteSha 60130b63fcb7d1724f36cf3f39af5e4aefc980c4

Contents

pmApi2df 2
pmApiRequest 3
pmCitedBy 4
pmCollect 5
pmCountByYear 7
pmEnrichCitations 8
pmExtractReferences 10
pmFetchByDoi 11
pmFetchById 11
pmICite 13
pmQueryBuild 14
pmQueryTotalCount 15
pmReferences 16

Index **18**

`pmApi2df` *Convert xml PubMed bibliographic data into a dataframe*

Description

It converts PubMed data, downloaded using Entrez API, into a dataframe

Usage

```
pmApi2df(P, format = "bibliometrix")
```

Arguments

`P`	is a list following the xml PubMed structure, downloaded using the function `pmApiRequest`.
`format`	is a character. If `format = "bibliometrix"` data will be converted in the bibliometrix compatible data format. If `format = "raw"` data will save in a data frame without any other data editing procedure.

Value

a dataframe containing bibliographic records.

To obtain a free access to NCBI API, please visit: https://pmc.ncbi.nlm.nih.gov/tools/developers/

To obtain more information about how to write a NCBI search query, please visit: https://pubmed.ncbi.nlm.nih.gov/help/#search-tags

See Also

`pmApiRequest`

`pmQueryTotalCount`

Examples

```
# Example: Querying a collection of publications

query <- "bibliometric*[Title/Abstract] AND english[LA]
         AND Journal Article[PT] AND 2000:2020[DP]"
D <- pmApiRequest(query = query, limit = 100, api_key = NULL)
M <- pmApi2df(D)
```

`pmApiRequest` *Gather bibliographic content from PubMed database using NCBI entrez APIs*

Description

It gathers metadata about publications from the NCBI PubMed database. The use of NCBI PubMed APIs is entirely free, and doesn't necessarily require an API key. The function `pmApiRequest` queries NCBI PubMed using an entrez query formulated through the Entrez query language or the helper function `pmQueryBuild`.

Usage

```
pmApiRequest(query, limit, api_key = NULL, batch_size = 200)
```

Arguments

`query`	is a character. It contains a search query formulated using the Entrez query language.
`limit`	is numeric. It indicates the max number of records to download.
`api_key`	is a character. It contains a valid API key for the NCBI E-utilities. Default is `api_key=NULL`. The API key can also be set via the environment variable `PUBMED_API_KEY` or `ENTREZ_KEY`.
`batch_size`	is numeric. The number of records to download per API request. Default is 200.

Details

Official API documentation is https://www.ncbi.nlm.nih.gov/books/NBK25500/.

PubMed serves only the first 9,999 records of a search. When more than that are requested, the query is split by the date each record was added to PubMed, and each part is downloaded in turn, so `limit` can exceed this figure. Records then come ordered by that date period, newest first, not as in the whole search.

Value

a list D composed by 5 objects:

data	It is the xml-structured list containing the bibliographic metadata collection downloaded from the P
query	It a character object containing the original query formulated by the user.
query_translation	It a character object containing the query, translated by the NCBI Automatic Terms Translation syst
records_downloaded	It is an integer object indicating the total number of records downloaded and stored in "data".
total_count	It is an integer object indicating the total number of records matching the query (stored in the "quer

To obtain a free access to NCBI API, please visit: https://pmc.ncbi.nlm.nih.gov/tools/developers/

To obtain more information about how to write a NCBI search query, please visit: https://pubmed.ncbi.nlm.nih.gov/help/#sear tags

See Also

pmQueryTotalCount

pmApi2df

pmQueryBuild

Examples

```
query <- "bibliometric*[Title/Abstract] AND english[LA]
          AND Journal Article[PT] AND 2000:2020[DP]"
 D <- pmApiRequest(query = query, limit = 100, api_key = NULL)
```

---

pmCitedBy *Find articles that cite a given PubMed article*

Description

It retrieves the PMIDs of articles that cite a given PubMed article, using the NCBI E-Link service (PubMed Cited by).

Usage

```
pmCitedBy(pmid, api_key = NULL)
```

Arguments

pmid	is a character or numeric. A single PubMed identifier (PMID).
api_key	is a character. It contains a valid API key for the NCBI E-utilities. Default is api_key=NULL. The API key can also be set via the environment variable PUBMED_API_KEY or ENTREZ_KEY.

Details

This function uses the NCBI E-Link endpoint with linkname "pubmed_pubmed_citedin" to find articles in PubMed that cite the given article.

Note: Citation data in PubMed is based on PubMed Central (PMC) and may not be as comprehensive as commercial citation databases (e.g. Web of Science, Scopus).

Value

a list containing:

pmid	The queried PMID.
cited_by	A character vector of PMIDs that cite the queried article.
count	The number of citing articles found.

See Also

pmReferences

pmFetchById

Examples

```
# Find articles that cite PMID 25824007
cites <- pmCitedBy(pmid = "25824007")
cites$count
cites$cited_by
```

---

pmCollect *Collect and process PubMed bibliographic data in one step*

Description

A convenience wrapper that executes the full pubmedR workflow: query building, record count check, metadata download, conversion to data frame, and (optionally) citation enrichment via NCBI E-Link.

Usage

```
pmCollect(
  query = NULL,
  terms = NULL,
  fields = "Title/Abstract",
  language = NULL,
  pub_type = NULL,
  date_range = NULL,
  mesh_terms = NULL,
  limit = 2000,
  enrich = FALSE,
  format = "bibliometrix",
  api_key = NULL,
  batch_size = 200,
  verbose = TRUE,
  author = NULL,
  journal = NULL,
  operator = "AND"
)
```

Arguments

query	is a character. A PubMed search query in Entrez syntax. Alternatively, if terms is provided, or if query is missing and any of mesh_terms, author or journal is provided, the query is built automatically using pmQueryBuild.
terms	is a character or character vector or NULL. Search terms passed to pmQueryBuild. When provided, a query is built automatically and the query argument is ignored. Default is NULL.
fields	is a character or character vector. PubMed search tags used when building the query from terms. Default is "Title/Abstract".
language	is a character or NULL. Language filter for query building. Default is NULL.
pub_type	is a character or NULL. Publication type filter for query building. Default is NULL.
date_range	is a character vector of length 2 or NULL. Date range in format c("YYYY", "YYYY"). Default is NULL.
mesh_terms	is a character or character vector or NULL. MeSH terms for query building. Default is NULL.
limit	is numeric. Maximum number of records to download. Default is 2000.
enrich	is logical. If TRUE, citation counts (TC) and cited references (CR) are added via pmEnrichCitations. Default is FALSE because enrichment makes 2 API calls per article and can be slow for large collections.
format	is a character. Output format passed to pmApi2df. Either "bibliometrix" (default) or "raw".
api_key	is a character or NULL. NCBI API key. Can also be set via the environment variable PUBMED_API_KEY or ENTREZ_KEY. Default is NULL.
batch_size	is numeric. Records per API request. Default is 200.
verbose	is logical. If TRUE (default), prints progress messages.
author	is a character or character vector or NULL. Author names for query building. Default is NULL.
journal	is a character or character vector or NULL. Journal names for query building. Default is NULL.
operator	is a character. Boolean operator combining terms, "AND" or "OR". Default is "AND".

Details

This function chains together the core pubmedR functions in the recommended order:

1. **Query**: If terms is provided, builds the query with pmQueryBuild; otherwise uses the query string directly.
2. **Count**: Checks the total number of matching records with pmQueryTotalCount.
3. **Download**: Fetches metadata with pmApiRequest.
4. **Convert**: Transforms XML to a data frame with pmApi2df.
5. **Enrich** (optional): Adds citation data with pmEnrichCitations.

Value

a data frame containing bibliographic records, compatible with the `bibliometrix` package when `format = "bibliometrix"`.

See Also

pmQueryBuild, pmQueryTotalCount, pmApiRequest, pmApi2df, pmEnrichCitations

Examples

```
# Using a raw query string
M <- pmCollect(
  query = "bibliometric*[Title/Abstract] AND english[LA] AND 2020:2024[DP]",
  limit = 50
)

# Using the query builder parameters
M <- pmCollect(
  terms = "bibliometric*",
  language = "english",
  pub_type = "Journal Article",
  date_range = c("2020", "2024"),
  limit = 50
)

# With citation enrichment (slower, requires extra API calls)
M <- pmCollect(
  terms = "bibliometric*",
  date_range = c("2023", "2024"),
  limit = 10,
  enrich = TRUE
)
```

---

pmCountByYear *Count the documents of a query by publication year*

Description

It returns the publication trend of a query without downloading its records, with one request per year.

Usage

```
pmCountByYear(query, years = NULL, api_key = NULL)
```

Arguments

query	is a character. A search query in the Entrez query language.
years	is a numeric vector of years. Default is the last 20 years.
api_key	is a character. A valid API key for the NCBI E-utilities. Default is api_key=NULL. It can also be set via the environment variable PUBMED_API_KEY or ENTREZ_KEY.

Value

a data frame with the columns year and count, in the order of years.

See Also

pmQueryTotalCount, pmQueryBuild

Examples

```
pmCountByYear("bibliometric*[Title/Abstract]", years = 2015:2024)
```

---

pmEnrichCitations *Enrich a PubMed dataframe with citation data*

Description

Adds cited references (CR field), reference counts (NR field), and optionally citation counts (TC field) to a dataframe created by pmApi2df.

Usage

```
pmEnrichCitations(
  df,
  P = NULL,
  api_key = NULL,
  resolve_pmids = TRUE,
  only_multiple = FALSE,
  include_TC = TRUE,
  batch_size = 200,
  tc_source = c("pubmed", "icite")
)
```

Arguments

df	is a dataframe. A bibliometric dataframe produced by pmApi2df.
P	is the optional list returned by pmApiRequest or pmFetchById that produced df. Reuse it to avoid an extra round-trip when references are already available. If NULL, the function calls pmFetchById on df$PMID to retrieve the underlying XML.

api_key	is a character. It contains a valid API key for the NCBI E-utilities. Default is api_key=NULL. The API key can also be set via the environment variable PUBMED_API_KEY or ENTREZ_KEY.
resolve_pmids	logical. When TRUE (default) the function fetches metadata for every cited PMID present in the references and assembles structured WoS-style citation strings ("AUTHOR YYYY, JOURNAL, V##, P##, DOI ..."). When FALSE the free-text <Citation> block from the XML is used as-is.
only_multiple	logical. When TRUE only references cited by more than one source article are resolved to metadata (faster and cheaper). References not resolved keep their free-text citation. Defaults to FALSE.
include_TC	logical. When TRUE (default) also retrieve the citation count of each source article and write it to df$TC. An article whose count could not be retrieved keeps its value, with a warning. Disable to skip this step.
batch_size	integer. Number of records per API call when fetching metadata. Defaults to 200 (NCBI's hard cap for efetch).
tc_source	character. Where citation counts come from: "pubmed" (default), the articles in PubMed Central that cite the document, or "icite", the larger NIH Open Citation Collection (see pmICite).

Details

Cited references are extracted from the article's PubMed XML (<ReferenceList>). This is more reliable than the previous E-Link pubmed_pubmed_refs approach, which only worked for articles deposited in PMC. References whose XML carries an ArticleId IdType="pubmed" are resolved to bibliographic metadata in batched efetch requests so that CR matches the WoS convention used by bibliometrix; references with only free-text citations are kept verbatim (uppercased).

Value

The input dataframe with updated CR (cited references), NR (number of references), and TC (times cited, if include_TC = TRUE) fields.

See Also

pmExtractReferences, pmCitedBy, pmFetchById, pmApi2df

Examples

```
query <- "bibliometric*[Title/Abstract] AND english[LA]
         AND Journal Article[PT] AND 2000:2020[DP]"
D <- pmApiRequest(query = query, limit = 10, api_key = NULL)
M <- pmApi2df(D)
M <- pmEnrichCitations(M, P = D)        # avoid the extra fetch
```

pmExtractReferences *Extract references from PubMed XML records*

Description

Walks a result returned by pmApiRequest or pmFetchById and pulls the <ReferenceList> block out of every record. Returns one row per cited <Reference>, carrying the source PMID, the free-text citation, and (when present) the cited PMID and DOI parsed from <ArticleIdList>.

Usage

```
pmExtractReferences(P)
```

Arguments

P	A list following the PubMed XML structure produced by pmApiRequest() or pmFetchById(). Must contain a $data element with one entry per record.

Details

Reference data in PubMed XML is populated when the publisher submits a <ReferenceList> block to NLM (which is now common, but not universal). This function does not call any web API; it merely parses what is already present in the XML. Use pmEnrichCitations to also resolve cited PMIDs into structured WoS-style citation strings.

Value

A data.frame with columns

source_pmid	The PMID of the article that cites the reference.
citation	The free-text <Citation> string from PubMed.
pmid	The PMID of the cited reference (if available).
doi	The DOI of the cited reference (if available).

Returns an empty data.frame (with the same schema) if no references are found.

See Also

pmEnrichCitations, pmFetchById

Examples

```
D <- pmFetchById("37289732")
refs <- pmExtractReferences(D)
head(refs)
```

pmFetchByDoi *Fetch PubMed records by DOI*

Description

It downloads the PubMed records of a set of articles identified by their DOI, for instance to complete a collection coming from another database.

Usage

```
pmFetchByDoi(dois, api_key = NULL, batch_size = 50)
```

Arguments

dois	is a character vector of DOIs, with or without the https://doi.org/ prefix.
api_key	is a character. A valid API key for the NCBI E-utilities. Default is api_key=NULL. It can also be set via the environment variable PUBMED_API_KEY or ENTREZ_KEY.
batch_size	is numeric. DOIs per search. Default is 50.

Value

a list with the same structure as the output of pmFetchById, ready for pmApi2df, with one more element: not_found, the DOIs with no PubMed record.

See Also

pmFetchById, pmApi2df

Examples

```
D <- pmFetchByDoi(c("10.1016/j.joi.2017.08.007", "10.1038/nature14539"))
D$not_found
M <- pmApi2df(D)
```

pmFetchById *Fetch PubMed records by PMID*

Description

It downloads metadata for a set of PubMed articles identified by their PMID (PubMed Identifier). This is useful for retrieving specific known articles, updating existing datasets, or downloading records identified through other sources.

Usage

```
pmFetchById(pmids, api_key = NULL, batch_size = 200)
```

Arguments

pmids	is a character or numeric vector. A vector of PubMed identifiers (PMIDs).
api_key	is a character. It contains a valid API key for the NCBI E-utilities. Default is api_key=NULL. The API key can also be set via the environment variable PUBMED_API_KEY or ENTREZ_KEY.
batch_size	is numeric. The number of records to download per API request. Default is 200.

Details

The function uses the NCBI E-utilities efetch endpoint to retrieve records directly by their PMIDs, without requiring a search query. Records are downloaded in batches to respect API rate limits.

The output is compatible with pmApi2df for conversion to a dataframe.

Value

a list following the same structure as pmApiRequest output, containing:

data	The xml-structured list containing the bibliographic metadata.
query	A character string describing the PMID-based query.
query_translation	Same as query for PMID-based searches.
records_downloaded	The total number of records downloaded.
total_count	The total number of PMIDs requested.

See Also

pmApiRequest

pmApi2df

Examples

```
# Download specific articles by PMID
pmids <- c("34813985", "34813456", "34812345")
D <- pmFetchById(pmids = pmids)
M <- pmApi2df(D)
```

`pmICite` *Citation metrics of PubMed articles from NIH iCite*

Description

It retrieves citation counts and field-normalised metrics from the NIH iCite service, built on the NIH Open Citation Collection. No API key is required.

Usage

```
pmICite(pmids, batch_size = 500)
```

Arguments

`pmids`	is a character or numeric vector of PubMed identifiers (PMIDs).
`batch_size`	is numeric. PMIDs per request, at most 1000. Default is 500.

Details

PubMed itself counts only the citing articles in PubMed Central, so its figures are usually much lower than those of iCite.

Value

a data frame with one row per PMID requested, in the same order, and the columns:

pmid	The PMID.
doi	The DOI.
year	The publication year.
citation_count	The number of citing articles.
citations_per_year	Citations per year since publication.
relative_citation_ratio	Citations compared with those expected in the article's field (1 is the NIH-funded median).
nih_percentile	The percentile of the ratio among NIH-funded articles.
is_research_article	Whether iCite classes it as primary research.

A PMID unknown to iCite has `NA` in every other column.

See Also

`pmEnrichCitations`, `pmCitedBy`

Examples

```
pmICite(c("10171110", "25824007"))
```

pmQueryBuild *Build a PubMed search query programmatically*

Description

It helps to build a valid PubMed search query using the Entrez query language, combining multiple search terms with Boolean operators.

Usage

```
pmQueryBuild(
  terms = NULL,
  fields = "Title/Abstract",
  language = NULL,
  pub_type = NULL,
  date_range = NULL,
  mesh_terms = NULL,
  author = NULL,
  journal = NULL,
  operator = "AND"
)
```

Arguments

terms	is a character or character vector. Search terms to look for in title and abstract fields.
fields	is a character or character vector. PubMed search tags to apply. Default is `c("Title/Abstract")`. Common fields include: "Title/Abstract", "Title", "Author", "MeSH Terms", "Affiliation", "Journal".
language	is a character or character vector or NULL. Language filter (e.g. "english", "french"). Several languages are combined with OR. Default is `NULL` (no filter).
pub_type	is a character or character vector or NULL. Publication type filter (e.g. "Journal Article", "Review", "Clinical Trial"). Several types are combined with OR. Default is `NULL` (no filter).
date_range	is a character vector of length 2 or NULL. Date range in format `c("YYYY", "YYYY")` or `c("YYYY/MM/DD", "YYYY/MM/DD")`. Default is `NULL` (no filter).
mesh_terms	is a character or character vector or NULL. MeSH (Medical Subject Headings) terms. Default is `NULL` (no filter).
author	is a character or character vector or NULL. Author names. Default is `NULL`.
journal	is a character or character vector or NULL. Journal names or abbreviations. Default is `NULL`.
operator	is a character. Boolean operator to combine multiple `terms`. One of "AND", "OR". Default is `"AND"`.

Details

The function constructs a query string compatible with NCBI's Entrez search system. Multiple terms within the same parameter are combined with the specified `operator`, while different parameters (terms, language, pub_type, etc.) are combined with AND.

For more information about PubMed search tags, visit: https://pubmed.ncbi.nlm.nih.gov/help/#search-tags

Value

a character string containing the formatted PubMed query.

See Also

`pmQueryTotalCount`

`pmApiRequest`

Examples

```
# Simple query
q <- pmQueryBuild(terms = "bibliometrics", language = "english",
                  pub_type = "Journal Article", date_range = c("2000", "2023"))

# Multiple terms
q <- pmQueryBuild(terms = c("machine learning", "deep learning"),
                  operator = "OR", language = "english")

# MeSH terms query
q <- pmQueryBuild(mesh_terms = "COVID-19", pub_type = "Review",
                  date_range = c("2020", "2024"))

# Author search
q <- pmQueryBuild(terms = "bibliometrics", author = "Aria M")
```

---

pmQueryTotalCount *Count the number of documents returned by a query*

Description

It counts the number of documents that a query returns from the NCBI PubMed database.

Usage

```
pmQueryTotalCount(query, api_key = NULL)
```

Arguments

query	is a character. It contains a search query formulated using the Entrez query language.
api_key	is a character. It contains a valid API key for the NCBI E-utilities. Default is api_key=NULL. The use of NCBI PubMed APIs is entirely free, and doesn't necessarily require an API key. The API key can also be set via the environment variable PUBMED_API_KEY or ENTREZ_KEY.

Value

a list. It contains three objects:

total_count	The total number of records returned by the query
query_translation	The query translation by the NCBI Automatic Terms Translation system
web_history	The web history object. The NCBI provides search history features, which is useful for dealing with la

To obtain a free access to NCBI API, please visit: https://pmc.ncbi.nlm.nih.gov/tools/developers/

See Also

pmApiRequest

pmApi2df

Examples

```
query <- "bibliometric*[Title/Abstract] AND english[LA]
          AND Journal Article[PT] AND 2000:2020[DP]"
D <- pmQueryTotalCount(query = query, api_key = NULL)
```

---

pmReferences *Find references cited by a given PubMed article*

Description

It retrieves the PMIDs of articles that are cited by (referenced in) a given PubMed article, using the NCBI E-Link service.

Usage

```
pmReferences(pmid, api_key = NULL)
```

Arguments

pmid	is a character or numeric. A single PubMed identifier (PMID).
api_key	is a character. It contains a valid API key for the NCBI E-utilities. Default is api_key=NULL. The API key can also be set via the environment variable PUBMED_API_KEY or ENTREZ_KEY.

Details

This function uses the NCBI E-Link endpoint with linkname "pubmed_pubmed_refs" to find articles in PubMed that are referenced by the given article.

Note: Reference data is extracted from PubMed Central (PMC) full-text articles and is only available when the full text is deposited in PMC. Not all PubMed articles have reference data available.

Value

a list containing:

pmid	The queried PMID.
references	A character vector of PMIDs referenced by the queried article.
count	The number of references found.

See Also

pmCitedBy

pmFetchById

Examples

```
# Find references of PMID 25824007
refs <- pmReferences(pmid = "25824007")
refs$count
refs$references
```

Index

pmApi2df, 2, *4*, *6–9*, *11, 12*, *16*
pmApiRequest, *2*, 3, *6–8*, *10*, *12*, *15, 16*
pmCitedBy, 4, *9*, *13*, *17*
pmCollect, 5
pmCountByYear, 7
pmEnrichCitations, *6, 7*, 8, *10*, *13*
pmExtractReferences, *9*, 10
pmFetchByDoi, 11
pmFetchById, *5*, *8–10*, 11, *11*, *17*
pmICite, *9*, 13
pmQueryBuild, *3, 4*, *6–8*, 14
pmQueryTotalCount, *2*, *4*, *6–8*, 15, *15*
pmReferences, *5*, 16