

# Package: quickSentiment (via r-universe)

May 17, 2026

**Title** A Fast and Flexible Pipeline for Text Classification

**Version** 0.3.4

**Description** A high-level pipeline that simplifies text classification into three streamlined steps: preprocessing, model training, and standardized prediction. It unifies the interface for multiple algorithms (including 'glmnet', 'ranger', 'xgboost', and 'naivebayes') and memory-efficient sparse matrix vectorization methods (Bag-of-Words, Term Frequency, TF-IDF, and Binary). Users can go from raw text to a fully evaluated sentiment model, complete with ROC-optimized thresholds, in just a few function calls. The resulting model artifact automatically aligns the vocabulary of new datasets during the prediction phase, safely appending predicted classes and probability matrices directly to the user's original dataframe to preserve metadata.

**License** MIT + file LICENSE

**Encoding** UTF-8

**RoxygenNote** 7.3.3

**Imports** doParallel, foreach, glmnet, magrittr, Matrix, methods, naivebayes, quanteda, ranger, stopwords, stringr, textstem, xgboost

**VignetteBuilder** knitr

**Suggests** knitr, rmarkdown, spelling

**Language** en-US

**NeedsCompilation** no

**Author** Alabhya Dahal [aut, cre]

**Maintainer** Alabhya Dahal <alabhya.dahal@gmail.com>

**Repository** <https://cran.r-universe.dev>

**Date/Publication** 2026-04-17 06:17:01 UTC

**RemoteUrl** <https://github.com/cran/quickSentiment>

**RemoteRef** HEAD

**RemoteSha** 1c621de51fa914282a57addc9a6deeb6b614130a

## Contents

|                                     |    |
|-------------------------------------|----|
| BOW_test . . . . .                  | 2  |
| BOW_train . . . . .                 | 3  |
| evaluate_performance . . . . .      | 4  |
| logit_model . . . . .               | 5  |
| nb_model . . . . .                  | 6  |
| pipeline . . . . .                  | 7  |
| plot.quickSentiment_prc . . . . .   | 8  |
| plot.quickSentiment_roc . . . . .   | 9  |
| pre_process . . . . .               | 9  |
| predict_sentiment . . . . .         | 11 |
| print.quickSentiment_eval . . . . . | 11 |
| qs_negations . . . . .              | 12 |
| rf_model . . . . .                  | 12 |
| xgb_model . . . . .                 | 13 |

|              |           |
|--------------|-----------|
| <b>Index</b> | <b>15</b> |
|--------------|-----------|

---

|          |  |
|----------|--|
| BOW_test | <i>Transform New Text into a Document-Feature Matrix</i> |
|----------|--|

---

### Description

This function takes a character vector of new documents and transforms it into a DFM that has the exact same features as a pre-fitted training DFM, ensuring consistency for prediction.

### Usage

```
BOW_test(doc, fit)
```

### Arguments

|     |  |
|-----|--|
| doc | A character vector of new documents to be processed. |
| fit | A fitted BoW object returned by BOW_train().         |

### Value

A quanteda dfm aligned to the training features.

### Examples

```
train_txt <- c("apple orange banana", "apple apple")
fit <- BOW_train(train_txt, weighting_scheme = "bow")
new_txt <- c("banana pear", "orange apple")
test_dfm <- BOW_test(new_txt, fit)
test_dfm
```

---

`BOW_train`*Train a Bag-of-Words Model*

---

## Description

Train a Bag-of-Words Model

## Usage

```
BOW_train(doc, weighting_scheme = "bow", ngram_size = 1)
```

## Arguments

`doc` A character vector of documents to be processed.

`weighting_scheme` A string specifying the weighting to apply. Defaults to "bag\_of\_words".

- "bag\_of\_words" (Alias: "bow") - Standard count of words.
- "term\_frequency" (Alias: "tf") - Normalized counts (frequency relative to document length).
- "tfidf" (Alias: "tf-idf") - Term Frequency-Inverse Document Frequency.
- "binary" - Presence/Absence (1/0).

`ngram_size` An integer specifying the maximum n-gram size. For example, 'ngram\_size = 1' will create unigrams only; 'ngram\_size = 2' will create unigrams and bigrams. Defaults to 1.

## Value

An object of class "qs\_bow\_fit" containing:

- `dfm_template`: a quanteda dfm template
- `weighting_scheme`: the weighting used
- `ngram_size`: the n-gram size used

#'

## Examples

```
txt <- c("text one", "text two text")
fit <- BOW_train(txt, weighting_scheme = "bow")
fit$dfm_template
```

---

evaluate\_performance *Evaluate Model Performance (ROC and Precision-Recall)*

---

### Description

Evaluate Model Performance (ROC and Precision-Recall)

### Usage

```
evaluate_performance(predicted_probs, actual_classes, positive_label)
```

### Arguments

`predicted_probs` Numeric vector of predicted probabilities for the positive class.

`actual_classes` Factor or character vector of the actual true labels.

`positive_label` Character string. The target class you want to evaluate.

### Value

An object of class 'quickSentiment\_eval', which is a list containing the following metrics:

`target_class` Character. The specific positive label used for the evaluation.

`auc_roc` Numeric. The Area Under the Receiver Operating Characteristic curve.

`best_threshold_roc` Numeric. The optimal probability threshold that maximizes Youden's J statistic.

`auc_pr` Numeric. The Area Under the Precision-Recall curve.

`best_threshold_pr` Numeric. The probability threshold that maximizes the F1-Score.

`accuracy_at_best` Numeric. The overall accuracy of the model if 'best\_threshold\_pr' is applied.

`roc` S3 object containing the ROC curve data and metrics.

`prc` S3 object containing the Precision-Recall curve data and metrics.

`threshold_summary` A data frame summarizing Accuracy, Precision, Recall, and F1 at 0.1 threshold increments.

---

`logit_model`*Train a Regularized Logistic Regression Model using glmnet*

---

### Description

This function trains a logistic regression model using Lasso regularization via the `glmnet` package. It uses cross-validation to automatically find the optimal regularization strength (`lambda`).

### Usage

```
logit_model(  
  train_vectorized,  
  Y,  
  test_vectorized,  
  parallel = FALSE,  
  tune = FALSE  
)
```

### Arguments

|                               |  |
|-------------------------------|--|
| <code>train_vectorized</code> | The training feature matrix (e.g., a ‘dfm’ from <code>quanteda</code> ). This should be a sparse matrix. |
| <code>Y</code>                | The response variable for the training set. Should be a factor for classification.                       |
| <code>test_vectorized</code>  | The test feature matrix, which must have the same features as ‘ <code>train_vectorized</code> ’.         |
| <code>parallel</code>         | Logical  |
| <code>tune</code>             | Logical  |

### Value

A list containing two elements:

|                          |  |
|--------------------------|--|
| <code>pred</code>        | A vector of class predictions for the test set.                      |
| <code>probs</code>       | A matrix of predicted probabilities.                                 |
| <code>model</code>       | The final, trained ‘ <code>cv.glmnet</code> ’ model object.          |
| <code>best_lambda</code> | The optimal <code>lambda</code> value found during cross-validation. |

### Examples

```
## Not run:  
# Create dummy vectorized training and test data  
train_matrix <- matrix(runif(100), nrow = 10, ncol = 10)  
test_matrix <- matrix(runif(50), nrow = 5, ncol = 10)  
  
# Provide column names (vocabulary) required by glmnet
```

```

colnames(train_matrix) <- paste0("word", 1:10)
colnames(test_matrix) <- paste0("word", 1:10)

y_train <- factor(sample(c("P", "N"), 10, replace = TRUE))

# Run logistic regression model (glmnet)
model_results <- logit_model(train_matrix, y_train, test_matrix)

## End(Not run)

```

---

nb\_model

*Multinomial Naive Bayes for Text Classification*


---

## Description

Multinomial Naive Bayes for Text Classification

## Usage

```
nb_model(train_vectorized, Y, test_vectorized, parallel = FALSE, tune = FALSE)
```

## Arguments

|                  |  |
|------------------|--|
| train_vectorized | The training feature matrix (e.g., a ‘dfm’ from <code>quanteda</code> ). This should be a sparse matrix. |
| Y                | The response variable for the training set. Should be a factor for classification.                       |
| test_vectorized  | The test feature matrix, which must have the same features as ‘train_vectorized’                         |
| parallel         | Logical  |
| tune             | Logical. If TRUE, tests different Laplace smoothing values.  |

## Value

A list containing four elements:

|             |   |
|-------------|---|
| pred        | A vector of class predictions for the test set. |
| probs       | A matrix of predicted probabilities.            |
| model       | The final, trained ‘naivebayes’ model object.   |
| best_lambda | Placeholder (NULL) for pipeline consistency.    |

## Examples

```
# 1. Create dummy numeric matrices with BOTH row and column names
train_matrix <- matrix(
  as.numeric(sample(0:5, 100, replace = TRUE)),
  nrow = 10, ncol = 10,
  dimnames = list(paste0("doc", 1:10), paste0("word", 1:10))
)

test_matrix <- matrix(
  as.numeric(sample(0:5, 50, replace = TRUE)),
  nrow = 5, ncol = 10,
  dimnames = list(paste0("doc", 1:5), paste0("word", 1:10))
)

# 2. Create dummy target variable
y_train <- factor(sample(c("P", "N"), 10, replace = TRUE))

# 3. Run model
model_results <- nb_model(train_matrix, y_train, test_matrix)
print(model_results$pred)
```

---

pipeline

*Run a Full Text Classification Pipeline on Preprocessed Text*

---

## Description

This function takes a data frame with pre-cleaned text and handles the data splitting, vectorization, model training, and evaluation.

## Usage

```
pipeline(
  vect_method,
  model_name,
  text_vector,
  sentiment_vector,
  n_gram = 1,
  tune = FALSE,
  parallel = FALSE
)
```

## Arguments

**vect\_method** A string specifying the vectorization method. Defaults to "bag\_of\_words".

- "bag\_of\_words" (Alias: "bow") - Standard count of words.
- "term\_frequency" (Alias: "tf") - Normalized counts.
- "tfidf" (Alias: "tf-idf") - Term Frequency-Inverse Document Frequency.

|                  |   |
|------------------|---|
|                  | <ul style="list-style-type: none"> <li>• "binary" - Presence/Absence (1/0).</li> </ul>  |
| model_name       | A string specifying the model to train. Defaults to "logistic_regression". <ul style="list-style-type: none"> <li>• "random_forest" (Alias: "rf")</li> <li>• "xgboost" (Alias: "xgb")</li> <li>• "logistic_regression" (Alias: "logit", "glm")</li> </ul> |
| text_vector      | A character vector containing the <b>preprocessed</b> text.   |
| sentiment_vector | A vector or factor containing the target labels (e.g., ratings).  |
| n_gram           | The n-gram size to use for BoW/TF-IDF. Defaults to 1.   |
| tune             | Logical. If TRUE, the pipeline will perform hyperparameter tuning for the selected model. Defaults to FALSE. [NEW]  |
| parallel         | If TRUE, runs model training in parallel. Default FALSE.  |

**Value**

A list containing the trained model object, the DFM template, class levels, and a comprehensive evaluation report.

**Examples**

```
df <- data.frame(
  text = c("good product", "excellent", "loved it", "great quality",
           "bad service", "terrible", "hated it", "awful experience",
           "not good", "very bad", "fantastic", "wonderful"),
  y = c("P", "P", "P", "P", "N", "N", "N", "N", "N", "N", "P", "P")
)

out <- pipeline("bow", "naive_bayes", text_vector = df$text, sentiment_vector = df$y)
```

---

plot.quickSentiment\_prc

*Plot Precision-Recall Curve*

---

**Description**

Plot Precision-Recall Curve

**Usage**

```
## S3 method for class 'quickSentiment_prc'
plot(x, ...)
```

**Arguments**

x                   An object of class 'quickSentiment\_prc'.  
 ...                 Additional graphical parameters.

---

plot.quickSentiment\_roc  
*Plot ROC Curve*

---

### Description

Plot ROC Curve

### Usage

```
## S3 method for class 'quickSentiment_roc'  
plot(x, ...)
```

### Arguments

x                   An object of class 'quickSentiment\_roc'.  
...                  Additional graphical parameters.

---

pre\_process           *Preprocess a Vector of Text Documents*

---

### Description

This function provides a comprehensive and configurable pipeline for cleaning raw text data. It handles a variety of common preprocessing steps including removing URLs and HTML, lowercasing, stopword removal, and lemmatization.

### Usage

```
pre_process(  
  doc_vector,  
  remove_brackets = TRUE,  
  remove_urls = TRUE,  
  remove_html = TRUE,  
  remove_nums = FALSE,  
  remove_emojis_flag = TRUE,  
  to_lowercase = TRUE,  
  remove_punct = TRUE,  
  remove_stop_words = TRUE,  
  custom_stop_words = NULL,  
  keep_words = NULL,  
  lemmatize = TRUE,  
  retain_negations = TRUE  
)
```

**Arguments**

|                    |   |
|--------------------|---|
| doc_vector         | A character vector where each element is a document.  |
| remove_brackets    | A logical value indicating whether to remove text in square brackets.   |
| remove_urls        | A logical value indicating whether to remove URLs and email addresses.  |
| remove_html        | A logical value indicating whether to remove HTML tags.   |
| remove_nums        | A logical value indicating whether to remove numbers.   |
| remove_emojis_flag | A logical value indicating whether to remove common emojis.   |
| to_lowercase       | A logical value indicating whether to convert text to lowercase.  |
| remove_punct       | A logical value indicating whether to remove punctuation.   |
| remove_stop_words  | A logical value indicating whether to remove English stopwords.   |
| custom_stop_words  | A character vector of additional custom words to remove (e.g., c("rt", "via")). Default is NULL.  |
| keep_words         | A character vector of words to protect from deletion (e.g., c("no", "not", "nor")). Default is NULL.  |
| lemmatize          | A logical value indicating whether to lemmatize words to their dictionary form.   |
| retain_negations   | Logical. If TRUE (the default), automatically protects common negation words (e.g., "not", "no", "never") from being deleted by the standard stopword list to preserve sentiment context. |

**Value**

A character vector of the cleaned and preprocessed text.

**Examples**

```
raw_text <- c(
  "This is a <b>test</b>! Visit https://example.com",
  "Email me at test.user@example.org [important]"
)

# Basic preprocessing with defaults
clean_text <- pre_process(raw_text)
print(clean_text)

# Keep punctuation and stopwords
clean_text_no_stop <- pre_process(
  raw_text,
  remove_stop_words = FALSE,
  remove_punct = FALSE
)
print(clean_text_no_stop)
```

---

predict\_sentiment      *Predict Sentiment on New Data Using a Saved Pipeline Artifact*

---

### Description

This is a generic prediction function that handles different model types and ensures consistent pre-processing and vectorization for new, unseen text.

### Usage

```
predict_sentiment(pipeline_object, text_column, threshold = 0.5)
```

### Arguments

**pipeline\_object**      A list object returned by the main ‘pipeline()’ function. It must contain the trained model, DFM template, preprocessing function, and n-gram settings.

**text\_column**      A string specifying the column name of the text to predict.

**threshold**      Numeric. Optional custom threshold for binary classification. If NULL, uses the optimized threshold from training (if available).

### Value

A data frame containing the ‘predicted\_class’ and probability columns.

### Examples

```
if (exists("my_artifacts")) {  
  dummy_df <- data.frame(text = c("loved it", "hated it"), stringsAsFactors = FALSE)  
  preds <- predict_sentiment(my_artifacts, df = dummy_df, text_column = "text")  
}
```

---

print.quickSentiment\_eval  
    *Print quickSentiment Evaluation Results*

---

### Description

Print quickSentiment Evaluation Results

### Usage

```
## S3 method for class 'quickSentiment_eval'  
print(x, ...)
```

**Arguments**

x                    An object of class 'quickSentiment\_eval'.  
 ...                  Further arguments passed to or from other methods.

---

qs\_negations                    *Standard Negation Words for Sentiment Analysis*

---

**Description**

A character vector of 25 common negation words. These words are automatically protected by the [pre\\_process](#) function when `retain_negations = TRUE` to prevent standard stopwords lists from destroying sentiment polarity.

**Usage**

```
qs_negations
```

**Format**

An object of class character of length 25.

---

rf\_model                    *functions/random\_forest\_fast.R Train a Random Forest Model using Ranger*

---

**Description**

This function trains a Random Forest model using the high-performance ranger package. It natively utilizes sparse matrices (dgCMatrix) to avoid memory exhaustion and utilizes Out-Of-Bag (OOB) error for rapid hyperparameter tuning.

**Usage**

```
rf_model(train_vectorized, Y, test_vectorized, parallel = FALSE, tune = FALSE)
```

**Arguments**

train\_vectorized                    The training feature matrix (e.g., a 'dfm' from `quanteda`).

Y                    The response variable for the training set. Should be a factor.

test\_vectorized                    The test feature matrix, which must have the same features as 'train\_vectorized'.

parallel                    Logical

tune                    Logical. If TRUE, tunes 'mtry' using native OOB error

**Value**

A list containing four elements:

|             |   |
|-------------|---|
| pred        | A vector of class predictions for the test set. |
| probs       | A matrix of predicted probabilities.            |
| model       | The final, trained ‘ranger’ model object.       |
| best_lambda | Placeholder (NULL) for pipeline consistency.    |

**Examples**

```
## Not run:
# Create dummy vectorized training and test data
train_matrix <- matrix(runif(100), nrow = 10, ncol = 10)
test_matrix <- matrix(runif(50), nrow = 5, ncol = 10)

# Provide column names (vocabulary) required by ranger
colnames(train_matrix) <- paste0("word", 1:10)
colnames(test_matrix) <- paste0("word", 1:10)

y_train <- factor(sample(c("P", "N"), 10, replace = TRUE))

# Run random forest model
model_results <- rf_model(train_matrix, y_train, test_matrix)

## End(Not run)
```

---

xgb\_model

*Train a Gradient Boosting Model using XGBoost*


---

**Description**

This function trains a model using the xgboost package. It is highly efficient and natively supports sparse matrices, making it ideal for text data. It automatically handles both binary and multi-class classification problems.

**Usage**

```
xgb_model(train_vectorized, Y, test_vectorized, parallel = FALSE, tune = FALSE)
```

**Arguments**

|                  |   |
|------------------|---|
| train_vectorized | The training feature matrix (e.g., a ‘dfm’ from quanteda).                        |
| Y                | The response variable for the training set. Should be a factor.                   |
| test_vectorized  | The test feature matrix, which must have the same features as ‘train_vectorized’. |
| parallel         | Logical   |
| tune             | Logical   |

**Value**

A list containing four elements:

|             |   |
|-------------|---|
| pred        | A vector of class predictions for the test set. |
| probs       | A matrix of predicted probabilities.            |
| model       | The final, trained 'xgb.Booster' model object.  |
| best_lambda | Placeholder (NULL) for pipeline consistency.    |

**Examples**

```
## Not run:
# Create dummy vectorized training and test data
train_matrix <- matrix(runif(100), nrow = 10, ncol = 10)
test_matrix <- matrix(runif(50), nrow = 5, ncol = 10)

# Provide column names (vocabulary) required by xgboost
colnames(train_matrix) <- paste0("word", 1:10)
colnames(test_matrix) <- paste0("word", 1:10)

y_train <- factor(sample(c("P", "N"), 10, replace = TRUE))

# Run xgboost model
model_results <- xgb_model(train_matrix, y_train, test_matrix)

## End(Not run)
```

# Index

## \* datasets

qs\_negations, [12](#)

BOW\_test, [2](#)

BOW\_train, [3](#)

evaluate\_performance, [4](#)

logit\_model, [5](#)

nb\_model, [6](#)

pipeline, [7](#)

plot.quickSentiment\_prc, [8](#)

plot.quickSentiment\_roc, [9](#)

pre\_process, [9](#), [12](#)

predict\_sentiment, [11](#)

print.quickSentiment\_eval, [11](#)

qs\_negations, [12](#)

rf\_model, [12](#)

xgb\_model, [13](#)