

Package: rTwig (via r-universe)

November 25, 2024

Title Realistic Quantitative Structure Models

Version 1.3.0

Description Real Twig is a method to correct branch overestimation in quantitative structure models. Overestimated cylinders are correctly tapered using measured twig diameters of corresponding tree species. Supported quantitative structure modeling software includes 'TreeQSM', 'SimpleForest', 'Treegraph', and 'aRchi'. Also included is a novel database of twig diameters and tools for fractal analysis of point clouds.

Encoding UTF-8

RoxygenNote 7.3.2

RdMacros Rdpack

Imports R.matlab, rmatio, tidytable, cobs, igraph, rgl, colourvalues, Rdpack, rlang, Rcpp, RcppSimdJson, geometry

License GPL (>= 3)

Depends R (>= 3.5.0)

LazyData true

Suggests knitr, rmarkdown, ggplot2, ggpmisc, ggpubr, gt, yardstick, dplyr, tidyr

VignetteBuilder knitr

NeedsCompilation yes

Maintainer Aidan Morales <moral169@msu.edu>

URL <https://aidanmorales.github.io/rTwig/>,
<https://github.com/aidanmorales/rTwig>

BugReports <https://github.com/aidanmorales/rTwig/issues>

LinkingTo Rcpp, RcppArmadillo

Author Aidan Morales [aut, cre, cph]
(<<https://orcid.org/0009-0000-4513-4908>>), David W. MacFarlane
[aut, cph]

Repository CRAN

Date/Publication 2024-11-21 21:30:02 UTC

Config/pak/sysreqs libfreetype6-dev libglpk-dev libglu1-mesa-dev make
libpng-dev libxml2-dev libgl1-mesa-dev zlib1g-dev

Contents

box_dimension	2
cluster_cloud	3
correct_radii	5
export_mat	5
export_mesh	6
import_qsm	7
import_treagraph	8
plot_qsm	9
prune_qsm	11
qsm_summary	12
run_rtwig	13
smooth_qsm	14
standardize_qsm	15
tree_metrics	16
twigs	17
update_cylinders	18

Index **20**

box_dimension	<i>Box Dimension</i>
---------------	----------------------

Description

R port of Dominik Seidel's fractal analysis "box-dimension" metric.

Usage

```
box_dimension(cloud, lowercutoff = 0.01, rm_int_box = FALSE, plot = FALSE)
```

Arguments

cloud	A point cloud matrix size $n \times 3$. Non-matrices are automatically converted to a matrix.
lowercutoff	The smallest box size determined by the point spacing of the cloud in meters. Defaults to 1 cm.
rm_int_box	Remove the initial box as TRUE or FALSE. Defaults to FALSE.
plot	Plot the results. The user can specify "2D", "3D", or "ALL" plots. FALSE disables plotting. Defaults to FALSE.

Value

Returns a list

References

Arseniou G, MacFarlane DW, Seidel D (2021). “Measuring the Contribution of Leaves to the Structural Complexity of Urban Tree Crowns with Terrestrial Laser Scanning.” *Remote Sensing*, **13**(14). doi:10.3390/rs13142773.

Mandelbrot BB (1983). *The fractal geometry of nature*. Freeman.

Saarinen N, Calders K, Kankare V, Yrttimaa T, Junttila S, Luoma V, Huuskonen S, Hynynen J, Verbeeck H (2021). “Understanding 3D structural complexity of individual Scots pine trees with different management history.” *Ecology and Evolution*, **11**(6), 2561-2572. doi:10.1002/ece3.7216.

Seidel D (2018). “A holistic approach to determine tree structural complexity based on laser scanning data and fractal analysis.” *Ecology and Evolution*, **8**(1), 128-134. doi:10.1002/ece3.3661.

Seidel D, Annighöfer P, Stiers M, Zemp CD, Burkardt K, Ehbrecht M, Willim K, Kreft H, Hölscher D, Ammer C (2019). “How a measure of tree structural complexity relates to architectural benefit-to-cost ratio, light availability, and growth of trees.” *Ecology and Evolution*, **9**(12), 7134-7142. doi:10.1002/ece3.5281.

Examples

```
## Calculate Box Dimension
file <- system.file("extdata/cloud.txt", package = "rTwig")
cloud <- read.table(file, header = FALSE)
output <- box_dimension(cloud, plot = "ALL")
output
```

cluster_cloud

Cluster Cloud

Description

Cluster a point cloud or simulate a point cloud based on its QSM. If using the input point cloud, the cylinder ids are transferred to the cloud using the nearest neighbors. If simulating a cloud, the points are built directly from the cylinders with user controlled spacing. The cylinder id can be used to easily join the desired variables from the QSM to the cloud. The nearest neighbor search uses the C++ nanoflann library.

Usage

```
cluster_cloud(cylinder, cloud = NULL, spacing = NULL)
```

Arguments

cylinder	A QSM cylinder data frame.
cloud	The input point cloud for the QSM to cluster. If NULL (default), the simulated cloud is returned.
spacing	The point spacing in meters for the simulated cloud. Defaults to 0.02 meters.

Value

A point cloud data frame

References

Blanco JL, Rai PK (2014). “nanoflann: a C++ header-only fork of FLANN, a library for Nearest Neighbor (NN) with KD-trees.” <https://github.com/jlblancoc/nanoflann>.

Examples

```
## Load Data
file <- system.file("extdata/QSM.mat", package = "rTwig")
file2 <- system.file("extdata/cloud.txt", package = "rTwig")

qsm <- run_rtwig(file, twig_radius = 4.23, metrics = FALSE)
cloud <- read.table(file2)

## Clustered Cloud
clustered_cloud <- cluster_cloud(cylinder = qsm, cloud = cloud)

# # Join QSM variables and export
# filename <- tempfile(pattern = "clustered_cloud", fileext = ".txt")
# clustered_cloud %>%
#   left_join(qsm) %>%
#   fwrite(file = filename)

## Simulated Cloud
simulated_cloud <- cluster_cloud(cylinder = qsm, spacing = 0.01)

# Plot Simulated Cloud
plot_qsm(cloud = simulated_cloud)

# # Join QSM variables and export
# filename2 <- tempfile(pattern = "simulated_cloud", fileext = ".txt")
# simulated_cloud %>%
#   left_join(qsm) %>%
#   fwrite(file = filename2)
```

correct_radii	<i>Correct Radii</i>
---------------	----------------------

Description

Corrects cylinder radii

Usage

```
correct_radii(cylinder, twig_radius, broken_branch = TRUE)
```

Arguments

cylinder	QSM cylinder data frame
twig_radius	Twig radius in millimeters
broken_branch	Enable or disable the broken branch filter. Defaults to enabled (TRUE).

Value

Returns a data frame

Examples

```
## TreeQSM Processing Chain
file <- system.file("extdata/QSM.mat", package = "rTwig")
qsm <- import_qsm(file)
cylinder <- qsm$cylinder
cylinder <- update_cylinders(cylinder)
cylinder <- correct_radii(cylinder, twig_radius = 4.23)
str(cylinder)
```

export_mat	<i>Export MAT</i>
------------	-------------------

Description

Exports the cylinder data to be visualized with TreeQSM's `plot_cylinder_model()`.

Usage

```
export_mat(cylinder, filename)
```

Arguments

cylinder	QSM cylinder data frame
filename	Desired name of file

Value

Returns a .mat file

Examples

```
## TreeQSM Processing Chain
file <- system.file("extdata/QSM.mat", package = "rTwig")
qsm <- import_qsm(file)
cylinder <- qsm$cylinder
cylinder <- update_cylinders(cylinder)

filename <- tempfile(pattern = "TreeQSM_QSM", fileext = ".mat")
export_mat(cylinder, filename)

## SimpleForest Processing Chain
file <- system.file("extdata/QSM.csv", package = "rTwig")
cylinder <- read.csv(file)
cylinder <- update_cylinders(cylinder)

filename <- tempfile(pattern = "SimpleForest_QSM", fileext = ".mat")
export_mat(cylinder, filename)
```

export_mesh

Export Mesh

Description

Exports QSM cylinder mesh using the rgl library

Usage

```
export_mesh(
  cylinder,
  filename,
  radius = NULL,
  color = NULL,
  palette = NULL,
  facets = 6,
  normals = FALSE
)
```

Arguments

cylinder	QSM cylinder data frame
filename	File name and path for exporting. The .ply extension is automatically added if not present.

radius	Radius column name either quoted or unquoted. Defaults to modified cylinders from the cylinder data frame.
color	Optional cylinder color parameter. Colors must be a single hex color string, a <code>grDevices::colors()</code> , a vector of hex colors, or a quoted/unquoted column name. It can also be set to "random" to generate a random solid color, or FALSE to disable color on export. Vectors must have the same length as the cylinder data frame.
palette	Optional color palette for numerical data. Palettes include <code>colourvalues::color_palettes()</code> or a user supplied RGB palette matrix with the length of cylinder.
facets	The number of facets in the polygon cross section. Defaults to 6, but can be increased to improve visual smoothness at the cost of performance and memory.
normals	Option to export normals. Defaults to FALSE, but can be set to TRUE.

Value

A mesh .ply file

Examples

```
## TreeQSM Processing Chain
file <- system.file("extdata/QSM.mat", package = "rTwig")
qsm <- import_qsm(file)
cylinder <- qsm$cylinder
cylinder <- update_cylinders(cylinder)

filename <- tempfile(pattern = "TreeQSM_mesh")
export_mesh(cylinder, filename)

## SimpleForest Processing Chain
file <- system.file("extdata/QSM.csv", package = "rTwig")
cylinder <- read.csv(file)
cylinder <- update_cylinders(cylinder)

filename <- tempfile(pattern = "SimpleForest_mesh")
export_mesh(cylinder, filename)
```

import_qsm

Import TreeQSM

Description

Imports a QSM created by TreeQSM

Usage

```
import_qsm(filename, version = "2.x.x")
```

Arguments

filename a TreeQSM .mat MATLAB file
version TreeQSM version. Defaults to 2.x.x. The user can also specify the 2.0 format.

Value

Returns a list

References

Raunonen P, Kaasalainen M, Åkerblom M, Kaasalainen S, Kaartinen H, Vastaranta M, Holopainen M, Disney M, Lewis P (2013). "Fast Automatic Precision Tree Models from Terrestrial Laser Scanner Data." *Remote Sensing*, **5**(2), 491–520. doi:[10.3390/rs5020491](https://doi.org/10.3390/rs5020491).

Examples

```
## Read a TreeQSM MATLAB file in the 2.3.x - 2.4.x format
file <- system.file("extdata/QSM.mat", package = "rTwig")
qsm <- import_qsm(file, version = "2.x.x")
summary(qsm)

## Read a TreeQSM MATLAB file in the 2.0 format
file <- system.file("extdata/QSM_2.mat", package = "rTwig")
qsm <- import_qsm(file, version = "2.0")
names(qsm)
```

import_treegraph *Import Treegraph*

Description

Imports a QSM created by treegraph

Usage

```
import_treegraph(filename)
```

Arguments

filename a treegraph .json file

Value

Returns a list

References

Yang W, Wilkes P, Vicari MB, Hand K, Calders K, Disney M (2024). “Treegraph: tree architecture from terrestrial laser scanning point clouds.” *Remote Sensing in Ecology and Conservation*. ISSN 2056-3485, doi:10.1002/rse2.399.

Wilkes P, Shenkin A, Disney M, Malhi Y, Bentley LP, Vicari MB (2021). “Terrestrial laser scanning to reconstruct branch architecture from harvested branches.” *Methods in Ecology and Evolution*, **12**, 2487-2500. doi:10.1111/2041210X.13709.

Examples

```
## Not run:  
  
# Import a treegraph QSM  
qsm <- import_treegraph("path/to/json/file")  
  
## End(Not run)
```

plot_qsm

Plot QSM

Description

Efficiently plot QSMs and point clouds. Uses the Rcpp and RGL libraries as backends.

Usage

```
plot_qsm(  
  cylinder = NULL,  
  radius = NULL,  
  color = NULL,  
  palette = NULL,  
  alpha = 1,  
  facets = 6,  
  skeleton = FALSE,  
  skeleton_lwd = NULL,  
  cloud = NULL,  
  pt_color = NULL,  
  pt_size = NULL,  
  triangulation = NULL,  
  tri_color = NULL,  
  tri_palette = NULL,  
  axes = TRUE,  
  axes_color = NULL,  
  grid = FALSE,  
  grid_color = NULL,  
  hover = FALSE,
```

```

    bg_color = NULL,
    lit = TRUE,
    pan = TRUE,
    normalize = FALSE
)

```

Arguments

cylinder	A QSM cylinder data frame.
radius	Radius column name either quoted or unquoted. Defaults to the modified radii.
color	Optional cylinder color parameter. Colors must be a single hex color string, a <code>grDevices::colors()</code> , a vector of hex colors, or a quoted/unquoted column name. It can also be set to "random" to generate a random solid color, or <code>FALSE</code> to disable color on export. Vectors must have the same length as the cylinder data frame.
palette	Optional color palette for numerical data. Palettes include <code>colourvalues::color_palettes()</code> or a user supplied RGB palette matrix with the length of cylinder.
alpha	Set the transparency of the cylinders. Defaults to 1. 1 is opaque and 0 is fully transparent.
facets	The number of facets in the polygon cross section. Defaults to 6, but can be increased to improve visual smoothness at the cost of performance and memory.
skeleton	Plot the QSM skeleton instead of cylinders. Defaults to <code>FALSE</code> .
skeleton_lwd	Skeleton line width. Defaults to 1.
cloud	Point cloud data frame where the first three columns are the x, y, and z coordinates in the same coordinate system as the QSM. Defaults to <code>NULL</code> .
pt_color	Color of the point cloud. Accepts hex colors, <code>grDevices::colors()</code> , or "random". Defaults to black.
pt_size	Size of the points. Defaults to 0.1.
triangulation	Plot the stem triangulation mesh from <code>TreeQSM</code> . Defaults to <code>NULL</code> .
tri_color	Color of the triangulation mesh. Colors must be a single hex color.
tri_palette	Optional triangulation color palette for z values. Supports the same inputs as palettes.
axes	Show plot axes. Defaults to <code>TRUE</code> .
axes_color	Set the axes color. Defaults to black.
grid	Show plot grid lines. Defaults to <code>FALSE</code> .
grid_color	Set grid lines color. Defaults to grey.
hover	Show cylinder and branch id on mouse hover. Defaults to <code>FALSE</code> .
bg_color	Set the background color of the plot. Accepts hex colors or <code>grDevices::colors()</code> . Defaults to white.
lit	Enable light source in plot. Defaults to <code>TRUE</code> . Can be set to <code>FALSE</code> .
pan	Use right mouse button to pan plot. Defaults to <code>TRUE</code> , but is disabled when hover is enabled.
normalize	Normalize the QSM to 0,0,0 based on the provided data. Defaults to <code>FALSE</code> .

Value

A rgl plot

Examples

```
## TreeQSM Processing Chain & Triangulation
file <- system.file("extdata/QSM.mat", package = "rTwig")
qsm <- import_qsm(file)
cylinder <- qsm$cylinder
cylinder <- update_cylinders(cylinder)
plot_qsm(cylinder)

triangulation <- qsm$triangulation
plot_qsm(triangulation = triangulation)
```

prune_qsm

Prune QSM

Description

Efficiently prune a QSM. The user can prune by cylinder, branch, and segment ids, or by height or diameter classes, individually, or all at the same time, and return either the pruned data, the remaining data, or a binary index of which cylinders are pruned.

Usage

```
prune_qsm(
  cylinder,
  cylinder_ids = NULL,
  branch_ids = NULL,
  segment_ids = NULL,
  height_m = NULL,
  diameter_cm = NULL,
  invert = FALSE,
  index = FALSE
)
```

Arguments

cylinder	QSM cylinder data frame
cylinder_ids	A single or vector of cylinder ids. Everything connected above the cylinder is pruned.
branch_ids	A single or vector of branch ids. Everything connected to the branch is pruned.
segment_ids	A single or vector of segment ids. Everything connected above the segment is pruned.

height_m	Height class in meters below which all cylinders are pruned. Valid inputs are numeric to one decimal.
diameter_cm	Branch diameter class in centimeters below which all cylinders are pruned. Valid inputs are numeric to one decimal.
invert	Return the remaining or pruned data. Defaults to TRUE (the remaining data), but can be set to FALSE.
index	Returns a column index called pruning indicating if the cylinder is pruned (1) or un-pruned (0). Defaults to FALSE, but can be set to TRUE.

Value

a data frame

Examples

```
## Load QSM
file <- system.file("extdata/QSM.mat", package = "rTwig")
qsm <- import_qsm(file)
cylinder <- qsm$cylinder
cylinder <- update_cylinders(cylinder)

## Pruning Index
prune1 <- prune_qsm(cylinder, height_m = 2, index = TRUE)
plot_qsm(prune1, color = pruning, palette = "blue2red")

## Remaining
prune2 <- prune_qsm(cylinder, height_m = 2, invert = FALSE)
plot_qsm(prune2)

## Pruned
prune3 <- prune_qsm(cylinder, height_m = 2, invert = TRUE)
plot_qsm(prune3)
```

qsm_summary

QSM Summary

Description

Generates a simple QSM summary (e.g. volume, surface area, dbh, etc.) by totals and branch order.

Usage

```
qsm_summary(cylinder, radius, triangulation = NULL)
```

Arguments

cylinder QSM cylinder data frame
 radius Radius column name either quoted or unquoted.
 triangulation QSM triangulation list. Defaults to NULL. Only supports TreeQSM.

Value

Returns a list

Examples

```
## SimpleForest Processing Chain
file <- system.file("extdata/QSM.csv", package = "rTwig")
cylinder <- read.csv(file)
cylinder <- update_cylinders(cylinder)
qsm_summary(cylinder, radius)

# TreeQSM Triangulation
file <- system.file("extdata/QSM.mat", package = "rTwig")
qsm <- import_qsm(file)
cylinder <- qsm$cylinder
cylinder <- update_cylinders(cylinder)
qsm_summary(cylinder, radius, triangulation = qsm$triangulation)
```

 run_rtwig

Run Real Twig

Description

Runs all Real Twig steps

Usage

```
run_rtwig(
  filename,
  twig_radius,
  metrics = TRUE,
  version = NULL,
  smooth = TRUE,
  standardize = FALSE,
  broken_branch = TRUE
)
```

Arguments

filename	file path to QSM (.mat, .csv, .json)
twig_radius	Twig radius in millimeters
metrics	Calculate tree metrics? Defaults to TRUE.
version	Defaults to NULL. If using a specific version of TreeQSM, the user can specify the version (e.g. 2.4.1, 2.0, etc.).
smooth	Defaults to TRUE, if using TreeQSM. Can be set to FALSE.
standardize	Standardize QSM cylinder data? Defaults to FALSE. Can be set to TRUE.
broken_branch	Enable or disable the broken branch filter. Defaults to TRUE.

Value

Returns cylinder data frame or list if metrics is true.

Examples

```
## TreeQSM
file <- system.file("extdata/QSM.mat", package = "rTwig")
qsm <- run_rtwig(file, twig_radius = 4.23)
str(qsm$cylinder)
```

smooth_qsm

Smooth QSM

Description

Visual smoothing of a QSM by ensuring the midpoints of all cylinders are connected

Usage

```
smooth_qsm(cylinder)
```

Arguments

cylinder	QSM cylinder data frame
----------	-------------------------

Value

Returns a data frame

Examples

```
file <- system.file("extdata/QSM.mat", package = "rTwig")
qsm <- import_qsm(file)
cylinder <- qsm$cylinder
cylinder <- update_cylinders(cylinder)

## Before Smoothing
plot_qsm(cylinder)

## After Smoothing
cylinder <- smooth_qsm(cylinder)
plot_qsm(cylinder)
```

standardize_qsm	<i>Standardize QSM</i>
-----------------	------------------------

Description

Standardizes QSM variable names and ordering across different QSM software

Usage

```
standardize_qsm(cylinder)
```

Arguments

cylinder QSM cylinder data frame

Details

Renames supported QSM software output columns to be consistent. All names are lower case and underscore delimited. See the dictionary vignette for a detailed description of column names. A consistent QSM format ensures maximum compatibility when analyzing QSMs made with different software. This function can be run either before or after `update_cylinders()` has been run, or at any stage.

Value

Returns a data frame

Examples

```
## TreeQSM Processing Chain
file <- system.file("extdata/QSM.mat", package = "rTwig")
qsm <- import_qsm(file)
cylinder <- qsm$cylinder
cylinder <- standardize_qsm(cylinder)
str(cylinder)
```

```
## SimpleForest Processing Chain
file <- system.file("extdata/QSM.csv", package = "rTwig")
cylinder <- read.csv(file)
cylinder <- standardize_qsm(cylinder)
str(cylinder)

## aRchi Processing Chain
file <- system.file("extdata/QSM2.csv", package = "rTwig")
cylinder <- read.csv(file)
cylinder <- standardize_qsm(cylinder)
str(cylinder)
```

tree_metrics

Tree Metrics

Description

Calculates tree metrics from a QSM

Usage

```
tree_metrics(cylinder)
```

Arguments

cylinder QSM cylinder data frame

Details

Calculates detailed tree, branch, and segment metrics from a QSM. Valid inputs require a connected QSM, which can be a whole tree or an individual branch. The outputs include all of the standard outputs from TreeQSM, and also additional variables, including, but not limited to, growth length, reverse branch order, branch segment or node relationships, and distances from twigs and the base of the tree, across various distribution metrics. Also included is a simulated point cloud of the tree, based on the QSM cylinder radii. When corrected with Real Twig, this allows for the testing and validation of point cloud diameter overestimation throughout the tree.

Value

Returns a list of tree metric data frames and synthetic point cloud

References

- Raumonen P, Kaasalainen M, Åkerblom M, Kaasalainen S, Kaartinen H, Vastaranta M, Holopainen M, Disney M, Lewis P (2013). “Fast Automatic Precision Tree Models from Terrestrial Laser Scanner Data.” *Remote Sensing*, **5**(2), 491–520. doi:10.3390/rs5020491.
- Hackenberg J, Spiecker H, Calders K, Disney M, Raumonen P (2015). “SimpleTree —An Efficient Open Source Tool to Build Tree Models from TLS Clouds.” *Forests*, **6**(11), 4245–4294. doi:10.3390/f6114245.
- Hackenberg J, Bontemps J (2023). “Improving quantitative structure models with filters based on allometric scaling theory.” *Applied Geomatics*, **15**. doi:10.1007/s12518023005374.
- Yang W, Wilkes P, Vicari MB, Hand K, Calders K, Disney M (2024). “Treegraph: tree architecture from terrestrial laser scanning point clouds.” *Remote Sensing in Ecology and Conservation*. ISSN 2056-3485, doi:10.1002/rse2.399.

Examples

```
## TreeQSM Processing Chain
file <- system.file("extdata/QSM.mat", package = "rTwig")
cylinder <- import_qsm(file)$cylinder
cylinder <- update_cylinders(cylinder)
metrics <- tree_metrics(cylinder)
names(metrics)

## SimpleForest Processing Chain
file <- system.file("extdata/QSM.csv", package = "rTwig")
cylinder <- read.csv(file)
cylinder <- update_cylinders(cylinder)
metrics <- tree_metrics(cylinder)
names(metrics)
```

twigs

Twig Database

Description

Database of twig radii for common North American tree species

Usage

```
twigs
```

Format

```
twigs:
A data frame containing twig radii measurements
scientific_name The tree's genus and species
```

radius_mm The average twig radius in millimeters
n The twig measurement sample size
min The minimum twig radii from the samples
max The maximum twig radii from the samples
std The standard deviation of twig radii
cv The coefficient of variation of twig radii

update_cylinders	<i>Update Cylinders</i>
------------------	-------------------------

Description

Updates the QSM cylinder data in preparation for radii correction

Usage

```
update_cylinders(cylinder)
```

Arguments

`cylinder` QSM cylinder data frame

Details

Updates and verifies parent-child cylinder relationships and calculates new variables and metrics found throughout the supported QSM software. This function is required to run the rest of the rTwig functions.

Value

Returns a data frame

References

Hackenberg J, Spiecker H, Calders K, Disney M, Raunonen P (2015). “SimpleTree —An Efficient Open Source Tool to Build Tree Models from TLS Clouds.” *Forests*, **6**(11), 4245–4294. [doi:10.3390/f6114245](https://doi.org/10.3390/f6114245).

Hackenberg J, Bontemps J (2023). “Improving quantitative structure models with filters based on allometric scaling theory.” *Applied Geomatics*, **15**. [doi:10.1007/s12518023005374](https://doi.org/10.1007/s12518023005374).

Examples

```
## TreeQSM Processing Chain
file <- system.file("extdata/QSM.mat", package = "rTwig")
qsm <- import_qsm(file)
cylinder <- qsm$cylinder
cylinder <- update_cylinders(cylinder)
str(cylinder)

## SimpleForest Processing Chain
file <- system.file("extdata/QSM.csv", package = "rTwig")
cylinder <- read.csv(file)
cylinder <- update_cylinders(cylinder)
str(cylinder)

## aRchi Processing Chain
file <- system.file("extdata/QSM2.csv", package = "rTwig")
cylinder <- read.csv(file)
cylinder <- update_cylinders(cylinder)
str(cylinder)
```

Index

* datasets

twigs, [17](#)

box_dimension, [2](#)

cluster_cloud, [3](#)

correct_radii, [5](#)

export_mat, [5](#)

export_mesh, [6](#)

import_qsm, [7](#)

import_treegraph, [8](#)

plot_qsm, [9](#)

prune_qsm, [11](#)

qsm_summary, [12](#)

run_rtwig, [13](#)

smooth_qsm, [14](#)

standardize_qsm, [15](#)

tree_metrics, [16](#)

twigs, [17](#)

update_cylinders, [18](#)