

Package: reporter (via r-universe)

July 23, 2026

Type Package

Title Creates Statistical Reports

Version 1.4.8

Maintainer David Bosak <dbosak01@gmail.com>

Description Contains functions to create regulatory-style statistical reports. Originally designed to create tables, listings, and figures for the pharmaceutical, biotechnology, and medical device industries, these reports are generalized enough that they could be used in any industry. Generates text, rich-text, PDF, HTML, and Microsoft Word file formats. The package specializes in printing wide and long tables with automatic page wrapping and splitting. Reports can be produced with a minimum of function calls, and without relying on other table packages. The package supports titles, footnotes, page header, page footers, spanning headers, page by variables, and automatic page numbering.

License CC0

Encoding UTF-8

URL <https://reporter.r-sassy.org>, <https://github.com/dbosak01/reporter>

BugReports <https://github.com/dbosak01/reporter/issues>

Depends R (>= 3.6), common (>= 1.1.0)

Suggests testthat, magrittr, dplyr, tidyr, readr, knitr, rmarkdown, ggplot2, gridExtra, survminer, utils, logr, covr, libr, devEMF, patchwork, tools

Imports fmr (>= 1.5.8), stringi, crayon, jpeg, graphics, grDevices, zip, withr, glue

RoxygenNote 7.3.3

VignetteBuilder knitr

NeedsCompilation no

Author David Bosak [aut, cre], Bill Huang [aut], Kevin Kramer [ctb], Duong Tran [ctb], Raphael Huang [ctb], Archytas Clinical Solutions [cph]

Repository <https://cran.r-universe.dev>

Date/Publication 2026-07-21 04:30:02 UTC

RemoteUrl <https://github.com/cran/reporter>

RemoteRef HEAD

RemoteSha e804125304d2f2ce746ef723bbef7fdde8bb149f

Contents

add_content	3
add_style	5
cell_style	7
column_defaults	8
create_plot	11
create_report	13
create_style	16
create_table	19
create_text	24
define	25
footer_image	30
footnotes	31
ftn	34
get_theme	35
header_image	37
lowercase_parens	38
options_fixed	40
page_by	43
page_footer	47
page_header	49
print.plot_spec	51
print.report_spec	52
print.style_spec	53
print.table_spec	54
print.text_spec	55
report_options	56
set_margins	58
span	60
spanning_header	62
stub	64
title_header	68
titles	70
ttl	73
write_registration_file	74
write_report	76

Index

80

add_content	<i>Add content to a report</i>
-------------	--------------------------------

Description

This function adds an object to the report content list. A report will accept multiple pieces of content. The add_content function also controls overall alignment of the content on the page, and whether there is a page break before or after.

Usage

```
add_content(  
  x,  
  object,  
  page_break = TRUE,  
  align = "center",  
  blank_row = "below"  
)
```

Arguments

x	The report_spec to append content to.
object	The object to append.
page_break	Whether to add a page break after the object. Valid values are TRUE or FALSE. You can manipulate the page_break parameter to add multiple objects to the same page.
align	How to align the content. Valid values are 'left', 'right', 'center', and 'centre'.
blank_row	Whether to put a blank row above or below the content. Valid values are 'above', 'below', 'both', or 'none'.

Details

The add_content function adds a piece of content to a report. For a text report, valid objects are a table or text object. For an RTF, PDF, HTML, or DOCX report, valid objects are a table, text, or plot object. See [create_table](#), [create_text](#), or [create_plot](#) for further information on how to create content objects.

Content will be appended to the report in the order it is added. By default, a page break is added after the content. You can stack two pieces of content together closely by setting the page_break parameter to FALSE, and the blank_row parameter to "none".

Value

The modified report_spec.

See Also

`create_table`, `create_text`, and `create_plot` to create content for a report.

Other report: `create_report()`, `footer_image()`, `footnotes()`, `header_image()`, `options_fixed()`, `page_by()`, `page_footer()`, `page_header()`, `print.report_spec()`, `report_options()`, `set_margins()`, `title_header()`, `titles()`, `write_report()`

Examples

```
library(reporter)
library(magrittr)

# Create temp file path
tmp <- file.path(tempdir(), "mtcars.txt")

# Create first table
tbl1 <- create_table(mtcars[1:5, 1:6]) %>%
  column_defaults(width = .5)

# Create second table
tbl2 <- create_table(mtcars[6:10, 1:6], headerless=TRUE) %>%
  column_defaults(width = .5)

# Create the report object
rpt <- create_report(tmp) %>%
  titles("MTCARS Sample Data", align = "left") %>%
  add_content(tbl1, page_break = FALSE, align = "left", blank_row = "none") %>%
  add_content(tbl2, page_break = FALSE, align = "left") %>%
  add_content(create_text("* NOTE: Above table is actually two tables stacked."))

# Write the report to the file system
res <- write_report(rpt)

# Write report to console
writeLines(readLines(tmp, encoding = "UTF-8"))

# MTCARS Sample Data
#
#   mpg   cyl  disp    hp  drat    wt
#  -----
#    21     6   160   110   3.9   2.62
#    21     6   160   110   3.9   2.875
#   22.8     4   108    93   3.85   2.32
#   21.4     6   258   110   3.08   3.215
#   18.7     8   360   175   3.15   3.44
#   18.1     6   225   105   2.76   3.46
#   14.3     8   360   245   3.21   3.57
#   24.4     4  146.7    62   3.69   3.19
#   22.8     4  140.8    95   3.92   3.15
#   19.2     6  167.6   123   3.92   3.44
#
# * NOTE: Above table is actually two tables stacked.
```

add_style	<i>Add a style object to a report.</i>
-----------	--

Description

This function will add a style object to a report specification. The style may be added either by passing a style object to the `style` parameter, or by passing a theme name to the `theme` parameter.

Usage

```
add_style(rpt, style = NULL, theme = NULL)
```

Arguments

<code>rpt</code>	The report specification to add a style to.
<code>style</code>	A style object which contains style settings to add to the report. This parameter is optional. Default is <code>NULL</code> .
<code>theme</code>	A theme name to use for this report. Valid values are "MidnightBlue", "SteelBlue", "DarkRed", "SeaGreen", "SlateGrey", "Plain", and "SASDefault". Default is <code>NULL</code> .

Details

The `add_style()` function allows you to add styling to HTML reports. This functionality will apply to additional output types in future versions of the **reporter** package.

Styling can be added by passing a named theme to the `theme` parameter, or by creating a style object using the [create_style](#) function and passing that object to the `style` parameter. You may also export a theme as a style object using the [get_theme](#) function, modify it, and pass that to the `style` parameter.

Style Specifications

The style specification is created using the [create_style](#) function, and provides the most styling flexibility. The style object allows you to control background colors, font colors, border colors, and more. Colors can be specified using an RGB hex code, or an HTML/CSS-compliant color name. See the [create_style](#) documentation for additional information.

Themes

There are currently seven themes available: "MidnightBlue", "SteelBlue", "DarkRed", "SeaGreen", "SlateGrey", "Plain", and "SASDefault". All themes use Arial 10pt font. These themes are intended to provide a basic set of examples on how to create styles. Themes can be used by passing the theme name to the `theme` parameter on the `add_style()` function. The theme will assign a variety of style settings according to the specifics of the theme. For example, the "MidnightBlue" theme sets the title font and header background colors to "MidnightBlue" and sets the border color to "Grey".

To view theme style settings, you can use [get_theme](#) function. This function will return the theme as a style object. See the [get_theme](#) documentation for further details.

See Also

Other styles: `create_style()`, `get_theme()`, `print.style_spec()`

Examples

```
library(reporter)
library(magrittr)

# Prepare data
dat <- as.data.frame(HairEyeColor)
dat <- dat[dat$Freq >= 10, ]

## Example 1: Use Pre-defined Theme ##

# Create temp file path
tmp1 <- file.path(tempdir(), "HairAndEyes1.html")

# Create table object
tbl <- create_table(dat, borders = "outside") %>%
  titles("Hair and Eye Colors with Theme") %>%
  column_defaults(width = .6)

# Create report and add theme
rpt <- create_report(tmp1, output_type = "HTML") %>%
  add_content(tbl) %>%
  add_style(theme = "SteelBlue")

# Write out the report
write_report(rpt)

# Uncomment to View report
# file.show(tmp1)

#' ## Example 2: Create Custom Style ##

# Create temp file path
tmp2 <- file.path(tempdir(), "HairAndEyes2.html")

# Define custom style
sty <- create_style(font_name = "Times",
  font_size = 10,
  title_font_size = 12,
  title_font_bold = TRUE,
  title_font_color = "Blue",
  table_header_background = "Blue",
  table_header_font_bold = TRUE,
  table_header_font_color = "White",
  table_body_background = "White",
  table_body_stripe = "Red")

# Create table object
tbl <- create_table(dat, borders = "outside") %>%
```

```

titles("Hair and Eye Colors with Style") %>%
column_defaults(width = .6)

# Create report and add style spec
rpt <- create_report(tmp2, output_type = "HTML") %>%
  add_content(tbl) %>%
  add_style(style = sty)

# Write out the report
write_report(rpt)

# Uncomment to View report
# file.show(tmp2)

```

cell_style

A style specification for a table cell

Description

A class to define the style for a cell in a table. This class can be assigned to the "style" parameter of a [define](#) function, a [stub](#) function, or a [column_defaults](#) function. When assigned, the cell style will apply to some or all of the cells in the relevant columns. The "indicator" parameter identifies a column in the table to trigger the style. Alternatively, the "labelrow", "blankrow", or "datarow" shortcuts may be used to identify cells for styling.

Usage

```
cell_style(indicator = NULL, bold = FALSE)
```

Arguments

indicator	A keyword or column name to indicate which rows the cell style should be applied to. Valid keywords are "labelrow", "blankrow", or "datarow". To use an indicator column, create a column on the input dataset that has a TRUE value for each row that you want the cell style applied. Then pass the name of the column to the indicator parameter. If you do not want to see the indicator column on the report, set the "visible" property on the define function to FALSE for that column. The default value of the indicator parameter is NULL, meaning to apply the style to all rows.
bold	Whether to bold the text in the cell. Valid values are TRUE and FALSE. The default is FALSE.

Examples

```

library(reporter)
library(magrittr)

# Create temporary path

```

```

tmp <- file.path(tempdir(), "table1.rtf")

# Prepare data
df <- data.frame(names = rownames(mtcars), mtcars[, 1:3])

# Set indicator variable
df$mpgind <- ifelse(df$mpg > 20, TRUE, FALSE)

# Create table
tbl <- create_table(df, first_row_blank = TRUE,
                    header_bold = TRUE, borders = c("top", "bottom")) %>%
  column_defaults(style = cell_style(bold = TRUE, indicator = "mpgind")) %>%
  define(names, label = "Car Name") %>%
  define(mpg, label = "Miles Per Gallon") %>%
  define(cyl, label = "Cylinders") %>%
  define(displ, label = "Displacement") %>%
  define(mpgind, visible = FALSE) %>%
  titles("Table 1.0", "MTCARS with Indicator Variable",
        borders = "none", bold = TRUE, font_size = 11) %>%
  footnotes("* Motor Trend, 1974", borders = "none", blank_row = "none")

# Create report and add custom style
rpt <- create_report(tmp, output_type = "RTF", font = "Arial") %>%
  add_content(tbl)

# Write out report
write_report(rpt)

# View report
# file.show(tmp)

```

column_defaults

Set default attributes for one or more columns

Description

A function to set default attributes for columns on a table. The `column_defaults` function contains a subset of the parameters on the `define` function that can be shared across variables. Any attributes set by `column_defaults` can be overridden by the `define` function. The overall purpose of the function is to minimize redundancy in column definitions.

Usage

```

column_defaults(
  x,
  vars = NULL,
  from = NULL,
  to = NULL,
  label = NULL,

```

```

    format = NULL,
    align = NULL,
    label_align = NULL,
    width = NULL,
    n = NULL,
    standard_eval = FALSE,
    style = NULL
  )

```

Arguments

x	A table spec.
vars	The variable name or names to define defaults for. Variable names may be quoted or unquoted. The parameter will also accept integer column positions instead of names. For multiple variables, pass the names or positions as a vector. If you want to pass an R variable of names, set the <code>standard_eval</code> parameter to <code>TRUE</code> . The <code>standard_eval</code> parameter is useful when writing functions that construct reports dynamically.
from	The variable name or position that starts a column range. If passed as a variable name, it may be quoted or unquoted.
to	The variable name or position that ends a column range. If passed as a variable name, it may be quoted or unquoted.
label	The label to use for a column header. This label will be applied to all variables assigned to the <code>column_defaults</code> function.
format	The format to use for the column data. The format can be a string format, a formatting function, a lookup list, a user-defined format, or a formatting list. All formatting is performed by the fmtr package. For additional information, see the help for that package.
align	The column alignment. Valid values are "left", "right", "center", and "centre".
label_align	How to align the header labels for this column. Valid values are "left", "right", "center", and "centre".
width	The width of the column in the specified units of measure. The units of measure are specified on the <code>units</code> parameter of the create_report function. If no width is supplied, the write_report function will assign a default width based on the width of the column data and the label. <code>write_report</code> will not set a column width less than the width of the largest word in the data or label. In other words, <code>write_report</code> will not break words.
n	The <code>n</code> value to place in the "N=" header label. Formatting for the <code>n</code> value will be performed by the formatting function assigned to the <code>n_format</code> parameter on create_table .
standard_eval	A <code>TRUE</code> or <code>FALSE</code> value that indicates whether to use standard or non-standard evaluation of the <code>vars</code> , <code>from</code> , and <code>to</code> parameters. Set <code>standard_eval</code> to <code>TRUE</code> if you want to pass the column names as variables. Default is <code>FALSE</code> , meaning it will use non-standard (unquoted) evaluation.
style	A cell_style object that defines a style for all columns associated with the column defaults.

Details

Column defaults can be specified for multiple variables. By default, the function will apply to all variables. Alternately, you can specify a vector of columns on the `vars` parameter, or a range of columns using the `from` and `to` parameters. Both the `vars` parameters and the `from` and `to` parameters will accept column positions, quoted variable names, or unquoted variable names.

The parameters that can be set with the `column_defaults` include the formatting attributes `'width'`, `'justify'`, `'label'`, and `'format'`. Any parameters set with `column_defaults` will override any attributes set on the data frame.

Note that you may call the `column_defaults` function multiple times on the same table specification. Typically, multiple `column_defaults` calls would be made with a different set or range of variables.

Value

The modified table spec.

See Also

Other table: [create_table\(\)](#), [define\(\)](#), [print.table_spec\(\)](#), [spanning_header\(\)](#), [stub\(\)](#)

Examples

```
library(reporter)
library(magrittr)

# Create temp file name
tmp <- file.path(tempdir(), "mtcars.txt")

# Prepare data
dat <- mtcars[1:10, ]
dat <- data.frame(vehicle = rownames(dat), dat, stringsAsFactors = FALSE)

# Define table
tbl <- create_table(dat, show_cols = 1:8) %>%
  column_defaults(from = mpg, to = qsec, width = .5, format = "%.1f") %>%
  define(vehicle, label = "Vehicle", width = 1.5, align = "left") %>%
  define(c(cyl, hp), format = "%.0f")

# Create the report
rpt <- create_report(tmp, orientation = "portrait") %>%
  titles("Table 2.5", "MTCARS Sample Report") %>%
  add_content(tbl)

# Write the report
write_report(rpt)

# Send report to console for viewing
writeLines(readLines(tmp, encoding = "UTF-8"))

#                                     Table 2.5
```

```

#                               MTCARS Sample Report
#
#  Vehicle                mpg   cyl  disp    hp  drat    wt   qsec
#  -----
#  Mazda RX4               21.0    6  160.0   110   3.9    2.6   16.5
#  Mazda RX4 Wag           21.0    6  160.0   110   3.9    2.9   17.0
#  Datsun 710               22.8    4  108.0    93   3.8    2.3   18.6
#  Hornet 4 Drive           21.4    6  258.0   110   3.1    3.2   19.4
#  Hornet Sportabout        18.7    8  360.0   175   3.1    3.4   17.0
#  Valiant                  18.1    6  225.0   105   2.8    3.5   20.2
#  Duster 360               14.3    8  360.0   245   3.2    3.6   15.8
#  Merc 240D                24.4    4  146.7    62   3.7    3.2   20.0
#  Merc 230                 22.8    4  140.8    95   3.9    3.1   22.9
#  Merc 280                 19.2    6  167.6   123   3.9    3.4   18.3
#

```

create_plot

Create plot content

Description

Function to create a plot specification that can be added as content to a report. The `create_plot` function can be used to include charts, graphs, and figures on a statistical report. The function supports plot objects returned by `ggplot` or `ggsurvplot`. It does not support the Base R plot function.

Usage

```
create_plot(x, height, width, borders = "none")
```

Arguments

<code>x</code>	The plot to create. Specifically, this parameter should be set to an object returned from a call to <code>ggplot</code> or <code>ggsurvplot</code> . This parameter also accepts a path to a JPEG file. If a path is specified, the image will be appended to the report at the point the content object is added. For RTF and DOCX files, the function additionally accepts a path to an EMF file.
<code>height</code>	The height of the plot in the specified units of measure.
<code>width</code>	The width of the plot in the specified units of measure.
<code>borders</code>	Whether and where to place a border. Valid values are 'top', 'bottom', 'left', 'right', 'all', 'none', and 'outside'. Default is 'none'. The 'left', 'right', and 'outside' border specifications do not apply to TXT reports.

Details

To add a plot to a report, use the `create_plot` function. The function allows you to set a width and height for the plot. The function will preserve any other geometries you apply to the plot. See the [add_content](#) function to control page breaking and blank spaces above or below the plot.

A plot specification accepts a [page_by](#) function. If a page by is applied to the plot, the plot data will be subset by the page by variable, and re-run for each subset.

The plot specification also accepts titles and footnotes. See the [titles](#) and [footnotes](#) functions for further details.

The function also accepts a path to an image file stored on the file system instead of a plot object. This functionality was added to allow the user to create figures from other plotting packages. If you pass an image path, the image will be inserted into the report at the location specified. The system supports JPEG images for all output types that support graphics. EMF images are also supported for DOCX and RTF outputs. Note that EMF format may not render properly in all operating environments, and JPEG is the preferred image type.

Value

The plot specification.

See Also

[titles](#) to add a title block to the plot, [footnotes](#) to add footnotes, and [add_content](#) to add the plot object to a report.

Other plot: [print.plot_spec\(\)](#)

Examples

```
library(reporter)
library(ggplot2)
library(magrittr)

# Create temp file path
tmp <- file.path(tempdir(), "mtcars.rtf")

# Create ggplot
p <- ggplot(mtcars, aes(x=cyl, y=mpg)) + geom_point()

# Create plot object
plt <- create_plot(p, height = 4, width = 8)

rpt <- create_report(tmp, font = "Arial", output_type = "RTF") %>%
  page_header("Client", "Study: XYZ") %>%
  titles("Figure 1.0", "MTCARS Miles per Cylinder Plot") %>%
  set_margins(top = 1, bottom = 1) %>%
  add_content(plt) %>%
  footnotes("* Motor Trend, 1974") %>%
  page_footer("Time", "Confidential", "Page [pg] of [tpg]")

# Write out report
```

```

write_report(rpt)

# Uncomment to view RTF file
# shell.exec(tmp)

```

create_report

Create a report

Description

Creates a report shell to which you may add titles, footnotes, content, etc.

Usage

```

create_report(
  file_path = "",
  output_type = "TXT",
  orientation = "landscape",
  units = "inches",
  paper_size = "letter",
  missing = "",
  font = "Courier",
  font_size = NULL
)

```

Arguments

file_path	The output path of the desired report. Either a full path or a relative path is acceptable. This parameter is not required to create the report_spec object, but will be required to write the report. In addition, the file extension is not required. If the file extension is not supplied, the write_report function will add a file extension based on the output_type specified.
output_type	The report output type. Default is "TXT". Valid values are "TXT", "RTF", "PDF", "HTML", and "DOCX".
orientation	The page orientation of the desired report. Valid values are "landscape" or "portrait". The default page orientation is "landscape".
units	Specifies the units of measurement. This setting will indicate the units for columns widths, margins, paper size, and other measurements. Valid values are "inches" or "cm" (centimeters). Default value is "inches".
paper_size	The expected paper size on which the report may be printed. The paper_size will determine how much text can fit on one page. Valid values are "letter", "legal", "A4", and "RD4". Default is "letter". For the HTML output type, a paper size of "none" is also valid. That means the HTML will be generated in an unbounded manner as a typical web page. For a custom page size, the parameter also accepts a double vector with the page width and height. The width and height should be in the report units of measure, and assume a portrait orientation.

missing	How to display missing values in the report. Default is to replace them with an empty string, which removes them from the report. To display missing values as is, set the missing parameter to NULL. To replace missing values with a character string (such as ".", "-", or "<NA>") pass the desired character string to the missing parameter.
font	The font to use on the report. The font specified will be used for the entire report. Valid values are "Courier", "Arial", "Times", and "fixed". The value of "fixed" will create a fixed-width, text style report in Courier font. The font parameter only applies to RTF, HTML, PDF, and DOCX reports. The default value is "Courier".
font_size	The size of the font to use on the report. The font_size specified will be used for the entire report. Valid values are 8, 9, 10, 11, and 12. The font_size parameter only applies to RTF, PDF, HTML, and DOCX output types. The default value is 10.

Details

This function is the constructor for the report object. The report object contains information needed to create a report. The object is defined as an S3 object, and has a class of 'report_spec'.

The report object holds information concerning report page size, orientation, titles, footnotes, page header, page footer, margins, and other options. Use the [add_content](#) function to add content to the report. The report may be written to a file using the [write_report](#) function.

Value

A new report_spec object.

Report family of functions

The report is the primary container for report specifications. The following functions add additional specifications to the report object initialized with `create_report`.

- [titles](#) to add titles to the report.
- [footnotes](#) to add footnotes to the report.
- [title_header](#) to add a title header to the report.
- [page_header](#) to add a page header to the report.
- [page_footer](#) to add a page_footer to the report.
- [add_content](#) to add content to the report.
- [report_options](#) to set options for most reports.
- [options_fixed](#) to set options for fixed-width output.
- [add_content](#) to add content to the report.
- [write_report](#) to write the report to the file system.

The report family of functions are pipe-friendly. After creating the report, you may pipe the object to any of the above functions to append additional options.

See Also

`create_table`, `create_text`, and `create_plot` functions to create content for the report.

Other report: `add_content()`, `footer_image()`, `footnotes()`, `header_image()`, `options_fixed()`, `page_by()`, `page_footer()`, `page_header()`, `print.report_spec()`, `report_options()`, `set_margins()`, `title_header()`, `titles()`, `write_report()`

Examples

```
library(reporter)
library(magrittr)

# Create temp file path
tmp <- file.path(tempdir(), "airquality.txt")

# Prepare Data
dat <- airquality[sample(1:153, 15), ]
dat$Month <- as.Date(paste0("1973-", dat$Month, "-01"))

# Define table
tbl <- create_table(dat, show_cols = c("Month", "Day", "Wind", "Temp", "Ozone")) %>%
  titles("Table 9.6", "Air Quality Sample Report") %>%
  column_defaults(width = .5) %>%
  define(Month, format = "%B", align = "left", width = 1) %>%
  define(Temp, format = "%.0f") %>%
  footnotes("* New York, May to September 1973")

# Define report
rpt <- create_report(tmp, orientation = "portrait", missing = "-") %>%
  add_content(tbl)

# Write the report to the file system
write_report(rpt)

# Write the report to the console
writeLines(readLines(tmp, encoding = "UTF-8"))
```

```
#
#           Table 9.6
#       Air Quality Sample Report
#
#   Month      Day  Wind  Temp  Ozone
#   -----
#   July        8   6.3   92    97
#   July        9   5.7   92    97
#   August       1   6.9   81    39
#   July       23  11.5   82     -
#   June        9  13.8   90    71
#   July       12  14.3   73   10
#   July        4  10.9   84     -
#   May        31   7.4   76    37
#   September   30  11.5   68    20
#   June       25    8    75     -
```

```
#      June      28  11.5   80    -
#      August    18   7.4   76    23
#      June      20  10.3   76    13
#      July       1   4.1   84   135
#      May       23   9.7   61     4
#
#      * New York, May to September 1973
```

create_style	<i>Creates a style object</i>
--------------	-------------------------------

Description

This function will create a style object to control background colors and font settings on your report. The style object can be applied to a report using the [add_style](#) function. Currently, styles may only be applied to HTML reports.

Usage

```
create_style(
  font_name = NULL,
  font_size = NULL,
  text_color = NULL,
  background_color = NULL,
  title_font_size = NULL,
  title_font_bold = NULL,
  title_font_color = NULL,
  title_background = NULL,
  footnote_font_bold = NULL,
  footnote_font_color = NULL,
  footnote_background = NULL,
  border_color = NULL,
  table_header_background = NULL,
  table_header_font_bold = NULL,
  table_header_font_color = NULL,
  table_body_background = NULL,
  table_body_stripe = NULL,
  table_body_font_color = NULL,
  table_stub_background = NULL,
  table_stub_font_color = NULL,
  table_stub_font_bold = NULL,
  table_label_row_bold = NULL
)
```

Arguments

font_name	The name of the font to use on the report. Valid values are "Courier", "Arial", or "Times". The default is "Courier".
-----------	---

font_size	The default font size to use for the report. This font size will be used for all text, unless overridden by another font size parameter.
text_color	The default color to use for all text in the report. This parameter will apply to the entire report, unless overridden by other font color settings.
background_color	The color to use for the background of the report. This color will appear everywhere on the document unless overridden by another color specification.
title_font_size	The font size to use for the title font in points.
title_font_bold	Whether to bold the title or not. Valid values are TRUE or FALSE. By default, the title will not be bold.
title_font_color	The color to use for the title font.
title_background	The background color for the title block.
footnote_font_bold	Whether to bold the footnote or not. Valid values are TRUE or FALSE. By default, the footnote will not be bold.
footnote_font_color	The font color to use for footnotes.
footnote_background	The color to be used for the background of footnotes.
border_color	The color to use for all borders in the report. By default, the border will be black.
table_header_background	The background color to use in the table header. This color may be different than the background color used in the table body.
table_header_font_bold	Whether to bold the header labels or not. Valid values are TRUE and FALSE. By default, the header will not be bold.
table_header_font_color	The font color to use on the table header.
table_body_background	The background color to use in the body of any table in the report.
table_body_stripe	The background color to use for every other row in a table. The stripe color is used in conjunction with the body background color to perform table striping. The stripe color will start on the second row.
table_body_font_color	The font color to use for the body of any table in the report.
table_stub_background	The background color to use for the stub column, if one exists on the table.
table_stub_font_color	The font color to be used for the stub column, if one exists on the table.

table_stub_font_bold

Whether or not to bold the stub column. Valid values are TRUE and FALSE.

table_label_row_bold

Whether or not to bold the label row on a stub column. This parameter is so you can bold the label row, but not the values in the stub column. Valid values are TRUE and FALSE.

Details

The style object contains style settings for a report. The style object allows you to control background colors and font specifications such as font size, font color, and font bold. The style object can be created once and reused on many reports. See the [add_style](#) function to learn how to add the style object to a report.

Note that styles will be applied uniformly to the entire report. Also note that at present, styles can be used only on HTML output types. Future versions of the **reporter** package will provide style support for other output types.

On the style object, colors for background and fonts may be passed as an RGB hex code or a color name. For example, the color red may be passed as the hex code "#FF0000" or as the color name "Red". Color names must conform to HTML/CSS standards. These color names can be easily discovered on the internet. A sample of common color names is presented below.

Color Names

Many of the parameters on the style object accept a color name or code. The values accepted for these parameters follow standard HTML/CSS style color values. Below is a sample of common color names that can be used to specify colors with the `create_style` function. These color names should be passed as a quoted string:

- **Primary and Secondary Colors:** Black, White, Red, Yellow, Blue, Green, Orange, Purple and Brown.
- **Common Shades:** Beige, Crimson, Gold, Indigo, Ivory, Lavender, Maroon, Navy, Olive, Pink, Plum, RoyalBlue, Silver, Teal, Turquoise, Violet
- **Shades of White:** AntiqueWhite, Azure, GhostWhite, SeaShell, Snow, WhiteSmoke
- **Shades of Grey:** Grey, Gray, DarkGray, DarkGrey, DimGray, DimGrey, LightGray, LightGrey, SlateGray, SlateGrey
- **Shades of Blue:** AliceBlue, CadetBlue, CornflowerBlue, DodgerBlue, PowderBlue, LightBlue, MidnightBlue, SkyBlue, SlateBlue, SteelBlue
- **Earth Colors:** Beige, Bisque, BurlyWood, ForestGreen, Khaki, Linen, SandyBrown, SaddleBrown, Salmon, SeaGreen, Sienna, Tan, Thistle, Wheat
- **Bright Colors:** Aqua, Aquamarine, BlueViolet, Cyan, Fuchsia, HotPink, Lime, Magenta, OrangeRed, SpringGreen

See Also

Other styles: [add_style\(\)](#), [get_theme\(\)](#), [print.style_spec\(\)](#)

Examples

```

library(reporter)
library(magrittr)

# Prepare data
dat <- data.frame(stub = rownames(mtcars), mtcars)
dat <- dat[1:15, ]

# Create temp file path
tmp <- file.path(tempdir(), "HairAndEyes2.html")

# Define custom style
sty <- create_style(font_name = "Arial",
                    font_size = 10,
                    background_color = "WhiteSmoke",
                    border_color = "Grey",
                    title_font_size = 12,
                    title_font_bold = TRUE,
                    title_font_color = "SteelBlue",
                    table_header_background = "Tan",
                    table_header_font_bold = TRUE,
                    table_header_font_color = "White",
                    table_body_background = "White",
                    table_body_stripe = "Wheat",
                    table_stub_background = "Tan",
                    table_stub_font_color = "White")

# Create table object
tbl <- create_table(dat, borders = "all") %>%
  titles("MTCARS Dataset With Style") %>%
  column_defaults(width = .5) %>%
  define(stub, label = "Car Make and Model", width = 1.5)

# Create report and add style spec
rpt <- create_report(tmp, output_type = "HTML") %>%
  add_content(tbl) %>%
  add_style(style = sty)

# Write out the report
write_report(rpt)

# Uncomment to View report
# file.show(tmp)

```

create_table

*Create a table***Description**

The `create_table` function creates a table object to which further specifications can be added. The object can be added to a report using the `add_content` function. The object is implemented as an

S3 object of class 'table_spec'.

Usage

```
create_table(
  x,
  show_cols = "all",
  use_attributes = "all",
  width = NULL,
  first_row_blank = FALSE,
  n_format = upcase_parens,
  headerless = FALSE,
  borders = "none",
  header_bold = FALSE,
  continuous = FALSE,
  page_wrap = NULL,
  auto_page = NULL
)
```

Arguments

- | | |
|----------------|---|
| x | The data frame or tibble from which to create the table object. |
| show_cols | This parameter gives control over which columns in the input data to display on the report by default. Valid values are 'all', 'none', a vector of quoted column names, or a vector of column positions. 'all' means show all columns, unless overridden by the column definitions. 'none' means don't show any columns unless specified in the column definitions. If a vector of column names or positions is supplied, those columns will be shown in the report in the order specified, whether or not a definition is supplied. See the define function for additional information on how to show/hide report columns. |
| use_attributes | Whether or not to use any formatting attributes assigned to the columns on the input data frame. Valid values are 'all', 'none', or a vector of attribute names to use. Possible attributes that may be used are 'label', 'format', 'width', and 'justify'. By default, any of these attribute values will be applied to the table. For example, if you assign a label to the 'label' attribute of a data frame column, pass that data frame into create_table, and don't override the label value on a define function, the label will appear as a column header on the table. The use_attributes parameter allows you to control this default behavior, and use or ignore data frame attributes as desired. |
| width | The expected width of the table in the report units of measure. By default, the width setting is NULL, and columns will be sized according to the width of the data and labels. If the width parameter is set, the function will attempt to size the table to the specified width. If the sum of the column widths is less than the specified width, the function will adjust the columns widths proportionally to fit the specified width. If the sum of the column widths is wider than the table width parameter value, the table width parameter will be ignored. |

first_row_blank	Whether to place a blank row under the table header. Valid values are TRUE or FALSE. Default is FALSE.
n_format	The formatting function to apply to the header "N=" label. The default formatting function is upcase_parens .
headerless	Whether to create a headerless table. A headerless table displays the table data only. Default is FALSE, meaning the table will have a header.
borders	Whether and where to place a border. Valid values are 'top', 'bottom', 'left', 'right', 'all', 'none', 'outside', 'inside', and 'body'. Default is 'none'. The 'left', 'right', 'outside', 'inside', and 'body' border specifications only apply to RTF, HTML, PDF, and DOCX reports. The 'body' border specification means put borders around only the body of the table.
header_bold	Whether or not the column headers on the tables should be bolded. Valid values are TRUE and FALSE. The default is FALSE.
continuous	If a table crosses multiple pages, it is normally broken into a separate table for each page, and the titles and footnotes are repeated on each page. When the "continuous" parameter is TRUE, the table will instead be a single table, and the titles and footnotes will not be repeated on each page. This parameter currently only works for RTF outputs. Also, this parameter only works for titles and footnotes that are attached to the table body. Titles and footnotes attached to the report will still be shown on every page.
page_wrap	Whether to use automatic page wrapping when there are too many columns fit within the calculated content area. Default is TRUE, meaning automatic page wrapping is on. Set it to FALSE to disable this feature and control page wrapping yourself.
auto_page	Whether to use auto pagination. Default is TRUE. A value of FALSE will disable auto pagination, and let you control page breaking yourself using the 'page_break' variable on the define function. The "auto_page" value on create_table will override the corresponding setting in the report_options . Please note that turning off auto pagination may cause page overflows.

Details

A table object is a container to hold information about a table. The only required information for a table is the table data. All other parameters and functions are optional.

By default, the table will display all columns in the data frame. To change this default, use the `show_cols` parameter. Setting this parameter to 'none' will display none of the columns in the data, unless they are explicitly defined with a [define](#) function.

The `show_cols` parameter also accepts a vector of column positions or column names. When a vector is supplied, `create_table` will display only those columns on the report, in the order encountered in the vector. The `show_cols` parameter is the only mechanism in `create_table` to modify the column order. Otherwise, modify the order prior to sending the data to `create_table` using the many options available in Base R or supplemental packages.

Setting Formatting Attributes

Formatting attributes can be controlled in three ways. By default, formatting attributes assigned to the data frame will be passed through to the reporting functions. The reporting functions will recognize the 'label', 'format', 'width', and 'justify' attributes. In other words, you can control the column label, width, format, and alignment of your report columns simply by assigning those attributes to your data frame. The advantage of using attributes assigned to data frame columns is that you can store those attributes permanently with the data frame, and those attributes will not have to be re-specified for each report. To ignore attributes assigned to the data frame, set the `use_attributes` parameter to 'none'.

Secondly, attributes can be specified using the `column_defaults` function. This function allows the user to apply a default set of parameters to one or more columns. If no columns are specified in the `var` or `from` and `to` parameter of this function, the defaults will apply to all columns. Any default parameter value can be overridden by the `define` function.

Lastly, the `define` function provides the most control over column parameters. This function provides a significant amount of functionality that cannot be specified elsewhere. See the `define` function for additional information. The `define` function will also override any formatting attributes assigned to the data frame, or anything set by the `column_defaults` function.

Additional Functionality

The `create_table` function also provides the capabilities to create a "headerless" table. A headerless table is useful when combining two tables into one report. The example below illustrates use of a headerless table.

Since the purpose of the **reporter** package is to create statistical reports, the `create_table` function makes it easy to add population counts to the table header. These population counts are added to column labels and spanning header labels using the `n` parameter on the `define` or `spanning_header` functions. The population count is formatted according to the `n_format` parameter on `create_table`. The **reporter** package provides four population count formatting functions. You may create your own formatting function if one of these functions does not meet your needs. See `upcase_parens` for further details.

See Also

`create_report` to create a report, `create_plot` to create a plot, `create_text` to create text content, and `add_content` to append content to a report. Also see the `titles`, `footnotes`, and `page_by` functions to add those items to the table if desired.

Other table: `column_defaults()`, `define()`, `print.table_spec()`, `spanning_header()`, `stub()`

Examples

```
library(reporter)
library(magrittr)

# Create temp file path
tmp <- file.path(tempdir(), "mtcars.txt")

#Subset cars data
dat <- mtcars[1:10, 1:7]
```

```

# Calculate means for all columns
dat_sum <- data.frame(all_cars = "All cars average", as.list(sapply(dat, mean)),
                     stringsAsFactors = FALSE)

# Get vehicle names into first column
dat_mod <- data.frame(vehicle = rownames(dat), dat, stringsAsFactors = FALSE)

# Create table for averages
tbl1 <- create_table(dat_sum) %>%
  titles("Table 1.0", "MTCARS Sample Data") %>%
  column_defaults(width = .5) %>%
  define(all_cars, label = "", width = 2) %>%
  define(mpg, format = "%.1f") %>%
  define(dis, format = "%.1f") %>%
  define(hp, format = "%.0f") %>%
  define(qsec, format = "%.2f")

# Create table for modified data
tbl2 <- create_table(dat_mod, headerless = TRUE) %>%
  column_defaults(width = .5) %>%
  define(vehicle, width = 2)

# Create the report object
rpt <- create_report(tmp) %>%
  add_content(tbl1, align = "left", page_break = FALSE) %>%
  add_content(tbl2, align = "left")

# Write the report to the file system
write_report(rpt)

# Write report to console
writeLines(readLines(tmp, encoding = "UTF-8"))

```

```

#
#                               Table 1.0
#                               MTCARS Sample Data
#
#                               mpg    cyl  disp    hp  drat    wt  qsec
# -----
# All cars average           20.4    5.8  208.6   123  3.538  3.128  18.58
#
# Mazda RX4                  21      6   160    110   3.9    2.62  16.46
# Mazda RX4 Wag              21      6   160    110   3.9    2.875  17.02
# Datsun 710                  22.8    4   108    93    3.85   2.32  18.61
# Hornet 4 Drive              21.4    6   258    110   3.08   3.215  19.44
# Hornet Sportabout          18.7    8   360    175   3.15   3.44  17.02
# Valiant                     18.1    6   225    105   2.76   3.46  20.22
# Duster 360                  14.3    8   360    245   3.21   3.57  15.84
# Merc 240D                   24.4    4  146.7    62   3.69   3.19   20
# Merc 230                     22.8    4  140.8    95   3.92   3.15  22.9
# Merc 280                     19.2    6  167.6   123   3.92   3.44  18.3
#

```

create_text

Create text content

Description

Function to create a text specification that can be added as content to a report. The text content can be used to include analysis on a statistical report. A text specification is an S3 object of class 'text_spec'.

Usage

```
create_text(txt, width = NULL, align = "left", borders = "none")
```

Arguments

txt	The text to create.
width	The width of the text in the specified units of measure. If no width is specified, the full page width will be used.
align	How to align the text within the content area. Valid values are 'left', 'right', 'center', or 'centre'. Default is 'left'.
borders	Whether and where to place a border. Valid values are 'top', 'bottom', 'left', 'right', 'all', 'none', and 'outside'. Default is 'none'. The 'left', 'right', and 'outside' border specifications only apply to RTF reports.

Details

To add plain text to a report, use the `create_text` function. The function allows you to set a width and alignment for the text. The function will preserve any other formatting you apply to the text. See the [add_content](#) function to control page breaking and blanks spaces above or below the text.

The text specification also accepts titles and footnotes. See the [titles](#) and [footnotes](#) functions for further details.

Value

The text specification.

See Also

[titles](#) to add a title block to the text, [footnotes](#) to add footnotes, and [add_content](#) to add the text object to a report.

Other text: [print.text_spec\(\)](#)

Examples

```
library(reporter)
library(magrittr)

# Create temp file path
tmp <- file.path(tempdir(), "mtcars.txt")

# Create dummy text
dt <- paste0("Lorem ipsum dolor sit amet, consectetur adipiscing elit, ",
  "sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. ",
  "Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris ",
  "nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in ",
  "reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla ",
  "pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa ",
  "qui officia deserunt mollit anim id est laborum.")

# Create the text object
txt <- create_text(dt) %>%
  titles("Text Content 1.0", "Sample Text Report") %>%
  footnotes("* Cicero, 1st century BCE")

# Create the report object
rpt <- create_report(tmp, orientation = "portrait") %>%
  add_content(txt)

# Write the report to the file system
write_report(rpt)

# Write the report to console
writeLines(readLines(tmp, encoding = "UTF-8"))

#                               Text Content 1.0
#                               Sample Text Report
#
# Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor
# incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis
# nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat.
# Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore
# eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt
# in culpa qui officia deserunt mollit anim id est laborum.
#
# * Cicero, 1st century BCE
#
```

define

Defines a column

Description

A function to define a table column. The define function contains a variety of a parameters to control the appearance of the report. Using the define function, you can control simple options

like column alignment and width, but also control more sophisticated options like page wrapping and page breaking.

Usage

```
define(
  x,
  vars,
  label = NULL,
  format = NULL,
  align = NULL,
  label_align = NULL,
  width = NULL,
  visible = TRUE,
  n = NULL,
  blank_after = FALSE,
  blank_before = FALSE,
  dedupe = FALSE,
  id_var = FALSE,
  page_wrap = FALSE,
  page_break = FALSE,
  indent = NULL,
  label_row = FALSE,
  standard_eval = FALSE,
  style = NULL,
  group_border = FALSE,
  group_cohesion = FALSE,
  break_label = NULL
)
```

Arguments

<code>x</code>	The table spec.
<code>vars</code>	The variable name or names to define a column for. Names may be quoted or unquoted. If defining for multiple variables, pass them as a vector of names. If you want to pass an R variable of names, set the <code>standard_eval</code> parameter to <code>TRUE</code> . The <code>standard_eval</code> parameter is useful when writing functions that construct reports dynamically.
<code>label</code>	The label to use for the column header. If a label is assigned to the <code>label</code> column attribute, it will be used as a default. Otherwise, the column name will be used.
<code>format</code>	The format to use for the column data. The format can be a string format, a formatting function, a lookup list, a user-defined format, or a formatting list. All formatting is performed by the fapply function from the fmtr package. For a list of common formatting codes, see FormattingStrings .
<code>align</code>	The column alignment. Valid values are "left", "right", "center", and "centre". By default, text columns will be left aligned and numeric columns will be right aligned.

label_align	How to align the header labels for this column. Valid values are "left", "right", "center", and "centre". By default, the label alignment will follow any alignment set on the column align parameter.
width	The width of the column in the specified units of measure. The units of measure are specified on the units parameter of the create_report function. If no width is supplied, the write_report function will assign a default width based on the width of the column data and the label. write_report will not set a column width less than the width of the largest word in the data or label. In other words, write_report will not break words.
visible	Whether or not the column should be visible on the report. This parameter can be used as a simple way to drop columns from the report.
n	The n value to place in the "N=" header label. Formatting for the n value will be performed by the formatting function assigned to the n_format parameter on create_table .
blank_after	Whether to place a blank row after unique values of this variable. Valid values are TRUE or FALSE. Default is FALSE.
blank_before	Whether to place a blank row before unique values of this variable. Valid values are TRUE or FALSE. Default is FALSE.
dedupe	Whether to dedupe the values for this variable. Variables that are deduped only show the value on the first row of each group. This option is commonly used for grouping variables.
id_var	Whether this variable should be considered an ID variable. ID variables are retained on each page when the page is wrapped. ID variables are also moved to the far left of the page.
page_wrap	Force a page wrap on this variable. A page wrap is a vertical page break necessary when the table is too wide to fit on a single page. The excess variables will be wrapped to the next page. Page wraps will continue until all columns are displayed. Use the id_var parameter to identify rows across wrapped pages.
page_break	You may control when page breaks occur by defining a page break variable yourself, and setting this parameter to TRUE for that variable. Only one page break variable can be defined per table. If two or more variables are defined as a page break, an error will be generated.
indent	How much to indent the column values. The parameter takes a numeric value that will be interpreted according to the units (Unit Of Measure) setting on the report. This parameter can be used to help create a stub column. The default value is NULL, meaning the column should not be indented. See the stub function for additional information on creating a stub column.
label_row	Whether the values of the variable should be used to create a label row. Valid values are TRUE or FALSE. Default is FALSE. If label_row is set to TRUE, the dedupe parameter will also be set to TRUE. This parameter is often used in conjunction with the stub function and indent parameter to create a stub column.
standard_eval	A TRUE or FALSE value indicating whether to use standard evaluation on the vars parameter value. Default is FALSE. Set this parameter to TRUE if you want to pass the vars value(s) using a variable.

<code>style</code>	A cell_style object that defines the desired style for this column. The cell style object can be used to define conditional styling.
<code>group_border</code>	Adds a horizontal border at the end of a group. Valid values are TRUE or FALSE. Default is FALSE. The group border is another way to separate analysis groups, and can be used in addition to or instead of the "blank_before" and "blank_after" parameters.
<code>group_cohesion</code>	Default is FALSE. If TRUE, it would avoid splitting the same group across multiple pages with default strength 0.2. Users can increase the strength to make groups on the same page more likely. The accepted value is 0 to 1.
<code>break_label</code>	Decide whether to repeat the grouping value when the group spans multiple pages. If set it as TRUE, when a group spans, the break label will be displayed as a label of the first row. If set it as a text such as "(Continued)", it would be used as a suffix text. E.g., Investigation (Continued).

Details

Column definitions are optional. By default, all columns in the data are displayed in the order assigned to the data frame.

The report will use attributes assigned to the data frame such as 'width', 'justify', 'label', and 'format'. In other words, some control over the column formatting is available by manipulating the data frame attributes prior to assigning the data frame to `create_table`. See [create_table](#) for more details.

The `define` function is used to provide additional control over column appearance. For example, you may use the `define` function to assign an "N=" population count, eliminate duplicates from the column, or place a blank row after each unique value of the variable. See the parameter documentation for additional options.

Some of the parameters on the `define` function are used in the creation of a table stub. Specifically, the `label_row` and `indent` parameters participate in the creation of the stub column. See the [stub](#) function for further information.

A single column definition may be defined for multiple variables. To create a definition for multiple variables, pass the variables as a quoted or unquoted vector. When creating a single definition for multiple variables, the parameters will be unified across those variables. Note that some parameters (such as `page_break`) may only be set once per report, and cannot be shared across multiple variables.

Value

The modified table spec.

See Also

Other table: [column_defaults\(\)](#), [create_table\(\)](#), [print.table_spec\(\)](#), [spanning_header\(\)](#), [stub\(\)](#)

Examples

```

library(reporter)
library(magrittr)

# Create temp file name
tmp <- file.path(tempdir(), "mtcars.txt")

# Prepare data
dat <- mtcars[1:10, ]
dat <- data.frame(vehicle = rownames(dat), dat, stringsAsFactors = FALSE)

# Define table
tbl <- create_table(dat, show_cols = 1:8) %>%
  define(vehicle, label = "Vehicle", width = 3, id_var = TRUE, align = "left") %>%
  define(mpg, label = "Miles per Gallon", width = 1) %>%
  define(cyl, label = "Cylinders", format = "%.1f") %>%
  define(displ, label = "Displacement") %>%
  define(hp, label = "Horsepower", page_wrap = TRUE) %>%
  define(drat, visible = FALSE) %>%
  define(wt, label = "Weight") %>%
  define(qsec, label = "Quarter Mile Time", width = 1.5)

# Create the report
rpt <- create_report(tmp, orientation = "portrait") %>%
  titles("Listing 2.0", "MTCARS Data Listing with Page Wrap") %>%
  add_content(tbl, align = "left") %>%
  page_footer(right = "Page [pg] of [tpg]")

# Write the report
write_report(rpt)

# Send report to console for viewing
writeLines(readLines(tmp, encoding = "UTF-8"))

#
#                               Listing 2.0
#                               MTCARS Data Listing with Page Wrap
#
#                               Miles per
# Vehicle                      Gallon Cylinders Displacement
# -----
# Mazda RX4                     21      6.0      160
# Mazda RX4 Wag                 21      6.0      160
# Datsun 710                    22.8     4.0     108
# Hornet 4 Drive                21.4     6.0     258
# Hornet Sportabout            18.7     8.0     360
# Valiant                      18.1     6.0     225
# Duster 360                   14.3     8.0     360
# Merc 240D                    24.4     4.0    146.7
# Merc 230                     22.8     4.0    140.8
# Merc 280                     19.2     6.0    167.6
#

```

```
# ...
#
#
#                                     Page 1 of 2
#
#               Listing 2.0
#       MTCARS Data Listing with Page Wrap
#
# Vehicle                                Horsepower Weight   Quarter Mile Time
# -----
# Mazda RX4                               110    2.62              16.46
# Mazda RX4 Wag                           110    2.875             17.02
# Datsun 710                              93     2.32              18.61
# Hornet 4 Drive                          110    3.215             19.44
# Hornet Sportabout                       175    3.44              17.02
# Valiant                                 105    3.46              20.22
# Duster 360                             245    3.57              15.84
# Merc 240D                               62     3.19                20
# Merc 230                               95     3.15              22.9
# Merc 280                               123    3.44              18.3
#
# ...
#
#                                     Page 2 of 2
```

footer_image

Insert an image into the page footer

Description

The `footer_image` function inserts an image into the page footer. The function can be used to add a logo or other graphical element to the report. The image will then appear at the bottom of each page.

Usage

```
footer_image(x, image_path, height, width, align = "left")
```

Arguments

x	The report object to insert the image into.
image_path	The path of image file. Function accepts JPG images for RTF, DOCX, PDF, and HTML output types. Function also accepts PNG images for RTF, DOCX, and HTML output types.
height	Desired height of the image, in the report units of measure.
width	Desired width of the image, in the report units of measure.
align	Alignment of the image in the page footer. Valid values are "left", "right", "center", or "centre". The default value is "left".

Details

The function assumes the existence of a page footer inserted by the [page_footer](#) function. If there is no page footer, an error will be generated during the rendering process in [write_report](#). If there is text in the same cell as the image, the text will be disregarded. You may add text to other cells in the footer.

The "align" parameter determines which page footer cell the image will be inserted. That is, if you align an image "left", it will be inserted into the left column of the page footer. Options are "left", "right", and "center". To insert images in multiple cells, you may use multiple calls to [image_footer](#).

The page footer cell width will take priority over the image width. That is, if you set the image width larger than the cell width, the image width will be reduced to fit the cell. To make a wider image, increase the cell width on the page footer.

Note that page footer cells can be removed entirely by setting the width to zero. This feature can give you more room for a wide image. For instance, to create a banner image under the entire report, align the image "center" and set the left and right page header column widths to zero.

See the [page_footer](#) function for more information on setting footer column widths. For a demonstration of a header image insertion, see `vignette("reporter-hfimage")`.

Value

The modified report specification.

See Also

Other report: [add_content\(\)](#), [create_report\(\)](#), [footnotes\(\)](#), [header_image\(\)](#), [options_fixed\(\)](#), [page_by\(\)](#), [page_footer\(\)](#), [page_header\(\)](#), [print.report_spec\(\)](#), [report_options\(\)](#), [set_margins\(\)](#), [title_header\(\)](#), [titles\(\)](#), [write_report\(\)](#)

footnotes

Adds a footnote block

Description

The `footnotes` function adds one or more footnotes to the report. If added to the report specification, the footnotes will be added to the page template, and thus appear on each page of the report. Footnotes may also be added directly to table, text, or plot content.

Usage

```
footnotes(
  x,
  ...,
  align = "left",
  blank_row = "above",
  borders = "none",
```

```

    valign = NULL,
    width = NULL,
    footer = FALSE,
    italics = FALSE,
    columns = 1,
    font_size = NULL
)

```

Arguments

<code>x</code>	The object to assign footnotes to.
<code>...</code>	A set of footnote strings.
<code>align</code>	The position to align the footnotes. Valid values are: 'left', 'right', 'center', or 'centre'.
<code>blank_row</code>	Whether to print a blank row above or below the footnote. Valid values are 'above', 'below', 'both', or 'none'. Default is 'above'.
<code>borders</code>	Whether to print a border above or below the footnote. Valid values are 'top', 'bottom', 'outside', 'inside', 'all', or 'none'. Default is 'none'. For fixed width reports, the border character will be taken from the value of the <code>uchar</code> parameter on the options_fixed function. The 'left', 'right', 'outside', and 'inside' border specifications only apply to RTF, HTML, PDF, and DOCX reports.
<code>valign</code>	The vertical position to align the footnotes. Valid values are: 'top' and 'bottom'. For footnotes attached to a report, default is 'bottom'. For footnotes attached to content, default is 'top'.
<code>width</code>	The width of the footnotes block. If the footnotes are attached to the report, valid values are 'page' or a numeric width, and the default is 'page'. If the footnotes are attached to the table, plot, or text content, the valid values are 'page', 'content' or a numeric value, and the default is 'content'. The value 'content' means the footnotes will be aligned to the width of the table, plot, or text content. The value 'page' means the footnotes will be aligned to the width of the page. In addition to these two convenience settings, you may also specify a specific width in the current unit of measure. The unit of measure is determined by the 'units' parameter on create_report .
<code>footer</code>	Whether to put the footnotes in the page footer. Valid values are TRUE and FALSE. Default is FALSE. This parameter only works with RTF and DOCX output types. It also only applies to footnotes assigned to the report object. Footnotes in the page footer will appear on every page, and be the same throughout the report.
<code>italics</code>	A TRUE or FALSE value indicating whether the footnote text should be in italics font. If TRUE, the entire footnote will be in italics.
<code>columns</code>	The number of columns for the footnote block. Valid values are 1, 2, and 3. Default is 1. If this parameter is set to 2, the footnote block will be split into two columns, each aligned to the outside. If this parameter is set to 3, the title block will be split into 3 columns, with the outer columns aligned to the outside and the middle column aligned center. Footnotes are assigned to cells from top left to bottom right.

font_size The font size to use for the footnote block. The font size of the report will be used by default. Valid values are 8, 9, 10, 11, 12 This parameter only applies to variable-width RTF, HTML, PDF, and DOCX output types.

Details

The `footnotes` function accepts a set of strings of the desired footnote text. The footnotes may be aligned center, left or right using the `align` parameter. The user is responsible for adding desired footnote symbols. Footnote symbols will not be generated automatically.

If footnotes are assigned to the report, alignment will be oriented to the page body. If footnotes are assigned to a table or text, alignment will be oriented to the edge of the content.

One footnote function accepts up to 25 footnotes. However, multiple footnote blocks may be added to the same object.

Blank rows above or below the footnote block may be controlled using the `blank_row` parameter.

Each footnote string must fit within the available space. The **reporter** package will not wrap footnotes on fixed-width reports. If a footnote does not fit within the available space, a warning will be generated and the footnote will be truncated. In these situations, either shorten the footnote or split it into multiple footnotes that each fit within the available space.

Value

The modified report.

See Also

Other report: `add_content()`, `create_report()`, `footer_image()`, `header_image()`, `options_fixed()`, `page_by()`, `page_footer()`, `page_header()`, `print.report_spec()`, `report_options()`, `set_margins()`, `title_header()`, `titles()`, `write_report()`

Examples

```
library(reporter)
library(magrittr)

# Create a temporary file
tmp <- file.path(tempdir(), "expenses.txt")

# Prepare data
dat <- data.frame(category = rownames(USPersonalExpenditure),
                  USPersonalExpenditure, stringsAsFactors = FALSE)

# Define table
tbl <- create_table(dat) %>%
  titles("Table 1.0", "US Personal Expenditures from 1940 - 1960") %>%
  column_defaults(from = X1940, to = X1960, width = .6, format = "$%.2f") %>%
  define(category, label = "Category") %>%
  define(X1940, label = "1940") %>%
  define(X1945, label = "1945") %>%
  define(X1950, label = "1950") %>%
  define(X1955, label = "1955") %>%
```

```

define(X1960, label = "1960") %>%
  footnotes("* In billions of dollars")

# Define report
rpt <- create_report(tmp, orientation="portrait") %>%
  add_content(tbl)

# Write the report
write_report(rpt)

# Display in console
writeLines(readLines(tmp, encoding = "UTF-8"))

#
#               Table 1.0
#           US Personal Expenditures from 1940 - 1960
#
#   Category          1940    1945    1950    1955    1960
#   -----
#   Food and Tobacco   $22.20 $44.50 $59.60 $73.20 $86.80
#   Household Operation $10.50 $15.50 $29.00 $36.50 $46.20
#   Medical and Health  $3.53  $5.76  $9.71 $14.00 $21.10
#   Personal Care       $1.04  $1.98  $2.45  $3.40  $5.40
#   Private Education   $0.34  $0.97  $1.80  $2.60  $3.64
#
#   * In billions of dollars

```

ftn

Creates a footnote attribute

Description

The `ftn` function creates a footnote attribute, which may be attached as an attribute to a data frame and passed into `create_table`. This function is used internally to the system.

Usage

```

ftn(
  footnotes,
  align = "left",
  blank_row = "above",
  borders = "none",
  valign = NULL,
  width = NULL
)

```

Arguments

`footnotes` A vector of footnote strings.

align	The position to align the footnotes. Valid values are: 'left', 'right', 'center', or 'centre'.
blank_row	Whether to print a blank row above or below the footnote. Valid values are 'above', 'below', 'both', or 'none'. Default is 'above'.
borders	Whether to print a border above or below the footnote. Valid values are 'top', 'bottom', 'outside', 'inside', 'all', or 'none'. Default is 'none'.
valign	The vertical position to align the footnotes. Valid values are: 'top' and 'bottom'.
width	The width of the footnotes block.

Value

The footnote attribute object.

See Also

[footnotes](#) to create a footnote.

Other attributes: [span\(\)](#), [ttl\(\)](#)

get_theme

Get a theme

Description

This function will return a style object for a specified theme. There are currently seven themes available. The returned object may be modified and applied to a report using [add_style](#).

Usage

```
get_theme(theme)
```

Arguments

theme	A string that contains the desired theme name to return. Valid values are "MidnightBlue", "SteelBlue", "DarkRed", "SeaGreen", "SlateGrey", "Plain", and "SAS-Default".
-------	--

See Also

Other styles: [add_style\(\)](#), [create_style\(\)](#), [print.style_spec\(\)](#)

Examples

```

library(reporter)
library(magrittr)

# Get theme
tm <- get_theme("SteelBlue")

# View theme settings
print(tm)
## A style specification:
#- font_name: 'Arial'
#- font_size: 10
#- text_color: 'DimGrey'
#- title_font_size: 11
#- title_font_bold: TRUE
#- title_font_color: 'SteelBlue'
#- border_color: 'Grey'
#- table_header_background: 'SteelBlue'
#- table_header_font_bold: TRUE
#- table_header_font_color: 'LightGrey'
#- table_body_background: 'White'
#- table_body_stripe: 'WhiteSmoke'
#- table_stub_background: 'SteelBlue'
#- table_stub_font_color: 'LightGrey'
#- table_stub_font_bold: TRUE

# Modify theme
tm$font_size <- 12
tm$title_font_size <- 13

# Create temp file path
tmp <- file.path(tempdir(), "HairAndEyes.html")

# Get data
dat <- as.data.frame(HairEyeColor)

# Create table object
tbl <- create_table(dat[dat$Freq >= 10, ],
  borders = "outside") %>%
  titles("Hair and Eye Colors")

# Use modified theme
rpt <- create_report(tmp, output_type = "HTML") %>%
  add_content(tbl) %>%
  add_style(tm)

# Write out the report
write_report(rpt)

# Uncomment to View report
# file.show(tmp)

```

header_image	<i>Insert an image into the page header</i>
--------------	---

Description

The `header_image` function inserts an image into the page header. The function can be used to add a logo or other graphical element to the report. The image will then appear at the top of each page.

Usage

```
header_image(x, image_path, height, width, align = "left")
```

Arguments

<code>x</code>	The report object.
<code>image_path</code>	The path of image file. Function accepts JPG images for RTF, DOCX, PDF, and HTML output types. Function also accepts PNG images for RTF, DOCX, and HTML output types.
<code>height</code>	Desired height of the image, in the report units of measure.
<code>width</code>	Desired width of the image, in the report units of measure.
<code>align</code>	Alignment of the image. Valid values are "left", "right", "center", or "centre". The default value is "left".

Details

The function assumes the existence of a page header inserted by the [page_header](#) function. If there is no page header, an error will be generated during the rendering process in [write_report](#). If there is text in the same cell as the image, the text will be disregarded. You may add text to other cells in the header.

The "align" parameter determines which page header cell the image will be inserted. That is, if you align an image "left", it will be inserted into the left column of the page header. Options are "left", "right", and "center". To insert images in multiple cells, you may use multiple calls to `image_header`.

The page header cell width will take priority over the image width. That is, if you set the image width larger than the cell width, the image width will be reduced to fit the cell. To make a wider image, increase the cell width on the page header.

Note that page header cells can be removed entirely by setting the width to zero. This feature can give you more room for a wide image. For instance, to create a banner image over the entire report, align the image "center" and set the left and right page header column widths to zero.

See the [page_header](#) function for more information on setting header column widths. For a demonstration of a header image insertion, see `vignette("reporter-hfimage")`.

Value

The modified report specification.

See Also

Other report: [add_content\(\)](#), [create_report\(\)](#), [footer_image\(\)](#), [footnotes\(\)](#), [options_fixed\(\)](#), [page_by\(\)](#), [page_footer\(\)](#), [page_header\(\)](#), [print.report_spec\(\)](#), [report_options\(\)](#), [set_margins\(\)](#), [title_header\(\)](#), [titles\(\)](#), [write_report\(\)](#)

lowercase_parens

Functions to format the population label

Description

These functions are used to format the "N=" population label on column headers.

Usage

```
lowercase_parens(x)
```

```
uppercase_parens(x)
```

```
lowercase_n(x)
```

```
uppercase_n(x)
```

Arguments

x Population count

Details

Which function to use to format the population label is specified on the `n_format` parameter on the [create_table](#) function. These formatting functions provide several options for formatting the "N=", including whether the "N" should be upper case or lower case, and whether or not to put the value in parentheses. If one of these options does not meet the specifications for your report, you may also write your own formatting function and pass it to the `n_format` function. When an N value is supplied, the output of this function will be concatenated to the header label.

See Also

[create_table](#) function to create a table.

Examples

```
# Create test data
l <- "Label"
n <- 47

cat(paste0(l, lowercase_parens(n)))
# Label
# (n=47)
```

```

cat(paste0(1, upcase_parens(n)))
# Label
# (N=47)

cat(paste0(1, lowercase_n(n)))
# Label
# n=47

cat(paste0(1, upcase_n(n)))
# Label
# N=47

customN <- function(n) {
  return(paste0(" N=", n))
}
cat(paste0(1, customN(n)))
# Label: N=47

## Use alternate n format ##
library(reporter)
library(magrittr)

tmp <- tempfile(fileext = ".txt")

# Prepare data
df <- read.table(header = TRUE, text = '
  Hair Group1 Group2
  Black   25    16
  Brown   13    18
  Blonde   5     7
  Red      2     1')

# Create table with lowercase n formatting
tbl <- create_table(df, n_format=lowercase_n) %>%
  titles("Hair Color") %>%
  define(Group1, n = 45) %>%
  define(Group2, n = 42)

# Create report
rpt <- create_report(tmp) %>%
  add_content(tbl, align = "left")

# Write to file system
write_report(rpt)

writeLines(readLines(tmp))
#      Hair Color
#
#      Group1 Group2
# Hair      n=45  n=42
# -----
# Black      25    16

```

# Brown	13	18
# Blonde	5	7
# Red	2	1

options_fixed	<i>Set options for a fixed-width report</i>
---------------	---

Description

This function sets the options for a report with a fixed width font.

Usage

```
options_fixed(  
  x,  
  editor = NULL,  
  cpuom = NULL,  
  lpuom = NULL,  
  min_margin = NULL,  
  blank_margins = FALSE,  
  font_size = NULL,  
  line_size = NULL,  
  line_count = NULL,  
  uchar = ""  
)
```

Arguments

x	The report spec.
editor	The expected text editor to use for printing text reports. Assigning this parameter will set the cpuom and lpuom parameters appropriately for the text editor. Valid values are 'notepad', 'word', 'wordpad', 'notepad++', and 'editplus'. If the editor parameter is used, any settings for cpuom and lpuom will be ignored. It is not necessary to set this parameter for RTF and PDF reports.
cpuom	Characters per unit of measure of printed text. If units is inches, the default is 12. If units is centimeters (cm), the default is 4.687. This value will be used to determine how many characters can fit on a line.
lpuom	Lines per unit of measure of the printed text. Default for inches is 6. The default for centimeters (cm) is 2.55. This value will be used to determine the number of lines that can fit on a page.
min_margin	The editor minimum margin. This parameter normally defaults to 0, but may be set for some types of editors.
blank_margins	When this option is TRUE, reporter will use blank spaces and blank rows to create left and top margins, rather than rely on the editor to set margins. When used, editor margins should be set to zero. Valid values are TRUE and FALSE. Default is FALSE. This option is only valid for output_type = 'TXT'.

font_size	The size of the font in points. Default is 10pt. This option is only valid for output types RTF and PDF. Valid values are 8, 9, 10, 11, and 12.
line_size	The number of characters that will fit on a line. Normally, the line_size is calculated based on the page size, font size, and cpuom. You can override the calculated value by setting the line_size directly.
line_count	The number of lines that will fit on page. Normally, the line_count is calculated based on the page size, font size, and lpuom. You can override the calculated value by setting the line_count directly.
uchar	The character to use for underlines on the table header and spanning headers. Default is a Unicode macron character #U00AF. You may use a dash or underscore if your editor does not support Unicode. The uchar is forced to a dash for PDF output, as the LaTeX converter does not support the macron character.

Details

The options_fixed function sets options for reports with a fixed-width, monospace font. These reports are based off a text report, but may be output as type "RTF" or "PDF".

Value

The updated report spec.

Text Reports

The options_fixed function sets the characters per unit of measure (cpuom) and lines per unit of measure (lpuom) settings for the report. These settings determine how many characters and lines will fit within one unit of measure (uom), as specified on the [create_report](#) function. These settings are important to ensure the report content stays within the available page size and margins. Because every editor allows a different number of characters and lines on a page, these settings must be adjusted depending on the editor.

The options_fixed function provides a shortcut editor parameter to directly specify a popular editor. If this parameter is specified, the function will set the characters per unit of measure and lines per unit of measure for you. If the editor is not available in the editor parameter selections, for best results, you should set the cpuom and lpuom parameters manually. To determine your cpuom and lpuom, see the help for [write_registration_file](#).

Alternatively, using the options_fixed function, you may set the line_size and line_count directly. Note that the line_size and line_count may be different for different output types and editors.

The min_margin parameter is used to set the minimum margin allowed by the editor. This value will be subtracted from the margin settings when the blank_margins option is used. It is useful for editors that do not calculate margins from the edge of the page.

As some editors do not support Unicode characters, it may be necessary to change the character used for the header and spanning header underlines. The default character is a Unicode #U00AF macron. The macron is sometimes referred to as an "overline", since it is located at the top of the character area. If your editor does not support Unicode, the macron will not be displayed properly. In this case, change the underline character to a dash ("-") or an underscore ("_") using the uchar parameter.

RTF and PDF Reports

For RTF and PDF reports, most of the parameters on the `options_fixed` function do not apply. For RTF and PDF reports, these parameters will be set automatically, and cannot be changed.

Some of the `options_fixed` function apply only to RTF and PDF. In particular, the `font_size` parameter applies only to RTF and PDF reports. Valid font size options are 8, 9, 10, 11, and 12. The font size may also be set on the `create_report` function.

See Also

`create_report` to create a report and set the unit of measure, `write_registration_file` to determine the characters and lines per unit of measure manually.

Other report: `add_content()`, `create_report()`, `footer_image()`, `footnotes()`, `header_image()`, `page_by()`, `page_footer()`, `page_header()`, `print.report_spec()`, `report_options()`, `set_margins()`, `title_header()`, `titles()`, `write_report()`

Examples

```
library(reporter)
library(magrittr)

# Create a temporary file
tmp <- file.path(tempdir(), "bod.txt")

# Define table
tbl <- create_table(BOD, width = 2.5) %>%
  titles("Table 3.6", "BOD* Sample Report") %>%
  define(Time, format = "Day %s", align = "left") %>%
  define(demand, format = "%2.1f mg/l", label = "Demand") %>%
  footnotes("* Biochemical Oxygen Demand")

# Define report #1 - No blank margins
rpt <- create_report(tmp, orientation="portrait") %>%
  add_content(tbl, align = "left")

# Write the report
write_report(rpt)

# Write report to console
writeLines(readLines(tmp, encoding = "UTF-8"))

#           Table 3.6
#       BOD* Sample Report
#
# Time                      Demand
# -----
# Day 1                      8.3 mg/l
# Day 2                     10.3 mg/l
# Day 3                     19.0 mg/l
# Day 4                     16.0 mg/l
# Day 5                     15.6 mg/l
# Day 7                     19.8 mg/l
```

```
#
# * Biochemical Oxygen Demand

# Define report #2 - blank margins
rpt <- create_report(tmp, orientation="portrait") %>%
  options_fixed(blank_margins = TRUE) %>%
  set_margins(top = .5, left = 1) %>%
  add_content(tbl, align = "left")

# Write the report
write_report(rpt)

# Write report to console
writeLines(readLines(tmp, encoding = "UTF-8"))
```

```
#
#
#                                     Table 3.6
#                               BOD* Sample Report
#
#      Time                                Demand
#      -----
#      Day 1                             8.3 mg/l
#      Day 2                            10.3 mg/l
#      Day 3                             19.0 mg/l
#      Day 4                             16.0 mg/l
#      Day 5                             15.6 mg/l
#      Day 7                             19.8 mg/l
#
#      * Biochemical Oxygen Demand
```

page_by	Adds a page by variable
---------	-------------------------

Description

The `page_by` function adds a page by variable to a report, table, or plot. The page by will generate a page break for each value of the page by variable. A label will appear above the content showing the page by variable value. You must be sort the data by the page by variable prior to reporting.

Usage

```
page_by(
  x,
  var,
  label = NULL,
  align = "left",
  blank_row = "below",
```

```

    borders = "none",
    format = NULL,
    bold = FALSE
)

```

Arguments

x	The report specification to assign the page by to.
var	The page by variable. There can be only one page by per report, and one page by variable. The page by can be passed either quoted or unquoted.
label	A label to be used as a prefix to the page by variable value. By default, the label will be assigned to the variable name. Alternatively, you may specify a string value to use for the label.
align	How to align the page by. Default value is 'left'. Valid values are 'left', 'right', 'center', or 'centre'.
blank_row	Indicates whether a blank row is desired above or below the page by. Default value is 'none'. Valid values are 'above', 'below', 'both', or 'none'.
borders	Whether and where to place a border. Valid values are 'top', 'bottom', 'left', 'right', 'all', 'outside', or 'none'. Default is "none". The 'left' and 'right' border specifications only apply to RTF, HTML, PDF, and DOCX reports.
format	The format to use for the page by column data. The format can be a string format, a formatting function, a lookup list, a user-defined format, or a formatting list. All formatting is performed by the fapply function from the fmr package. For a list of common formatting codes, see FormattingStrings .
bold	A parameter to bold the page by text. Valid values are TRUE, FALSE, 'label' or 'value'. Default is FALSE. A value of TRUE bolds both the label and the page by value. The value 'label' bolds only the label, while a value of 'value' bolds only the page by value. This parameter applies to variable-width RTF, HTML, PDF, and DOCX output types only.

Details

Only one page by function is allowed per report, table, or plot. The page by label will appear on all pages of the object. The page by label may be aligned on the left, right, or center. Use the align parameter to specify the alignment.

You must sort the data by the page by variable prior to reporting. The page by labels will appear in the sorted order. Failure to sort the page by variable prior to reporting may produce unexpected results.

See Also

[create_table](#) to create a table, and [create_plot](#) to create a plot.

Other report: [add_content\(\)](#), [create_report\(\)](#), [footer_image\(\)](#), [footnotes\(\)](#), [header_image\(\)](#), [options_fixed\(\)](#), [page_footer\(\)](#), [page_header\(\)](#), [print.report_spec\(\)](#), [report_options\(\)](#), [set_margins\(\)](#), [title_header\(\)](#), [titles\(\)](#), [write_report\(\)](#)

Examples

```

library(reporter)
library(magrittr)

# Create temp file path
tmp <- file.path(tempdir(), "iris.txt")

# Sample and sort iris data frame
dat <- iris[sample(1:150, 50), ]
dat <- dat[order(dat$Species), ]

# Create table
tbl <- create_table(dat) %>%
  page_by(Species, "Species: ") %>%
  define(Species, visible = FALSE)

# Create the report object
rpt <- create_report(tmp, orientation = "portrait") %>%
  page_header("Sponsor: Iris Society", "Study: flowers") %>%
  titles("Table 2.0", "IRIS Sample Report with Page By") %>%
  add_content(tbl) %>%
  page_footer(Sys.time(), right = "Page [pg] of [tpg]")

# Write the report to the file system
write_report(rpt)

# Write report to console
writeLines(readLines(tmp, encoding = "UTF-8"))

# Sponsor: Iris Society                                     Study: flowers
#
#                               Table 2.0
#                               IRIS Sample Report with Page By
#
#                               Species: setosa
#
#                               Sepal.Length Sepal.Width Petal.Length Petal.Width
#                               -----
#                               5.4           3.9           1.7           0.4
#                               4.9           3.1           1.5           0.1
#                               4.8           3.1           1.6           0.2
#                               5.1           3.5           1.4           0.3
#                               5            3.5           1.6           0.6
#                               5            3.3           1.4           0.2
#                               4.4           3            1.3           0.2
#                               5.1           3.5           1.4           0.2
#                               5.4           3.4           1.5           0.4
#                               4.9           3.6           1.4           0.1
#                               4.6           3.1           1.5           0.2
#                               4.6           3.2           1.4           0.2
#                               5.1           3.3           1.7           0.5
# ...
# 2020-10-25 19:33:35                                     Page 1 of 3

```

```

#
# Sponsor: Iris Society
#
#                               Table 2.0
#                               IRIS Sample Report with Page By
#
#                               Species: versicolor
#
#                               Sepal.Length Sepal.Width Petal.Length Petal.Width
#                               -----
#                               4.9           2.4           3.3           1
#                               6.3           3.3           4.7           1.6
#                               6.1           2.8           4.7           1.2
#                               6           2.9           4.5           1.5
#                               6.7           3           5           1.7
#                               5.6           3           4.5           1.5
#                               5.8           2.7           4.1           1
#                               6.7           3.1           4.7           1.5
#                               6.1           2.9           4.7           1.4
#                               5           2           3.5           1
#                               5.9           3.2           4.8           1.8
#                               5.5           2.5           4           1.3
#                               7           3.2           4.7           1.4
#                               6.3           2.3           4.4           1.3
#                               6.1           2.8           4           1.3
#                               6           2.2           4           1
#                               5.5           2.6           4.4           1.2
#                               6           3.4           4.5           1.6
#                               5           2.3           3.3           1
#                               5.5           2.4           3.7           1
# ...
# 2020-10-25 19:33:35

```

Page 2 of 3

```

# Sponsor: Iris Society
#
#                               Table 2.0
#                               IRIS Sample Report with Page By
#
#                               Species: versicolor
#
#                               Sepal.Length Sepal.Width Petal.Length Petal.Width
#                               -----
#                               6.3           3.4           5.6           2.4
#                               7.9           3.8           6.4           2
#                               6.7           3.1           5.6           2.4
#                               6.2           2.8           4.8           1.8
#                               6.7           3.3           5.7           2.5
#                               6.2           3.4           5.4           2.3
#                               5.6           2.8           4.9           2
#                               7.7           3.8           6.7           2.2
#                               7.7           2.6           6.9           2.3
#                               6.9           3.1           5.4           2.1
#                               6.5           3.2           5.1           2
#                               6.1           2.6           5.6           1.4
#                               5.7           2.5           5           2

```

Study: flowers

#	6.5	3	5.8	2.2
#	6.3	2.8	5.1	1.5
#	7.6	3	6.6	2.1
#	6.3	2.5	5	1.9
# ...				
# 2020-10-25 19:33:35				

Page 3 of 3

page_footer	Adds a page footer
-------------	--------------------

Description

This function adds a page footer to the report. The page footer will appear on each page of the report, at the bottom of the page. The page footer contains three sections: left, center, and right. Content for each section may be specified with the appropriate parameter.

Usage

```
page_footer(  
  x,  
  left = "",  
  center = "",  
  right = "",  
  blank_row = "above",  
  width = NULL  
)
```

Arguments

x	The report spec object.
left	The left page footer text. May be a single string or a vector of strings.
center	The center page footer text. May be a single string or a vector of strings.
right	The right page footer text. May be a single string or a vector of strings.
blank_row	Whether to create a blank row above the page footer. Valid values are 'above' and 'none'. Default is 'above'.
width	Widths for left, center, and right columns of the page footer, passed as a vector of double values in the report unit of measure. If the vector contains fewer than three widths, the widths passed will be interpreted from left to right, and any unassigned column widths will be calculated from the remaining width on the page. For example, if two values are assigned, they will be interpreted as left and center, and the right column width will be calculated. Setting a cell width to zero (0) will remove that column from the page footer entirely. To set the left and right widths only, pass a zero for the center cell, i.e. width = c(6, 0, 3) for a total width of 9 inches.

Details

Only one page footer is allowed per report. The page footer will appear on all pages of the report. The page footer may contain text on the left, right, or center. Use the appropriate parameters to specify the desired text for each section. Multiple strings may be passed to each section as a vector of strings.

If the width of the page header string exceeds the available space, an error will be generated. In addition, there is a limit of 5 strings for each page footer section.

There are two special tokens to generate page numbers: [pg] and [tpg]. Use [pg] to indicate the current page number. Use [tpg] to indicate the total number of pages in the report. These tokens may be placed anywhere in the page header or page footer.

Use the `blank_row` parameter to control the blank space above the page footer.

Each footer string must fit within the available space. The **reporter** package will not wrap footer. If a footer string does not fit within the available space, an error will be generated. In these situations, either shorten the footer string or split it into multiple footers that each fit within the available space.

Value

The modified report.

See Also

Other report: [add_content\(\)](#), [create_report\(\)](#), [footer_image\(\)](#), [footnotes\(\)](#), [header_image\(\)](#), [options_fixed\(\)](#), [page_by\(\)](#), [page_header\(\)](#), [print.report_spec\(\)](#), [report_options\(\)](#), [set_margins\(\)](#), [title_header\(\)](#), [titles\(\)](#), [write_report\(\)](#)

Examples

```
library(reporter)
library(magrittr)

# Create temp file path
tmp <- file.path(tempdir(), "mtcars.txt")

dat <- data.frame(name = rownames(mtcars[1:10, ]), mtcars[1:10, 1:5],
                  stringsAsFactors = FALSE)

# Create the report object
rpt <- create_report(tmp, orientation = "portrait") %>%
  page_header("Client: Motor Trend", "Study: Cars") %>%
  titles("MTCARS Sample Report") %>%
  add_content(create_table(dat)) %>%
  page_footer(Sys.time(), right = "Page [pg] of [tpg]")

# Write the report to the file system
write_report(rpt)

# Write report to console
writeLines(readLines(tmp, encoding = "UTF-8"))
```

```

# Client: Motor Trend
#
# MTCARS Sample Report
#
#      name      mpg cyl  disp  hp  drat
# -----
#      Mazda RX4      21   6   160  110   3.9
#      Mazda RX4 Wag    21   6   160  110   3.9
#      Datsun 710      22.8  4   108   93  3.85
#      Hornet 4 Drive  21.4  6   258  110  3.08
#      Hornet Sportabout 18.7  8   360  175  3.15
#      Valiant        18.1  6   225  105  2.76
#      Duster 360     14.3  8   360  245  3.21
#      Merc 240D      24.4  4  146.7   62  3.69
#      Merc 230       22.8  4  140.8   95  3.92
#      Merc 280       19.2  6  167.6  123  3.92
#
# ...
#
# 2020-10-17 11:53:51

```

Study: Cars

Page 1 of 1

page_header

Add a page header

Description

This function adds a page header to the report. The page header will appear at the top of each page of the report.

Usage

```

page_header(
  x,
  left = "",
  right = "",
  blank_row = "none",
  width = NULL,
  center = ""
)

```

Arguments

<code>x</code>	The report object.
<code>left</code>	The left page header text. May be a single string or a vector of strings.
<code>right</code>	The right page header text. May be a single string or a vector of strings.
<code>blank_row</code>	Whether to create a blank row below the page header. Valid values are 'below' and 'none'. Default is 'none'.

width	Widths for left, center, and right columns of the page header, passed as a vector of double values in the report unit of measure. If the vector contains fewer than three widths, the widths passed will be interpreted from left to right, and any unassigned column widths will be calculated from the remaining width on the page. For example, if two values are assigned, they will be interpreted as left and center, and the right column width will be calculated. Setting a cell width to zero (0) will remove that column from the page header entirely. To set the left and right widths only, pass a zero for the center cell, i.e. <code>width = c(6, 0, 3)</code> for a total width of 9 inches.
center	The center page header text. May be a single string or a vector of strings. By default, the center column is not displayed. To display it, either assign a value on this parameter, or assign a width on the "width" parameter.

Details

The page header may contain text on the left or right. Use the appropriate parameters to specify the desired text. Only one page header is allowed on a report. The page header will be repeated on every page of the report. Multiple text values for each side may be specified as a vector of strings.

If the width of the page header string exceeds the available space, an error will be generated. There is also a limit of 5 page header strings per each side.

There are two special tokens to generate page numbers: `[pg]` and `[tpg]`. Use `[pg]` to indicate the current page number. Use `[tpg]` to indicate the total number of pages in the report. These tokens may be placed anywhere in the page header or page footer.

Each header string must fit within the available space. The **reporter** package will not wrap headers. If a header string does not fit within the available space, an error will be generated. In these situations, either shorten the header string or split it into multiple headers that each fit within the available space.

Value

The modified report specification.

See Also

Other report: `add_content()`, `create_report()`, `footer_image()`, `footnotes()`, `header_image()`, `options_fixed()`, `page_by()`, `page_footer()`, `print.report_spec()`, `report_options()`, `set_margins()`, `title_header()`, `titles()`, `write_report()`

Examples

```
library(magrittr)

# Create temp file path
tmp <- file.path(tempdir(), "mtcars.txt")

dat <- data.frame(name = rownames(mtcars[1:10, ]), mtcars[1:10, 1:5],
                  stringsAsFactors = FALSE)

# Create the report object
```

```

rpt <- create_report(tmp, orientation = "portrait") %>%
  page_header("Client: Motor Trend", "Study: Cars") %>%
  titles("MTCARS Sample Report") %>%
  add_content(create_table(dat)) %>%
  page_footer(Sys.time(), right = "Page [pg] of [tpg]")

# Write the report to the file system
write_report(rpt)

# Write report to console
writeLines(readLines(tmp, encoding = "UTF-8"))

# Client: Motor Trend                                Study: Cars
#
#                                     MTCARS Sample Report
#
#          name                mpg cyl  disp  hp  drat
#          -----
#          Mazda RX4                21   6   160  110   3.9
#          Mazda RX4 Wag            21   6   160  110   3.9
#          Datsun 710               22.8  4   108   93   3.85
#          Hornet 4 Drive            21.4  6   258  110   3.08
#          Hornet Sportabout         18.7  8   360  175   3.15
#          Valiant                   18.1  6   225  105   2.76
#          Duster 360                14.3  8   360  245   3.21
#          Merc 240D                 24.4  4  146.7   62   3.69
#          Merc 230                  22.8  4  140.8   95   3.92
#          Merc 280                  19.2  6  167.6  123   3.92
#
# ...
#
# 2020-10-17 11:53:51                                Page 1 of 1

```

```
print.plot_spec      Prints the plot spec
```

Description

A function to print the plot spec. The **print** function will print the plot spec in summary form. To view all parameters, set the verbose parameter to TRUE.

Usage

```
## S3 method for class 'plot_spec'
print(x, ..., verbose = FALSE)
```

Arguments

x	The plot spec.
...	Additional parameters to pass to the underlying print function.
verbose	Whether to print in verbose form. Default is FALSE.

Value

The plot spec, invisibly.

See Also

[create_plot](#) function to create a plot specification.

Other plot: [create_plot\(\)](#)

Examples

```
txt <- create_text("Lorem ipsum dolor sit amet, consectetur...")
print(txt)

# A text specification:
# - text: data.frame 'mtcars' 32 rows 11 cols
```

print.report_spec	<i>Prints the report specification</i>
-------------------	--

Description

A function to print the report specification. The **print** function will print the report spec in summary form by default. To print in list form, set the verbose parameter to TRUE.

Usage

```
## S3 method for class 'report_spec'
print(x, ..., verbose = FALSE)
```

Arguments

x	The report spec.
...	Additional parameters to pass to the underlying print function.
verbose	Whether to print the report object in verbose (list) form or summary form. The default is FALSE.

Value

The report spec, invisibly.

See Also

[create_report](#) function to create a report specification.

Other report: [add_content\(\)](#), [create_report\(\)](#), [footer_image\(\)](#), [footnotes\(\)](#), [header_image\(\)](#), [options_fixed\(\)](#), [page_by\(\)](#), [page_footer\(\)](#), [page_header\(\)](#), [report_options\(\)](#), [set_margins\(\)](#), [title_header\(\)](#), [titles\(\)](#), [write_report\(\)](#)

Examples

```

library(reporter)
library(magrittr)

# Create temp file path
tmp <- file.path(tempdir(), "mtcars.txt")

# Create the table
tbl <- create_table(mtcars) %>%
  titles("Table 1.0", "MTCARS Sample Report") %>%
  footnotes("* NOTE: Data from 1974")

# Create the report object
rpt <- create_report(tmp) %>%
  add_content(tbl, align = "left")

# Write the report to the file system
res <- write_report(rpt)

# Write the modified report object to the console
print(res)

## A report specification: 1 pages
# - file_path: 'C:/Users/User/AppData/Local/Temp/RtmpWQybXs/mtcars.txt'
# - output_type: TXT
# - units: inches
# - orientation: landscape
# - line size/count: 108/45
# - content:
## A table specification:
# - data: data.frame 'mtcars' 32 rows 11 cols
# - show_cols: all
# - use_attributes: all
# - title 1: 'Table 1.0'
# - title 2: 'MTCARS Sample Report'
# - footnote 1: '* NOTE: Data from 1974'

```

print.style_spec	<i>Prints a style specification</i>
------------------	-------------------------------------

Description

This function will print a style object to the console. The print function will display each style setting that has been assigned, and the value which is assigned.

Usage

```

## S3 method for class 'style_spec'
print(x, ..., verbose = FALSE)

```

Arguments

x	A style object to print.
...	Any follow-on parameters to pass to print().
verbose	If verbose is TRUE, the function will print the style object as a list. Otherwise, the object will print using the custom print function. The custom print is more compact than the verbose style print. Default is FALSE.

See Also

Other styles: [add_style\(\)](#), [create_style\(\)](#), [get_theme\(\)](#)

Examples

```
library(reporter)

# Get theme
tm <- get_theme("SteelBlue")

# View theme settings
print(tm)
## A style specification:
#- font_name: 'Arial'
#- font_size: 10
#- text_color: 'DimGrey'
#- title_font_size: 11
#- title_font_bold: TRUE
#- title_font_color: 'SteelBlue'
#- border_color: 'Grey'
#- table_header_background: 'SteelBlue'
#- table_header_font_bold: TRUE
#- table_header_font_color: 'LightGrey'
#- table_body_background: 'White'
#- table_body_stripe: 'WhiteSmoke'
#- table_stub_background: 'SteelBlue'
#- table_stub_font_color: 'LightGrey'
#- table_stub_font_bold: TRUE
```

print.table_spec	<i>Prints the table spec</i>
------------------	------------------------------

Description

A function to print the table spec. The **print** function will print the table spec in summary form. To view all parameters, set the verbose parameter to TRUE.

Usage

```
## S3 method for class 'table_spec'
print(x, ..., verbose = FALSE)
```

Arguments

x	The table spec.
...	Additional parameters to pass to the underlying print function.
verbose	Whether to print in verbose form, which is similar to a list. Default is FALSE, which prints in summary form.

Value

The table spec, invisibly.

See Also

[create_table](#) function to create a table specification.

Other table: [column_defaults\(\)](#), [create_table\(\)](#), [define\(\)](#), [spanning_header\(\)](#), [stub\(\)](#)

Examples

```
library(magrittr)

# Create Table
tbl <- create_table(mtcars) %>%
  define(mpg, label = "Miles Per Gallon", width = .5) %>%
  define(cyl, label = "Cylinders") %>%
  titles("Table 6.4", "MTCARS Sample Table") %>%
  footnotes("* Motor Trend, 1974")

tbl

# A table specification:
# - data: data.frame 'mtcars' 32 rows 11 cols
# - show_cols: all
# - use_attributes: all
# - title 1: 'Table 6.4'
# - title 2: 'MTCARS Sample Table'
# - footnote 1: '* Motor Trend, 1974'
# - define: mpg 'Miles Per Gallon' width=0.5
# - define: cyl 'Cylinders'
```

print.text_spec	<i>Prints the text spec</i>
-----------------	-----------------------------

Description

A function to print the text spec. The **print** function will print the text spec in summary form. To view all parameters, set the verbose parameter to TRUE.

Usage

```
## S3 method for class 'text_spec'
print(x, ..., verbose = FALSE)
```

Arguments

x	The text spec.
...	Additional parameters to pass to the underlying print function.
verbose	Whether to print in verbose form. Default is FALSE.

Value

The text spec, invisibly.

See Also

[create_text](#) function to create a text specification.

Other text: [create_text\(\)](#)

Examples

```
txt <- create_text("Lorem ipsum dolor sit amet, consectetur...",
                  align = "left", width = 3)

txt

# A text specification: 6 words
# - text: Lorem ipsum dolor sit amet, consectetur...
# - width: 3
# - align: left
```

report_options	<i>Set options for the report</i>
----------------	-----------------------------------

Description

A function to set some options for the report. The options include the ability to control features such as auto line breaking, auto pagination, and auto page wrapping. These features are normally on by default, but sometimes it is desirable to turn them off. It also provides options for allowing users to insert custom code and decide the structure of titles.

Usage

```
report_options(
  x,
  allow_code = FALSE,
  line_break = TRUE,
  line_count = NULL,
```

```

    page_wrap = TRUE,
    auto_page = TRUE,
    title_block = "table"
)

```

Arguments

x	The report spec object.
allow_code	Whether to allow the user to insert custom code into the report. Currently applies to RTF and HTML outputs. Default is FALSE. When TRUE, users can insert code in the data, titles, or footnotes. To insert curly braces, double them so as to not interfere with the glue functionality, which uses single curly braces as an escape.
line_break	Whether to use auto line breaking. Default is TRUE. This option applies to RTF, DOCX, and HTML only. When "line_break" is FALSE, the rendering will not insert a line break code at the end of a line, and instead let the editor wrap the line as needed.
line_count	The number of lines that will fit on page. Normally, the line_count is calculated automatically. You can override the calculated value by setting the line_count directly.
page_wrap	By default, columns that exceed the available width of the page will be wrapped to a new page. The "page_wrap" parameter allows you to turn this feature off for the entire report. Default is TRUE. A "page_wrap" parameter has also been added to the create_table function, so that page wrapping may be controlled at the table level. The table level setting will override the report level setting. Note that turning off page wrapping may cause the report content to exceed the margins.
auto_page	By default, when there are too many lines to fit on a page, a new page will be automatically created. Sometimes it is desirable to turn this feature off. The "auto_page" parameter allows you to turn automatic page breaking off for the entire report. There is a corresponding parameter in create_table that allows you to control page breaking at a table level. The table setting will override the report setting. When a 'page_break' variable is set in the define function, you can set 'auto_page' to FALSE to let reporter follow the paging variable without any auto paging. Note that turning off auto pagination may cause page overflows.
title_block	To decide whether the structure of titles is "table" or "paragraph". Default is "table". Applies only to RTF. The "paragraph" structure is useful on some editors which do not render the table title block appropriately. Note that if the "paragraph" setting is applied, some features of the titles function may not work as expected.

Value

The report_spec with option settings.

See Also

Other report: [add_content\(\)](#), [create_report\(\)](#), [footer_image\(\)](#), [footnotes\(\)](#), [header_image\(\)](#), [options_fixed\(\)](#), [page_by\(\)](#), [page_footer\(\)](#), [page_header\(\)](#), [print.report_spec\(\)](#), [set_margins\(\)](#), [title_header\(\)](#), [titles\(\)](#), [write_report\(\)](#)

Examples

```
library(reporter)
library(magrittr)

# Create a temporary file
tmp <- file.path(tempdir(), "bod.rtf")

# Define table
tbl <- create_table(BOD, width = 2.5) %>%
  titles("Table 3.6", "BOD1 Sample Report") %>%
  define(Time, format = "Day %s", align = "left") %>%
  define(demand, format = "%2.1f mg/l", label = "Demand") %>%
  footnotes("1 Biochemical Oxygen Demand")

# Define report #1 - No blank margins
rpt <- create_report(tmp, orientation="portrait", output_type = "RTF",
  font = "Arial", font_size = 9) %>%
  add_content(tbl) %>%
  report_options(allow_code = TRUE, line_break = FALSE,
    auto_page = FALSE, page_wrap = FALSE,
    title_block = "paragraph")

# Write the report
write_report(rpt)
```

set_margins

Set page margins

Description

Sets the page margins for the report. The units for this parameter can be inches or centimeters, depending on the units of measure specified on the [create_report](#) function.

Usage

```
set_margins(x, top = NULL, bottom = NULL, left = NULL, right = NULL)
```

Arguments

x	The report spec object.
top	The top margin.
bottom	The bottom margin.

left	The left margin.
right	The right margin.

Details

The margins set with `set_margins` will be used for the entire report. Units for the margins are specified by the `units` parameter on the `create_report` function. Available units are 'inches' and 'cm'. When the unit of measure is inches, default margins are 1 inch on the left and right, and .5 inches on top and bottom. When the unit of measure is centimeters, default margins are 2.54 cm on left and right, and 1.27 cm on top and bottom.

Note that when using output type of TXT, and not using the `blank_margins` option, setting the margins only reduces the area available for content on a page. You must still set the actual margins on the available editor to match those specified in `set_margins`. Any mismatch may result in content not fitting properly on the page. For best results, set the right and bottom margins to zero to allow for slight overflow without causing a page break or wrapping lines.

Value

The `report_spec` with margins set as desired.

See Also

Other report: `add_content()`, `create_report()`, `footer_image()`, `footnotes()`, `header_image()`, `options_fixed()`, `page_by()`, `page_footer()`, `page_header()`, `print.report_spec()`, `report_options()`, `title_header()`, `titles()`, `write_report()`

Examples

```
library(reporter)
library(magrittr)

# Create a temporary file
tmp <- file.path(tempdir(), "bod.txt")

# Define table
tbl <- create_table(BOD, width = 2.5) %>%
  titles("Table 3.6", "BOD1 Sample Report") %>%
  define(Time, format = "Day %s", align = "left") %>%
  define(demand, format = "%2.1f mg/l", label = "Demand") %>%
  footnotes("1 Biochemical Oxygen Demand")

# Define report #1 - No blank margins
rpt <- create_report(tmp, orientation="portrait") %>%
  add_content(tbl, align = "left")

# Write the report
write_report(rpt)

# Write report to console
writeLines(readLines(tmp, encoding = "UTF-8"))
```

```
#           Table 3.6
#       BOD* Sample Report
#
# Time                Demand
# -----
# Day 1                8.3 mg/l
# Day 2               10.3 mg/l
# Day 3               19.0 mg/l
# Day 4               16.0 mg/l
# Day 5               15.6 mg/l
# Day 7               19.8 mg/l
#
# * Biochemical Oxygen Demand

# Define report #2 - blank margins
rpt <- create_report(tmp, orientation="portrait") %>%
  options_fixed(blank_margins = TRUE) %>%
  set_margins(top = .5, left = 1) %>%
  add_content(tbl, align = "left")

# Write the report
write_report(rpt)

# Write report to console
writeLines(readLines(tmp, encoding = "UTF-8"))

#
#
#
#           Table 3.6
#       BOD* Sample Report
#
#           Time                Demand
#           -----
#           Day 1                8.3 mg/l
#           Day 2               10.3 mg/l
#           Day 3               19.0 mg/l
#           Day 4               16.0 mg/l
#           Day 5               15.6 mg/l
#           Day 7               19.8 mg/l
#
#           * Biochemical Oxygen Demand
```

span	<i>Defines a spanning header attribute</i>
------	--

Description

Create a spanning header attribute object that can be attached to a data frame and passed to the `create_table` function. This attribute is used internally by other packages in the **r-sassy** system.

Usage

```
span(
  from,
  to,
  label = NULL,
  label_align = "center",
  level = 1,
  underline = TRUE
)
```

Arguments

from	The starting column to span. Spanning columns are defined as range of columns 'from' and 'to'. The columns may be identified by position, or by quoted or unquoted variable names. The from parameter is required.
to	The ending column to span. Spanning columns are defined as range of columns 'from' and 'to'. The columns may be identified by position, or by quoted or unquoted variable names. The to parameter is required.
label	The label to apply to the spanning header.
label_align	The alignment to use for the label. Valid values are "left", "right", "center", and "centre". The default for spanning columns is "center".
level	The level to use for the spanning header. The lowest spanning level is level 1, the next level above is level 2, and so on. By default, the level is set to 1.
underline	A TRUE or FALSE value indicating whether the spanning header should be underlined. Default is TRUE.

Details

A spanning header is a label and underline that spans one or more columns. A spanning header is defined minimally by identifying the column range to be spanned, and a label. A label alignment may also be supplied.

The spanning column range is defined by the from and to parameters. The range identifies a contiguous set of variables on the data. Variables can be identified by position, a quoted variable name, or an unquoted variable name.

Value

The spanning header attribute object.

See Also

Other attributes: [ftn\(\)](#), [ttl\(\)](#)

spanning_header	<i>Defines a spanning header</i>
-----------------	----------------------------------

Description

Create a header that spans multiple columns. Spanning headers are used to group related columns. Such groupings are a common feature of statistical reports.

Usage

```
spanning_header(
  x,
  from,
  to,
  label = "",
  label_align = "center",
  level = 1,
  n = NULL,
  underline = TRUE,
  bold = FALSE,
  standard_eval = FALSE
)
```

Arguments

x	The table object to add spanning headers to.
from	The starting column to span. Spanning columns are defined as range of columns 'from' and 'to'. The columns may be identified by position, or by quoted or unquoted variable names. If you want to pass the from value using an R variable, set the standard_eval parameter to TRUE. The from parameter is required.
to	The ending column to span. Spanning columns are defined as range of columns 'from' and 'to'. The columns may be identified by position, or by quoted or unquoted variable names. If you want to pass the to value using an R variable, set the standard_eval parameter to TRUE. The to parameter is required.
label	The label to apply to the spanning header.
label_align	The alignment to use for the label. Valid values are "left", "right", "center", and "centre". The default for spanning columns is "center".
level	The level to use for the spanning header. The lowest spanning level is level 1, the next level above is level 2, and so on. By default, the level is set to 1.
n	The population count to use for the "N=" label on the spanning header. The "N=" label will be formatted according to the n_format parameter on the create_table function.
underline	A TRUE or FALSE value indicating whether the spanning header should be underlined. Default is TRUE.

bold	A TRUE or FALSE value indicating whether the spanning header label should be bold. Default is FALSE.
standard_eval	A TRUE or FALSE value that indicates whether to use standard or non-standard evaluation of the from, and to parameters. Set standard_eval to TRUE if you want to pass the column names as variables. Default is FALSE, meaning it will use non-standard (unquoted) evaluation.

Details

A spanning header is a label and underline that spans one or more columns. A spanning header is defined minimally by identifying the column range to be spanned, and a label. A label alignment and "N=" value may also be supplied.

The spanning column range is defined by the from and to parameters. The range identifies a contiguous set of variables on the data. Variables can be identified by position, a quoted variable name, or an unquoted variable name.

Value

The modified table spec.

See Also

Other table: [column_defaults\(\)](#), [create_table\(\)](#), [define\(\)](#), [print.table_spec\(\)](#), [stub\(\)](#)

Examples

```
library(reporter)
library(magrittr)

# Create a temporary file
tmp <- file.path(tempdir(), "iris.txt")

# Prepare data
dat <- iris[sample(1:150, 15), c(5, 1, 2, 3, 4)]
dat <- dat[order(dat$Species), ]

# Define table
tbl <- create_table(dat) %>%
  titles("Table 3.2", "IRIS Sample Report") %>%
  spanning_header(2, 3, label = "Sepal") %>%
  spanning_header(4, 5, label = "Petal") %>%
  column_defaults(2:5, format = "%.1f") %>%
  define(Species, align = "left", dedupe = TRUE, blank_after = TRUE) %>%
  define(Sepal.Length, label = "Length") %>%
  define(Sepal.Width, label = "Width") %>%
  define(Petal.Length, label = "Length") %>%
  define(Petal.Width, label = "Width") %>%
  footnotes("* From Fisher's Iris Dataset")

# Define report
rpt <- create_report(tmp, orientation="portrait") %>%
```

```

options_fixed(blank_margins = TRUE) %>%
set_margins(top = 1, bottom = 1) %>%
add_content(tbl, align = "left")

# Write the report
write_report(rpt)

writeLines(readLines(tmp, encoding = "UTF-8"))

#
#
#
#
#           Table 3.2
#       IRIS Sample Report
#
#           Sepal      Petal
#           -----  -----
# Species      Length Width Length Width
# -----
# setosa        5.0   3.0   1.6   0.2
#               4.6   3.4   1.4   0.3
#               5.0   3.4   1.6   0.4
#               5.7   3.8   1.7   0.3
#
# versicolor    5.7   2.8   4.1   1.3
#               6.2   2.9   4.3   1.3
#               7.0   3.2   4.7   1.4
#               6.6   2.9   4.6   1.3
#
# virginica     6.2   3.4   5.4   2.3
#               7.2   3.0   5.8   1.6
#               6.9   3.1   5.1   2.3
#               5.6   2.8   4.9   2.0
#               7.7   2.6   6.9   2.3
#               6.3   2.8   5.1   1.5
#               7.7   2.8   6.7   2.0
#
#
# * From Fisher's Iris Dataset

```

stub

Defines a report stub

Description

Combine columns into a nested report stub. The report stub is a common feature of statistical reports. The stub is created with the `stub` function, and frequently appears in combination with the `label_row` and `indent` parameters from the `define` function. These elements work together to define the appearance of the stub.

Usage

```

stub(
  x,
  vars,
  label = "",
  label_align = NULL,
  align = "left",
  width = NULL,
  standard_eval = FALSE,
  style = NULL
)

```

Arguments

<code>x</code>	The table spec.
<code>vars</code>	A vector of quoted or unquoted variable names from which to create the stub. If you want to pass an R variable of names, escape the values with double curly braces, i.e. <code>vars = {{myvar}}</code> . The curly brace escape is useful when writing functions that construct reports dynamically.
<code>label</code>	The label for the report stub. The default label is an empty string.
<code>label_align</code>	The alignment for the stub column label. Valid values are 'left', 'right', 'center', and 'centre'. Default follows the <code>align</code> parameter.
<code>align</code>	How to align the stub column. Valid values are 'left', 'right', 'center', and 'centre'. Default is 'left'.
<code>width</code>	The width of the stub, in report units of measure.
<code>standard_eval</code>	A TRUE or FALSE value that indicates whether to use standard or non-standard evaluation of the <code>vars</code> , <code>from</code> , and <code>to</code> parameters. Set <code>standard_eval</code> to TRUE if you want to pass the column names as variables. Default is FALSE, meaning it will use non-standard (unquoted) evaluation.
<code>style</code>	A cell_style object that contains the style specifications for the stub.

Details

The table stub is a nested set of labels that identify rows on the table. The stub is created by combining two or more columns into a single stub column. The relationship between the columns is typically visualized as a hierarchy, with lower level concepts indented under higher level concepts.

A typical stub is created with the following steps:

- Prepare the data.
- Create the table object.
- Define the stub on the table using the `stub` function, and identify the variables to be combined.
- Identify higher level concepts with the `label_row` parameter on the [define](#) function.
- Identify lower level concepts using the `indent` parameter on the [define](#) function.

The stub will be automatically added as an identity variable on the report, and will always appear as the leftmost column. There can only be one stub defined on a report.

If you wish to create multiple levels of nested labels, use an NA value to prevent lower level labels from overwriting higher level labels.

For example, the following data:

continent	country	state_province
"North America"	NA	NA
"North America"	"Canada"	NA
"North America"	"Canada"	"Ontario"
"North America"	"USA"	NA
"North America"	"USA"	"New York"
"South America"	NA	NA
"South America"	"Brazil"	NA
"South America"	"Brazil"	"Amazonas"
"South America"	"Brazil"	"Bahia"

Will produce the following stub:

```
North America
  Canada
    Ontario
  USA
    New York
South America
  Brazil
    Amazonas
    Bahia
```

With the following code:

```
tbl <- create_table(dat) %>%
  stub(c(continent, country, state_province)) %>%
  define(country, indent = .25) %>%
  define(state_province, indent = .5)
```

Value

The modified table spec.

See Also

Other table: [column_defaults\(\)](#), [create_table\(\)](#), [define\(\)](#), [print.table_spec\(\)](#), [spanning_header\(\)](#)

Examples

```
library(reporter)
library(magrittr)
```

```
# Create temporary path
tmp <- file.path(tempdir(), "stub.txt")

# Read in prepared data
df <- read.table(header = TRUE, text = '
var      label      A      B
"ampg"   "N"        "19"    "13"
"ampg"   "Mean"       "18.8 (6.5)" "22.0 (4.9)"
"ampg"   "Median"      "16.4"    "21.4"
"ampg"   "Q1 - Q3"     "15.1 - 21.2" "19.2 - 22.8"
"ampg"   "Range"     "10.4 - 33.9" "14.7 - 32.4"
"cyl"    "8 Cylinder"  "10 ( 52.6%)" "4 ( 30.8%)"
"cyl"    "6 Cylinder"  "4 ( 21.1%)"  "3 ( 23.1%)"
"cyl"    "4 Cylinder"  "5 ( 26.3%)"  "6 ( 46.2%)'"')

# Create table
tbl <- create_table(df, first_row_blank = TRUE) %>%
  stub(c(var, label)) %>%
  define(var, blank_after = TRUE, label_row = TRUE,
         format = c(ampg = "Miles Per Gallon", cyl = "Cylinders")) %>%
  define(label, indent = .25) %>%
  define(A, label = "Group A", align = "center", n = 19) %>%
  define(B, label = "Group B", align = "center", n = 13)

# Create report and add content
rpt <- create_report(tmp, orientation = "portrait") %>%
  page_header(left = "Client: Motor Trend", right = "Study: Cars") %>%
  titles("Table 1.0", "MTCARS Summary Table") %>%
  add_content(tbl) %>%
  footnotes("* Motor Trend, 1974") %>%
  page_footer(left = Sys.time(),
              center = "Confidential",
              right = "Page [pg] of [tpg]")

# Write out report
write_report(rpt)

# View report in console
writeLines(readLines(tmp, encoding = "UTF-8"))
```

```
# Client: Motor Trend                                     Study: Cars
#
#                               Table 1.0
#                             MTCARS Summary Table
#
#                                Group A          Group B
#                              (N=19)           (N=13)
# -----
#
# Miles Per Gallon
# N                19                 13
# Mean             18.8 (6.5)         22.0 (4.9)
# Median            16.4               21.4
```

```
#           Q1 - Q3      15.1 - 21.2  19.2 - 22.8
#           Range       10.4 - 33.9  14.7 - 32.4
#
#           Cylinders
#           8 Cylinder   10 ( 52.6%)   4 ( 30.8%)
#           6 Cylinder    4 ( 21.1%)   3 ( 23.1%)
#           4 Cylinder    5 ( 26.3%)   6 ( 46.2%)
#
# ...
#
#
# * Motor Trend, 1974
#
# 2020-08-30 03:50:02           Confidential           Page 1 of 1
#
```

title_header	Adds a title header block
--------------	---------------------------

Description

This function adds a title header to an object. A title header is a special type of title layout that has titles on the left and header information on the right.

Usage

```
title_header(
  x,
  ...,
  right = "",
  blank_row = "below",
  borders = "none",
  width = NULL
)
```

Arguments

x	The object to assign titles to. Valid objects are a report, table, text, or plot specification.
...	A set of title strings.
right	A set of header strings to be shown on the right side of the title header. Pass the header strings as a vector of strings.
blank_row	Where to place a blank row. Valid values are 'above', 'below', 'both', or 'none'. Default is 'below'.
borders	Whether and where to place a border. Valid values are 'top', 'bottom', 'left', 'right', 'outside', 'inside', 'all', or 'none'. Default is 'none'. The 'left', 'right', 'outside', and 'inside' border specifications only apply to RTF, HTML, PDF and DOCX reports.

width The width of the title header. If the title header is attached to the report, valid values are 'page' or a numeric width, and the default is 'page'. If the title header is attached to the table, plot, or text content, the valid values are 'page', 'content' or a numeric value, and the default is 'content'. The value 'content' means the footnotes will be aligned to the width of the table, plot, or text content. The value 'page' means the footnotes will be aligned to the width of the page. In addition to these two convenience settings, you may also specify a specific width in the current units of measure. The units of measure is determined by the 'units' parameter on [create_report](#).

Details

The `title_header` function accepts a set of strings of the desired title text, and a vector of header strings. The titles will appear on the left of the title header, and the header strings on the right. To specify multiple titles for the block, pass them to the function as separate strings.

Title headers may be assigned to a report, a table, a text specification, or a plot. If assigned to the report, the title header will appear at the top of the page, and be repeated for every page of the report. If the title header is assigned to content, the titles will appear above the content, and be repeated if the content breaks to the next page.

One title header function accepts up to 10 titles. Blank rows above or below the title block may be controlled using the `blank_row` parameter.

Each title string must fit within the available space. The **reporter** package will not wrap titles on fixed-width reports. If a title does not fit within the available space, an error will be generated. In these situations, either shorten the title or split it into multiple titles that each fit within the available space.

Value

The modified report.

See Also

Other report: [add_content\(\)](#), [create_report\(\)](#), [footer_image\(\)](#), [footnotes\(\)](#), [header_image\(\)](#), [options_fixed\(\)](#), [page_by\(\)](#), [page_footer\(\)](#), [page_header\(\)](#), [print.report_spec\(\)](#), [report_options\(\)](#), [set_margins\(\)](#), [titles\(\)](#), [write_report\(\)](#)

Examples

```
library(reporter)
library(magrittr)

# Create a temporary file
tmp <- file.path(tempdir(), "expenses.txt")

# Prepare data
dat <- data.frame(category = rownames(USPersonalExpenditure),
                  USPersonalExpenditure, stringsAsFactors = FALSE)

# Define table
```

```
tbl <- create_table(dat) %>%
  title_header("Table 1.0", "US Personal Expenditures from 1940 - 1960",
    right = c("Page [pg] of [tpg]", "World Almanac")) %>%
  column_defaults(from = X1940, to = X1960, width = .6, format = "$%.2f") %>%
  define(category, label = "Category") %>%
  define(X1940, label = "1940") %>%
  define(X1945, label = "1945") %>%
  define(X1950, label = "1950") %>%
  define(X1955, label = "1955") %>%
  define(X1960, label = "1960") %>%
  footnotes("* In billions of dollars")

# Define report
rpt <- create_report(tmp, orientation="portrait") %>%
  add_content(tbl)

# Write the report
write_report(rpt)

# Display in console
writeLines(readLines(tmp, encoding = "UTF-8"))
```

```
#      Table 1.0                                     Page 1 of 1
#      US Personal Expenditures from 1940 - 1960       World Almanac
#
#      Category          1940    1945    1950    1955    1960
#      -----
#      Food and Tobacco   $22.20  $44.50  $59.60  $73.20  $86.80
#      Household Operation $10.50  $15.50  $29.00  $36.50  $46.20
#      Medical and Health  $3.53   $5.76   $9.71  $14.00  $21.10
#      Personal Care       $1.04   $1.98   $2.45   $3.40   $5.40
#      Private Education   $0.34   $0.97   $1.80   $2.60   $3.64
#
#      * In billions of dollars
```

titles
Adds a title block

Description

This function adds one or more titles to an object as a title block. If added to a report, the titles will be added to the page template, and thus appear on each page of the report. Titles may also be added to a table, text, or plot object.

Usage

```
titles(
  x,
  ...,
  align = "center",
```

```

    blank_row = "below",
    borders = "none",
    width = NULL,
    bold = FALSE,
    font_size = NULL,
    header = FALSE,
    columns = 1
)

```

Arguments

<code>x</code>	The object to assign titles to. Valid objects are a report, or a table, text, or plot specification.
<code>...</code>	A set of title strings.
<code>align</code>	The position to align the titles. Valid values are 'left', 'right', 'center' or 'centre'. For titles, the default is 'center'.
<code>blank_row</code>	Where to place a blank row. Valid values are 'above', 'below', 'both', or 'none'. Default is "below".
<code>borders</code>	Whether and where to place a border. Valid values are 'top', 'bottom', 'left', 'right', 'outside', 'inside', 'all', or 'none'. Default is "none". The 'left', 'right', 'outside', and 'inside' border specifications only apply to RTF, HTML, PDF and DOCX reports.
<code>width</code>	The width of the titles block. If the titles are attached to the report, valid values are 'page' or a numeric width, and the default is 'page'. If the titles are attached to the table, plot, or text content, the valid values are 'page', 'content' or a numeric value, and the default is 'content'. The value 'content' means the titles will be aligned to the width of the table, plot, or text content. The value 'page' means the titles will be aligned to the width of the page. In addition to these two convenience settings, you may also specify a specific width in the current units of measure. The units of measure is determined by the 'units' parameter on create_report .
<code>bold</code>	A parameter to bold the titles. Valid values are TRUE and FALSE. Default is FALSE. This parameter only applies to variable-width RTF, HTML, PDF, and DOCX output types.
<code>font_size</code>	The font size to use for the title block. The font size of the report will be used by default. Valid values are 8, 9, 10, 11, 12, 13, and 14. This parameter only applies to variable-width RTF, HTML, PDF, and DOCX output types.
<code>header</code>	Whether to put the titles in the page header. Valid values are TRUE and FALSE. Default is FALSE. This option only works on the RTF and DOCX output types, and only applies to titles assigned to the report object. Titles in the page header will appear on every page, and be the same throughout the report.
<code>columns</code>	The number of columns for the title block. Valid values are 1, 2, and 3. Default is 1. If this parameter is set to 2, the title block will be split into two columns, each aligned to the outside. If this parameter is set to 3, the title block will be split into 3 columns, with the outer columns aligned to the outside and the middle column aligned center. Titles are assigned to cells from top left to bottom right.

Details

The `titles` function accepts a set of strings of the desired title text. To specify multiple titles for the block, pass them to the function as separate strings.

The titles may be aligned center, left or right using the `align` parameter. The alignment will be applied to all titles contained in the block. To control alignment of titles separately for each title, use multiple `titles` functions.

Titles may be assigned to a report, a table, a text specification, or a plot. If assigned to the report, the title will appear at the top of the page, and be repeated for every page of the report. If the titles are assigned to content, the titles will appear above the content, and be repeated if the content breaks to the next page.

If titles are assigned to the report, alignment will be oriented to the page body. If titles are assigned to content, alignment will be oriented to the edge of the content.

One title function accepts up to 10 titles. However, multiple title blocks may be added to the same object if needed.

Blank rows above or below the title block may be controlled using the `blank_row` parameter.

Each title string must fit within the available space. The **reporter** package will not wrap titles on fixed-width reports. If a title does not fit within the available space, a warning will be generated and the title will be truncated. In these situations, either shorten the title or split it into multiple titles that each fit within the available space.

Value

The modified report.

See Also

Other report: `add_content()`, `create_report()`, `footer_image()`, `footnotes()`, `header_image()`, `options_fixed()`, `page_by()`, `page_footer()`, `page_header()`, `print.report_spec()`, `report_options()`, `set_margins()`, `title_header()`, `write_report()`

Examples

```
library(reporter)
library(magrittr)

# Create a temporary file
tmp <- file.path(tempdir(), "expenses.txt")

# Prepare data
dat <- data.frame(category = rownames(USPersonalExpenditure),
                  USPersonalExpenditure, stringsAsFactors = FALSE)

# Define table
tbl <- create_table(dat) %>%
  titles("Table 1.0", "US Personal Expenditures from 1940 - 1960") %>%
  column_defaults(from = X1940, to = X1960, width = .6, format = "$%.2f") %>%
  define(category, label = "Category") %>%
  define(X1940, label = "1940") %>%
```

```

define(X1945, label = "1945") %>%
define(X1950, label = "1950") %>%
define(X1955, label = "1955") %>%
define(X1960, label = "1960") %>%
footnotes("* In billions of dollars")

# Define report
rpt <- create_report(tmp, orientation="portrait") %>%
  add_content(tbl)

# Write the report
write_report(rpt)

# Display in console
writeLines(readLines(tmp, encoding = "UTF-8"))
#
#           Table 1.0
#           US Personal Expenditures from 1940 - 1960
#
# Category          1940    1945    1950    1955    1960
# -----
# Food and Tobacco   $22.20 $44.50 $59.60 $73.20 $86.80
# Household Operation $10.50 $15.50 $29.00 $36.50 $46.20
# Medical and Health  $3.53  $5.76  $9.71 $14.00 $21.10
# Personal Care       $1.04  $1.98  $2.45 $3.40  $5.40
# Private Education   $0.34  $0.97  $1.80 $2.60  $3.64
#
# * In billions of dollars

```

ttl	<i>Creates a title attribute</i>
-----	----------------------------------

Description

This function creates a titles attribute, which can be used to define titles by attaching as an attribute to a data frame. This function is used internally to the system.

Usage

```

ttl(
  titles,
  align = "center",
  blank_row = "below",
  borders = NULL,
  width = NULL,
  bold = FALSE,
  font_size = NULL
)

```

Arguments

titles	A vector of title strings.
align	The position to align the titles. Valid values are 'left', 'right', 'center' or 'centre'. For titles, the default is 'center'.
blank_row	Where to place a blank row. Valid values are 'above', 'below', 'both', or 'none'. Default is "below".
borders	Whether and where to place a border. Valid values are 'top', 'bottom', 'left', 'right', 'outside', 'inside', 'all', or 'none'. Default is "none".
width	The width of the titles block.
bold	A parameter to bold the titles. Valid values are TRUE and FALSE. Default is FALSE.
font_size	The font size to use for the title block. The font size of the report will be used by default. Valid values are 8, 9, 10, 11, 12, 13, and 14.

Value

A title attribute object.

See Also

[titles](#) function.

Other attributes: [ftn\(\)](#), [span\(\)](#)

write_registration_file

Create a registration file

Description

This function will create a registration file to help determine the correct cpuom and lpuom for your editor/printer.

Usage

```
write_registration_file(file_path)
```

Arguments

file_path The full or relative file name and path to create the registration file.

Details

The cpi and lpi are used in output_type = "TXT" to determine available space on the page. The registration file can help determine the correct settings for the target text editor and printer. Failure to set the correct characters per unit of measure (cpuom) and lines per unit of measure (lpuom) may result in misalignment of content on the page when printing text output.

How to Use the Registration File

To use the registration file, first decide the units of measure you wish to use, inches or centimeters. Next, create the registration file by calling the `write_registration_file` function. Then print the registration file.

Once the registration file is printed, take a ruler and measure both the horizontal and vertical registration lines from zero to 60 in the desired units of measure. For example, if your units of measure is 'inches', measure the registration lines in inches.

Record the distance measured in each direction. For each direction, divide 60 by the distance measured, and round to three decimal places. The horizontal result is the characters per unit of measure (cpuom). The vertical result is the lines per unit of measure (lpuom). To get an accurate printing of text reports, assign these values to the `cpuom` and `lpuom` parameters on the [options_fixed](#) function.

For best results, test the calculated values by printing some reports and checking for undesired page breaks or wrapped lines. If necessary, adjust the calculated `cpuom` and `lpuom` values until all content stays within the available space without wrapping or breaking.

Examples

```
library(reporter)

# Create temp file path
tmp <- file.path(tempdir(), "reg.txt")

# Create the registration file
write_registration_file(tmp)

# Write registration file to the console
writeLines(readLines(tmp))

# 0-----+-----+-----+-----+-----+
# -      10      20      30      40      50      60
# -
# -
# -
# -
# -
# -
# -
# -
# + 10
# -
# -
# -
# -
# -
# -
# -
# -
# -
# -
# + 20
# -
```

```
# -  
# -  
# -  
# -  
# -  
# -  
# -  
# -  
# -  
# + 30  
# -  
# -  
# -  
# -  
# -  
# -  
# -  
# -  
# -  
# + 40  
# -  
# -  
# -  
# -  
# -  
# -  
# -  
# -  
# -  
# + 50  
# -  
# -  
# -  
# -  
# -  
# -  
# -  
# -  
# -  
# + 60
```

write_report

Write a report to the file system

Description

This function writes a report_spec object to the file system, using the specifications provided in the object.

Usage

```
write_report(
  x,
  file_path = NULL,
  output_type = NULL,
  preview = NULL,
  log = TRUE
)
```

Arguments

x	The report object to write.
file_path	The file name and path to write the report to. If supplied, this parameter overrides the file_path parameter on the create_report function. Default is NULL.
output_type	The output file type. This parameter will override the output_type on the create_report function. This parameter can be used to output the same report object to multiple output types. Default value is NULL, meaning it will not override the create_report value. Valid values are 'TXT', 'RTF', 'DOCX', 'PDF' and 'HTML'.
preview	Whether to write the entire report, or a report preview. A report preview is a subset of pages of the report. The default value is NULL, meaning the entire report will be written. You may also pass a number of pages to write. For example, passing the number 1 will print the first page, while passing a 5 will print the first five pages.
log	Whether the function should log itself automatically, if the logr package is available. This parameter is used internally. Default is TRUE.

Details

The function renders the report in the requested format, and writes it to the location specified in the report file_path parameter. Attempts to write an object that is not of class "report_spec" will generate an error.

The write_report function is a driver for very complex set of rendering functions. The rendering functions perform most of the advanced functionality of the **reporter** package: generating spanning headers, page wrapping and breaking, creating stub columns, etc. When things go wrong, they will usually go wrong during this function call. For that reason, although this function can be part of the pipeline that creates the report object, it is best to call write_report independently, to help isolate any issues from the report definition procedure.

Value

The report spec, with settings modified during rendering. These modified settings can sometimes be useful for documentation, and for debugging issues with the procedure.

See Also

Other report: `add_content()`, `create_report()`, `footer_image()`, `footnotes()`, `header_image()`, `options_fixed()`, `page_by()`, `page_footer()`, `page_header()`, `print.report_spec()`, `report_options()`, `set_margins()`, `title_header()`, `titles()`

Examples

```
library(reporter)
library(fmtr)
library(magrittr)

# Create temp file path
tmp <- file.path(tempdir(), "beaver2.txt")

# Take Sample of Data
dat <- beaver2[sample(1:100, 15), ]

# Create format for active variable
fmt <- value(condition(x == 0, "No"),
              condition(x == 1, "Yes"))

# Create the table
tbl <- create_table(dat) %>%
  titles("Table 1.0", "BEAVERS Sample Report") %>%
  column_defaults(width = .75) %>%
  define(day, label = "Day", format = "Day %s") %>%
  define(time, label = "Time") %>%
  define(temp, label = "Temperature", width = 1, format = "%.1f") %>%
  define(activ, label = "Active", format = fmt) %>%
  footnotes("* NOTE: Data on beaver habits")

# Create the report object
rpt <- create_report(tmp) %>%
  add_content(tbl, align = "left")

# Write the report to the file system
res <- write_report(rpt)

# Write the modified report object to the console
print(res)

# Write the report to console
writeLines(readLines(tmp, encoding = "UTF-8"))
```

```
#           Table 1.0
#           BEAVERS Sample Report
#
#      Day      Time Temperature      Active
# -----
# Day 307      1020         37.2         No
# Day 307      1030         37.2         No
# Day 307       940         36.7         No
```

#	Day 307	1340	37.1	No
#	Day 307	1410	37.2	No
#	Day 307	1400	37.1	No
#	Day 307	1130	36.9	No
#	Day 307	1140	37.0	No
#	Day 307	1120	37.0	No
#	Day 307	1000	37.1	No
#	Day 307	1250	37.0	No
#	Day 307	2100	37.9	Yes
#	Day 307	1210	37.0	No
#	Day 307	1740	38.0	Yes
#	Day 308	130	37.8	Yes
#				
#	* NOTE: Data on beaver habits			

Index

- * **attributes**
 - ftn, [34](#)
 - span, [60](#)
 - ttn, [73](#)
 - * **plot**
 - create_plot, [11](#)
 - print.plot_spec, [51](#)
 - * **report**
 - add_content, [3](#)
 - create_report, [13](#)
 - footer_image, [30](#)
 - footnotes, [31](#)
 - header_image, [37](#)
 - options_fixed, [40](#)
 - page_by, [43](#)
 - page_footer, [47](#)
 - page_header, [49](#)
 - print.report_spec, [52](#)
 - report_options, [56](#)
 - set_margins, [58](#)
 - title_header, [68](#)
 - titles, [70](#)
 - write_report, [76](#)
 - * **styles**
 - add_style, [5](#)
 - create_style, [16](#)
 - get_theme, [35](#)
 - print.style_spec, [53](#)
 - * **table**
 - column_defaults, [8](#)
 - create_table, [19](#)
 - define, [25](#)
 - print.table_spec, [54](#)
 - spanning_header, [62](#)
 - stub, [64](#)
 - * **text**
 - create_text, [24](#)
 - print.text_spec, [55](#)
- [add_content](#), [3](#), [12](#), [14](#), [15](#), [19](#), [22](#), [24](#), [31](#), [33](#),
[38](#), [42](#), [44](#), [48](#), [50](#), [52](#), [58](#), [59](#), [69](#), [72](#),
[78](#)
- [add_style](#), [5](#), [16](#), [18](#), [35](#), [54](#)
- [cell_style](#), [7](#), [9](#), [28](#), [65](#)
- [column_defaults](#), [7](#), [8](#), [22](#), [28](#), [55](#), [63](#), [66](#)
- [create_plot](#), [3](#), [4](#), [11](#), [15](#), [22](#), [44](#), [52](#)
- [create_report](#), [4](#), [9](#), [13](#), [22](#), [27](#), [31–33](#), [38](#),
[41](#), [42](#), [44](#), [48](#), [50](#), [52](#), [58](#), [59](#), [69](#), [71](#),
[72](#), [78](#)
- [create_style](#), [5](#), [6](#), [16](#), [35](#), [54](#)
- [create_table](#), [3](#), [4](#), [9](#), [10](#), [15](#), [19](#), [21](#), [27](#), [28](#),
[34](#), [38](#), [44](#), [55](#), [57](#), [60](#), [62](#), [63](#), [66](#)
- [create_text](#), [3](#), [4](#), [15](#), [22](#), [24](#), [56](#)
- [define](#), [7](#), [8](#), [10](#), [20–22](#), [25](#), [55](#), [57](#), [63–66](#)
- [fapply](#), [26](#), [44](#)
- [fmtr](#), [9](#), [26](#), [44](#)
- [footer_image](#), [4](#), [15](#), [30](#), [33](#), [38](#), [42](#), [44](#), [48](#),
[50](#), [52](#), [58](#), [59](#), [69](#), [72](#), [78](#)
- [footnotes](#), [4](#), [12](#), [14](#), [15](#), [22](#), [24](#), [31](#), [31](#), [35](#),
[38](#), [42](#), [44](#), [48](#), [50](#), [52](#), [58](#), [59](#), [69](#), [72](#),
[78](#)
- [FormattingStrings](#), [26](#), [44](#)
- [ftn](#), [34](#), [61](#), [74](#)
- [get_theme](#), [5](#), [6](#), [18](#), [35](#), [54](#)
- [ggplot](#), [11](#)
- [ggsurvplot](#), [11](#)
- [header_image](#), [4](#), [15](#), [31](#), [33](#), [37](#), [42](#), [44](#), [48](#),
[50](#), [52](#), [58](#), [59](#), [69](#), [72](#), [78](#)
- [lowercase_n](#) ([lowercase_parens](#)), [38](#)
- [lowercase_parens](#), [38](#)
- [options_fixed](#), [4](#), [14](#), [15](#), [31–33](#), [38](#), [40](#), [44](#),
[48](#), [50](#), [52](#), [58](#), [59](#), [69](#), [72](#), [75](#), [78](#)
- [page_by](#), [4](#), [12](#), [15](#), [22](#), [31](#), [33](#), [38](#), [42](#), [43](#), [48](#),
[50](#), [52](#), [58](#), [59](#), [69](#), [72](#), [78](#)

page_footer, [4](#), [14](#), [15](#), [31](#), [33](#), [38](#), [42](#), [44](#), [47](#),
[50](#), [52](#), [58](#), [59](#), [69](#), [72](#), [78](#)
page_header, [4](#), [14](#), [15](#), [31](#), [33](#), [37](#), [38](#), [42](#), [44](#),
[48](#), [49](#), [52](#), [58](#), [59](#), [69](#), [72](#), [78](#)
print.plot_spec, [12](#), [51](#)
print.report_spec, [4](#), [15](#), [31](#), [33](#), [38](#), [42](#), [44](#),
[48](#), [50](#), [52](#), [58](#), [59](#), [69](#), [72](#), [78](#)
print.style_spec, [6](#), [18](#), [35](#), [53](#)
print.table_spec, [10](#), [22](#), [28](#), [54](#), [63](#), [66](#)
print.text_spec, [24](#), [55](#)

report_options, [4](#), [14](#), [15](#), [21](#), [31](#), [33](#), [38](#), [42](#),
[44](#), [48](#), [50](#), [52](#), [56](#), [59](#), [69](#), [72](#), [78](#)

set_margins, [4](#), [15](#), [31](#), [33](#), [38](#), [42](#), [44](#), [48](#), [50](#),
[52](#), [58](#), [58](#), [69](#), [72](#), [78](#)
span, [35](#), [60](#), [74](#)
spanning_header, [10](#), [22](#), [28](#), [55](#), [62](#), [66](#)
stub, [7](#), [10](#), [22](#), [27](#), [28](#), [55](#), [63](#), [64](#)

title_header, [4](#), [14](#), [15](#), [31](#), [33](#), [38](#), [42](#), [44](#),
[48](#), [50](#), [52](#), [58](#), [59](#), [68](#), [72](#), [78](#)
titles, [4](#), [12](#), [14](#), [15](#), [22](#), [24](#), [31](#), [33](#), [38](#), [42](#),
[44](#), [48](#), [50](#), [52](#), [57–59](#), [69](#), [70](#), [74](#), [78](#)
ttl, [35](#), [61](#), [73](#)

upcase_n (lowcase_parens), [38](#)
upcase_parens, [21](#), [22](#)
upcase_parens (lowcase_parens), [38](#)

write_registration_file, [41](#), [42](#), [74](#)
write_report, [4](#), [9](#), [13–15](#), [27](#), [31](#), [33](#), [37](#), [38](#),
[42](#), [44](#), [48](#), [50](#), [52](#), [58](#), [59](#), [69](#), [72](#), [76](#)