Package: robregcc (via r-universe)

October 18, 2026

Type Package

Title Robust Regression with Compositional Covariates

Version 1.1

Date 2020-10-10

Maintainer Aditya Mishra <amishra@flatironinstitute.org>

Description We implement the algorithm estimating the parameters of the robust regression model with compositional covariates. The model simultaneously treats outliers and provides reliable parameter estimates. Publication reference: Mishra, A., Mueller, C.,(2019) <doi:10.48550/arXiv.1909.04990>.

URL https://arxiv.org/abs/1909.04990, https://github.com/amishra-stats/robregcc

Depends R (>= 3.5.0), stats, utils

License GPL (>= 3.0)

LazyData true

Imports Rcpp (>= 0.12.0), MASS, magrittr, graphics

LinkingTo Rcpp, RcppArmadillo

NeedsCompilation yes

RoxygenNote 7.1.1

Encoding UTF-8

Author Aditya Mishra [aut, cre], Christian Muller [ctb]

Repository https://cran.r-universe.dev

Date/Publication 2020-07-25 19:20:03 UTC

RemoteUrl https://github.com/cran/robregcc

RemoteRef HEAD

RemoteSha 3ba1185aba0bc372c7ec8f324506fa13fec3ffa8

Contents

classo 2
classo_path 3
coef_cc 4
cpsc_sp 6
plot_cv 8
plot_path 9
plot_resid 11
residuals 13
robregcc_option 15
robregcc_sim 17
robregcc_sp 19
simulate_robregcc 21

Index **23**

`classo` *Estimate parameters of linear regression model with compositional covariates using method suggested by Pixu shi.*

Description

The model uses scaled lasoo approach for model selection.

Usage

```
classo(Xt, y, C, we = NULL, type = 1, control = list())
```

Arguments

`Xt`	CLR transformed predictor matrix.
`y`	model response vector
`C`	sub-compositional matrix
`we`	specify weight of model parameter
`type`	1/2 for l1 / l2 loss in the model
`control`	a list of internal parameters controlling the model fitting

Value

`beta`	model parameter estimate

References

Shi, P., Zhang, A. and Li, H., 2016. *Regression analysis for microbiome compositional data. The Annals of Applied Statistics*, 10(2), pp.1019-1040.

Examples

```
library(robregcc)
library(magrittr)

data(simulate_robregcc)
X <- simulate_robregcc$X;
y <- simulate_robregcc$y
C <- simulate_robregcc$C
n <- nrow(X); p <- ncol(X); k <-  nrow(C)

# Predictor transformation due to compositional constraint:
Xt <- cbind(1,X)          # accounting for intercept in predictor
C <- cbind(0,C)            # accounting for intercept in constraint
bw <- c(0,rep(1,p))        # weight matrix to not penalize intercept

# Non-robust regression, [Pixu Shi 2016]
control <- robregcc_option(maxiter = 5000, tol = 1e-7, lminfac = 1e-12)
fit.nr <- classo(Xt, y, C, we = bw, type = 1, control = control)
```

---

classo_path *Compute solution path of constrained lasso.*

Description

The model uses scaled lasoo approach for model selection.

Usage

```
classo_path(Xt, y, C, we = NULL, control = list())
```

Arguments

Xt	CLR transformed predictor matrix.
y	model response vector
C	sub-compositional matrix
we	specify weight of model parameter
control	a list of internal parameters controlling the model fitting

Value

betapath	solution path estimate
beta	model parameter estimate

Examples

```
library(robregcc)
library(magrittr)

data(simulate_robregcc)
X <- simulate_robregcc$X;
y <- simulate_robregcc$y
C <- simulate_robregcc$C
n <- nrow(X); p <- ncol(X); k <-  nrow(C)


#
Xt <- cbind(1,X)                          # accounting for intercept in predictor
C <- cbind(0,C)                            # accounting for intercept in constraint
bw <- c(0,rep(1,p))                        # weight matrix to not penalize intercept

# Non-robust regression
control <- robregcc_option(maxiter = 5000, tol = 1e-7, lminfac = 1e-12)
fit.path <- classo_path(Xt, y, C, we = bw, control = control)
```

`coef_cc` *Extract coefficients estimate from the sparse version of the robregcc fitted object.*

Description

S3 methods extracting estimated coefficients for objects generated by `robregcc`. Robust coeffcient estimate.

Usage

```
coef_cc(object, type = 0, s = 0)
```

Arguments

`object`	Object generated by `robregcc`.
`type`	0/1 residual estimate before/after sanity check
`s`	0/1 no/yes 1se rule

Value

coefficient estimate

Examples

```
library(magrittr)
library(robregcc)

data(simulate_robregcc)
X <- simulate_robregcc$X;
y <- simulate_robregcc$y
C <- simulate_robregcc$C
n <- nrow(X); p <- ncol(X); k <-  nrow(C)

Xt <- cbind(1,X)                          # accounting for intercept in predictor
C <- cbind(0,C)                            # accounting for intercept in constraint
bw <- c(0,rep(1,p))                        # weight matrix to not penalize intercept

example_seed <- 2*p+1
set.seed(example_seed)

# Breakdown point for tukey Bisquare loss function
b1 = 0.5                    # 50% breakdown point
cc1 =  1.567                # corresponding model parameter
b1 = 0.25; cc1 =  2.937

# Initialization [PSC analysis for compositional data]
control <- robregcc_option(maxiter=1000,tol = 1e-4,lminfac = 1e-7)
fit.init <- cpsc_sp(Xt, y,alp = 0.4, cfac = 2, b1 = b1,
cc1 = cc1,C,bw,1,control)

## Robust model fitting

# control parameters
control <- robregcc_option()
beta.wt <- fit.init$betaR    # Set weight for model parameter beta
beta.wt[1] <- 0
control$gamma = 1            # gamma for constructing  weighted penalty
control$spb = 40/p           # fraction of maximum non-zero model parameter beta
control$outMiter = 1000      # Outer loop iteration
control$inMiter = 3000       # Inner loop iteration
control$nlam = 50            # Number of tuning parameter lambda to be explored
control$lmaxfac = 1          # Parameter for constructing sequence of lambda
control$lminfac = 1e-8       # Parameter for constructing sequence of lambda
control$tol = 1e-20;         # tolrence parameter for converging [inner  loop]
control$out.tol = 1e-16      # tolerence parameter for convergence [outer loop]
control$kfold = 10           # number of fold of crossvalidation
control$sigmafac = 2#1.345
# Robust regression using adaptive lasso penalty
fit.ada <- robregcc_sp(Xt,y,C,
                       beta.init = beta.wt,  cindex = 1,
                       gamma.init = fit.init$residuals,
                       control = control,
                       penalty.index = 1, alpha = 0.95)
```

```
# Robust regression using lasso penalty [Huber equivalent]
fit.soft <- robregcc_sp(Xt,y,C, cindex = 1,
                        control = control, penalty.index = 2,
                        alpha = 0.95)


# Robust regression using hard thresholding penalty
control$lmaxfac = 1e2               # Parameter for constructing sequence of lambda
control$lminfac = 1e-3              # Parameter for constructing sequence of lambda
control$sigmafac = 2#1.345
fit.hard <- robregcc_sp(Xt,y,C, beta.init = fit.init$betaf,
                        gamma.init = fit.init$residuals,
                        cindex = 1,
                        control = control, penalty.index = 3,
                        alpha = 0.95)

coef_cc(fit.ada)
coef_cc(fit.soft)
coef_cc(fit.hard)
```

`cpsc_sp` *Principal sensitivity component analysis with compositional covariates in sparse setting.*

Description

Produce model and its residual estimate based on PCS analysis.

Usage

```
cpsc_sp(
  X0,
  y0,
  alp = 0.4,
  cfac = 2,
  b1 = 0.25,
  cc1 = 2.937,
  C = NULL,
  we,
  type,
  control = list()
)
```

Arguments

`X0`	CLR transformed predictor matrix.
`y0`	model response vector

alp	(0,0.5) fraction of data sample to be removed to generate subsample
cfac	initial value of shift parameter for weight construction/initialization
b1	tukey bisquare function parameter producing desired breakdown point
cc1	tukey bisquare function parameter producing desired breakdown point
C	sub-compositional matrix
we	penalization index for model parameters beta
type	1/2 for l1 / l2 loss in the model
control	a list of internal parameters controlling the model fitting

Value

betaf	TModel parameter estimate
residuals	residual estimate

References

Mishra, A., Mueller, C.,(2019) *Robust regression with compositional covariates. In prepration*. arXiv:1909.04990.

Examples

```
library(robregcc)
library(magrittr)

data(simulate_robregcc)
X <- simulate_robregcc$X;
y <- simulate_robregcc$y
C <- simulate_robregcc$C
n <- nrow(X); p <- ncol(X); k <-  nrow(C)

Xt <- cbind(1,X)  # include intercept in predictor
C <- cbind(0,C)    # include intercept in constraint
bw <- c(0,rep(1,p)) # weights not penalize intercept

example_seed <- 2*p+1
set.seed(example_seed)

# Breakdown point for tukey Bisquare loss function
b1 = 0.5                    # 50% breakdown point
cc1 =  1.567                # corresponding model parameter
b1 = 0.25; cc1 =  2.937

# Initialization [PSC analysis for compositional data]
control <- robregcc_option(maxiter = 1000,
 tol = 1e-4,lminfac = 1e-7)
fit.init <- cpsc_sp(Xt, y,alp = 0.4, cfac = 2, b1 = b1,
cc1 = cc1,C,bw,1,control)
```

plot_cv *Plot cross-validation error plot*

Description

S3 methods plotting crossvalidation error using the object obtained from robregcc.

Usage

```
plot_cv(object)
```

Arguments

object	robregcc fitted onject

Value

generate cv error plot

Examples

```
library(magrittr)
library(robregcc)

data(simulate_robregcc)
X <- simulate_robregcc$X;
y <- simulate_robregcc$y
C <- simulate_robregcc$C
n <- nrow(X); p <- ncol(X); k <-  nrow(C)

Xt <- cbind(1,X)                          # accounting for intercept in predictor
C <- cbind(0,C)                            # accounting for intercept in constraint
bw <- c(0,rep(1,p))                        # weight matrix to not penalize intercept

example_seed <- 2*p+1
set.seed(example_seed)

# Breakdown point for tukey Bisquare loss function
b1 = 0.5                    # 50% breakdown point
cc1 =  1.567                # corresponding model parameter
b1 = 0.25; cc1 =  2.937

# Initialization [PSC analysis for compositional data]
control <- robregcc_option(maxiter=1000,tol = 1e-4,lminfac = 1e-7)
fit.init <- cpsc_sp(Xt, y,alp = 0.4, cfac = 2, b1 = b1,
cc1 = cc1,C,bw,1,control)

## Robust model fitting

# control parameters
```

```
control <- robregcc_option()
beta.wt <- fit.init$betaR    # Set weight for model parameter beta
beta.wt[1] <- 0
control$gamma = 1            # gamma for constructing  weighted penalty
control$spb = 40/p           # fraction of maximum non-zero model parameter beta
control$outMiter = 1000      # Outer loop iteration
control$inMiter = 3000       # Inner loop iteration
control$nlam = 50            # Number of tuning parameter lambda to be explored
control$lmaxfac = 1          # Parameter for constructing sequence of lambda
control$lminfac = 1e-8       # Parameter for constructing sequence of lambda
control$tol = 1e-20;         # tolrence parameter for converging [inner  loop]
control$out.tol = 1e-16      # tolerence parameter for convergence [outer loop]
control$kfold = 10           # number of fold of crossvalidation
control$sigmafac = 2#1.345
# Robust regression using adaptive lasso penalty
fit.ada <- robregcc_sp(Xt,y,C,
                       beta.init = beta.wt,  cindex = 1,
                       gamma.init = fit.init$residuals,
                       control = control,
                       penalty.index = 1, alpha = 0.95)

# Robust regression using lasso penalty [Huber equivalent]
fit.soft <- robregcc_sp(Xt,y,C, cindex = 1,
                        control = control, penalty.index = 2,
                        alpha = 0.95)


# Robust regression using hard thresholding penalty
control$lmaxfac = 1e2              # Parameter for constructing sequence of lambda
control$lminfac = 1e-3             # Parameter for constructing sequence of lambda
control$sigmafac = 2#1.345
fit.hard <- robregcc_sp(Xt,y,C, beta.init = fit.init$betaf,
                        gamma.init = fit.init$residuals,
                        cindex = 1,
                        control = control, penalty.index = 3,
                        alpha = 0.95)



plot_cv(fit.ada)
plot_cv(fit.soft)
plot_cv(fit.hard)
```

---

plot_path *Plot solution path at different value of lambda*

Description

S3 methods plotting solution path of model parameter and mean shift using the object obtained from robregcc.

Usage

```
plot_path(object, ptype = 0)
```

Arguments

object	Object generated by robregcc.
ptype	path type 0/1 for Gamma/Beta path respectvely

Value

plot solution path

Examples

```
library(magrittr)
library(robregcc)

data(simulate_robregcc)
X <- simulate_robregcc$X;
y <- simulate_robregcc$y
C <- simulate_robregcc$C
n <- nrow(X); p <- ncol(X); k <-  nrow(C)

Xt <- cbind(1,X)                          # accounting for intercept in predictor
C <- cbind(0,C)                            # accounting for intercept in constraint
bw <- c(0,rep(1,p))                        # weight matrix to not penalize intercept

example_seed <- 2*p+1
set.seed(example_seed)

# Breakdown point for tukey Bisquare loss function
b1 = 0.5                    # 50% breakdown point
cc1 =  1.567                # corresponding model parameter
b1 = 0.25; cc1 =  2.937

# Initialization [PSC analysis for compositional data]
control <- robregcc_option(maxiter=1000,tol = 1e-4,lminfac = 1e-7)
fit.init <- cpsc_sp(Xt, y,alp = 0.4, cfac = 2, b1 = b1,
cc1 = cc1,C,bw,1,control)

## Robust model fitting

# control parameters
control <- robregcc_option()
beta.wt <- fit.init$betaR    # Set weight for model parameter beta
beta.wt[1] <- 0
```

```
control$gamma = 1            # gamma for constructing  weighted penalty
control$spb = 40/p           # fraction of maximum non-zero model parameter beta
control$outMiter = 1000      # Outer loop iteration
control$inMiter = 3000       # Inner loop iteration
control$nlam = 50            # Number of tuning parameter lambda to be explored
control$lmaxfac = 1          # Parameter for constructing sequence of lambda
control$lminfac = 1e-8       # Parameter for constructing sequence of lambda
control$tol = 1e-20;         # tolrence parameter for converging [inner  loop]
control$out.tol = 1e-16      # tolerence parameter for convergence [outer loop]
control$kfold = 10           # number of fold of crossvalidation
control$sigmafac = 2#1.345
# Robust regression using adaptive lasso penalty
fit.ada <- robregcc_sp(Xt,y,C,
                       beta.init = beta.wt,  cindex = 1,
                       gamma.init = fit.init$residuals,
                       control = control,
                       penalty.index = 1, alpha = 0.95)

# Robust regression using lasso penalty [Huber equivalent]
fit.soft <- robregcc_sp(Xt,y,C, cindex = 1,
                        control = control, penalty.index = 2,
                        alpha = 0.95)


# Robust regression using hard thresholding penalty
control$lmaxfac = 1e2              # Parameter for constructing sequence of lambda
control$lminfac = 1e-3             # Parameter for constructing sequence of lambda
control$sigmafac = 2#1.345
fit.hard <- robregcc_sp(Xt,y,C, beta.init = fit.init$betaf,
                        gamma.init = fit.init$residuals,
                        cindex = 1,
                        control = control, penalty.index = 3,
                        alpha = 0.95)
plot_path(fit.ada)
plot_path(fit.soft)
plot_path(fit.hard)
```

`plot_resid` *Plot residuals estimate from robregcc object*

Description

S3 methods extracting residuals from the objects generated by `robregcc`.

Usage

```
plot_resid(object, type = 0, s = 0)
```

Arguments

object	Object generated by robregcc.
type	0/1 residual estimate before/after sanity check
s	0/1 no/yes 1se rule

Value

plot estimated residual

Examples

```
library(magrittr)
library(robregcc)

data(simulate_robregcc)
X <- simulate_robregcc$X;
y <- simulate_robregcc$y
C <- simulate_robregcc$C
n <- nrow(X); p <- ncol(X); k <-  nrow(C)

Xt <- cbind(1,X)                          # accounting for intercept in predictor
C <- cbind(0,C)                            # accounting for intercept in constraint
bw <- c(0,rep(1,p))                        # weight matrix to not penalize intercept

example_seed <- 2*p+1
set.seed(example_seed)

# Breakdown point for tukey Bisquare loss function
b1 = 0.5                    # 50% breakdown point
cc1 =  1.567                # corresponding model parameter
b1 = 0.25; cc1 =  2.937

# Initialization [PSC analysis for compositional data]
control <- robregcc_option(maxiter=1000,tol = 1e-4,lminfac = 1e-7)
fit.init <- cpsc_sp(Xt, y,alp = 0.4, cfac = 2, b1 = b1,
cc1 = cc1,C,bw,1,control)

## Robust model fitting

# control parameters
control <- robregcc_option()
beta.wt <- fit.init$betaR    # Set weight for model parameter beta
beta.wt[1] <- 0
control$gamma = 1            # gamma for constructing  weighted penalty
control$spb = 40/p           # fraction of maximum non-zero model parameter beta
control$outMiter = 1000      # Outer loop iteration
control$inMiter = 3000       # Inner loop iteration
control$nlam = 50            # Number of tuning parameter lambda to be explored
control$lmaxfac = 1          # Parameter for constructing sequence of lambda
control$lminfac = 1e-8       # Parameter for constructing sequence of lambda
```

```
control$tol = 1e-20;         # tolrence parameter for converging [inner  loop]
control$out.tol = 1e-16      # tolerence parameter for convergence [outer loop]
control$kfold = 10           # number of fold of crossvalidation
control$sigmafac = 2#1.345
# Robust regression using adaptive lasso penalty
fit.ada <- robregcc_sp(Xt,y,C,
                       beta.init = beta.wt,  cindex = 1,
                       gamma.init = fit.init$residuals,
                       control = control,
                       penalty.index = 1, alpha = 0.95)

# Robust regression using lasso penalty [Huber equivalent]
fit.soft <- robregcc_sp(Xt,y,C, cindex = 1,
                        control = control, penalty.index = 2,
                        alpha = 0.95)


# Robust regression using hard thresholding penalty
control$lmaxfac = 1e2               # Parameter for constructing sequence of lambda
control$lminfac = 1e-3              # Parameter for constructing sequence of lambda
control$sigmafac = 2#1.345
fit.hard <- robregcc_sp(Xt,y,C, beta.init = fit.init$betaf,
                        gamma.init = fit.init$residuals,
                        cindex = 1,
                        control = control, penalty.index = 3,
                        alpha = 0.95)



plot_resid(fit.ada)
plot_resid(fit.soft)
plot_resid(fit.hard)
```

`residuals` *Extract residuals estimate from the sparse version of the robregcc fitted object.*

Description

Robust residuals estimate

Usage

```
## S3 method for class 'robregcc'
residuals(object, ...)
```

Arguments

object	robregcc fitted onject
...	Other argumnts for future usage.

Value

residuals estimate

Examples

```
library(magrittr)
library(robregcc)

data(simulate_robregcc)
X <- simulate_robregcc$X;
y <- simulate_robregcc$y
C <- simulate_robregcc$C
n <- nrow(X); p <- ncol(X); k <-  nrow(C)

Xt <- cbind(1,X)                          # accounting for intercept in predictor
C <- cbind(0,C)                            # accounting for intercept in constraint
bw <- c(0,rep(1,p))                        # weight matrix to not penalize intercept


example_seed <- 2*p+1
set.seed(example_seed)

# Breakdown point for tukey Bisquare loss function
b1 = 0.5                    # 50% breakdown point
cc1 =  1.567                # corresponding model parameter
b1 = 0.25; cc1 =  2.937

# Initialization [PSC analysis for compositional data]
control <- robregcc_option(maxiter=1000,tol = 1e-4,lminfac = 1e-7)
fit.init <- cpsc_sp(Xt, y,alp = 0.4, cfac = 2, b1 = b1,
cc1 = cc1,C,bw,1,control)

## Robust model fitting

# control parameters
control <- robregcc_option()
beta.wt <- fit.init$betaR    # Set weight for model parameter beta
beta.wt[1] <- 0
control$gamma = 1            # gamma for constructing  weighted penalty
control$spb = 40/p           # fraction of maximum non-zero model parameter beta
control$outMiter = 1000      # Outer loop iteration
control$inMiter = 3000       # Inner loop iteration
control$nlam = 50            # Number of tuning parameter lambda to be explored
control$lmaxfac = 1          # Parameter for constructing sequence of lambda
control$lminfac = 1e-8       # Parameter for constructing sequence of lambda
control$tol = 1e-20;         # tolrence parameter for converging [inner  loop]
```

```
control$out.tol = 1e-16      # tolerence parameter for convergence [outer loop]
control$kfold = 10           # number of fold of crossvalidation
control$sigmafac = 2#1.345
# Robust regression using adaptive lasso penalty
fit.ada <- robregcc_sp(Xt,y,C,
                       beta.init = beta.wt,  cindex = 1,
                       gamma.init = fit.init$residuals,
                       control = control,
                       penalty.index = 1, alpha = 0.95)

# Robust regression using lasso penalty [Huber equivalent]
fit.soft <- robregcc_sp(Xt,y,C, cindex = 1,
                        control = control, penalty.index = 2,
                        alpha = 0.95)


# Robust regression using hard thresholding penalty
control$lmaxfac = 1e2               # Parameter for constructing sequence of lambda
control$lminfac = 1e-3              # Parameter for constructing sequence of lambda
control$sigmafac = 2#1.345
fit.hard <- robregcc_sp(Xt,y,C, beta.init = fit.init$betaf,
                        gamma.init = fit.init$residuals,
                        cindex = 1,
                        control = control, penalty.index = 3,
                        alpha = 0.95)


residuals(fit.ada)
residuals(fit.soft)
residuals(fit.hard)
```

`robregcc_option` *Control parameter for model estimation:*

Description

The model approach use scaled lasoo approach for model selection.

Usage

```
robregcc_option(
  maxiter = 10000,
  tol = 1e-10,
  nlam = 100,
  out.tol = 1e-08,
  lminfac = 1e-08,
  lmaxfac = 10,
```

```
  mu = 1,
  nu = 1.05,
  sp = 0.3,
  gamma = 2,
  outMiter = 3000,
  inMiter = 500,
  kmaxS = 500,
  tolS = 1e-04,
  nlamx = 20,
  nlamy = 20,
  spb = 0.3,
  spy = 0.3,
  lminfacX = 1e-06,
  lminfacY = 0.01,
  kfold = 10,
  fullpath = 0,
  sigmafac = 2
)
```

Arguments

maxiter	maximum number of iteration for convergence
tol	tolerance value set for convergence
nlam	number of lambda to be genrated to obtain solution path
out.tol	tolernce value set for convergence of outer loop
lminfac	a multiplier of determing lambda_min as a fraction of lambda_max
lmaxfac	a multiplier of lambda_max
mu	penalty parameter used in enforcing orthogonality
nu	penalty parameter used in enforcing orthogonality (incremental rate of mu)
sp	maximum proportion of nonzero elements in shift parameter
gamma	adaptive penalty weight exponential factor
outMiter	maximum number of outer loop iteration
inMiter	maximum number of inner loop iteration
kmaxS	maximum number of iteration for fast S estimator for convergence
tolS	tolerance value set for convergence in case of fast S estimator
nlamx	number of x lambda
nlamy	number of y lambda
spb	sparsity in beta
spy	sparsity in shift gamma
lminfacX	a multiplier of determing lambda_min as a fraction of lambda_max for sparsity in X
lminfacY	a multiplier of determing lambda_min as a fraction of lambda_max for sparsity in shift parameter

kfold	nummber of folds for crossvalidation
fullpath	1/0 to get full path yes/no
sigmafac	multiplying factor for the range of standard deviation

Value

a list of controling parameter.

Examples

```
# default options
library(robregcc)
control_default = robregcc_option()
# manual options
control_manual <- robregcc_option(maxiter=1000,tol = 1e-4,lminfac = 1e-7)
```

---

robregcc_sim *Simulation data*

Description

Simulate data for the robust regression with compositional covariates

Usage

```
robregcc_sim(n, betacc, beta0, O, Sigma, levg, snr, shft, m, C, out = list())
```

Arguments

n	sample size
betacc	model parameter satisfying compositional covariates
beta0	intercept
O	number of outlier
Sigma	covariance matrix of simulated predictors
levg	1/0 whether to include leveraged observation or not
snr	noise to signal ratio
shft	multiplying factor to model variance for creating outlier
m	test sample size
C	subcompositional matrix
out	list for obtaining output with simulated data structure

Value

a list containing simulated output.

References

Mishra, A., Mueller, C.,(2019) *Robust regression with compositional covariates. In prepration.* arXiv:1909.04990.

Examples

```
## Simulation example:
library(robregcc)
library(magrittr)

## n: sample size
## p: number of predictors
## o: fraction of observations as outliers
## L: {0,1} => leveraged {no, yes},
## s: multiplicative factor
## ngrp: number of subgroup in the model
## snr: noise to signal ratio for computing true std_err

## Define parameters to simulate example
p <- 80                # number of predictors
n <- 300               # number of sample
O <- 0.10*n            # number of outlier
L <- 1
s <- 8
ngrp <- 4              # number of sub-composition
snr <- 3               # Signal to noise ratio
example_seed <- 2*p+1  # example seed
set.seed(example_seed)
# Simulate subcomposition matrix
C1 <- matrix(0,ngrp,23)
tind <- c(0,10,16,20,23)
for (ii in 1:ngrp)
  C1[ii,(tind[ii] + 1):tind[ii + 1]] <- 1
C <- matrix(0,ngrp,p)
C[,1:ncol(C1)] <- C1
# model parameter beta
beta0 <- 0.5
beta <- c(1, -0.8, 0.4, 0, 0, -0.6, 0, 0, 0, 0, -1.5, 0, 1.2, 0, 0, 0.3)
beta <- c(beta,rep(0,p - length(beta)))
# Simulate response and predictor, i.e., X, y
Sigma  <- 1:p %>% outer(.,.,'-') %>% abs(); Sigma  <- 0.5^Sigma
data.case <- vector("list",1)
set.seed(example_seed)
data.case <- robregcc_sim(n,beta,beta0, O = O,
      Sigma,levg = L, snr,shft = s,0, C,out = data.case)
data.case$C <- C
# We have saved a copy of simulated data in the package
# with name simulate_robregcc
# simulate_robregcc = data.case;
# save(simulate_robregcc, file ='data/simulate_robregcc.rda')

X <- data.case$X                # predictor matrix
```

```
y <- data.case$y                # model response
```

`robregcc_sp` *Robust model estimation approach for regression with compositional covariates.*

Description

Fit regression model with compositional covariates for a range of tuning parameter lambda. Model parameters is assumed to be sparse.

Usage

```
robregcc_sp(
  X,
  y,
  C,
  beta.init = NULL,
  gamma.init = NULL,
  cindex = 1,
  control = list(),
  penalty.index = 3,
  alpha = 1,
  verbose = TRUE
)
```

Arguments

`X`	predictor matrix
`y`	phenotype/response vector
`C`	conformable sub-compositional matrix
`beta.init`	initial value of model parameter beta
`gamma.init`	inital value of shift parameter gamma
`cindex`	index of control (not penalized) variable in the model
`control`	a list of internal parameters controlling the model fitting
`penalty.index`	a vector of length 2 specifying type of penalty for model parameter and shift parameter respectively. 1, 2, 3 corresponding to adaptive, soft and hard penalty
`alpha`	elastic net penalty
`verbose`	TRUE/FALSE for showing progress of the cross validation

Value

Method	Type of penalty used
betapath	model parameter estimate along solution path
gammapath	shift parameter estimate along solution path
lampath	sequence of fitted lambda)
k0	scaling factor
cver	error from k fold cross validation
selInd	selected index from minimum and 1se rule cross validation error
beta0	beta estimate corresponding to selected index
gamma0	mean shift estimate corresponding to selected index
residual0	residual estimate corresponding to selected index
inlier0	inlier index corresponding to selected index
betaE	Post selection estimate corresponding to selected index
residualE	post selection residual corresponding to selected index
inlierE	post selection inlier index corresponding to selected index

References

Mishra, A., Mueller, C.,(2019) *Robust regression with compositional covariates. In prepration.* arXiv:1909.04990.

Examples

```
library(magrittr)
library(robregcc)

data(simulate_robregcc)
X <- simulate_robregcc$X;
y <- simulate_robregcc$y
C <- simulate_robregcc$C
n <- nrow(X); p <- ncol(X); k <-  nrow(C)

Xt <- cbind(1,X)                          # accounting for intercept in predictor
C <- cbind(0,C)                            # accounting for intercept in constraint
bw <- c(0,rep(1,p))                        # weight matrix to not penalize intercept

example_seed <- 2*p+1
set.seed(example_seed)

# Breakdown point for tukey Bisquare loss function
b1 = 0.5                    # 50% breakdown point
cc1 =  1.567                # corresponding model parameter
b1 = 0.25; cc1 =  2.937

# Initialization [PSC analysis for compositional data]
control <- robregcc_option(maxiter=1000,tol = 1e-4,lminfac = 1e-7)
```

```
fit.init <- cpsc_sp(Xt, y,alp = 0.4, cfac = 2, b1 = b1,
cc1 = cc1,C,bw,1,control)

## Robust model fitting

# control parameters
control <- robregcc_option()
beta.wt <- fit.init$betaR    # Set weight for model parameter beta
beta.wt[1] <- 0
control$gamma = 1            # gamma for constructing  weighted penalty
control$spb = 40/p           # fraction of maximum non-zero model parameter beta
control$outMiter = 1000      # Outer loop iteration
control$inMiter = 3000       # Inner loop iteration
control$nlam = 50            # Number of tuning parameter lambda to be explored
control$lmaxfac = 1          # Parameter for constructing sequence of lambda
control$lminfac = 1e-8       # Parameter for constructing sequence of lambda
control$tol = 1e-20;         # tolrence parameter for converging [inner  loop]
control$out.tol = 1e-16      # tolerence parameter for convergence [outer loop]
control$kfold = 10           # number of fold of crossvalidation
control$sigmafac = 2#1.345
# Robust regression using adaptive lasso penalty
fit.ada <- robregcc_sp(Xt,y,C,
                       beta.init = beta.wt,  cindex = 1,
                       gamma.init = fit.init$residuals,
                       control = control,
                       penalty.index = 1, alpha = 0.95)

# Robust regression using lasso penalty [Huber equivalent]
fit.soft <- robregcc_sp(Xt,y,C, cindex = 1,
                        control = control, penalty.index = 2,
                        alpha = 0.95)


# Robust regression using hard thresholding penalty
control$lmaxfac = 1e2               # Parameter for constructing sequence of lambda
control$lminfac = 1e-3              # Parameter for constructing sequence of lambda
control$sigmafac = 2#1.345
fit.hard <- robregcc_sp(Xt,y,C, beta.init = fit.init$betaf,
                        gamma.init = fit.init$residuals,
                        cindex = 1,
                        control = control, penalty.index = 3,
                        alpha = 0.95)
```

`simulate_robregcc` *Simulated date for testing functions in the robregcc package (sparse setting).*

Description

A list of response (y), predictors (X) and sub-cpmposition matrix (C).

Usage

```
data(simulate_robregcc)
```

Format

A list with three components:

X Compositional predictors.

y Outcome with outliers.

C Sub-cmposition matrix.

Details

Vector y, response with a certain percentage of observations as outliers.

Matrix X, Compositional predictors.

Source

Similated data

Examples

```
library(robregcc)
data(simulate_robregcc)
X <- simulate_robregcc$X;
y <- simulate_robregcc$y
C <- simulate_robregcc$C
n <- nrow(X); p <- ncol(X); k <-  nrow(C)
```

Index

∗ **datasets**
simulate_robregcc, 21

classo, 2
classo_path, 3
coef_cc, 4
cpsc_sp, 6

plot_cv, 8
plot_path, 9
plot_resid, 11

residuals, 13
robregcc_option, 15
robregcc_sim, 17
robregcc_sp, 19

simulate_robregcc, 21