

Package: robustreg (via r-universe)

September 8, 2024

Version 0.1-11

Date 2019-05-09

Title Robust Regression Functions

Author Ian M. Johnson <ijca2013@gmail.com>

Maintainer Ian M. Johnson <ijca2013@gmail.com>

Depends R (>= 3.6.0)

Description Linear regression functions using Huber and bisquare psi functions. Optimal weights are calculated using IRLS algorithm.

License GPL (>= 2)

Imports stats (>= 3.6.0), Matrix (>= 1.1.0), Rcpp (>= 0.11.3)

LinkingTo Rcpp, RcppArmadillo

NeedsCompilation yes

Repository CRAN

Date/Publication 2019-05-10 07:50:03 UTC

Contents

fit_rcpp	2
mad_rcpp	2
median_rcpp	3
psiBS_rcpp	3
psiHuber_rcpp	4
robustRegBS	5
robustRegH	6
Index	8

`fit_rcpp`*Predict y from X and b*

Description

Predict y vector from X design matrix and b vector

Usage

```
fit_rcpp(X,b)
```

Arguments

X	Design matrix
b	Estimates of beta

Author(s)

Ian M. Johnson

Examples

```
j <- rep(1, 5)
x1 <- rnorm(5)
x2 <- rnorm(5, 10, 20)
X = as.matrix(data.frame(j, x1, x2))
b <- 1:3
fit_rcpp(X, b)
```

`mad_rcpp`*Median Absolute Deviation (MAD)*

Description

Rcpp fast implementation of median absolute deviation (MAD)

Usage

```
mad_rcpp(r, scale_factor = 1.4826)
```

Arguments

r	A numeric vector
scale_factor	Scale factor

Author(s)

Ian M. Johnson

Examples

```
mad(1:100)
```

median_rcpp

Median

Description

Rcpp fast implementation of median

Usage

```
median_rcpp(x)
```

Arguments

x A numeric vector containing the values whose median is to be computed.

Author(s)

Ian M. Johnson

Examples

```
median_rcpp(1:100)
```

psiBS_rcpp

Tukey's Bisquare Psi Function

Description

Rcpp fast implementation of Tukey's Bisquare psi function

Usage

```
psiBS_rcpp(r,c)
```

Arguments

r A numeric vector
c Tuning constant

Author(s)

Ian M. Johnson

Examples

```
## Not run:  
psiBS_rcpp(r,c)  
  
## End(Not run)
```

psiHuber_rcpp

Huber Psi Function

Description

Rcpp fast implementation of Huber's Psi Function

Usage

```
psiHuber_rcpp(r,c)
```

Arguments

r	A numeric vector
c	Tuning constant

Author(s)

Ian M. Johnson

Examples

```
## Not run:  
psiHuber_rcpp(r,c)  
  
## End(Not run)
```

robustRegBS

Robust Fitting of Linear Models using Bisquare Psi Function

Description

Using iteratively reweighted least squares (IRLS), the function calculates the optimal weights to perform m-estimator or bounded influence regression. Returns robust beta estimates, mean squared error (MSE) and prints robust ANOVA table.

Usage

```
robustRegBS(formula, data, tune=4.685, m=TRUE, max.it=1000, tol=1e-5, anova.table=FALSE)
```

Arguments

formula	Model
data	A data frame containing the variables in the model.
tune	Tuning Constant. Default value of 4.685 is 95% asymptotically efficient against outliers
m	If TRUE, calculates m estimates of beta. If FALSE, calculates bounded influence estimates of beta
max.it	Maximum number of iterations to achieve convergence in IRLS algorithm
tol	Tolerance level in determining convergence
anova.table	If TRUE, prints robust ANOVA table

Details

M-estimates of beta should be used when evaluating least squares estimates of beta and diagnostics show outliers. Least squares estimates of beta should be used as starting points to achieve convergence.

Bounded influence estimates of beta should be used when evaluating least squares estimates of beta and diagnostics show large values of the "Hat Matrix" diagonals and outliers.

Note

Original package written in 2006

Author(s)

Ian M. Johnson

References

Tukey,
Birch, Robust F-Test, 1983

See Also

robustRegH()

Examples

```
data(stackloss)
robustRegBS(stack.loss~Air.Flow+Water.Temp,data=stackloss)

#If X matrix contained large values of H matrix (high influence points)
robustRegBS(stack.loss~Air.Flow+Water.Temp,data=stackloss,m=FALSE)
```

robustRegH

Robust Fitting of Linear Models using Huber Psi Function

Description

Using iteratively reweighted least squares (IRLS), the function calculates the optimal weights to perform m-estimator or bounded influence regression. Returns robust beta estimates, mean squared error (MSE) and prints robust ANOVA table

Usage

```
robustRegH(formula,data,tune=1.345,m=TRUE,max.it=1000,tol=1e-5,anova.table=FALSE)
```

Arguments

formula	Model
data	A data frame containing the variables in the model.
tune	Tuning Constant. Default value of 1.345 is 95% asymptotically efficient against outliers
m	If TRUE, calculates m estimates of beta. If FALSE, calculates bounded influence estimates of beta
max.it	Maximum number of iterations to achieve convergence in IRLS algorithm
tol	Tolerance level in determining convergence
anova.table	If TRUE, prints robust ANOVA table

Details

M-estimates of beta should be used when evaluating least squares estimates of beta and diagnostics show outliers. Least squares estimates of beta are used as starting points to achieve convergence.

Bounded influence estimates of beta should be used when evaluating least squares estimates of beta and diagnostics show large values of the "Hat Matrix" diagonals and outliers.

Note

Original package written in 2006

Author(s)

Ian M. Johnson

References

P. J. Huber (1981) Robust Statistics. Wiley.

Birch (1983) Robust F-Test

See Also

`robustRegBS()`

Examples

```
data(stackloss)
```

```
robustRegH(stack.loss~Air.Flow+Water.Temp,data=stackloss)
```

```
#If X matrix contained large values of H matrix (high influence points)
```

```
robustRegH(stack.loss~Air.Flow+Water.Temp,data=stackloss,m=FALSE)
```

Index

* regression

robustRegBS, 5

robustRegH, 6

fit_rcpp, 2

mad_rcpp, 2

median_rcpp, 3

psiBS_rcpp, 3

psiHuber_rcpp, 4

robustRegBS, 5

robustRegH, 6