

Package: rstanemax (via r-universe)

December 6, 2024

Version 0.1.7

Title Emax Model Analysis with 'Stan'

Description Perform sigmoidal Emax model fit using 'Stan' in a formula notation, without writing 'Stan' model code.

Encoding UTF-8

License GPL-3 | file LICENSE

LazyData true

ByteCompile true

Depends R (>= 3.5.0), methods, Rcpp (>= 1.0.0)

Imports rstan (>= 2.26.0), rstantools (>= 2.3.0), magrittr (>= 1.5), dplyr (>= 0.8.0), tidyr (>= 1.0.0), purrr (>= 0.3.0), ggplot2 (>= 2.2.1), posterior, boot

LinkingTo StanHeaders (>= 2.26.0), rstan (>= 2.26.0), BH (>= 1.69.0-1), Rcpp (>= 1.0.0), RcppEigen (>= 0.3.3.5.0), RcppParallel (>= 5.0.2)

SystemRequirements GNU make

NeedsCompilation yes

RoxygenNote 7.3.2

Suggests testthat, knitr, rmarkdown, spelling

VignetteBuilder knitr

Language en-US

URL <https://github.com/yoshidk6/rstanemax>,
<https://yoshidk6.github.io/rstanemax/>

BugReports <https://github.com/yoshidk6/rstanemax/issues>

Author Kenta Yoshida [aut, cre]

(<<https://orcid.org/0000-0003-4967-3831>>), Danielle Navarro [aut], Trustees of Columbia University [cph] (src/init.cpp, tools/make_cc.R, R/stanmodels.R)

Maintainer Kenta Yoshida <yoshida.kenta.6@gmail.com>

Repository CRAN

Date/Publication 2024-12-06 15:10:02 UTC

Config/pak/sysreqs make libicu-dev

Contents

rstanemax-package	2
as_draws	3
exposure.response.sample	5
exposure.response.sample.binary	5
exposure.response.sample.with.cov	6
extract_param	7
posterior_predict	7
stanemax-methods	9
stan_emax	10
stan_emax_binary	12

Index **14**

rstanemax-package *The 'rstanemax' package.*

Description

Perform sigmoidal Emax model fit using Stan without writing Stan model code.

Author(s)

Maintainer: Kenta Yoshida <yoshida.kenta.6@gmail.com> ([ORCID](#))

Authors:

- Danielle Navarro <djnavarro@protonmail.com>

Other contributors:

- Trustees of Columbia University (src/init.cpp, tools/make_cc.R, R/stanmodels.R) [copyright holder]

References

Stan Development Team (2018). RStan: the R interface to Stan. R package version 2.18.2. <http://mc-stan.org>

See Also

Useful links:

- <https://github.com/yoshidk6/rstanemax>
- <https://yoshidk6.github.io/rstanemax/>
- Report bugs at <https://github.com/yoshidk6/rstanemax/issues>

as_draws

Convert stanemax object to a posterior draws object

Description

Convert stanemax object to a posterior draws object

Usage

```
as_draws(x, ...)  
  
as_draws_list(x, ...)  
  
as_draws_array(x, ...)  
  
as_draws_df(x, ...)  
  
as_draws_matrix(x, ...)  
  
as_draws_rvars(x, ...)  
  
## S3 method for class 'stanemax'  
as_draws(x, inc_warmup = FALSE, ...)  
  
## S3 method for class 'stanemaxbin'  
as_draws(x, inc_warmup = FALSE, ...)  
  
## S3 method for class 'stanemax'  
as_draws_list(x, inc_warmup = FALSE, ...)  
  
## S3 method for class 'stanemaxbin'  
as_draws_list(x, inc_warmup = FALSE, ...)  
  
## S3 method for class 'stanemax'  
as_draws_array(x, inc_warmup = FALSE, ...)  
  
## S3 method for class 'stanemaxbin'  
as_draws_array(x, inc_warmup = FALSE, ...)
```

```
## S3 method for class 'stanemax'  
as_draws_df(x, inc_warmup = FALSE, ...)  
  
## S3 method for class 'stanemaxbin'  
as_draws_df(x, inc_warmup = FALSE, ...)  
  
## S3 method for class 'stanemax'  
as_draws_matrix(x, inc_warmup = FALSE, ...)  
  
## S3 method for class 'stanemaxbin'  
as_draws_matrix(x, inc_warmup = FALSE, ...)  
  
## S3 method for class 'stanemax'  
as_draws_rvars(x, inc_warmup = FALSE, ...)  
  
## S3 method for class 'stanemaxbin'  
as_draws_rvars(x, inc_warmup = FALSE, ...)
```

Arguments

x	An object of class stanemax.
...	Arguments passed to individual methods (if applicable).'
inc_warmup	Should warmup draws be included? Defaults to FALSE.

Value

A draws object of the appropriate subclass

See Also

[draws subset_draws](#)

Examples

```
## Not run:  
data(exposure.response.sample)  
fit <- stan_emax(response ~ exposure, exposure.response.sample)  
posterior::as_draws_list(fit)  
posterior::as_draws_array(fit)  
posterior::as_draws_df(fit)  
posterior::as_draws_matrix(fit)  
posterior::as_draws_rvars(fit)  
  
## End(Not run)
```

`exposure.response.sample`*Sample simulated data for exposure-response.*

Description

Sample simulated data for exposure-response.

Usage`exposure.response.sample`**Format**

A data frame with columns:

dose Dose levels used for simulation of pharmacokinetics

exposure Simulated exposure

response Simulated pharmacodynamic response

Examples`exposure.response.sample`

`exposure.response.sample.binary`*Sample simulated data for exposure-response for binary endpoint*

Description

Sample simulated data for exposure-response for binary endpoint

Usage`exposure.response.sample.binary`**Format**

A data frame with columns:

conc Simulated exposure

y_logit Simulated logit(p)

y_prob Simulated p

y Simulated event (1 or 0)

y_cov_logit Simulated logit(p) for model with covariate

y_cov_prob Simulated p for model with covariate
y_cov Simulated event (1 or 0) for model with covariate
sex_num 1 or 0
sex female or male

Examples

```
exposure.response.sample
```

```
exposure.response.sample.with.cov
```

Sample simulated data for exposure-response with covariates

Description

Sample simulated data for exposure-response with covariates

Usage

```
exposure.response.sample.with.cov
```

Format

A data frame with columns:

dose Dose levels used for simulation of pharmacokinetics

conc Simulated exposure

resp Simulated pharmacodynamic response

cov1 Covariate 1 for e0

cov2 Covariate 2 for emax

cov3 Covariate 3 for ec50 (data type factor)

cov3num Covariate 3 for ec50 (data type numeric)

Examples

```
exposure.response.sample
```

extract_param	<i>Extract posterior draws of key parameters</i>
---------------	--

Description

Extract posterior draws of key parameters

Usage

```
extract_param(object)
```

Arguments

object A stanemax class object

Value

A tibble containing posterior draws of key parameters. If covariate(s) are included in the model, posterior draws for different combinations of covariates are supplied in a long format - e.g. if there are posterior draws of 100 samples and 4 levels of the covariates, the returned tibble will have the length of 400

posterior_predict	<i>Outcome prediction from posterior distribution of parameters</i>
-------------------	---

Description

Compute outcome predictions using posterior samples. Exposure data for prediction can be either original data used for model fit or new data.

Usage

```
posterior_predict(object, ...)

## S3 method for class 'stanemax'
posterior_predict(
  object,
  newdata = NULL,
  returnType = c("matrix", "dataframe", "tibble"),
  newDatatype = c("raw", "modelframe"),
  ...
)

## S3 method for class 'stanemaxbin'
posterior_predict(
  object,
```

```

newdata = NULL,
returnType = c("matrix", "dataframe", "tibble"),
newDataType = c("raw", "modelframe"),
...
)

posterior_predict_quantile(
  object,
  newdata = NULL,
  ci = 0.9,
  pi = 0.9,
  newDataType = c("raw", "modelframe")
)

```

Arguments

object	A stanemax class object
...	Additional arguments passed to methods.
newdata	An optional data frame that contains columns needed for model to run (exposure and covariates). If the model does not have any covariate, this can be a numeric vector corresponding to the exposure metric.
returnType	An optional string specifying the type of return object.
newDataType	An optional string specifying the type of newdata input, whether in the format of an original data frame or a processed model frame. Mostly used for internal purposes and users can usually leave at default.
ci	Credible interval of the response without residual variability.
pi	Prediction interval of the response with residual variability.

Details

Run `vignette("emaxmodel", package = "rstanemax")` to see how you can use the posterior prediction for plotting estimated Emax curve.

Value

An object that contain predicted response with posterior distribution of parameters. The default is a matrix containing predicted response for `stan_emax()` and `.epred` for `stan_emax_binary()`. Each row of the matrix is a vector of predictions generated using a single draw of the model parameters from the posterior distribution.

If either `dataframe` or `tibble` is specified, the function returns a data frame or tibble object in a long format - each row is a prediction generated using a single draw of the model parameters and a corresponding exposure.

Several types of predictions are generated with this function.

For continuous endpoint model (`stan_emax()`),

- `.linpred` & `.epred`: prediction without considering residual variability and is intended to provide credible interval of "mean" response.

- `.prediction`: include residual variability in its calculation, therefore the range represents prediction interval of observed response.
- (deprecated) `respHat`: replaced by `.linpred` & `.epred`
- (deprecated) `response`: replaced by `.prediction`

For binary endpoint model (`stan_emax_binary()`),

- `.linpred`: predicted probability on logit scale
- `.epred`: predicted probability on probability scale
- `.prediction`: predicted event (1) or non-event (0)

The return object also contains exposure and parameter values used for calculation.

With `posterior_predict_quantile()` function, you can obtain quantiles of `respHat` and `response` as specified by `ci` and `pi`.

stanemax-methods

Methods for stanemax objects

Description

Methods for stanemax objects

Usage

```
## S3 method for class 'stanemax'
print(x, digits_summary = 2, ...)

## S3 method for class 'stanemaxbin'
print(x, digits_summary = 2, ...)

extract_stanfit(x)

extract_obs_mod_frame(x)

## S3 method for class 'stanemax'
plot(x, show.ci = TRUE, show.pi = FALSE, ci = 0.9, pi = 0.9, ...)

## S3 method for class 'stanemaxbin'
plot(x, show.ci = TRUE, show.pi = FALSE, ci = 0.9, pi = 0.9, ...)
```

Arguments

`x` An object of class `stanemax` or `stanemaxbin`

`digits_summary` The number of significant digits to use when printing the summary, defaulting to 2. Applies to the quantities other than the effective sample size, which is always rounded to the nearest integer.

...	Additional arguments passed to methods.
show.ci	An logical specifying if the output figure include credible interval of posterior prediction. Default TRUE.
show.pi	An logical specifying if the output figure include prediction interval. Default FALSE.
ci	Credible interval range.
pi	Prediction interval range.

stan_emax

Bayesian Emax model fit with Stan

Description

Run sigmoidal Emax model fit with formula notation

Usage

```
stan_emax(
  formula,
  data,
  gamma.fix = 1,
  e0.fix = NULL,
  emax.fix = NULL,
  priors = NULL,
  param.cov = NULL,
  ...
)
```

Arguments

formula	a symbolic description of variables for Emax model fit.
data	an optional data frame containing the variables in the model.
gamma.fix	a (positive) numeric or NULL to specify gamma (Hill coefficient) in the sigmoidal Emax model. If NULL, gamma will be estimated from the data. If numeric, gamma is fixed at the number provided. Default = 1 (normal Emax model).
e0.fix	a numeric or NULL to specify E0 in the Emax model. If NULL, E0 will be estimated from the data. If numeric, E0 is fixed at the number provided. Default = NULL (estimate from the data).
emax.fix	a numeric or NULL to specify Emax in the Emax model. If NULL, Emax will be estimated from the data. If numeric, Emax is fixed at the number provided. Default = NULL (estimate from the data).
priors	a named list specifying priors of parameters (ec50, emax, e0, gamma, sigma). Each list item should be length 2 numeric vector, one corresponding to mean and another corresponding to standard deviation. Currently only supports normal distribution for priors.

param.cov a named list specifying categorical covariates on parameters (ec50, emax, e0).
 Convert a column into factor if specific order of covariates are needed.

... Arguments passed to `rstan::sampling` (e.g. iter, chains).

Details

The following structure is used for the Emax model:

$$Response = e_0 + e_{max} \times exposure^\gamma / (ec50^\gamma + exposure^\gamma) + \epsilon$$

$$\epsilon \sim N(0, \sigma^2)$$

Value

An object of class stanemax

Examples

```
## Not run:
data(exposure.response.sample)
fit1 <- stan_emax(response ~ exposure,
  data = exposure.response.sample,
  # the next line is only to make the example go fast enough
  chains = 1, iter = 500, seed = 12345
)
print(fit1)

# Set priors manually, also estimate gamma instead of the default of fix to 1
fit2 <- stan_emax(response ~ exposure,
  data = exposure.response.sample, gamma.fix = NULL,
  priors = list(
    ec50 = c(100, 30), emax = c(100, 30), e0 = c(10, 5),
    gamma = c(0, 3), sigma = c(0, 30)
  ),
  # the next line is only to make the example go fast enough
  chains = 1, iter = 500, seed = 12345
)
print(fit2)

data(exposure.response.sample.with.cov)
# Specify covariates
fit3 <- stan_emax(
  formula = resp ~ conc, data = exposure.response.sample.with.cov,
  param.cov = list(emax = "cov2", ec50 = "cov3", e0 = "cov1"),
  # the next line is only to make the example go fast enough
  chains = 1, iter = 500, seed = 12345
)
print(fit3)

## End(Not run)
```

stan_emax_binary *Bayesian Emax model fit with Stan for binary endpoint*

Description

Bayesian Emax model fit with Stan for binary endpoint

Usage

```
stan_emax_binary(
  formula,
  data,
  gamma.fix = 1,
  e0.fix = NULL,
  emax.fix = NULL,
  priors = NULL,
  param.cov = NULL,
  ...
)
```

Arguments

formula	a symbolic description of variables for Emax model fit.
data	an optional data frame containing the variables in the model.
gamma.fix	a (positive) numeric or NULL to specify gamma (Hill coefficient) in the sigmoidal Emax model. If NULL, gamma will be estimated from the data. If numeric, gamma is fixed at the number provided. Default = 1 (normal Emax model).
e0.fix	a numeric or NULL to specify E0 in the Emax model. If NULL, E0 will be estimated from the data. If numeric, E0 is fixed at the number provided. Default = NULL (estimate from the data).
emax.fix	a numeric or NULL to specify Emax in the Emax model. If NULL, Emax will be estimated from the data. If numeric, Emax is fixed at the number provided. Default = NULL (estimate from the data).
priors	a named list specifying priors of parameters (ec50, emax, e0, gamma, sigma). Each list item should be length 2 numeric vector, one corresponding to mean and another corresponding to standard deviation. Currently only supports normal distribution for priors.
param.cov	a named list specifying categorical covariates on parameters (ec50, emax, e0). Convert a column into factor if specific order of covariates are needed.
...	Arguments passed to <code>rstan::sampling</code> (e.g. iter, chains).

Examples

```
## Not run:
data(exposure.response.sample.binary)
fit1 <- stan_emax_binary(
  y ~ conc,
  data = exposure.response.sample.binary,
  # the next line is only to make the example go fast enough
  chains = 2, iter = 500, seed = 12345
)
print(fit1)

# Specify covariates
fit2 <- stan_emax_binary(
  formula = y ~ conc, data = exposure.response.sample.binary,
  param.cov = list(emax = "sex"),
  # the next line is only to make the example go fast enough
  chains = 2, iter = 500, seed = 12345
)
print(fit2)

## End(Not run)
```

Index

* datasets

- exposure.response.sample, 5
- exposure.response.sample.binary, 5
- exposure.response.sample.with.cov, 6

as_draws, 3

as_draws_array (as_draws), 3

as_draws_df (as_draws), 3

as_draws_list (as_draws), 3

as_draws_matrix (as_draws), 3

as_draws_rvars (as_draws), 3

draws, 4

exposure.response.sample, 5

exposure.response.sample.binary, 5

exposure.response.sample.with.cov, 6

extract_obs_mod_frame
(stanemax-methods), 9

extract_param, 7

extract_stanfit (stanemax-methods), 9

plot.stanemax (stanemax-methods), 9

plot.stanemaxbin (stanemax-methods), 9

posterior_predict, 7

posterior_predict_quantile
(posterior_predict), 7

posterior_predict_quantile(), 9

print.stanemax (stanemax-methods), 9

print.stanemaxbin (stanemax-methods), 9

rstan::sampling, 11, 12

rstanemax (rstanemax-package), 2

rstanemax-package, 2

stan_emax, 10

stan_emax(), 8

stan_emax_binary, 12

stan_emax_binary(), 8, 9

stanemax-methods, 9

subset_draws, 4