

Package: rtsplot (via r-universe)

September 18, 2024

Type Package

Title Time Series Plot

Version 0.1.5

Description A fast and elegant time series visualization package. In addition to the standard R plot types, this package supports candle sticks, open-high-low-close, and volume plots. Useful for visualizing any time series data, e.g., stock prices and technical indicators.

License MIT + file LICENSE

Imports xts, quantmod, zoo, RColorBrewer

Suggests TTR

URL <https://bitbucket.org/rtsvizteam/rtsplot>

BugReports <https://bitbucket.org/rtsvizteam/rtsplot/issues>

LazyLoad yes

RoxygenNote 7.2.3

NeedsCompilation no

Author RTSVizTeam [aut, cph], Irina Kapler [cre]

Maintainer Irina Kapler <irkapler@gmail.com>

Repository CRAN

Date/Publication 2023-09-24 00:10:02 UTC

Contents

register.theme	2
rtsplot	3
rtsplot.candle	6
rtsplot.candle.col	7
rtsplot.corner.label	7
rtsplot.fake.stock.data	8
rtsplot.format	9

rtsplot.grid	10
rtsplot.hl	10
rtsplot.layout	11
rtsplot.legend	11
rtsplot.lines	13
rtsplot.matplot	13
rtsplot.ohlc	14
rtsplot.polygon	15
rtsplot.scale.volume	16
rtsplot.stacked	16
rtsplot.text	17
rtsplot.volume	18
rtsplot.x.highlight	18
rtsplot.y.highlight	19
rtsplot2Y	20

Index	21
--------------	-----------

register.theme	<i>Theme</i>
----------------	--------------

Description

Setup theme

Usage

```
register.theme(
  grid.color = "gray90",
  colors = "Set1",
  col.border = "black",
  col.up = "green",
  col.dn = "red",
  col.x.highlight = "orange",
  col.y.highlight = "orange",
  cex = 1,
  legend.bg.col = grDevices::adjustcolor("white", 200/255)
)
```

```
rtsplot.theme()
```

```
rtsplot.theme.set(...)
```

```
rtsplot.colors(n)
```

Arguments

grid.color	color for grid lines, defaults to 'gray90'
colors	RColorBrewer set to generate colors, defaults to "Set1" in RColorBrewer
col.border	border color for drawing candles, defaults to 'black'
col.up	up color for drawing candles, defaults to 'green'
col.dn	down color for drawing candles, defaults to 'red'
col.x.highlight	color for highlighting along x axis, defaults to 'orange'
col.y.highlight	color for highlighting along y axis, defaults to 'orange'
cex	font size, defaults to 1
legend.bg.col	background legend color, defaults to grDevices::adjustcolor('white', 200/255)
...	additional settings
n	number of colors to generate

Value

None

rtsplot	<i>'rtsplot' - Time series plot with base R Graphics.</i>
---------	---

Description

Plot time series data with base R Graphics.

The 'rtsplot' package is **fast** time series plot package with base R Graphics.

Usage

```

rtsplot(
  y,
  main = NULL,
  plotX = TRUE,
  LeftMargin = 0,
  grid = "xy",
  x.highlight = NULL,
  y.highlight = NULL,
  y.highlight.col = NULL,
  las = 1,
  type = "l",
  xlab = "",
  ylab = "",
  ylim = NULL,

```

```

log = "",
skip.breaks = FALSE,
xaxis.map = rtsplot.create.xaxis.map,
...
)

```

Arguments

<code>y</code>	<code>xts</code> object
<code>main</code>	plot title
<code>plotX</code>	flag to display X axis
<code>LeftMargin</code>	to plot second Y axis, set <code>LeftMargin=3</code> , defaults to 0
<code>grid</code>	which grid lines to draw, defaults to 'xy'
<code>x.highlight</code>	segments to highlight along X axis, defaults to NULL
<code>y.highlight</code>	segments to highlight along Y axis, defaults to NULL
<code>y.highlight.col</code>	color to highlight segments Y axis, defaults to NULL
<code>las</code>	rotation of Y axis labels, defaults to 1 , for more info see par
<code>type</code>	plot type, defaults to 'l' , for more info see plot also support 'ohlc', 'hl', 'candle', 'volume' types
<code>xlab</code>	X label, defaults to "" , for more info see plot
<code>ylab</code>	Y label, defaults to "" , for more info see plot
<code>ylim</code>	range on Y values, defaults to NULL
<code>log</code>	log scale x, y, xy axes, defaults to ""
<code>skip.breaks</code>	flag to skip plotting missing date/times (i.e. nights and weekends), defaults to FALSE
<code>xaxis.map</code>	xaxis map function used if <code>skip.breaks</code> is TRUE, defaults to rtsplot.create.xaxis.map
<code>...</code>	additional parameters to the plot

Value

nothing

Author(s)

Maintainer: Irina Kapler <irkapler@gmail.com>

Authors:

- RTSVizTeam <rtsvizteam@gmail.com> [copyright holder]

See Also

Useful links:

- <https://bitbucket.org/rtsvizteam/rtsplot>
- Report bugs at <https://bitbucket.org/rtsvizteam/rtsplot/issues>

Examples

```
# generate time series data
y = rtspplot.fake.stock.data(1000)
symbol = 'Test'

sma = TTR::SMA(y, 250)
rsi = TTR::RSI(y, 20)

# plot candles and RSI charts
layout(c(1,1,1,2))
cols = rtspplot.colors(2)

rtspplot(y, type = 'l', plotX = FALSE, col=cols[1],lwd=1.5)
rtspplot.lines(sma, col=cols[2], lwd=1.5)
rtspplot.legend(c(symbol, 'SMA(250)'), cols[1:2], list(y,sma))

# plot rsi
rtspplot(rsi, type = 'l', ylim=c(0,100),
y.highlight = c(c(0,30), c(70,100)),
y.highlight.col = grDevices::adjustcolor(c('green','red'), 50/255)
)
rtspplot.legend('RSI(20)', 'black', rsi)

y = rtspplot.fake.stock.data(1000)
symbol = 'SPY'

# simple example
highlight = which(y < 10)

# plot
layout(1)
rtspplot.theme.set(col.x.highlight=grDevices::adjustcolor('orange', 200/255))

rtspplot(y, type = 'l', main = symbol, x.highlight = highlight)

# 'skip.breaks' example with daily data
y = rtspplot.fake.stock.data(10, remove.non.trading = TRUE)

layout(1:2)
rtspplot(y, type='b')
rtspplot.legend('skip.breaks=FALSE', text.col='red')
rtspplot(y, type='b', skip.breaks=TRUE)
rtspplot.legend('skip.breaks=TRUE', text.col='red')

# 'skip.breaks' example with intra-day data
y = rtspplot.fake.stock.data(5*24*60, period = 'minute', remove.non.trading = TRUE)

layout(1:2)
rtspplot(y, type='l')
```

```
rtsplot.legend('skip.breaks=FALSE', text.col='red')
rtsplot(y, type='l', skip.breaks=TRUE)
rtsplot.legend('skip.breaks=TRUE', text.col='red')
```

rtsplot.candle *Create Candle Plot*

Description

Plot candles if dx is sufficient otherwise ohlc or bars

Usage

```
rtsplot.candle(
  y,
  col = rtsplot.candle.col(y),
  border = rtsplot.theme()$col.border
)
```

Arguments

y	xts object
col	color for bars, defaults to rtsplot.candle.col
border	border color, defaults to rtsplot.theme()\$col.border

Value

nothing

Examples

```
y = rtsplot.fake.stock.data(50, ohlc=TRUE)
symbol = 'SPY'

# plot
layout(1)
rtsplot(y, type = 'n')
rtsplot.candle(y)
rtsplot.legend(symbol, 'black', y)
```

`rtspplot.candle.col` *Bar Colors for Candle and Volume plots*

Description

Bar Colors for Candle and Volume plots

Usage

```
rtspplot.candle.col(y)
```

```
rtspplot.volume.col(y)
```

Arguments

`y` `xts` object

Value

colors

`rtspplot.corner.label` *Plot corner label*

Description

Plot corner label, based on the [text at the upper left corner outside of the plot region](<http://r.789695.n4.nabble.com/text-at-the-upper-left-corner-outside-of-the-plot-region-td885675.html>)

Usage

```
rtspplot.corner.label(  
  label = NULL,  
  col = "black",  
  x = -1,  
  y = 1,  
  xoffset = NA,  
  yoffset = NA,  
  space = c("plot", "figure"),  
  cex = 1,  
  border = NA  
)
```

Arguments

label	label
col	label color
x	x location, defaults to -1
y	y location, defaults to 1
xoffset	x offset, defaults to NA
yoffset	y offset, defaults to NA
space	coordinate space, can be "plot" or "figure", defaults to "plot"
cex	font size, defaults to 1
border	border color, defaults to NA - no color

Value

nothing

Examples

```

rtsplot.theme.set(legend.bg.col=grDevices::adjustcolor('orange', 200/255))
plot(rnorm(20), rnorm(20))

rtsplot.corner.label('test1', y=-1, space='figure')
rtsplot.corner.label('test2', y=1, space='figure')
rtsplot.corner.label('test3', x=1, space='figure')
rtsplot.corner.label('test4', x=1, y=-1, space='figure')
rtsplot.theme.set(legend.bg.col=grDevices::adjustcolor('white', 50/255))

```

```

rtsplot.fake.stock.data
      Generate fake stock data

```

Description

Generate fake stock data for use in rtsplot examples

Usage

```

rtsplot.fake.stock.data(
  n,
  y0 = 10,
  stdev = 0.1,
  ohlc = FALSE,
  method = c("normal", "adhoc"),
  period = c("day", "minute"),
  remove.non.trading = FALSE
)

```


Arguments

n	number of points to generate
y0	starting price, defaults to 10
stdev	standard deviation, defaults to 0.1
ohlc	generate ohlc data, defaults to FALSE
method	method to generate fake stock data, defaults to 'normal' two methods are implemented: * 'normal' - generate fake stock data assuming returns are normally distributed with zero drift * 'uniform' - generate fake stock data assuming returns are uniformly distributed with zero drift
period	frequency to generate fake stock data, (possible values: "day", "minute"), defaults to "day"
remove.non.trading	flag to remove non trading periods(i.e. weekends and non-trading hours). Note, this flag likely will cause function return less than 'n' observation, defaults to FALSE

Value

`xts` object with fake stock data

Examples

```
rtsplot.fake.stock.data(10)
```

rtsplot.format	<i>Format numbers using 1000 separator</i>
----------------	--

Description

Format numbers using 1000 separator

Usage

```
rtsplot.format(temp, nround = 2, sprefix = "", eprefix = "")
```

Arguments

temp	numbers
nround	number of rounding digits, defaults to '2'
sprefix	start prefix string, defaults to ""
eprefix	end postfix string, defaults to ""

Value

numbers formatted using 1000 separator

rtsplot.grid	<i>Add grid to time series plot</i>
--------------	-------------------------------------

Description

Add grid to time series plot

Usage

```
rtsplot.grid(grid, xaxis.ticks, col = rtsplot.theme()$grid.color)
```

Arguments

grid	which grid lines to draw, defaults to 'xy'
xaxis.ticks	location of x axis ticks
col	grid color, defaults to rtsplot.theme()\$grid.color

Value

nothing

rtsplot.hl	<i>Create HL Plot</i>
------------	-----------------------

Description

Create HL Plot

Usage

```
rtsplot.hl(y, col = rtsplot.volume.col(y), border = rtsplot.theme()$col.border)
```

Arguments

y	xts object
col	color for bars, defaults to rtsplot.volume.col
border	border color, defaults to rtsplot.theme()\$col.border

Value

nothing

Examples

```
y = rtspplot.fake.stock.data(50, ohlc=TRUE)
symbol = 'SPY'

# plot
layout(1)
rtspplot(y, type = 'n')
rtspplot.hl(y)
rtspplot.legend(symbol, 'black', y)
```

rtspplot.layout	<i>Create layout</i>
-----------------	----------------------

Description

Create layout

Usage

```
rtspplot.layout(ilyayout, delim = ",")
```

Arguments

ilyayout	matrix stored as a string
delim	delimiter, defaults to ','

Value

nothing

rtspplot.legend	<i>Plot legend - shortcut to the legend function</i>
-----------------	--

Description

Plot legend - shortcut to the [legend](#) function

Usage

```
rtsplot.legend(  
  labels,  
  fill = NULL,  
  lastobs = NULL,  
  x = "topleft",  
  merge = FALSE,  
  bty = "n",  
  border = NA,  
  yformat = rtsplot.format,  
  cex = 1,  
  ...  
)
```

Arguments

labels	legend labels
fill	fill colors, defaults to NULL
lastobs	list of last observations, defaults to NULL
x	location of legend, defaults to 'topleft'
merge	merge, defaults to FALSE , see legend function for more info
bty	box, defaults to 'n' , see legend function for more info
border	border color, defaults to NA - no color
yformat	format Y values function, defaults to rtsplot.format
cex	font size, defaults to 1
...	other parameters to legend, see legend function for more info

Value

nothing

Examples

```
y = rtsplot.fake.stock.data(1000)  
symbol = 'SPY'  
  
# plot  
layout(1)  
rtsplot(y, type = 'l', col='black')  
rtsplot.legend(symbol, 'black', y)
```

rtsp <code>plot</code> .lines	<i>Add lines to time series plot</i>
-------------------------------	--------------------------------------

Description

Add lines to time series plot

Usage

```
rtspplot.lines(y, type = "l", col = graphics::par("col"), ...)
```

Arguments

y	xts object
type	line type, defaults to 'l' , for more info see lines
col	color, defaults to par('col')
...	additional parameters to the lines

Value

nothing

Examples

```
y = rtspplot.fake.stock.data(1000)
symbol = 'SPY'

# moving average
sma = TTR::SMA(y, 250)

# plot
layout(1)
rtspplot(y, type = 'l', col='black')
rtspplot.lines(sma, col='blue', lwd=1.5)
rtspplot.legend(c(symbol, 'SMA(250)'), 'black,blue', list(y,sma))
```

rtsp <code>plot</code> .matplot	matplot version for xts object
---------------------------------	--

Description

[matplot](#) version for [xts](#) object

Usage

```

rtsplot.matplot(
  y,
  dates = NULL,
  ylim = NULL,
  type = "l",
  cols = rtsplot.colors(ncol(y)),
  ...
)

```

Arguments

y	xts object
dates	subset of dates defaults to NULL
ylim	range on Y values, defaults to NULL
type	plot type, defaults to 'l' , see plot for details
cols	colors
...	additional parameters to the matplot

Value

nothing

 rtsplot.ohlc

Create OHLC Plot

Description

Plot ohlc if dx is sufficient otherwise bars

Usage

```

rtsplot.ohlc(y, col = rtsplot.theme()$col.border)

```

Arguments

y	xts object
col	color for bars, defaults to rtsplot.theme()\$col.border

Value

nothing

Examples

```

y = rtspplot.fake.stock.data(50, ohlc=TRUE)
symbol = 'SPY'

# plot
layout(1)
rtspplot(y, type = 'n')
rtspplot.ohlc(y)
rtspplot.legend(symbol, 'black', y)

rtspplot.theme.set(legend.bg.col=grDevices::adjustcolor('blue', 25/255))
rtspplot.corner.label('Logo \uA9', x=1, y=-1, cex = 0.7, space='figure', col='blue')
rtspplot.theme.set(legend.bg.col = grDevices::adjustcolor('white', 200/255))

```

rtspplot.polygon	<i>Add polygon to time series plot</i>
------------------	--

Description

Add polygon to time series plot

Usage

```
rtspplot.polygon(y, col = graphics::par("col"), ...)
```

Arguments

y	xts object with 2 columns
col	color, defaults to par('col')
...	additional parameters to the lines

Value

nothing

Examples

```

y = rtspplot.fake.stock.data(1000, ohlc=TRUE)
symbol = 'SPY'

# moving average
bbands = TTR::BBands(quantmod::HLC(y), n=200, sd=1)[,c('up', 'dn')]

# plot
layout(1)
rtspplot(y, type = 'l', col='black')
col = grDevices::adjustcolor('green', 50/255)

```

```
rtsplot.polygon(bbands, col = col)
rtsplot.legend(c(symbol, 'BBands'), c('black', col), list(y,bbands))
```

`rtsplot.scale.volume` *Scale volume*

Description

Scale volume

Usage

```
rtsplot.scale.volume(y)
```

Arguments

`y` [xts](#) object

Value

adjusted y object

`rtsplot.stacked` *Create Stacked plot*

Description

Create Stacked plot

Usage

```
rtsplot.stacked(
  x,
  y,
  xlab = "",
  cols = rtsplot.colors(ncol(y)),
  type = c("l", "s"),
  flip.legend = FALSE,
  ...
)
```


Arguments

x	dates object
y	matrix with weights
xlab	X label, defaults to "", for more info see plot
cols	colors, defaults to colors rtsplot.theme
type	plot type: lines, step stairs c('l','s')
flip.legend	flag to reverse legend order, defaults to FALSE
...	additional parameters to the plot

Value

nothing

rtsplot.text	<i>Add text to time series plot</i>
--------------	-------------------------------------

Description

Add text to time series plot

Usage

```
rtsplot.text(y, ...)
```

Arguments

y	xts object
...	additional parameters to the lines

Value

nothing

Examples

```
y = rtsplot.fake.stock.data(1000)
symbol = 'SPY'

# plot
layout(1)
rtsplot(y, type = 'l', col='black')
rtsplot.text(y[100], 'Text', col='red')
rtsplot.legend(symbol, 'black', y)
```

`rtsplot.volume` *Plot volume*

Description

Plot volume

Usage

```
rtsplot.volume(
  y,
  col = rtsplot.volume.col(y),
  border = rtsplot.theme()$col.border
)
```

Arguments

<code>y</code>	<code>xts</code> object
<code>col</code>	color for volume bars
<code>border</code>	color for volume bars border

Value

nothing

`rtsplot.x.highlight` *Highlight vertical segments*

Description

Highlight vertical segments

Usage

```
rtsplot.x.highlight(y, highlight, col = rtsplot.theme()$col.x.highlight)
```

Arguments

<code>y</code>	<code>xts</code> object
<code>highlight</code>	segments to highlight along X axis
<code>col</code>	highlight color, defaults to <code>rtsplot.control\$col.x.highlight</code>

Value

nothing

rtsplot.y.highlight *Highlight horizontal segments*

Description

Highlight horizontal segments

Usage

```
rtsplot.y.highlight(highlight, col = rtsplot.theme()$col.y.highlight)
```

Arguments

highlight	segments to highlight along Y axis
col	highlight color, defaults to rtsplot.control\$col.y.highlight

Value

nothing

Examples

```
# generate time series data
y = rtsplot.fake.stock.data(1000)

rsi = TTR::RSI(y, 20)

#set up two regions for graphs candlestick price data on top 2/3 of the plot
#and rsi on the bottom 1/3 of the plot
layout(c(1,1,2))

rtsplot(y, type = 'line', plotX = FALSE)
  rtsplot.legend('SPY', 'grey70', y)

rtsplot(rsi, type = 'l')

col = grDevices::adjustcolor(c('green','red'), 80/255)
rtsplot.y.highlight(col=col[1], highlight=c(50,100))
rtsplot.y.highlight(col=col[2], highlight=c(0,50))

abline(h = 50, col = 'gray20')

rtsplot.legend('RSI(20)', 'black', rsi)
```

rtsplot2Y

*Plot time series with second Y axis***Description**

Detailed discussion for validity of dual Y axis at [Dual axes time series plots may be ok sometimes after all](<http://freerangestats.info/blog/2016/08/18/dualaxes>)

Usage

```
rtsplot2Y(y, las = 1, type = "l", col.axis = "red", ylim = NULL, log = "", ...)
```

Arguments

y	xts object
las	rotation of Y axis labels, defaults to 1 , for more info see par
type	plot type, defaults to 'l' , for more info see plot also support 'ohlc', 'hl', 'candle', 'volume' types
col.axis	axis color, defaults to 'red'
ylim	range on Y values, defaults to NULL
log	log scale x, y, xy axes, defaults to ""
...	additional parameters to the plot

Value

nothing

Examples

```
# generate time series data
y = rtsplot.fake.stock.data(1000)
symbol = 'SPY'

y1 = rtsplot.fake.stock.data(1000, 100)
symbol = 'IBM'

# two Y axis example
# to plot second Y axis, free some space on left side, set LeftMargin=3
layout(1)
cols = c('black', 'red')

rtsplot(y, type = 'l', LeftMargin=3, col=cols[1])

rtsplot2Y(y1, type='l', las=1, col=cols[2], col.axis=cols[2])

rtsplot.legend('SPY(rhs),IBM(lhs)', cols, list(y,y1))
```

Index

legend, [11](#), [12](#)
lines, [13](#), [15](#), [17](#)

matplotlib, [13](#), [14](#)

par, [4](#), [20](#)
plot, [4](#), [14](#), [17](#), [20](#)

register.theme, [2](#)
rtsplot, [3](#)
rtsplot-package (rtsplot), [3](#)
rtsplot.candle, [6](#)
rtsplot.candle.col, [7](#)
rtsplot.colors (register.theme), [2](#)
rtsplot.corner.label, [7](#)
rtsplot.fake.stock.data, [8](#)
rtsplot.format, [9](#), [12](#)
rtsplot.grid, [10](#)
rtsplot.hl, [10](#)
rtsplot.layout, [11](#)
rtsplot.legend, [11](#)
rtsplot.lines, [13](#)
rtsplot.matplot, [13](#)
rtsplot.ohlc, [14](#)
rtsplot.polygon, [15](#)
rtsplot.scale.volume, [16](#)
rtsplot.stacked, [16](#)
rtsplot.text, [17](#)
rtsplot.theme, [17](#)
rtsplot.theme (register.theme), [2](#)
rtsplot.volume, [18](#)
rtsplot.volume.col
 (rtsplot.candle.col), [7](#)
rtsplot.x.highlight, [18](#)
rtsplot.y.highlight, [19](#)
rtsplot2Y, [20](#)

xts, [4](#), [6](#), [7](#), [9](#), [10](#), [13–18](#), [20](#)