Package: saeHB.TF.beta (via r-universe)

October 29, 2026

Title SAE using HB Twofold Subarea Model under Beta Distribution

Version 0.2.0

Maintainer Nasya Zahira Putri <nasyazp28@gmail.com>

Description Estimates area and subarea level proportions using the Small Area Estimation (SAE) Twofold Subarea Model with a hierarchical Bayesian (HB) approach under Beta distribution. A number of simulated datasets generated for illustration purposes are also included. The 'rstan' package is employed to estimate parameters via the Hamiltonian Monte Carlo and No U-Turn Sampler algorithm. The model-based estimators include the HB mean, the variation of the mean, and quantiles. For references, see Rao and Molina (2015) <doi:10.1002/9781118735855>, Torabi and Rao (2014) <doi:10.1016/j.jmva.2014.02.001>, Leyla Mohadjer et al.(2007) <http://www.asasrms.org/Proceedings/y2007/Files/JSM2007-000559.pdf>, Erciulescu et al.(2019) <doi:10.1111/rssa.12390>, and Yudasena (2024).

License GPL (>= 3)

Encoding UTF-8

RoxygenNote 7.3.2

Biarch true

Depends R (>= 3.5)

Imports methods, Rcpp (>= 0.12.0), RcppParallel (>= 5.0.1), rstan (>= 2.18.1), rstantools (>= 2.4.0), bayesplot, stringr

LinkingTo BH (>= 1.66.0), Rcpp (>= 0.12.0), RcppEigen (>= 0.3.3.3.0), RcppParallel (>= 5.0.1), rstan (>= 2.18.1), StanHeaders (>= 2.18.0)

SystemRequirements GNU make

URL https://github.com/Nasyazahira/saeHB.TF.beta

BugReports https://github.com/Nasyazahira/saeHB.TF.beta/issues

LazyData true

Suggests knitr, rmarkdown, testthat (>= 3.0.0), ggplot2

VignetteBuilder knitr

Config/testthat/edition 3

NeedsCompilation yes

Author Nasya Zahira Putri [aut, cre], Cucu Sumarni [aut], Rizal Fauziarochman Yudasena [aut]

Config/pak/sysreqs make

Repository https://cran.r-universe.dev

Date/Publication 2025-09-03 06:50:02 UTC

RemoteUrl https://github.com/cran/saeHB.TF.beta

RemoteRef HEAD

RemoteSha e6078018f8ab99f45c7ef959458dce557449300b

Contents

saeHB.TF.beta-package 2
betaTF 3
dataBeta 4
dataBetaNS 5
explore 6

Index **7**

`saeHB.TF.beta-package` *The 'saeHB.TF.beta' package.*

Description

Small Area Estimation using Hierarchical Bayes Twofold Subarea Level Model under Beta Distribution

References

Stan Development Team (NA). RStan: the R interface to Stan. R package version 2.36.0.9000. https://mc-stan.org

betaTF *Small Area Estimation using Hierarchical Bayes Twofold Subarea Level Model under Beta Distribution*

Description

Function betaTF used for estimation of subarea and area means simultaneously under Twofold Subarea Level Small Area Estimation Model Using Hierarchical Bayesian Method with Beta distribution The range of data must be $0 < y < 1$.

Usage

```
betaTF(
  formula,
  area,
  weight,
  iter.update = 3,
  iter.mcmc = 1000,
  coef = NULL,
  var.coef = NULL,
  thin = 1,
  burn.in = floor(iter.mcmc/2),
  sigma2.u = 1,
  sigma2.v = 1,
  data
)
```

Arguments

formula	Formula that describe the fitted model
area	Index that describes the code relating to area in each subarea.This should be defined for aggregation to get area estimator. Index start from 1 until m
weight	Vector contain proportion units or proportion of population on each subarea. w_{ij}
iter.update	Number of updates perform (default = 3)
iter.mcmc	Number of total iterations per chain (default = 1000)
coef	Vector contains prior initial value of Coefficient of Regression Model for fixed effect with default vector of 0 with the length of the number of regression coefficients
var.coef	Vector contains prior initial value of variance of Coefficient of Regression Model for fixed effect with default vector of 1 with the length of the number of regression coefficients
thin	Thinning rate, must be a positive integer
burn.in	Number of iterations to discard at the beginning
sigma2.u	Number of prior initial value of variance of subarea random effect
sigma2.v	Number of prior initial value of variance of area random effect
data	The data frame

Value

This function returns a list with following objects:

`Est_sub`	A dataframe contains the values, standard deviation, and quantile of Subarea mean Estimates using Twofold Subarea level model under Hierarchical Bayes method
`Est_area`	A dataframe contains the values, standard deviation, and quantile of Area mean Estimates using Twofold Subarea level model under Hierarchical Bayes method
`area_randeff`	A dataframe contains area random effect
`sub_randeff`	A dataframe contains subarea random effect
`refVar`	A dataframe that contains estimated subarea and area random effect variance (σ_u^2 and σ_v^2)
`coefficient`	A dataframe that contains the estimated model coefficient β
`plot`	Trace, Density, Autocorrelation Function Plot of coefficient

Examples

```
fit <- betaTF(y~X1+X2,area="codearea",weight="w",data=dataBeta, iter.mcmc = 500)
```

---

dataBeta *Simulated dataset Under Two Fold Subarea level model with Beta distribution.*

Description

A dataset to simulate Small Area Estimation using Hierarchical Bayesian method under Two Fold Subarea level model with Beta distribution on variable interest.

This data is generated by these following steps:

1. Generate auxiliary variable X_{ij1}, X_{ij2}, sampling error e_{ij},subarea random effect u_{ij}, area random effect v_i, and weight or proportions of unit w_{ij}
   - Generate auxiliary variable on subarea level X_{ij1}~ $U(0,1)$
   - Generate auxiliary variable on subarea level X_{ij2}~$N(0,1)$
   - Setting coefficient $\beta_0 = \beta_1 = \beta_2 = 0.5$
   - Generate area random effect v_i ~ $N(0,1)$
   - Generate subarea random effect u_{ij}~$N(0,1)$
   - Calculate target parameter $\mu_{ij} = \beta_0 + \beta_1 x_{ij1} + \beta_2 x_{ij2} + v_i + u_{ij}$
   - Generate constant for Beta parameter π_{ij}~ $Gamma(1, 0.5)$
   - Calculate Beta parameter $A = \mu_{ij}\pi_{ij}$ and $A = (1-\mu_{ij})\pi_{ij}$
   - Generate direct estimator y_{ij}~ $Beta(A, B)$
   - Generate weight on each subarea w_{ij}~$U(0.2, 0.7)$
2. Direct estimation (y_{ij}), Auxiliary variables X_{ij1},X_{ij2}, vardir, codearea, and weight w_{ij} are combined in a dataframe called dataBeta

Usage

```
dataBeta
```

Format

A data frame with 90 rows and 6 columns:

y Direct estimation of subarea mean y_{ij}

X1 Auxiliary variable of X_{ij1}

X2 Auxiliary variable of X_{ij2}

codearea Index that describes the code relating to area for each subarea

w Unit proportion on each subarea or weight w_{ij}

vardir Sampling variance of direct estimator y_{ij}

`dataBetaNS` *Simulated dataset Under Two Fold Subarea level model with Beta distribution and Non-Sampled subarea.*

Description

1. A dataset to simulate Small Area Estimation using Hierarchical Bayesian method under Two Fold Subarea level model with Beta distribution and Non-sampled subarea
2. This data contains NA values that indicates no sampled at one or more Subareas. It uses the `dataBeta` with the direct estimates and the related variances in 5 subareas are missing.

Usage

```
dataBetaNS
```

Format

A data frame with 90 rows and 6 columns:

y Direct estimation of subarea mean y_{ij}

X1 Auxiliary variable of X_{ij1}

X2 Auxiliary variable of X_{ij2}

codearea Index that describes the code relating to area for each subarea

w Unit proportion on each subarea or weight w_{ij}

vardir Sampling variance of direct estimator y_{ij}

explore *Exploration of the Data Used for Modeling*

Description

Function explore provides an initial exploration of a dataset. It calculate summary statistics for all variables in the provided formula or dataset, visualizes the distribution of the response variable as a histogram density,and boxplot for Coefficient of Variation (CV) / Relative Standard Error (RSE).

Usage

```
explore(formula, CV = NULL, data, normality = FALSE)
```

Arguments

formula	Optional formula to specify a response variable (e.g., y ~ x1 + x2).
CV	Coefficient of Variation (CV) or Relative Standard Error (RSE) of the response variable
data	The dataframe to be explored
normality	Logical; if TRUE, the function will additionally check the normality of the response variable and display the result. Defaults to FALSE.

Value

Prints a data frame of summary statistics for the selected variables, including minimum, 1st quartile, median, mean, 3rd quartile, maximum, and number of missing values (NA). Plots are drawn to the current graphics device.

Examples

```
dataBeta$CV <- sqrt(dataBeta$vardir)/dataBeta$y
explore(y~X1+X2, CV = "CV", data = dataBeta)
```

Index

∗ **datasets**
dataBeta, 4
dataBetaNS, 5

betaTF, 3

dataBeta, 4, *5*
dataBetaNS, 5

explore, 6

saeHB.TF.beta *(*saeHB.TF.beta-package*)*, 2
saeHB.TF.beta-package, 2