

Package: `scplot` (via `r-universe`)

June 30, 2024

Type Package

Title Plot Function for Single-Case Data Frames

Version 0.4.0

Date 2024-06-29

Description Add-on for the 'scan' package that creates plots from single-case data frames ('scdf'). It includes functions for styling single-case plots, adding phase-based lines to indicate various statistical parameters, and predefined themes for presentations and publications. More information and in depth examples can be found in the online book ``Analyzing Single-Case Data with R and 'scan' Jürgen Wilbert (2023) <<https://jazznbass.github.io/scan-Book/>>.

Depends R (>= 3.5.0)

Imports ggplot2, scan (>= 0.57.0), stats, utils, mblm

Suggests rmarkdown, knitr

License GPL (>= 3)

Encoding UTF-8

RoxygenNote 7.3.1

NeedsCompilation no

Author Juergen Wilbert [aut, cre]
(<<https://orcid.org/0000-0002-8392-2873>>)

Maintainer Juergen Wilbert <juergen.wilbert@uni-muenster.de>

Repository CRAN

Date/Publication 2024-06-29 22:40:11 UTC

Contents

<code>scplot-package</code>	2
<code>add_arrow</code>	3
<code>add_grid</code>	4
<code>add_labels</code>	5

add_legend	6
add_line	7
add_marks	8
add_ridge	9
add_statline	9
add_text	10
add_title	11
as_ggplot	12
element_point	13
new_theme	13
plot.sc_hplm	14
plot.sc_tauu	15
scplot	15
set_background	16
set_base_text	16
set_casenames	17
set_dataline	18
set_phasenames	19
set_separator	19
set_theme	20
set_theme_element	20
set_xaxis	22
set_xlabel	23
Index	25

scplot-package	<i>Single-Case Data Plots</i>
----------------	-------------------------------

Description

A collection of procedures for visualizing single-case data. It is an add-on package for the scan package.

Author(s)

Juergen Wilbert [aut, cre]

add_arrow	<i>Add arrows to an splot</i>
-----------	-------------------------------

Description

Add arrows to an splot

Usage

```
add_arrow(  
  object,  
  case = 1,  
  x0,  
  y0,  
  x1,  
  y1,  
  color = "black",  
  angle = 30,  
  length = unit(5, "points"),  
  type = "open",  
  ends = "last",  
  linewidth = 0.7  
)
```

Arguments

object	An splot object (class <code>splot</code>) returned from the <code>splot()</code> function.
case	Numerical vector with the case number or character string. <code>case = "all"</code> for all cases.
x0	Origin x position of the line.
y0	Origin y position of the line.
x1	End x position of the line.
y1	End y position of the line.
color	A character string or a number defining the color of an element.
angle	Angle (in $[0,360]$)
length	Size of the arrow angels.
type	One of "open" or "closed" indicating whether the arrow head should be a closed triangle.
ends	One of "last", "first", or "both", indicating which ends of the line to draw arrow heads.
linewidth	A number with the width of the line.

Value

An object of class `splot` (see [splot\(\)](#)) with added element lines.

Examples

```
data(exampleAB, package = "scan")
p1 <- scplot(exampleAB$Anja) |>
  add_arrow(case = 1, 2, 70, 6, 55, color = "darkred")
```

add_grid	<i>Add grid to an scplot</i>
----------	------------------------------

Description

Add grid to an scplot

Usage

```
add_grid(object, ...)
```

Arguments

object	An scplot object (class scplot) returned from the scplot() function.
...	Line arguments (see element_line())

Value

An object of class scplot (see [scplot\(\)](#)).

See Also

[element_line\(\)](#)

Examples

```
data(exampleAB, package = "scan")
p1 <- scplot(exampleAB$Anja) |>
  set_theme("minimal") |>
  add_grid(color = "grey70")
```

add_labels	<i>Add value labels to an splot</i>
------------	-------------------------------------

Description

Add value labels to an splot

Usage

```
add_labels(  
  object,  
  nudge_y = 5,  
  nudge_x = 0,  
  round = NULL,  
  text = list(),  
  background = list(),  
  variable = ".dvar",  
  padding = NULL  
)
```

Arguments

object	An splot object (class <code>splot</code>) returned from the <code>splot()</code> function.
nudge_y	Offset on the y-axis.
nudge_x	Offset on the x-axis.
round	Number of digits of the labels.
text	List with text parameters ("family", "face", "colour", "size", "hjust", "vjust", "angle", "l..."). See element_text() .
background	A list with background styling arguments (fill, color, size, linetype).
variable	Name of the dataline variable to apply the style.
padding	Padding size around text.

Value

An object of class `splot` (see [splot\(\)](#)) with added/changed element labels.

add_legend	<i>Add a legend to an scplot</i>
------------	----------------------------------

Description

Add a legend to an scplot

Usage

```
add_legend(
  object,
  labels = NULL,
  section_labels = c("Lines", "Phases"),
  case = 1,
  position = "right",
  datalines = TRUE,
  statlines = TRUE,
  phases = TRUE,
  title = NULL,
  text = NULL,
  background = NULL
)
```

Arguments

object	An scplot object (class scplot) returned from the scplot() function.
labels	A character vector. Replaces the automatically build labels. When a vector element is NA, the corresponding element will not be replaced (e.g. c(NA, "Variable 2", NA, "Variable 4")).
section_labels	A character vector of length two. The labels for the lines section and phase section.
case	Numerical vector with the case number or character string. case = "all" for all cases.
position	The position ("none", "left", "right", "bottom", "top", or two-element numeric vector)
datalines	If TRUE, a legend for the datalines is generated.
statlines	If TRUE, a legend for the statlines is generated.
phases	If TRUE, a legend for the phases is generated.
title	A list with text style parameters for the title.
text	List with text parameters ("family", "face", "colour", "size", "hjust", "vjust", "angle", "1"). See element_text() .
background	A list with background styling arguments (fill, color, size, linetype).

Value

An object of class scplot (see [scplot\(\)](#)) with changed element legend.

add_line	<i>Add line to an splot</i>
----------	-----------------------------

Description

Add line to an splot

Usage

```
add_line(  
  object,  
  case = 1,  
  x0 = NULL,  
  y0 = NULL,  
  x1 = NULL,  
  y1 = NULL,  
  hline = NULL,  
  vline = NULL,  
  color = "black",  
  linewidth = 0.7,  
  linetype = "solid"  
)
```

Arguments

object	An splot object (class <code>splot</code>) returned from the <code>splot()</code> function.
case	Numerical vector with the case number or character string. <code>case = "all"</code> for all cases.
x0	Origin x position of the line.
y0	Origin y position of the line.
x1	End x position of the line.
y1	End y position of the line.
hline	y position of horizontal line.
vline	x position of vertical line.
color	A character string or a number defining the color of an element.
linewidth	A number with the width of the line.
linetype	A character string with the line type: "solid", "dashed", "dotted"

Value

An object of class `splot` (see [splot\(\)](#)) with added element lines.

Examples

```
data(exampleAB, package = "scan")
p1 <- splot(exampleAB$Anja) |>
  add_line(hline = 70, color = "darkred") |>
  add_line(vline = 3, color = "blue") |>
  add_line(x0 = 1, y0 = 70, x1 = 4, y1 = 80, color = "green")
```

add_marks

Add marks to an splot

Description

Add marks to an splot

Usage

```
add_marks(
  object,
  case = 1,
  positions,
  color = "red",
  size = 1,
  shape = 1,
  variable = ".dvar"
)
```

Arguments

object	An splot object (class splot) returned from the splot() function.
case	Numerical vector with the case number or character string. case = "all" for all cases.
positions	Either a vector indicating the points to be highlighted or a character string with a logical expression (e.g. values < mean(values))
color	A character string or a number defining the color of an element.
size	Text size relative to the base text size.
shape	Number. See pch graphical parameter on par help page par() .
variable	Name of the dataline variable to apply the style.

Details

If positions is an object returned from an outlier analysis outlier(), the corresponding outliers are marked.

Value

An object of class splot (see [splot\(\)](#)) with changed element marks.

Examples

```
library(scan)
p1 <- splot(exampleA1B1A2B2$Moritz) |> add_marks(positions = c(1,5,10,14))
p1 <- splot(Huber2014) |> add_marks(positions = outlier(Huber2014))
```

add_ridge	<i>Add a ridge to an splot</i>
-----------	--------------------------------

Description

Add a ridge to an splot

Usage

```
add_ridge(object, color = "grey98", variable = ".dvar")
```

Arguments

object	An splot object (class splot) returned from the splot() function.
color	A character string or a number defining the color of an element.
variable	Name of the dataline variable to apply the style.

Value

An object of class splot (see [splot\(\)](#)) with changed element ridges.

add_statline	<i>Add a statline to an splot</i>
--------------	-----------------------------------

Description

Add a statline to an splot

Usage

```
add_statline(  
  object,  
  stat = c("mean", "median", "min", "max", "quantile", "sd", "mad", "trend", "trendA",  
    "trendA theil-sen", "moving mean", "moving median", "loreg", "lowess", "loess"),  
  phase = NULL,  
  color = NULL,  
  linewidth = NULL,  
  linetype = NULL,  
  variable = NULL,  
  ...  
)
```

Arguments

object	An splot object (class splot) returned from the splot() function.
stat	A character string for defining a statistical line or curve to be plotted.
phase	Either a numeric or a character vector specifying the reference phase (see details)
color	A character string or a number defining the color of an element.
linewidth	A number with the width of the line.
linetype	A character string with the line type: "solid", "dashed", "dotted"
variable	Name of the dataline variable to apply the style.
...	additional parameters passed to the statistical function.

Details

The phase argument defines the reference phase for some statistical functions ("median", "mean", "min", "max", "quantile"). The default is NULL which calculates and plots statistics for each phase separately. The argument takes a numeric vector (phase number(s)) or a character vector (phase name(s)). When more than one phase is defined, statistics are based on the combined values of these phases. Various methods for an extrapolated *trendA* line exist: "trendA" is based on an OLS regression, "trendA theil-sen" on a nonparametric regression, and "trendA bisplit" / "trendA trisplit" are two median based approaches. Some of the functions defined in stats have additional arguments. The `mean()` function has a trim argument (e.g. `trim = 0.1`). `quantile()` has a proportion argument (e.g. `prob = 0.75` for calculating the 75% quantile). `moving mean` and `moving median` have a lag argument (e.g. `lag = 2`). The local-regression curve function "lowess" (or "loreg") has a proportion argument (e.g. `f = 0.5`; see `lowess()`) and the local-regression curve function "loess" has a span argument (e.g. `span = 0.75`; see `loess()`).

Value

An object of class splot (see `splot()`) with changed element statlines.

add_text	<i>Add test to an splot</i>
----------	-----------------------------

Description

Add test to an splot

Usage

```
add_text(
  object,
  label,
  case = 1,
  x,
  y,
```

```

    color = "black",
    size = 1,
    angle = 0,
    hjust = 0.5,
    vjust = 0.5,
    face = 1
  )

```

Arguments

object	An scplot object (class scplot) returned from the scplot() function.
label	A Character vector with text labels.
case	Numerical vector with the case number or character string. case = "all" for all cases.
x	x position
y	y position
color	A character string or a number defining the color of an element.
size	Text size relative to the base text size.
angle	Angle (in [0,360])
hjust	Horizontal justification (in [0,1])
vjust	Vertical justification (in [0,1])
face	Font face ("plain", "italic", "bold", "bold.italic")

Value

An object of class scplot (see [scplot\(\)](#)) with a changed texts element.

add_title	<i>Add title and caption to an scplot</i>
-----------	---

Description

Add title and caption to an scplot

Usage

```
add_title(object, label, ...)
```

```
add_caption(object, label, header = "Note:\n", ...)
```

Arguments

object	An scplot object (class scplot) returned from the <code>scplot()</code> function.
label	A Character vector with text labels.
...	List with text parameters ("family", "face", "colour", "size", "hjust", "vjust", "angle", "1. See element_text() .
header	String with header above footnote/ caption

Value

An object of class `scplot` (see [scplot\(\)](#)) with changed title and caption elements.

as_ggplot	<i>Creates a ggplot2 object from an scplot() object</i>
-----------	---

Description

Creates a ggplot2 object from an [scplot\(\)](#) object

Usage

```
as_ggplot(scplot)
```

Arguments

scplot	An scplot object
--------	------------------

Details

`as_ggplot()` is used when you want to return a ggplot2 object for further use with external ggplot functions.

Value

A ggplot2 plot object.

element_point	<i>Point element</i>
---------------	----------------------

Description

In conjunction with ggplot an object to represent point attributes.

Usage

```
element_point(colour = NULL, size = NULL, shape = NULL, color = NULL)
```

Arguments

size	Relative size.
shape	Point shape.
color, colour	Point colour.

Value

An object of class `c("element_point", "element")`.

new_theme	<i>Create a new scplot theme</i>
-----------	----------------------------------

Description

Create a new scplot theme

Usage

```
new_theme()
extract_theme(object)
```

Arguments

object	An scplot object (class <code>scplot</code>) returned from the <code>scplot()</code> function.
--------	---

Value

An scplot-theme object

An object of class `scplot-theme` which can be used with the `set_theme()` function.

Examples

```
data(exampleABC, package = "scan")
my_theme <- new_theme() |>
  set_panel(color = "red") |>
  set_base_text(size = 12, color = "blue") |>
  set_dataline(color = "darkred", linewidth = 2)
p1 <- scplot(exampleABC) |> set_theme(my_theme)
```

plot.sc_hplm	<i>This function generates a forest plot for the random effects of a mixed hplm model</i>
--------------	---

Description

This function generates a forest plot for the random effects of a mixed hplm model

Usage

```
## S3 method for class 'sc_hplm'
plot(x, effect = "intercept", mark = "mean", ci = 0.95, ...)
```

Arguments

x	The return from the hplm() function.
effect	The specific effect to be plotted (default is the intercept).
mark	Set a reference line.
ci	Value between 0 and 1 for calculating the confidence interval.
...	Further arguments.

Value

A forest plot displaying Tau-U effects.

Examples

```
# plot(hplm(Leidig2018), effect = "intercept")
```

plot.sc_tauu	<i>Plot Tau-U Effects</i>
--------------	---------------------------

Description

This function generates a forest plot of Tau-U effects.

Usage

```
## S3 method for class 'sc_tauu'
plot(x, effect = "A vs. B - Trend A", ...)
```

Arguments

x	The return from the tau_u() function.
effect	The specific effect to be plotted (default is "A vs. B - Trend A").
...	Further arguments.

Value

A forest plot displaying Tau-U effects.

Examples

```
# plot(tau_u(Leidig2018), effect = "A vs. B - Trend A")
```

scplot	<i>Plot single-case data</i>
--------	------------------------------

Description

This function provides a plot of a single-case or multiple single-cases.

Usage

```
scplot(scdf)
```

Arguments

scdf	A single-case data-frame object (scdf).
------	---

Value

An object of class scplot containing the single-case data (element scdf), and information about the plot style (element theme).

Author(s)

Juergen Wilbert

set_background *Set plot and panel background of an scplot*

Description

Set plot and panel background of an scplot

Usage

```
set_background(object, ...)
```

```
set_panel(object, ...)
```

Arguments

object An scplot object (class scplot) returned from the scplot() function.

... List with rectangle parameters ("fill", "colour", "linewidth", "linetype"). See [element_rect\(\)](#).

Value

An object of class scplot (see [scplot\(\)](#)).

Examples

```
data(exampleAB, package = "scan")
p1 <- scplot(exampleAB) |>
  set_background(fill = "lightblue", colour = "darkblue", linewidth = 1.5) |>
  set_panel(fill = "deepskyblue", color = "darkblue", linewidth = 0.3)
```

set_base_text *Set base text parameters of an scplot*

Description

Set base text parameters of an scplot

Usage

```
set_base_text(object, ...)
```


Arguments

object An scplot object (class scplot) returned from the scplot() function.

... List with text parameters ("family", "face", "colour", "size", "hjust", "vjust", "angle", "1". See [element_text\(\)](#).

Value

An object of class scplot (see [scplot\(\)](#)).

set_casenames	<i>Set casenames of an scplot</i>
---------------	-----------------------------------

Description

Set casenames of an scplot

Usage

```
set_casenames(object, labels = NULL, position = NULL, background = list(), ...)
```

Arguments

object An scplot object (class scplot) returned from the scplot() function.

labels A Character vector with text labels.

position Either "topleft", "bottomleft", "topright", "bottomright", "strip-right", "strip-top", or a numerical vector of length 2 with the x and y position (e.g. c(19, 20)).

background A list with background styling arguments (fill, color, size, linetype).

... List with text parameters ("family", "face", "colour", "size", "hjust", "vjust", "angle", "1". See [element_text\(\)](#).

Value

An object of class scplot (see [scplot\(\)](#)) with a changed casenames element.

set_dataline	<i>Set data lines of an scplot</i>
--------------	------------------------------------

Description

Either set aesthetics of the default data line or add another data line.

Usage

```
set_dataline(object, variable = NULL, line, point, type = "continuous", ...)
add_dataline(...)
```

Arguments

object	An scplot object (class scplot) returned from the scplot() function.
variable	String. The name of a new variable for adding a new line. If left empty, the aesthetics of the default data line are changed.
line	List with line parameters ("colour", "linewidth", "linetype", "lineend", "arrow"). See element_line() .
point	A list with point parameters ("colour", "size", "shape"). See element_point() .
type	Either "continuous" or "discrete"
...	As a shortcut, arguments passed here are bundled as line arguments (see element_line()).

Value

An object of class scplot (see [scplot\(\)](#)) with a changed datalines element.

See Also

[element_line\(\)](#), [element_point\(\)](#)

Examples

```
data(exampleAB_add, package = "scan")
p1 <- scplot(exampleAB_add) |>
  set_dataline("depression", color = "darkblue")
```

set_theme	<i>Add a theme of to an splot</i>
-----------	-----------------------------------

Description

Possible themes are: 'basic', 'grid', 'default', 'small', 'tiny', 'big', 'minimal', 'dark', 'sienna', 'phas

Usage

```
set_theme(object, theme, ...)
```

```
add_theme(...)
```

Arguments

object	An splot object (class splot) returned from the splot() function.
theme	A character string with a predefined graphical theme or a theme object created with new_theme() .
...	Further character strings or splot-theme objects that are "added" on top.

Value

An object of class splot (see [splot\(\)](#)) with a changed theme element.

set_theme_element	<i>Set a theme element</i>
-------------------	----------------------------

Description

Set a theme element

Usage

```
set_theme_element(object, ...)
```

Arguments

object	An splot object (class splot) returned from the splot() function.
...	various style parameter

Details

Usually, you don't need this function. Possible theme elements are: "text", "plot.background", "panel.background", "panel.spacing.y", "dataline", "datapoint", "statline", "axis.expand.x", "axis.expand.y", "axis.line.x", "axis.line.y", "axis.ticks.length", "axis.ticks", "axis.title.y", "axis.title.x", "axis.text.x", "axis.text.y", "plot.title", "plot.caption", "plot.margin", "casenames", "casenames.strip", "casenames.background", "casenames.position", "phasenames", "phasenames.position.x", "separators", "separators.extent", "label.text", "label.background", "label.padding", "grid", "legend.position", "legend.background", "legend.text", "legend.title", "legend.margin".

The elements are of the following classes:

- text = c("element_text", "element"),
- plot.background = c("element_rect", "element"),
- panel.spacing.y = c("simpleUnit", "unit", "unit_v2"),
- dataline = "list",
- datapoint = "list",
- statline = c("element_line", "element"),
- axis.expand.x = "numeric",
- axis.expand.y = "numeric",
- axis.line.x = c("element_line", "element"),
- axis.line.y = c("element_line", "element"),
- axis.ticks.length = c("simpleUnit", "unit", "unit_v2"),
- axis.ticks = c("element_line", "element"),
- axis.title.y = c("element_text", "element"),
- axis.title.x = c("element_text", "element"),
- axis.text.x = c("element_text", "element"),
- axis.text.y = c("element_text", "element"),
- plot.title = c("element_text", "element"),
- plot.caption = c("element_text", "element"),
- plot.margin = c("margin", "simpleUnit", "unit", "unit_v2"),
- casenames = c("element_text", "element"),
- casenames.strip = c("element_rect", "element"),
- casenames.background = c("element_rect", "element"),
- casenames.position = "character",
- phasenames = c("element_text", "element"),
- phasenames.position.x = "character",
- separators = c("element_line", "element"),
- separators.extent = "character",
- label.text = c("element_text", "element"),
- label.background = c("element_rect", "element"),

- `label.padding = "numeric", grid = c("element_line", "element")`),
- `legend.position = "character",`
- `legend.background = c("element_rect", "element"),`
- `legend.text = c("element_text", "element"),`
- `legend.title = c("element_text", "element"),`
- `legend.margin = c("margin", "simpleUnit", "unit", "unit_v2")`

Value

An object of class `scplot` (see `scplot()`) with a changed theme element.

Examples

```
data(exampleABC, package = "scan")
p1 <- scplot(exampleABC) |>
  set_theme_element(
    axis.ticks.length = unit(0, "points"),
    axis.line.y = element_line(color = "darkred", linewidth = 2),
    panel.background = element_rect(color = "darkblue", linewidth = 1),
    panel.spacing.y = unit(0, "points"),
    phasenames = element_text(color = "#00000000")
  )
```

set_xaxis

Set axis parameters of an scplot

Description

Set axis parameters of an `scplot`

Usage

```
set_xaxis(
  object,
  limits = NULL,
  increment = NULL,
  increment_from = NULL,
  line = NULL,
  expand = NULL,
  ...
)
```

```
set_yaxis(
  object,
  limits = NULL,
  increment = NULL,
  increment_from = NULL,
```

```

    line = NULL,
    expand = NULL,
    ...
)

```

Arguments

object	An splot object (class splot) returned from the splot() function.
limits	Lower and upper limits of the axis (e.g., limits = c(0, 20) sets the axis to a scale from 0 to 20). With multiple single-cases you can use limits = c(0, NA) to scale the axis from 0 to the maximum of each case. limits is not set by default, which makes splot set a proper scale based on the given data.
increment	An integer. Increment of the x-axis. 1 :each mt value will be printed, 2 : every other value, 3 : every third values etc.
increment_from	Number from which increment starts to count. Usually set to 0 if you want marks like 1,5,10,15,...
line	List with line parameters ("colour", "linewidth", "linetype", "lineend", "arrow"). See element_line() .
expand	Vector with two values.
...	Further styling arguments: color, size, face, family, hjust, vjust, lineheight, angle, linetype, lineend, arrow, fill, margin.

Value

An object of class splot (see [splot\(\)](#)) with changed xaxis and yaxis elements.

set_xlabel	<i>Set label for axis</i>
------------	---------------------------

Description

Set label for axis

Usage

```
set_xlabel(object, label = NULL, ...)
```

```
set_ylabel(object, label = NULL, ...)
```

Arguments

object	An splot object (class splot) returned from the splot() function.
label	A Character vector with text labels.
...	Further styling arguments: color, size, face, family, hjust, vjust, lineheight, angle, linetype, lineend, arrow, fill, margin.

Value

An object of class `scplot` (see [scplot\(\)](#)) with a changed `xlabel` or `ylabel` element.

Index

- * **package**
 - scplot-package, 2

- add_arrow, 3
- add_caption (add_title), 11
- add_dataline (set_dataline), 18
- add_grid, 4
- add_labels, 5
- add_legend, 6
- add_line, 7
- add_marks, 8
- add_ridge, 9
- add_statline, 9
- add_text, 10
- add_theme (set_theme), 20
- add_title, 11
- as_ggplot, 12

- element_line(), 4, 18, 23
- element_point, 13
- element_point(), 18
- element_rect(), 16
- element_text(), 5, 6, 12, 17, 19
- extract_theme (new_theme), 13

- loess(), 10
- lowess(), 10

- mean(), 10

- new_theme, 13
- new_theme(), 20

- par(), 8
- plot.sc_hplm, 14
- plot.sc_tauu, 15

- quantile(), 10

- scplot, 15
- scplot(), 3–12, 16–20, 22–24

- scplot-package, 2
- set_background, 16
- set_base_text, 16
- set_casenames, 17
- set_dataline, 18
- set_panel (set_background), 16
- set_phasenames, 19
- set_separator, 19
- set_theme, 20
- set_theme(), 13
- set_theme_element, 20
- set_xaxis, 22
- set_xlabel, 23
- set_yaxis (set_xaxis), 22
- set_ylabel (set_xlabel), 23