Package: simts (via r-universe)

October 28, 2026

Type Package

Title Time Series Analysis Tools

Version 0.2.4

LazyData true

Maintainer Stéphane Guerrier <stef.guerrier@gmail.com>

Description A system contains easy-to-use tools as a support for time series analysis courses. In particular, it incorporates a technique called Generalized Method of Wavelet Moments (GMWM) as well as its robust implementation for fast and robust parameter estimation of time series models which is described, for example, in Guerrier et al. (2013) <doi:10.1080/01621459.2013.799920>. More details can also be found in the paper linked to via the URL below.

Depends R (>= 3.6.0)

License AGPL-3 | file LICENSE

Imports Rcpp, stats, utils, scales, grDevices, graphics, broom, dplyr, magrittr, methods, purrr, tidyr, robcor, rlang

LinkingTo Rcpp, RcppArmadillo

RoxygenNote 7.3.3

Encoding UTF-8

Suggests knitr, rmarkdown

VignetteBuilder knitr

URL https://github.com/SMAC-Group/simts, https://arxiv.org/pdf/1607.04543.pdf

BugReports https://github.com/SMAC-Group/simts/issues

NeedsCompilation yes

Author Stéphane Guerrier [aut, cre, cph], James Balamuta [aut, cph], Roberto Molinari [aut, cph], Justin Lee [aut], Lionel Voirol [aut], Yuming Zhang [aut], Wenchao Yang [ctb], Nathanael Claussen [ctb], Yunxiang Zhang [ctb], Christian Gunning [cph], Romain Francois [cph], Ross Ihaka [cph], R Core Team [cph]

Repository https://cran.r-universe.dev

Date/Publication 2026-03-10 09:50:02 UTC

RemoteUrl https://github.com/cran/simts

RemoteRef HEAD

RemoteSha 8263958806b372e731d5c50b517b8d079ef59529

Contents

[.imu . . . 4
AIC.fitsimts . . . 5
AR . . . 6
AR1 . . . 7
ar1_to_wv . . . 8
ARIMA . . . 9
ARMA . . . 10
arma_to_wv . . . 11
ARMA11 . . . 12
arma11_to_wv . . . 13
australia . . . 14
auto_corr . . . 14
best_model . . . 15
check . . . 16
compare_acf . . . 17
corr_analysis . . . 18
deriv_2nd_ar1 . . . 19
deriv_2nd_arma11 . . . 20
deriv_2nd_dr . . . 22
deriv_2nd_ma1 . . . 22
deriv_ar1 . . . 23
deriv_arma11 . . . 24
deriv_dr . . . 25
deriv_ma1 . . . 26
deriv_qn . . . 27
deriv_rw . . . 27
deriv_wn . . . 28
derivative_first_matrix . . . 29
diag_boxpierce . . . 29
diag_ljungbox . . . 30
diag_plot . . . 31
diag_portmanteau_ . . . 31
DR . . . 32
dr_to_wv . . . 33
estimate . . . 34
evaluate . . . 35
FGN . . . 36
gen_ar1blocks . . . 37

gen_bi . . . 38
gen_gts . . . 39
gen_lts . . . 40
gen_nswn . . . 42
GM . . . 43
gmwm . . . 44
gmwm_imu . . . 47
gts . . . 48
hydro . . . 50
imu . . . 50
imu_time . . . 52
is.gts . . . 53
lts . . . 54
M . . . 55
MA . . . 56
MA1 . . . 57
ma1_to_wv . . . 58
make_frame . . . 59
MAPE . . . 60
MAT . . . 61
np_boot_sd_med . . . 62
plot.gmwm . . . 62
plot.PACF . . . 63
plot.simtsACF . . . 65
plot_pred . . . 66
PLP . . . 67
predict.fitsimts . . . 68
predict.gmwm . . . 69
QN . . . 70
qn_to_wv . . . 71
read.imu . . . 71
resid_plot . . . 72
rgmwm . . . 73
rtruncated_normal . . . 74
RW . . . 74
rw_to_wv . . . 75
RW2dimension . . . 76
SARIMA . . . 76
SARMA . . . 78
savingrt . . . 79
select . . . 79
select_arima . . . 80
simple_diag_plot . . . 81
simplified_print_SARIMA . . . 82
SIN . . . 83
summary.fitsimts . . . 84
summary.gmwm . . . 84
theo_acf . . . 85

theo_pacf 86
update.gmwm 87
update.lts 88
value 89
WN 90
wn_to_wv 91

Index **92**

`[.imu` *Subset an IMU Object*

Description

Enables the IMU object to be subsettable. That is, you can load all the data in and then select certain properties.

Usage

```
## S3 method for class 'imu'
x[i, j, drop = FALSE]
```

Arguments

`x`	A `imu` object
`i`	A `integer vector` that specifies the rows to subset. If blank, all rows are selected.
`j`	A `integer vector` that specifies the columns to subset. Special rules apply see details.
`drop`	A `boolean` indicating whether the structure should be preserved or simplified.

Details

When using the subset operator, note that all the Gyroscopes are placed at the front of object and, then, the Accelerometers are placed.

Value

An `imu` object class.

Examples

```
## Not run:
if(!require("imudata")){
install_imudata()
library("imudata")
}
```

```
data(imu6)

# Create an IMU Object that is full.
ex = imu(imu6, gyros = 1:3, accels = 4:6, axis = c('X', 'Y', 'Z', 'X', 'Y', 'Z'), freq = 100)

# Create an IMU object that has only gyros.
ex.gyro = ex[,1:3]
ex.gyro2 = ex[,c("Gyro. X","Gyro. Y","Gyro. Z")]

# Create an IMU object that has only accels.
ex.accel = ex[,4:6]
ex.accel2 = ex[,c("Accel. X","Accel. Y","Accel. Z")]

# Create an IMU object with both gyros and accels on axis X and Y
ex.b = ex[,c(1,2,4,5)]
ex.b2 = ex[,c("Gyro. X","Gyro. Y","Accel. X","Accel. Y")]


## End(Not run)
```

`AIC.fitsimts` *Akaike's Information Criterion*

Description

This function calculates AIC, BIC or HQ for a fitsimts object. This function currently only supports models estimated by the MLE.

Usage

```
## S3 method for class 'fitsimts'
AIC(object, k = 2, ...)
```

Arguments

`object`	A fitsimts object.
`k`	The penalty per parameter to be used; the default k = 2 is the classical AIC.
`...`	Optionally more fitted model objects.

Value

AIC, BIC or HQ

Author(s)

Stéphane Guerrier

Examples

```
set.seed(1)
n = 300
Xt = gen_gts(n, AR(phi = c(0, 0, 0.8), sigma2 = 1))
mod = estimate(AR(3), Xt)

# AIC
AIC(mod)

# BIC
AIC(mod, k = log(n))

# HQ
AIC(mod, k = 2*log(log(n)))
```

AR *Create an Autoregressive P [AR(P)] Process*

Description

Sets up the necessary backend for the AR(P) process.

Usage

```
AR(phi = NULL, sigma2 = 1)
```

Arguments

phi	A `vector` with double values for the ϕ of an AR(P) process (see Note for details).
sigma2	A `double` value for the variance, σ^2, of an AR(P) process. (see Note for details).

Value

An S3 object with called ts.model with the following structure:

process.desc Used in summary: "AR-1","AR-2", ..., "AR-P", "SIGMA2"

theta ϕ_1, ϕ_2, ..., ϕ_p, σ^2

plength Number of Parameters

desc "AR"

print String containing simplified model

obj.desc Depth of Parameters e.g. list(p,1)

starting Guess starting values? TRUE or FALSE (e.g. specified value)

Note

We consider the following model:

$$X_t = \sum_{j=1}^{p} \phi_j X_{t-1} + \varepsilon_t$$

, where ε_t is iid from a zero mean normal distribution with variance σ^2.

Author(s)

James Balamuta

Examples

```
AR(1) # Slower version of AR1()
AR(phi=.32, sigma=1.3) # Slower version of AR1()
AR(2) # Equivalent to ARMA(2,0).
```

`AR1` *Definition of an Autoregressive Process of Order 1*

Description

Definition of an Autoregressive Process of Order 1

Usage

```
AR1(phi = NULL, sigma2 = 1)
```

Arguments

`phi`	A `double` value for the parameter ϕ (see Note for details).
`sigma2`	A `double` value for the variance parameter σ^2 (see Note for details).

Value

An S3 object containing the specified ts.model with the following structure:

process.desc Used in summary: "AR1","SIGMA2"

theta Parameter vector including ϕ, σ^2

plength Number of parameters

print String containing simplified model

desc "AR1"

obj.desc Depth of Parameters e.g. list(1,1)

starting Find starting values? TRUE or FALSE (e.g. specified value)

Note

We consider the following AR(1) model:

$$X_t = \phi X_{t-1} + \varepsilon_t$$

, where ε_t is iid from a zero mean normal distribution with variance σ^2.

Author(s)

James Balamuta

Examples

```
AR1()
AR1(phi=.32, sigma2 = 1.3)
```

---

ar1_to_wv *AR(1) process to WV*

Description

This function computes the Haar WV of an AR(1) process

Usage

```
ar1_to_wv(phi, sigma2, tau)
```

Arguments

`phi`	A `double` that is the phi term of the AR(1) process
`sigma2`	A `double` corresponding to variance of AR(1) process
`tau`	A `vec` containing the scales e.g. 2^τ

Details

This function is significantly faster than its generalized counter part `arma_to_wv`.

Value

A `vec` containing the wavelet variance of the AR(1) process.

Process Haar Wavelet Variance Formula

The Autoregressive Order 1 (AR(1)) process has a Haar Wavelet Variance given by:

$$\frac{2\sigma^2\left(4\phi^{\frac{\tau_j}{2}+1} - \phi^{\tau_j+1} - \frac{1}{2}\phi^2\tau_j + \frac{\tau_j}{2} - 3\phi\right)}{\left(1-\phi\right)^2\left(1-\phi^2\right)\tau_j^2}$$

ARIMA *Create an Autoregressive Integrated Moving Average (ARIMA) Process*

Description

Sets up the necessary backend for the ARIMA process.

Usage

```
ARIMA(ar = 1, i = 0, ma = 1, sigma2 = 1)
```

Arguments

ar	A vector or integer containing either the coefficients for ϕ's or the process number p for the Autoregressive (AR) term.
i	An integer containing the number of differences to be done.
ma	A vector or integer containing either the coefficients for θ's or the process number q for the Moving Average (MA) term.
sigma2	A double value for the standard deviation, σ, of the ARIMA process.

Details

A variance is required since the model generation statements utilize randomization functions expecting a variance instead of a standard deviation like R.

Value

An S3 object with called ts.model with the following structure:

process.desc $AR * p$, $MA * q$

theta σ

plength Number of parameters

print String containing simplified model

obj.desc y desc replicated x times

obj Depth of parameters e.g. list(c(length(ar),length(ma),1))

starting Guess starting values? TRUE or FALSE (e.g. specified value)

Note

We consider the following model:

$$\Delta^i X_t = \sum_{j=1}^{p} \phi_j \Delta^i X_{t-j} + \sum_{j=1}^{q} \theta_j \varepsilon_{t-j} + \varepsilon_t$$

, where ε_t is iid from a zero mean normal distribution with variance σ^2.

Author(s)

James Balamuta

Examples

```
# Create an ARMA(1,2) process
ARIMA(ar=1,2)
# Creates an ARMA(3,2) process with predefined coefficients.
ARIMA(ar=c(0.23,.43, .59), ma=c(0.4,.3))

# Creates an ARMA(3,2) process with predefined coefficients and standard deviation
ARIMA(ar=c(0.23,.43, .59), ma=c(0.4,.3), sigma2 = 1.5)
```

ARMA *Create an Autoregressive Moving Average (ARMA) Process*

Description

Sets up the necessary backend for the ARMA process.

Usage

```
ARMA(ar = 1, ma = 1, sigma2 = 1)
```

Arguments

`ar`	A `vector` or `integer` containing either the coefficients for ϕ's or the process number p for the Autoregressive (AR) term.
`ma`	A `vector` or `integer` containing either the coefficients for θ's or the process number q for the Moving Average (MA) term.
`sigma2`	A `double` value for the standard deviation, σ, of the ARMA process.

Details

A variance is required since the model generation statements utilize randomization functions expecting a variance instead of a standard deviation like R.

Value

An S3 object with called ts.model with the following structure:

process.desc $AR * p$, $MA * q$

theta σ

plength Number of Parameters

print String containing simplified model

obj.desc y desc replicated x times

obj Depth of Parameters e.g. list(c(length(ar),length(ma),1))

starting Guess Starting values? TRUE or FALSE (e.g. specified value)

Note

We consider the following model:

$$X_t = \sum_{j=1}^{p} \phi_j X_{t-j} + \sum_{j=1}^{q} \theta_j \varepsilon_{t-j} + \varepsilon_t$$

, where ε_t is iid from a zero mean normal distribution with variance σ^2.

Author(s)

James Balamuta

Examples

```
# Create an ARMA(1,2) process
ARMA(ar=1,2)
# Creates an ARMA(3,2) process with predefined coefficients.
ARMA(ar=c(0.23,.43, .59), ma=c(0.4,.3))

# Creates an ARMA(3,2) process with predefined coefficients and standard deviation
ARMA(ar=c(0.23,.43, .59), ma=c(0.4,.3), sigma2 = 1.5)
```

---

arma_to_wv *ARMA process to WV*

Description

This function computes the Haar Wavelet Variance of an ARMA process

Usage

```
arma_to_wv(ar, ma, sigma2, tau)
```

Arguments

ar	A vec containing the coefficients of the AR process
ma	A vec containing the coefficients of the MA process
sigma2	A double containing the residual variance
tau	A vec containing the scales e.g. 2^τ

Details

The function is a generic implementation that requires a stationary theoretical autocorrelation function (ACF) and the ability to transform an ARMA(p,q) process into an MA(∞) (e.g. infinite MA process).

Value

A vec containing the wavelet variance of the ARMA process.

Process Haar Wavelet Variance Formula

The Autoregressive Order p and Moving Average Order q (ARMA(p,q)) process has a Haar Wavelet Variance given by:

$$\frac{\tau_j \left[1 - \rho\left(\frac{\tau_j}{2}\right)\right] + 2 \sum_{i=1}^{\frac{\tau_j}{2}-1} i \left[2\rho\left(\frac{\tau_j}{2} - i\right) - \rho\left(i\right) - \rho\left(\tau_j - i\right)\right]}{\tau_j^2} \sigma_X^2$$

where σ_X^2 is given by the variance of the ARMA process. Furthermore, this assumes that stationarity has been achieved as it directly

---

ARMA11 *Definition of an ARMA(1,1)*

Description

Definition of an ARMA(1,1)

Usage

```
ARMA11(phi = NULL, theta = NULL, sigma2 = 1)
```

Arguments

phi	A double containing the parameter ϕ_1 (see Note for details).
theta	A double containing the parameter θ_1 (see Note for details).
sigma2	A double value for the parameter σ^2 (see Note for details).

Details

A variance is required since the model generation statements utilize randomization functions expecting a variance instead of a standard deviation like R.

Value

An S3 object with called ts.model with the following structure:

process.desc $AR1$, $MA1$, $SIGMA2$

theta ϕ, θ, σ^2

plength Number of Parameters: 3

print String containing simplified model

obj.desc Depth of Parameters e.g. list(c(1,1,1))

starting Guess Starting values? TRUE or FALSE (e.g. specified value)

Note

We consider the following model:

$$X_t = \phi X_{t-1} + \theta_1 \varepsilon_{t-1} + \varepsilon_t,$$

where ε_t is iid from a zero mean normal distribution with variance σ^2.

Author(s)

James Balamuta

Examples

```
# Creates an ARMA(1,1) process with predefined coefficients.
ARMA11(phi = .23, theta = .1, sigma2 = 1)

# Creates an ARMA(1,1) process with values to be guessed on callibration.
ARMA11()
```

`arma11_to_wv` *ARMA(1,1) to WV*

Description

This function computes the WV (haar) of an Autoregressive Order 1 - Moving Average Order 1 (ARMA(1,1)) process.

Usage

```
arma11_to_wv(phi, theta, sigma2, tau)
```

Arguments

`phi`	A `double` corresponding to the autoregressive term.
`theta`	A `double` corresponding to the moving average term.
`sigma2`	A `double` the variance of the process.
`tau`	A `vec` containing the scales e.g. 2^τ

Details

This function is significantly faster than its generalized counter part `arma_to_wv`

Value

A `vec` containing the wavelet variance of the ARMA(1,1) process.

Process Haar Wavelet Variance Formula

The Autoregressive Order 1 and Moving Average Order 1 (ARMA(1,1)) process has a Haar Wavelet Variance given by:

$$\nu_j^2\left(\phi,\theta,\sigma^2\right) = -\frac{2\sigma^2\left(-\frac{1}{2}(\theta+1)^2\left(\phi^2-1\right)\tau_j-(\theta+\phi)(\theta\phi+1)\left(\phi^{\tau_j}-4\phi^{\frac{\tau_j}{2}}+3\right)\right)}{(\phi-1)^3(\phi+1)\tau_j^2}$$

`australia` *Quarterly Increase in Stocks Non-Farm Total, Australia*

Description

A dataset containing the quarterly increase in stocks non-farm total in Australia, with frequency 4 starting from September 1959 to March 1991 with a total of 127 observations.

Usage

```
australia
```

Format

A data frame with 127 rows and 2 variables:

Quarter year and quarter

Increase quarterly increase in stocks non-farm total

Source

Time Series Data Library (citing: Australian Bureau of Statistics) datamarket

---

`auto_corr` *Empirical ACF and PACF*

Description

This function can estimate either the autocovariance / autocorrelation for univariate time series, or the partial autocovariance / autocorrelation for univariate time series.

Usage

```
auto_corr(
  x,
  lag.max = NULL,
  pacf = FALSE,
  type = "correlation",
  demean = TRUE,
  robust = FALSE
)
```

Arguments

x	A vector or ts object (of length $N > 1$).
lag.max	An integer indicating the maximum lag up to which to compute the empirical ACF / PACF.
pacf	A boolean indicating whether to output the PACF. If it's TRUE, then the function will only estimate the empirical PACF. If it's FALSE (the default), then the function will only estimate the empirical ACF.
type	A character string giving the type of acf to be computed. Allowed values are "correlation" (the default) and "covariance".
demean	A boolean indicating whether the data should be detrended (TRUE) or not (FALSE). Defaults to TRUE.
robust	A boolean indicating whether a robust estimator should be used (TRUE) or not (FALSE). Defaults to FALSE. This only works when the function is estimating ACF.

Details

lagmax default is $10 * log10(N/m)$ where N is the number of observations and m is the number of time series being compared. If lagmax supplied is greater than the number of observations N, then one less than the total will be taken (i.e. N - 1).

Value

An array of dimensions $N \times 1 \times 1$.

Author(s)

Yuming Zhang

Examples

```
m = auto_corr(datasets::AirPassengers)
m = auto_corr(datasets::AirPassengers, pacf = TRUE)
```

---

best_model *Select the Best Model*

Description

This function retrieves the best model from a selection procedure.

Usage

```
best_model(x, ic = "aic")
```

Arguments

x	An object of class select_arma, select_ar or select_ma.
ic	A string indicating the type of criterion to use in selecting the best model. Supported criteria include "aic" (AIC), "bic" (BIC) and "hq" (HQ).

Examples

```
set.seed(18)
xt = gen_arima(N=100, ar=0.3, d=1, ma=0.3)
x = select_arima(xt, d=1L)
best_model(x, ic = "aic")

set.seed(19)
xt = gen_ma1(100, 0.3, 1)
x = select_ma(xt, q.min=2L, q.max=5L)
best_model(x, ic = "bic")

set.seed(20)
xt = gen_arma(100, c(.3,.5), c(.1), 1, 0)
x = select_arma(xt, p.min = 1L, p.max = 4L,
                q.min = 1L, q.max = 3L)
best_model(x, ic = "hq")
```

---

check *Diagnostics on Fitted Time Series Model*

Description

This function can perform (simple) diagnostics on the fitted time series model. It can output 6 diagnostic plots to assess the model, including (1) residuals plot, (2) histogram of distribution of standardized residuals, (3) Normal Q-Q plot of residuals, (4) ACF plot, (5) PACF plot, (6) Box test results.

Usage

```
check(model = NULL, resids = NULL, simple = FALSE)
```

Arguments

model	A fitsimts, lm or gam object.
resids	A vector of residuals for diagnostics.
simple	A boolean indicating whether to return simple diagnostic plots or not.

Author(s)

Stéphane Guerrier and Yuming Zhang

Examples

```
Xt = gen_gts(300, AR(phi = c(0, 0, 0.8), sigma2 = 1))
model = estimate(AR(3), Xt)
check(model)

check(resids = rnorm(100))

Xt = gen_gts(1000, SARIMA(ar = c(0.5, -0.25), i = 0, ma = 0.5, sar = -0.8,
si = 1, sma = 0.25, s = 24, sigma2 = 1))
model = estimate(SARIMA(ar = 2, i = 0, ma = 1, sar = 1, si = 1, sma = 1, s = 24),
Xt, method = "rgmwm")
check(model)
check(model, simple=TRUE)
```

---

compare_acf *Comparison of Classical and Robust Correlation Analysis Functions*

Description

Compare classical and robust ACF of univariate time series.

Usage

```
compare_acf(
  x,
  lag.max = NULL,
  demean = TRUE,
  show.ci = TRUE,
  alpha = 0.05,
  plot = TRUE,
  ...
)
```

Arguments

x	A vector or "ts" object (of length $N > 1$).
lag.max	A integer indicating the maximum lag up to which to compute the ACF and PACF functions.
demean	A bool indicating whether the data should be detrended (TRUE) or not (FALSE). Defaults to TRUE.
show.ci	A bool indicating whether to compute and show the confidence region. Defaults to TRUE.
alpha	A double indicating the level of significance for the confidence interval. By default alpha = 0.05 which gives a 1 - alpha = 0.95 confidence interval.
plot	A bool indicating whether a plot of the computed quantities should be produced. Defaults to TRUE.
...	Additional parameters.

Author(s)

Yunxiang Zhang

Examples

```
# Estimate both the ACF and PACF functions
compare_acf(datasets::AirPassengers)
```

`corr_analysis` *Correlation Analysis Functions*

Description

Correlation Analysis function computes and plots both empirical ACF and PACF of univariate time series.

Usage

```
corr_analysis(
  x,
  lag.max = NULL,
  type = "correlation",
  demean = TRUE,
  show.ci = TRUE,
  alpha = 0.05,
  plot = TRUE,
  ...
)
```

Arguments

`x`	A `vector` or `"ts"` object (of length $N > 1$).
`lag.max`	A `integer` indicating the maximum lag up to which to compute the ACF and PACF functions.
`type`	A `character` string giving the type of acf to be computed. Allowed values are "correlation" (the default) and "covariance".
`demean`	A `bool` indicating whether the data should be detrended (`TRUE`) or not (`FALSE`). Defaults to `TRUE`.
`show.ci`	A `bool` indicating whether to compute and show the confidence region. Defaults to `TRUE`.
`alpha`	A `double` indicating the level of significance for the confidence interval. By default `alpha` = `0.05` which gives a 1 - `alpha` = 0.95 confidence interval.
`plot`	A `bool` indicating whether a plot of the computed quantities should be produced. Defaults to `TRUE`.
`...`	Additional parameters.

Value

Two `array` objects (ACF and PACF) of dimension $N \times S \times S$.

Author(s)

Yunxiang Zhang

Examples

```
# Estimate both the ACF and PACF functions
corr_analysis(datasets::AirPassengers)
```

`deriv_2nd_ar1` *Analytic second derivative matrix for AR(1) process*

Description

Calculates the second derivative for the AR(1) process and places it into a matrix form. The matrix form in this case is for convenience of the calculation.

Usage

```
deriv_2nd_ar1(phi, sigma2, tau)
```

Arguments

`phi`	A `double` corresponding to the phi coefficient of an AR(1) process.
`sigma2`	A `double` corresponding to the error term of an AR(1) process.
`tau`	A `vec` containing the scales e.g. 2^τ

Value

A `matrix` with the first column containing the second partial derivative with respect to ϕ and the second column contains the second partial derivative with respect to σ^2

Process Haar WV Second Derivative

Taking the second derivative with respect to ϕ yields:

$$\frac{\partial^2}{\partial\phi^2}\nu_j^2\left(\phi,\sigma^2\right) = \frac{2\sigma^2\left(\left(\phi^2-1\right)\tau_j\left(2(\phi(7\phi+4)+1)\phi^{\frac{\tau_j}{2}-1}-(\phi(7\phi+4)+1)\phi^{\tau_j-1}+3(\phi+1)^2\right)+\left(\phi^2-1\right)^2\tau_j^2\left(\phi^{\tau}\right.\right.}{(\phi-1)^5(\phi+1)^3\tau_j^2}$$

Taking the second derivative with respect to σ^2 yields:

$$\frac{\partial^2}{\partial\sigma^4}\nu_j^2\left(\sigma^2\right) = 0$$

Taking the derivative with respect to ϕ and σ^2 yields:

$$\frac{\partial^2}{\partial\phi\partial\sigma^2}\nu_j^2\left(\phi,\sigma^2\right) = \frac{2\left(\left(\phi^2-1\right)\tau_j\left(\phi^{\tau_j}-2\phi^{\frac{\tau_j}{2}}-\phi-1\right)-\left(\phi(3\phi+2)+1\right)\left(\phi^{\tau_j}-4\phi^{\frac{\tau_j}{2}}+3\right)\right)}{(\phi-1)^4(\phi+1)^2\tau_j^2}$$

Author(s)

James Joseph Balamuta (JJB)

`deriv_2nd_arma11` *Analytic D matrix for ARMA(1,1) process*

Description

Obtain the second derivative of the ARMA(1,1) process.

Usage

```
deriv_2nd_arma11(phi, theta, sigma2, tau)
```

Arguments

`phi`	A `double` corresponding to the phi coefficient of an ARMA(1,1) process.
`theta`	A `double` corresponding to the theta coefficient of an ARMA(1,1) process.
`sigma2`	A `double` corresponding to the error term of an ARMA(1,1) process.
`tau`	A `vec` containing the scales e.g. 2^τ

Value

A `matrix` with:

- The **first** column containing the second partial derivative with respect to ϕ;
- The **second** column containing the second partial derivative with respect to θ;
- The **third** column contains the second partial derivative with respect to σ^2.
- The **fourth** column contains the partial derivative with respect to ϕ and θ.
- The **fiveth** column contains the partial derivative with respect to σ^2 and ϕ.
- The **sixth** column contains the partial derivative with respect to σ^2 and θ.

Process Haar WV Second Derivative

Taking the second derivative with respect to ϕ yields:

$$\frac{\partial^2}{\partial\phi^2}\nu_j^2\left(\phi,\theta,\sigma^2\right) = \frac{2\sigma^2}{\left(\phi-1\right)^5\left(\phi+1\right)^3\tau_j^2}\left(\begin{array}{r} (\phi-1)^2\left((\phi+1)^2\left(\theta^2\phi+\theta\phi^2+\theta+\phi\right)\tau_j^2\left(\phi^{\frac{\tau_j}{2}}\right.\right. \\ -12(\phi- \\ +6(\phi+1)(\phi-1)\left(\frac{1}{2}(\theta+1)^2\left(\phi^2-1\right)\tau_j+(\theta+\phi)(\theta\phi+1)\left(\phi^{\tau_j}-4\phi^{\frac{\tau_j}{2}}\right.\right. \end{array}\right.$$

Taking the second derivative with respect to θ yields:

$$\frac{\partial^2}{\partial\theta^2}\nu_j^2\left(\phi,\theta,\sigma^2\right) = \frac{2\sigma^2\left(\left(\phi^2-1\right)\tau_j+2\phi\left(\phi^{\tau_j}-4\phi^{\frac{\tau_j}{2}}+3\right)\right)}{\left(\phi-1\right)^3\left(\phi+1\right)\tau_j^2}$$

Taking the second derivative with respect to σ^2 yields:

$$\frac{\partial^2}{\partial\sigma^4}\nu_j^2\left(\phi,\theta,\sigma^2\right) = 0$$

Taking the derivative with respect to σ^2 and θ yields:

$$\frac{\partial}{\partial\theta}\frac{\partial}{\partial\sigma^2}\nu_j^2\left(\phi,\theta,\sigma^2\right) = \frac{2}{\left(\phi-1\right)^3\left(\phi+1\right)\tau_j^2}\left(\left(\theta+1\right)\left(\phi^2-1\right)\tau_j+\left(2\theta\phi+\phi^2+1\right)\left(\phi^{\tau_j}-4\phi^{\frac{\tau_j}{2}}+3\right)\right)$$

Taking the derivative with respect to σ^2 and ϕ yields:

$$\frac{\partial}{\partial\phi}\frac{\partial}{\partial\sigma^2}\nu_j^2\left(\phi,\theta,\sigma^2\right) = \frac{2}{\left(\phi-1\right)^4\left(\phi+1\right)^2\tau_j^2}\left(\begin{array}{l} -(\phi-1)(\phi+1)\left(\begin{array}{l} -(\theta+\phi)(\theta\phi+1)\tau_j\left(\phi^{\frac{\tau_j}{2}}-2\right)\phi^{\frac{\tau_j}{2}-1} \\ -\theta(\theta+\phi)\left(\phi^{\tau_j}-4\phi^{\frac{\tau_j}{2}}+3\right) \\ -(\theta\phi+1)\left(\phi^{\tau_j}-4\phi^{\frac{\tau_j}{2}}+3\right) \\ -(\theta+1)^2\phi\tau_j \end{array}\right) \\ +(\phi-1)\left(-\frac{1}{2}(\theta+1)^2\left(\phi^2-1\right)\tau_j-(\theta+\phi)(\theta\phi+1)\left(\phi^{\tau_j}-4\phi^{\frac{\tau_j}{2}}+\right. \\ +3(\phi+1)\left(-\frac{1}{2}(\theta+1)^2\left(\phi^2-1\right)\tau_j-(\theta+\phi)(\theta\phi+1)\left(\phi^{\tau_j}-4\phi^{\frac{\tau_j}{2}}+\right. \end{array}\right.$$

Taking the derivative with respect to ϕ and θ yields:

$$\frac{\partial}{\partial\theta}\frac{\partial}{\partial\phi}\nu_j^2\left(\phi,\theta,\sigma^2\right) = -\frac{2\sigma^2}{\left(\phi-1\right)^4\left(\phi+1\right)^2\tau_j^2}\left(\begin{array}{c} \tau_j\left(\begin{array}{c} 2(\theta+1)(\phi-1)(\phi+1)^2 \\ +2\left(\phi^2-1\right)\left(2\theta\phi+\phi^2+1\right)\phi^{\frac{\tau_j}{2}-1} \\ -\left(\phi^2-1\right)\left(2\theta\phi+\phi^2+1\right)\phi^{\tau_j-1} \end{array}\right) \\ +2\left(\theta(\phi(3\phi+2)+1)+\phi\left(\phi^2+\phi+3\right)+1\right)\left(\phi^{\tau_j}-4\phi^{\frac{\tau_j}{2}}+3\right) \end{array}\right)$$

Author(s)

James Joseph Balamuta (JJB)

deriv_2nd_dr *Analytic second derivative matrix for drift process*

Description

To ease a later calculation, we place the result into a matrix structure.

Usage

```
deriv_2nd_dr(tau)
```

Arguments

tau	A vec containing the scales e.g. 2^τ

Value

A matrix with the first column containing the second partial derivative with respect to ω.

Author(s)

James Joseph Balamuta (JJB)

deriv_2nd_ma1 *Analytic second derivative for MA(1) process*

Description

To ease a later calculation, we place the result into a matrix structure.

Usage

```
deriv_2nd_ma1(theta, sigma2, tau)
```

Arguments

theta	A double corresponding to the theta coefficient of an MA(1) process.
sigma2	A double corresponding to the error term of an MA(1) process.
tau	A vec containing the scales e.g. 2^τ

Value

A matrix with the first column containing the second partial derivative with respect to θ, the second column contains the partial derivative with respect to θ and σ^2, and lastly we have the second partial derivative with respect to σ^2.

Process Haar WV Second Derivative

Taking the second derivative with respect to θ yields:

$$\frac{\partial^2}{\partial\theta^2}\nu_j^2\left(\theta,\sigma^2\right)=\frac{2\sigma^2}{\tau_j}$$

Taking the second derivative with respect to σ^2 yields:

$$\frac{\partial^2}{\partial\sigma^4}\nu_j^2\left(\theta,\sigma^2\right)=0$$

Taking the first derivative with respect to θ and σ^2 yields:

$$\frac{\partial}{\partial\theta}\frac{\partial}{\partial\sigma^2}\nu_j^2\left(\theta,\sigma^2\right)=\frac{2(\theta+1)\tau_j-6}{\tau_j^2}$$

Author(s)

James Joseph Balamuta (JJB)

---

deriv_ar1 *Analytic D matrix for AR(1) process*

Description

Obtain the first derivative of the AR(1) process.

Usage

```
deriv_ar1(phi, sigma2, tau)
```

Arguments

phi	A double corresponding to the phi coefficient of an AR(1) process.
sigma2	A double corresponding to the error term of an AR(1) process.
tau	A vec containing the scales e.g. 2^τ

Value

A matrix with the first column containing the partial derivative with respect to ϕ and the second column contains the partial derivative with respect to σ^2

Process Haar WV First Derivative

Taking the derivative with respect to ϕ yields:

$$\frac{\partial}{\partial\phi}\nu_j^2\left(\phi,\sigma^2\right)=\frac{2\sigma^2\left(\left(\phi^2-1\right)\tau_j\left(-2\phi^{\frac{\tau_j}{2}}+\phi^{\tau_j}-\phi-1\right)-\left(\phi\left(3\phi+2\right)+1\right)\left(-4\phi^{\frac{\tau_j}{2}}+\phi^{\tau_j}+3\right)\right)}{\left(\phi-1\right)^4\left(\phi+1\right)^2\tau_j^2}$$

Taking the derivative with respect to σ^2 yields:

$$\frac{\partial}{\partial\sigma^2}\nu_j^2\left(\phi,\sigma^2\right)=\frac{\left(\phi^2-1\right)\tau_j+2\phi\left(-4\phi^{\frac{\tau_j}{2}}+\phi^{\tau_j}+3\right)}{\left(\phi-1\right)^3\left(\phi+1\right)\tau_j^2}$$

Author(s)

James Joseph Balamuta (JJB)

`deriv_arma11` *Analytic D matrix for ARMA(1,1) process*

Description

Obtain the first derivative of the ARMA(1,1) process.

Usage

```
deriv_arma11(phi, theta, sigma2, tau)
```

Arguments

`phi`	A `double` corresponding to the phi coefficient of an ARMA(1,1) process.
`theta`	A `double` corresponding to the theta coefficient of an ARMA(1,1) process.
`sigma2`	A `double` corresponding to the error term of an ARMA(1,1) process.
`tau`	A `vec` containing the scales e.g. 2^τ

Value

A `matrix` with:

- The **first** column containing the partial derivative with respect to ϕ;
- The **second** column containing the partial derivative with respect to θ;
- The **third** column contains the partial derivative with respect to σ^2.

Process Haar WV First Derivative

Taking the derivative with respect to ϕ yields:

$$\frac{\partial}{\partial\phi}\nu_j^2\left(\phi,\theta,\sigma^2\right) = \frac{2\sigma^2}{(\phi-1)^4(\phi+1)^2\tau_j^2}\left(\begin{array}{r}\tau_j\left(-(\theta+1)^2(\phi-1)(\phi+1)^2-2\left(\phi^2-1\right)(\theta+\phi)(\theta\phi+1)\phi^{\frac{\tau_j}{2}-1}+\left(\phi^2-\right.\right.\\ -\left(\theta^2((3\phi+2)\phi+1)+2\theta\left(\left(\phi^2+\phi+3\right)\phi+1\right)+(3\phi+2)\phi+1\right.\end{array}\right.$$

Taking the derivative with respect to θ yields:

$$\frac{\partial}{\partial\theta}\nu_j^2\left(\phi,\theta,\sigma^2\right) = \frac{2\sigma^2\left(\left(\theta+1\right)\left(\phi^2-1\right)\tau_j+\left(2\theta\phi+\phi^2+1\right)\left(\phi^{\tau_j}-4\phi^{\frac{\tau_j}{2}}+3\right)\right)}{(\phi-1)^3(\phi+1)\tau_j^2}$$

Taking the derivative with respect to σ^2 yields:

$$\frac{\partial}{\partial\sigma^2}\nu_j^2\left(\phi,\theta,\sigma^2\right) = \frac{2\sigma^2\left(\left(\phi^2-1\right)\tau_j+2\phi\left(\phi^{\tau_j}-4\phi^{\frac{\tau_j}{2}}+3\right)\right)}{(\phi-1)^3(\phi+1)\tau_j^2}$$

Author(s)

James Joseph Balamuta (JJB)

`deriv_dr` *Analytic D matrix for Drift (DR) Process*

Description

Obtain the first derivative of the Drift (DR) process.

Usage

```
deriv_dr(omega, tau)
```

Arguments

`omega`	A `double` that is the slope of the drift.
`tau`	A `vec` containing the scales e.g. 2^τ

Value

A `matrix` with the first column containing the partial derivative with respect to ω.

Process Haar WV First Derivative

Taking the derivative with respect to ω yields:

$$\frac{\partial}{\partial \omega} \nu_j^2 (\omega) = \frac{\tau_j^2 \omega}{8}$$

Note: We are taking the derivative with respect to ω and not ω^2 as the ω relates to the slope of the process and not the processes variance like RW and WN. As a result, a second derivative exists and is not zero.

Author(s)

James Joseph Balamuta (JJB)

`deriv_ma1` *Analytic D matrix for MA(1) process*

Description

Obtain the first derivative of the MA(1) process.

Usage

```
deriv_ma1(theta, sigma2, tau)
```

Arguments

`theta`	A `double` corresponding to the theta coefficient of an MA(1) process.
`sigma2`	A `double` corresponding to the error term of an MA(1) process.
`tau`	A `vec` containing the scales e.g. 2^τ

Value

A `matrix` with the first column containing the partial derivative with respect to θ and the second column contains the partial derivative with respect to σ^2

Process Haar WV First Derivative

Taking the derivative with respect to θ yields:

$$\frac{\partial}{\partial \theta} \nu_j^2 \left(\theta, \sigma^2\right) = \frac{\sigma^2 \left(2 \left(\theta + 1\right) \tau_j - 6\right)}{\tau_j^2}$$

Taking the derivative with respect to σ^2 yields:

$$\frac{\partial}{\partial \sigma^2} \nu_j^2 \left(\theta, \sigma^2\right) = \frac{\left(\theta + 1\right)^2 \tau_j - 6\theta}{\tau_j^2}$$

Author(s)

James Joseph Balamuta (JJB)

deriv_qn *Analytic D matrix for Quantization Noise (QN) Process*

Description

Obtain the first derivative of the Quantization Noise (QN) process.

Usage

```
deriv_qn(tau)
```

Arguments

tau	A vec containing the scales e.g. 2^τ

Value

A matrix with the first column containing the partial derivative with respect to Q^2.

Process Haar WV First Derivative

Taking the derivative with respect to Q^2 yields:

$$\frac{\partial}{\partial Q^2}\nu_j^2\left(Q^2\right) = \frac{6}{\tau_j^2}$$

Author(s)

James Joseph Balamuta (JJB)

deriv_rw *Analytic D matrix Random Walk (RW) Process*

Description

Obtain the first derivative of the Random Walk (RW) process.

Usage

```
deriv_rw(tau)
```

Arguments

tau	A vec containing the scales e.g. 2^τ

Value

A `matrix` with the first column containing the partial derivative with respect to γ^2.

Process Haar WV First Derivative

Taking the derivative with respect to γ^2 yields:

$$\frac{\partial}{\partial \gamma^2} \nu_j^2 \left(\gamma^2\right) = \frac{\tau_j^2 + 2}{12\tau_j}$$

Author(s)

James Joseph Balamuta (JJB)

---

deriv_wn *Analytic D Matrix for a Gaussian White Noise (WN) Process*

Description

Obtain the first derivative of the Gaussian White Noise (WN) process.

Usage

```
deriv_wn(tau)
```

Arguments

`tau`	A `vec` containing the scales e.g. 2^τ

Value

A `matrix` with the first column containing the partial derivative with respect to σ^2.

Process Haar WV First Derivative

Taking the derivative with respect to σ^2 yields:

$$\frac{\partial}{\partial \sigma^2} \nu_j^2 \left(\sigma^2\right) = \frac{1}{\tau_j}$$

Author(s)

James Joseph Balamuta (JJB)

`derivative_first_matrix` *Analytic D matrix of Processes*

Description

This function computes each process to WV (haar) in a given model.

Usage

```
derivative_first_matrix(theta, desc, objdesc, tau)
```

Arguments

`theta`	A `vec` containing the list of estimated parameters.
`desc`	A `vector<string>` containing a list of descriptors.
`objdesc`	A `field<vec>` containing a list of object descriptors.
`tau`	A `vec` containing the scales e.g. 2^τ

Details

Function returns the matrix effectively known as "D"

Value

A `matrix` with the process derivatives going down the column

Author(s)

James Joseph Balamuta (JJB)

`diag_boxpierce` *Box-Pierce*

Description

Performs the Box-Pierce test to assess the Null Hypothesis of Independence in a Time Series

Usage

```
diag_boxpierce(x, order = NULL, stop_lag = 20, stdres = FALSE, plot = TRUE)
```

Arguments

x	An arima or data set.
order	An integer indicating the degrees of freedom. If 'x' is not a series of residuals, then set equal to 0.
stop_lag	An integer indicating the length of lags that should be calculated.
stdres	A boolean indicating whether to standardize the residualizes (e.g. $res/sd(res)$) or not.
plot	A logical. If TRUE (the default) a plot should be produced.

Author(s)

James Balamuta, Stéphane Guerrier, Yuming Zhang

---

diag_ljungbox *Ljung-Box*

Description

Performs the Ljung-Box test to assess the Null Hypothesis of Independence in a Time Series

Usage

```
diag_ljungbox(x, order = NULL, stop_lag = 20, stdres = FALSE, plot = TRUE)
```

Arguments

x	An arima or data set.
order	An integer indicating the degrees of freedom. If 'x' is not a series of residuals, then set equal to 0.
stop_lag	An integer indicating the length of lags that should be calculated.
stdres	A boolean indicating whether to standardize the residualizes (e.g. $res/sd(res)$) or not.
plot	A logical. If TRUE (the default) a plot should be produced.

Author(s)

James Balamuta, Stéphane Guerrier, Yuming Zhang

diag_plot *Diagnostic Plot of Residuals*

Description

This function will plot 8 diagnostic plots to assess the model used to fit the data. These include: (1) residuals plot, (2) residuals vs fitted values, (3) histogram of distribution of standardized residuals, (4) Normal Q-Q plot of residuals, (5) ACF plot, (6) PACF plot, (7) Haar Wavelet Variance Representation, (8) Box test results.

Usage

```
diag_plot(Xt = NULL, model = NULL, resids = NULL, std = FALSE)
```

Arguments

Xt	The data used to construct said model.
model	A fitsimts, lm or gam object.
resids	A vector of residuals for diagnostics.
std	A boolean indicating whether we use standardized residuals for (1) residuals plot and (8) Box test results.

Author(s)

Yuming Zhang

diag_portmanteau_ *Portmanteau Tests*

Description

Performs the Portmanteau test to assess the Null Hypothesis of Independence in a Time Series

Usage

```
diag_portmanteau_(
  x,
  order = NULL,
  stop_lag = 20,
  stdres = FALSE,
  test = "Ljung-Box",
  plot = TRUE
)
```

Arguments

x	An arima or data set.
order	An integer indicating the degrees of freedom. If 'x' is not a series of residuals, then set equal to 0.
stop_lag	An integer indicating the length of lags that should be calculated.
stdres	A boolean indicating whether to standardize the residualizes (e.g. $res/sd(res)$) or not.
test	A string indicating whether to perform Ljung-Box test or Box-Pierce test.
plot	A logical. If TRUE (the default) a plot should be produced.

Author(s)

James Balamuta, Stéphane Guerrier, Yuming Zhang

DR *Create an Drift (DR) Process*

Description

Sets up the necessary backend for the DR process.

Usage

```
DR(omega = NULL)
```

Arguments

omega	A double value for the slope of a DR process (see Note for details).

Value

An S3 object with called ts.model with the following structure:

process.desc Used in summary: "DR"

theta slope

print String containing simplified model

plength Number of parameters

obj.desc y desc replicated x times

obj Depth of parameters e.g. list(1)

starting Guess starting values? TRUE or FALSE (e.g. specified value)

Note

We consider the following model:

$$Y_t = \omega t$$

Author(s)

James Balamuta

Examples

```
DR()
DR(omega=3.4)
```

`dr_to_wv` *Drift to WV*

Description

This function compute the WV (haar) of a Drift process

Usage

```
dr_to_wv(omega, tau)
```

Arguments

`omega`	A `double` corresponding to the slope of the drift
`tau`	A `vec` containing the scales e.g. 2^τ

Value

A `vec` containing the wavelet variance of the drift.

Process Haar Wavelet Variance Formula

The Drift (DR) process has a Haar Wavelet Variance given by:

$$\nu_j^2(\omega) = \frac{\tau_j^2 \omega^2}{16}$$

`estimate` *Fit a Time Series Model to Data*

Description

This function can fit a time series model to data using different methods.

Usage

```
estimate(model, Xt, method = "mle", demean = TRUE)
```

Arguments

`model`	A time series model.
`Xt`	A `vector` of time series data.
`method`	A `string` indicating the method used for model fitting. Supported methods include `mle`, `yule-walker`, `gmwm` and `rgmwm`.
`demean`	A `boolean` indicating whether the model includes a mean / intercept term or not.

Author(s)

Stéphane Guerrier and Yuming Zhang

Examples

```
Xt = gen_gts(300, AR(phi = c(0, 0, 0.8), sigma2 = 1))
plot(Xt)
estimate(AR(3), Xt)

Xt = gen_gts(300, MA(theta = 0.5, sigma2 = 1))
plot(Xt)
estimate(MA(1), Xt, method = "gmwm")

Xt = gen_gts(300, ARMA(ar = c(0.8, -0.5), ma = 0.5, sigma2 = 1))
plot(Xt)
estimate(ARMA(2,1), Xt, method = "rgmwm")

Xt = gen_gts(300, ARIMA(ar = c(0.8, -0.5), i = 1, ma = 0.5, sigma2 = 1))
plot(Xt)
estimate(ARIMA(2,1,1), Xt, method = "mle")

Xt = gen_gts(1000, SARIMA(ar = c(0.5, -0.25), i = 0, ma = 0.5, sar = -0.8,
si = 1, sma = 0.25, s = 24, sigma2 = 1))
plot(Xt)
estimate(SARIMA(ar = 2, i = 0, ma = 1, sar = 1, si = 1, sma = 1, s = 24), Xt,
method = "rgmwm")
```

`evaluate` *Evalute a time series or a list of time series models*

Description

This function calculates AIC, BIC and HQ or the MAPE for a list of time series models. This function currently only supports models estimated by the MLE.

Usage

```
evaluate(
  models,
  Xt,
  criterion = "IC",
  start = 0.8,
  demean = TRUE,
  print = TRUE
)
```

Arguments

`models`	A time series model or a list of time series models.
`Xt`	A time series (i.e gts object).
`criterion`	Either "IC" for AIC, BIC and HQ or "MAPE" for MAPE.
`start`	A `numeric` indicating the starting proportion of the data that is used for prediction (assuming criterion = "MAPE").
`demean`	A `boolean` indicating whether the model includes a mean / intercept term or not.
`print`	logical. If `TRUE` (the default) results are printed.

Value

AIC, BIC and HQ or MAPE

Author(s)

Stéphane Guerrier

Examples

```
set.seed(18)
n = 300
Xt = gen_gts(n, AR(phi = c(0, 0, 0.8), sigma2 = 1))
evaluate(AR(1), Xt)
evaluate(list(AR(1), AR(3), MA(3), ARMA(1,2),
SARIMA(ar = 1, i = 0, ma = 1, sar = 1, si = 1, sma = 1, s = 12)), Xt)
evaluate(list(AR(1), AR(3)), Xt, criterion = "MAPE")
```

FGN *Definition of a Fractional Gaussian Noise (FGN) Process*

Description

Definition of a Fractional Gaussian Noise (FGN) Process

Usage

```
FGN(sigma2 = 1, H = 0.9999)
```

Arguments

sigma2	A double.
H	A double.

Value

An S3 object containing the specified ts.model with the following structure:

process.desc Used in summary: "SIGMA2","H"

theta Parameter vector including σ^2, H

plength Number of parameters

print String containing simplified model

desc "FGN"

obj.desc Depth of Parameters e.g. list(1,1)

starting Find starting values? TRUE or FALSE (e.g. specified value)

Author(s)

Lionel Voirol, Davide Cucci

Examples

```
FGN()
FGN(sigma2 = 1, H = 0.9999)
```

gen_ar1blocks *Generate AR(1) Block Process*

Description

This function allows us to generate a non-stationary AR(1) block process.

Usage

```
gen_ar1blocks(phi, sigma2, n_total, n_block, scale = 10,
title = NULL, seed = 135, ...)
```

Arguments

phi	A double value for the autocorrection parameter ϕ.
sigma2	A double value for the variance parameter σ^2.
n_total	An integer indicating the length of the simulated AR(1) block process.
n_block	An integer indicating the length of each block of the AR(1) block process.
scale	An integer indicating the number of levels of decomposition. The default value is 10.
title	A string indicating the name of the time series data.
seed	An integer defined for simulation replication purposes.
...	Additional parameters.

Value

A vector containing the AR(1) block process.

Note

This function generates a non-stationary AR(1) block process whose theoretical maximum overlapping allan variance (MOAV) is different from the theoretical MOAV of a stationary AR(1) process. This difference in the value of the allan variance between stationary and non-stationary processes has been shown through the calculation of the theoretical allan variance given in "A Study of the Allan Variance for Constant-Mean Non-Stationary Processes" by Xu et al. (IEEE Signal Processing Letters, 2017), preprint available: https://arxiv.org/abs/1702.07795.

Author(s)

Yuming Zhang and Haotian Xu

Examples

```
Xt = gen_ar1blocks(phi = 0.9, sigma2 = 1,
n_total = 1000, n_block = 10, scale = 100)
plot(Xt)

Yt = gen_ar1blocks(phi = 0.5, sigma2 = 5, n_total = 800,
n_block = 20, scale = 50)
plot(Yt)
```

---

gen_bi *Generate Bias-Instability Process*

Description

This function allows to generate a non-stationary bias-instability process.

Usage

```
gen_bi(sigma2, n_total, n_block, title = NULL, seed = 135, ...)
```

Arguments

sigma2	A double value for the variance parameter σ^2.
n_total	An integer indicating the length of the simulated bias-instability process.
n_block	An integer indicating the length of each block of the bias-instability process.
title	A string defining the name of the time series data.
seed	An integer defined for simulation replication purposes.
...	Additional parameters.

Value

A vector containing the bias-instability process.

Note

This function generates a non-stationary bias-instability process whose theoretical maximum overlapping allan variance (MOAV) is close to the theoretical MOAV of the best approximation of this process through a stationary AR(1) process over some scales. However, this approximation is not good enough when considering the logarithmic representation of the allan variance. Therefore, the exact form of the allan variance of this non-stationary process allows us to better interpret the signals characterized by bias-instability, as shown in "A Study of the Allan Variance for Constant-Mean Non-Stationary Processes" by Xu et al. (IEEE Signal Processing Letters, 2017), preprint available: https://arxiv.org/abs/1702.07795.

Author(s)

Yuming Zhang

Examples

```
Xt = gen_bi(sigma2 = 1, n_total = 1000, n_block = 10)
plot(Xt)

Yt = gen_bi(sigma2 = 0.8, n_total = 800, n_block = 20,
title = "non-stationary bias-instability process")
plot(Yt)
```

---

gen_gts *Simulate a simts TS object using a theoretical model*

Description

Create a `gts` object based on a time series model.

Usage

```
gen_gts(
  n,
  model,
  start = 0,
  end = NULL,
  freq = 1,
  unit_ts = NULL,
  unit_time = NULL,
  name_ts = NULL,
  name_time = NULL
)
```

Arguments

`n`	An `integer` containing the length of the time series.
`model`	A `ts.model` or `simts` object containing the available models in the simts package.
`start`	A `numeric` that provides the time of the first observation.
`end`	A `numeric` that provides the time of the last observation.
`freq`	A `numeric` that provides the rate of samples. Default value is 1.
`unit_ts`	A `string` that contains the unit expression of the time series. Default value is `NULL`.
`unit_time`	A `string` that contains the unit expression of the time. Default value is `NULL`.
`name_ts`	A `string` that provides an identifier for the time series data. Default value is `NULL`.
`name_time`	A `string` that provides an identifier for the time. Default value is `NULL`.

Details

This function accepts either a `ts.model` object (e.g. AR1(phi = .3, sigma2 =1) + WN(sigma2 = 1)) or a `simts` object.

Value

A `gts` object

Author(s)

James Balamuta and Wenchao Yang

Examples

```
# Set seed for reproducibility
set.seed(1336)
n = 1000

# AR1 + WN
model = AR1(phi = .5, sigma2 = .1) + WN(sigma2=1)
x = gen_gts(n, model)
plot(x)

# Reset seed
set.seed(1336)

# GM + WN
# Convert from AR1 to GM values
m = ar1_to_gm(c(.5,.1),10)

# Beta = 6.9314718, Sigma2_gm = 0.1333333
model = GM(beta = m[1], sigma2_gm = m[2]) + WN(sigma2=1)
x2 = gen_gts(n, model, freq = 10, unit_time = 'sec')
plot(x2)

# Same time series
all.equal(x, x2, check.attributes = FALSE)
```

---

gen_lts *Generate a Latent Time Series Object Based on a Model*

Description

Simulate a `lts` object based on a supplied time series model.

Usage

```
gen_lts(
  n,
  model,
  start = 0,
  end = NULL,
  freq = 1,
  unit_ts = NULL,
  unit_time = NULL,
  name_ts = NULL,
  name_time = NULL,
  process = NULL
)
```

Arguments

n	An interger indicating the amount of observations generated in this function.
model	A ts.model or simts object containing one of the allowed models.
start	A numeric that provides the time of the first observation.
end	A numeric that provides the time of the last observation.
freq	A numeric that provides the rate/frequency at which the time series is sampled. The default value is 1.
unit_ts	A string that contains the unit of measure of the time series. The default value is NULL.
unit_time	A string that contains the unit of measure of the time. The default value is NULL.
name_ts	A string that provides an identifier for the time series data. Default value is NULL.
name_time	A string that provides an identifier for the time. Default value is NULL.
process	A vector that contains model names of each column in the data object where the last name is the sum of the previous names.

Details

This function accepts either a ts.model object (e.g. AR1(phi = .3, sigma2 =1) + WN(sigma2 = 1)) or a simts object.

Value

A lts object with the following attributes:

start The time of the first observation.

end The time of the last observation.

freq Numeric representation of the sampling frequency/rate.

unit A string reporting the unit of measurement.

name Name of the generated dataset.

process A vector that contains model names of decomposed and combined processes

Author(s)

James Balamuta, Wenchao Yang, and Justin Lee

Examples

```
# AR
set.seed(1336)
model = AR1(phi = .99, sigma2 = 1) + WN(sigma2 = 1)
test = gen_lts(1000, model)
plot(test)
```

---

gen_nswn *Generate Non-Stationary White Noise Process*

Description

This function allows to generate a non-stationary white noise process.

Usage

```
gen_nswn(n_total, title = NULL, seed = 135, ...)
```

Arguments

n_total	An integer indicating the length of the simulated non-stationary white noise process.
title	A string defining the name of the time series data.
seed	An integer defined for simulation replication purposes.
...	Additional parameters.

Value

A vector containing the non-stationary white noise process.

Note

This function generates a non-stationary white noise process whose theoretical maximum overlapping allan variance (MOAV) corresponds to the theoretical MOAV of the stationary white noise process. This example confirms that the allan variance is unable to distinguish between a stationary white noise process and a white noise process whose second-order behavior is non-stationary, as pointed out in the paper "A Study of the Allan Variance for Constant-Mean Non-Stationary Processes" by Xu et al. (IEEE Signal Processing Letters, 2017), preprint available: https://arxiv.org/abs/1702.07795.

Author(s)

Yuming Zhang

Examples

```
Xt = gen_nswn(n_total = 1000)
plot(Xt)

Yt = gen_nswn(n_total = 2000, title = "non-stationary
white noise process", seed = 1960)
plot(Yt)
```

GM *Create a Gauss-Markov (GM) Process*

Description

Sets up the necessary backend for the GM process.

Usage

```
GM(beta = NULL, sigma2_gm = 1)
```

Arguments

beta	A double value for the β of an GM process (see Note for details).
sigma2_gm	A double value for the variance, σ^2_{gm}, of a GM process (see Note for details).

Details

When supplying values for β and σ^2_{gm}, these parameters should be of a GM process and NOT of an AR1. That is, do not supply AR1 parameters such as ϕ, σ^2.

Internally, GM parameters are converted to AR1 using the 'freq' supplied when creating data objects (gts) or specifying a 'freq' parameter in simts or simts.imu.

The 'freq' of a data object takes precedence over the 'freq' set when modeling.

Value

An S3 object with called ts.model with the following structure:

process.desc Used in summary: "BETA","SIGMA2"

theta β, σ^2_{gm}

plength Number of parameters

print String containing simplified model

desc "GM"

obj.desc Depth of parameters e.g. list(1,1)

starting Guess starting values? TRUE or FALSE (e.g. specified value)

Note

We consider the following model:

$$X_t = e^{(-\beta)} X_{t-1} + \varepsilon_t$$

, where ε_t is iid from a zero mean normal distribution with variance $\sigma^2(1 - e^{2\beta})$.

Author(s)

James Balamuta

Examples

```
GM()
GM(beta=.32, sigma2_gm=1.3)
```

---

gmwm *Generalized Method of Wavelet Moments (GMWM)*

Description

Performs estimation of time series models by using the GMWM estimator.

Usage

```
gmwm(
  model,
  data,
  model.type = "imu",
  compute.v = "auto",
  robust = FALSE,
  eff = 0.6,
  alpha = 0.05,
  seed = 1337,
  G = NULL,
  K = 1,
  H = 100,
  freq = 1
)
```

Arguments

model	A ts.model object containing one of the allowed models.
data	A matrix or data.frame object with only column (e.g. $N \times 1$), a lts object, or a gts object.
model.type	A string containing the type of GMWM needed: "imu" or "ssm".

compute.v	A string indicating the type of covariance matrix solver. Valid values are: "fast", "bootstrap", "diag" (asymptotic diag), "full" (asymptotic full). By default, the program will fit a "fast" model.
robust	A boolean indicating whether to use the robust computation (TRUE) or not (FALSE).
eff	A double between 0 and 1 that indicates the efficiency.
alpha	A double between 0 and 1 that correspondings to the $\frac{\alpha}{2}$ value for the wavelet confidence intervals.
seed	An integer that controls the reproducibility of the auto model selection phase.
G	An integer to sample the space for IMU and SSM models to ensure optimal identitability.
K	An integer that controls how many times the bootstrapping procedure will be initiated.
H	An integer that indicates how many different samples the bootstrap will be collect.
freq	A double that indicates the sampling frequency. By default, this is set to 1 and only is important if GM() is in the model

Details

This function is under work. Some of the features are active. Others... Not so much.

The V matrix is calculated by: $diag\left[(Hi - Lo)^2\right]$.

The function is implemented in the following manner: 1. Calculate MODWT of data with levels = floor(log2(data)) 2. Apply the brick.wall of the MODWT (e.g. remove boundary values) 3. Compute the empirical wavelet variance (WV Empirical). 4. Obtain the V matrix by squaring the difference of the WV Empirical's Chi-squared confidence interval (hi - lo)^2 5. Optimize the values to obtain $\hat{\theta}$ 6. If FAST = TRUE, return these results. Else, continue.

Loop k = 1 to K Loop h = 1 to H 7. Simulate xt under $F_{\hat{\theta}}$ 8. Compute WV Empirical END 9. Calculate the covariance matrix 10. Optimize the values to obtain $\hat{\theta}$ END 11. Return optimized values.

The function estimates a variety of time series models. If type = "imu" or "ssm", then parameter vector should indicate the characters of the models that compose the latent or state-space model. The model options are:

- "AR1": a first order autoregressive process with parameters (ϕ, σ^2)
- "GM": a guass-markov process (β, σ^2_{gm})
- "ARMA": an autoregressive moving average process with parameters $(\phi_p, \theta_q, \sigma^2)$
- "DR": a drift with parameter ω
- "QN": a quantization noise process with parameter Q
- "RW": a random walk process with parameter σ^2
- "WN": a white noise process with parameter σ^2

If only an ARMA() term is supplied, then the function takes conditional least squares as starting values If robust = TRUE the function takes the robust estimate of the wavelet variance to be used in the GMWM estimation procedure.

Value

A `gmwm` object with the structure:

- estimate: Estimated Parameters Values from the GMWM Procedure
- init.guess: Initial Starting Values given to the Optimization Algorithm
- wv.empir: The data's empirical wavelet variance
- ci_low: Lower Confidence Interval
- ci_high: Upper Confidence Interval
- orgV: Original V matrix
- V: Updated V matrix (if bootstrapped)
- omega: The V matrix inversed
- obj.fun: Value of the objective function at Estimated Parameter Values
- theo: Summed Theoretical Wavelet Variance
- decomp.theo: Decomposed Theoretical Wavelet Variance by Process
- scales: Scales of the GMWM Object
- robust: Indicates if parameter estimation was done under robust or classical
- eff: Level of efficiency of robust estimation
- model.type: Models being guessed
- compute.v: Type of V matrix computation
- augmented: Indicates moments have been augmented
- alpha: Alpha level used to generate confidence intervals
- expect.diff: Mean of the First Difference of the Signal
- N: Length of the Signal
- G: Number of Guesses Performed
- H: Number of Bootstrap replications
- K: Number of V matrix bootstraps
- model: `ts.model` supplied to gmwm
- model.hat: A new value of `ts.model` object supplied to gmwm
- starting: Indicates whether the procedure used the initial guessing approach
- seed: Randomization seed used to generate the guessing values
- freq: Frequency of data

gmwm_imu *GMWM for (Robust) Inertial Measurement Units (IMUs)*

Description

Performs the GMWM estimation procedure using a parameter transform and sampling scheme specific to IMUs.

Usage

```
gmwm_imu(model, data, compute.v = "fast", robust = F, eff = 0.6, ...)
```

Arguments

model	A ts.model object containing one of the allowed models.
data	A matrix or data.frame object with only column (e.g. $N \times 1$), or a lts object, or a gts object.
compute.v	A string indicating the type of covariance matrix solver. "fast", "bootstrap", "asymp.diag", "asymp.comp", "fft"
robust	A boolean indicating whether to use the robust computation (TRUE) or not (FALSE).
eff	A double between 0 and 1 that indicates the efficiency.
...	Other arguments passed to the main gmwm function

Details

This version of the gmwm function has customized settings ideal for modeling with an IMU object. If you seek to model with an Gauss Markov, GM, object. Please note results depend on the freq specified in the data construction step within the imu. If you wish for results to be stable but lose the ability to interpret with respect to freq, then use AR1 terms.

Value

A gmwm object with the structure:

estimate	Estimated Parameters Values from the GMWM Procedure
init.guess	Initial Starting Values given to the Optimization Algorithm
wv.empir	The data's empirical wavelet variance
ci_low	Lower Confidence Interval
ci_high	Upper Confidence Interval
orgV	Original V matrix
V	Updated V matrix (if bootstrapped)
omega	The V matrix inversed
obj.fun	Value of the objective function at Estimated Parameter Values

theo	Summed Theoretical Wavelet Variance
decomp.theo	Decomposed Theoretical Wavelet Variance by Process
scales	Scales of the GMWM Object
robust	Indicates if parameter estimation was done under robust or classical
eff	Level of efficiency of robust estimation
model.type	Models being guessed
compute.v	Type of V matrix computation
augmented	Indicates moments have been augmented
alpha	Alpha level used to generate confidence intervals
expect.diff	Mean of the First Difference of the Signal
N	Length of the Signal
G	Number of Guesses Performed
H	Number of Bootstrap replications
K	Number of V matrix bootstraps
model	ts.model supplied to gmwm
model.hat	A new value of ts.model object supplied to gmwm
starting	Indicates whether the procedure used the initial guessing approach
seed	Randomization seed used to generate the guessing values
freq	Frequency of data

---

gts *Create a simts TS object using time series data*

Description

Takes a time series and turns it into a time series oriented object that can be used for summary and graphing functions in the simts package.

Usage

```
gts(
  data,
  start = 0,
  end = NULL,
  freq = 1,
  unit_ts = NULL,
  unit_time = NULL,
  name_ts = NULL,
  name_time = NULL,
  data_name = NULL,
  Time = NULL,
  time_format = NULL
)
```

Arguments

data	A one-column matrix, data.frame, or a numeric vector.
start	A numeric that provides the time of the first observation.
end	A numeric that provides the time of the last observation.
freq	A numeric that provides the rate/frequency at which the time series is sampled. The default value is 1.
unit_ts	A string that contains the unit of measure of the time series. The default value is NULL.
unit_time	A string that contains the unit of measure of the time. The default value is NULL.
name_ts	A string that provides an identifier for the time series data. Default value is NULL.
name_time	A string that provides an identifier for the time. Default value is NULL.
data_name	A string that contains the name of the time series data.
Time	A numeric or character vector containing the times of observations. Default value is NULL. See x object in as.Date function.
time_format	A string specifiying the format of 'Time'. If not provided, 'Time' is assumed to be all integers. Default value is NULL. See format argument in as.Date function.

Value

A gts object

Author(s)

James Balamuta and Wenchao Yang

Examples

```
m = data.frame(rnorm(50))
x = gts(m, unit_time = 'sec', name_ts = 'example')
plot(x)

x = gen_gts(50, WN(sigma2 = 1))
x = gts(x, freq = 100, unit_time = 'sec')
plot(x)
```

hydro *Mean Monthly Precipitation, from 1907 to 1972*

Description

Hydrology data that indicates a robust approach may be preferred to a classical approach when estimating time series.

Usage

```
hydro
```

Format

A time series object with frequency 12 starting at 1907 and going to 1972 for a total of 781 observations.

Source

datamarket, mean-monthly-precipitation-1907-1972

imu *Create an IMU Object*

Description

Builds an IMU object that provides the program with gyroscope, accelerometer, and axis information per column in the dataset.

Usage

```
imu(
  data,
  gyros = NULL,
  accels = NULL,
  axis = NULL,
  freq = NULL,
  unit = NULL,
  name = NULL
)
```

Arguments

data	A vector which contains data, or a matrix or data.frame which contains the data in each column.
gyros	A vector that contains the index of columns where gyroscope data (such as Gyro. X, Gyro. Y and Gyro. Z) is placed.
accels	A vector that contains the index of columns where accelerometer data (such as Accel. X, Accel. Y and Accel. Z) is placed.
axis	A vector that indicates the axises, such as 'X', 'Y', 'Z'. Please supply the axises for gyroscope data before that for accelerometer data, if gyroscope data exists.
freq	An integer that provides the frequency for the data.
unit	A string that contains the unit expression of the frequency. Default value is NULL.
name	A string that provides an identifier to the data. Default value is NULL.

Details

data can be a numeric vector, matrix or data frame.

gyros and accels cannot be NULL at the same time, but it will be fine if one of them is NULL. In the new implementation, the length of gyros and accels do not need to be equal.

In axis, duplicate elements are not alowed for each sensor. In the new implementation, please specify the axis for each column of data. axis will be automatically generated if there are less than or equal to 3 axises for each sensor.

Value

An imu object in the following attributes:

sensor A vector that indicates whether data contains gyroscope sensor, accelerometer sensor, or both.

num.sensor A vector that indicates how many columns of data are for gyroscope sensor and accelerometer sensor.

axis Axis value such as 'X', 'Y', 'Z'.

freq Observations per second.

unit String representation of the unit.

name Name of the dataset.

Author(s)

James Balamuta and Wenchao Yang

Examples

```
## Not run:
if(!require("imudata")){
   install_imudata()
   library("imudata")
}

data(imu6)

# Example 1 - Only gyros
test1 = imu(imu6, gyros = 1:3, axis = c('X', 'Y', 'Z'), freq = 100)
df1 = wvar.imu(test1)
plot(df1)

# Example 2 - One gyro and one accelerometer
test2 = imu(imu6, gyros = 1, accels = 4, freq = 100)
df2 = wvar.imu(test2)
plot(df2)

# Example 3 - 3 gyros and 3 accelerometers
test3 = imu(imu6, gyros = 1:3, accels = 4:6, axis =
                       c('X', 'Y', 'Z', 'X', 'Y', 'Z'), freq = 100)
df3 = wvar.imu(test3)
plot(df3)

# Example 4 - Custom axis
test4 = imu(imu6, gyros = 1:2, accels = 4:6, axis =
                       c('X', 'Y', 'X', 'Y', 'Z'), freq = 100)
df4 = wvar.imu(test4)
plot(df4)

## End(Not run)
```

`imu_time` *Pulls the IMU time from the IMU object*

Description

Helper function for the IMU object to access `rownames()` with a numeric conversion.

Usage

```
imu_time(x)
```

Arguments

`x`	A `imu` object

Value

A `vector` with numeric information.

`is.gts` *Is simts Object*

Description

Is the object a `gts`, `imu`, or `lts` object?

Usage

```
is.gts(x)

is.imu(x)

is.lts(x)

is.ts.model(x)
```

Arguments

`x`	A `gts`, `imu`, `lts` object.

Details

Uses `inherits` over `is` for speed.

Value

A `logical` value that indicates whether the object is of that class (TRUE) or not (FALSE).

Author(s)

James Balamuta

`lts` *Generate a Latent Time Series Object from Data*

Description

Create a `lts` object based on a supplied matrix or data frame. The latent time series is obtained by the sum of underlying time series.

Usage

```
lts(
  data,
  start = 0,
  end = NULL,
  freq = 1,
  unit_ts = NULL,
  unit_time = NULL,
  name_ts = NULL,
  name_time = NULL,
  process = NULL
)
```

Arguments

`data`	A multiple-column `matrix` or `data.frame`. It must contain at least 3 columns of which the last represents the latent time series obtained through the sum of the previous columns.
`start`	A `numeric` that provides the time of the first observation.
`end`	A `numeric` that provides the time of the last observation.
`freq`	A `numeric` that provides the rate/frequency at which the time series is sampled. The default value is 1.
`unit_ts`	A `string` that contains the unit of measure of the time series. The default value is `NULL`.
`unit_time`	A `string` that contains the unit of measure of the time. The default value is `NULL`.
`name_ts`	A `string` that provides an identifier for the time series data. Default value is `NULL`.
`name_time`	A `string` that provides an identifier for the time. Default value is `NULL`.
`process`	A `vector` that contains model names of each column in the `data` object where the last name is the sum of the previous names.

Value

A `lts` object

Author(s)

Wenchao Yang and Justin Lee

Examples

```
model1 = AR1(phi = .99, sigma2 = 1)
model2 = WN(sigma2 = 1)
col1 = gen_gts(1000, model1)
col2 = gen_gts(1000, model2)
testMat = cbind(col1, col2, col1+col2)
testLts = lts(testMat, unit_time = 'sec', process = c('AR1', 'WN', 'AR1+WN'))
plot(testLts)
```

M *Definition of a Mean deterministic vector returned by the matrix by vector product of matrix X and vector β*

Description

Definition of a Mean deterministic vector returned by the matrix by vector product of matrix X and vector β

Usage

```
M(X, beta)
```

Arguments

X	A Matrix with dimension n*p.
beta	A vector with dimension p*1

Value

An S3 object containing the specified ts.model with the following structure:

process.desc Used in summary: "X","BETA"

theta Matrix X, vector beta

plength Number of parameters

print String containing simplified model

desc "M"

obj.desc Depth of Parameters e.g. list(1,1)

starting Find starting values? TRUE or FALSE (e.g. specified value)

Author(s)

Lionel Voirol, Davide Cucci

Examples

```
X = matrix(rnorm(15*5), nrow = 15, ncol = 5)
beta=seq(5)
M(X = X, beta = beta)
```

MA *Create an Moving Average Q [MA(Q)] Process*

Description

Sets up the necessary backend for the MA(Q) process.

Usage

```
MA(theta = NULL, sigma2 = 1)
```

Arguments

theta	A double value for the parameter θ (see Note for details).
sigma2	A double value for the variance parameter σ^2 (see Note for details).

Value

An S3 object with called ts.model with the following structure:

process.desc Used in summary: "MA-1","MA-2", ..., "MA-Q", "SIGMA2"

theta θ_1, θ_2, ..., θ_q, σ^2

plength Number of parameters

desc "MA"

print String containing simplified model

obj.desc Depth of parameters e.g. list(q,1)

starting Guess starting values? TRUE or FALSE (e.g. specified value)

Note

We consider the following model:

$$X_t = \sum_{j=1}^{q} \theta_j \varepsilon_{t-1} + \varepsilon_t$$

, where ε_t is iid from a zero mean normal distribution with variance σ^2.

Author(s)

James Balamuta

Examples

```
MA(1) # One theta
MA(2) # Two thetas!

MA(theta=.32, sigma=1.3) # 1 theta with a specific value.
MA(theta=c(.3,.5), sigma=.3) # 2 thetas with specific values.
```

MA1 *Definition of an Moving Average Process of Order 1*

Description

Definition of an Moving Average Process of Order 1

Usage

```
MA1(theta = NULL, sigma2 = 1)
```

Arguments

theta	A double value for the parameter θ (see Note for details).
sigma2	A double value for the variance parameter σ^2 (see Note for details).

Value

An S3 object with called ts.model with the following structure:

process.desc Used in summary: "MA1","SIGMA2"

theta θ, σ^2

plength Number of parameters

print String containing simplified model

desc "MA1"

obj.desc Depth of parameters e.g. list(1,1)

starting Guess starting values? TRUE or FALSE (e.g. specified value)

Note

We consider the following model:

$$X_t = \theta\varepsilon_{t-1} + \varepsilon_t$$

, where ε_t is iid from a zero mean normal distribution with variance σ^2.

Author(s)

James Balamuta

Examples

```
MA1()
MA1(theta = .32, sigma2 = 1.3)
```

`ma1_to_wv` *Moving Average Order 1 (MA(1)) to WV*

Description

This function computes the WV (haar) of a Moving Average order 1 (MA1) process.

Usage

```
ma1_to_wv(theta, sigma2, tau)
```

Arguments

`theta`	A `double` corresponding to the moving average term.
`sigma2`	A `double` the variance of the process.
`tau`	A `vec` containing the scales e.g. 2^τ

Details

This function is significantly faster than its generalized counter part `arma_to_wv`.

Value

A `vec` containing the wavelet variance of the MA(1) process.

Process Haar Wavelet Variance Formula

The Moving Average Order 1 (MA(1)) process has a Haar Wavelet Variance given by:

$$\nu_j^2\left(\theta, \sigma^2\right) = \frac{\left((\theta+1)^2 \tau_j - 6\theta\right)\sigma^2}{\tau_j^2}$$

make_frame *Default utility function for various plots titles*

Description

Adds title, grid, and required x- and y-axes.

Usage

```
make_frame(
  x_range,
  y_range,
  xlab,
  ylab,
  main = "",
  mar = c(5.1, 5.1, 1, 2.1),
  add_axis_x = TRUE,
  add_axis_y = TRUE,
  col_box = "black",
  col_grid = "grey95",
  col_band = "grey95",
  col_title = "black",
  add_band = TRUE,
  title_band_width = 0.09,
  grid_lty = 1
)
```

Arguments

x_range	A numeric providing the range of values for the x-axis.
y_range	A numeric providing the range of values for the y-axis.
xlab	A string that gives a title for the x-axis.
ylab	A string that gives a title for the y-axis.
main	A string that gives an overall title for the plot. Default is an empty string.
mar	A vector indicating overall margin values for the plot.
add_axis_x	A boolean indicating whether a x-axis should be added.
add_axis_y	A boolean indicating whether a y-axis should be added.
col_box	A string indicating the color for the title box.
col_grid	A string indicating the color of the grid for the plot.
col_band	A string indicating the color of the band.
col_title	A string indicating the color of the plot title.
add_band	A boolean indicating whether there should be a band.
title_band_width	A double providing the value of the band width. Default is 0.09.
grid_lty	A integer indicating the line type of the grid lines.

Value

Added title, grid, and axes.

Author(s)

Stephane Guerrier and Justin Lee

Examples

```
make_frame(x_range = c(0, 1), y_range = c(0, 1), xlab = "my xlab",
           ylab = "my ylab", main = "my title")

make_frame(x_range = c(0, 1), y_range = c(0, 1), xlab = "my xlab",
           ylab = "my ylab", add_band = FALSE)

make_frame(x_range = c(0, 1), y_range = c(0, 1), xlab = "my xlab",
           ylab = "my ylab", main = "my title", col_band = "blue3",
           col_title = "white", col_grid = "lightblue", grid_lty = 3)

make_frame(x_range = c(0, 1), y_range = c(0, 1), xlab = "my xlab",
           ylab = "my ylab", main = "my title", col_band = "blue3",
           col_title = "white", col_grid = "lightblue", grid_lty = 3,
           title_band_width = 0.18)
```

MAPE *Median Absolute Prediction Error*

Description

This function calculates Median Absolute Prediction Error (MAPE), which assesses the prediction performance with respect to point forecasts of a given model. It is calculated based on one-step ahead prediction and reforecasting.

Usage

```
MAPE(model, Xt, start = 0.8, plot = TRUE)
```

Arguments

model	A time series model.
Xt	A vector of time series data.
start	A numeric indicating the starting proportion of the data that is used for prediction.
plot	A boolean indicating whether a model accuracy plot based on MAPE is returned or not.

Value

The MAPE calculated based on one-step ahead prediction and reforecasting is returned along with its standard deviation.

Author(s)

Stéphane Guerrier and Yuming Zhang

MAT *Definition of a Matérn Process*

Description

Definition of a Matérn Process

Usage

```
MAT(sigma2 = 1, lambda = 0.35, alpha = 0.9)
```

Arguments

sigma2	A double.
lambda	A double.
alpha	A double.

Value

An S3 object containing the specified ts.model with the following structure:

process.desc Used in summary: "SIGMA2","LAMBDA""ALPHA"

theta Parameter vector including σ^2, λ,α

plength Number of parameters

print String containing simplified model

desc "MAT"

obj.desc Depth of Parameters e.g. list(1,1,1)

starting Find starting values? TRUE or FALSE (e.g. specified value)

Author(s)

Lionel Voirol, Davide Cucci

Examples

```
MAT()
MAT(sigma2 = 1, lambda = 0.35, alpha = 0.9)
```

np_boot_sd_med *Bootstrap standard error for the median*

Description

Non-parametric bootstrap to obtain the standard of the median of iid data.

Usage

```
np_boot_sd_med(x, B = 5000)
```

Arguments

x	A vector of data.
B	A numeric indicating the number of simulations.

Value

Bootstrap standard error for the median

plot.gmwm *Plot the GMWM with the Wavelet Variance*

Description

Displays a plot of the Wavelet Variance (WV) with the CI values and the WV implied by the estimated parameters.

Usage

```
## S3 method for class 'gmwm'
plot(
  x,
  decomp = FALSE,
  units = NULL,
  xlab = NULL,
  ylab = NULL,
  main = NULL,
  col_wv = NULL,
  col_ci = NULL,
  nb_ticks_x = NULL,
  nb_ticks_y = NULL,
  legend_position = NULL,
  ci_wv = NULL,
  point_cex = NULL,
  point_pch = NULL,
  ...
)
```

Arguments

x	A gmwm object.
decomp	A boolean that determines whether the contributions of each individual model are plotted.
units	A string that specifies the units of time plotted on the x axis.
xlab	A string that gives a title for the x axis.
ylab	A string that gives a title for the y axis.
main	A string that gives an overall title for the plot.
col_wv	A string that specifies the color of the wavelet variance line.
col_ci	A string that specifies the color of the shaded area covered by the confidence intervals.
nb_ticks_x	An integer that specifies the maximum number of ticks for the x-axis.
nb_ticks_y	An integer that specifies the maximum number of ticks for the y-axis.
legend_position	A string that specifies the position of the legend (use legend_position = NA to remove legend).
ci_wv	A boolean that determines whether to plot the confidence interval shaded area.
point_cex	A double that specifies the size of each symbol to be plotted.
point_pch	A double that specifies the symbol type to be plotted.
...	Additional arguments affecting the plot.

Value

Plot of WV and relative confidence intervals for each scale.

Author(s)

Stephane Guerrier and Yuming Zhang

---

plot.PACF *Plot Partial Auto-Covariance and Correlation Functions*

Description

The function plots the output of the theo_pacf and auto_corr functions (partial autocovariance or autocorrelation functions).

Usage

```
## S3 method for class 'PACF'
plot(
  x,
  xlab = NULL,
  ylab = NULL,
  show.ci = TRUE,
  alpha = NULL,
  col_ci = NULL,
  transparency = NULL,
  main = NULL,
  parValue = NULL,
  ...
)
```

Arguments

x	A "PACF" object output from theo_pacf or auto_corr.
xlab	A string indicating the label of the x axis: the default name is 'Lags'.
ylab	A string indicating the label of the y axis: the default name is 'PACF'.
show.ci	A bool indicating whether to show the confidence region. Defaults to TRUE.
alpha	A double indicating the level of significance for the confidence interval. By default alpha = 0.05 which gives a 1 - alpha = 0.95 confidence interval.
col_ci	A string that specifies the color of the region covered by the confidence intervals (confidence region).
transparency	A double between 0 and 1 indicating the transparency level of the color defined in col_ci. Defaults to 0.25.
main	A string indicating the title of the plot. Default name is "Variable name PACF plot'.
parValue	A vector defining the margins for the plot.
...	Additional parameters

Author(s)

Yunxiang Zhang and Yuming Zhang

Examples

```
# Plot the Partial Autocorrelation
m = auto_corr(datasets::AirPassengers, pacf = TRUE)
plot(m)

# More customized CI
plot(m, xlab = "my xlab", ylab = "my ylab", show.ci = TRUE,
alpha = NULL, col_ci = "grey", transparency = 0.5, main = "my main")
```

plot.simtsACF *Plot Auto-Covariance and Correlation Functions*

Description

The function plots the output of the theo_acf and auto_corr functions (autocovariance or autocorrelation functions).

Usage

```
## S3 method for class 'simtsACF'
plot(
  x,
  xlab = NULL,
  ylab = NULL,
  show.ci = TRUE,
  alpha = NULL,
  col_ci = NULL,
  transparency = NULL,
  main = NULL,
  parValue = NULL,
  ...
)
```

Arguments

x	An "ACF" object output from theo_acf and auto_corr.
xlab	A string indicating the label of the x axis: the default name is 'Lags'.
ylab	A string indicating the label of the y axis: the default name is 'ACF'.
show.ci	A bool indicating whether to show the confidence region. Defaults to TRUE.
alpha	A double indicating the level of significance for the confidence interval. By default alpha = 0.05 which gives a 1 - alpha = 0.95 confidence interval.
col_ci	A string that specifies the color of the region covered by the confidence intervals (confidence region).
transparency	A double between 0 and 1 indicating the transparency level of the color defined in col_ci. Defaults to 0.25.
main	A string indicating the title of the plot. Default name is "Variable name ACF plot'.
parValue	A vector defining the margins for the plot.
...	Additional parameters

Author(s)

Yunxiang Zhang, Stéphane Guerrier and Yuming Zhang

Examples

```
# Calculate the Autocorrelation
m = auto_corr(datasets::AirPassengers)

# Plot with 95% CI
plot(m)

# Plot with 90% CI
plot(m, alpha = 0.1)

# Plot without 95% CI
plot(m, show.ci = FALSE)

# More customized CI
plot(m, xlab = "my xlab", ylab = "my ylab", show.ci = TRUE,
alpha = NULL, col_ci = "grey", transparency = 0.5, main = "my main")
```

`plot_pred` *Plot Time Series Forecast Function*

Description

This function plots the time series output from a forecast method with approximate 68

Usage

```
plot_pred(
  x,
  model,
  n.ahead,
  level = NULL,
  xlab = NULL,
  ylab = NULL,
  main = NULL,
  ...
)
```

Arguments

`x`	A `gts` object
`model`	A `ts` model
`n.ahead`	An `integer` indicating number of units of time ahead for which to make forecasts
`level`	A `double` or `vector` indicating confidence level of prediction interval. By default, it uses the levels of 0.50 and 0.95.
`xlab`	A `string` for the title of x axis

ylab	A string for the title of y axis
main	A string for the over all title of the plot
...	Additional parameters

Author(s)

Yuming Zhang

PLP *Definition of a Power Law Process*

Description

Definition of a Power Law Process

Usage

```
PLP(sigma2 = 1, d = 0.4)
```

Arguments

sigma2	A double.
d	A double.

Value

An S3 object containing the specified ts.model with the following structure:

process.desc Used in summary: "SIGMA2","d"

theta Parameter vector including σ^2, d

plength Number of parameters

print String containing simplified model

desc "PLP"

obj.desc Depth of Parameters e.g. list(1,1)

starting Find starting values? TRUE or FALSE (e.g. specified value)

Author(s)

Lionel Voirol, Davide Cucci

Examples

```
PLP()
PLP(sigma2 = 1, d = 0.4)
```

`predict.fitsimts` *Time Series Prediction*

Description

This function plots the time series forecast.

Usage

```
## S3 method for class 'fitsimts'
predict(
  object,
  n.ahead = 10,
  show_last = 100,
  level = NULL,
  xlab = NULL,
  ylab = NULL,
  main = NULL,
  plot = TRUE,
  ...
)
```

Arguments

`object`	A `fitsimts` object obtained from `estimate` function.
`n.ahead`	An `integer` indicating number of units of time ahead for which to make forecasts.
`show_last`	A `integer` indicating the number of last observations to show in the forecast plot.
`level`	A `double` or `vector` indicating confidence level of prediction interval. By default, it uses the levels of 0.50 and 0.95.
`xlab`	A `string` for the title of x axis.
`ylab`	A `string` for the title of y axis.
`main`	A `string` for the over all title of the plot.
`plot`	A `logical` value. logical. If `TRUE`(the default) the predictions are plotted.
`...`	Additional arguments.

Author(s)

Stéphane Guerrier and Yuming Zhang

Examples

```
Xt = gen_gts(300, AR(phi = c(0, 0, 0.8), sigma2 = 1))
model = estimate(AR(3), Xt)
predict(model)
predict(model, level = 0.95)

x = gts(as.vector(lynx), start = 1821, end = 1934, freq = 1,
unit_ts = bquote(paste(10^8," ",m^3)), name_ts = "Numbers",
unit_time = "year", data_name = "Annual Numbers of Lynx Trappings")
model = estimate(AR(1), x)
predict(model, n.ahead = 20)
predict(model, n.ahead = 20, level = 0.95)
predict(model, n.ahead = 20, level = c(0.50, 0.80, 0.95))
```

---

predict.gmwm *Predict future points in the time series using the solution of the Generalized Method of Wavelet Moments*

Description

Creates a prediction using the estimated values of GMWM through the ARIMA function within R.

Usage

```
## S3 method for class 'gmwm'
predict(object, data.in.gmwm, n.ahead = 1, ...)
```

Arguments

object	A gmwm object
data.in.gmwm	The data SAME EXACT DATA used in the GMWM estimation
n.ahead	Number of observations to forecast
...	Additional parameters passed to ARIMA Predict

Value

A predict.gmwm object with:

pred	Predictions
se	Standard Errors
resid	Residuals from ARIMA ML Fit

QN *Create an Quantisation Noise (QN) Process*

Description

Sets up the necessary backend for the QN process.

Usage

```
QN(q2 = NULL)
```

Arguments

q2	A double value for the Q^2 of a QN process.

Value

An S3 object with called ts.model with the following structure:

process.desc Used in summary: "QN"

theta Q^2

plength Number of parameters

print String containing simplified model

desc y desc replicated x times

obj.desc Depth of parameters e.g. list(1)

starting Guess starting values? TRUE or FALSE (e.g. specified value)

Author(s)

James Balamuta

Examples

```
QN()
QN(q2=3.4)
```

qn_to_wv *Quantisation Noise (QN) to WV*

Description

This function compute the Haar WV of a Quantisation Noise (QN) process

Usage

```
qn_to_wv(q2, tau)
```

Arguments

q2	A double corresponding to variance of drift
tau	A vec containing the scales e.g. 2^τ

Value

A vec containing the wavelet variance of the QN.

Process Haar Wavelet Variance Formula

The Quantization Noise (QN) process has a Haar Wavelet Variance given by:

$$\nu_j^2\left(Q^2\right) = \frac{6Q^2}{\tau_j^2}$$

read.imu *Read an IMU Binary File into R*

Description

Process binary files within the

Usage

```
read.imu(file, type, unit = NULL, name = NULL)
```

Arguments

file	A string containing file names or paths.
type	A string that contains a supported IMU type given below.
unit	A string that contains the unit expression of the frequency. Default value is NULL.
name	A string that provides an identifier to the data. Default value is NULL.

Details

Currently supports the following IMUs:

- IMAR
- LN200
- LN200IG
- IXSEA
- NAVCHIP_INT
- NAVCHIP_FLT

Value

An `imu` object that contains 3 gyroscopes and 3 accelerometers in that order.

Author(s)

James Balamuta We hope to soon be able to support delimited files.

References

Thanks goes to Philipp Clausen of Labo TOPO, EPFL, Switzerland, topo.epfl.ch, Tel:+41(0)21 693 27 55 for providing a matlab function that reads in IMUs. This function is a heavily modified port of MATLAB code into Armadillo/C++.

Examples

```
## Not run:
# Relative
setwd("F:/")

a = read.imu(file = "Documents/James/short_test_data.imu", type = "IXSEA")

# Fixed path
b = read.imu(file = "F:/Desktop/short_test_data.imu", type = "IXSEA")

## End(Not run)
```

`resid_plot` *Plot the Distribution of (Standardized) Residuals*

Description

This function plots a histogram (with kernel density function and normal distribution) of the standardized residuals or a basic plot the (standardized) residuals, or both.

Usage

```
resid_plot(res, std = FALSE, type = "hist", ...)
```

Arguments

res	A vector of residuals.
std	A boolean indicating whether the residuals plot is for standardized residuals or original residuals.
type	A string indicating either: "hist" (standardized residual histogram with superimposed kernel density estimator and normal distribution), "resid" (standard residual plot), or "both"
...	Additional parameters

Author(s)

Yuming Zhang

---

rgmwm *GMWM for Robust/Classical Comparison*

Description

Creates a rgmwm object to compare the results generated by robust/classical method.

Usage

```
rgmwm(model, data, eff = c(0.9, 0.8, 0.6), ...)
```

Arguments

model	A ts.model object containing one of the allowed models.
data	A matrix or data.frame object with only one column (e.g. $N \times 1$), or a lts object, or a gts object.
eff	A double vector between 0 and 1 that indicates the efficiency.
...	Other arguments passed to the main gmwm function.

Details

By default, the rgmwm function will fit a classical gmwm object. From there, the user has the ability to specify any eff that is less than or equal to 0.99.

Value

A rgmwm object

rtruncated_normal *Truncated Normal Distribution Sampling Algorithm*

Description

Enables sampling from a truncated normal

Usage

```
rtruncated_normal(n, mu, sigma, a, b)
```

Arguments

n	An unsigned int indicating the number of observations to generate.
mu	A double indicating the mean of the normal.
sigma	A double indicating the standard deviation of the normal.
a	A double that is the lower bound of the truncated normal.
b	A double that is the upper bound of the truncated normal.

RW *Create an Random Walk (RW) Process*

Description

Sets up the necessary backend for the RW process.

Usage

```
RW(gamma2 = NULL)
```

Arguments

gamma2	A double value for the variance γ^2

Value

An S3 object with called ts.model with the following structure:

process.desc Used in summary: "RW"

theta σ

plength Number of parameters

print String containing simplified model

desc y desc replicated x times

obj.desc Depth of parameters e.g. list(1)

starting Guess starting values? TRUE or FALSE (e.g. specified value)

Note

We consider the following model:

$$Y_t = \sum_{t=0}^{T} \gamma_0 * Z_t$$

where Z_t is iid and follows a standard normal distribution.

Author(s)

James Balamuta

Examples

```
RW()
RW(gamma2=3.4)
```

---

rw_to_wv *Random Walk to WV*

Description

This function compute the WV (haar) of a Random Walk process

Usage

```
rw_to_wv(gamma2, tau)
```

Arguments

gamma2	A double corresponding to variance of RW
tau	A vec containing the scales e.g. 2^τ

Value

A vec containing the wavelet variance of the random walk.

Process Haar Wavelet Variance Formula

The Random Walk (RW) process has a Haar Wavelet Variance given by:

$$\nu_j^2\left(\gamma^2\right) = \frac{\left(\tau_j^2 + 2\right)\gamma^2}{12\tau_j}$$

RW2dimension *Function to Compute Direction Random Walk Moves*

Description

The RW2dimension function computes direction random walk moves.

Usage

```
RW2dimension(steps = 100, probs = c(0.25, 0.5, 0.75))
```

Arguments

steps	An integer that counts the number of steps of the random walk.
probs	A vector of double that specifies the probabilities to choose each direction.

Author(s)

Stéphane Guerrier

Examples

```
RW2dimension(steps = 50, probs = c(0.2, 0.5, 0.6))
```

SARIMA *Create a Seasonal Autoregressive Integrated Moving Average (SARIMA) Process*

Description

Sets up the necessary backend for the SARIMA process.

Usage

```
SARIMA(ar = 1, i = 0, ma = 1, sar = 1, si = 0, sma = 1, s = 12, sigma2 = 1)
```

Arguments

ar	A vector or integer containing either the coefficients for ϕ's or the process number p for the Autoregressive (AR) term.
i	An integer containing the number of differences to be done.
ma	A vector or integer containing either the coefficients for θ's or the process number q for the Moving Average (MA) term.
sar	A vector or integer containing either the coefficients for Φ's or the process number P for the Seasonal Autoregressive (SAR) term.

si	An integer containing the number of seasonal differences to be done.
sma	A vector or integer containing either the coefficients for Θ's or the process number Q for the Seasonal Moving Average (SMA) term.
s	An integer containing the seasonality.
sigma2	A double value for the standard deviation, σ, of the SARMA process.

Details

A variance is required since the model generation statements utilize randomization functions expecting a variance instead of a standard deviation unlike R.

Value

An S3 object with called ts.model with the following structure:

process.desc $AR * p$, $MA * q$, $SAR * P$, $SMA * Q$

theta σ

plength Number of parameters

desc Type of model

desc.simple Type of model (after simplification)

print String containing simplified model

obj.desc y desc replicated x times

obj Depth of Parameters e.g. list(c(length(ar), length(ma), length(sar), length(sma), 1, i, si))

starting Guess Starting values? TRUE or FALSE (e.g. specified value)

Author(s)

James Balamuta

Examples

```
# Create an SARIMA(1,1,2)x(1,0,1) process
SARIMA(ar = 1, i = 1, ma = 2, sar = 1, si = 0, sma =1)

# Creates an SARMA(1,0,1)x(1,1,1) process with predefined coefficients.
SARIMA(ar=0.23, i = 0, ma=0.4, sar = .3,  sma = .3)
```

SARMA *Create a Seasonal Autoregressive Moving Average (SARMA) Process*

Description

Sets up the necessary backend for the SARMA process.

Usage

```
SARMA(ar = 1, ma = 1, sar = 1, sma = 1, s = 12, sigma2 = 1)
```

Arguments

`ar`	A `vector` or `integer` containing either the coefficients for ϕ's or the process number p for the Autoregressive (AR) term.
`ma`	A `vector` or `integer` containing either the coefficients for θ's or the process number q for the Moving Average (MA) term.
`sar`	A `vector` or `integer` containing either the coefficients for Φ's or the process number P for the Seasonal Autoregressive (SAR) term.
`sma`	A `vector` or `integer` containing either the coefficients for Θ's or the process number Q for the Seasonal Moving Average (SMA) term.
`s`	A `integer` indicating the seasonal value of the data.
`sigma2`	A `double` value for the standard deviation, σ, of the SARMA process.

Details

A variance is required since the model generation statements utilize randomization functions expecting a variance instead of a standard deviation unlike R.

Value

An S3 object with called ts.model with the following structure:

process.desc $AR * p$, $MA * q$, $SAR * P$, $SMA * Q$

theta σ

plength Number of Parameters

print String containing simplified model

obj.desc y desc replicated x times

obj Depth of Parameters e.g. list(c(length(ar), length(ma), length(sar), length(sma), 1))

starting Guess Starting values? TRUE or FALSE (e.g. specified value)

Author(s)

James Balamuta

Examples

```
# Create an SARMA(1,2)x(1,1) process
SARMA(ar = 1, ma = 2,sar = 1, sma =1)

# Creates an SARMA(1,1)x(1,1) process with predefined coefficients.
SARMA(ar=0.23, ma=0.4, sar = .3, sma = .3)
```

---

savingrt *Personal Saving Rate*

Description

Personal saving as a percentage of disposable personal income (DPI), frequently referred to as "the personal saving rate," is calculated as the ratio of personal saving to DPI.

Usage

```
savingrt
```

Format

A gts time series object with frequency 12 starting at 1959 and going to 2016 for a total of 691 observations.

Source

https://fred.stlouisfed.org/series/PSAVERT

---

select *Time Series Model Selection*

Description

This function performs model fitting and calculates the model selection criteria to be plotted.

Usage

```
select(model, Xt, include.mean = TRUE, criterion = "aic", plot = TRUE)
```

Arguments

model	A time series model (only ARIMA are currently supported).
Xt	A vector of time series data.
include.mean	A boolean indicating whether to fit ARIMA with the mean or not.
criterion	A string indicating which model selection criterion should be used (possible values: "aic" (default), "bic", "hq").
plot	A boolean indicating whether a model selection plot is returned or not.

Author(s)

Stéphane Guerrier and Yuming Zhang

Examples

```
set.seed(763)
Xt = gen_gts(100, AR(phi = c(0.2, -0.5, 0.4), sigma2 = 1))
select(AR(5), Xt, include.mean = FALSE)

Xt = gen_gts(100, MA(theta = c(0.2, -0.5, 0.4), sigma2 = 1))
select(MA(5), Xt, include.mean = FALSE)

Xt = gen_gts(500, ARMA(ar = 0.5, ma = c(0.5, -0.5, 0.4), sigma2 = 1))
select(ARMA(5,3), Xt, criterion = "hq", include.mean = FALSE)
```

---

select_arima *Run Model Selection Criteria on ARIMA Models*

Description

This function performs model fitting and calculates the model selection criteria to be plotted or used in `best_model` function.

Usage

```
select_arima(
  xt,
  p.min = 0L,
  p.max = 3L,
  d = 0L,
  q.min = 0L,
  q.max = 3L,
  include.mean = TRUE,
  plot = TRUE
)

select_arma(
  xt,
  p.min = 0L,
  p.max = 3L,
  q.min = 0L,
  q.max = 3L,
  include.mean = TRUE,
  plot = TRUE
)

select_ar(xt, p.min = 0L, p.max = 3L, include.mean = TRUE, plot = TRUE)
```

```
select_ma(xt, q.min = 0L, q.max = 3L, include.mean = TRUE, plot = TRUE)
```

Arguments

xt	A vector of univariate time series.
p.min	An integer indicating the lowest order of AR(p) process to search.
p.max	An integer indicating the highest order of AR(p) process to search.
d	An integer indicating the differencing order for the data.
q.min	An integer indicating the lowest order of MA(q) process to search.
q.max	An integer indicating the highest order of MA(q) process to search.
include.mean	A bool indicating whether to fit ARIMA with the mean or not.
plot	A logical. If TRUE (the default) a plot should be produced.

Examples

```
xt = gen_arima(N=100, ar=0.3, d=1, ma=0.3)
x = select_arima(xt, d=1L)

xt = gen_ma1(100, 0.3, 1)
x = select_ma(xt, q.min=2L, q.max=5L)
best_model(x)

xt = gen_arma(10, c(.4,.5), c(.1), 1, 0)
x = select_arma(xt, p.min = 1L, p.max = 4L,
                q.min = 1L, q.max = 3L)
```

---

simple_diag_plot *Basic Diagnostic Plot of Residuals*

Description

This function will plot four diagnostic plots to assess how well the model fits the data. These plots are: (1) residuals plot, (2) histogram of (standardized) residuals, (3) normal Q-Q plot of residuals and (4) residuals vs fitted values plot.

Usage

```
simple_diag_plot(Xt, model, std = FALSE)
```

Arguments

Xt	The original time series data.
model	The arima model fit to the data.
std	A boolean indicating whether we use standardized residuals for the (1) residuals plot and the (2) histogram of (standardized) residuals.

Author(s)

Yuming Zhang

`simplified_print_SARIMA`

Simplify and print SARIMA model

Description

Simplify and print SARIMA model

Usage

```
simplified_print_SARIMA(p, i, q, P, si, Q, s)
```

Arguments

`p`	An `integer` denoting the length of `ar`.
`i`	An `integer` containing the number of differences to be done.
`q`	An `integer` denoting the length of `ma`.
`P`	An `integer` denoting the length of `sma`.
`si`	An `integer` containing the number of seasonal differences to be done.
`Q`	An `integer` denoting the length of `sar`.
`s`	An `integer` indicating the seasonal value of the data.

Value

An S3 object with the following structure:

print String containing simplified model

simplified Type of model (after simplification)

Author(s)

Stephane Guerrier

SIN *Definition of a Sinusoidal (SIN) Process*

Description

Definition of a Sinusoidal (SIN) Process

Usage

```
SIN(alpha2 = 9e-04, beta = 0.06, U = NULL)
```

Arguments

alpha2	A double value for the squared amplitude parameter α^2 (see Note for details).
beta	A double value for the angular frequency parameter β (see Note for details).
U	A double value for the phase parameter U (see Note for details).

Value

An S3 object containing the specified ts.model with the following structure:

process.desc Used in summary: "ALPHA2","BETA"

theta Parameter vector including α^2, β

plength Number of parameters

print String containing simplified model

desc "SIN"

obj.desc Depth of Parameters e.g. list(1,1)

starting Find starting values? TRUE or FALSE (e.g. specified value)

Note

We consider the following sinusoidal process :

$$X_t = \alpha \sin(\beta t + U)$$

, where $U \sim \mathcal{U}(0, 2\pi)$ and $\beta \in (0, \frac{\pi}{2})$

Author(s)

Lionel Voirol

Examples

```
SIN()
SIN(alpha2 = .5, beta = .05)
```

summary.fitsimts *Summary of fitsimts object*

Description

Displays summary information about fitsimts object

Usage

```
## S3 method for class 'fitsimts'
summary(object, ...)
```

Arguments

object	A fitsimts object
...	Other arguments passed to specific methods

Value

Estimated parameters values with confidence intervals and standard errors.

Author(s)

Stéphane Guerrier

summary.gmwm *Summary of GMWM object*

Description

Displays summary information about GMWM object

Usage

```
## S3 method for class 'gmwm'
summary(
  object,
  inference = NULL,
  bs.gof = NULL,
  bs.gof.p.ci = NULL,
  bs.theta.est = NULL,
  bs.ci = NULL,
  B = 100,
  ...
)
```

Arguments

object	A GMWM object
inference	A value containing either: NULL (auto), TRUE, or FALSE
bs.gof	A value containing either: NULL (auto), TRUE, FALSE
bs.gof.p.ci	A value containing either: NULL (auto), TRUE, FALSE
bs.theta.est	A value containing either: NULL (auto), TRUE, FALSE
bs.ci	A value containing either: NULL (auto), TRUE, FALSE
B	An int that indicates how many bootstraps should be performed.
...	Other arguments passed to specific methods

Value

A summary.gmwm object with:

estimate	Estimated Theta Values
testinfo	Goodness of Fit Information
inference	Inference performed? T/F
bs.gof	Bootstrap GOF? T/F
bs.gof.p.ci	Bootstrap GOF P-Value CI? T/F
bs.theta.est	Bootstrap Theta Estimates? T/F
bs.ci	Bootstrap CI? T/F
starting	Indicates if program supplied initial starting values
seed	Seed used during guessing / bootstrapping
obj.fun	Value of obj.fun at minimized theta
N	Length of Time Series

Author(s)

JJB

---

theo_acf *Theoretical Autocorrelation (ACF) of an ARMA process*

Description

This function computes the theoretical Autocorrelation (ACF) of an ARMA process.

Usage

```
theo_acf(ar, ma = NULL, lagmax = 20)
```

Arguments

ar	A vector containing the AR coefficients.
ma	A vector containing the MA coefficients.
lagmax	An integer indicating the maximum lag up to which to compute the theoretical ACF.

Author(s)

Yuming Zhang

Examples

```
# Compute the theoretical ACF for an ARMA(1,0) (i.e. a first-order autoregressive model: AR(1))
theo_acf(ar = -0.25, ma = NULL)
# Computes the theoretical ACF for an ARMA(2, 1)
theo_acf(ar = c(.50, -0.25), ma = 0.20, lagmax = 10)
```

---

theo_pacf *Theoretical Partial Autocorrelation (PACF) of an ARMA process*

Description

This function computes the theoretical Partial Autocorrelation (PACF) of an ARMA process.

Usage

```
theo_pacf(ar, ma = NULL, lagmax = 20)
```

Arguments

ar	A vector containing the AR coefficients.
ma	A vector containing the MA coefficients.
lagmax	An integer indicating the maximum lag up to which to compute the theoretical PACF.

Author(s)

Yuming Zhang

Examples

```
# Computes the theoretical ACF for an ARMA(1,0) (i.e. a first-order autoregressive model: AR(1))
theo_pacf(ar = -0.25, ma = NULL, lagmax = 7)
# Computes the theoretical ACF for an ARMA(2, 1)
theo_pacf(ar = c(.50, -0.25), ma = .20, lagmax = 10)
```

update.gmwm *Update (Robust) GMWM object for IMU or SSM*

Description

Provides a way to estimate different models over the previously estimated wavelet variance values and covariance matrix.

Usage

```
## S3 method for class 'gmwm'
update(object, model, ...)
```

Arguments

object	A gmwm object.
model	A ts.model object containing one of the allowed models
...	Additional parameters (not used)

Value

A gmwm object with the structure:

estimate	Estimated Parameters Values from the GMWM Procedure
init.guess	Initial Starting Values given to the Optimization Algorithm
wv.empir	The data's empirical wavelet variance
ci_low	Lower Confidence Interval
ci_high	Upper Confidence Interval
orgV	Original V matrix
V	Updated V matrix (if bootstrapped)
omega	The V matrix inversed
obj.fun	Value of the objective function at Estimated Parameter Values
theo	Summed Theoretical Wavelet Variance
decomp.theo	Decomposed Theoretical Wavelet Variance by Process
scales	Scales of the GMWM Object
robust	Indicates if parameter estimation was done under robust or classical
eff	Level of efficiency of robust estimation
model.type	Models being guessed
compute.v	Type of V matrix computation
augmented	Indicates moments have been augmented
alpha	Alpha level used to generate confidence intervals

expect.diff	Mean of the First Difference of the Signal
N	Length of the Signal
G	Number of Guesses Performed
H	Number of Bootstrap replications
K	Number of V matrix bootstraps
model	ts.model supplied to gmwm
model.hat	A new value of ts.model object supplied to gmwm
starting	Indicates whether the procedure used the initial guessing approach
seed	Randomization seed used to generate the guessing values
freq	Frequency of data

`update.lts` *Update Object Attribute*

Description

Update the attributes of lts, gts and imu object

Usage

```
## S3 method for class 'lts'
update(object, type, new, keep.start = T, ...)

## S3 method for class 'gts'
update(object, type, new, keep.start = T, ...)

## S3 method for class 'imu'
update(object, type, new, ...)
```

Arguments

object	A lts, gts or imu object
type	A string that contains the attribute to be updated
new	The updated value for the attribute
keep.start	A boolean value that indicates whether 'start' or 'end' should remain the same when 'freq' is updated
...	Further arguments passed to or from other methods.

Details

This function is able to update some attributes for gts, lts and imu objects. For lts object, the attributes that can be updated are 'start', 'end', 'freq', 'unit_time', 'name_ts' and 'process'. For gts object, the attributes that can be updated are 'start', 'end', 'freq', 'unit_time' and 'name_ts'. For imu object, the attributes that can be updated are 'axis', 'freq', 'unit_time' and 'name_ts'.

If one between 'start' and 'end' is updated, the other one will also be updated, since `end-start == (N-1)/freq` must be TRUE, where N is the number of observations in the object.

If 'freq' is updated, by default 'start' will remain the same, and 'end' will be updated at the same time, unless you set 'keep.start = F'.

If 'unit_time' is updated, the old unit_time will be replaced by the new one, and other attributes will remain the same. It is different from the unit_time conversion feature.

Value

An object with the updated attribute.

Examples

```
gts1 = gts(rnorm(50), freq = 1, unit_time = 'sec', name_ts = 'test1')
gts2 = update(gts1, 'unit_time', 'min')
attr(gts2, 'unit_time')

gts3 = update(gts1, 'name_ts', 'test2')
attr(gts3, 'name_ts')
```

---

value *Obtain the value of an object's properties*

Description

Used to access different properties of the gts, imu, or lts object.

Usage

```
value(x, type)

## S3 method for class 'imu'
value(x, type)
```

Arguments

x	A gts, imu, or lts object.
type	A string indicating the field to be retrieved.

Details

To access information about `imu` properties use:

`"accel"` Returns the number of accelerometers

`"gyro"` Returns the number of gyroscopes

`"sensors"` Returns total number of sensors

Value

The method will return a single numeric or string result depending on the slot being accessed.

Methods (by class)

- `value(imu)`: Access `imu` object properties

Author(s)

James Balamuta

WN *Create an White Noise (WN) Process*

Description

Sets up the necessary backend for the WN process.

Usage

```
WN(sigma2 = NULL)
```

Arguments

`sigma2`	A `double` value for the variance, σ^2, of a WN process.

Value

An S3 object with called ts.model with the following structure:

process.desc Used in summary: "WN"

theta σ

plength Number of Parameters

print String containing simplified model

desc y desc replicated x times

obj.desc Depth of Parameters e.g. list(1)

starting Guess Starting values? TRUE or FALSE (e.g. specified value)

Note

In this process, Y_t is iid from a zero mean normal distribution with variance σ^2

Author(s)

James Balamuta

Examples

```
WN()
WN(sigma2=3.4)
```

---

wn_to_wv *Gaussian White Noise to WV*

Description

This function compute the Haar WV of a Gaussian White Noise process

Usage

```
wn_to_wv(sigma2, tau)
```

Arguments

sigma2	A double corresponding to variance of WN
tau	A vec containing the scales e.g. 2^τ

Value

A vec containing the wavelet variance of the white noise.

Process Haar Wavelet Variance Formula

The Gaussian White Noise (WN) process has a Haar Wavelet Variance given by:

$$\nu_j^2\left(\sigma^2\right) = \frac{\sigma^2}{\tau_j^2}$$

Index

∗ **datasets**
australia, 14
hydro, 50
savingrt, 79
[.imu, 4

AIC.fitsimts, 5
AR, 6
AR1, 7
ar1_to_wv, 8
ARIMA, 9
ARMA, 10
ARMA11, 12
arma11_to_wv, 13
arma_to_wv, *8*, 11, *13*, *58*
australia, 14
auto_corr, 14, *63, 64*

best_model, 15

check, 16
compare_acf, 17
corr_analysis, 18

deriv_2nd_ar1, 19
deriv_2nd_arma11, 20
deriv_2nd_dr, 22
deriv_2nd_ma1, 22
deriv_ar1, 23
deriv_arma11, 24
deriv_dr, 25
deriv_ma1, 26
deriv_qn, 27
deriv_rw, 27
deriv_wn, 28
derivative_first_matrix, 29
diag_boxpierce, 29
diag_ljungbox, 30
diag_plot, 31
diag_portmanteau_, 31

DR, 32
dr_to_wv, 33

estimate, 34
evaluate, 35

FGN, 36

gen_ar1blocks, 37
gen_bi, 38
gen_gts, 39
gen_lts, 40
gen_nswn, 42
GM, 43
gmwm, 44
gmwm_imu, 47
gts, *43*, 48

hydro, 50

imu, 50
imu_time, 52
inherits, *53*
is, *53*
is.gts, 53
is.imu *(*is.gts*)*, 53
is.lts *(*is.gts*)*, 53
is.ts.model *(*is.gts*)*, 53

lts, 54

M, 55
MA, 56
MA1, 57
ma1_to_wv, 58
make_frame, 59
MAPE, 60
MAT, 61

np_boot_sd_med, 62

plot.gmwm, 62

plot.PACF, 63
plot.simtsACF, 65
plot_pred, 66
PLP, 67
predict.fitsimts, 68
predict.gmwm, 69

QN, 70
qn_to_wv, 71

read.imu, 71
resid_plot, 72
rgmwm, 73
rtruncated_normal, 74
RW, 74
RW2dimension, 76
rw_to_wv, 75

SARIMA, 76
SARMA, 78
savingrt, 79
select, 79
select_ar, *16*
select_ar *(*select_arima*)*, 80
select_arima, 80
select_arma, *16*
select_arma *(*select_arima*)*, 80
select_ma, *16*
select_ma *(*select_arima*)*, 80
simple_diag_plot, 81
simplified_print_SARIMA, 82
SIN, 83
summary.fitsimts, 84
summary.gmwm, 84

theo_acf, 85
theo_pacf, *63, 64*, 86

update.gmwm, 87
update.gts *(*update.lts*)*, 88
update.imu *(*update.lts*)*, 88
update.lts, 88

value, 89

WN, 90
wn_to_wv, 91