Package: sirt (via r-universe)

October 18, 2026

Type Package

Title Supplementary Item Response Theory Models

Version 4.2-133

Date 2025-09-27 12:57:51

Maintainer Alexander Robitzsch <robitzsch@ipn.uni-kiel.de>

Description Supplementary functions for item response models aiming to complement existing R packages. The functionality includes among others multidimensional compensatory and noncompensatory IRT models (Reckase, 2009, <doi:10.1007/978-0-387-89976-3>), MCMC for hierarchical IRT models and testlet models (Fox, 2010, <doi:10.1007/978-1-4419-0742-4>), NOHARM (McDonald, 1982, <doi:10.1177/014662168200600402>), Rasch copula model (Braeken, 2011, <doi:10.1007/s11336-010-9190-4>; Schroeders, Robitzsch & Schipolowski, 2014, <doi:10.1111/jedm.12054>), faceted and hierarchical rater models (DeCarlo, Kim & Johnson, 2011, <doi:10.1111/j.1745-3984.2011.00143.x>), ordinal IRT model (ISOP; Scheiblechner, 1995, <doi:10.1007/BF02301417>), DETECT statistic (Stout, Habing, Douglas & Kim, 1996, <doi:10.1177/014662169602000403>), local structural equation modeling (LSEM; Hildebrandt, Luedtke, Robitzsch, Sommer & Wilhelm, 2016, <doi:10.1080/00273171.2016.1142856>).

Depends R (>= 3.5)

Imports CDM, graphics, methods, parallel, pbapply, Rcpp, stats, TAM, utils

Suggests coda, igraph, lavaan, MASS, Matrix, miceadds, minqa, mirt, mvtnorm, nloptr, optimx, pbivnorm, pbv, psych, sfsmisc, sm, survey

LinkingTo pbv, Rcpp, RcppArmadillo

URL https://github.com/alexanderrobitzsch/sirt, https://sites.google.com/view/alexander-robitzsch/software

License GPL (>= 2)

NeedsCompilation yes

Author Alexander Robitzsch [aut, cre] (ORCID:
<https://orcid.org/0000-0002-8226-3132>)

Repository https://cran.r-universe.dev

Date/Publication 2025-09-27 23:30:02 UTC

RemoteUrl https://github.com/cran/sirt

RemoteRef HEAD

RemoteSha 38c78c42f204a5107a2a290075573dbc7c3a3b6a

Contents

sirt-package 5
automatic.recode 10
brm-Methods 12
btm 16
categorize 21
ccov.np 22
cfa_meas_inv 24
class.accuracy.rasch 26
conf.detect 27
data.activity.itempars 32
data.befki 33
data.big5 34
data.bs 39
data.eid 41
data.ess2005 49
data.g308 50
data.inv4gr 52
data.liking.science 53
data.long 54
data.lsem 58
data.math 59
data.mcdonald 61
data.mixed1 64
data.ml 65
data.noharm 66
data.pars1.rasch 67
data.pirlsmissing 68
data.pisa2006Read 69
data.pisaMath 69
data.pisaPars 70
data.pisaRead 71
data.pw 72
data.ratings 72
data.raw1 73
data.read 74
data.reck 94

data.sirt . . . 100
data.timss . . . 105
data.timss07.G8.RUS . . . 106
data.trees . . . 107
data.wide2long . . . 109
detect.index . . . 111
dif.logistic.regression . . . 112
dif.strata.variance . . . 116
dif.variance . . . 117
dirichlet.mle . . . 118
dirichlet.simul . . . 120
dmlavaan . . . 122
eigenvalues.manymatrices . . . 124
equating.rasch . . . 125
equating.rasch.jackknife . . . 127
expl.detect . . . 128
f1d.irt . . . 130
fit.isop . . . 133
fuzcluster . . . 135
fuzdiscr . . . 138
gom.em . . . 141
gom.jml . . . 150
greenyang.reliability . . . 151
invariance.alignment . . . 154
IRT.mle . . . 167
isop . . . 170
isop.scoring . . . 174
isop.test . . . 176
latent.regression.em.raschtype . . . 177
lavaan2mirt . . . 183
lc.2raters . . . 190
likelihood.adjustment . . . 192
linking.haberman . . . 194
linking.haebara . . . 206
linking.robust . . . 210
linking_2groups . . . 212
locpolycor . . . 214
lq_fit . . . 216
lsdm . . . 218
lsem.estimate . . . 225
lsem.permutationTest . . . 234
lsem.test . . . 236
marginal.truescore.reliability . . . 237
matrixfunctions.sirt . . . 240
mcmc.2pno . . . 241
mcmc.2pno.ml . . . 244
mcmc.2pnoh . . . 249
mcmc.3pno.testlet . . . 251

mcmc.list.descriptives . . . 256
mcmc_coef . . . 258
mcmc_Rhat . . . 260
mcmclist2coda . . . 261
md.pattern.sirt . . . 262
mgsem . . . 263
mirt.specify.partable . . . 268
mirt.wrapper . . . 269
mle.pcm.group . . . 276
modelfit.sirt . . . 278
monoreg.rowwise . . . 282
nedelsky-methods . . . 283
noharm.sirt . . . 287
np.dich . . . 296
parmsummary_extend . . . 297
pbivnorm2 . . . 298
pcm.conversion . . . 299
pcm.fit . . . 301
person.parameter.rasch.copula . . . 303
personfit.stat . . . 305
pgenlogis . . . 307
plausible.value.imputation.raschtype . . . 309
plot.mcmc.sirt . . . 313
plot.np.dich . . . 314
polychoric2 . . . 315
prior_model_parse . . . 316
prmse.subscores.scales . . . 317
prob.guttman . . . 319
Q3 . . . 323
Q3.testlet . . . 325
qmc.nodes . . . 326
R2conquest . . . 327
R2noharm . . . 332
R2noharm.EAP . . . 340
R2noharm.jackknife . . . 341
rasch.copula2 . . . 342
rasch.evm.pcm . . . 351
rasch.jml . . . 356
rasch.jml.biascorr . . . 359
rasch.jml.jackknife1 . . . 361
rasch.mirtlc . . . 362
rasch.mml2 . . . 374
rasch.pairwise . . . 392
rasch.pairwise.itemcluster . . . 394
rasch.pml3 . . . 397
rasch.prox . . . 405
rasch.va . . . 406
reliability.nonlinearSEM . . . 408

resp_groupwise . . . 409
rinvgamma2 . . . 410
rm.facets . . . 412
rm.sdt . . . 418
rmvn . . . 423
scale_group_means . . . 425
sia.sirt . . . 426
sim.qm.ramsay . . . 428
sim.rasch.dep . . . 431
sim.raschtype . . . 433
sirt-defunct . . . 435
sirt-utilities . . . 435
sirt_eigenvalues . . . 440
smirt . . . 441
stratified.cronbach.alpha . . . 450
summary.mcmc.sirt . . . 451
tam2mirt . . . 452
testlet.marginalized . . . 457
tetrachoric2 . . . 459
truescore.irt . . . 461
unidim.test.csn . . . 464
wle.rasch . . . 466
wle.rasch.jackknife . . . 467
xxirt . . . 469
xxirt_createParTable . . . 488
xxirt_createThetaDistribution . . . 490

Index **492**

`sirt-package` *Supplementary Item Response Theory Models*

Description

Supplementary functions for item response models aiming to complement existing R packages. The functionality includes among others multidimensional compensatory and noncompensatory IRT models (Reckase, 2009, <doi:10.1007/978-0-387-89976-3>), MCMC for hierarchical IRT models and testlet models (Fox, 2010, <doi:10.1007/978-1-4419-0742-4>), NOHARM (McDonald, 1982, <doi:10.1177/014662168200600402>), Rasch copula model (Braeken, 2011, <doi:10.1007/s11336-010-9190-4>; Schroeders, Robitzsch & Schipolowski, 2014, <doi:10.1111/jedm.12054>), faceted and hierarchical rater models (DeCarlo, Kim & Johnson, 2011, <doi:10.1111/j.1745-3984.2011.00143.x>), ordinal IRT model (ISOP; Scheiblechner, 1995, <doi:10.1007/BF02301417>), DETECT statistic (Stout, Habing, Douglas & Kim, 1996, <doi:10.1177/014662169602000403>), local structural equation modeling (LSEM; Hildebrandt, Luedtke, Robitzsch, Sommer & Wilhelm, 2016, <doi:10.1080/00273171.2016.1142

Details

The **sirt** package enables the estimation of following models:

- Multidimensional marginal maximum likelihood estimation (MML) of generalized logistic Rasch type models using the generalized logistic link function (Stukel, 1988) can be conducted with `rasch.mml2` and the argument `itemtype="raschtype"`. This model also allows the estimation of the 4PL item response model (Loken & Rulison, 2010). Multiple group estimation, latent regression models and plausible value imputation are supported. In addition, pseudo-likelihood estimation for fractional item response data can be conducted.
- Multidimensional noncompensatory, compensatory and partially compensatory item response models for dichotomous item responses (Reckase, 2009) can be estimated with the `smirt` function and the options `irtmodel="noncomp"` , `irtmodel="comp"` and `irtmodel="partcomp"`.
- The unidimensional quotient model (Ramsay, 1989) can be estimated using `rasch.mml2` with `itemtype="ramsay.qm"`.
- Unidimensional nonparametric item response models can be estimated employing MML estimation (Rossi, Wang & Ramsay, 2002) by making use of `rasch.mml2` with `itemtype="npirt"`. Kernel smoothing for item response function estimation (Ramsay, 1991) is implemented in `np.dich`.
- The multidimensional IRT copula model (Braeken, 2011) can be applied for handling local dependencies, see `rasch.copula3`.
- Unidimensional joint maximum likelihood estimation (JML) of the Rasch model is possible with the `rasch.jml` function. Bias correction methods for item parameters are included in `rasch.jml.jackknife1` and `rasch.jml.biascorr`.
- The multidimensional latent class Rasch and 2PL model (Bartolucci, 2007) which employs a discrete trait distribution can be estimated with `rasch.mirtlc`.
- The unidimensional 2PL rater facets model (Lincare, 1994) can be estimated with `rm.facets`. A hierarchical rater model based on signal detection theory (DeCarlo, Kim & Johnson, 2011) can be conducted with `rm.sdt`. A simple latent class model for two exchangeable raters is implemented in `lc.2raters`. See Robitzsch and Steinfeld (2018) for more details.
- The discrete grade of membership model (Erosheva, Fienberg & Joutard, 2007) and the Rasch grade of membership model can be estimated by `gom.em`.
- Some hierarchical IRT models and random item models for dichotomous and normally distributed data (van den Noortgate, de Boeck & Meulders, 2003; Fox & Verhagen, 2010) can be estimated with `mcmc.2pno.ml`.
- Unidimensional pairwise conditional likelihood estimation (PCML; Zwinderman, 1995) is implemented in `rasch.pairwise` or `rasch.pairwise.itemcluster`.
- Unidimensional pairwise marginal likelihood estimation (PMML; Renard, Molenberghs & Geys, 2004) can be conducted using `rasch.pml3`. In this function local dependence can be handled by imposing residual error structure or omitting item pairs within a dependent item cluster from the estimation.
  The function `rasch.evm.pcm` estimates the multiple group partial credit model based on the pairwise eigenvector approach which avoids iterative estimation.
- Some item response models in **sirt** can be estimated via Markov Chain Monte Carlo (MCMC) methods. In `mcmc.2pno` the two-parameter normal ogive model can be estimated. A hierarchical version of this model (Janssen, Tuerlinckx, Meulders & de Boeck, 2000) is implemented

in mcmc.2pnoh. The 3PNO testlet model (Wainer, Bradlow & Wang, 2007; Glas, 2012) can be estimated with mcmc.3pno.testlet. Some hierarchical IRT models and random item models (van den Noortgate, de Boeck & Meulders, 2003) can be estimated with mcmc.2pno.ml.

- For dichotomous response data, the free NOHARM software (McDonald, 1982, 1997) estimates the multidimensional compensatory 3PL model and the function R2noharm runs NOHARM from within R. Note that NOHARM must be downloaded from *http://noharm.niagararesearch.ca/nh4cldl.html* at first. A pure R implementation of the NOHARM model with some extensions can be found in noharm.sirt.
- The measurement theoretic founded nonparametric item response models of Scheiblechner (1995, 1999) – the ISOP and the ADISOP model – can be estimated with isop.dich or isop.poly. Item scoring within this theory can be conducted with isop.scoring.
- The functional unidimensional item response model (Ip et al., 2013) can be estimated with f1d.irt.
- The Rasch model can be estimated by variational approximation (Rijmen & Vomlel, 2008) using rasch.va.
- The unidimensional probabilistic Guttman model (Proctor, 1970) can be specified with prob.guttman.
- A jackknife method for the estimation of standard errors of the weighted likelihood trait estimate (Warm, 1989) is available in wle.rasch.jackknife.
- Model based reliability for dichotomous data can be calculated by the method of Green and Yang (2009) with greenyang.reliability and the marginal true score method of Dimitrov (2003) using the function marginal.truescore.reliability.
- Essential unidimensionality can be assessed by the DETECT index (Stout, Habing, Douglas & Kim, 1996), see the function conf.detect.
- Item parameters from several studies can be linked using the Haberman method (Haberman, 2009) in linking.haberman. See also equating.rasch and linking.robust. The alignment procedure (Asparouhov & Muthen, 2013) invariance.alignment is originally for comfirmatory factor analysis and aims at obtaining approximate invariance.
- Some person fit statistics in the Rasch model (Meijer & Sijtsma, 2001) are included in personfit.stat.
- An alternative to the linear logistic test model (LLTM), the so called least squares distance model for cognitive diagnosis (LSDM; Dimitrov, 2007), can be estimated with the function lsdm.
- Local structural equation models (LSEM) can be estimated with the lsem.estimate function (Hildebrandt et al., 2016).

Author(s)

NA

Maintainer: Alexander Robitzsch <robitzsch@ipn.uni-kiel.de>

References

Asparouhov, T., & Muthen, B. (2014). Multiple-group factor analysis alignment. *Structural Equation Modeling, 21*(4), 1-14. doi:10.1080/10705511.2014.919210

Bartolucci, F. (2007). A class of multidimensional IRT models for testing unidimensionality and clustering items. *Psychometrika, 72*, 141-157.

Braeken, J. (2011). A boundary mixture approach to violations of conditional independence. *Psychometrika, 76*(1), 57-76. doi:10.1007/s1133601091904

DeCarlo, T., Kim, Y., & Johnson, M. S. (2011). A hierarchical rater model for constructed responses, with a signal detection rater model. *Journal of Educational Measurement, 48*(3), 333-356. doi:10.1111/j.17453984.2011.00143.x

Dimitrov, D. (2003). Marginal true-score measures and reliability for binary items as a function of their IRT parameters. *Applied Psychological Measurement, 27*, 440-458.

Dimitrov, D. M. (2007). Least squares distance method of cognitive validation and analysis for binary items using their item response theory parameters. *Applied Psychological Measurement, 31*, 367-387.

Erosheva, E. A., Fienberg, S. E., & Joutard, C. (2007). Describing disability through individual-level mixture models for multivariate binary data. *Annals of Applied Statistics, 1*, 502-537.

Fox, J.-P. (2010). *Bayesian item response modeling*. New York: Springer. doi:10.1007/97814419-07424

Fox, J.-P., & Verhagen, A.-J. (2010). Random item effects modeling for cross-national survey data. In E. Davidov, P. Schmidt, & J. Billiet (Eds.), *Cross-cultural Analysis: Methods and Applications* (pp. 467-488), London: Routledge Academic.

Fraser, C., & McDonald, R. P. (1988). NOHARM: Least squares item factor analysis. *Multivariate Behavioral Research, 23*, 267-269.

Glas, C. A. W. (2012). *Estimating and testing the extended testlet model.* LSAC Research Report Series, RR 12-03.

Green, S.B., & Yang, Y. (2009). Reliability of summed item scores using structural equation modeling: An alternative to coefficient alpha. *Psychometrika, 74*, 155-167.

Haberman, S. J. (2009). *Linking parameter estimates derived from an item response model through separate calibrations*. ETS Research Report ETS RR-09-40. Princeton, ETS. doi:10.1002/j.2333-8504.2009.tb02197.x

Hildebrandt, A., Luedtke, O., Robitzsch, A., Sommer, C., & Wilhelm, O. (2016). Exploring factor model parameters across continuous variables with local structural equation models. *Multivariate Behavioral Research, 51*(2-3), 257-278. doi:10.1080/00273171.2016.1142856

Ip, E. H., Molenberghs, G., Chen, S. H., Goegebeur, Y., & De Boeck, P. (2013). Functionally unidimensional item response models for multivariate binary data. *Multivariate Behavioral Research, 48*, 534-562.

Janssen, R., Tuerlinckx, F., Meulders, M., & de Boeck, P. (2000). A hierarchical IRT model for criterion-referenced measurement. *Journal of Educational and Behavioral Statistics, 25*, 285-306.

Jeon, M., & Rijmen, F. (2016). A modular approach for item response theory modeling with the R package **flirt**. *Behavior Research Methods, 48*(2), 742-755. doi:10.3758/s134280150606z

Linacre, J. M. (1994). *Many-Facet Rasch Measurement*. Chicago: MESA Press.

Loken, E. & Rulison, K. L. (2010). Estimation of a four-parameter item response theory model. *British Journal of Mathematical and Statistical Psychology, 63*, 509-525.

McDonald, R. P. (1982). Linear versus nonlinear models in item response theory. *Applied Psychological Measurement, 6*(4), 379-396. doi:10.1177/014662168200600402

McDonald, R. P. (1997). Normal-ogive multidimensional model. In W. van der Linden & R. K. Hambleton (1997): *Handbook of modern item response theory* (pp. 257-269). New York: Springer. doi:10.1007/9781475726916_15

Meijer, R. R., & Sijtsma, K. (2001). Methodology review: Evaluating person fit. *Applied Psychological Measurement, 25*, 107-135.

Proctor, C. H. (1970). A probabilistic formulation and statistical analysis for Guttman scaling. *Psychometrika, 35*, 73-78.

Ramsay, J. O. (1989). A comparison of three simple test theory models. *Psychometrika, 54*, 487-499.

Ramsay, J. O. (1991). Kernel smoothing approaches to nonparametric item characteristic curve estimation. *Psychometrika, 56*, 611-630.

Reckase, M. (2009). *Multidimensional item response theory*. New York: Springer. doi:10.1007/9780387899763

Renard, D., Molenberghs, G., & Geys, H. (2004). A pairwise likelihood approach to estimation in multilevel probit models. *Computational Statistics & Data Analysis, 44*, 649-667.

Rijmen, F., & Vomlel, J. (2008). Assessing the performance of variational methods for mixed logistic regression models. *Journal of Statistical Computation and Simulation, 78*, 765-779.

Robitzsch, A., & Steinfeld, J. (2018). Item response models for human ratings: Overview, estimation methods, and implementation in R. *Psychological Test and Assessment Modeling, 60*(1), 101-139.

Rossi, N., Wang, X. & Ramsay, J. O. (2002). Nonparametric item response function estimates with the EM algorithm. *Journal of Educational and Behavioral Statistics, 27*, 291-317.

Rusch, T., Mair, P., & Hatzinger, R. (2013). *Psychometrics with* R*: A Review of CRAN Packages for Item Response Theory.* http://epub.wu.ac.at/4010/1/resrepIRThandbook.pdf

Scheiblechner, H. (1995). Isotonic ordinal probabilistic models (ISOP). *Psychometrika, 60*(2), 281-304. doi:10.1007/BF02301417

Scheiblechner, H. (1999). Additive conjoint isotonic probabilistic models (ADISOP). *Psychometrika, 64*, 295-316.

Schroeders, U., Robitzsch, A., & Schipolowski, S. (2014). A comparison of different psychometric approaches to modeling testlet structures: An example with C-tests. *Journal of Educational Measurement, 51*(4), 400-418. doi:10.1111/jedm.12054

Stout, W., Habing, B., Douglas, J., & Kim, H. R. (1996). Conditional covariance-based nonparametric multidimensionality assessment. *Applied Psychological Measurement, 20*(4), 331-354. doi:10.1177/014662169602000403

Stukel, T. A. (1988). Generalized logistic models. *Journal of the American Statistical Association, 83*(402), 426-431. doi:10.1080/01621459.1988.10478613

Uenlue, A., & Yanagida, T. (2011). R you ready for R?: The CRAN psychometrics task view. *British Journal of Mathematical and Statistical Psychology, 64*(1), 182-186. doi:10.1348/000711010X519320

van den Noortgate, W., De Boeck, P., & Meulders, M. (2003). Cross-classification multilevel logistic models in psychometrics. *Journal of Educational and Behavioral Statistics, 28*, 369-386.

Warm, T. A. (1989). Weighted likelihood estimation of ability in item response theory. *Psychometrika, 54*, 427-450.

Wainer, H., Bradlow, E. T., & Wang, X. (2007). *Testlet response theory and its applications*. Cambridge: Cambridge University Press.

Zwinderman, A. H. (1995). Pairwise parameter estimation in Rasch models. *Applied Psychological Measurement, 19*, 369-375.

See Also

For estimating multidimensional models for polytomous item responses see the **mirt**, **flirt** (Jeon & Rijmen, 2016) and **TAM** packages.

For conditional maximum likelihood estimation see the **eRm** package.

For pairwise estimation likelihood methods (also known as composite likelihood methods) see **pln** or **lavaan**.

The estimation of cognitive diagnostic models is possible using the **CDM** package.

For the multidimensional latent class IRT model see the **MultiLCIRT** package which also allows the estimation IRT models with polytomous item responses.

Latent class analysis can be carried out with **covLCA**, **poLCA**, **BayesLCA**, **randomLCA** or **lcmm** packages.

Markov Chain Monte Carlo estimation for item response models can also be found in the **MCMCpack** package (see the `MCMCirt` functions therein).

See Rusch, Mair and Hatzinger (2013) and Uenlue and Yanagida (2011) for reviews of psychometrics packages in R.

Examples

```
##
##   |-----------------------------------------------------------------|
##   | sirt 0.40-4 (2013-11-26)                                        |
##   | Supplementary Item Response Theory                              |
##   | Maintainer: Alexander Robitzsch <a.robitzsch at bifie.at >      |
##   | https://sites.google.com/site/alexanderrobitzsch/software       |
##   |-----------------------------------------------------------------|
##
##                        _/              _/
##             _/_/_/       _/  _/_/  _/_/_/_/
##           _/_/       _/  _/_/         _/
##              _/_/  _/  _/           _/
##         _/_/_/    _/  _/            _/_/
##
```

`automatic.recode` *Automatic Method of Finding Keys in a Dataset with Raw Item Responses*

Description

This function calculates keys of a dataset with raw item responses. It starts with setting the most frequent category of an item to 1. Then, in each iteration keys are changed such that the highest item discrimination is found.

Usage

```
automatic.recode(data, exclude=NULL, pstart.min=0.6, allocate=200,
    maxiter=20, progress=TRUE)
```

Arguments

data	Dataset with raw item responses
exclude	Vector with categories to be excluded for searching the key
pstart.min	Minimum probability for an initial solution of keys.
allocate	Maximum number of categories per item. This argument is used in the function tam.ctt3 of the **TAM** package.
maxiter	Maximum number of iterations
progress	A logical which indicates if iteration progress should be displayed

Value

A list with following entries

item.stat	Data frame with item name, p value, item discrimination and the calculated key
data.scored	Scored data frame using calculated keys in item.stat
categ.stats	Data frame with statistics for all categories of all items

Examples

```
## Not run:
#############################################################################
# EXAMPLE 1: data.raw1
#############################################################################
data(data.raw1)

# recode data.raw1 and exclude keys 8 and 9 (missing codes) and
# start with initially setting all categories larger than 50
res1 <- sirt::automatic.recode( data.raw1, exclude=c(8,9), pstart.min=.50 )
# inspect calculated keys
res1$item.stat

#############################################################################
# EXAMPLE 2: data.timssAusTwn from TAM package
#############################################################################

miceadds::library_install("TAM")
data(data.timssAusTwn,package="TAM")
raw.resp <- data.timssAusTwn[,1:11]
res2 <- sirt::automatic.recode( data=raw.resp )

## End(Not run)
```

brm-Methods *Functions for the Beta Item Response Model*

Description

Functions for simulating and estimating the Beta item response model (Noel & Dauvier, 2007). `brm.sim` can be used for simulating the model, `brm.irf` computes the item response function. The Beta item response model is estimated as a discrete version to enable estimation in *standard* IRT software like **mirt** or **TAM** packages.

Usage

```
# simulating the beta item response model
brm.sim(theta, delta, tau, K=NULL)

# computing the item response function of the beta item response model
brm.irf( Theta, delta, tau, ncat, thdim=1, eps=1E-10 )
```

Arguments

`theta`	Ability vector of θ values
`delta`	Vector of item difficulty parameters
`tau`	Vector item dispersion parameters
`K`	Number of discretized categories. The default is `NULL` which means that the simulated item responses are real number values between 0 and 1. If an integer `K` chosen, then values are discretized such that values of 0, 1, ..., K-1 arise.
`Theta`	Matrix of the ability vector $\boldsymbol{\theta}$
`ncat`	Number of categories
`thdim`	Theta dimension in the matrix `Theta` on which the item loads.
`eps`	Nuisance parameter which stabilize probabilities.

Details

The discrete version of the beta item response model is defined as follows. Assume that for item i there are K categories resulting in values $k = 0, 1, \ldots, K-1$. Each value k is associated with a corresponding the transformed value in $[0, 1]$, namely $q(k) = 1/(2 \cdot K), 1/(2 \cdot K) + 1/K, \ldots, 1 - 1/(2 \cdot K)$. The item response model is defined as

$$P(X_{pi} = x_{pi} | \theta_p) \propto q(x_{pi})^{m_{pi}-1} [1 - q(x_{pi})]^{n_{pi}-1}$$

This density is a discrete version of a Beta distribution with shape parameters m_{pi} and n_{pi}. These parameters are defined as

$$m_{pi} = \exp\left[(\theta_p - \delta_i + \tau_i)/2\right] \qquad \text{and} \qquad n_{pi} = \exp\left[(-\theta_p + \delta_i + \tau_i)/2\right]$$

The item response function can also be formulated as

$$\log\left[P(X_{pi}=x_{pi}|\theta_p)\right] \propto (m_{pi}-1)\cdot\log[q(x_{pi})] + (n_{pi}-1)\cdot\log[1-q(x_{pi})]$$

The item parameters can be reparameterized as $a_i = \exp\left[(-\delta_i+\tau_i)/2\right]$ and $b_i = \exp\left[(\delta_i+\tau_i)/2\right]$. Then, the original item parameters can be retrieved by $\tau_i = \log(a_i b_i)$ and $\delta_i = \log(b_i/a_i)$. Using $\gamma_p = \exp(\theta_p/2)$, we obtain

$$\log\left[P(X_{pi}=x_{pi}|\theta_p)\right] \propto a_i\gamma_p\cdot\log[q(x_{pi})] + b_i/\gamma_p\cdot\log[1-q(x_{pi})] - [\log q(x_{pi}) + \log[1-q(x_{pi})]]$$

This formulation enables the specification of the Beta item response model as a structured latent class model (see `TAM::tam.mml.3pl`; Example 1).

See Smithson and Verkuilen (2006) for motivations for treating continuous indicators not as normally distributed variables.

Value

A simulated dataset of item responses if `brm.sim` is applied.

A matrix of item response probabilities if `brm.irf` is applied.

References

Gruen, B., Kosmidis, I., & Zeileis, A. (2012). Extended Beta regression in R: Shaken, stirred, mixed, and partitioned. *Journal of Statistical Software, 48*(11), 1-25. doi:10.18637/jss.v048.i11

Noel, Y., & Dauvier, B. (2007). A beta item response model for continuous bounded responses. *Applied Psychological Measurement, 31*(1), 47-73. doi:10.1177/0146621605287691

Smithson, M., & Verkuilen, J. (2006). A better lemon squeezer? Maximum-likelihood regression with beta-distributed dependent variables. *Psychological Methods, 11*(1), 54-71. doi: 10.1037/1082-989X.11.1.54

See Also

See also the **betareg** package for fitting Beta regression regression models in R (Gruen, Kosmidis & Zeileis, 2012).

Examples

```
#############################################################################
# EXAMPLE 1: Simulated data beta response model
#############################################################################

#*** (1) Simulation of the beta response model
# Table 3 (p. 65) of Noel and Dauvier (2007)
delta <- c( -.942, -.649, -.603, -.398, -.379, .523, .649, .781, .907 )
tau <- c( .382, .166, 1.799, .615, 2.092, 1.988, 1.899, 1.439, 1.057 )
K <- 5        # number of categories for discretization
N <- 500        # number of persons
I <- length(delta) # number of items
```

```
set.seed(865)
theta <- stats::rnorm( N )
dat <- sirt::brm.sim( theta=theta, delta=delta, tau=tau, K=K)
psych::describe(dat)

#*** (2) some preliminaries for estimation of the model in mirt
#*** define a mirt function
library(mirt)
Theta <- matrix( seq( -4, 4, len=21), ncol=1 )

# compute item response function
ii <- 1     # item ii=1
b1 <- sirt::brm.irf( Theta=Theta, delta=delta[ii], tau=tau[ii],  ncat=K )
# plot item response functions
graphics::matplot( Theta[,1], b1, type="l" )

#*** defining the beta item response function for estimation in mirt
par <- c( 0, 1,  1)
names(par) <- c( "delta", "tau","thdim")
est <- c( TRUE, TRUE, FALSE )
names(est) <- names(par)
brm.icc <- function( par, Theta, ncat ){
     delta <- par[1]
     tau <- par[2]
     thdim <- par[3]
     probs <- sirt::brm.irf( Theta=Theta, delta=delta, tau=tau,  ncat=ncat,
            thdim=thdim)
     return(probs)
            }
name <- "brm"
# create item response function
brm.itemfct <- mirt::createItem(name, par=par, est=est, P=brm.icc)
#*** define model in mirt
mirtmodel <- mirt::mirt.model("
           F1=1-9
            " )
itemtype <- rep("brm", I )
customItems <- list("brm"=brm.itemfct)

# define parameters to be estimated
mod1.pars <- mirt::mirt(dat, mirtmodel, itemtype=itemtype,
                  customItems=customItems, pars="values")

## Not run:
#*** (3) estimate beta item response model in mirt
mod1 <- mirt::mirt(dat,mirtmodel, itemtype=itemtype, customItems=customItems,
               pars=mod1.pars, verbose=TRUE  )
# model summaries
print(mod1)
summary(mod1)
coef(mod1)
# estimated coefficients and comparison with simulated data
```

```
cbind( sirt::mirt.wrapper.coef( mod1 )$coef, delta, tau )
mirt.wrapper.itemplot(mod1,ask=TRUE)

#---------------------------
# estimate beta item response model in TAM
library(TAM)

# define the skill space: standard normal distribution
TP <- 21                   # number of theta points
theta.k <- diag(TP)
theta.vec <-  seq( -6,6, len=TP)
d1 <- stats::dnorm(theta.vec)
d1 <- d1 / sum(d1)
delta.designmatrix <- matrix( log(d1), ncol=1 )
delta.fixed <- cbind( 1, 1, 1 )

# define design matrix E
E <- array(0, dim=c(I,K,TP,2*I + 1) )
dimnames(E)[[1]] <- items <- colnames(dat)
dimnames(E)[[4]] <- c( paste0( rep( items, each=2 ),
        rep( c("_a","_b" ), I) ), "one" )
for (ii in 1:I){
    for (kk in 1:K){
      for (tt in 1:TP){
        qk <- (2*(kk-1)+1)/(2*K)
        gammap <- exp( theta.vec[tt] / 2 )
        E[ii, kk, tt, 2*(ii-1) + 1 ] <- gammap * log( qk )
        E[ii, kk, tt, 2*(ii-1) + 2 ] <- 1 / gammap * log( 1 - qk )
        E[ii, kk, tt, 2*I+1 ] <- - log(qk) - log( 1 - qk )
                    }
            }
        }
gammaslope.fixed <- cbind( 2*I+1, 1 )
gammaslope <- exp( rep(0,2*I+1) )

# estimate model in TAM
mod2 <- TAM::tam.mml.3pl(resp=dat, E=E,control=list(maxiter=100),
              skillspace="discrete", delta.designmatrix=delta.designmatrix,
              delta.fixed=delta.fixed, theta.k=theta.k, gammaslope=gammaslope,
              gammaslope.fixed=gammaslope.fixed, notA=TRUE )
summary(mod2)

# extract original tau and delta parameters
m1 <- matrix( mod2$gammaslope[1:(2*I) ], ncol=2, byrow=TRUE )
m1 <- as.data.frame(m1)
colnames(m1) <- c("a","b")
m1$delta.TAM <- log( m1$b / m1$a)
m1$tau.TAM <- log( m1$a * m1$b )

# compare estimated parameter
m2 <- cbind( sirt::mirt.wrapper.coef( mod1 )$coef, delta, tau )[,-1]
colnames(m2) <- c(  "delta.mirt", "tau.mirt", "thdim","delta.true","tau.true"   )
m2 <- cbind(m1,m2)
```

```
round( m2, 3 )

## End(Not run)
```

---

btm *Extended Bradley-Terry Model*

Description

The function btm estimates an extended Bradley-Terry model (Hunter, 2004; see Details). Parameter estimation uses a bias corrected joint maximum likelihood estimation method based on ε-adjustment (see Bertoli-Barsotti, Lando & Punzo, 2014). See Details for the algorithm.

The function btm_sim simulated data from the extended Bradley-Terry model.

Usage

```
btm(data, judge=NULL, ignore.ties=FALSE, fix.eta=NULL, fix.delta=NULL, fix.theta=NULL,
       maxiter=100, conv=1e-04, eps=0.3, wgt.ties=.5)

## S3 method for class 'btm'
summary(object, file=NULL, digits=4,...)

## S3 method for class 'btm'
predict(object, data=NULL, ...)

btm_sim(theta, eta=0, delta=-99, repeated=FALSE)
```

Arguments

data	Data frame with three columns. The first two columns contain labels from the units in the pair comparison. The third column contains the result of the comparison. "1" means that the first units wins, "0" means that the second unit wins and "0.5" means a draw (a tie).
judge	Optional vector of judge identifiers (if multiple judges are available)
ignore.ties	Logical indicating whether ties should be ignored.
fix.eta	Numeric value for a fixed η value
fix.delta	Numeric value for a fixed δ value
fix.theta	A vector with entries for fixed theta values.
maxiter	Maximum number of iterations
conv	Convergence criterion
eps	The ε parameter for the ε-adjustment method (see Bertoli-Barsotti, Lando & Punzo, 2014) which reduces bias in ability estimates. In case of $\varepsilon = 0$, persons with extreme scores are removed from the pairwise comparison.
wgt.ties	Weighting parameter for ties, see formula in Details. The default is .5

object	Object of class btm
file	Optional file name for sinking the summary into
digits	Number of digits after decimal to print
...	Further arguments to be passed.
theta	Vector of abilities
eta	Value of η parameter
delta	Value of δ parameter
repeated	Logical indicating whether repeated ratings of dyads (for home advantage effect) should be simulated

Details

The extended Bradley-Terry model for the comparison of individuals i and j is defined as

$$P(X_{ij} = 1) \propto \exp(\eta + \theta_i)$$

$$P(X_{ij} = 0) \propto \exp(\theta_j)$$

$$P(X_{ij} = 0.5) \propto \exp(\delta + w_T(\eta + \theta_i + \theta_j))$$

The parameters θ_i denote the abilities, δ is the tendency of the occurrence of ties and η is the home-advantage effect. The weighting parameter w_T governs the importance of ties and can be chosen in the argument wgt.ties.

A joint maximum likelihood (JML) estimation is applied for simulataneous estimation of η, δ and all θ_i parameters. In the Rasch model, it was shown that JML can result in biased parameter estimates. The ε-adjustment approach has been proposed to reduce the bias in parameter estimates (Bertoli-Bersotti, Lando & Punzo, 2014). This estimation approach is adapted to the Bradley-Terry model in the btm function. To this end, the likelihood function is modified for the purpose of bias reduction. It can be easily shown that there exist sufficient statistics for η, δ and all θ_i parameters. In the ε-adjustment approach, the sufficient statistic for the θ_i parameter is modified. In JML estimation of the Bradley-Terry model, $S_i = \sum_{j \neq i}(x_{ij} + x_{ji})$ is a sufficient statistic for θ_i. Let M_i the maximum score for person i which is the number of x_{ij} terms appearing in S_i. In the ε-adjustment approach, the sufficient statistic S_i is modified to

$$S_{i,\varepsilon} = \varepsilon + \frac{M_i - 2\varepsilon}{M_i} S_i$$

and $S_{i,\varepsilon}$ instead of S_i is used in JML estimation. Hence, original scores S_i are linearly transformed for all persons i.

Value

List with following entries

pars	Parameter summary for η and δ
effects	Parameter estimates for θ and outfit and infit statistics
summary.effects	Summary of θ parameter estimates

`mle.rel`	MLE reliability, also known as separation reliability
`sepG`	Separation index G
`probs`	Estimated probabilities
`data`	Used dataset with integer identifiers
`fit_judges`	Fit statistics (outfit and infit) for judges if `judge` is provided. In addition, average agreement of the rating with the mode of the ratings is calculated for each judge (at least three ratings per dyad has to be available for computing the agreement).
`residuals`	Unstandardized and standardized residuals for each observation

References

Bertoli-Barsotti, L., Lando, T., & Punzo, A. (2014). Estimating a Rasch Model via fuzzy empirical probability functions. In D. Vicari, A. Okada, G. Ragozini & C. Weihs (Eds.). *Analysis and Modeling of Complex Data in Behavioral and Social Sciences*. Springer. doi:10.1007/9783319066929_4

Hunter, D. R. (2004). MM algorithms for generalized Bradley-Terry models. *Annals of Statistics, 32*, 384-406. doi: 10.1214/aos/1079120141

See Also

See also the R packages **BradleyTerry2**, **psychotools**, **psychomix** and **prefmod**.

Examples

```
##############################################################################
# EXAMPLE 1: Bradley-Terry model | data.pw01
##############################################################################

data(data.pw01)

dat <- data.pw01
dat <- dat[, c("home_team", "away_team", "result") ]

# recode results according to needed input
dat$result[ dat$result==0 ] <- 1/2   # code for ties
dat$result[ dat$result==2 ] <- 0     # code for victory of away team

#********************
# Model 1: Estimation with ties and home advantage
mod1 <- sirt::btm( dat)
summary(mod1)

## Not run:
#*** Model 2: Estimation with ties, no epsilon adjustment
mod2 <- sirt::btm( dat, eps=0)
summary(mod2)

#*** Model 3: Estimation with ties, no epsilon adjustment, weight for ties of .333 which
#    corresponds to the rule of 3 points for a victory and 1 point of a draw in football
mod3 <- sirt::btm( dat, eps=0, wgt.ties=1/3)
summary(mod3)
```

```
#*** Model 4: Some fixed abilities
fix.theta <- c("Anhalt Dessau"=-1 )
mod4 <- sirt::btm( dat, eps=0, fix.theta=fix.theta)
summary(mod4)

#*** Model 5: Ignoring ties, no home advantage effect
mod5 <- sirt::btm( dat, ignore.ties=TRUE, fix.eta=0)
summary(mod5)

#*** Model 6: Ignoring ties, no home advantage effect (JML approach and eps=0)
mod6 <- sirt::btm( dat, ignore.ties=TRUE, fix.eta=0, eps=0)
summary(mod5)

############################################################################
# EXAMPLE 2: Venice chess data
############################################################################

# See http://www.rasch.org/rmt/rmt113o.htm
# Linacre, J. M. (1997). Paired Comparisons with Standard Rasch Software.
# Rasch Measurement Transactions, 11:3, 584-585.

# dataset with chess games -> "D" denotes a draw (tie)
chessdata <- scan( what="character")
    1D.0..1...1....1.....1......D.......D........1.........1.......... Browne
    0.1.D..0...1....1.....1......D.......1........D.........1......... Mariotti
    .D0..0..1...D....D.....1......1.......1........1.........D........ Tatai
    ...1D1...D...D....1.....D......D.......D........1.........0....... Hort
    ......010D....D....D.....1......D.......1........1.........D...... Kavalek
    ..........00DDD.....D.....D......D.......1........D.........1..... Damjanovic
    ..............00D0DD......D......1.......1........1.........0.... Gligoric
    ......................000D0DD.......D.......1........D.........1... Radulov
    ............................DD0DDD0D........0........0.........1.. Bobotsov
    ....................................D00D00001.........1.........1. Cosulich
    ............................................0D000D0D10..........1 Westerinen
    ....................................................00D1D010000 Zichichi

L <- length(chessdata) / 2
games <- matrix( chessdata, nrow=L, ncol=2, byrow=TRUE )
G <- nchar(games[1,1])
# create matrix with results
results <- matrix( NA, nrow=G, ncol=3 )
for (gg in 1:G){
    games.gg <- substring( games[,1], gg, gg )
    ind.gg <- which( games.gg !="." )
    results[gg, 1:2 ] <- games[ ind.gg, 2]
    results[gg, 3 ] <- games.gg[ ind.gg[1] ]
}
results <- as.data.frame(results)
results[,3] <- paste(results[,3] )
results[ results[,3]=="D", 3] <- 1/2
results[,3] <- as.numeric( results[,3] )
```

```
# fit model ignoring draws
mod1 <- sirt::btm( results, ignore.ties=TRUE, fix.eta=0, eps=0 )
summary(mod1)

# fit model with draws
mod2 <- sirt::btm( results, fix.eta=0, eps=0 )
summary(mod2)

#############################################################################
# EXAMPLE 3: Simulated data from the Bradley-Terry model
#############################################################################

set.seed(9098)
N <- 22
theta <- seq(2,-2, len=N)

#** simulate and estimate data without repeated dyads
dat1 <- sirt::btm_sim(theta=theta)
mod1 <- sirt::btm( dat1, ignore.ties=TRUE, fix.delta=-99, fix.eta=0)
summary(mod1)

#*** simulate data with home advantage effect and ties
dat2 <- sirt::btm_sim(theta=theta, eta=.8, delta=-.6, repeated=TRUE)
mod2 <- sirt::btm(dat2)
summary(mod2)

#############################################################################
# EXAMPLE 4: Estimating the Bradley-Terry model with multiple judges
#############################################################################

#*** simulating data with multiple judges
set.seed(987)
N <- 26  # number of objects to be rated
theta <- seq(2,-2, len=N)
s1 <- stats::sd(theta)
dat <- NULL
# judge discriminations which define tendency to provide reliable ratings
discrim <- c( rep(.9,10), rep(.5,2), rep(0,2) )
#=> last four raters provide less reliable ratings

RR <- length(discrim)
for (rr in 1:RR){
    theta1 <- discrim[rr]*theta + stats::rnorm(N, mean=0, sd=s1*sqrt(1-discrim[rr]))
    dat1 <- sirt::btm_sim(theta1)
    dat1$judge <- rr
    dat <- rbind(dat, dat1)
}

#** estimate the Bradley-Terry model and compute judge-specific fit statistics
mod <- sirt::btm( dat[,1:3], judge=paste0("J",100+dat[,4]), fix.eta=0, ignore.ties=TRUE)
summary(mod)

## End(Not run)
```

categorize *Categorize and Decategorize Variables in a Data Frame*

Description

The function `categorize` defines categories for variables in a data frame, starting with a user-defined index (e.g. 0 or 1). Continuous variables can be categorized by defining categories by discretizing the variables in different quantile groups.

The function `decategorize` does the reverse operation.

Usage

```
categorize(dat, categorical=NULL, quant=NULL, lowest=0)

decategorize(dat, categ_design=NULL)
```

Arguments

`dat`	Data frame
`categorical`	Vector with variable names which should be converted into categories, beginning with integer `lowest`
`quant`	Vector with number of classes for each variables. Variables are categorized among quantiles. The vector must have names containing variable names.
`lowest`	Lowest category index. Default is 0.
`categ_design`	Data frame containing informations about categorization which is the output of `categorize`.

Value

For `categorize`, it is a list with entries

`data`	Converted data frame
`categ_design`	Data frame containing some informations about categorization

For `decategorize` it is a data frame.

Examples

```
## Not run:
library(mice)
library(miceadds)

#############################################################################
# EXAMPLE 1: Categorize questionnaire data
#############################################################################

data(data.smallscale, package="miceadds")
```

```
dat <- data.smallscale

# (0) select dataset
dat <- dat[, 9:20 ]
summary(dat)
categorical <- colnames(dat)[2:6]

# (1) categorize data
res <- sirt::categorize( dat, categorical=categorical )

# (2) multiple imputation using the mice package
dat2 <- res$data
VV <- ncol(dat2)
impMethod <- rep( "sample", VV )    # define random sampling imputation method
names(impMethod) <- colnames(dat2)
imp <- mice::mice( as.matrix(dat2), impMethod=impMethod, maxit=1, m=1 )
dat3 <- mice::complete(imp,action=1)

# (3) decategorize dataset
dat3a <- sirt::decategorize( dat3, categ_design=res$categ_design )

#############################################################################
# EXAMPLE 2: Categorize ordinal and continuous data
#############################################################################

data(data.ma01,package="miceadds")
dat <- data.ma01
summary(dat[,-c(1:2)] )

# define variables to be categorized
categorical <- c("books", "paredu" )
# define quantiles
quant <-  c(6,5,11)
names(quant) <- c("math", "read", "hisei")

# categorize data
res <- sirt::categorize( dat, categorical=categorical, quant=quant)
str(res)

## End(Not run)
```

---

ccov.np *Nonparametric Estimation of Conditional Covariances of Item Pairs*

Description

This function estimates conditional covariances of itempairs (Stout, Habing, Douglas & Kim, 1996; Zhang & Stout, 1999a). The function is used for the estimation of the DETECT index. The `ccov.np` function has the (default) option to smooth item response functions (argument `smooth`) in the computation of conditional covariances (Douglas, Kim, Habing, & Gao, 1998).

Usage

```
ccov.np(data, score, bwscale=1.1, thetagrid=seq(-3, 3, len=200),
    progress=TRUE, scale_score=TRUE, adjust_thetagrid=TRUE, smooth=TRUE,
    use_sum_score=FALSE, bias_corr=TRUE)
```

Arguments

`data`	An $N \times I$ data frame of dichotomous responses. Missing responses are allowed.
`score`	An ability estimate, e.g. the WLE
`bwscale`	Bandwidth factor for calculation of conditional covariance. The bandwidth used in the estimation is `bwscale` times $N^{-1/5}$.
`thetagrid`	A vector which contains theta values where conditional covariances are evaluated.
`progress`	Display progress?
`scale_score`	Logical indicating whether `score` should be z standardized in advance of the calculation of conditional covariances
`adjust_thetagrid`	Logical indicating whether `thetagrid` should be adjusted if observed values in `score` are outside of `thetagrid`.
`smooth`	Logical indicating whether smoothing should be applied for conditional covariance estimation
`use_sum_score`	Logical indicating whether sum score should be used. With this option, the bias corrected conditional covariance of Zhang and Stout (1999) is used.
`bias_corr`	Logical indicating whether bias correction (Zhang & Stout, 1999) should be utilized if `use_sum_score=TRUE`.

Note

This function is used in `conf.detect` and `expl.detect`.

References

Douglas, J., Kim, H. R., Habing, B., & Gao, F. (1998). Investigating local dependence with conditional covariance functions. *Journal of Educational and Behavioral Statistics, 23*(2), 129-151. doi:10.3102/10769986023002129

Stout, W., Habing, B., Douglas, J., & Kim, H. R. (1996). Conditional covariance-based nonparametric multidimensionality assessment. *Applied Psychological Measurement, 20*(4), 331-354. doi:10.1177/014662169602000403

Zhang, J., & Stout, W. (1999). Conditional covariance structure of generalized compensatory multidimensional items. *Psychometrika, 64*(2), 129-152. doi:10.1007/BF02294532

Examples

```
## Not run:
#############################################################################
# EXAMPLE 1: data.read | different settings for computing conditional covariance
```

```
#############################################################################

data(data.read, package="sirt")
dat <- data.read

#* fit Rasch model
mod <- sirt::rasch.mml2(dat)
score <- sirt::wle.rasch(dat=dat, b=mod$item$b)$theta

#* ccov with smoothing
cmod1 <- sirt::ccov.np(data=dat, score=score, bwscale=1.1)
#* ccov without smoothing
cmod2 <- sirt::ccov.np(data=dat, score=score, smooth=FALSE)

#- compare results
100*cbind( cmod1$ccov.table[1:6, "ccov"], cmod2$ccov.table[1:6, "ccov"])

## End(Not run)
```

`cfa_meas_inv` *Estimation of a Unidimensional Factor Model under Full and Partial Measurement Invariance*

Description

Estimates a unidimensional factor model based on the normal distribution fitting function under full and partial measurement invariance. Item loadings and item intercepts are successively freed based on the largest modification index and a chosen significance level `alpha`.

Usage

```
cfa_meas_inv(dat, group, weights=NULL, alpha=0.01, verbose=FALSE, op=c("~1","=~"))
```

Arguments

`dat`	Data frame containing items
`group`	Vector of group identifiers
`weights`	Optional vector of sampling weights
`alpha`	Significance level
`verbose`	Logical indicating whether progress should be shown
`op`	Operators (intercepts or loadings) for which estimation should be freed

Value

List with several entries

`pars_mi`	Model parameters under full invariance

pars_pi	Model parameters under partial invariance
mod_mi	Fitted model under full invariance
mod_pi	Fitted model under partial invariance
...	More output

See Also

See also sirt::invariance.alignment

Examples

```
## Not run:
#############################################################################
# EXAMPLE 1: Factor model under full and partial invariance
#############################################################################

#--- data simulation

set.seed(65)
G <- 3  # number of groups
I <- 5  # number of items
# define lambda and nu parameters
lambda <- matrix(1, nrow=G, ncol=I)
nu <- matrix(0, nrow=G, ncol=I)
err_var <- matrix(1, nrow=G, ncol=I)

# define size of noninvariance
dif <- 1
#- 1st group: N(0,1)
lambda[1,3] <- 1+dif*.4; nu[1,5] <- dif*.5
#- 2nd group: N(0.3,1.5)
gg <- 2 ;
lambda[gg,5] <- 1-.5*dif; nu[gg,1] <- -.5*dif
#- 3nd group: N(.8,1.2)
gg <- 3
lambda[gg,4] <- 1-.7*dif; nu[gg,2] <- -.5*dif
#- define distributions of groups
mu <- c(0,.3,.8)
sigma <- sqrt(c(1,1.5,1.2))
N <- rep(1000,3) # sample sizes per group

#* use simulation function
dat <- sirt::invariance_alignment_simulate(nu, lambda, err_var, mu, sigma, N,
                exact=TRUE)

#--- estimate CFA
mod <- sirt::cfa_meas_inv(dat=dat[,-1], group=dat$group, verbose=TRUE, alpha=0.05)
mod$pars_mi
mod$pars_pi

## End(Not run)
```

`class.accuracy.rasch` *Classification Accuracy in the Rasch Model*

Description

This function computes the classification accuracy in the Rasch model for the maximum likelihood (person parameter) estimate according to the method of Rudner (2001).

Usage

```
class.accuracy.rasch(cutscores, b, meantheta, sdtheta, theta.l, n.sims=0)
```

Arguments

`cutscores`	Vector of cut scores
`b`	Vector of item difficulties
`meantheta`	Mean of the trait distribution
`sdtheta`	Standard deviation of the trait distribution
`theta.l`	Discretized theta distribution
`n.sims`	Number of simulated persons in a data set. The default is 0 which means that no simulation is performed.

Value

A list with following entries:

`class.stats`	Data frame containing classification accuracy statistics. The column `agree0` refers to absolute agreement, `agree1` to the agreement of at most a difference of one level.
`class.prob`	Probability table of classification

References

Rudner, L.M. (2001). Computing the expected proportions of misclassified examinees. *Practical Assessment, Research & Evaluation, 7*(14).

See Also

Classification accuracy of other IRT models can be obtained with the R package **cacIRT**.

Examples

```
#############################################################################
# EXAMPLE 1: Reading dataset
#############################################################################
data( data.read, package="sirt")
dat <- data.read

# estimate the Rasch model
mod <- sirt::rasch.mml2( dat )

# estimate classification accuracy (3 levels)
cutscores <- c( -1, .3 )    # cut scores at theta=-1 and theta=.3
sirt::class.accuracy.rasch( cutscores=cutscores, b=mod$item$b,
           meantheta=0,  sdtheta=mod$sd.trait,
           theta.l=seq(-4,4,len=200), n.sims=3000)
  ##   Cut Scores
  ##   [1] -1.0  0.3
  ##
  ##   WLE reliability (by simulation)=0.671
  ##   WLE consistency (correlation between two parallel forms)=0.649
  ##
  ##   Classification accuracy and consistency
  ##               agree0 agree1 kappa consistency
  ##   analytical   0.68  0.990 0.492          NA
  ##   simulated    0.70  0.997 0.489       0.599
  ##
  ##   Probability classification table
  ##                Est_Class1 Est_Class2 Est_Class3
  ##   True_Class1      0.136      0.041      0.001
  ##   True_Class2      0.081      0.249      0.093
  ##   True_Class3      0.009      0.095      0.294
```

`conf.detect` *Confirmatory DETECT and polyDETECT Analysis*

Description

This function computes the DETECT statistics for dichotomous item responses and the polyDETECT statistic for polytomous item responses under a confirmatory specification of item clusters (Stout, Habing, Douglas & Kim, 1996; Zhang & Stout, 1999a, 1999b; Zhang, 2007; Bonifay, Reise, Scheines, & Meijer, 2015).

Item responses in a multi-matrix design are allowed (Zhang, 2013).

An exploratory DETECT analysis can be conducted using the `expl.detect` function.

Usage

```
conf.detect(data, score, itemcluster, bwscale=1.1, progress=TRUE,
     thetagrid=seq(-3, 3, len=200), smooth=TRUE, use_sum_score=FALSE, bias_corr=TRUE)
```

```
## S3 method for class 'conf.detect'
summary(object, digits=3, file=NULL, ...)
```

Arguments

data	An $N \times I$ data frame of dichotomous or polytomous responses. Missing responses are allowed.
score	An ability estimate, e.g. the WLE, sum score or mean score
itemcluster	Item cluster for each item. The order of entries must correspond to the columns in data.
bwscale	Bandwidth factor for calculation of conditional covariance (see ccov.np)
progress	Display progress?
smooth	Logical indicating whether smoothing should be applied for conditional covariance estimation
thetagrid	A vector which contains theta values where conditional covariances are evaluated.
use_sum_score	Logical indicating whether sum score should be used. With this option, the bias corrected conditional covariance of Zhang and Stout (1999) is used.
bias_corr	Logical indicating whether bias correction (Zhang & Stout, 1999) should be utilized if use_sum_score=TRUE.
object	Object of class conf.detect
digits	Number of digits for rounding in summary
file	Optional file name to be sunk for summary
...	Further arguments to be passed

Details

The result of DETECT are the indices DETECT, ASSI and RATIO (see Zhang 2007 for details) calculated for the options unweighted and weighted. The option unweighted means that all conditional covariances of item pairs are equally weighted, weighted means that these covariances are weighted by the sample size of item pairs. In case of multi matrix item designs, both types of indices can differ.

The classification scheme of these indices are as follows (Jang & Roussos, 2007; Zhang, 2007):

Strong multidimensionality	DETECT > 1.00
Moderate multidimensionality	.40 < DETECT < 1.00
Weak multidimensionality	.20 < DETECT < .40
Essential unidimensionality	DETECT < .20

Maximum value under simple structure	ASSI=1	RATIO=1
Essential deviation from unidimensionality	ASSI > .25	RATIO > .36
Essential unidimensionality	ASSI < .25	RATIO < .36

Note that the expected value of a conditional covariance for an item pair is negative when a unidimensional model holds. In consequence, the DETECT index can become negative for unidimensional data (see Example 3). This can be also seen in the statistic `MCOV100` in the value `detect`.

Value

A list with following entries:

`detect`	Data frame with statistics DETECT, ASSI, RATIO, MADCOV100 and MCOV100
`ccovtable`	Individual contributions to conditional covariance
`ccov.matrix`	Evaluated conditional covariance

References

Bonifay, W. E., Reise, S. P., Scheines, R., & Meijer, R. R. (2015). When are multidimensional data unidimensional enough for structural equation modeling? An evaluation of the DETECT multidimensionality index. *Structural Equation Modeling, 22*(4), 504-516. doi:10.1080/10705511.2014.938596

Jang, E. E., & Roussos, L. (2007). An investigation into the dimensionality of TOEFL using conditional covariance-based nonparametric approach. *Journal of Educational Measurement, 44*(1), 1-21. doi:10.1111/j.17453984.2007.00024.x

Stout, W., Habing, B., Douglas, J., & Kim, H. R. (1996). Conditional covariance-based nonparametric multidimensionality assessment. *Applied Psychological Measurement, 20*(4), 331-354. doi:10.1177/014662169602000403

Zhang, J. (2007). Conditional covariance theory and DETECT for polytomous items. *Psychometrika, 72*(1), 69-91. doi:10.1007/s1133600412577

Zhang, J. (2013). A procedure for dimensionality analyses of response data from various test designs. *Psychometrika, 78*(1), 37-58. doi:10.1007/s113360129287z

Zhang, J., & Stout, W. (1999a). Conditional covariance structure of generalized compensatory multidimensional items. *Psychometrika, 64*(2), 129-152. doi:10.1007/BF02294532

Zhang, J., & Stout, W. (1999b). The theoretical DETECT index of dimensionality and its application to approximate simple structure. *Psychometrika, 64*(2), 213-249. doi:10.1007/BF02294536

See Also

For a download of the free *DIM-Pack* software (DIMTEST, DETECT) see *https://psychometrics.onlinehelp.measuredprogres*

See `expl.detect` for exploratory DETECT analysis.

Examples

```
#############################################################################
# EXAMPLE 1: TIMSS mathematics data set (dichotomous data)
#############################################################################
data(data.timss)

# extract data
```

```
dat <- data.timss$data
dat <- dat[, substring( colnames(dat),1,1)=="M" ]
# extract item informations
iteminfo <- data.timss$item
# estimate Rasch model
mod1 <- sirt::rasch.mml2( dat )
# estimate WLEs
wle1 <- sirt::wle.rasch( dat, b=mod1$item$b )$theta

# DETECT for content domains
detect1 <- sirt::conf.detect( data=dat, score=wle1,
                    itemcluster=iteminfo$Content.Domain )
  ##          unweighted weighted
  ##   DETECT      0.316    0.316
  ##   ASSI        0.273    0.273
  ##   RATIO       0.355    0.355

## Not run:
# DETECT cognitive domains
detect2 <- sirt::conf.detect( data=dat, score=wle1,
                    itemcluster=iteminfo$Cognitive.Domain )
  ##          unweighted weighted
  ##   DETECT      0.251    0.251
  ##   ASSI        0.227    0.227
  ##   RATIO       0.282    0.282

# DETECT for item format
detect3 <- sirt::conf.detect( data=dat, score=wle1,
                    itemcluster=iteminfo$Format )
  ##          unweighted weighted
  ##   DETECT      0.056    0.056
  ##   ASSI        0.060    0.060
  ##   RATIO       0.062    0.062

# DETECT for item blocks
detect4 <- sirt::conf.detect( data=dat, score=wle1,
                    itemcluster=iteminfo$Block )
  ##          unweighted weighted
  ##   DETECT      0.301    0.301
  ##   ASSI        0.193    0.193
  ##   RATIO       0.339    0.339
## End(Not run)

# Exploratory DETECT: Application of a cluster analysis employing the Ward method
detect5 <- sirt::expl.detect( data=dat, score=wle1,
               nclusters=10, N.est=nrow(dat)  )
# Plot cluster solution
pl <- graphics::plot( detect5$clusterfit, main="Cluster solution" )
stats::rect.hclust(detect5$clusterfit, k=4, border="red")

## Not run:
#############################################################################
# EXAMPLE 2: Big 5 data set (polytomous data)
```

```
#############################################################################

# attach Big5 Dataset
data(data.big5)

# select 6 items of each dimension
dat <- data.big5
dat <- dat[, 1:30]

# estimate person score by simply using a transformed sum score
score <- stats::qnorm( ( rowMeans( dat )+.5 )  / ( 30 + 1 ) )

# extract item cluster (Big 5 dimensions)
itemcluster <- substring( colnames(dat), 1, 1 )

# DETECT Item cluster
detect1 <- sirt::conf.detect( data=dat, score=score, itemcluster=itemcluster )
  ##        unweighted weighted
  ## DETECT      1.256    1.256
  ## ASSI        0.384    0.384
  ## RATIO       0.597    0.597

# Exploratory DETECT
detect5 <- sirt::expl.detect( data=dat, score=score,
                    nclusters=9, N.est=nrow(dat)  )
  ## DETECT (unweighted)
  ## Optimal Cluster Size is  6  (Maximum of DETECT Index)
  ##   N.Cluster N.items N.est N.val      size.cluster DETECT.est ASSI.est RATIO.est
  ## 1         2      30   500     0              6-24      1.073    0.246     0.510
  ## 2         3      30   500     0           6-10-14      1.578    0.457     0.750
  ## 3         4      30   500     0         6-10-11-3      1.532    0.444     0.729
  ## 4         5      30   500     0        6-8-11-2-3      1.591    0.462     0.757
  ## 5         6      30   500     0       6-8-6-2-5-3      1.610    0.499     0.766
  ## 6         7      30   500     0     6-3-6-2-5-5-3      1.557    0.476     0.740
  ## 7         8      30   500     0   6-3-3-2-3-5-5-3      1.540    0.462     0.732
  ## 8         9      30   500     0 6-3-3-2-3-5-3-3-2      1.522    0.444     0.724

# Plot Cluster solution
pl <- graphics::plot( detect5$clusterfit, main="Cluster solution" )
stats::rect.hclust(detect5$clusterfit, k=6, border="red")

#############################################################################
# EXAMPLE 3: DETECT index for unidimensional data
#############################################################################

set.seed(976)
N <- 1000
I <- 20
b <- sample( seq( -2, 2, len=I) )
dat <- sirt::sim.raschtype( stats::rnorm(N), b=b )

# estimate Rasch model and corresponding WLEs
mod1 <- TAM::tam.mml( dat )
```

```
wmod1 <- TAM::tam.wle(mod1)$theta

# define item cluster
itemcluster <- c( rep(1,5), rep(2,I-5) )

# compute DETECT statistic
detect1 <- sirt::conf.detect( data=dat, score=wmod1, itemcluster=itemcluster)
  ##            unweighted weighted
  ##  DETECT        -0.184   -0.184
  ##  ASSI          -0.147   -0.147
  ##  RATIO         -0.226   -0.226
  ##  MADCOV100      0.816    0.816
  ##  MCOV100       -0.786   -0.786

## End(Not run)
```

`data.activity.itempars`

Item Parameters Cultural Activities

Description

List with item parameters for cultural activities of Austrian students for 9 Austrian countries.

Usage

```
data(data.activity.itempars)
```

Format

The format is a list with number of students per group (`N`), item loadings (`lambda`) and item intercepts (`nu`):

```
List of 3
$ N : 'table' int [1:9(1d)] 2580 5279 15131 14692 5525 11005 7080 ...
..- attr(*, "dimnames")=List of 1
.. ..$ : chr [1:9] "1" "2" "3" "4" ...
$ lambda: num [1:9, 1:5] 0.423 0.485 0.455 0.437 0.502 ...
..- attr(*, "dimnames")=List of 2
.. ..$ : chr [1:9] "country1" "country2" "country3" "country4" ...
.. ..$ : chr [1:5] "act1" "act2" "act3" "act4" ...
$ nu : num [1:9, 1:5] 1.65 1.53 1.7 1.59 1.7 ...
..- attr(*, "dimnames")=List of 2
.. ..$ : chr [1:9] "country1" "country2" "country3" "country4" ...
.. ..$ : chr [1:5] "act1" "act2" "act3" "act4" ...
```

`data.befki` *BEFKI Dataset (Schroeders, Schipolowski, & Wilhelm, 2015)*

Description

The synthetic dataset is based on the standardization sample of the Berlin Test of Fluid and Crystallized Intelligence (BEFKI, Wilhelm, Schroeders, & Schipolowski, 2014). The underlying sample consists of N=11,756 students from all German federal states (except for the smallest one) and all school types of the general educational system attending Grades 5 to 12. A detailed description of the study, the sample, and the measure is given in Schroeders, Schipolowski, and Wilhelm (2015).

Usage

```
data(data.befki)
data(data.befki_resp)
```

Format

- The dataset `data.befki` contains 11756 students, nested within 581 classes.

```
'data.frame': 11756 obs. of 12 variables:
$ idclass: int 1276 1276 1276 1276 1276 1276 1276 1276 1276 1276 ...
$ idstud : int 127601 127602 127603 127604 127605 127606 127607 127608 127609 127610
...
$ grade : int 5 5 5 5 5 5 5 5 5 5 ...
$ gym : int 0 0 0 0 0 0 0 0 0 0 ...
$ female : int 0 1 0 0 0 0 1 0 0 0 ...
$ age : num 12.2 11.8 11.5 10.8 10.9 ...
$ sci : num -3.14 -3.44 -2.62 -2.16 -1.01 -1.91 -1.01 -4.13 -2.16 -3.44 ...
$ hum : num -1.71 -1.29 -2.29 -2.48 -0.65 -0.92 -1.71 -2.31 -1.99 -2.48 ...
$ soc : num -2.87 -3.35 -3.81 -2.35 -1.32 -1.11 -1.68 -2.96 -2.69 -3.35 ...
$ gfv : num -2.25 -2.19 -2.25 -1.17 -2.19 -3.05 -1.7 -2.19 -3.05 -1.7 ...
$ gfn : num -2.2 -1.85 -1.85 -1.85 -1.85 -0.27 -1.37 -2.58 -1.85 -3.13 ...
$ gff : num -0.91 -0.43 -1.17 -1.45 -0.61 -1.78 -1.17 -1.78 -1.78 -3.87 ...
```

- The dataset `data.befki_resp` contains response indicators for observed data points in the dataset `data.befki`.

```
 num [1:11756, 1:12] 1 1 1 1 1 1 1 1 1 1 ...
- attr(*, "dimnames")=List of 2
..$ : NULL
..$ : chr [1:12] "idclass" "idstud" "grade" "gym" ...
```

Details

The procedure for generating this dataset is based on a factorization of the joint distribution. All variables are simulated from unidimensional conditional parametric regression models including

several interaction and quadratic terms. The multilevel structure is approximated by including cluster means as predictors in the regression models.

Source

Synthetic dataset

References

Schroeders, U., Schipolowski, S., & Wilhelm, O. (2015). Age-related changes in the mean and covariance structure of fluid and crystallized intelligence in childhood and adolescence. *Intelligence, 48*, 15-29. doi:10.1016/j.intell.2014.10.006

Wilhelm, O., Schroeders, U., & Schipolowski, S. (2014). *Berliner Test zur Erfassung fluider und kristalliner Intelligenz fuer die 8. bis 10. Jahrgangsstufe* [Berlin test of fluid and crystallized intelligence for grades 8-10]. Goettingen: Hogrefe.

---

data.big5 *Dataset Big 5 from* **qgraph** *Package*

Description

This is a Big 5 dataset from the **qgraph** package (Dolan, Oorts, Stoel, Wicherts, 2009). It contains 500 subjects on 240 items.

Usage

```
data(data.big5)
data(data.big5.qgraph)
```

Format

- The format of `data.big5` is:

```
num [1:500, 1:240] 1 0 0 0 0 1 1 2 0 1 ...
- attr(*, "dimnames")=List of 2
..$ : NULL
..$ : chr [1:240] "N1" "E2" "O3" "A4" ...
```

- The format of `data.big5.qgraph` is:

```
 num [1:500, 1:240] 2 3 4 4 5 2 2 1 4 2 ...
- attr(*, "dimnames")=List of 2
..$ : NULL
..$ : chr [1:240] "N1" "E2" "O3" "A4" ...
```

Details

In these datasets, there exist 48 items for each dimension. The Big 5 dimensions are Neuroticism (N), Extraversion (E), Openness (O), Agreeableness (A) and Conscientiousness (C). Note that the data.big5 differs from data.big5.qgraph in a way that original items were recoded into three categories 0,1 and 2.

Source

See big5 in **qgraph** package.

References

Dolan, C. V., Oort, F. J., Stoel, R. D., & Wicherts, J. M. (2009). Testing measurement invariance in the target rotates multigroup exploratory factor model. *Structural Equation Modeling, 16*, 295-314.

Examples

```
## Not run:
# list of needed packages for the following examples
packages <- scan(what="character")
     sirt   TAM   eRm   CDM   mirt  ltm   mokken  psychotools  psychomix
     psych

# load packages. make an installation if necessary
miceadds::library_install(packages)

#############################################################################
# EXAMPLE 1: Unidimensional models openness scale
#############################################################################

data(data.big5)
# extract first 10 openness items
items <- which( substring( colnames(data.big5), 1, 1 )=="O"  )[1:10]
dat <- data.big5[, items ]
I <- ncol(dat)
summary(dat)
  ##   > colnames(dat)
  ##    [1] "O3"  "O8"  "O13" "O18" "O23" "O28" "O33" "O38" "O43" "O48"
# descriptive statistics
psych::describe(dat)

#****************
# Model 1: Partial credit model
#****************

#-- M1a: rm.facets (in sirt)
m1a <- sirt::rm.facets( dat )
summary(m1a)

#-- M1b: tam.mml (in TAM)
m1b <- TAM::tam.mml( resp=dat )
```

```
summary(m1b)

#-- M1c: gdm (in CDM)
theta.k <- seq(-6,6,len=21)
m1c <- CDM::gdm( dat, irtmodel="1PL",theta.k=theta.k, skillspace="normal")
summary(m1c)
# compare results with loglinear skillspace
m1c2 <- CDM::gdm( dat, irtmodel="1PL",theta.k=theta.k, skillspace="loglinear")
summary(m1c2)

#-- M1d: PCM (in eRm)
m1d <- eRm::PCM( dat )
summary(m1d)

#-- M1e: gpcm (in ltm)
m1e <- ltm::gpcm( dat, constraint="1PL", control=list(verbose=TRUE))
summary(m1e)

#-- M1f: mirt (in mirt)
m1f <- mirt::mirt( dat, model=1, itemtype="1PL", verbose=TRUE)
summary(m1f)
coef(m1f)

#-- M1g: PCModel.fit (in psychotools)
mod1g <- psychotools::PCModel.fit(dat)
summary(mod1g)
plot(mod1g)

#*****************
# Model 2: Generalized partial credit model
#*****************

#-- M2a: rm.facets (in sirt)
m2a <- sirt::rm.facets( dat, est.a.item=TRUE)
summary(m2a)
# Note that in rm.facets the mean of item discriminations is fixed to 1

#-- M2b: tam.mml.2pl (in TAM)
m2b <- TAM::tam.mml.2pl( resp=dat, irtmodel="GPCM")
summary(m2b)

#-- M2c: gdm (in CDM)
m2c <- CDM::gdm( dat, irtmodel="2PL",theta.k=seq(-6,6,len=21),
                   skillspace="normal", standardized.latent=TRUE)
summary(m2c)

#-- M2d: gpcm (in ltm)
m2d <- ltm::gpcm( dat, control=list(verbose=TRUE))
summary(m2d)

#-- M2e: mirt (in mirt)
m2e <- mirt::mirt( dat, model=1,  itemtype="GPCM", verbose=TRUE)
summary(m2e)
```

```
coef(m2e)

#*****************
# Model 3: Nonparametric item response model
#*****************

#-- M3a: ISOP and ADISOP model - isop.poly (in sirt)
m3a <- sirt::isop.poly( dat )
summary(m3a)
plot(m3a)

#-- M3b: Mokken scale analysis (in mokken)
# Scalability coefficients
mokken::coefH(dat)
# Assumption of monotonicity
monotonicity.list <- mokken::check.monotonicity(dat)
summary(monotonicity.list)
plot(monotonicity.list)
# Assumption of non-intersecting ISRFs using method restscore
restscore.list <- mokken::check.restscore(dat)
summary(restscore.list)
plot(restscore.list)

#*****************
# Model 4: Graded response model
#*****************

#-- M4a: mirt (in mirt)
m4a <- mirt::mirt( dat, model=1,  itemtype="graded", verbose=TRUE)
print(m4a)
mirt.wrapper.coef(m4a)

#----  M4b: WLSMV estimation with cfa (in lavaan)
lavmodel <- "F=~ O3__O48
             F ~~ 1*F
                "
# transform lavaan syntax with lavaanify.IRT
lavmodel <- TAM::lavaanify.IRT( lavmodel, items=colnames(dat) )$lavaan.syntax
mod4b <- lavaan::cfa( data=as.data.frame(dat), model=lavmodel, std.lv=TRUE,
                 ordered=colnames(dat),  parameterization="theta")
summary(mod4b, standardized=TRUE, fit.measures=TRUE, rsquare=TRUE)
coef(mod4b)

#*****************
# Model 5: Normally distributed residuals
#*****************

#----  M5a: cfa (in lavaan)
lavmodel <- "F=~ O3__O48
             F ~~ 1*F
             F ~ 0*1
             O3__O48 ~ 1
                "
```

```
lavmodel <- TAM::lavaanify.IRT( lavmodel, items=colnames(dat) )$lavaan.syntax
mod5a <- lavaan::cfa( data=as.data.frame(dat), model=lavmodel, std.lv=TRUE,
                estimator="MLR" )
summary(mod5a, standardized=TRUE, fit.measures=TRUE, rsquare=TRUE)

#----  M5b: mirt (in mirt)

# create user defined function
name <- 'normal'
par <- c("d"=1, "a1"=0.8, "vy"=1)
est <- c(TRUE, TRUE,FALSE)
P.normal <- function(par,Theta,ncat){
     d <- par[1]
     a1 <- par[2]
     vy <- par[3]
     psi <- vy - a1^2
     # expected values given Theta
     mui <- a1*Theta[,1] + d
     TP <- nrow(Theta)
     probs <- matrix( NA, nrow=TP, ncol=ncat )
     eps <- .01
     for (cc in 1:ncat){
        probs[,cc] <- stats::dnorm( cc, mean=mui, sd=sqrt( abs( psi + eps) ) )
                    }
     psum <- matrix( rep(rowSums( probs ),each=ncat), nrow=TP, ncol=ncat, byrow=TRUE)
     probs <- probs / psum
     return(probs)
}

# create item response function
normal <- mirt::createItem(name, par=par, est=est, P=P.normal)
customItems <- list("normal"=normal)
itemtype <- rep( "normal",I)
# define parameters to be estimated
mod5b.pars <- mirt::mirt(dat, 1, itemtype=itemtype,
                  customItems=customItems, pars="values")
ind <- which( mod5b.pars$name=="vy")
vy <- apply( dat, 2, var, na.rm=TRUE )
mod5b.pars[ ind, "value" ] <- vy
ind <- which( mod5b.pars$name=="a1")
mod5b.pars[ ind, "value" ] <- .5* sqrt(vy)
ind <- which( mod5b.pars$name=="d")
mod5b.pars[ ind, "value" ] <- colMeans( dat, na.rm=TRUE )

# estimate model
mod5b <- mirt::mirt(dat, 1, itemtype=itemtype, customItems=customItems,
                pars=mod5b.pars, verbose=TRUE    )
sirt::mirt.wrapper.coef(mod5b)$coef

# some item plots
    par(ask=TRUE)
plot(mod5b, type='trace', layout=c(1,1))
    par(ask=FALSE)
```

```
# Alternatively:
sirt::mirt.wrapper.itemplot(mod5b)

## End(Not run)
```

`data.bs` *Datasets from Borg and Staufenbiel (2007)*

Description

Datasets of the book of Borg and Staufenbiel (2007) *Lehrbuch Theorien and Methoden der Skalierung*.

Usage

```
data(data.bs07a)
```

Format

- The dataset `data.bs07a` contains the data *Gefechtsangst* (p. 130) and contains 8 of the original 9 items. The items are symptoms of anxiety in engagement.
  `GF1`: starkes Herzklopfen, `GF2`: flaues Gefuehl in der Magengegend, `GF3`: Schwaechegefuehl, `GF4`: Uebelkeitsgefuehl, `GF5`: Erbrechen, `GF6`: Schuettelfrost, `GF7`: in die Hose urinieren/einkoten, `GF9`: Gefuehl der Gelaehmtheit

  The format is

  ```
  'data.frame': 100 obs. of 9 variables:
  $ idpatt: int 44 29 1 3 28 50 50 36 37 25 ...
  $ GF1 : int 1 1 1 1 1 0 0 1 1 1 ...
  $ GF2 : int 0 1 1 1 1 0 0 1 1 1 ...
  $ GF3 : int 0 0 1 1 0 0 0 0 0 1 ...
  $ GF4 : int 0 0 1 1 0 0 0 1 0 1 ...
  $ GF5 : int 0 0 1 1 0 0 0 0 0 0 ...
  $ GF6 : int 1 1 1 1 1 0 0 0 0 0 ...
  $ GF7 : num 0 0 1 1 0 0 0 0 0 0 ...
  $ GF9 : int 0 0 1 1 1 0 0 0 0 0 ...
  ```

- *MORE DATASETS*

References

Borg, I., & Staufenbiel, T. (2007). *Lehrbuch Theorie und Methoden der Skalierung*. Bern: Hogrefe.

Examples

```
## Not run:
#############################################################################
# EXAMPLE 07a: Dataset Gefechtsangst
#############################################################################
```

```
data(data.bs07a)
dat <- data.bs07a
items <- grep( "GF", colnames(dat), value=TRUE )

#************************
# Model 1: Rasch model
mod1 <- TAM::tam.mml(dat[,items] )
summary(mod1)
IRT.WrightMap(mod1)

#************************
# Model 2: 2PL model
mod2 <- TAM::tam.mml.2pl(dat[,items] )
summary(mod2)

#************************
# Model 3: Latent class analysis (LCA) with two classes
tammodel <- "
ANALYSIS:
  TYPE=LCA;
  NCLASSES(2)
  NSTARTS(5,10)
LAVAAN MODEL:
  F=~ GF1__GF9
  "
mod3 <- TAM::tamaan( tammodel, dat )
summary(mod3)

#************************
# Model 4: LCA with three classes
tammodel <- "
ANALYSIS:
  TYPE=LCA;
  NCLASSES(3)
  NSTARTS(5,10)
LAVAAN MODEL:
  F=~ GF1__GF9
  "
mod4 <- TAM::tamaan( tammodel, dat )
summary(mod4)

#************************
# Model 5: Located latent class model (LOCLCA) with two classes
tammodel <- "
ANALYSIS:
  TYPE=LOCLCA;
  NCLASSES(2)
  NSTARTS(5,10)
LAVAAN MODEL:
  F=~ GF1__GF9
  "
mod5 <- TAM::tamaan( tammodel, dat )
summary(mod5)
```

```
#************************
# Model 6: Located latent class model with three classes
tammodel <- "
ANALYSIS:
  TYPE=LOCLCA;
  NCLASSES(3)
  NSTARTS(5,10)
LAVAAN MODEL:
  F=~ GF1__GF9
  "
mod6 <- TAM::tamaan( tammodel, dat )
summary(mod6)

#************************
# Model 7: Probabilistic Guttman model
mod7 <- sirt::prob.guttman( dat[,items] )
summary(mod7)

#-- model comparison
IRT.compareModels( mod1, mod2, mod3, mod4, mod5, mod6, mod7 )

## End(Not run)
```

`data.eid` *Examples with Datasets from Eid and Schmidt (2014)*

Description

Examples with datasets from Eid and Schmidt (2014), illustrations with several R packages. The examples follow closely the online material of Hosoya (2014). The datasets are completely synthetic datasets which were resimulated from the originally available data.

Usage

```
data(data.eid.kap4)
data(data.eid.kap5)
data(data.eid.kap6)
data(data.eid.kap7)
```

Format

- `data.eid.kap4` is the dataset from Chapter 4.

  ```
  'data.frame': 193 obs. of 11 variables:
  $ sex : int 0 0 0 0 0 0 1 0 0 1 ...
  $ Freude_1: int 1 1 1 0 1 1 1 1 1 1 ...
  $ Wut_1 : int 1 1 1 0 1 1 1 1 1 1 ...
  $ Angst_1 : int 1 0 0 0 1 1 1 0 1 0 ...
  $ Trauer_1: int 1 1 1 0 1 1 1 1 1 1 ...
  ```

```
$ Ueber_1 : int 1 1 1 0 1 1 0 1 1 1 ...
$ Trauer_2: int 0 1 1 1 1 1 1 1 1 0 ...
$ Angst_2 : int 0 0 1 0 0 1 0 0 0 0 ...
$ Wut_2 : int 1 1 1 1 1 1 1 1 1 1 ...
$ Ueber_2 : int 1 0 1 0 1 1 1 0 1 1 ...
$ Freude_2: int 1 1 1 0 1 1 1 1 1 1 ...
```

- `data.eid.kap5` is the dataset from Chapter 5.

```
'data.frame': 499 obs. of 7 variables:
$ sex : int 0 0 0 0 1 1 1 0 0 0 ...
$ item_1: int 2 3 3 2 4 1 0 0 0 2 ...
$ item_2: int 1 1 4 1 3 3 2 1 2 3 ...
$ item_3: int 1 3 3 2 3 3 0 0 0 1 ...
$ item_4: int 2 4 3 4 3 3 3 2 0 2 ...
$ item_5: int 1 3 2 2 0 0 0 0 1 2 ...
$ item_6: int 4 3 4 3 4 3 2 1 1 3 ...
```

- `data.eid.kap6` is the dataset from Chapter 6.

```
'data.frame': 238 obs. of 7 variables:
$ geschl: int 1 1 0 0 0 1 0 1 1 0 ...
$ item_1: int 3 3 3 3 2 0 1 4 3 3 ...
$ item_2: int 2 2 2 2 2 0 2 3 1 3 ...
$ item_3: int 2 2 1 3 2 0 0 3 1 3 ...
$ item_4: int 2 3 3 3 3 0 2 4 3 4 ...
$ item_5: int 1 2 1 2 2 0 1 2 2 2 ...
$ item_6: int 2 2 2 2 2 0 1 2 1 2 ...
```

- `data.eid.kap7` is the dataset *Emotionale Klarheit* from Chapter 7.

```
'data.frame': 238 obs. of 9 variables:
$ geschl : int 1 0 1 1 0 1 0 1 0 1 ...
$ reakt_1: num 2.13 1.78 1.28 1.82 1.9 1.63 1.73 1.49 1.43 1.27 ...
$ reakt_2: num 1.2 1.73 0.95 1.5 1.99 1.75 1.58 1.71 1.41 0.96 ...
$ reakt_3: num 1.77 1.42 0.76 1.54 2.36 1.84 2.06 1.21 1.75 0.92 ...
$ reakt_4: num 2.18 1.28 1.39 1.82 2.09 2.15 2.1 1.13 1.71 0.78 ...
$ reakt_5: num 1.47 1.7 1.08 1.77 1.49 1.73 1.96 1.76 1.88 1.1 ...
$ reakt_6: num 1.63 0.9 0.82 1.63 1.79 1.37 1.79 1.11 1.27 1.06 ...
$ kla_th1: int 8 11 11 8 10 11 12 5 6 12 ...
$ kla_th2: int 7 11 12 8 10 11 12 5 8 11 ...
```

Source

The material and original datasets can be downloaded from *http://www.hogrefe.de/buecher/lehrbuecher/psychlehrbuchplus/le*
testtheorie-und-testkonstruktion/zusatzmaterial/.

References

Eid, M., & Schmidt, K. (2014). *Testtheorie und Testkonstruktion*. Goettingen, Hogrefe.

Hosoya, G. (2014). *Einfuehrung in die Analyse testtheoretischer Modelle mit* R. Available at *http://www.hogrefe.de/buecher/lehrbuecher/psychlehrbuchplus/lehrbuecher/testtheorie-und-testkonstruktion/zusatzmaterial/*

Examples

```
## Not run:
miceadds::library_install("foreign")
#---- load some IRT packages in R
miceadds::library_install("TAM")        # package (a)
miceadds::library_install("mirt")       # package (b)
miceadds::library_install("sirt")       # package (c)
miceadds::library_install("eRm")        # package (d)
miceadds::library_install("ltm")        # package (e)
miceadds::library_install("psychomix")  # package (f)

############################################################################
# EXAMPLES Ch. 4: Unidimensional IRT models | dichotomous data
############################################################################

data(data.eid.kap4)
data0 <- data.eid.kap4

# load data
data0 <- foreign::read.spss( linkname, to.data.frame=TRUE, use.value.labels=FALSE)
# extract items
dat <- data0[,2:11]

#*********************************************************
# Model 1: Rasch model
#*********************************************************

#-----------
#-- 1a: estimation with TAM package

# estimation with tam.mml
mod1a <- TAM::tam.mml(dat)
summary(mod1a)

# person parameters in TAM
pp1a <- TAM::tam.wle(mod1a)

# plot item response functions
plot(mod1a,export=FALSE,ask=TRUE)

# Infit and outfit in TAM
itemf1a <- TAM::tam.fit(mod1a)
itemf1a

# model fit
modf1a <- TAM::tam.modelfit(mod1a)
summary(modf1a)

#-----------
```

```
#-- 1b: estimation with mirt package

# estimation with mirt
mod1b <- mirt::mirt( dat, 1, itemtype="Rasch")
summary(mod1b)
print(mod1b)

# person parameters
pp1b <- mirt::fscores(mod1b, method="WLE")

# extract coefficients
sirt::mirt.wrapper.coef(mod1b)

# plot item response functions
plot(mod1b, type="trace" )
par(mfrow=c(1,1))

# item fit
itemf1b <- mirt::itemfit(mod1b)
itemf1b

# model fit
modf1b <- mirt::M2(mod1b)
modf1b

#-----------
#-- 1c: estimation with sirt package

# estimation with rasch.mml2
mod1c <- sirt::rasch.mml2(dat)
summary(mod1c)

# person parameters (EAP)
pp1c <- mod1c$person

# plot item response functions
plot(mod1c, ask=TRUE )

# model fit
modf1c <- sirt::modelfit.sirt(mod1c)
summary(modf1c)

#-----------
#-- 1d: estimation with eRm package

# estimation with RM
mod1d <- eRm::RM(dat)
summary(mod1d)

# estimation person parameters
pp1d <- eRm::person.parameter(mod1d)
summary(pp1d)
```

```
# plot item response functions
eRm::plotICC(mod1d)

# person-item map
eRm::plotPImap(mod1d)

# item fit
itemf1d <- eRm::itemfit(pp1d)

# person fit
persf1d <- eRm::personfit(pp1d)

#-----------
#-- 1e: estimation with ltm package

# estimation with rasch
mod1e <- ltm::rasch(dat)
summary(mod1e)

# estimation person parameters
pp1e <- ltm::factor.scores(mod1e)

# plot item response functions
plot(mod1e)

# item fit
itemf1e <- ltm::item.fit(mod1e)

# person fit
persf1e <- ltm::person.fit(mod1e)

# goodness of fit with Bootstrap
modf1e <- ltm::GoF.rasch(mod1e,B=20)    # use more bootstrap samples
modf1e

#*********************************************************
# Model 2: 2PL model
#*********************************************************

#-----------
#-- 2a: estimation with TAM package

# estimation
mod2a <- TAM::tam.mml.2pl(dat)
summary(mod2a)

# model fit
modf2a <- TAM::tam.modelfit(mod2a)
summary(modf2a)

# item response functions
plot(mod2a, export=FALSE, ask=TRUE)
```

```
# model comparison
anova(mod1a,mod2a)

#-----------
#-- 2b: estimation with mirt package

# estimation
mod2b <- mirt::mirt(dat,1,itemtype="2PL")
summary(mod2b)
print(mod2b)
sirt::mirt.wrapper.coef(mod2b)

# model fit
modf2b <- mirt::M2(mod2b)
modf2b

#-----------
#-- 2c: estimation with sirt package

I <- ncol(dat)
# estimation
mod2c <- sirt::rasch.mml2(dat,est.a=1:I)
summary(mod2c)

# model fit
modf2c <- sirt::modelfit.sirt(mod2c)
summary(modf2c)

#-----------
#-- 2e: estimation with ltm package

# estimation
mod2e <- ltm::ltm(dat ~ z1 )
summary(mod2e)

# item response functions
plot(mod2e)

#*********************************************************
# Model 3: Mixture Rasch model
#*********************************************************

#-----------
#-- 3a: estimation with TAM package

# avoid "_" in column names if the "__" operator is used in
# the tamaan syntax
dat1 <- dat
colnames(dat1) <- gsub("_", "", colnames(dat1) )
# define tamaan model
tammodel <- "
ANALYSIS:
  TYPE=MIXTURE ;
```

```
  NCLASSES(2);
  NSTARTS(20,25);   # 20 random starts with 25 initial iterations each
LAVAAN MODEL:
  F=~ Freude1__Freude2
  F ~~ F
ITEM TYPE:
  ALL(Rasch);
    "
mod3a <- TAM::tamaan( tammodel, resp=dat1 )
summary(mod3a)
# extract item parameters
ipars <- mod2$itempartable_MIXTURE[ 1:10, ]
plot( 1:10, ipars[,3], type="o", ylim=range( ipars[,3:4] ), pch=16,
        xlab="Item", ylab="Item difficulty")
lines( 1:10, ipars[,4], type="l", col=2, lty=2)
points( 1:10, ipars[,4],  col=2, pch=2)

#-----------
#-- 3f: estimation with psychomix package

# estimation
mod3f <- psychomix::raschmix( as.matrix(dat), k=2, scores="meanvar")
summary(mod3f)
# plot class-specific item difficulties
plot(mod3f)

############################################################################
# EXAMPLES Ch. 5: Unidimensional IRT models | polytomous data
############################################################################

data(data.eid.kap5)
data0 <- data.eid.kap5
# extract items
dat <- data0[,2:7]

#*********************************************************
# Model 1: Partial credit model
#*********************************************************

#-----------
#-- 1a: estimation with TAM package

# estimation with tam.mml
mod1a <- TAM::tam.mml(dat)
summary(mod1a)

# person parameters in TAM
pp1a <- tam.wle(mod1a)

# plot item response functions
plot(mod1a,export=FALSE,ask=TRUE)

# Infit and outfit in TAM
```

```
itemf1a <- TAM::tam.fit(mod1a)
itemf1a

# model fit
modf1a <- TAM::tam.modelfit(mod1a)
summary(modf1a)

#-----------
#-- 1b: estimation with mirt package

# estimation with tam.mml
mod1b <- mirt::mirt( dat, 1, itemtype="Rasch")
summary(mod1b)
print(mod1b)
sirt::mirt.wrapper.coef(mod1b)

# plot item response functions
plot(mod1b, type="trace" )
par(mfrow=c(1,1))

# item fit
itemf1b <- mirt::itemfit(mod1b)
itemf1b

#-----------
#-- 1c: estimation with sirt package

# estimation with rm.facets
mod1c <- sirt::rm.facets(dat)
summary(mod1c)
summary(mod1a)

#-----------
#-- 1d: estimation with eRm package

# estimation
mod1d <- eRm::PCM(dat)
summary(mod1d)

# plot item response functions
eRm::plotICC(mod1d)

# person-item map
eRm::plotPImap(mod1d)

# item fit
itemf1d <- eRm::itemfit(pp1d)

#-----------
#-- 1e: estimation with ltm package

# estimation
mod1e <- ltm::gpcm(dat, constraint="1PL")
```

```
summary(mod1e)
# plot item response functions
plot(mod1e)

#*********************************************************
# Model 2: Generalized partial credit model
#*********************************************************

#-----------
#-- 2a: estimation with TAM package

# estimation with tam.mml
mod2a <- TAM::tam.mml.2pl(dat, irtmodel="GPCM")
summary(mod2a)

# model fit
modf2a <- TAM::tam.modelfit(mod2a)
summary(modf2a)

#-----------
#-- 2b: estimation with mirt package

# estimation
mod2b <- mirt::mirt( dat, 1, itemtype="gpcm")
summary(mod2b)
print(mod2b)
sirt::mirt.wrapper.coef(mod2b)

#-----------
#-- 2c: estimation with sirt package

# estimation with rm.facets
mod2c <- sirt::rm.facets(dat, est.a.item=TRUE)
summary(mod2c)

#-----------
#-- 2e: estimation with ltm package

# estimation
mod2e <- ltm::gpcm(dat)
summary(mod2e)
plot(mod2e)

## End(Not run)
```

`data.ess2005` *Dataset European Social Survey 2005*

Description

This dataset contains item loadings λ and intercepts ν for 26 countries for the European Social Survey (ESS 2005; see Asparouhov & Muthen, 2014).

Usage

```
data(data.ess2005)
```

Format

The format of the dataset is:

```
List of 2
$ lambda: num [1:26, 1:4] 0.688 0.721 0.72 0.687 0.625 ...
..- attr(*, "dimnames")=List of 2
.. ..$ : NULL
.. ..$ : chr [1:4] "ipfrule" "ipmodst" "ipbhprp" "imptrad"
$ nu : num [1:26, 1:4] 3.26 2.52 3.41 2.84 2.79 ...
..- attr(*, "dimnames")=List of 2
.. ..$ : NULL
.. ..$ : chr [1:4] "ipfrule" "ipmodst" "ipbhprp" "imptrad"
```

References

Asparouhov, T., & Muthen, B. (2014). Multiple-group factor analysis alignment. *Structural Equation Modeling, 21*(4), 1-14. doi:10.1080/10705511.2014.919210

`data.g308` *C-Test Datasets*

Description

Some datasets of C-tests are provided. The dataset `data.g308` was used in Schroeders, Robitzsch and Schipolowski (2014).

Usage

```
data(data.g308)
```

Format

- The dataset `data.g308` is a C-test containing 20 items and is used in Schroeders, Robitzsch and Schipolowski (2014) and is of the following format

```
'data.frame': 747 obs. of 21 variables:
$ id : int 1 2 3 4 5 6 7 8 9 10 ...
$ G30801: int 1 1 1 1 1 0 0 1 1 1 ...
```

```
$ G30802: int 1 1 1 1 1 1 1 1 1 1 ...
$ G30803: int 1 1 1 1 1 1 1 1 1 1 ...
$ G30804: int 1 1 1 1 1 0 1 1 1 1 ...
[...]
$ G30817: int 0 0 0 0 1 0 1 0 1 0 ...
$ G30818: int 0 0 1 0 0 0 0 1 1 0 ...
$ G30819: int 1 1 1 1 0 0 1 1 1 0 ...
$ G30820: int 1 1 1 1 0 0 0 1 1 0 ...
```

References

Schroeders, U., Robitzsch, A., & Schipolowski, S. (2014). A comparison of different psychometric approaches to modeling testlet structures: An example with C-tests. *Journal of Educational Measurement, 51*(4), 400-418.

Examples

```
## Not run:
#############################################################################
# EXAMPLE 1: Dataset G308 from Schroeders et al. (2014)
#############################################################################

data(data.g308)
dat <- data.g308

library(TAM)
library(sirt)

# define testlets
testlet <- c(1, 1, 2, 2, 2, 2, 2, 2, 3, 3, 4, 4, 4, 4, 4, 5, 5, 6, 6, 6)

#****************************************
#*** Model 1: Rasch model
mod1 <- TAM::tam.mml(resp=dat, control=list(maxiter=300, snodes=1500))
summary(mod1)

#****************************************
#*** Model 2: Rasch testlet model

# testlets are dimensions, assign items to Q-matrix
TT <- length(unique(testlet))
Q <- matrix(0, nrow=ncol(dat), ncol=TT + 1)
Q[,1] <- 1 # First dimension constitutes g-factor
for (tt in 1:TT){Q[testlet==tt, tt+1] <- 1}

# In a testlet model, all dimensions are uncorrelated among
# each other, that is, all pairwise correlations are set to 0,
# which can be accomplished with the "variance.fixed" command
variance.fixed <- cbind(t( utils::combn(TT+1,2)), 0)
mod2 <- TAM::tam.mml(resp=dat, Q=Q, variance.fixed=variance.fixed,
            control=list(snodes=1500, maxiter=300))
```

```
summary(mod2)

#*****************************************
#*** Model 3: Partial credit model

scores <- list()
testlet.names <- NULL
dat.pcm <- NULL
for (tt in 1:max(testlet) ){
   scores[[tt]] <- rowSums (dat[, testlet==tt, drop=FALSE])
   dat.pcm <- c(dat.pcm, list(c(scores[[tt]])))
   testlet.names <- append(testlet.names, paste0("testlet",tt) )
   }
dat.pcm <- as.data.frame(dat.pcm)
colnames(dat.pcm) <- testlet.names
mod3 <- TAM::tam.mml(resp=dat.pcm, control=list(snodes=1500, maxiter=300) )
summary(mod3)

#*****************************************
#*** Model 4: Copula model

mod4 <- sirt::rasch.copula2 (dat=dat, itemcluster=testlet)
summary(mod4)

## End(Not run)
```

`data.inv4gr` *Dataset for Invariance Testing with 4 Groups*

Description

Dataset for invariance testing with 4 groups.

Usage

```
data(data.inv4gr)
```

Format

A data frame with 4000 observations on the following 12 variables. The first variable is a group identifier, the other variables are items.

`group` A group identifier

`I01` a numeric vector

`I02` a numeric vector

`I03` a numeric vector

`I04` a numeric vector

`I05` a numeric vector

I06 a numeric vector

I07 a numeric vector

I08 a numeric vector

I09 a numeric vector

I10 a numeric vector

I11 a numeric vector

Source

Simulated dataset

`data.liking.science` *Dataset 'Liking For Science'*

Description

Dataset 'Liking for science' published by Wright and Masters (1982).

Usage

```
data(data.liking.science)
```

Format

The format is:

```
 num [1:75, 1:24] 1 2 2 1 1 1 2 2 0 2 ...
- attr(*, "dimnames")=List of 2
..$ : NULL
..$ : chr [1:24] "LS01" "LS02" "LS03" "LS04" ...
```

References

Wright, B. D., & Masters, G. N. (1982). *Rating scale analysis*. Chicago: MESA Press.

data.long *Longitudinal Dataset*

Description

This dataset contains 200 observations on 12 items. 6 items (I1T1, ...,I6T1) were administered at measurement occasion T1 and 6 items at T2 (I3T2, ..., I8T2). There were 4 anchor items which were presented at both time points. The first column in the dataset contains the student identifier.

Usage

```
data(data.long)
```

Format

The format of the dataset is

```
'data.frame': 200 obs. of 13 variables:
$ idstud: int 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 ...
$ I1T1 : int 1 1 1 1 1 1 1 0 1 1 ...
$ I2T1 : int 0 0 1 1 1 1 0 1 1 1 ...
$ I3T1 : int 1 0 1 1 0 1 0 0 0 0 ...
$ I4T1 : int 1 0 0 1 0 0 0 0 1 1 ...
$ I5T1 : int 1 0 0 1 0 0 0 0 1 0 ...
$ I6T1 : int 1 0 0 0 0 0 0 0 0 0 ...
$ I3T2 : int 1 1 0 0 1 1 1 1 0 1 ...
$ I4T2 : int 1 1 0 0 1 1 0 0 0 1 ...
$ I5T2 : int 1 0 1 1 1 1 1 0 1 1 ...
$ I6T2 : int 1 1 0 0 0 0 0 0 0 1 ...
$ I7T2 : int 1 0 0 0 0 0 0 0 0 1 ...
$ I8T2 : int 0 0 0 0 1 0 0 0 0 0 ...
```

Examples

```
## Not run:
data(data.long)
dat <- data.long
dat <- dat[,-1]
I <- ncol(dat)

#************************************************
# Model 1: 2-dimensional Rasch model
#************************************************
# define Q-matrix
Q <- matrix(0,I,2)
Q[1:6,1] <- 1
Q[7:12,2] <- 1
rownames(Q) <- colnames(dat)
```

```
colnames(Q) <- c("T1","T2")

# vector with same items
itemnr <- as.numeric( substring( colnames(dat),2,2) )
# fix mean at T2 to zero
mu.fixed <- cbind( 2,0 )

#--- M1a: rasch.mml2 (in sirt)
mod1a <- sirt::rasch.mml2(dat, Q=Q, est.b=itemnr, mu.fixed=mu.fixed)
summary(mod1a)

#--- M1b: smirt (in sirt)
mod1b <- sirt::smirt(dat, Qmatrix=Q, irtmodel="comp", est.b=itemnr,
                  mu.fixed=mu.fixed )

#--- M1c: tam.mml (in TAM)

# assume equal item difficulty of I3T1 and I3T2, I4T1 and I4T2, ...
# create draft design matrix and modify it
A <- TAM::designMatrices(resp=dat)$A
dimnames(A)[[1]] <- colnames(dat)
  ##   > str(A)
  ##    num [1:12, 1:2, 1:12] 0 0 0 0 0 0 0 0 0 0 ...
  ##    - attr(*, "dimnames")=List of 3
  ##     ..$ : chr [1:12] "Item01" "Item02" "Item03" "Item04" ...
  ##     ..$ : chr [1:2] "Category0" "Category1"
  ##     ..$ : chr [1:12] "I1T1" "I2T1" "I3T1" "I4T1" ...
A1 <- A[,, c(1:6, 11:12 ) ]
A1[7,2,3] <- -1     # difficulty(I3T1)=difficulty(I3T2)
A1[8,2,4] <- -1     # I4T1=I4T2
A1[9,2,5] <- A1[10,2,6] <- -1
dimnames(A1)[[3]] <- substring( dimnames(A1)[[3]],1,2)
  ##   > A1[,2,]
  ##        I1 I2 I3 I4 I5 I6 I7 I8
  ##   I1T1 -1  0  0  0  0  0  0  0
  ##   I2T1  0 -1  0  0  0  0  0  0
  ##   I3T1  0  0 -1  0  0  0  0  0
  ##   I4T1  0  0  0 -1  0  0  0  0
  ##   I5T1  0  0  0  0 -1  0  0  0
  ##   I6T1  0  0  0  0  0 -1  0  0
  ##   I3T2  0  0 -1  0  0  0  0  0
  ##   I4T2  0  0  0 -1  0  0  0  0
  ##   I5T2  0  0  0  0 -1  0  0  0
  ##   I6T2  0  0  0  0  0 -1  0  0
  ##   I7T2  0  0  0  0  0  0 -1  0
  ##   I8T2  0  0  0  0  0  0  0 -1

# estimate model
# set intercept of second dimension (T2) to zero
beta.fixed <- cbind( 1, 2, 0 )
mod1c <- TAM::tam.mml( resp=dat, Q=Q, A=A1, beta.fixed=beta.fixed)
summary(mod1c)
```

```
#************************************************
# Model 2: 2-dimensional 2PL model
#************************************************

# set variance at T2 to 1
variance.fixed <- cbind(2,2,1)

# M2a: rasch.mml2 (in sirt)
mod2a <- sirt::rasch.mml2(dat, Q=Q, est.b=itemnr, est.a=itemnr, mu.fixed=mu.fixed,
             variance.fixed=variance.fixed, mmliter=100)
summary(mod2a)

#************************************************
# Model 3: Concurrent calibration by assuming invariant item parameters
#************************************************

library(mirt)   # use mirt for concurrent calibration
data(data.long)
dat <- data.long[,-1]
I <- ncol(dat)

# create user defined function for between item dimensionality 4PL model
name <- "4PLbw"
par <- c("low"=0,"upp"=1,"a"=1,"d"=0,"dimItem"=1)
est <- c(TRUE, TRUE,TRUE,TRUE,FALSE)
# item response function
irf <- function(par,Theta,ncat){
     low <- par[1]
     upp <- par[2]
     a <- par[3]
     d <- par[4]
     dimItem <- par[5]
     P1 <- low + ( upp - low ) * plogis( a*Theta[,dimItem] + d )
     cbind(1-P1, P1)
}

# create item response function
fourPLbetw <- mirt::createItem(name, par=par, est=est, P=irf)
head(dat)

# create mirt model (use variable names in mirt.model)
mirtsyn <- "
     T1=I1T1,I2T1,I3T1,I4T1,I5T1,I6T1
     T2=I3T2,I4T2,I5T2,I6T2,I7T2,I8T2
     COV=T1*T2,,T2*T2
     MEAN=T1
     CONSTRAIN=(I3T1,I3T2,d),(I4T1,I4T2,d),(I5T1,I5T2,d),(I6T1,I6T2,d),
                (I3T1,I3T2,a),(I4T1,I4T2,a),(I5T1,I5T2,a),(I6T1,I6T2,a)
        "
# create mirt model
mirtmodel <- mirt::mirt.model( mirtsyn, itemnames=colnames(dat) )
# define parameters to be estimated
mod3.pars <- mirt::mirt(dat, mirtmodel$model, rep( "4PLbw",I),
```

```
                    customItems=list("4PLbw"=fourPLbetw), pars="values")
# select dimensions
ind <- intersect( grep("T2",mod3.pars$item), which( mod3.pars$name=="dimItem" ) )
mod3.pars[ind,"value"] <- 2
# set item parameters low and upp to non-estimated
ind <- which( mod3.pars$name %in% c("low","upp") )
mod3.pars[ind,"est"] <- FALSE

# estimate 2PL model
mod3 <- mirt::mirt(dat, mirtmodel$model, itemtype=rep( "4PLbw",I),
                customItems=list("4PLbw"=fourPLbetw), pars=mod3.pars, verbose=TRUE,
                technical=list(NCYCLES=50)  )
mirt.wrapper.coef(mod3)

#****** estimate model in lavaan
library(lavaan)

# specify syntax
lavmodel <- "
             #**** T1
             F1=~ a1*I1T1+a2*I2T1+a3*I3T1+a4*I4T1+a5*I5T1+a6*I6T1
             I1T1 | b1*t1 ; I2T1 | b2*t1 ; I3T1 | b3*t1 ; I4T1 | b4*t1
             I5T1 | b5*t1 ; I6T1 | b6*t1
             F1 ~~ 1*F1
             #**** T2
             F2=~ a3*I3T2+a4*I4T2+a5*I5T2+a6*I6T2+a7*I7T2+a8*I8T2
             I3T2 | b3*t1 ; I4T2 | b4*t1 ; I5T2 | b5*t1 ; I6T2 | b6*t1
             I7T2 | b7*t1 ; I8T2 | b8*t1
             F2 ~~ NA*F2
             F2 ~ 1
             #*** covariance
             F1 ~~ F2
                "
# estimate model using theta parameterization
mod3lav <- lavaan::cfa( data=dat, model=lavmodel,
            std.lv=TRUE, ordered=colnames(dat), parameterization="theta")
summary(mod3lav, standardized=TRUE, fit.measures=TRUE, rsquare=TRUE)

#************************************************
# Model 4: Linking with items of different item slope groups
#************************************************

data(data.long)
dat <- data.long
# dataset for T1
dat1 <- dat[, grep( "T1", colnames(dat) ) ]
colnames(dat1) <- gsub("T1","", colnames(dat1) )
# dataset for T2
dat2 <- dat[, grep( "T2", colnames(dat) ) ]
colnames(dat2) <- gsub("T2","", colnames(dat2) )

# 2PL model with slope groups T1
mod1 <- sirt::rasch.mml2( dat1, est.a=c( rep(1,2), rep(2,4) ) )
```

```
summary(mod1)

# 2PL model with slope groups T2
mod2 <- sirt::rasch.mml2( dat2, est.a=c( rep(1,4), rep(2,2) ) )
summary(mod2)

#------- Link 1: Haberman Linking
# collect item parameters
dfr1 <- data.frame( "study1", mod1$item$item, mod1$item$a, mod1$item$b )
dfr2 <- data.frame( "study2", mod2$item$item, mod2$item$a, mod2$item$b )
colnames(dfr2) <- colnames(dfr1) <- c("study", "item", "a", "b" )
itempars <- rbind( dfr1, dfr2 )
# Linking
link1 <- sirt::linking.haberman(itempars=itempars)

#------- Link 2: Invariance alignment method
# create objects for invariance.alignment
nu <- rbind( c(mod1$item$thresh,NA,NA), c(NA,NA,mod2$item$thresh) )
lambda <- rbind( c(mod1$item$a,NA,NA), c(NA,NA,mod2$item$a ) )
colnames(lambda) <- colnames(nu) <- paste0("I",1:8)
rownames(lambda) <- rownames(nu) <- c("T1", "T2")
# Linking
link2a <- sirt::invariance.alignment( lambda, nu )
summary(link2a)

## End(Not run)
```

`data.lsem` *Datasets for Local Structural Equation Models / Moderated Factor Analysis*

Description

Datasets for local structural equation models or moderated factor analysis.

Usage

```
data(data.lsem01)
data(data.lsem02)
data(data.lsem03)
```

Format

- The dataset `data.lsem01` has the following structure

```
'data.frame': 989 obs. of 6 variables:
$ age: num 4 4 4 4 4 4 4 4 4 4 ...
$ v1 : num 1.83 2.38 1.85 4.53 -0.04 4.35 2.38 1.83 4.81 2.82 ...
$ v2 : num 6.06 9.08 7.41 8.24 6.18 7.4 6.54 4.28 6.43 7.6 ...
$ v3 : num 1.42 3.05 6.42 -1.05 -1.79 4.06 -0.17 -2.64 0.84 6.42 ...
```

```
$ v4 : num 3.84 4.24 3.24 3.36 2.31 6.07 4 5.93 4.4 3.49 ...
$ v5 : num 7.84 7.51 6.62 8.02 7.12 7.99 7.25 7.62 7.66 7.03 ...
```

- The dataset `data.lsem02` is a slightly perturbed dataset of the Woodcock-Johnson III (WJ-III) Tests of Cognitive Abilities used in Hildebrandt et al. (2016) and has the following structure

```
'data.frame': 1129 obs. of 8 variables:
$ age : int 4 4 4 4 4 4 4 4 4 4 ...
$ gcw : num -3.53 -3.73 -3.77 -3.84 -4.26 -4.6 -3.66 -4.31 -4.46 -3.64 ...
$ gvw : num -1.98 -1.35 -1.66 -3.24 -1.17 -2.78 -2.97 -3.88 -3.22 -0.68 ...
$ gfw : num -2.49 -2.41 -4.48 -4.17 -4.43 -5.06 -3.94 -3.66 -3.7 -2.74 ...
$ gsw : num -4.85 -5.05 -5.66 -4.3 -5.23 -5.63 -4.91 -5.75 -6.29 -5.47 ...
$ gsmw: num -2.99 -1.13 -4.21 -3.59 -3.79 -4.77 -2.98 -4.48 -2.99 -3.83 ...
$ glrw: num -2.49 -2.91 -3.45 -2.91 -3.31 -3.78 -3.5 -3.96 -2.97 -3.14 ...
$ gaw : num -3.22 -3.77 -3.54 -3.6 -3.22 -3.5 -1.27 -2.08 -2.23 -3.25 ...
```

- The dataset `data.lsem03` is a synthetic dataset of the SON-R application used in Hueluer et al. (2011) has the following structure

```
'data.frame': 1027 obs. of 10 variables:
$ id : num 10001 10002 10003 10004 10005 ...
$ female : int 0 0 0 0 0 0 0 0 0 0 ...
$ age : num 2.62 2.65 2.66 2.67 2.68 2.68 2.68 2.69 2.71 2.71 ...
$ age_group: int 1 1 1 1 1 1 1 1 1 1 ...
$ p1 : num -1.98 -1.98 -1.67 -2.29 -1.67 -1.98 -2.29 -1.98 -2.6 -1.67 ...
$ p2 : num -1.51 -1.51 -0.55 -1.84 -1.51 -1.84 -2.16 -1.84 -2.48 -1.84 ...
$ p3 : num -1.4 -2.31 -1.1 -2 -1.4 -1.7 -2.31 -1.4 -2.31 -0.79 ...
$ r1 : num -1.46 -1.14 -0.49 -2.11 -1.46 -1.46 -2.11 -1.46 -2.75 -1.78 ...
$ r2 : num -2.67 -1.74 0.74 -1.74 -0.81 -1.43 -2.05 -1.43 -1.74 -1.12 ...
$ r3 : num -1.64 -1.64 -1.64 -0.9 -1.27 -3.11 -2.74 -1.64 -2.37 -1.27 ...
```

  The subtests Mosaics (`p1`), Puzzles (`p1`), and Patterns (`p3`) constitute the performance subscale; the subtests Categories (`r1`), Analogies (`r2`), and Situations (`r3`) constitute the reasoning subscale.

References

Hildebrandt, A., Luedtke, O., Robitzsch, A., Sommer, C., & Wilhelm, O. (2016). Exploring factor model parameters across continuous variables with local structural equation models. *Multivariate Behavioral Research, 51*(2-3), 257-278. doi:10.1080/00273171.2016.1142856

Hueluer, G., Wilhelm, O., & Robitzsch, A. (2011). Intelligence differentiation in early childhood. *Journal of Individual Differences, 32*(3), 170-179. doi:10.1027/16140001/a000049

`data.math` *Dataset Mathematics*

Description

This is an example dataset involving Mathematics items for German fourth graders. Items are classified into several domains and subdomains (see Section Format). The dataset contains 664 students on 30 items.

Usage

```
data(data.math)
```

Format

The dataset is a list. The list element `data` contains the dataset with the demographic variables student ID (`idstud`) and a dummy variable for female students (`female`). The remaining variables (starting with `M` in the name) are the mathematics items.
The item metadata are included in the list element `item` which contains item name (`item`) and the testlet label (`testlet`). An item not included in a testlet is indicated by `NA`. Each item is allocated to one and only competence domain (`domain`).

The format is:

```
List of 2
$ data:'data.frame':
..$ idstud: int [1:664] 1001 1002 1003 ...
..$ female: int [1:664] 1 1 0 0 1 1 1 0 0 1 ...
..$ MA1 : int [1:664] 1 1 1 0 0 1 1 1 1 1 ...
..$ MA2 : int [1:664] 1 1 1 1 1 0 0 0 0 1 ...
..$ MA3 : int [1:664] 1 1 0 0 0 0 0 1 0 0 ...
..$ MA4 : int [1:664] 0 1 1 1 0 0 1 0 0 0 ...
..$ MB1 : int [1:664] 0 1 0 1 0 0 0 0 0 1 ...
..$ MB2 : int [1:664] 1 1 1 1 0 1 0 1 0 0 ...
..$ MB3 : int [1:664] 1 1 1 1 0 0 0 1 0 1 ...
[...]
..$ MH3 : int [1:664] 1 1 0 1 0 0 1 0 1 0 ...
..$ MH4 : int [1:664] 0 1 1 1 0 0 0 0 1 0 ...
..$ MI1 : int [1:664] 1 1 0 1 0 1 0 0 1 0 ...
..$ MI2 : int [1:664] 1 1 0 0 0 1 1 0 1 1 ...
..$ MI3 : int [1:664] 0 1 0 1 0 0 0 0 0 0 ...
$ item:'data.frame':
..$ item : Factor w/ 30 levels "MA1","MA2","MA3",..: 1 2 3 4 5 ...
..$ testlet : Factor w/ 9 levels "","MA","MB","MC",..: 2 2 2 2 3 3 ...
..$ domain : Factor w/ 3 levels "arithmetic","geometry",..: 1 1 1 ...
..$ subdomain: Factor w/ 9 levels "","addition",..: 2 2 2 2 7 7 ...
```

`data.mcdonald` *Some Datasets from McDonald's* Test Theory *Book*

Description

Some datasets from McDonald (1999), especially related to using NOHARM for item response modeling. See Examples below.

Usage

```
data(data.mcdonald.act15)
data(data.mcdonald.LSAT6)
data(data.mcdonald.rape)
```

Format

- The format of the ACT15 data `data.mcdonald.act15` is:

  ```
  num [1:15, 1:15] 0.49 0.44 0.38 0.3 0.29 0.13 0.23 0.16 0.16 0.23 ...
  - attr(*, "dimnames")=List of 2
  ..$ : chr [1:15] "A01" "A02" "A03" "A04" ...
  ..$ : chr [1:15] "A01" "A02" "A03" "A04" ...
  ```

  The dataset (which is the product-moment covariance matrix) is obtained from Ch. 12 in McDonald (1999).

- The format of the LSAT6 data `data.mcdonald.LSAT6` is:

  ```
  'data.frame': 1004 obs. of 5 variables:
  $ L1: int 0 0 0 0 0 0 0 0 0 0 ...
  $ L2: int 0 0 0 0 0 0 0 0 0 0 ...
  $ L3: int 0 0 0 0 0 0 0 0 0 0 ...
  $ L4: int 0 0 0 0 0 0 0 0 0 1 ...
  $ L5: int 0 0 0 1 1 1 1 1 1 0 ...
  ```

  The dataset is obtained from Ch. 6 in McDonald (1999).

- The format of the rape myth scale data `data.mcdonald.rape` is

  ```
  List of 2
  $ lambda: num [1:2, 1:19] 1.13 0.88 0.85 0.77 0.79 0.55 1.12 1.01 0.99 0.79 ...
  ..- attr(*, "dimnames")=List of 2
  .. ..$ : chr [1:2] "male" "female"
  .. ..$ : chr [1:19] "I1" "I2" "I3" "I4" ...
  $ nu : num [1:2, 1:19] 2.88 1.87 3.12 2.32 2.13 1.43 3.79 2.6 3.01 2.11 ...
  ..- attr(*, "dimnames")=List of 2
  .. ..$ : chr [1:2] "male" "female"
  .. ..$ : chr [1:19] "I1" "I2" "I3" "I4" ...
  ```

  The dataset is obtained from Ch. 15 in McDonald (1999).

Source

Tables in McDonald (1999)

References

McDonald, R. P. (1999). *Test theory: A unified treatment*. Psychology Press.

Examples

```
## Not run:
#############################################################################
# EXAMPLE 1: LSAT6 data    | Chapter 12 McDonald (1999)
#############################################################################
data(data.mcdonald.act15)

#************
# Model 1: 2-parameter normal ogive model

#++ NOHARM estimation
I <- ncol(dat)
# covariance structure
P.pattern <- matrix( 0, ncol=1, nrow=1 )
P.init <- 1+0*P.pattern
# fix all entries in the loading matrix to 1
F.pattern <- matrix( 1, nrow=I, ncol=1 )
F.init <- F.pattern
# estimate model
mod1a <- sirt::R2noharm( dat=dat, model.type="CFA", F.pattern=F.pattern,
             F.init=F.init, P.pattern=P.pattern, P.init=P.init,
             writename="LSAT6__1dim_2pno", noharm.path=noharm.path, dec="," )
summary(mod1a, logfile="LSAT6__1dim_2pno__SUMMARY")

#++ pairwise marginal maximum likelihood estimation using the probit link
mod1b <- sirt::rasch.pml3( dat, est.a=1:I, est.sigma=FALSE)

#************
# Model 2: 1-parameter normal ogive model

#++ NOHARM estimation
# covariance structure
P.pattern <- matrix( 0, ncol=1, nrow=1 )
P.init <- 1+0*P.pattern
# fix all entries in the loading matrix to 1
F.pattern <- matrix( 2, nrow=I, ncol=1 )
F.init <- 1+0*F.pattern
# estimate model
mod2a <- sirt::R2noharm( dat=dat, model.type="CFA", F.pattern=F.pattern,
               F.init=F.init, P.pattern=P.pattern, P.init=P.init,
               writename="LSAT6__1dim_1pno", noharm.path=noharm.path, dec="," )
summary(mod2a, logfile="LSAT6__1dim_1pno__SUMMARY")

# PMML estimation
```

```
mod2b <- sirt::rasch.pml3( dat, est.a=rep(1,I), est.sigma=FALSE )
summary(mod2b)

#************
# Model 3: 3-parameter normal ogive model with fixed guessing parameters

#++ NOHARM estimation
# covariance structure
P.pattern <- matrix( 0, ncol=1, nrow=1 )
P.init <- 1+0*P.pattern
# fix all entries in the loading matrix to 1
F.pattern <- matrix( 1, nrow=I, ncol=1 )
F.init <- 1+0*F.pattern
# estimate model
mod <- sirt::R2noharm( dat=dat, model.type="CFA",  guesses=rep(.2,I),
            F.pattern=F.pattern, F.init=F.init, P.pattern=P.pattern,
            P.init=P.init, writename="LSAT6__1dim_3pno",
            noharm.path=noharm.path, dec="," )
summary(mod, logfile="LSAT6__1dim_3pno__SUMMARY")

#++ logistic link function employed in smirt function
mod1d <- sirt::smirt(dat, Qmatrix=F.pattern, est.a=matrix(1:I,I,1), c.init=rep(.2,I))
summary(mod1d)

############################################################################
# EXAMPLE 2: ACT15 data    | Chapter 6 McDonald (1999)
############################################################################
data(data.mcdonald.act15)
pm <- data.mcdonald.act15

#************
# Model 1: 2-dimensional exploratory factor analysis
mod1 <- sirt::R2noharm( pm=pm, n=1000, model.type="EFA", dimensions=2,
             writename="ACT15__efa_2dim", noharm.path=noharm.path, dec="," )
summary(mod1)

#************
# Model 2: 2-dimensional independent clusters basis solution
P.pattern <- matrix(1,2,2)
diag(P.pattern) <- 0
P.init <- 1+0*P.pattern
F.pattern <- matrix(0,15,2)
F.pattern[ c(1:5,11:15),1] <- 1
F.pattern[ c(6:10,11:15),2] <- 1
F.init <- F.pattern

# estimate model
mod2 <- sirt::R2noharm( pm=pm, n=1000,  model.type="CFA", F.pattern=F.pattern,
            F.init=F.init, P.pattern=P.pattern,P.init=P.init,
            writename="ACT15_indep_clusters", noharm.path=noharm.path, dec="," )
summary(mod2)

#************
```

```
# Model 3: Hierarchical model

P.pattern <- matrix(0,3,3)
P.init <- P.pattern
diag(P.init) <- 1
F.pattern <- matrix(0,15,3)
F.pattern[,1] <- 1    # all items load on g factor
F.pattern[ c(1:5,11:15),2] <- 1   # Items 1-5 and 11-15 load on first nested factor
F.pattern[ c(6:10,11:15),3] <- 1  # Items 6-10 and 11-15 load on second nested factor
F.init <- F.pattern

# estimate model
mod3 <- sirt::R2noharm( pm=pm, n=1000,  model.type="CFA", F.pattern=F.pattern,
           F.init=F.init, P.pattern=P.pattern, P.init=P.init,
           writename="ACT15_hierarch_model", noharm.path=noharm.path, dec="," )
summary(mod3)

#############################################################################
# EXAMPLE 3: Rape myth scale | Chapter 15 McDonald (1999)
#############################################################################
data(data.mcdonald.rape)
lambda <- data.mcdonald.rape$lambda
nu <- data.mcdonald.rape$nu

# obtain multiplier for factor loadings (Formula 15.5)
k <- sum( lambda[1,] * lambda[2,] ) / sum( lambda[2,]^2 )
  ##   [1] 1.263243

# additive parameter (Formula 15.7)
c <- sum( lambda[2,]*(nu[1,]-nu[2,]) ) / sum( lambda[2,]^2 )
  ##   [1] 1.247697

# SD in the female group
1/k
  ##   [1] 0.7916132

# M in the female group
- c/k
  ##   [1] -0.9876932

# Burt's coefficient of factorial congruence (Formula 15.10a)
sum( lambda[1,] * lambda[2,] ) / sqrt( sum( lambda[1,]^2 ) * sum( lambda[2,]^2 ) )
  ##   [1] 0.9727831

# congruence for mean parameters
sum(  (nu[1,]-nu[2,]) * lambda[2,] ) / sqrt( sum( (nu[1,]-nu[2,])^2 ) * sum( lambda[2,]^2 ) )
  ##   [1] 0.968176

## End(Not run)
```

`data.mixed1` *Dataset with Mixed Dichotomous and Polytomous Item Responses*

Description

Dataset with mixed dichotomous and polytomous item responses.

Usage

```
data(data.mixed1)
```

Format

A data frame with 1000 observations on the following 37 variables.

```
'data.frame': 1000 obs. of 37 variables:
$ I01: num 1 1 1 1 1 1 1 0 1 1 ...
$ I02: num 1 1 1 1 1 1 1 1 0 1 ...
[...]
$ I36: num 1 1 1 1 0 0 0 0 1 1 ...
$ I37: num 0 1 1 1 0 1 0 0 1 1 ...
```

Examples

```
data(data.mixed1)
apply( data.mixed1, 2, max )
  ##   I01 I02 I03 I04 I05 I06 I07 I08 I09 I10 I11 I12 I13 I14 I15 I16
  ##     1   1   1   1   1   1   1   1   1   1   1   1   1   1   1   1
  ##   I17 I18 I19 I20 I21 I22 I23 I24 I25 I26 I27 I28 I29 I30 I31 I32
  ##     1   1   1   1   4   4   1   1   1   1   1   1   1   1   1   1
  ##   I33 I34 I35 I36 I37
  ##     1   1   1   1   1
```

---

data.ml *Multilevel Datasets*

Description

Datasets for conducting multilevel IRT analysis. This dataset is used in the examples of the function `mcmc.2pno.ml`.

Usage

```
data(data.ml1)
data(data.ml2)
```

Format

- `data.ml1`

  A data frame with 2000 student observations in 100 classes on 17 variables. The first variable `group` contains the class identifier. The remaining 16 variables are dichotomous test items.

```
'data.frame': 2000 obs. of 17 variables:
$ group: num 1001 1001 1001 1001 1001 ...
$ X1 : num 1 1 1 1 1 1 1 1 1 1 ...
$ X2 : num 1 1 1 0 1 1 1 1 1 1 ...
$ X3 : num 0 1 1 0 1 0 1 0 1 0 ...
$ X4 : num 1 1 1 0 0 1 1 1 1 1 ...
$ X5 : num 0 0 0 1 1 1 0 0 1 1 ...
[...]
$ X16 : num 0 0 1 0 0 0 1 0 0 0 ...
```

- `data.ml2`

  A data frame with 2000 student observations in 100 classes on 6 variables. The first variable `group` contains the class identifier. The remaining 5 variables are polytomous test items.

```
'data.frame': 2000 obs. of 6 variables:
$ group: num 1 1 1 1 1 1 1 1 1 1 ...
$ X1 : num 2 3 4 3 3 3 1 4 4 3 ...
$ X2 : num 2 2 4 3 3 2 2 3 4 3 ...
$ X3 : num 3 4 5 4 2 3 3 4 4 2 ...
$ X4 : num 2 3 3 2 1 3 1 4 4 3 ...
$ X5 : num 2 3 3 2 3 3 1 3 2 2 ...
```

`data.noharm` *Datasets for NOHARM Analysis*

Description

Datasets for analyses in NOHARM (see `R2noharm`).

Usage

```
data(data.noharmExC)
data(data.noharm18)
```

Format

- `data.noharmExC`

  The format of this dataset is

```
'data.frame': 300 obs. of 8 variables:
$ C1: int 1 1 1 1 1 0 1 1 1 1 ...
```

```
$ C2: int 1 1 1 1 0 1 1 1 1 1 ...
$ C3: int 1 1 1 1 1 0 0 0 1 1 ...
$ C4: int 0 0 1 1 1 1 1 0 1 0 ...
$ C5: int 1 1 1 1 1 0 0 1 1 0 ...
$ C6: int 1 0 0 0 1 0 1 1 0 1 ...
$ C7: int 1 1 0 0 1 1 0 0 0 1 ...
$ C8: int 1 0 1 0 1 0 1 0 1 1 ...
```

- `data.noharm18`

  A data frame with 200 observations on the following 18 variables `I01`, ..., `I18`. The format is `'data.frame': 200 obs. of 18 variables:`

```
$ I01: int 1 1 1 1 1 0 1 1 0 1 ...
$ I02: int 1 1 0 1 1 0 1 1 1 1 ...
$ I03: int 1 0 0 1 0 0 1 1 0 1 ...
$ I04: int 0 1 0 1 0 0 0 1 1 1 ...
$ I05: int 1 0 0 0 1 0 1 1 0 1 ...
$ I06: int 1 1 0 1 0 0 1 1 0 1 ...
$ I07: int 1 1 1 1 1 0 1 1 1 1 ...
$ I08: int 1 1 1 1 1 1 1 1 1 0 1 ...
$ I09: int 1 1 1 1 0 0 1 1 0 1 ...
$ I10: int 1 0 0 1 1 0 1 1 0 1 ...
$ I11: int 1 1 1 1 0 0 1 1 0 1 ...
$ I12: int 0 0 0 0 0 1 0 0 0 0 ...
$ I13: int 1 1 1 1 0 1 1 0 1 1 ...
$ I14: int 1 1 1 0 1 0 1 1 0 1 ...
$ I15: int 1 1 1 0 0 1 1 1 0 1 ...
$ I16: int 1 1 0 1 1 0 1 0 1 1 ...
$ I17: int 0 1 0 0 0 0 1 1 0 1 ...
$ I18: int 0 0 0 0 0 0 0 0 1 0 ...
```

`data.pars1.rasch` *Item Parameters for Three Studies Obtained by 1PL and 2PL Estimation*

Description

The datasets contain item parameters to be prepared for linking using the function `linking.haberman`.

Usage

```
data(data.pars1.rasch)
data(data.pars1.2pl)
```

Format

- The format of data.pars1.rasch is:

  ```
  'data.frame': 22 obs. of 4 variables:
  $ study: chr "study1" "study1" "study1" "study1" ...
  $ item : Factor w/ 12 levels "M133","M176",..: 1 2 3 4 5 1 6 7 3 8 ...
  $ a : num 1 1 1 1 1 1 1 1 1 1 ...
  $ b : num -1.5862 0.40762 1.78031 2.00382 0.00862 ...
  ```

  Item slopes a are fixed to 1 in 1PL estimation. Item difficulties are denoted by b.

- The format of data.pars1.2pl is:

  ```
  'data.frame': 22 obs. of 4 variables:
  $ study: chr "study1" "study1" "study1" "study1" ...
  $ item : Factor w/ 12 levels "M133","M176",..: 1 2 3 4 5 1 6 7 3 8 ...
  $ a : num 1.238 0.957 1.83 1.927 2.298 ...
  $ b : num -1.16607 0.35844 1.06571 1.17159 0.00792 ...
  ```

---

data.pirlsmissing *Dataset from PIRLS Study with Missing Responses*

Description

This is a dataset of the PIRLS 2011 study for 4th graders for the reading booklet 13 (the 'PIRLS reader') and 4 countries (Austria, Germany, France, Netherlands). Missing responses (missing by intention and not reached) are coded by 9.

Usage

```
data(data.pirlsmissing)
```

Format

A data frame with 3480 observations on the following 38 variables.

The format is:

```
'data.frame': 3480 obs. of 38 variables:
$ idstud : int 1000001 1000002 1000003 1000004 1000005 ...
$ country : Factor w/ 4 levels "AUT","DEU","FRA",..: 1 1 1 1 1 1 1 1 1 1 ...
$ studwgt : num 1.06 1.06 1.06 1.06 1.06 ...
$ R31G01M : int 1 1 1 1 1 1 0 1 1 0 ...
$ R31G02C : int 0 9 0 1 0 0 0 0 1 0 ...
$ R31G03M : int 1 1 1 1 1 0 1 0 0 1 1 ...
[...]
$ R31P15C : int 1 9 0 1 0 0 0 0 1 0 ...
$ R31P16C : int 0 0 0 0 0 0 0 0 9 0 1 ...
```

Examples

```
data(data.pirlsmissing)
# inspect missing rates
round( colMeans( data.pirlsmissing==9 ), 3 )
  ##    idstud  country  studwgt  R31G01M  R31G02C  R31G03M  R31G04C  R31G05M
  ##     0.000    0.000    0.000    0.009    0.076    0.012    0.203    0.018
  ##   R31G06M  R31G07M R31G08CZ R31G08CA R31G08CB  R31G09M  R31G10C  R31G11M
  ##     0.010    0.020    0.189    0.225    0.252    0.019    0.126    0.023
  ##   R31G12C R31G13CZ R31G13CA R31G13CB R31G13CC  R31G14M  R31P01M  R31P02C
  ##     0.202    0.170    0.198    0.220    0.223    0.074    0.013    0.039
  ##   R31P03C  R31P04M  R31P05C  R31P06C  R31P07C  R31P08M  R31P09C  R31P10M
  ##     0.056    0.012    0.075    0.043    0.074    0.024    0.062    0.025
  ##   R31P11M  R31P12M  R31P13M  R31P14C  R31P15C  R31P16C
  ##     0.027    0.030    0.030    0.126    0.130    0.127
```

---

data.pisa2006Read *Dataset PISA 2006 Reading*

Description

This is the PISA 2006 dataset of item responses from 26 OECD countries.

Usage

```
data(data.pisa2006Read)
```

Format

The dataset includes item responses, student weights and replicate weights.

---

data.pisaMath *Dataset PISA Mathematics*

Description

This is an example PISA dataset of reading items from the PISA 2009 study of students from Austria. The dataset contains 565 students who worked on the 11 mathematics items from item cluster M3.

Usage

```
data(data.pisaMath)
```

Format

The dataset is a list. The list element `data` contains the dataset with the demographical variables student ID (`idstud`), school ID (`idschool`), a dummy variable for female students (`female`), socioeconomic status (`hisei`) and migration background (`migra`). The remaining variables (starting with `M` in the name) are the mathematics items.
The item metadata are included in the list element `item` which contains item name (`item`) and the testlet label (`testlet`). An item not included in a testlet is indicated by `NA`.

The format is:

```
List of 2
$ data:'data.frame':
..$ idstud : num [1:565] 9e+10 9e+10 9e+10 9e+10 9e+10 ...
..$ idschool: int [1:565] 900015 900015 900015 900015 ...
..$ female : int [1:565] 0 0 0 0 0 0 0 0 0 0 ...
..$ hisei : num [1:565] -1.16 -1.099 -1.588 -0.365 -1.588 ...
..$ migra : int [1:565] 0 0 0 0 0 0 0 0 0 1 ...
..$ M192Q01 : int [1:565] 1 0 1 1 1 1 1 0 0 0 ...
..$ M406Q01 : int [1:565] 1 1 1 0 1 0 0 0 1 0 ...
..$ M406Q02 : int [1:565] 1 0 0 0 1 0 0 0 1 0 ...
..$ M423Q01 : int [1:565] 0 1 0 1 1 1 1 1 1 0 ...
..$ M496Q01 : int [1:565] 1 0 0 0 0 0 0 0 1 0 ...
..$ M496Q02 : int [1:565] 1 0 0 1 0 1 0 1 1 0 ...
..$ M564Q01 : int [1:565] 1 1 1 1 1 1 1 0 0 1 0 ...
..$ M564Q02 : int [1:565] 1 0 1 1 1 0 0 0 0 0 ...
..$ M571Q01 : int [1:565] 1 0 0 0 1 0 0 0 0 0 ...
..$ M603Q01 : int [1:565] 1 0 0 0 1 0 0 0 0 0 ...
..$ M603Q02 : int [1:565] 1 0 0 0 1 0 0 0 1 0 ...
$ item:'data.frame':
..$ item : Factor w/ 11 levels "M192Q01","M406Q01",..: 1 2 3 4 ...
..$ testlet: chr [1:11] NA "M406" "M406" NA ...
```

`data.pisaPars` *Item Parameters from Two PISA Studies*

Description

This data frame contains item parameters from two PISA studies. Because the Rasch model is used, only item difficulties are considered.

Usage

```
data(data.pisaPars)
```

Format

A data frame with 25 observations on the following 4 variables.

`item` Item names

`testlet` Items are arranged in corresponding testlets. These names are located in this column.

`study1` Item difficulties of study 1

`study2` Item difficulties of study 2

`data.pisaRead` *Dataset PISA Reading*

Description

This is an example PISA dataset of reading items from the PISA 2009 study of students from Austria. The dataset contains 623 students who worked on the 12 reading items from item cluster R7.

Usage

```
data(data.pisaRead)
```

Format

The dataset is a list. The list element `data` contains the dataset with the demographical variables student ID (`idstud`), school ID (`idschool`), a dummy variable for female students (`female`), socioeconomic status (`hisei`) and migration background (`migra`). The remaining variables (starting with `R` in the name) are the reading items.
The item metadata are included in the list element `item` which contains item name (`item`), testlet label (`testlet`), item format (`ItemFormat`), text type (`TextType`) and text aspect (`Aspect`).

The format is:

```
List of 2
$ data:'data.frame':
..$ idstud : num [1:623] 9e+10 9e+10 9e+10 9e+10 9e+10 ...
..$ idschool: int [1:623] 900003 900003 900003 900003 ...
..$ female : int [1:623] 1 0 1 0 0 0 1 0 1 0 ...
..$ hisei : num [1:623] -1.16 -0.671 1.286 0.185 1.225 ...
..$ migra : int [1:623] 0 0 0 0 0 0 0 0 0 0 ...
..$ R432Q01 : int [1:623] 1 1 1 1 1 1 1 1 1 1 ...
..$ R432Q05 : int [1:623] 1 1 1 1 1 0 1 1 1 0 ...
..$ R432Q06 : int [1:623] 0 0 0 0 0 0 0 0 0 0 ...
..$ R456Q01 : int [1:623] 1 1 1 1 1 1 1 1 1 1 ...
..$ R456Q02 : int [1:623] 1 1 1 1 1 1 1 1 1 1 ...
..$ R456Q06 : int [1:623] 1 1 1 1 1 1 0 0 1 1 ...
..$ R460Q01 : int [1:623] 1 1 0 0 0 0 0 1 1 1 ...
..$ R460Q05 : int [1:623] 1 1 1 1 1 1 1 1 1 1 ...
```

```
..$ R460Q06 : int [1:623] 0 1 1 1 1 1 0 0 1 1 ...
..$ R466Q02 : int [1:623] 0 1 0 1 1 0 1 0 0 1 ...
..$ R466Q03 : int [1:623] 0 0 0 1 0 0 0 1 0 1 ...
..$ R466Q06 : int [1:623] 0 1 1 1 1 1 0 1 1 1 ...
$ item:'data.frame':
..$ item : Factor w/ 12 levels "R432Q01","R432Q05",..: 1 2 3 4 ...
..$ testlet : Factor w/ 4 levels "R432","R456",..: 1 1 1 2 ...
..$ ItemFormat: Factor w/ 2 levels "CR","MC": 1 1 2 2 1 1 1 2 2 1 ...
..$ TextType : Factor w/ 3 levels "Argumentation",..: 1 1 1 3 ...
..$ Aspect : Factor w/ 3 levels "Access_and_retrieve",..: 2 3 2 1 ...
```

`data.pw` *Datasets for Pairwise Comparisons*

Description

Some datasets for pairwise comparisons.

Usage

```
data(data.pw01)
```

Format

The dataset `data.pw01` contains results of a German football league from the season 2000/01.

`data.ratings` *Rating Datasets*

Description

Some rating datasets.

Usage

```
data(data.ratings1)
data(data.ratings2)
data(data.ratings3)
```

Format

- Dataset data.ratings1:

  Data frame with 274 observations containing 5 criteria (k1, ..., k5), 135 students and 7 raters.

```
'data.frame': 274 obs. of 7 variables:
$ idstud: int 100020106 100020106 100070101 100070101 100100109 ...
$ rater : Factor w/ 16 levels "db01","db02",..: 3 15 5 10 2 1 5 4 1 5 ...
$ k1 : int 1 1 0 1 2 0 1 3 0 0 ...
$ k2 : int 1 1 1 1 1 0 0 3 0 0 ...
$ k3 : int 1 1 1 1 2 0 0 3 1 0 ...
$ k4 : int 1 1 1 2 1 0 0 2 0 1 ...
$ k5 : int 2 2 1 2 0 1 0 3 1 0 ...
```

  Data from a 2009 Austrian survey of national educational standards for 8th graders in German language writing. Variables k1 to k5 denote several rating criteria of writing competency.

- Dataset data.ratings2:

  Data frame with 615 observations containing 5 criteria (k1, ..., k5), 178 students and 16 raters.

```
'data.frame': 615 obs. of 7 variables:
$ idstud: num 1001 1001 1002 1002 1003 ...
$ rater : chr "R03" "R15" "R05" "R10" ...
$ k1 : int 1 1 0 1 2 0 1 3 3 0 ...
$ k2 : int 1 1 1 1 1 0 0 3 3 0 ...
$ k3 : int 1 1 1 1 2 0 0 3 3 1 ...
$ k4 : int 1 1 1 2 1 0 0 2 2 0 ...
$ k5 : int 2 2 1 2 0 1 0 3 2 1 ...
```

- Dataset data.ratings3:

  Data frame with 3169 observations containing 4 criteria (crit2, ..., crit6), 561 students and 52 raters.

```
'data.frame': 3169 obs. of 6 variables:
$ idstud: num 10001 10001 10002 10002 10003 ...
$ rater : num 840 838 842 808 830 845 813 849 809 802 ...
$ crit2 : int 1 3 3 1 2 2 2 2 3 3 ...
$ crit3 : int 2 2 2 2 2 2 2 2 3 3 ...
$ crit4 : int 1 2 2 2 1 1 1 2 2 2 ...
$ crit6 : num 4 4 4 3 4 4 4 4 4 4 ...
```

---

data.raw1 *Dataset with Raw Item Responses*

Description

Dataset with raw item responses

Usage

```
data(data.raw1)
```

Format

A data frame with raw item responses of 1200 persons on the following 77 items:

```
'data.frame': 1200 obs. of 77 variables:
$ I101: num 0 0 0 2 0 0 0 0 0 0 ...
$ I102: int NA NA 2 1 2 1 3 2 NA NA ...
$ I103: int 1 1 NA NA NA NA NA NA 1 1 ...
...
$ I179: chr "E" "C" "D" "E" ...
```

`data.read` *Dataset Reading*

Description

This dataset contains $N = 328$ students and $I = 12$ items measuring reading competence. All 12 items are arranged into 3 testlets (items with common text stimulus) labeled as A, B and C. The allocation of items to testlets is indicated by their variable names.

Usage

```
data(data.read)
```

Format

A data frame with 328 persons on the following 12 variables. Rows correspond to persons and columns to items. The following items are included in `data.read`:

Testlet A: `A1`, `A2`, `A3`, `A4`

Testlet B: `B1`, `B2`, `B3`, `B4`

Testlet C: `C1`, `C2`, `C3`, `C4`

Examples

```
## Not run:
data(data.read)
dat <- data.read
I <- ncol(dat)

# list of needed packages for the following examples
packages <- scan(what="character")
     eRm  ltm  TAM mRm  CDM  mirt psychotools  IsingFit  igraph  qgraph  pcalg
     poLCA  randomLCA psychomix MplusAutomation lavaan

# load packages. make an installation if necessary
miceadds::library_install(packages)

#*****************************************************
# Model 1: Rasch model
#*****************************************************

#----  M1a: rasch.mml2 (in sirt)
mod1a <- sirt::rasch.mml2(dat)
summary(mod1a)

#----  M1b: smirt (in sirt)
Qmatrix <- matrix(1,nrow=I, ncol=1)
mod1b <- sirt::smirt(dat,Qmatrix=Qmatrix)
summary(mod1b)

#----  M1c: gdm (in CDM)
theta.k <- seq(-6,6,len=21)
mod1c <- CDM::gdm(dat,theta.k=theta.k,irtmodel="1PL", skillspace="normal")
summary(mod1c)

#----  M1d: tam.mml (in TAM)
mod1d <- TAM::tam.mml( resp=dat )
summary(mod1d)

#----  M1e: RM (in eRm)
mod1e <- eRm::RM( dat )
  # eRm uses Conditional Maximum Likelihood (CML) as the estimation method.
summary(mod1e)
eRm::plotPImap(mod1e)

#----  M1f: mrm (in mRm)
mod1f <- mRm::mrm( dat, cl=1)   # CML estimation
mod1f$beta  # item parameters

#----  M1g: mirt (in mirt)
mod1g <- mirt::mirt( dat, model=1, itemtype="Rasch", verbose=TRUE )
print(mod1g)
summary(mod1g)
coef(mod1g)
    # arrange coefficients in nicer layout
```

```
sirt::mirt.wrapper.coef(mod1g)$coef

#----  M1h: rasch (in ltm)
mod1h <- ltm::rasch( dat, control=list(verbose=TRUE ) )
summary(mod1h)
coef(mod1h)

#----  M1i: RaschModel.fit (in psychotools)
mod1i <- psychotools::RaschModel.fit(dat)  # CML estimation
summary(mod1i)
plot(mod1i)

#----  M1j: noharm.sirt (in sirt)
Fpatt <- matrix( 0, I, 1 )
Fval <- 1 + 0*Fpatt
Ppatt <- Pval <- matrix(1,1,1)
mod1j <- sirt::noharm.sirt( dat=dat, Ppatt=Ppatt, Fpatt=Fpatt, Fval=Fval, Pval=Pval)
summary(mod1j)
  #   Normal-ogive model, multiply item discriminations with constant D=1.7.
  #   The same holds for other examples with noharm.sirt and R2noharm.
plot(mod1j)

#----  M1k: rasch.pml3 (in sirt)
mod1k <- sirt::rasch.pml3( dat=dat)
  #         pairwise marginal maximum likelihood estimation
summary(mod1k)

#----  M1l: running Mplus (using MplusAutomation package)
mplus_path <- "c:/Mplus7/Mplus.exe"    # locate Mplus executable
#*****************
  # specify Mplus object
mplusmod <- MplusAutomation::mplusObject(
    TITLE="1PL in Mplus ;",
    VARIABLE=paste0( "CATEGORICAL ARE ", paste0(colnames(dat),collapse=" ") ),
    MODEL="
       ! fix all item loadings to 1
       F1 BY A1@1 A2@1 A3@1 A4@1 ;
       F1 BY B1@1 B2@1 B3@1 B4@1 ;
       F1 BY C1@1 C2@1 C3@1 C4@1 ;
       ! estimate variance
       F1 ;
            ",
    ANALYSIS="ESTIMATOR=MLR;",
    OUTPUT="stand;",
    usevariables=colnames(dat),  rdata=dat )
#*****************

  # write Mplus syntax
filename <- "mod1u"   # specify file name
  # create Mplus syntaxes
res2 <- MplusAutomation::mplusModeler(object=mplusmod, dataout=paste0(filename,".dat"),
               modelout=paste0(filename,".inp"), run=0 )
  # run Mplus model
```

```
MplusAutomation::runModels( filefilter=paste0(filename,".inp"), Mplus_command=mplus_path)
  # alternatively, the system() command can also be used
  # get results
mod1l <- MplusAutomation::readModels(target=getwd(), filefilter=filename )
mod1l$summaries    # summaries
mod1l$parameters$unstandardized   # parameter estimates

#*****************************************************
# Model 2: 2PL model
#*****************************************************

#----  M2a: rasch.mml2 (in sirt)
mod2a <- sirt::rasch.mml2(dat, est.a=1:I)
summary(mod2a)

#----  M2b: smirt (in sirt)
mod2b <- sirt::smirt(dat,Qmatrix=Qmatrix,est.a="2PL")
summary(mod2b)

#----  M2c: gdm (in CDM)
mod2c <- CDM::gdm(dat,theta.k=theta.k,irtmodel="2PL", skillspace="normal")
summary(mod2c)

#----  M2d: tam.mml (in TAM)
mod2d <- TAM::tam.mml.2pl( resp=dat )
summary(mod2d)

#----  M2e: mirt (in mirt)
mod2e <- mirt::mirt( dat, model=1, itemtype="2PL" )
print(mod2e)
summary(mod2e)
sirt::mirt.wrapper.coef(mod1g)$coef

#----  M2f: ltm (in ltm)
mod2f <- ltm::ltm( dat ~ z1, control=list(verbose=TRUE ) )
summary(mod2f)
coef(mod2f)
plot(mod2f)

#----  M2g: R2noharm (in NOHARM, running from within R using sirt package)
  # define noharm.path where 'NoharmCL.exe' is located
noharm.path <- "c:/NOHARM"
  # covariance matrix
P.pattern <- matrix( 1, ncol=1, nrow=1 )
P.init <- P.pattern
P.init[1,1] <- 1
  # loading matrix
F.pattern <- matrix(1,I,1)
F.init <- F.pattern
  # estimate model
mod2g <- sirt::R2noharm( dat=dat, model.type="CFA", F.pattern=F.pattern,
             F.init=F.init, P.pattern=P.pattern, P.init=P.init,
             writename="ex2g", noharm.path=noharm.path, dec="," )
```

```
summary(mod2g)

#----  M2h: noharm.sirt (in sirt)
mod2h <- sirt::noharm.sirt( dat=dat, Ppatt=P.pattern,Fpatt=F.pattern,
              Fval=F.init, Pval=P.init )
summary(mod2h)
plot(mod2h)

#----  M2i: rasch.pml2 (in sirt)
mod2i <- sirt::rasch.pml2(dat, est.a=1:I)
summary(mod2i)

#----  M2j: WLSMV estimation with cfa (in lavaan)
lavmodel <- "F=~ A1+A2+A3+A4+B1+B2+B3+B4+
                      C1+C2+C3+C4"
mod2j <- lavaan::cfa( data=dat, model=lavmodel, std.lv=TRUE, ordered=colnames(dat))
summary(mod2j, standardized=TRUE, fit.measures=TRUE, rsquare=TRUE)

#*****************************************************
# Model 3: 3PL model (note that results can be quite unstable!)
#*****************************************************

#----  M3a: rasch.mml2 (in sirt)
mod3a <- sirt::rasch.mml2(dat, est.a=1:I, est.c=1:I)
summary(mod3a)

#----  M3b: smirt (in sirt)
mod3b <- sirt::smirt(dat,Qmatrix=Qmatrix,est.a="2PL", est.c=1:I)
summary(mod3b)

#----  M3c: mirt (in mirt)
mod3c <- mirt::mirt( dat, model=1, itemtype="3PL", verbose=TRUE)
summary(mod3c)
coef(mod3c)
  # stabilize parameter estimating using informative priors for guessing parameters
mirtmodel <- mirt::mirt.model("
            F=1-12
            PRIOR=(1-12, g, norm, -1.38, 0.25)
            ")
  # a prior N(-1.38,.25) is specified for transformed guessing parameters: qlogis(g)
  # simulate values from this prior for illustration
N <- 100000
logit.g <- stats::rnorm(N, mean=-1.38, sd=sqrt(.5) )
graphics::plot( stats::density(logit.g) )  # transformed qlogis(g)
graphics::plot( stats::density( stats::plogis(logit.g)) )  # g parameters
  # estimate 3PL with priors
mod3c1 <- mirt::mirt(dat, mirtmodel, itemtype="3PL",verbose=TRUE)
coef(mod3c1)
  # In addition, set upper bounds for g parameters of .35
mirt.pars <- mirt::mirt( dat, mirtmodel, itemtype="3PL",  pars="values")
ind <- which( mirt.pars$name=="g" )
mirt.pars[ ind, "value" ] <- stats::plogis(-1.38)
mirt.pars[ ind, "ubound" ] <- .35
```

```
  # prior distribution for slopes
ind <- which( mirt.pars$name=="a1" )
mirt.pars[ ind, "prior_1" ] <- 1.3
mirt.pars[ ind, "prior_2" ] <- 2
mod3c2 <- mirt::mirt(dat, mirtmodel, itemtype="3PL",
                pars=mirt.pars,verbose=TRUE, technical=list(NCYCLES=100) )
coef(mod3c2)
sirt::mirt.wrapper.coef(mod3c2)

#----  M3d: ltm (in ltm)
mod3d <- ltm::tpm( dat, control=list(verbose=TRUE), max.guessing=.3)
summary(mod3d)
coef(mod3d) #=> numerical instabilities

#*****************************************************
# Model 4: 3-dimensional Rasch model
#*****************************************************

# define Q-matrix
Q <- matrix( 0, nrow=12, ncol=3 )
Q[ cbind(1:12, rep(1:3,each=4) ) ] <- 1
rownames(Q) <- colnames(dat)
colnames(Q) <- c("A","B","C")

# define nodes
theta.k <- seq(-6,6,len=13)

#----  M4a: smirt (in sirt)
mod4a <- sirt::smirt(dat,Qmatrix=Q,irtmodel="comp", theta.k=theta.k, maxiter=30)
summary(mod4a)

#----  M4b: rasch.mml2 (in sirt)
mod4b <- sirt::rasch.mml2(dat,Q=Q,theta.k=theta.k, mmliter=30)
summary(mod4b)

#----  M4c: gdm (in CDM)
mod4c <- CDM::gdm( dat, irtmodel="1PL", theta.k=theta.k, skillspace="normal",
            Qmatrix=Q, maxiter=30, centered.latent=TRUE )
summary(mod4c)

#----  M4d: tam.mml (in TAM)
mod4d <- TAM::tam.mml( resp=dat, Q=Q, control=list(nodes=theta.k, maxiter=30) )
summary(mod4d)

#----  M4e: R2noharm (in NOHARM, running from within R using sirt package)
noharm.path <- "c:/NOHARM"
  # covariance matrix
P.pattern <- matrix( 1, ncol=3, nrow=3 )
P.init <- 0.8+0*P.pattern
diag(P.init) <- 1
  # loading matrix
F.pattern <- 0*Q
F.init <- Q
```

```
  # estimate model
mod4e <- sirt::R2noharm( dat=dat, model.type="CFA", F.pattern=F.pattern,
    F.init=F.init, P.pattern=P.pattern, P.init=P.init,
    writename="ex4e", noharm.path=noharm.path, dec="," )
summary(mod4e)

#----  M4f: mirt (in mirt)
cmodel <- mirt::mirt.model("
     F1=1-4
     F2=5-8
     F3=9-12
     # equal item slopes correspond to the Rasch model
     CONSTRAIN=(1-4, a1), (5-8, a2), (9-12,a3)
     COV=F1*F2, F1*F3, F2*F3
     " )
mod4f <- mirt::mirt(dat, cmodel, verbose=TRUE)
summary(mod4f)

#*****************************************************
# Model 5: 3-dimensional 2PL model
#*****************************************************

#----  M5a: smirt (in sirt)
mod5a <- sirt::smirt(dat,Qmatrix=Q,irtmodel="comp", est.a="2PL", theta.k=theta.k,
                maxiter=30)
summary(mod5a)

#----  M5b: rasch.mml2 (in sirt)
mod5b <- sirt::rasch.mml2(dat,Q=Q,theta.k=theta.k,est.a=1:12, mmliter=30)
summary(mod5b)

#----  M5c: gdm (in CDM)
mod5c <- CDM::gdm( dat, irtmodel="2PL", theta.k=theta.k, skillspace="loglinear",
            Qmatrix=Q, maxiter=30, centered.latent=TRUE,
            standardized.latent=TRUE)
summary(mod5c)

#----  M5d: tam.mml (in TAM)
mod5d <- TAM::tam.mml.2pl( resp=dat, Q=Q, control=list(nodes=theta.k, maxiter=30) )
summary(mod5d)

#----  M5e: R2noharm (in NOHARM, running from within R using sirt package)
noharm.path <- "c:/NOHARM"
  # covariance matrix
P.pattern <- matrix( 1, ncol=3, nrow=3 )
diag(P.pattern) <- 0
P.init <- 0.8+0*P.pattern
diag(P.init) <- 1
  # loading matrix
F.pattern <- Q
F.init <- Q
  # estimate model
mod5e <- sirt::R2noharm( dat=dat, model.type="CFA", F.pattern=F.pattern,
```

```
    F.init=F.init, P.pattern=P.pattern, P.init=P.init,
    writename="ex5e", noharm.path=noharm.path, dec="," )
summary(mod5e)

#----  M5f: mirt (in mirt)
cmodel <- mirt::mirt.model("
   F1=1-4
   F2=5-8
   F3=9-12
   COV=F1*F2, F1*F3, F2*F3
   "  )
mod5f <- mirt::mirt(dat, cmodel, verbose=TRUE)
summary(mod5f)

#*****************************************************
# Model 6: Network models (Graphical models)
#*****************************************************

#----  M6a: Ising model using the IsingFit package (undirected graph)
#        - fit Ising model using the "OR rule" (AND=FALSE)
mod6a <- IsingFit::IsingFit(x=dat, family="binomial", AND=FALSE)
summary(mod6a)
##           Network Density:                0.29
##    Gamma:                  0.25
##    Rule used:              Or-rule
# plot results
qgraph::qgraph(mod6a$weiadj,fade=FALSE)

#**-- graph estimation using pcalg package

# some packages from Bioconductor must be downloaded at first (if not yet done)
if (FALSE){  # set 'if (TRUE)' if packages should be downloaded
     source("http://bioconductor.org/biocLite.R")
     biocLite("RBGL")
     biocLite("Rgraphviz")
}

#----  M6b: graph estimation based on Pearson correlations
V <- colnames(dat)
n <- nrow(dat)
mod6b <- pcalg::pc(suffStat=list(C=stats::cor(dat), n=n ),
             indepTest=gaussCItest, ## indep.test: partial correlations
             alpha=0.05, labels=V, verbose=TRUE)
plot(mod6b)
# plot in qgraph package
qgraph::qgraph(mod6b, label.color=rep( c( "red", "blue","darkgreen" ), each=4 ),
         edge.color="black")
summary(mod6b)

#----  M6c: graph estimation based on tetrachoric correlations
mod6c <- pcalg::pc(suffStat=list(C=sirt::tetrachoric2(dat)$rho, n=n ),
             indepTest=gaussCItest, alpha=0.05, labels=V, verbose=TRUE)
plot(mod6c)
```

```
summary(mod6c)

#----  M6d: Statistical implicative analysis (in sirt)
mod6d <- sirt::sia.sirt(dat, significance=.85 )
  # plot results with igraph and qgraph package
plot( mod6d$igraph.obj, vertex.shape="rectangle", vertex.size=30 )
qgraph::qgraph( mod6d$adj.matrix )

#*****************************************************
# Model 7: Latent class analysis with 3 classes
#*****************************************************

#----  M7a: randomLCA (in randomLCA)
  #        - use two trials of starting values
mod7a <- randomLCA::randomLCA(dat,nclass=3, notrials=2, verbose=TRUE)
summary(mod7a)
plot(mod7a,type="l", xlab="Item")

#----  M7b: rasch.mirtlc (in sirt)
mod7b <- sirt::rasch.mirtlc( dat, Nclasses=3,seed=-30,  nstarts=2 )
summary(mod7b)
matplot( t(mod7b$pjk), type="l", xlab="Item" )

#----  M7c: poLCA (in poLCA)
  #   define formula for outcomes
f7c <- paste0( "cbind(", paste0(colnames(dat),collapse=","), ") ~ 1 " )
dat1 <- as.data.frame( dat + 1 ) # poLCA needs integer values from 1,2,..
mod7c <- poLCA::poLCA( stats::as.formula(f7c),dat1,nclass=3, verbose=TRUE)
plot(mod7c)

#----  M7d: gom.em (in sirt)
  #    - the latent class model is a special grade of membership model
mod7d <- sirt::gom.em( dat, K=3, problevels=c(0,1),  model="GOM"  )
summary(mod7d)

#---- - M7e: mirt (in mirt)
  # define three latent classes
Theta <- diag(3)
  # define mirt model
I <- ncol(dat)  # I=12
mirtmodel <- mirt::mirt.model("
        C1=1-12
        C2=1-12
        C3=1-12
        ")
  # get initial parameter values
mod.pars <- mirt::mirt(dat, model=mirtmodel,  pars="values")
  # modify parameters: only slopes refer to item-class probabilities
set.seed(9976)
  # set starting values for class specific item probabilities
mod.pars[ mod.pars$name=="d","value" ]  <- 0
mod.pars[ mod.pars$name=="d","est" ]  <- FALSE
b1 <- stats::qnorm( colMeans( dat ) )
```

```
mod.pars[ mod.pars$name=="a1","value" ]  <- b1
  # random starting values for other classes
mod.pars[ mod.pars$name %in% c("a2","a3"),"value" ]  <- b1 + stats::runif(12*2,-1,1)
mod.pars
  #** define prior for latent class analysis
lca_prior <- function(Theta,Etable){
  # number of latent Theta classes
  TP <- nrow(Theta)
  # prior in initial iteration
  if ( is.null(Etable) ){
    prior <- rep( 1/TP, TP )
  }
  # process Etable (this is correct for datasets without missing data)
  if ( ! is.null(Etable) ){
    # sum over correct and incorrect expected responses
    prior <- ( rowSums(Etable[, seq(1,2*I,2)]) + rowSums(Etable[,seq(2,2*I,2)]) )/I
  }
  prior <- prior / sum(prior)
  return(prior)
}
  #** estimate model
mod7e <- mirt::mirt(dat, mirtmodel, pars=mod.pars, verbose=TRUE,
            technical=list( customTheta=Theta, customPriorFun=lca_prior) )
  # compare estimated results
print(mod7e)
summary(mod7b)
  # The number of estimated parameters is incorrect because mirt does not correctly count
  # estimated parameters from the user customized  prior distribution.
mod7e@nest <- as.integer(sum(mod.pars$est) + 2)  # two additional class probabilities
  # extract log-likelihood
mod7e@logLik
  # compute AIC and BIC
( AIC <- -2*mod7e@logLik+2*mod7e@nest )
( BIC <- -2*mod7e@logLik+log(mod7e@Data$N)*mod7e@nest )
  # RMSEA and SRMSR fit statistic
mirt::M2(mod7e)     # TLI and CFI does not make sense in this example
  #** extract item parameters
sirt::mirt.wrapper.coef(mod7e)
  #** extract class-specific item-probabilities
probs <- apply( coef1[, c("a1","a2","a3") ], 2, stats::plogis )
matplot( probs, type="l", xlab="Item", main="mirt::mirt")
  #** inspect estimated distribution
mod7e@Theta
mod7e@Prior[[1]]

#*****************************************************
# Model 8: Mixed Rasch model with two classes
#*****************************************************

#----  M8a: raschmix (in psychomix)
mod8a <- psychomix::raschmix(data=as.matrix(dat), k=2, scores="saturated")
summary(mod8a)
```

```
#----  M8b: mrm (in mRm)
mod8b <- mRm::mrm(data.matrix=dat, cl=2)
mod8b$conv.to.bound
plot(mod8b)
print(mod8b)

#----  M8c: mirt (in mirt)
  #* define theta grid
theta.k <- seq( -5, 5, len=9 )
TP <- length(theta.k)
Theta <- matrix( 0, nrow=2*TP, ncol=4)
Theta[1:TP,1:2] <- cbind(theta.k, 1 )
Theta[1:TP + TP,3:4] <- cbind(theta.k, 1 )
Theta
  # define model
I <- ncol(dat)  # I=12
mirtmodel <- mirt::mirt.model("
        F1a=1-12  # slope Class 1
        F1b=1-12  # difficulty Class 1
        F2a=1-12  # slope Class 2
        F2b=1-12  # difficulty Class 2
        CONSTRAIN=(1-12,a1),(1-12,a3)
        ")
  # get initial parameter values
mod.pars <- mirt::mirt(dat, model=mirtmodel,  pars="values")
  # set starting values for class specific item probabilities
mod.pars[ mod.pars$name=="d","value" ]  <- 0
mod.pars[ mod.pars$name=="d","est" ]  <- FALSE
mod.pars[ mod.pars$name=="a1","value" ]  <- 1
mod.pars[ mod.pars$name=="a3","value" ]  <- 1
  # initial values difficulties
b1 <-  stats::qlogis( colMeans(dat) )
mod.pars[ mod.pars$name=="a2","value" ]  <- b1
mod.pars[ mod.pars$name=="a4","value" ]  <- b1 + stats::runif(I, -1, 1)
  #* define prior for mixed Rasch analysis
mixed_prior <- function(Theta,Etable){
  NC <- 2   # number of theta classes
  TP <- nrow(Theta) / NC
  prior1 <- stats::dnorm( Theta[1:TP,1] )
  prior1 <- prior1 / sum(prior1)
  if ( is.null(Etable) ){   prior <- c( prior1, prior1 ) }
  if ( ! is.null(Etable) ){
    prior <- ( rowSums( Etable[, seq(1,2*I,2)] ) +
                  rowSums( Etable[,seq(2,2*I,2)]) )/I
    a1 <- stats::aggregate( prior, list( rep(1:NC, each=TP) ), sum )
    a1[,2] <- a1[,2] / sum( a1[,2])
    # print some information during estimation
    cat( paste0( " Class proportions: ",
              paste0( round(a1[,2], 3 ), collapse=" " ) ), "\n")
    a1 <- rep( a1[,2], each=TP )
    # specify mixture of two normal distributions
    prior <- a1*c(prior1,prior1)
  }
```

```
  prior <- prior / sum(prior)
  return(prior)
}
  #* estimate model
mod8c <- mirt::mirt(dat, mirtmodel, pars=mod.pars, verbose=TRUE,
        technical=list(  customTheta=Theta, customPriorFun=mixed_prior ) )
  # Like in Model 7e, the number of estimated parameters must be included.
mod8c@nest <- as.integer(sum(mod.pars$est) + 1)
      # two class proportions and therefore one probability is freely estimated.
  #* extract item parameters
sirt::mirt.wrapper.coef(mod8c)
  #* estimated distribution
mod8c@Theta
mod8c@Prior

#----  M8d: tamaan (in TAM)

tammodel <- "
ANALYSIS:
  TYPE=MIXTURE ;
  NCLASSES(2);
  NSTARTS(7,20);
LAVAAN MODEL:
  F=~ A1__C4
  F ~~ F
ITEM TYPE:
  ALL(Rasch);
    "
mod8d <- TAM::tamaan( tammodel, resp=dat )
summary(mod8d)
# plot item parameters
I <- 12
ipars <- mod8d$itempartable_MIXTURE[ 1:I, ]
plot( 1:I, ipars[,3], type="o", ylim=range( ipars[,3:4] ), pch=16,
        xlab="Item", ylab="Item difficulty")
lines( 1:I, ipars[,4], type="l", col=2, lty=2)
points( 1:I, ipars[,4],  col=2, pch=2)

#*****************************************************
# Model 9: Mixed 2PL model with two classes
#*****************************************************

#----  M9a: tamaan (in TAM)

tammodel <- "
ANALYSIS:
  TYPE=MIXTURE ;
  NCLASSES(2);
  NSTARTS(10,30);
LAVAAN MODEL:
  F=~ A1__C4
  F ~~ F
ITEM TYPE:
```

```
  ALL(2PL);
    "
mod9a <- TAM::tamaan( tammodel, resp=dat )
summary(mod9a)

#*****************************************************
# Model 10: Rasch testlet model
#*****************************************************

#----  M10a: tam.fa (in TAM)
dims <- substring( colnames(dat),1,1 )  # define dimensions
mod10a <- TAM::tam.fa( resp=dat, irtmodel="bifactor1", dims=dims,
               control=list(maxiter=60) )
summary(mod10a)

#----  M10b: mirt (in mirt)
cmodel <- mirt::mirt.model("
        G=1-12
        A=1-4
        B=5-8
        C=9-12
        CONSTRAIN=(1-12,a1), (1-4, a2), (5-8, a3), (9-12,a4)
      ")
mod10b <- mirt::mirt(dat, model=cmodel, verbose=TRUE)
summary(mod10b)
coef(mod10b)
mod10b@logLik   # equivalent is slot( mod10b, "logLik")

#alternatively, using a dimensional reduction approach (faster and better accuracy)
cmodel <- mirt::mirt.model("
      G=1-12
      CONSTRAIN=(1-12,a1), (1-4, a2), (5-8, a3), (9-12,a4)
     ")
item_bundles <- rep(c(1,2,3), each=4)
mod10b1 <- mirt::bfactor(dat, model=item_bundles, model2=cmodel, verbose=TRUE)
coef(mod10b1)

#----  M10c: smirt (in sirt)
  # define Q-matrix
Qmatrix <- matrix(0,12,4)
Qmatrix[,1] <- 1
Qmatrix[ cbind( 1:12, match( dims, unique(dims)) +1 ) ]  <- 1
  # uncorrelated factors
variance.fixed <- cbind( c(1,1,1,2,2,3), c(2,3,4,3,4,4), 0 )
  # estimate model
mod10c <- sirt::smirt( dat, Qmatrix=Qmatrix, irtmodel="comp",
              variance.fixed=variance.fixed, qmcnodes=1000, maxiter=60)
summary(mod10c)

#*****************************************************
# Model 11: Bifactor model
#*****************************************************
```

```
#----  M11a: tam.fa (in TAM)
dims <- substring( colnames(dat),1,1 )  # define dimensions
mod11a <- TAM::tam.fa( resp=dat, irtmodel="bifactor2", dims=dims,
                 control=list(maxiter=60) )
summary(mod11a)

#----  M11b: bfactor (in mirt)
dims1 <- match( dims, unique(dims) )
mod11b <- mirt::bfactor(dat, model=dims1, verbose=TRUE)
summary(mod11b)
coef(mod11b)
mod11b@logLik

#----  M11c: smirt (in sirt)
  # define Q-matrix
Qmatrix <- matrix(0,12,4)
Qmatrix[,1] <- 1
Qmatrix[ cbind( 1:12, match( dims, unique(dims)) +1 ) ]  <- 1
  # uncorrelated factors
variance.fixed <- cbind( c(1,1,1,2,2,3), c(2,3,4,3,4,4), 0 )
  # estimate model
mod11c <- sirt::smirt( dat, Qmatrix=Qmatrix, irtmodel="comp", est.a="2PL",
                variance.fixed=variance.fixed, qmcnodes=1000, maxiter=60)
summary(mod11c)

#*****************************************************
# Model 12: Located latent class model: Rasch model with three theta classes
#*****************************************************

# use 10th item as the reference item
ref.item <- 10
# ability grid
theta.k <- seq(-4,4,len=9)

#----  M12a: rasch.mirtlc (in sirt)
mod12a <- sirt::rasch.mirtlc(dat, Nclasses=3, modeltype="MLC1", ref.item=ref.item)
summary(mod12a)

#----  M12b: gdm (in CDM)
theta.k <- seq(-1, 1, len=3)      # initial matrix
b.constraint <- matrix( c(10,1,0), nrow=1,ncol=3)
  # estimate model
mod12b <- CDM::gdm( dat, theta.k=theta.k, skillspace="est", irtmodel="1PL",
              b.constraint=b.constraint, maxiter=200)
summary(mod12b)

#----  M12c: mirt (in mirt)
items <- colnames(dat)
  # define three latent classes
Theta <- diag(3)
  # define mirt model
I <- ncol(dat)  # I=12
mirtmodel <- mirt::mirt.model("
```

```
        C1=1-12
        C2=1-12
        C3=1-12
        CONSTRAIN=(1-12,a1),(1-12,a2),(1-12,a3)
        ")
  # get parameters
mod.pars <- mirt(dat, model=mirtmodel,  pars="values")
 # set starting values for class specific item probabilities
mod.pars[ mod.pars$name=="d","value" ]  <- stats::qlogis( colMeans(dat,na.rm=TRUE) )
  # set item difficulty of reference item to zero
ind <- which( ( paste(mod.pars$item)==items[ref.item] ) &
              ( ( paste(mod.pars$name)=="d" ) ) )
mod.pars[ ind,"value" ]  <- 0
mod.pars[ ind,"est" ]  <- FALSE
  # initial values for a1, a2 and a3
mod.pars[ mod.pars$name %in% c("a1","a2","a3"),"value" ]  <- c(-1,0,1)
mod.pars
  #* define prior for latent class analysis
lca_prior <- function(Theta,Etable){
  # number of latent Theta classes
  TP <- nrow(Theta)
  # prior in initial iteration
  if ( is.null(Etable) ){
    prior <- rep( 1/TP, TP )
             }
  # process Etable (this is correct for datasets without missing data)
  if ( ! is.null(Etable) ){
    # sum over correct and incorrect expected responses
    prior <- ( rowSums( Etable[, seq(1,2*I,2)] ) + rowSums( Etable[, seq(2,2*I,2)] ) )/I
           }
  prior <- prior / sum(prior)
  return(prior)
   }
 #* estimate model
mod12c <- mirt(dat, mirtmodel, technical=list(
            customTheta=Theta, customPriorFun=lca_prior),
            pars=mod.pars, verbose=TRUE )
  # estimated parameters from the user customized  prior distribution.
mod12c@nest <- as.integer(sum(mod.pars$est) + 2)
  #* extract item parameters
coef1 <- sirt::mirt.wrapper.coef(mod12c)
  #* inspect estimated distribution
mod12c@Theta
coef1$coef[1,c("a1","a2","a3")]
mod12c@Prior[[1]]

#*****************************************************
# Model 13: Multidimensional model with discrete traits
#*****************************************************
# define Q-Matrix
Q <- matrix( 0, nrow=12,ncol=3)
Q[1:4,1] <- 1
Q[5:8,2] <- 1
```

```
Q[9:12,3] <- 1
# define discrete theta distribution with 3 dimensions
Theta <- scan(what="character",nlines=1)
  000 100 010 001 110 101 011 111
Theta <- as.numeric( unlist( lapply( Theta, strsplit, split="")   ) )
Theta <- matrix(Theta, 8, 3, byrow=TRUE )
Theta

#----  Model 13a: din (in CDM)
mod13a <- CDM::din( dat, q.matrix=Q, rule="DINA")
summary(mod13a)
# compare used Theta distributions
cbind( Theta, mod13a$attribute.patt.splitted)

#----  Model 13b: gdm (in CDM)
mod13b <- CDM::gdm( dat, Qmatrix=Q, theta.k=Theta, skillspace="full")
summary(mod13b)

#----  Model 13c: mirt (in mirt)
  # define mirt model
I <- ncol(dat)  # I=12
mirtmodel <- mirt::mirt.model("
        F1=1-4
        F2=5-8
        F3=9-12
        ")
  # get parameters
mod.pars <- mirt(dat, model=mirtmodel,  pars="values")
# starting values d parameters (transformed guessing parameters)
ind <- which(  mod.pars$name=="d"  )
mod.pars[ind,"value"] <- stats::qlogis(.2)
# starting values transformed slipping parameters
ind <- which( ( mod.pars$name %in% paste0("a",1:3)  ) &  ( mod.pars$est ) )
mod.pars[ind,"value"] <- stats::qlogis(.8) - stats::qlogis(.2)
mod.pars

  #* define prior for latent class analysis
lca_prior <- function(Theta,Etable){
  TP <- nrow(Theta)
  if ( is.null(Etable) ){
    prior <- rep( 1/TP, TP )
              }
  if ( ! is.null(Etable) ){
    prior <- ( rowSums( Etable[, seq(1,2*I,2)] ) + rowSums( Etable[, seq(2,2*I,2)] ) )/I
            }
  prior <- prior / sum(prior)
  return(prior)
}
 #* estimate model
mod13c <- mirt(dat, mirtmodel, technical=list(
            customTheta=Theta, customPriorFun=lca_prior),
            pars=mod.pars, verbose=TRUE )
  # estimated parameters from the user customized  prior distribution.
```

```
mod13c@nest <- as.integer(sum(mod.pars$est) + 2)
  #* extract item parameters
coef13c <- sirt::mirt.wrapper.coef(mod13c)$coef
  #* inspect estimated distribution
mod13c@Theta
mod13c@Prior[[1]]

 #-* comparisons of estimated  parameters
# extract guessing and slipping parameters from din
dfr <- coef(mod13a)[, c("guess","slip") ]
colnames(dfr) <- paste0("din.",c("guess","slip") )
# estimated parameters from gdm
dfr$gdm.guess <- stats::plogis(mod13b$item$b)
dfr$gdm.slip <- 1 - stats::plogis( rowSums(mod13b$item[,c("b.Cat1","a.F1","a.F2","a.F3")] ) )
# estimated parameters from mirt
dfr$mirt.guess <- stats::plogis( coef13c$d )
dfr$mirt.slip <- 1 - stats::plogis( rowSums(coef13c[,c("d","a1","a2","a3")]) )
# comparison
round(dfr[, c(1,3,5,2,4,6)],3)
  ##      din.guess gdm.guess mirt.guess din.slip gdm.slip mirt.slip
  ##   A1     0.691     0.684      0.686    0.000    0.000     0.000
  ##   A2     0.491     0.489      0.489    0.031    0.038     0.036
  ##   A3     0.302     0.300      0.300    0.184    0.193     0.190
  ##   A4     0.244     0.239      0.240    0.337    0.340     0.339
  ##   B1     0.568     0.579      0.577    0.163    0.148     0.151
  ##   B2     0.329     0.344      0.340    0.344    0.326     0.329
  ##   B3     0.817     0.827      0.825    0.014    0.007     0.009
  ##   B4     0.431     0.463      0.456    0.104    0.089     0.092
  ##   C1     0.188     0.191      0.189    0.013    0.013     0.013
  ##   C2     0.050     0.050      0.050    0.239    0.238     0.239
  ##   C3     0.000     0.002      0.001    0.065    0.065     0.065
  ##   C4     0.000     0.004      0.000    0.212    0.212     0.212

# estimated class sizes
dfr <- data.frame( "Theta"=Theta, "din"=mod13a$attribute.patt$class.prob,
                   "gdm"=mod13b$pi.k, "mirt"=mod13c@Prior[[1]])
# comparison
round(dfr,3)
  ##     Theta.1 Theta.2 Theta.3   din   gdm  mirt
  ##   1       0       0       0 0.039 0.041 0.040
  ##   2       1       0       0 0.008 0.009 0.009
  ##   3       0       1       0 0.009 0.007 0.008
  ##   4       0       0       1 0.394 0.417 0.412
  ##   5       1       1       0 0.011 0.011 0.011
  ##   6       1       0       1 0.017 0.042 0.037
  ##   7       0       1       1 0.042 0.008 0.016
  ##   8       1       1       1 0.480 0.465 0.467

#*****************************************************
# Model 14: DINA model with two skills
#*****************************************************

# define some simple Q-Matrix (does not really make in this application)
```

```
Q <- matrix( 0, nrow=12,ncol=2)
Q[1:4,1] <- 1
Q[5:8,2] <- 1
Q[9:12,1:2] <- 1
# define discrete theta distribution with 3 dimensions
Theta <- scan(what="character",nlines=1)
  00 10 01 11
Theta <- as.numeric( unlist( lapply( Theta, strsplit, split="")   ) )
Theta <- matrix(Theta, 4, 2, byrow=TRUE )
Theta

#----  Model 14a: din (in CDM)
mod14a <- CDM::din( dat, q.matrix=Q, rule="DINA")
summary(mod14a)
# compare used Theta distributions
cbind( Theta, mod14a$attribute.patt.splitted)

#----  Model 14b: mirt (in mirt)
  # define mirt model
I <- ncol(dat)  # I=12
mirtmodel <- mirt::mirt.model("
        F1=1-4
        F2=5-8
        (F1*F2)=9-12
        ")
#-> constructions like (F1*F2*F3) are also allowed in mirt.model
  # get parameters
mod.pars <- mirt(dat, model=mirtmodel,  pars="values")
# starting values d parameters (transformed guessing parameters)
ind <- which(  mod.pars$name=="d"  )
mod.pars[ind,"value"] <- stats::qlogis(.2)
# starting values transformed slipping parameters
ind <- which( ( mod.pars$name %in% paste0("a",1:3)  ) &  ( mod.pars$est ) )
mod.pars[ind,"value"] <- stats::qlogis(.8) - stats::qlogis(.2)
mod.pars
 #* use above defined prior lca_prior
 # lca_prior <- function(prior,Etable) ...
 #* estimate model
mod14b <- mirt(dat, mirtmodel, technical=list(
            customTheta=Theta, customPriorFun=lca_prior),
            pars=mod.pars, verbose=TRUE )
  # estimated parameters from the user customized  prior distribution.
mod14b@nest <- as.integer(sum(mod.pars$est) + 2)
  #* extract item parameters
coef14b <- sirt::mirt.wrapper.coef(mod14b)$coef

 #-* comparisons of estimated  parameters
# extract guessing and slipping parameters from din
dfr <- coef(mod14a)[, c("guess","slip") ]
colnames(dfr) <- paste0("din.",c("guess","slip") )
# estimated parameters from mirt
dfr$mirt.guess <- stats::plogis( coef14b$d )
dfr$mirt.slip <- 1 - stats::plogis( rowSums(coef14b[,c("d","a1","a2","a3")]) )
```

```
# comparison
round(dfr[, c(1,3,2,4)],3)
  ##      din.guess mirt.guess din.slip mirt.slip
  ##   A1     0.674      0.671    0.030     0.030
  ##   A2     0.423      0.420    0.049     0.050
  ##   A3     0.258      0.255    0.224     0.225
  ##   A4     0.245      0.243    0.394     0.395
  ##   B1     0.534      0.543    0.166     0.164
  ##   B2     0.338      0.347    0.382     0.380
  ##   B3     0.796      0.802    0.016     0.015
  ##   B4     0.421      0.436    0.142     0.140
  ##   C1     0.850      0.851    0.000     0.000
  ##   C2     0.480      0.480    0.097     0.097
  ##   C3     0.746      0.746    0.026     0.026
  ##   C4     0.575      0.577    0.136     0.137

# estimated class sizes
dfr <- data.frame( "Theta"=Theta, "din"=mod13a$attribute.patt$class.prob,
                   "mirt"=mod14b@Prior[[1]])
# comparison
round(dfr,3)
  ##     Theta.1 Theta.2   din  mirt
  ##   1       0       0 0.357 0.369
  ##   2       1       0 0.044 0.049
  ##   3       0       1 0.047 0.031
  ##   4       1       1 0.553 0.551

#*****************************************************
# Model 15: Rasch model with non-normal distribution
#*****************************************************

# A non-normal theta distributed is specified by log-linear smoothing
# the distribution as described in
# Xu, X., & von Davier, M. (2008). Fitting the structured general diagnostic model
# to NAEP data. ETS Research Report ETS RR-08-27. Princeton, ETS.

# define theta grid
theta.k <- matrix( seq(-4,4,len=15), ncol=1 )
# define design matrix for smoothing (up to cubic moments)
delta.designmatrix <- cbind( 1, theta.k, theta.k^2, theta.k^3 )
# constrain item difficulty of fifth item (item B1) to zero
b.constraint <- matrix( c(5,1,0), ncol=3 )

#----  Model 15a: gdm (in CDM)
mod15a <- CDM::gdm( dat, irtmodel="1PL", theta.k=theta.k,
              b.constraint=b.constraint  )
summary(mod15a)
 # plot estimated distribution
graphics::barplot( mod15a$pi.k[,1], space=0, names.arg=round(theta.k[,1],2),
           main="Estimated Skewed Distribution (gdm function)")

#----  Model 15b: mirt (in mirt)
 # define mirt model
```

```
mirtmodel <- mirt::mirt.model("
    F=1-12
    ")
 # get parameters
mod.pars <- mirt::mirt(dat, model=mirtmodel, pars="values", itemtype="Rasch")
  # fix variance (just for correct counting of parameters)
mod.pars[ mod.pars$name=="COV_11", "est"] <- FALSE
  # fix item difficulty
ind <- which( ( mod.pars$item=="B1" ) & ( mod.pars$name=="d" ) )
mod.pars[ ind, "value"] <- 0
mod.pars[ ind, "est"] <- FALSE

 # define prior
loglinear_prior <- function(Theta,Etable){
    TP <- nrow(Theta)
    if ( is.null(Etable) ){
    prior <- rep( 1/TP, TP )
           }
    # process Etable (this is correct for datasets without missing data)
    if ( ! is.null(Etable) ){
          # sum over correct and incorrect expected responses
      prior <- ( rowSums( Etable[, seq(1,2*I,2)] ) + rowSums( Etable[, seq(2,2*I,2)] ) )/I
       # smooth prior using the above design matrix and a log-linear model
       # see Xu & von Davier (2008).
       y <- log( prior + 1E-15 )
       lm1 <- lm( y ~ 0 + delta.designmatrix, weights=prior )
       prior <- exp(fitted(lm1))   # smoothed prior
           }
    prior <- prior / sum(prior)
    return(prior)
}

#* estimate model
mod15b <- mirt::mirt(dat, mirtmodel, technical=list(
                customTheta=theta.k, customPriorFun=loglinear_prior ),
                pars=mod.pars, verbose=TRUE )
# estimated parameters from the user customized prior distribution.
mod15b@nest <- as.integer(sum(mod.pars$est) + 3)
#* extract item parameters
coef1 <- sirt::mirt.wrapper.coef(mod15b)$coef

#** compare estimated item parameters
dfr <- data.frame( "gdm"=mod15a$item$b.Cat1, "mirt"=coef1$d )
rownames(dfr) <- colnames(dat)
round(t(dfr),4)
  ##           A1     A2      A3      A4 B1      B2     B3     B4     C1    C2     C3    C4
  ##   gdm  0.9818 0.1538 -0.7837 -1.3197  0 -1.0902 1.6088 -0.170 1.9778 0.006 1.1859 0.135
  ##   mirt 0.9829 0.1548 -0.7826 -1.3186  0 -1.0892 1.6099 -0.169 1.9790 0.007 1.1870 0.136
# compare estimated theta distribution
dfr <- data.frame( "gdm"=mod15a$pi.k, "mirt"=mod15b@Prior[[1]] )
round(t(dfr),4)
  ##       1 2     3     4      5      6      7      8      9     10     11     12     13
  ##   gdm  0 0 1e-04 9e-04 0.0056 0.0231 0.0652 0.1299 0.1881 0.2038 0.1702 0.1129 0.0612
```

```
##   mirt 0 0 1e-04 9e-04 0.0056 0.0232 0.0653 0.1300 0.1881 0.2038 0.1702 0.1128 0.0611
##            14    15
##   gdm  0.0279 0.011
##   mirt 0.0278 0.011

## End(Not run)
```

`data.reck` *Datasets from Reckase' Book* Multidimensional Item Response Theory

---

Description

Some simulated datasets from Reckase (2009).

Usage

```
data(data.reck21)
data(data.reck61DAT1)
data(data.reck61DAT2)
data(data.reck73C1a)
data(data.reck73C1b)
data(data.reck75C2)
data(data.reck78ExA)
data(data.reck79ExB)
```

Format

- The format of the `data.reck21` (Table 2.1, p. 45) is:

```
List of 2
$ data: num [1:2500, 1:50] 0 0 0 1 1 0 0 0 1 0 ...
..- attr(*, "dimnames")=List of 2
.. ..$ : NULL
.. ..$ : chr [1:50] "I0001" "I0002" "I0003" "I0004" ...
$ pars:'data.frame':
..$ a: num [1:50] 1.83 1.38 1.47 1.53 0.88 0.82 1.02 1.19 1.15 0.18 ...
..$ b: num [1:50] 0.91 0.81 0.06 -0.8 0.24 0.99 1.23 -0.47 2.78 -3.85 ...
..$ c: num [1:50] 0 0 0 0.25 0.21 0.29 0.26 0.19 0 0.21 ...
```

- The format of the datasets `data.reck61DAT1` and `data.reck61DAT2` (Table 6.1, p. 153) is

```
List of 4
$ data : num [1:2500, 1:30] 1 0 0 1 1 0 0 1 1 0 ...
..- attr(*, "dimnames")=List of 2
.. ..$ : NULL
.. ..$ : chr [1:30] "A01" "A02" "A03" "A04" ...
$ pars :'data.frame':
..$ a1: num [1:30] 0.747 0.46 0.861 1.014 0.552 ...
```

```
..$ a2: num [1:30] 0.025 0.0097 0.0067 0.008 0.0204 0.0064 0.0861 ...
..$ a3: num [1:30] 0.1428 0.0692 0.404 0.047 0.1482 ...
..$ d : num [1:30] 0.183 -0.192 -0.466 -0.434 -0.443 ...
$ mu : num [1:3] -0.4 -0.7 0.1
$ sigma: num [1:3, 1:3] 1.21 0.297 1.232 0.297 0.81 ...
```

The dataset `data.reck61DAT2` has correlated dimensions while `data.reck61DAT1` has uncorrelated dimensions.

- Datasets `data.reck73C1a` and `data.reck73C1b` use item parameters from Table 7.3 (p. 188). The dataset `C1a` has uncorrelated dimensions, while `C1b` has perfectly correlated dimensions. The items are sensitive to 3 dimensions. The format of the datasets is

```
List of 4
$ data : num [1:2500, 1:30] 1 0 1 1 1 0 1 1 1 1 ...
..- attr(*, "dimnames")=List of 2
.. ..$ : NULL
.. ..$ : chr [1:30] "A01" "A02" "A03" "A04" ...
$ pars :'data.frame': 30 obs. of 4 variables:
..$ a1: num [1:30] 0.747 0.46 0.861 1.014 0.552 ...
..$ a2: num [1:30] 0.025 0.0097 0.0067 0.008 0.0204 0.0064 ...
..$ a3: num [1:30] 0.1428 0.0692 0.404 0.047 0.1482 ...
..$ d : num [1:30] 0.183 -0.192 -0.466 -0.434 -0.443 ...
$ mu : num [1:3] 0 0 0
$ sigma: num [1:3, 1:3] 0.167 0.236 0.289 0.236 0.334 ...
```

- The dataset `data.reck75C2` is simulated using item parameters from Table 7.5 (p. 191). It contains items which are sensitive to only one dimension but individuals which have abilities in three uncorrelated dimensions. The format is

```
List of 4
$ data : num [1:2500, 1:30] 0 0 1 1 1 0 0 1 1 1 ...
..- attr(*, "dimnames")=List of 2
.. ..$ : NULL
.. ..$ : chr [1:30] "A01" "A02" "A03" "A04" ...
$ pars :'data.frame': 30 obs. of 4 variables:
..$ a1: num [1:30] 0.56 0.48 0.67 0.57 0.54 0.74 0.7 0.59 0.63 0.64 ...
..$ a2: num [1:30] 0.62 0.53 0.63 0.69 0.58 0.69 0.75 0.63 0.64 0.64 ...
..$ a3: num [1:30] 0.46 0.42 0.43 0.51 0.41 0.48 0.46 0.5 0.51 0.46 ...
..$ d : num [1:30] 0.1 0.06 -0.38 0.46 0.14 0.31 0.06 -1.23 0.47 1.06 ...
$ mu : num [1:3] 0 0 0
$ sigma: num [1:3, 1:3] 1 0 0 0 1 0 0 0 1
```

- The dataset `data.reck78ExA` contains simulated item responses from Table 7.8 (p. 204 ff.). There are three item clusters and two ability dimensions. The format is

```
List of 4
$ data : num [1:2500, 1:50] 0 1 1 0 1 0 0 0 0 0 ...
..- attr(*, "dimnames")=List of 2
.. ..$ : NULL
.. ..$ : chr [1:50] "A01" "A02" "A03" "A04" ...
```

```
$ pars :'data.frame': 50 obs. of 3 variables:
..$ a1: num [1:50] 0.889 1.057 1.047 1.178 1.029 ...
..$ a2: num [1:50] 0.1399 0.0432 0.016 0.0231 0.2347 ...
..$ d : num [1:50] 0.2724 1.2335 -0.0918 -0.2372 0.8471 ...
$ mu : num [1:2] 0 0
$ sigma: num [1:2, 1:2] 1 0 0 1
```

- The dataset `data.reck79ExB` contains simulated item responses from Table 7.9 (p. 207 ff.). There are three item clusters and three ability dimensions. The format is

```
List of 4
$ data : num [1:2500, 1:50] 1 1 0 1 0 0 0 1 1 0 ...
..- attr(*, "dimnames")=List of 2
.. ..$ : NULL
.. ..$ : chr [1:50] "A01" "A02" "A03" "A04" ...
$ pars :'data.frame': 50 obs. of 4 variables:
..$ a1: num [1:50] 0.895 1.032 1.036 1.163 1.022 ...
..$ a2: num [1:50] 0.052 0.132 0.144 0.13 0.165 ...
..$ a3: num [1:50] 0.0722 0.1923 0.0482 0.1321 0.204 ...
..$ d : num [1:50] 0.2724 1.2335 -0.0918 -0.2372 0.8471 ...
$ mu : num [1:3] 0 0 0
$ sigma: num [1:3, 1:3] 1 0 0 0 1 0 0 0 1
```

Source

Simulated datasets

References

Reckase, M. (2009). *Multidimensional item response theory*. New York: Springer. doi:10.1007/9780387899763

Examples

```
## Not run:
#############################################################################
# EXAMPLE 1: data.reck21 dataset, Table 2.1, p. 45
#############################################################################
data(data.reck21)

dat <- data.reck21$dat      # extract dataset

# items with zero guessing parameters
guess0 <- c( 1, 2, 3, 9,11,27,30,35,45,49,50 )
I <- ncol(dat)

#***
# Model 1: 3PL estimation using rasch.mml2
est.c <- est.a <- 1:I
est.c[ guess0 ] <- 0
```

```
mod1 <- sirt::rasch.mml2( dat, est.a=est.a, est.c=est.c, mmliter=300 )
summary(mod1)

#***
# Model 2: 3PL estimation using smirt
Q <- matrix(1,I,1)
mod2 <- sirt::smirt( dat, Qmatrix=Q, est.a="2PL", est.c=est.c, increment.factor=1.01)
summary(mod2)

#***
# Model 3: estimation in mirt package
library(mirt)
itemtype <- rep("3PL", I )
itemtype[ guess0 ] <- "2PL"
mod3 <- mirt::mirt(dat, 1, itemtype=itemtype, verbose=TRUE)
summary(mod3)

c3 <- unlist( coef(mod3) )[ 1:(4*I) ]
c3 <- matrix( c3, I, 4, byrow=TRUE )
# compare estimates of rasch.mml2, smirt and true parameters
round( cbind( mod1$item$c, mod2$item$c,c3[,3],data.reck21$pars$c ), 2 )
round( cbind( mod1$item$a, mod2$item$a.Dim1,c3[,1], data.reck21$pars$a ), 2 )
round( cbind( mod1$item$b, mod2$item$b.Dim1 / mod2$item$a.Dim1, - c3[,2] / c3[,1],
            data.reck21$pars$b ), 2 )

#############################################################################
# EXAMPLE 2: data.reck61 dataset, Table 6.1, p. 153
#############################################################################

data(data.reck61DAT1)
dat <- data.reck61DAT1$data

#***
# Model 1: Exploratory factor analysis

#-- Model 1a: tam.fa in TAM
library(TAM)
mod1a <- TAM::tam.fa( dat, irtmodel="efa", nfactors=3 )
# varimax rotation
varimax(mod1a$B.stand)

# Model 1b: EFA in NOHARM (Promax rotation)
mod1b <- sirt::R2noharm( dat=dat, model.type="EFA",  dimensions=3,
              writename="reck61__3dim_efa", noharm.path="c:/NOHARM",dec=",")
summary(mod1b)

# Model 1c: EFA with noharm.sirt
mod1c <- sirt::noharm.sirt( dat=dat, dimensions=3  )
summary(mod1c)
plot(mod1c)

# Model 1d: EFA with 2 dimensions in noharm.sirt
mod1d <- sirt::noharm.sirt( dat=dat, dimensions=2  )
```

```
summary(mod1d)
plot(mod1d, efa.load.min=.2)   # plot loadings of at least .20

#***
# Model 2: Confirmatory factor analysis

#-- Model 2a: tam.fa in TAM
dims <- c( rep(1,10), rep(3,10), rep(2,10)  )
Qmatrix <- matrix( 0, nrow=30, ncol=3 )
Qmatrix[ cbind( 1:30, dims) ] <- 1
mod2a <- TAM::tam.mml.2pl( dat,Q=Qmatrix,
            control=list( snodes=1000, QMC=TRUE, maxiter=200) )
summary(mod2a)

#-- Model 2b: smirt in sirt
mod2b <- sirt::smirt( dat,Qmatrix=Qmatrix, est.a="2PL", maxiter=20, qmcnodes=1000 )
summary(mod2b)

#-- Model 2c: rasch.mml2 in sirt
mod2c <- sirt::rasch.mml2( dat,Qmatrix=Qmatrix, est.a=1:30,
                mmliter=200, theta.k=seq(-5,5,len=11) )
summary(mod2c)

#-- Model 2d: mirt in mirt
cmodel <- mirt::mirt.model("
     F1=1-10
     F2=21-30
     F3=11-20
     COV=F1*F2, F1*F3, F2*F3 " )
mod2d <- mirt::mirt(dat, cmodel, verbose=TRUE)
summary(mod2d)
coef(mod2d)

#-- Model 2e: CFA in NOHARM
# specify covariance pattern
P.pattern <- matrix( 1, ncol=3, nrow=3 )
P.init <- .4*P.pattern
diag(P.pattern) <- 0
diag(P.init) <- 1
# fix all entries in the loading matrix to 1
F.pattern <- matrix( 0, nrow=30, ncol=3 )
F.pattern[1:10,1] <- 1
F.pattern[21:30,2] <- 1
F.pattern[11:20,3] <- 1
F.init <- F.pattern
# estimate model
mod2e <- sirt::R2noharm( dat=dat, model.type="CFA", P.pattern=P.pattern,
            P.init=P.init, F.pattern=F.pattern, F.init=F.init,
            writename="reck61__3dim_cfa", noharm.path="c:/NOHARM",dec=",")
summary(mod2e)

#-- Model 2f: CFA with noharm.sirt
mod2f <- sirt::noharm.sirt( dat=dat, Fval=F.init, Fpatt=F.pattern,
```

```
                Pval=P.init, Ppatt=P.pattern )
summary(mod2f)

#############################################################################
# EXAMPLE 3: DETECT analysis data.reck78ExA and data.reck79ExB
#############################################################################

data(data.reck78ExA)
data(data.reck79ExB)

#************************
# Example A
dat <- data.reck78ExA$data
#- estimate person score
score <- stats::qnorm( ( rowMeans( dat )+.5 )  / ( ncol(dat) + 1 ) )
#- extract item cluster
itemcluster <- substring( colnames(dat), 1, 1 )
#- confirmatory DETECT Item cluster
detectA <- sirt::conf.detect( data=dat, score=score, itemcluster=itemcluster )
  ##          unweighted weighted
  ##   DETECT      0.571    0.571
  ##   ASSI        0.523    0.523
  ##   RATIO       0.757    0.757

#- exploratory DETECT analysis
detect_explA <- sirt::expl.detect(data=dat, score, nclusters=10, N.est=nrow(dat)/2  )
  ##  Optimal Cluster Size is  5  (Maximum of DETECT Index)
  ##     N.Cluster N.items N.est N.val         size.cluster DETECT.est ASSI.est
  ##   1         2      50  1250  1250               31-19      0.531    0.404
  ##   2         3      50  1250  1250             10-19-21      0.554    0.407
  ##   3         4      50  1250  1250           10-19-14-7      0.630    0.509
  ##   4         5      50  1250  1250         10-19-3-7-11      0.653    0.546
  ##   5         6      50  1250  1250       10-12-7-3-7-11      0.593    0.458
  ##   6         7      50  1250  1250      10-12-7-3-7-9-2      0.604    0.474
  ##   7         8      50  1250  1250    10-12-7-3-3-9-4-2      0.608    0.481
  ##   8         9      50  1250  1250  10-12-7-3-3-5-4-2-4      0.617    0.494
  ##   9        10      50  1250  1250 10-5-7-7-3-3-5-4-2-4      0.592    0.460

# cluster membership
cluster_membership <- detect_explA$itemcluster$cluster3
# Cluster 1:
colnames(dat)[ cluster_membership==1 ]
  ##   [1] "A01" "A02" "A03" "A04" "A05" "A06" "A07" "A08" "A09" "A10"
# Cluster 2:
colnames(dat)[ cluster_membership==2 ]
  ##    [1] "B11" "B12" "B13" "B14" "B15" "B16" "B17" "B18" "B19" "B20" "B21" "B22"
  ##   [13] "B23" "B25" "B26" "B27" "B28" "B29" "B30"
# Cluster 3:
colnames(dat)[ cluster_membership==3 ]
  ##    [1] "B24" "C31" "C32" "C33" "C34" "C35" "C36" "C37" "C38" "C39" "C40" "C41"
  ##   [13] "C42" "C43" "C44" "C45" "C46" "C47" "C48" "C49" "C50"

#************************
```

```
# Example B
dat <- data.reck79ExB$data
#- estimate person score
score <- stats::qnorm( ( rowMeans( dat )+.5 )  / ( ncol(dat) + 1 ) )
#- extract item cluster
itemcluster <- substring( colnames(dat), 1, 1 )
#- confirmatory DETECT Item cluster
detectB <- sirt::conf.detect( data=dat, score=score, itemcluster=itemcluster )
  ##          unweighted weighted
  ##   DETECT      0.715    0.715
  ##   ASSI        0.624    0.624
  ##   RATIO       0.855    0.855

#- exploratory DETECT analysis
detect_explB <- sirt::expl.detect(data=dat, score, nclusters=10, N.est=nrow(dat)/2  )
  ##   Optimal Cluster Size is  4  (Maximum of DETECT Index)
  ##
  ##     N.Cluster N.items N.est N.val         size.cluster DETECT.est ASSI.est
  ##   1         2      50  1250  1250                30-20      0.665    0.546
  ##   2         3      50  1250  1250             10-20-20      0.686    0.585
  ##   3         4      50  1250  1250           10-20-8-12      0.728    0.644
  ##   4         5      50  1250  1250         10-6-14-8-12      0.654    0.553
  ##   5         6      50  1250  1250       10-6-14-3-12-5      0.659    0.561
  ##   6         7      50  1250  1250      10-6-14-3-7-5-5      0.664    0.576
  ##   7         8      50  1250  1250     10-6-7-7-3-7-5-5      0.616    0.518
  ##   8         9      50  1250  1250   10-6-7-7-3-5-5-5-2      0.612    0.512
  ##   9        10      50  1250  1250 10-6-7-7-3-5-3-5-2-2      0.613    0.512

## End(Not run)
```

`data.sirt` *Some Example Datasets for the* `sirt` *Package*

Description

Some example datasets for the `sirt` package.

Usage

```
data(data.si01)
data(data.si02)
data(data.si03)
data(data.si04)
data(data.si05)
data(data.si06)
data(data.si07)
data(data.si08)
data(data.si09)
data(data.si10)
```

Format

- The format of the dataset `data.si01` is:

```
'data.frame': 1857 obs. of 3 variables:
$ idgroup: int 1 1 1 1 1 1 1 1 1 1 ...
$ item1 : int NA NA NA NA NA NA NA NA NA NA ...
$ item2 : int 4 4 4 4 4 4 4 2 4 4 ...
```

- The dataset `data.si02` is the Stouffer-Toby-dataset published in Lindsay, Clogg and Grego (1991; Table 1, p.97, Cross-classification A):

```
List of 2
$ data : num [1:16, 1:4] 1 0 1 0 1 0 1 0 1 0 ...
..- attr(*, "dimnames")=List of 2
.. ..$ : NULL
.. ..$ : chr [1:4] "I1" "I2" "I3" "I4"
$ weights: num [1:16] 42 1 6 2 6 1 7 2 23 4 ...
```

- The format of the dataset `data.si03` (containing item parameters of two studies) is:

```
'data.frame': 27 obs. of 3 variables:
$ item : Factor w/ 27 levels "M1","M10","M11",..: 1 12 21 22 ...
$ b_study1: num 0.297 1.163 0.151 -0.855 -1.653 ...
$ b_study2: num 0.72 1.118 0.351 -0.861 -1.593 ...
```

- The dataset `data.si04` is adapted from Bartolucci, Montanari and Pandolfi (2012; Table 4, Table 7). The data contains 4999 persons, 79 items on 5 dimensions. See `rasch.mirtlc` for using the data in an analysis.

```
List of 3
$ data : num [1:4999, 1:79] 0 1 1 0 1 1 0 0 1 1 ...
..- attr(*, "dimnames")=List of 2
.. ..$ : NULL
.. ..$ : chr [1:79] "A01" "A02" "A03" "A04" ...
$ itempars :'data.frame': 79 obs. of 4 variables:
..$ item : Factor w/ 79 levels "A01","A02","A03",..: 1 2 3 4 5 6 7 8 9 10 ...
..$ dim : num [1:79] 1 1 1 1 1 1 1 1 1 1 ...
..$ gamma : num [1:79] 1 1 1 1 1 1 1 1 1 1 ...
..$ gamma.beta: num [1:79] -0.189 0.25 0.758 1.695 1.022 ...
$ distribution: num [1:9, 1:7] 1 2 3 4 5 ...
..- attr(*, "dimnames")=List of 2
.. ..$ : NULL
.. ..$ : chr [1:7] "class" "A" "B" "C" ...
```

- The dataset `data.si05` contains double ratings of two exchangeable raters for three items which are in `Ex1`, `Ex2` and `Ex3`, respectively.

```
List of 3
$ Ex1:'data.frame': 199 obs. of 2 variables:
..$ C7040: num [1:199] NA 1 0 1 1 0 0 0 1 0 ...
..$ C7041: num [1:199] 1 1 0 0 0 0 0 0 1 0 ...
```

```
$ Ex2:'data.frame': 2000 obs. of 2 variables:
..$ rater1: num [1:2000] 2 0 3 1 2 2 0 0 0 0 ...
..$ rater2: num [1:2000] 4 1 3 2 1 0 0 0 0 2 ...
$ Ex3:'data.frame': 2000 obs. of 2 variables:
..$ rater1: num [1:2000] 5 1 6 2 3 3 0 0 0 0 ...
..$ rater2: num [1:2000] 7 2 6 3 2 1 0 1 0 3 ...
```

- The dataset `data.si06` contains multiple choice item responses. The correct alternative is denoted as 0, distractors are indicated by the codes 1, 2 or 3.

```
'data.frame': 4441 obs. of 14 variables:
$ WV01: num 0 0 0 0 0 0 0 0 0 3 ...
$ WV02: num 0 0 0 3 0 0 0 0 0 1 ...
$ WV03: num 0 1 0 0 0 0 0 0 0 0 ...
$ WV04: num 0 0 0 0 0 0 0 0 0 1 ...
$ WV05: num 3 1 1 1 0 0 1 1 0 2 ...
$ WV06: num 0 1 3 0 0 0 2 0 0 1 ...
$ WV07: num 0 0 0 0 0 0 0 0 0 0 ...
$ WV08: num 0 1 1 0 0 0 0 0 0 0 ...
$ WV09: num 0 0 0 0 0 0 0 0 0 2 ...
$ WV10: num 1 1 3 0 0 2 0 0 0 0 ...
$ WV11: num 0 0 0 0 0 0 0 0 0 0 ...
$ WV12: num 0 0 0 2 0 0 2 0 0 0 ...
$ WV13: num 3 1 1 3 0 0 3 0 0 0 ...
$ WV14: num 3 1 2 3 0 3 1 3 3 0 ...
```

- The dataset `data.si07` contains parameters of the empirical illustration of DeCarlo (2020). The simulation function `sim_fun` can be used for simulating data from the IRSDT model (see DeCarlo, 2020)

```
List of 3
$ pars :'data.frame': 16 obs. of 3 variables:
..$ item: Factor w/ 16 levels "I01","I02","I03",..: 1 2 3 4 5 6 7 8 9 10 ...
..$ b : num [1:16] -1.1 -0.18 1.44 1.78 -1.19 0.45 -1.12 0.33 0.82 -0.43 ...
..$ d : num [1:16] 2.69 4.6 6.1 3.11 3.2 ...
$ trait :'data.frame': 20 obs. of 2 variables:
..$ x : num [1:20] 0.025 0.075 0.125 0.175 0.225 0.275 0.325 0.375 0.425 0.475 ...
..$ prob: num [1:20] 0.0238 0.1267 0.105 0.0594 0.0548 ...
$ sim_fun:function (lambda, b, d, items)
```

- The dataset `data.si08` contains 5 items with respect to knowledge about lung cancer and the kind of information acquisition (Goodman, 1970; see also Rasch, Kubinger & Yanagida, 2011). `L1`: reading newspapers, `L2`: listening radio, `L3`: reading books and magazines, `L4`: attending talks, `L5`: knowledge about lung cancer

```
'data.frame': 32 obs. of 6 variables:
$ L1 : num 1 1 1 1 1 1 1 1 1 1 ...
$ L2 : num 1 1 1 1 1 1 1 1 0 0 ...
$ L3 : num 1 1 1 1 0 0 0 0 1 1 ...
$ L4 : num 1 1 0 0 1 1 0 0 1 1 ...
```

```
$ L5 : num 1 0 1 0 1 0 1 0 1 0 ...
$ wgt: num 23 8 102 67 8 4 35 59 27 18 ...
```

- The dataset `data.si09` was used in Fischer and Karl (2019) and they asked employees in a eight countries, to report whether they typically help other employees (helping behavior, seven items, `help`) and whether they make suggestions to improve work conditions and products (voice behavior, five items, `voice`). Individuals responded to these items on a 1-7 Likert-type scale. The dataset was downloaded from https://osf.io/wkx8c/.

```
'data.frame': 5201 obs. of 13 variables:
$ country: Factor w/ 8 levels "BRA","CAN","KEN",..: 5 5 5 5 5 5 5 5 5 5 ...
$ help1 : int 6 6 5 5 5 6 6 6 4 6 ...
$ help2 : int 3 6 5 6 6 6 6 6 6 7 ...
$ help3 : int 5 6 6 7 7 6 5 6 6 7 ...
$ help4 : int 7 6 5 6 6 7 7 6 6 7 ...
$ help5 : int 5 5 5 6 6 6 6 6 6 7 ...
$ help6 : int 3 4 5 6 6 7 7 6 6 5 ...
$ help7 : int 5 4 4 5 5 7 7 6 6 6 ...
$ voice1 : int 3 6 5 6 4 7 6 6 5 7 ...
$ voice2 : int 3 6 4 7 6 5 6 6 4 7 ...
$ voice3 : int 6 6 5 7 6 5 6 6 6 5 ...
$ voice4 : int 6 6 6 5 5 7 5 6 6 6 ...
$ voice5 : int 6 7 4 7 6 6 6 6 5 7 ...
```

- The dataset `data.si10` contains votes of 435 members of the U.S. House of Representatives, 267 Democrates and 168 Republicans. The dataset was used by Fop and Murphy (2017).

```
'data.frame': 435 obs. of 17 variables:
$ party : Factor w/ 2 levels "democrat","republican": 2 2 1 1 1 1 1 2 2 1 ...
$ vote01: num 0 0 NA 0 1 0 0 0 0 1 ...
$ vote02: num 1 1 1 1 1 1 1 1 1 1 ...
$ vote03: num 0 0 1 1 1 1 0 0 0 1 ...
$ vote04: num 1 1 NA 0 0 0 1 1 1 0 ...
$ vote05: num 1 1 1 NA 1 1 1 1 1 0 ...
$ vote06: num 1 1 1 1 1 1 1 1 1 0 ...
$ vote07: num 0 0 0 0 0 0 0 0 0 1 ...
$ vote08: num 0 0 0 0 0 0 0 0 0 1 ...
$ vote09: num 0 0 0 0 0 0 0 0 0 1 ...
$ vote10: num 1 0 0 0 0 0 0 0 0 0 ...
$ vote11: num NA 0 1 1 1 0 0 0 0 0 ...
$ vote12: num 1 1 0 0 NA 0 0 0 1 0 ...
$ vote13: num 1 1 1 1 1 1 NA 1 1 0 ...
$ vote14: num 1 1 1 0 1 1 1 1 1 0 ...
$ vote15: num 0 0 0 0 1 1 1 NA 0 NA ...
$ vote16: num 1 NA 0 1 1 1 1 1 1 NA ...
```

References

Bartolucci, F., Montanari, G. E., & Pandolfi, S. (2012). Dimensionality of the latent structure and item selection via latent class multidimensional IRT models. *Psychometrika, 77*(4), 782-802. doi:10.1007/s1133601292780

DeCarlo, L. T. (2020). An item response model for true-false exams based on signal detection theory. *Applied Psychological Measurement, 34*(3). 234-248. doi:10.1177/0146621619843823

Fischer, R., & Karl, J. A. (2019). A primer to (cross-cultural) multi-group invariance testing possibilities in R. *Frontiers in Psychology | Cultural Psychology, 10*:1507. doi:10.3389/fpsyg.2019.01507

Fop, M., & Murphy, T. B. (2018). Variable selection methods for model-based clustering. *Statistics Surveys, 12*, 18-65. https://doi.org/10.1214/18-SS119

Goodman, L. A. (1970). The multivariate analysis of qualitative data: Interactions among multiple classifications. *Journal of the American Statistical Association, 65*(329), 226-256. doi:10.1080/01621459.1970.10481076

Lindsay, B., Clogg, C. C., & Grego, J. (1991). Semiparametric estimation in the Rasch model and related exponential response models, including a simple latent class model for item analysis. *Journal of the American Statistical Association, 86*(413), 96-107. doi:10.1080/01621459.1991.10475008

Rasch, D., Kubinger, K. D., & Yanagida, T. (2011). *Statistics in psychology using R and SPSS*. New York: Wiley. doi:10.1002/9781119979630

See Also

Some free datasets can be obtained from
Psychological questionnaires: http://personality-testing.info/_rawdata/
PISA 2012: http://pisa2012.acer.edu.au/downloads.php
PIAAC: http://www.oecd.org/site/piaac/publicdataandanalysis.htm
TIMSS 2011: http://timssandpirls.bc.edu/timss2011/international-database.html
ALLBUS: http://www.gesis.org/allbus/allbus-home/

Examples

```
## Not run:
#############################################################################
# EXAMPLE 1: Nested logit model multiple choice dataset data.si06
#############################################################################

data(data.si06, package="sirt")
dat <- data.si06

#** estimate 2PL nested logit model
library(mirt)
mod1 <- mirt::mirt( dat, model=1, itemtype="2PLNRM", key=rep(0,ncol(dat) ),
            verbose=TRUE  )
summary(mod1)
cmod1 <- sirt::mirt.wrapper.coef(mod1)$coef
cmod1[,-1] <- round( cmod1[,-1], 3)

#** normalize item parameters according Suh and Bolt (2010)
cmod2 <- cmod1
```

```
# slope parameters
ind <-  grep("ak",colnames(cmod2))
h1 <- cmod2[,ind ]
cmod2[,ind] <- t( apply( h1, 1, FUN=function(ll){ ll - mean(ll) } ) )
# item intercepts
ind <-  paste0( "d", 0:9 )
ind <- which( colnames(cmod2) %in% ind )
h1 <- cmod2[,ind ]
cmod2[,ind] <- t( apply( h1, 1, FUN=function(ll){ ll - mean(ll) } ) )
cmod2[,-1] <- round( cmod2[,-1], 3)

#############################################################################
# EXAMPLE 2: Item response modle based on signal detection theory (IRSDT model)
#############################################################################

data(data.si07, package="sirt")
data <- data.si07

#-- simulate data
set.seed(98)
N <- 2000 # define sample size
# generate membership scores
lambda <- sample(size=N, x=data$trait$x, prob=data$trait$prob, replace=TRUE)
b <- data$pars$b
d <- data$pars$d
items <- data$pars$item
dat <- data$sim_fun(lambda=lambda, b=b, d=d, items=items)

#- estimate IRSDT model as a grade of membership model with two classes
problevels <- seq( 0.025, 0.975, length=20 )
mod1 <- sirt::gom.em( dat, K=2, problevels=problevels )
summary(mod1)

## End(Not run)
```

`data.timss` *Dataset TIMSS Mathematics*

Description

This datasets contains TIMSS mathematics data from 345 students on 25 items.

Usage

```
data(data.timss)
```

Format

This dataset is a list. data is the dataset containing student ID (idstud), a dummy variable for female (girl) and student age (age). The following variables (starting with M in the variable name are items.

The format is:

```
List of 2
$ data:'data.frame':
..$ idstud : num [1:345] 4e+09 4e+09 4e+09 4e+09 4e+09 ...
..$ girl : int [1:345] 0 0 0 0 0 0 0 0 1 0 ...
..$ age : num [1:345] 10.5 10 10.25 10.25 9.92 ...
..$ M031286 : int [1:345] 0 0 0 1 1 0 1 0 1 0 ...
..$ M031106 : int [1:345] 0 0 0 1 1 0 1 1 0 0 ...
..$ M031282 : int [1:345] 0 0 0 1 1 0 1 1 0 0 ...
..$ M031227 : int [1:345] 0 0 0 0 1 0 0 0 0 0 ...
[...]
..$ M041203 : int [1:345] 0 0 0 1 1 0 0 0 0 1 ...
$ item:'data.frame':
..$ item : Factor w/ 25 levels "M031045","M031068",..: ...
..$ Block : Factor w/ 2 levels "M01","M02": 1 1 1 1 1 1 ..
..$ Format : Factor w/ 2 levels "CR","MC": 1 1 1 1 2 ...
..$ Content.Domain : Factor w/ 3 levels "Data Display",..: 3 3 3 3 ...
..$ Cognitive.Domain: Factor w/ 3 levels "Applying","Knowing",..: 2 3 3 ..
```

---

data.timss07.G8.RUS *TIMSS 2007 Grade 8 Mathematics and Science Russia*

Description

This TIMSS 2007 dataset contains item responses of 4472 eigth grade Russian students in Mathematics and Science.

Usage

```
data(data.timss07.G8.RUS)
```

Format

The datasets contains raw responses (raw), scored responses (scored) and item informations (iteminfo).

The format of the dataset is:

```
List of 3
$ raw :'data.frame':
..$ idstud : num [1:4472] 3010101 3010102 3010104 3010105 3010106 ...
..$ M022043 : atomic [1:4472] NA 1 4 NA NA NA NA NA NA NA ...
.. ..- attr(*, "value.labels")=Named num [1:7] 9 6 5 4 3 2 1
```

```
.. .. ..- attr(*, "names")=chr [1:7] "OMITTED" "NOT REACHED" "E" "D*" ...
[...]
..$ M032698 : atomic [1:4472] NA NA NA NA NA NA NA 2 1 NA ...
.. ..- attr(*, "value.labels")=Named num [1:6] 9 6 4 3 2 1
.. .. ..- attr(*, "names")=chr [1:6] "OMITTED" "NOT REACHED" "D" "C" ...
..$ M032097 : atomic [1:4472] NA NA NA NA NA NA NA 2 3 NA ...
.. ..- attr(*, "value.labels")=Named num [1:6] 9 6 4 3 2 1
.. .. ..- attr(*, "names")=chr [1:6] "OMITTED" "NOT REACHED" "D" "C*" ...
.. [list output truncated]
$ scored : num [1:4472, 1:443] 3010101 3010102 3010104 3010105 3010106 ...
..- attr(*, "dimnames")=List of 2
.. ..$ : NULL
.. ..$ : chr [1:443] "idstud" "M022043" "M022046" "M022049" ...
$ iteminfo:'data.frame':
..$ item : Factor w/ 442 levels "M022043","M022046",..: 1 2 3 4 5 6 21 7 8 17 ...
..$ content : Factor w/ 8 levels "Algebra","Biology",..: 7 7 6 1 6 7 4 6 7 7 ...
..$ topic : Factor w/ 49 levels "Algebraic Expression",..: 32 32 41 29 ...
..$ cognitive : Factor w/ 3 levels "Applying","Knowing",..: 2 1 3 2 1 1 1 1 2 1 ...
..$ item.type : Factor w/ 2 levels "CR","MC": 2 1 2 2 1 2 2 2 2 1 ...
..$ N.options : Factor w/ 4 levels "-"," -","4","5": 4 1 3 4 1 4 4 4 3 1 ...
..$ key : Factor w/ 7 levels "-"," -","A","B",..: 6 1 6 7 1 5 5 4 6 1 ...
..$ max.points: int [1:442] 1 1 1 1 1 1 1 1 1 2 ...
..$ item.label: Factor w/ 432 levels "1 teacher for every 12 students ",..: 58 351 ...
```

Source

TIMSS 2007 8th Grade, Russian Sample

`data.trees` *Dataset Used in Stoyan, Pommerening and Wuensche (2018)*

Description

Dataset used in Stoyan, Pommerening and Wuensche (2018; see also Pommerening et al., 2018). In the dataset, 15 forest managers classify 387 trees either as trees to be maintained or as trees to be removed. They assign tree marks, either 0 or 1, where mark 1 means remove.

Usage

```
data(data.trees)
```

Format

The dataset has the following structure.

```
'data.frame': 387 obs. of 16 variables:
$ Number: int 142 184 9 300 374 42 382 108 125 201 ...
$ FM1 : int 1 1 1 1 1 1 1 1 1 0 ...
$ FM2 : int 1 1 1 0 1 1 1 1 1 1 ...
$ FM3 : int 1 0 1 1 1 1 1 1 1 1 ...
$ FM4 : int 1 1 1 1 1 1 0 1 1 1 ...
$ FM5 : int 1 1 1 1 1 1 0 0 0 1 ...
$ FM6 : int 1 1 1 1 0 1 1 1 1 0 ...
$ FM7 : int 1 0 1 1 0 0 1 0 1 1 ...
$ FM8 : int 1 1 1 1 1 0 0 1 0 1 ...
$ FM9 : int 1 1 0 1 1 1 1 0 1 1 ...
$ FM10 : int 0 1 1 0 1 1 1 1 0 0 ...
$ FM11 : int 1 1 1 1 0 1 1 0 1 0 ...
$ FM12 : int 1 1 1 1 1 1 0 1 0 0 ...
$ FM13 : int 0 1 0 0 1 1 1 1 1 1 ...
$ FM14 : int 1 1 1 1 1 0 1 1 1 1 ...
$ FM15 : int 1 1 0 1 1 0 1 0 0 1 ...
```

Source

https://www.pommerening.org/wiki/images/d/dc/CoedyBreninSortedforPublication.txt

References

Pommerening, A., Ramos, C. P., Kedziora, W., Haufe, J., & Stoyan, D. (2018). Rating experiments in forestry: How much agreement is there in tree marking? *PloS ONE, 13*(3), e0194747. doi:10.1371/journal.pone.0194747

Stoyan, D., Pommerening, A., & Wuensche, A. (2018). Rater classification by means of set-theoretic methods applied to forestry data. *Journal of Environmental Statistics, 8*(2), 1-17.

Examples

```
## Not run:
#############################################################################
# EXAMPLE 1: Latent class models, latent trait models, mixed membership models
#############################################################################

data(data.trees, package="sirt")
dat <- data.trees[,-1]
I <- ncol(dat)

#** latent class models with 2, 3, and 4 classes
problevels <- seq( 0, 1, len=2 )
mod02 <- sirt::gom.em(dat, K=2, problevels, model="GOM")
mod03 <- sirt::gom.em(dat, K=3, problevels, model="GOM")
mod04 <- sirt::gom.em(dat, K=4, problevels, model="GOM")

#** grade of membership models
mod11 <- sirt::gom.em(dat, K=2, theta0.k=10*seq(-1,1,len=11), model="GOMnormal")
```

```
problevels <- seq( 0, 1, len=3 )
mod12 <- sirt::gom.em(dat, K=2, problevels, model="GOM")
mod13 <- sirt::gom.em(dat, K=3, problevels, model="GOM")
mod14 <- sirt::gom.em(dat, K=4, problevels, model="GOM")
problevels <- seq( 0, 1, len=4 )
mod22 <- sirt::gom.em(dat, K=2, problevels, model="GOM")
mod23 <- sirt::gom.em(dat, K=3, problevels, model="GOM")
mod24 <- sirt::gom.em(dat, K=4, problevels, model="GOM")

#** latent trait models
#- 1PL
mod31 <- sirt::rasch.mml2(dat)
#- 2PL
mod32 <- sirt::rasch.mml2(dat, est.a=1:I)

#- model comparison
IRT.compareModels(mod02, mod03, mod04, mod11, mod12, mod13, mod14,
                    mod22, mod23, mod24, mod31, mod32)

#-- inspect model results
summary(mod12)
round( cbind( mod12$theta.k, mod12$pi.k ),3)

summary(mod13)
round(cbind( mod13$theta.k, mod13$pi.k ),3)

## End(Not run)
```

`data.wide2long` *Converting a Data Frame from Wide Format in a Long Format*

Description

Converts a data frame in wide format into long format.

Usage

```
data.wide2long(dat, id=NULL, X=NULL, Q=NULL)
```

Arguments

`dat`	Data frame with item responses and a person identifier if `id !=NULL`.
`id`	An optional string with the variable name of the person identifier.
`X`	Data frame with person covariates for inclusion in the data frame of long format
`Q`	Data frame with item predictors. Item labels must be included as a column named by `"item"`.

Value

Data frame in long format

Examples

```
## Not run:
#############################################################################
# EXAMPLE 1: data.pisaRead
#############################################################################
miceadds::library_install("lme4")

data(data.pisaRead)
dat <- data.pisaRead$data
Q <- data.pisaRead$item   # item predictors

# define items
items <- colnames(dat)[ substring( colnames(dat), 1, 1 )=="R" ]
dat1 <- dat[, c( "idstud", items ) ]
# matrix with person predictors
X <- dat[, c("idschool", "hisei", "female", "migra") ]

# create dataset in long format
dat.long <- sirt::data.wide2long( dat=dat1, id="idstud", X=X, Q=Q )

#***
# Model 1: Rasch model
mod1 <- lme4::glmer( resp ~ 0 + ( 1 | idstud ) + as.factor(item), data=dat.long,
            family="binomial", verbose=TRUE)
summary(mod1)

#***
# Model 2: Rasch model and inclusion of person predictors
mod2 <- lme4::glmer( resp ~ 0 + ( 1 | idstud ) + as.factor(item) + female + hisei + migra,
           data=dat.long, family="binomial", verbose=TRUE)
summary(mod2)

#***
# Model 3: LLTM
mod3 <- lme4::glmer(resp ~ (1|idstud) + as.factor(ItemFormat) + as.factor(TextType),
            data=dat.long, family="binomial", verbose=TRUE)
summary(mod3)

#############################################################################
# EXAMPLE 2: Rasch model in lme4
#############################################################################

set.seed(765)
N <- 1000  # number of persons
I <- 10    # number of items
b <- seq(-2,2,length=I)
dat <- sirt::sim.raschtype( stats::rnorm(N,sd=1.2), b=b )
dat.long <- sirt::data.wide2long( dat=dat )
#***
# estimate Rasch model with lmer
library(lme4)
mod1 <- lme4::glmer( resp ~ 0 + as.factor( item ) + ( 1 | id_index), data=dat.long,
```

```
            verbose=TRUE, family="binomial")
summary(mod1)
  ##   Random effects:
  ##    Groups   Name        Variance Std.Dev.
  ##    id_index (Intercept) 1.454    1.206
  ##   Number of obs: 10000, groups: id_index, 1000
  ##
  ##   Fixed effects:
  ##                       Estimate Std. Error z value Pr(>|z|)
  ##   as.factor(item)I0001  2.16365    0.10541  20.527  < 2e-16 ***
  ##   as.factor(item)I0002  1.66437    0.09400  17.706  < 2e-16 ***
  ##   as.factor(item)I0003  1.21816    0.08700  14.002  < 2e-16 ***
  ##   as.factor(item)I0004  0.68611    0.08184   8.383  < 2e-16 ***
  ##   [...]

## End(Not run)
```

`detect.index` *Calculation of the DETECT and polyDETECT Index*

Description

This function calculated the DETECT and polyDETECT index (Stout, Habing, Douglas & Kim, 1996; Zhang & Stout, 1999a; Zhang, 2007). At first, conditional covariances have to be estimated using the `ccov.np` function.

Usage

```
detect.index(ccovtable, itemcluster)
```

Arguments

`ccovtable`	A value of `ccov.np`.
`itemcluster`	Item cluster for each item. The order of entries must correspond to the columns in `data` (submitted to `ccov.np`).

References

Stout, W., Habing, B., Douglas, J., & Kim, H. R. (1996). Conditional covariance-based nonparametric multidimensionality assessment. *Applied Psychological Measurement, 20*, 331-354.

Zhang, J., & Stout, W. (1999a). Conditional covariance structure of generalized compensatory multidimensional items. *Psychometrika, 64*, 129-152.

Zhang, J., & Stout, W. (1999b). The theoretical DETECT index of dimensionality and its application to approximate simple structure. *Psychometrika, 64*, 213-249.

Zhang, J. (2007). Conditional covariance theory and DETECT for polytomous items. *Psychometrika, 72*, 69-91.

See Also

For examples see `conf.detect`.

`dif.logistic.regression`
Differential Item Functioning using Logistic Regression Analysis

---

Description

This function assesses differential item functioning using logistic regression analysis (Zumbo, 1999).

Usage

```
dif.logistic.regression(dat, group, score,quant=1.645)
```

Arguments

`dat`	Data frame with dichotomous item responses
`group`	Group identifier
`score`	Ability estimate, e.g. the WLE.
`quant`	Used quantile of the normal distribution for assessing statistical significance

Details

Items are classified into A (negligible DIF), B (moderate DIF) and C (large DIF) levels according to the ETS classification system (Longford, Holland & Thayer, 1993, p. 175). See also Monahan, McHorney, Stump and Perkins (2007) for further DIF effect size classifications.

Value

A data frame with following variables:

`itemnr`	Numeric index of the item
`sortDIFindex`	Rank of item with respect to the uniform DIF (from negative to positive values)
`item`	Item name
`N`	Sample size per item
`R`	Value of `group` variable for reference group
`F`	Value of `group` variable for focal group
`nR`	Sample size per item in reference group
`nF`	Sample size per item in focal group
`p`	Item p value
`pR`	Item p value in reference group
`pF`	Item p value in focal group

`pdiff`	Item p value differences
`pdiff.adj`	Adjusted p value difference
`uniformDIF`	Uniform DIF estimate
`se.uniformDIF`	Standard error of uniform DIF
`t.uniformDIF`	The t value for uniform DIF
`sig.uniformDIF`	Significance label for uniform DIF
`DIF.ETS`	DIF classification according to the ETS classification system (see Details)
`uniform.EBDIF`	Empirical Bayes estimate of uniform DIF (Longford, Holland & Thayer, 1993) which takes degree of DIF standard error into account
`DIF.SD`	Value of the DIF standard deviation
`nonuniformDIF`	Nonuniform DIF estimate
`se.nonuniformDIF`	Standard error of nonuniform DIF
`t.nonuniformDIF`	The t value for nonuniform DIF
`sig.nonuniformDIF`	Significance label for nonuniform DIF

References

Longford, N. T., Holland, P. W., & Thayer, D. T. (1993). Stability of the MH D-DIF statistics across populations. In P. W. Holland & H. Wainer (Eds.). *Differential Item Functioning* (pp. 171-196). Hillsdale, NJ: Erlbaum.

Magis, D., Beland, S., Tuerlinckx, F., & De Boeck, P. (2010). A general framework and an R package for the detection of dichotomous differential item functioning. *Behavior Research Methods, 42*(3), 847-862. doi:10.3758/BRM.42.3.847

Monahan, P. O., McHorney, C. A., Stump, T. E., & Perkins, A. J. (2007). Odds ratio, delta, ETS classification, and standardization measures of DIF magnitude for binary logistic regression. *Journal of Educational and Behavioral Statistics, 32*(1), 92-109. doi:10.3102/1076998606298035

Zumbo, B. D. (1999). *A handbook on the theory and methods of differential item functioning (DIF): Logistic regression modeling as a unitary framework for binary and Likert-type (ordinal) item scores*. Ottawa ON: Directorate of Human Resources Research and Evaluation, Department of National Defense.

See Also

For assessing DIF variance see `dif.variance` and `dif.strata.variance`

See also `rasch.evm.pcm` for assessing differential item functioning in the partial credit model.

See the **difR** package for a large collection of DIF detection methods (Magis, Beland, Tuerlinckx, & De Boeck, 2010).

For a download of the free *DIF-Pack* software (SIBTEST, ...) see *http://psychometrictools.measuredprogress.org/home*.

Examples

```
#############################################################################
# EXAMPLE 1: Mathematics data | Gender DIF
#############################################################################

data( data.math )
dat <- data.math$data
items <- grep( "M", colnames(dat))

# estimate item parameters and WLEs
mod <- sirt::rasch.mml2( dat[,items] )
wle <- sirt::wle.rasch( dat[,items], b=mod$item$b )$theta

# assess DIF by logistic regression
mod1 <- sirt::dif.logistic.regression( dat=dat[,items], score=wle, group=dat$female)

# calculate DIF variance
dif1 <- sirt::dif.variance( dif=mod1$uniformDIF, se.dif=mod1$se.uniformDIF )
dif1$unweighted.DIFSD
  ## > dif1$unweighted.DIFSD
  ## [1] 0.1963958

# calculate stratified DIF variance
# stratification based on domains
dif2 <- sirt::dif.strata.variance( dif=mod1$uniformDIF, se.dif=mod1$se.uniformDIF,
              itemcluster=data.math$item$domain )
  ## $unweighted.DIFSD
  ## [1] 0.1455916

## Not run:
#****
# Likelihood ratio test and graphical model test in eRm package
miceadds::library_install("eRm")
# estimate Rasch model
res <- eRm::RM( dat[,items] )
summary(res)
# LR-test with respect to female
lrres <- eRm::LRtest(res, splitcr=dat$female)
summary(lrres)
# graphical model test
eRm::plotGOF(lrres)

#############################################################################
# EXAMPLE 2: Comparison with Mantel-Haenszel test
#############################################################################

library(TAM)
library(difR)

#*** (1) simulate data
set.seed(776)
N <- 1500   # number of persons per group
```

```
I <- 12     # number of items
mu2 <- .5   # impact (group difference)
sd2 <- 1.3  # standard deviation group 2

# define item difficulties
b <- seq( -1.5, 1.5, length=I)
# simulate DIF effects
bdif <- scale( stats::rnorm(I, sd=.6 ), scale=FALSE )[,1]
# item difficulties per group
b1 <- b + 1/2 * bdif
b2 <- b - 1/2 * bdif
# simulate item responses
dat1 <- sirt::sim.raschtype( theta=stats::rnorm(N, mean=0, sd=1 ), b=b1 )
dat2 <- sirt::sim.raschtype( theta=stats::rnorm(N, mean=mu2, sd=sd2 ), b=b2 )
dat <- rbind( dat1, dat2 )
group <- rep( c(1,2), each=N ) # define group indicator

#*** (2) scale data
mod <- TAM::tam.mml( dat, group=group )
summary(mod)

#*** (3) extract person parameter estimates
mod_eap <- mod$person$EAP
mod_wle <- tam.wle( mod )$theta

#*********************************
# (4) techniques for assessing differential item functioning

# Model 1: assess DIF by logistic regression and WLEs
dif1 <- sirt::dif.logistic.regression( dat=dat, score=mod_wle, group=group)
# Model 2: assess DIF by logistic regression and EAPs
dif2 <- sirt::dif.logistic.regression( dat=dat, score=mod_eap, group=group)
# Model 3: assess DIF by Mantel-Haenszel statistic
dif3 <- difR::difMH(Data=dat, group=group, focal.name="1",  purify=FALSE )
print(dif3)
  ##  Mantel-Haenszel Chi-square statistic:
  ##
  ##        Stat.    P-value
  ##  I0001  14.5655   0.0001 ***
  ##  I0002 300.3225   0.0000 ***
  ##  I0003   2.7160   0.0993 .
  ##  I0004 191.6925   0.0000 ***
  ##  I0005   0.0011   0.9740
  ##  [...]
  ##  Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
  ##  Detection threshold: 3.8415 (significance level: 0.05)
  ##
  ##  Effect size (ETS Delta scale):
  ##
  ##  Effect size code:
  ##   'A': negligible effect
  ##   'B': moderate effect
  ##   'C': large effect
```

```
  ##
  ##        alphaMH deltaMH
  ##  I0001  1.3908 -0.7752 A
  ##  I0002  0.2339  3.4147 C
  ##  I0003  1.1407 -0.3093 A
  ##  I0004  2.8515 -2.4625 C
  ##  I0005  1.0050 -0.0118 A
  ##  [...]
  ##
  ##  Effect size codes: 0 'A' 1.0 'B' 1.5 'C'
  ##   (for absolute values of 'deltaMH')

# recompute DIF parameter from alphaMH
uniformDIF3 <- log(dif3$alphaMH)

# compare different DIF statistics
dfr <- data.frame( "bdif"=bdif, "LR_wle"=dif1$uniformDIF,
        "LR_eap"=dif2$uniformDIF, "MH"=uniformDIF3 )
round( dfr, 3 )
  ##       bdif LR_wle LR_eap     MH
  ##  1   0.236  0.319  0.278  0.330
  ##  2  -1.149 -1.473 -1.523 -1.453
  ##  3   0.140  0.122  0.038  0.132
  ##  4   0.957  1.048  0.938  1.048
  ##  [...]
colMeans( abs( dfr[,-1] - bdif ))
  ##      LR_wle     LR_eap         MH
  ##  0.07759187 0.19085743 0.07501708

## End(Not run)
```

`dif.strata.variance` *Stratified DIF Variance*

Description

Calculation of stratified DIF variance

Usage

```
dif.strata.variance(dif, se.dif, itemcluster)
```

Arguments

`dif`	Vector of uniform DIF effects
`se.dif`	Standard error of uniform DIF effects
`itemcluster`	Vector of item strata

Value

A list with following entries:

`stratadif`	Summary statistics of DIF effects within item strata
`weighted.DIFSD`	Weighted DIF standard deviation
`unweigted.DIFSD`	DIF standard deviation

References

Longford, N. T., Holland, P. W., & Thayer, D. T. (1993). Stability of the MH D-DIF statistics across populations. In P. W. Holland & H. Wainer (Eds.). *Differential Item Functioning* (pp. 171-196). Hillsdale, NJ: Erlbaum.

See Also

See `dif.logistic.regression` for examples.

`dif.variance` *DIF Variance*

Description

This function calculates the variance of DIF effects, the so called DIF variance (Longford, Holland & Thayer, 1993).

Usage

```
dif.variance(dif, se.dif, items=paste("item", 1:length(dif), sep="") )
```

Arguments

`dif`	Vector of uniform DIF effects
`se.dif`	Standard error of uniform DIF effects
`items`	Optional vector of item names

Value

A list with following entries

`weighted.DIFSD`	Weighted DIF standard deviation
`unweigted.DIFSD`	DIF standard deviation
`mean.se.dif`	Mean of standard errors of DIF effects
`eb.dif`	Empirical Bayes estimates of DIF effects

References

Longford, N. T., Holland, P. W., & Thayer, D. T. (1993). Stability of the MH D-DIF statistics across populations. In P. W. Holland & H. Wainer (Eds.). *Differential Item Functioning* (pp. 171-196). Hillsdale, NJ: Erlbaum.

See Also

See `dif.logistic.regression` for examples.

`dirichlet.mle` *Maximum Likelihood Estimation of the Dirichlet Distribution*

Description

Maximum likelihood estimation of the parameters of the Dirichlet distribution

Usage

```
dirichlet.mle(x, weights=NULL, eps=10^(-5), convcrit=1e-05, maxit=1000,
     oldfac=.3, progress=FALSE)
```

Arguments

`x`	Data frame with N observations and K variables of a Dirichlet distribution
`weights`	Optional vector of frequency weights
`eps`	Tolerance number which is added to prevent from logarithms of zero
`convcrit`	Convergence criterion
`maxit`	Maximum number of iterations
`oldfac`	Convergence acceleration factor. It must be a parameter between 0 and 1.
`progress`	Display iteration progress?

Value

A list with following entries

`alpha`	Vector of α parameters
`alpha0`	The concentration parameter $\alpha_0 = \sum_k \alpha_k$
`xsi`	Vector of proportions $\xi_k = \alpha_k / \alpha_0$

References

Minka, T. P. (2012). *Estimating a Dirichlet distribution*. Technical Report.

See Also

For simulating Dirichlet vectors with matrix-wise α parameters see dirichlet.simul.

For a variety of functions concerning the Dirichlet distribution see the **DirichletReg** package.

Examples

```
#############################################################################
# EXAMPLE 1: Simulate and estimate Dirichlet distribution
#############################################################################

# (1) simulate data
set.seed(789)
N <- 200
probs <- c(.5, .3, .2 )
alpha0 <- .5
alpha <- alpha0*probs
alpha <- matrix( alpha, nrow=N, ncol=length(alpha), byrow=TRUE  )
x <- sirt::dirichlet.simul( alpha )

# (2) estimate Dirichlet parameters
dirichlet.mle(x)
  ##   $alpha
  ##   [1] 0.24507708 0.14470944 0.09590745
  ##   $alpha0
  ##   [1] 0.485694
  ##   $xsi
  ##   [1] 0.5045916 0.2979437 0.1974648

## Not run:
#############################################################################
# EXAMPLE 2: Fitting Dirichlet distribution with frequency weights
#############################################################################

# define observed data
x <- scan( nlines=1)
    1 0   0 1   .5 .5
x <- matrix( x, nrow=3, ncol=2, byrow=TRUE)

# transform observations x into (0,1)
eps <- .01
x <- ( x + eps ) / ( 1 + 2 * eps )

# compare results with likelihood fitting package maxLik
miceadds::library_install("maxLik")
# define likelihood function
dirichlet.ll <- function(param) {
    ll <- sum( weights * log( ddirichlet( x, param ) ) )
    ll
}

#*** weights 10-10-1
weights <- c(10, 10, 1 )
```

```
mod1a <- sirt::dirichlet.mle( x, weights=weights )
mod1a
# estimation in maxLik
mod1b <- maxLik::maxLik(loglik, start=c(.5,.5))
print( mod1b )
coef( mod1b )

#*** weights 10-10-10
weights <- c(10, 10, 10 )
mod2a <- sirt::dirichlet.mle( x, weights=weights )
mod2a
# estimation in maxLik
mod2b <- maxLik::maxLik(loglik, start=c(.5,.5))
print( mod2b )
coef( mod2b )

#*** weights 30-10-2
weights <- c(30, 10, 2 )
mod3a <- sirt::dirichlet.mle( x, weights=weights )
mod3a
# estimation in maxLik
mod3b <- maxLik::maxLik(loglik, start=c(.25,.25))
print( mod3b )
coef( mod3b )

## End(Not run)
```

`dirichlet.simul` *Simulation of a Dirichlet Distributed Vectors*

Description

This function makes random draws from a Dirichlet distribution.

Usage

```
dirichlet.simul(alpha)
```

Arguments

`alpha`	A matrix with α parameters of the Dirichlet distribution

Value

A data frame with Dirichlet distributed responses

Examples

```
#############################################################################
# EXAMPLE 1: Simulation with two components
#############################################################################

set.seed(789)
N <- 2000
probs <- c(.7, .3)    # define (extremal) class probabilities

#*** alpha0=.2  -> nearly crisp latent classes
alpha0 <- .2
alpha <- alpha0*probs
alpha <- matrix( alpha, nrow=N, ncol=length(alpha), byrow=TRUE  )
x <- sirt::dirichlet.simul( alpha )
htitle <- expression(paste( alpha[0], "=.2, ", p[1], "=.7"   ) )
hist( x[,1], breaks=seq(0,1,len=20), main=htitle)

#*** alpha0=3 -> strong deviation from crisp membership
alpha0 <- 3
alpha <- alpha0*probs
alpha <- matrix( alpha, nrow=N, ncol=length(alpha), byrow=TRUE  )
x <- sirt::dirichlet.simul( alpha )
htitle <- expression(paste( alpha[0], "=3, ", p[1], "=.7"   ) )
hist( x[,1], breaks=seq(0,1,len=20), main=htitle)

## Not run:
#############################################################################
# EXAMPLE 2: Simulation with three components
#############################################################################

set.seed(986)
N <- 2000
probs <- c( .5, .35, .15 )

#*** alpha0=.2
alpha0 <- .2
alpha <- alpha0*probs
alpha <- matrix( alpha, nrow=N, ncol=length(alpha), byrow=TRUE  )
x <- sirt::dirichlet.simul( alpha )
htitle <- expression(paste( alpha[0], "=.2, ", p[1], "=.7"   ) )
miceadds::library_install("ade4")
ade4::triangle.plot(x, label=NULL, clabel=1)

#*** alpha0=3
alpha0 <- 3
alpha <- alpha0*probs
alpha <- matrix( alpha, nrow=N, ncol=length(alpha), byrow=TRUE  )
x <- sirt::dirichlet.simul( alpha )
htitle <- expression(paste( alpha[0], "=3, ", p[1], "=.7"   ) )
ade4::triangle.plot(x, label=NULL, clabel=1)

## End(Not run)
```

`dmlavaan` *Comparing Regression Parameters of Different lavaan Models Fitted to the Same Dataset*

Description

The function `dmlavaan` compares model parameters from different **lavaan** models fitted to the same dataset. This leads to dependent coefficients. Statistical inference is either conducted by M-estimation (i.e., robust sandwich method; `method="bootstrap"`) or bootstrap (`method="bootstrap"`). See Mize et al. (2019) or Weesie (1999) for more details.

Usage

```
dmlavaan(fun1, args1, fun2, args2, method="sandwich", R=50)
```

Arguments

`fun1`	lavaan function of the first model (e.g., `"lavaan"`, `"cfa"`, or `"sem"`)
`args1`	arguments for lavaan function in the first model
`fun2`	lavaan function of the second model (e.g., `"lavaan"`, `"cfa"`, or `"sem"`)
`args2`	arguments for lavaan function in the second model
`method`	estimation method for standard errors
`R`	Number of bootstrap samples

Details

In bootstrap estimation, a normal approximation is applied in the computation of confidence intervals. Hence, `R` could be chosen relatively small.

TO DO (not yet implemented):

1) inclusion of sampling weights
2) cluster robust standard errors in hierarchical sampling
3) stratification

Value

A list with following entries

`coef`	Model parameters of both models
`vcov`	Covariance matrix of model parameters of both models
`partable`	Parameter table containing all univariate model parameters
`...`	More entries

References

Mize, T.D., Doan, L., & Long, J.S. (2019). A general framework for comparing predictions and marginal effects across models. *Sociological Methodology, 49*(1), 152-189. doi:10.1177/0081175019852763

Weesie, J. (1999) Seemingly unrelated estimation and the cluster-adjusted sandwich estimator. *Stata Technical Bulletin, 9*, 231-248.

Examples

```
## Not run:
#############################################################################
# EXAMPLE 1: Confirmatory factor analysis with and without fourth item
#############################################################################

#**** simulate data
N <- 200  # number of persons
I <- 4    # number of items

# loadings and error correlations
lam <- seq(.7,.4, len=I)
PSI <- diag( 1-lam^2 )

# define some model misspecification
sd_error <- .1
S1 <- matrix( c( -1.84, 0.39,-0.68, 0.13,
  0.39,-1.31,-0.07,-0.27,
 -0.68,-0.07, 0.90, 1.91,
  0.13,-0.27, 1.91,-0.56 ), nrow=4, ncol=4, byrow=TRUE)
S1 <- ( S1 - mean(S1) ) / sd(S1) * sd_error

Sigma <- lam %*% t(lam) + PSI + S1
dat <- MASS::mvrnorm(n=N, mu=rep(0,I), Sigma=Sigma)
colnames(dat) <- paste0("X",1:4)
dat <- as.data.frame(dat)
rownames(Sigma) <- colnames(Sigma) <- colnames(dat)


#*** define two lavaan models
lavmodel1 <- "F=~ X1 + X2 + X3 + X4"
lavmodel2 <- "F=~ X1 + X2 + X3"

#*** define lavaan estimation arguments and functions
fun2 <- fun1 <- "cfa"
args1 <- list( model=lavmodel1, data=dat, std.lv=TRUE, estimator="MLR")
args2 <- args1
args2$model <- lavmodel2

#* run model comparison
res1 <- sirt::dmlavaan( fun1=fun1, args1=args1, fun2=fun2, args2=args2)

# inspect results
```

```
sirt:::print_digits(res1$partable, digits=3)

## End(Not run)
```

`eigenvalues.manymatrices` *Computation of Eigenvalues of Many Symmetric Matrices*

Description

This function computes the eigenvalue decomposition of N symmetric positive definite matrices. The eigenvalues are computed by the Rayleigh quotient method (Lange, 2010, p. 120). In addition, the inverse matrix can be calculated.

Usage

```
eigenvalues.manymatrices(Sigma.all, itermax=10, maxconv=0.001,
    inverse=FALSE )
```

Arguments

`Sigma.all`	An $N \times D^2$ matrix containing the D^2 entries of N symmetric matrices of dimension $D \times D$
`itermax`	Maximum number of iterations
`maxconv`	Convergence criterion for convergence of eigenvectors
`inverse`	A logical which indicates if the inverse matrix shall be calculated

Value

A list with following entries

`lambda`	Matrix with eigenvalues
`U`	An $N \times D^2$ Matrix of orthonormal eigenvectors
`logdet`	Vector of logarithm of determinants
`det`	Vector of determinants
`Sigma.inv`	Inverse matrix if `inverse=TRUE`.

References

Lange, K. (2010). *Numerical Analysis for Statisticians*. New York: Springer.

Examples

```
# define matrices
Sigma <- diag(1,3)
Sigma[ lower.tri(Sigma) ] <- Sigma[ upper.tri(Sigma) ] <- c(.4,.6,.8 )
Sigma1 <- Sigma

Sigma <- diag(1,3)
Sigma[ lower.tri(Sigma) ] <- Sigma[ upper.tri(Sigma) ] <- c(.2,.1,.99 )
Sigma2 <- Sigma

# collect matrices in a "super-matrix"
Sigma.all <- rbind( matrix( Sigma1, nrow=1, byrow=TRUE),
                matrix( Sigma2, nrow=1, byrow=TRUE) )
Sigma.all <- Sigma.all[ c(1,1,2,2,1 ), ]

# eigenvalue decomposition
m1 <- sirt::eigenvalues.manymatrices( Sigma.all )
m1

# eigenvalue decomposition for Sigma1
s1 <- svd(Sigma1)
s1
```

---

equating.rasch *Equating in the Generalized Logistic Rasch Model*

Description

This function does the linking in the generalized logistic item response model. Only item difficulties (b item parameters) are allowed. Mean-mean linking and the methods of Haebara and Stocking-Lord are implemented (Kolen & Brennan, 2004).

Usage

```
equating.rasch(x, y, theta=seq(-4, 4, len=100),
       alpha1=0, alpha2=0)
```

Arguments

x	Matrix with two columns: First column items, second column item difficulties
y	Matrix with two columns: First columns item, second column item difficulties
theta	Vector of theta values at which the linking functions should be evaluated. If a weighting according to a prespecified normal distribution $N(\mu, \sigma^2)$ is aimed, then choose `theta=stats::qnorm( seq(.001, .999, len=100), mean=mu, sd=sigma)`
alpha1	Fixed α_1 parameter in the generalized item response model
alpha2	Fixed α_2 parameter in the generalized item response model

Value

B.est	Estimated linking constants according to the methods Mean.Mean (Mean-mean linking), Haebara (Haebara method) and Stocking.Lord (Stocking-Lord method).
descriptives	Descriptives of the linking. The linking error (linkerror) is calculated under the assumption of simple random sampling of items
anchor	Original and transformed item parameters of anchor items
transf.par	Original and transformed item parameters of all items

References

Kolen, M. J., & Brennan, R. L. (2004). *Test Equating, Scaling, and Linking: Methods and Practices*. New York: Springer.

See Also

For estimating standard errors (due to inference with respect to the item domain) of this procedure see equating.rasch.jackknife.

For linking several studies see linking.haberman or invariance.alignment.

A robust alternative to mean-mean linking is implemented in linking.robust.

For linking under more general item response models see the **plink** package.

Examples

```
#############################################################################
# EXAMPLE 1: Linking item parameters of the PISA study
#############################################################################

data(data.pisaPars)
pars <- data.pisaPars

# linking the two studies with the Rasch model
mod <- sirt::equating.rasch(x=pars[,c("item","study1")], y=pars[,c("item","study2")])
  ##   Mean.Mean    Haebara Stocking.Lord
  ## 1   0.08828 0.08896269    0.09292838

## Not run:
#*** linking using the plink package
# The plink package is not available on CRAN anymore.
# You can download the package with
# utils::install.packages("plink", repos="http://www2.uaem.mx/r-mirror")
library(plink)
I <- nrow(pars)
pm <- plink::as.poly.mod(I)
# linking parameters
plink.pars1 <- list( "study1"=data.frame( 1, pars$study1, 0 ),
                     "study2"=data.frame( 1, pars$study2, 0 ) )
      # the parameters are arranged in the columns:
      # Discrimination, Difficulty, Guessing Parameter
# common items
```

```
common.items <- cbind("study1"=1:I,"study2"=1:I)
# number of categories per item
cats.item <- list( "study1"=rep(2,I), "study2"=rep(2,I))
# convert into plink object
x <- plink::as.irt.pars( plink.pars1, common.items, cat=cats.item,
          poly.mod=list(pm,pm))
# linking using plink: first group is reference group
out <- plink::plink(x, rescale="MS", base.grp=1, D=1.7)
# summary for linking
summary(out)
  ##   -------  group2/group1*  -------
  ##   Linking Constants
  ##
  ##                         A         B
  ##   Mean/Mean     1.000000 -0.088280
  ##   Mean/Sigma    1.000000 -0.088280
  ##   Haebara       1.000000 -0.088515
  ##   Stocking-Lord 1.000000 -0.096610
# extract linked parameters
pars.out <- plink::link.pars(out)

## End(Not run)
```

`equating.rasch.jackknife`

Jackknife Equating Error in Generalized Logistic Rasch Model

Description

This function estimates the linking error in linking based on Jackknife (Monseur & Berezner, 2007).

Usage

```
equating.rasch.jackknife(pars.data, display=TRUE,
   se.linkerror=FALSE, alpha1=0, alpha2=0)
```

Arguments

`pars.data`	Data frame with four columns: jackknife unit (1st column), item parameter study 1 (2nd column), item parameter study 2 (3rd column), item (4th column)
`display`	Display progress?
`se.linkerror`	Compute standard error of the linking error
`alpha1`	Fixed α_1 parameter in the generalized item response model
`alpha2`	Fixed α_2 parameter in the generalized item response model

Value

A list with following entries:

`pars.data`	Used item parameters
`itemunits`	Used units for jackknife
`descriptives`	Descriptives for Jackknife. `linkingerror.jackknife` is the estimated linking error.

References

Monseur, C., & Berezner, A. (2007). The computation of equating errors in international surveys in education. *Journal of Applied Measurement, 8*, 323-335.

See Also

For more details on linking methods see `equating.rasch`.

Examples

```
#############################################################################
# EXAMPLE 1: Linking errors PISA study
#############################################################################

data(data.pisaPars)
pars <- data.pisaPars

# Linking error: Jackknife unit is the testlet
vars <- c("testlet","study1","study2","item")
res1 <- sirt::equating.rasch.jackknife(pars[, vars])
res1$descriptives
  ##   N.items N.units      shift        SD linkerror.jackknife SE.SD.jackknife
  ## 1      25       8 0.09292838 0.1487387          0.04491197      0.03466309

# Linking error: Jackknife unit is the item
res2 <- sirt::equating.rasch.jackknife(pars[, vars ] )
res2$descriptives
  ##   N.items N.units      shift        SD linkerror.jackknife SE.SD.jackknife
  ## 1      25      25 0.09292838 0.1487387          0.02682839      0.02533327
```

`expl.detect` *Exploratory DETECT Analysis*

Description

This function estimates the DETECT index (Stout, Habing, Douglas & Kim, 1996; Zhang & Stout, 1999a, 1999b) in an exploratory way. Conditional covariances of itempairs are transformed into a distance matrix such that items are clustered by the hierarchical Ward algorithm (Roussos, Stout & Marden, 1998). Note that the function will not provide the same output as the original DETECT software.

Usage

```
expl.detect(data, score, nclusters, N.est=NULL, seed=NULL, bwscale=1.1,
    smooth=TRUE, use_sum_score=FALSE, hclust_method="ward.D", estsample=NULL)
```

Arguments

data	An $N \times I$ data frame of dichotomous or polytomous responses. Missing responses are allowed.
score	An ability estimate, e.g. the WLE, sum score or mean score
nclusters	Maximum number of clusters used in the exploratory analysis
N.est	Number of students in a (possible) validation of the DETECT index. N.est students are drawn at random from data.
seed	Random seed
bwscale	Bandwidth scale factor
smooth	Logical indicating whether smoothing should be applied for conditional covariance estimation
use_sum_score	Logical indicating whether sum score should be used. With this option, the bias corrected conditional covariance of Zhang and Stout (1999) is used.
hclust_method	Clustering method used as the argument method in stats::hclust.
estsample	Optional vector of subject indices that defines the estimation sample

Value

A list with following entries

detect.unweighted
: Unweighted DETECT statistics

detect.weighted
: Weighted DETECT statistics. Weighting is done proportionally to sample sizes of item pairs.

clusterfit
: Fit of the cluster method

itemcluster
: Cluster allocations

use_sum_score

References

Roussos, L. A., Stout, W. F., & Marden, J. I. (1998). Using new proximity measures with hierarchical cluster analysis to detect multidimensionality. *Journal of Educational Measurement, 35*, 1-30.

Stout, W., Habing, B., Douglas, J., & Kim, H. R. (1996). Conditional covariance-based nonparametric multidimensionality assessment. *Applied Psychological Measurement, 20*, 331-354.

Zhang, J., & Stout, W. (1999a). Conditional covariance structure of generalized compensatory multidimensional items, *Psychometrika, 64*, 129-152.

Zhang, J., & Stout, W. (1999b). The theoretical DETECT index of dimensionality and its application to approximate simple structure, *Psychometrika, 64*, 213-249.

See Also

For examples see `conf.detect`.

`f1d.irt` *Functional Unidimensional Item Response Model*

Description

Estimates the functional unidimensional item response model for dichotomous data (Ip, Molenberghs, Chen, Goegebeur & De Boeck, 2013). Either the IRT model is estimated using a probit link and employing tetrachoric correlations or item discriminations and intercepts of a pre-estimated multidimensional IRT model are provided as input.

Usage

```
f1d.irt(dat=NULL, nnormal=1000, nfactors=3, A=NULL, intercept=NULL,
    mu=NULL, Sigma=NULL, maxiter=100, conv=10^(-5), progress=TRUE)
```

Arguments

`dat`	Data frame with dichotomous item responses
`nnormal`	Number of θ_p grid points for approximating the normal distribution
`nfactors`	Number of dimensions to be estimated
`A`	Matrix of item discriminations (if the IRT model is already estimated)
`intercept`	Vector of item intercepts (if the IRT model is already estimated)
`mu`	Vector of estimated means. In the default it is assumed that all means are zero.
`Sigma`	Estimated covariance matrix. In the default it is the identity matrix.
`maxiter`	Maximum number of iterations
`conv`	Convergence criterion
`progress`	Display progress? The default is `TRUE`.

Details

The functional unidimensional item response model (F1D model) for dichotomous item responses is based on a multidimensional model with a link function g (probit or logit):

$$P(X_{pi}=1|\boldsymbol{\theta}_p) = g(\sum_d a_{id}\theta_{pd} - d_i)$$

It is assumed that $\boldsymbol{\theta}_p$ is multivariate normally distribution with a zero mean vector and identity covariance matrix.

The F1D model estimates unidimensional item response functions such that

$$P(X_{pi}=1|\theta_p^*) \approx g\left(a_i^*\theta_p^* - d_i^*\right)$$

The optimization function F minimizes the deviations of the approximation equations

$$a_i^* \theta_p^* - d_i^* \approx \sum_d a_{id} \theta_{pd} - d_i$$

The optimization function F is defined by

$$F(\{a_i^*, d_i^*\}_i, \{\theta_p^*\}_p) = \sum_p \sum_i w_p (a_{id} \theta_{pd} - d_i - a_i^* \theta_p^* + d_i^*)^2 \to Min!$$

All items i are equally weighted whereas the ability distribution of persons p are weighted according to the multivariate normal distribution (using weights w_p). The estimation is conducted using an alternating least squares algorithm (see Ip et al. 2013 for a different algorithm). The ability distribution θ_p^* of the functional unidimensional model is assumed to be standardized, i.e. does have a zero mean and a standard deviation of one.

Value

A list with following entries:

`item`	Data frame with estimated item parameters: Item intercepts for the functional unidimensional a_i^* (`ai.ast`) and the ('ordinary') unidimensional (`ai0`) item response model. The same holds for item intercepts d_i^* (`di.ast` and `di0` respectively).
`person`	Data frame with estimated θ_p^* distribution. Locations are `theta.ast` with corresponding probabilities in `wgt`.
`A`	Estimated or provided item discriminations
`intercept`	Estimated or provided intercepts
`dat`	Used dataset
`tetra`	Object generated by `tetrachoric2` if `dat` is specified as input. This list entry is useful for applying `greenyang.reliability`.

References

Ip, E. H., Molenberghs, G., Chen, S. H., Goegebeur, Y., & De Boeck, P. (2013). Functionally unidimensional item response models for multivariate binary data. *Multivariate Behavioral Research, 48*, 534-562.

See Also

For estimation of bifactor models and Green-Yang reliability based on tetrachoric correlations see `greenyang.reliability`.

For estimation of bifactor models based on marginal maximum likelihood (i.e. full information maximum likelihood) see the `TAM::tam.fa` function in the **TAM** package.

Examples

```
#############################################################################
# EXAMPLE 1: Dataset Mathematics data.math | Exploratory multidimensional model
#############################################################################
data(data.math)
dat <- ( data.math$data )[, -c(1,2) ] # select Mathematics items

#****
# Model 1: Functional unidimensional model based on original data

#++ (1) estimate model with 3 factors
mod1 <- sirt::f1d.irt( dat=dat, nfactors=3)

#++ (2) plot results
     par(mfrow=c(1,2))
# Intercepts
plot( mod1$item$di0, mod1$item$di.ast, pch=16, main="Item Intercepts",
        xlab=expression( paste( d[i], " (Unidimensional Model)" )),
        ylab=expression( paste( d[i], " (Functional Unidimensional Model)" )))
abline( lm(mod1$item$di.ast ~ mod1$item$di0), col=2, lty=2 )
# Discriminations
plot( mod1$item$ai0, mod1$item$ai.ast, pch=16, main="Item Discriminations",
        xlab=expression( paste( a[i], " (Unidimensional Model)" )),
        ylab=expression( paste( a[i], " (Functional Unidimensional Model)" )))
abline( lm(mod1$item$ai.ast ~ mod1$item$ai0), col=2, lty=2 )
     par(mfrow=c(1,1))

#++ (3) estimate bifactor model and Green-Yang reliability
gy1 <- sirt::greenyang.reliability( mod1$tetra, nfactors=3 )

## Not run:
#****
# Model 2: Functional unidimensional model based on estimated multidimensional
#          item response model

#++ (1) estimate 2-dimensional exploratory factor analysis with 'smirt'
I <- ncol(dat)
Q <- matrix( 1, I,2 )
Q[1,2] <- 0
variance.fixed <- cbind( 1,2,0 )
mod2a <- sirt::smirt( dat, Qmatrix=Q, irtmodel="comp", est.a="2PL",
               variance.fixed=variance.fixed, maxiter=50)
#++ (2) input estimated discriminations and intercepts for
#       functional unidimensional model
mod2b <- sirt::f1d.irt( A=mod2a$a, intercept=mod2a$b )

#############################################################################
# EXAMPLE 2: Dataset Mathematics data.math | Confirmatory multidimensional model
#############################################################################

data(data.math)
library(TAM)
```

```
# dataset
dat <- data.math$data
dat <- dat[, grep("M", colnames(dat) ) ]
# extract item informations
iteminfo <- data.math$item
I <- ncol(dat)
# define Q-matrix
Q <- matrix( 0, nrow=I, ncol=3 )
Q[ grep( "arith", iteminfo$domain ), 1 ] <- 1
Q[ grep( "Meas", iteminfo$domain ), 2 ] <- 1
Q[ grep( "geom", iteminfo$domain ), 3 ] <- 1

# fit three-dimensional model in TAM
mod1 <- TAM::tam.mml.2pl(  dat, Q=Q, control=list(maxiter=40, snodes=1000) )
summary(mod1)

# specify functional unidimensional model
intercept <- mod1$xsi[, c("xsi") ]
names(intercept) <- rownames(mod1$xsi)
fumod1 <- sirt::f1d.irt( A=mod1$B[,2,], intercept=intercept, Sigma=mod1$variance)
fumod1$item

## End(Not run)
```

`fit.isop` *Fitting the ISOP and ADISOP Model for Frequency Tables*

Description

Fit the isotonic probabilistic model (ISOP; Scheiblechner, 1995) and the additive isotonic probabilistic model (ADISOP; Scheiblechner, 1999).

Usage

```
fit.isop(freq.correct, wgt, conv=1e-04, maxit=100,
      progress=TRUE, calc.ll=TRUE)

fit.adisop(freq.correct, wgt, conv=1e-04, maxit=100,
      epsilon=0.01, progress=TRUE, calc.ll=TRUE)
```

Arguments

`freq.correct`	Frequency table
`wgt`	Weights for frequency table (number of persons in each cell)
`conv`	Convergence criterion
`maxit`	Maximum number of iterations
`epsilon`	Additive constant to handle cell frequencies of 0 or 1 in `fit.adisop`

progress	Display progress?
calc.ll	Calculate log-likelihood values? The default is TRUE.

Details

See isop.dich for more details of the ISOP and ADISOP model.

Value

A list with following entries

fX	Fitted frequency table
ResX	Residual frequency table
fit	Fit statistic: weighted least squares of deviations between observed and expected frequencies
item.sc	Estimated item parameters
person.sc	Estimated person parameters
ll	Log-likelihood of the model
freq.fitted	Fitted frequencies in a long data frame

Note

For fitting the ADISOP model it is recommended to first fit the ISOP model and then proceed with the fitted frequency table from ISOP (see Examples).

References

Scheiblechner, H. (1995). Isotonic ordinal probabilistic models (ISOP). *Psychometrika, 60*, 281-304.

Scheiblechner, H. (1999). Additive conjoint isotonic probabilistic models (ADISOP). *Psychometrika, 64*, 295-316.

See Also

For fitting the ISOP model to dichotomous and polytomous data see isop.dich.

Examples

```
#############################################################################
# EXAMPLE 1: Dataset Reading
#############################################################################

data(data.read)
dat <- as.matrix( data.read)
dat.resp <- 1 - is.na(dat) # response indicator matrix
I <- ncol(dat)

#***
# (1) Data preparation
```

```
#     actually only freq.correct and wgt are needed
#     but these matrices must be computed in advance.

# different scores of students
stud.p <- rowMeans( dat, na.rm=TRUE )
# different item p values
item.p <- colMeans( dat, na.rm=TRUE )
item.ps <- sort( item.p, index.return=TRUE)
dat <- dat[,  item.ps$ix ]
# define score groups students
scores <- sort( unique( stud.p ) )
SC <- length(scores)
# create table
freq.correct <- matrix( NA, SC, I )
wgt <- freq.correct
# percent correct
a1 <- stats::aggregate( dat==1, list( stud.p ), mean, na.rm=TRUE )
freq.correct <- a1[,-1]
# weights
a1 <- stats::aggregate( dat.resp, list( stud.p ), sum, na.rm=TRUE )
wgt <- a1[,-1]

#***
# (2) Fit ISOP model
res.isop <- sirt::fit.isop( freq.correct, wgt )
# fitted frequency table
res.isop$fX

#***
# (3) Fit ADISOP model
# use monotonely smoothed frequency table from ISOP model
res.adisop <- sirt::fit.adisop( freq.correct=res.isop$fX, wgt )
# fitted frequency table
res.adisop$fX
```

`fuzcluster` *Clustering for Continuous Fuzzy Data*

Description

This function performs clustering for continuous fuzzy data for which membership functions are assumed to be Gaussian (Denoeux, 2013). The mixture is also assumed to be Gaussian and (conditionally cluster membership) independent.

Usage

```
fuzcluster(dat_m, dat_s, K=2, nstarts=7, seed=NULL, maxiter=100,
     parmconv=0.001, fac.oldxsi=0.75, progress=TRUE)

## S3 method for class 'fuzcluster'
summary(object,...)
```

Arguments

dat_m	Centers for individual item specific membership functions
dat_s	Standard deviations for individual item specific membership functions
K	Number of latent classes
nstarts	Number of random starts. The default is 7 random starts.
seed	Simulation seed. If one value is provided, then only one start is performed.
maxiter	Maximum number of iterations
parmconv	Maximum absolute change in parameters
fac.oldxsi	Convergence acceleration factor which should take values between 0 and 1. The default is 0.75.
progress	An optional logical indicating whether iteration progress should be displayed.
object	Object of class fuzcluster
...	Further arguments to be passed

Value

A list with following entries

deviance	Deviance
iter	Number of iterations
pi_est	Estimated class probabilities
mu_est	Cluster means
sd_est	Cluster standard deviations
posterior	Individual posterior distributions of cluster membership
seed	Simulation seed for cluster solution
ic	Information criteria

References

Denoeux, T. (2013). Maximum likelihood estimation from uncertain data in the belief function framework. *IEEE Transactions on Knowledge and Data Engineering, 25*, 119-130.

See Also

See fuzdiscr for estimating discrete distributions for fuzzy data.

See the **fclust** package for fuzzy clustering.

Examples

```
## Not run:
#############################################################################
# EXAMPLE 1: 2 classes and 3 items
#############################################################################

#*-*-*-*-*-*-*-*-*-*-*-*-*-*-*-*-*-*-*-*-*-*-*-
# simulate data (2 classes and 3 items)
set.seed(876)
library(mvtnorm)
Ntot <- 1000  # number of subjects
# define SDs for simulating uncertainty
sd_uncertain <- c( .2, 1, 2 )

dat_m <- NULL   # data frame containing mean of membership function
dat_s <- NULL   # data frame containing SD of membership function

# *** Class 1
pi_class <- .6
Nclass <- Ntot * pi_class
mu <- c(3,1,0)
Sigma <- diag(3)
# simulate data
dat_m1 <- mvtnorm::rmvnorm( Nclass, mean=mu, sigma=Sigma )
dat_s1 <- matrix( stats::runif( Nclass * 3 ), nrow=Nclass )
for ( ii in 1:3){ dat_s1[,ii] <- dat_s1[,ii] * sd_uncertain[ii] }
dat_m <- rbind( dat_m, dat_m1 )
dat_s <- rbind( dat_s, dat_s1 )

# *** Class 2
pi_class <- .4
Nclass <- Ntot * pi_class
mu <- c(0,-2,0.4)
Sigma <- diag(c(0.5, 2, 2 ) )
# simulate data
dat_m1 <- mvtnorm::rmvnorm( Nclass, mean=mu, sigma=Sigma )
dat_s1 <- matrix( stats::runif( Nclass * 3 ), nrow=Nclass )
for ( ii in 1:3){ dat_s1[,ii] <- dat_s1[,ii] * sd_uncertain[ii] }
dat_m <- rbind( dat_m, dat_m1 )
dat_s <- rbind( dat_s, dat_s1 )
colnames(dat_s) <- colnames(dat_m) <- paste0("I", 1:3 )

#*-*-*-*-*-*-*-*-*-*-*-*-*-*-*-*-*-*-*-*-*-*-*-
# estimation

#*** Model 1: Clustering with 8 random starts
res1 <- sirt::fuzcluster(K=2,dat_m, dat_s, nstarts=8, maxiter=25)
summary(res1)
  ##  Number of iterations=22 (Seed=5090 )
  ##  ---------------------------------------------------
  ##  Class probabilities (2 Classes)
  ##  [1] 0.4083 0.5917
```

```
  ##
  ##  Means
  ##           I1      I2     I3
  ##  [1,] 0.0595 -1.9070 0.4011
  ##  [2,] 3.0682  1.0233 0.0359
  ##
  ##  Standard deviations
  ##         [,1]   [,2]   [,3]
  ##  [1,] 0.7238 1.3712 1.2647
  ##  [2,] 0.9740 0.8500 0.7523

#*** Model 2: Clustering with one start with seed 4550
res2 <- sirt::fuzcluster(K=2,dat_m, dat_s, nstarts=1, seed=5090 )
summary(res2)

#*** Model 3: Clustering for crisp data
#             (assuming no uncertainty, i.e. dat_s=0)
res3 <- sirt::fuzcluster(K=2,dat_m, dat_s=0*dat_s, nstarts=30, maxiter=25)
summary(res3)
  ##  Class probabilities (2 Classes)
  ##  [1] 0.3645 0.6355
  ##
  ##  Means
  ##           I1      I2      I3
  ##  [1,] 0.0463 -1.9221  0.4481
  ##  [2,] 3.0527  1.0241 -0.0008
  ##
  ##  Standard deviations
  ##         [,1]   [,2]   [,3]
  ##  [1,] 0.7261 1.4541 1.4586
  ##  [2,] 0.9933 0.9592 0.9535

#*** Model 4: kmeans cluster analysis
res4 <- stats::kmeans( dat_m, centers=2 )
  ##   K-means clustering with 2 clusters of sizes 607, 393
  ##   Cluster means:
  ##             I1        I2          I3
  ##   1 3.01550780  1.035848 -0.01662275
  ##   2 0.03448309 -2.008209  0.48295067

## End(Not run)
```

`fuzdiscr` *Estimation of a Discrete Distribution for Fuzzy Data (Data in Belief Function Framework)*

Description

This function estimates a discrete distribution for uncertain data based on the belief function framework (Denoeux, 2013; see Details).

Usage

```
fuzdiscr(X, theta0=NULL, maxiter=200, conv=1e-04)
```

Arguments

X	Matrix with fuzzy data. Rows corresponds to subjects and columns to values of the membership function
theta0	Initial vector of parameter estimates
maxiter	Maximum number of iterations
conv	Convergence criterion

Details

For n subjects, membership functions $m_n(k)$ are observed which indicate the belief in data $X_n = k$. The membership function is interpreted as *epistemic uncertainty* (Denoeux, 2011). However, associated parameters in statistical models are crisp which means that models are formulated at the basis of precise (crisp) data if they would be observed.

In the present estimation problem of a discrete distribution, the parameters of interest are category probabilities $\theta_k = P(X = k)$.

The parameter estimation follows the evidential EM algorithm (Denoeux, 2013).

Value

Vector of probabilities of the discrete distribution

References

Denoeux, T. (2011). Maximum likelihood estimation from fuzzy data using the EM algorithm. *Fuzzy Sets and Systems, 183*, 72-91.

Denoeux, T. (2013). Maximum likelihood estimation from uncertain data in the belief function framework. *IEEE Transactions on Knowledge and Data Engineering, 25*, 119-130.

Examples

```
#############################################################################
# EXAMPLE 1: Binomial distribution Denoeux Example 4.3 (2013)
#############################################################################

#*** define uncertain data
X_alpha <- function( alpha ){
    Q <- matrix( 0, 6, 2 )
    Q[5:6,2] <- Q[1:3,1] <- 1
    Q[4,] <- c( alpha, 1 - alpha )
    return(Q)
        }

# define data for alpha=0.5
X <- X_alpha( alpha=.5 )
```

```
  ##   > X
  ##        [,1] [,2]
  ##   [1,]  1.0  0.0
  ##   [2,]  1.0  0.0
  ##   [3,]  1.0  0.0
  ##   [4,]  0.5  0.5
  ##   [5,]  0.0  1.0
  ##   [6,]  0.0  1.0

  ## The fourth observation has equal plausibility for the first and the
  ## second category.

# parameter estimate uncertain data
fuzdiscr( X )
  ##   > sirt::fuzdiscr( X )
  ##   [1] 0.5999871 0.4000129

# parameter estimate pseudo likelihood
colMeans( X )
  ##   > colMeans( X )
  ##   [1] 0.5833333 0.4166667
##-> Observations are weighted according to belief function values.

#*****
# plot parameter estimates as function of alpha
alpha <- seq( 0, 1, len=100 )
res <- sapply( alpha, FUN=function(aa){
             X <- X_alpha( alpha=aa )
             c( sirt::fuzdiscr( X )[1], colMeans( X )[1] )
                    } )
# plot
plot( alpha, res[1,], xlab=expression(alpha), ylab=expression( theta[alpha] ), type="l",
        main="Comparison Belief Function and Pseudo-Likelihood (Example 1)")
lines( alpha, res[2,], lty=2, col=2)
legend( 0, .67, c("Belief Function", "Pseudo-Likelihood" ), col=c(1,2), lty=c(1,2) )

############################################################################
# EXAMPLE 2: Binomial distribution (extends Example 1)
############################################################################

X_alpha <- function( alpha ){
    Q <- matrix( 0, 6, 2 )
    Q[6,2] <- Q[1:2,1] <- 1
    Q[3:5,] <- matrix( c( alpha, 1 - alpha ), 3, 2, byrow=TRUE)
    return(Q)
        }

X <- X_alpha( alpha=.5 )
alpha <- seq( 0, 1, len=100 )
res <- sapply( alpha, FUN=function(aa){
           X <- X_alpha( alpha=aa )
           c( sirt::fuzdiscr( X )[1], colMeans( X )[1] )
                    } )
```

```
# plot
plot( alpha, res[1,], xlab=expression(alpha), ylab=expression( theta[alpha] ), type="l",
        main="Comparison Belief Function and Pseudo-Likelihood (Example 2)")
lines( alpha, res[2,], lty=2, col=2)
legend( 0, .67, c("Belief Function", "Pseudo-Likelihood" ), col=c(1,2), lty=c(1,2) )

############################################################################
# EXAMPLE 3: Multinomial distribution with three categories
############################################################################

# define uncertain data
X <- matrix( c( 1,0,0, 1,0,0,   0,1,0, 0,0,1, .7, .2, .1,
         .4, .6, 0 ), 6, 3, byrow=TRUE )
  ##   > X
  ##        [,1] [,2] [,3]
  ##   [1,]  1.0  0.0  0.0
  ##   [2,]  1.0  0.0  0.0
  ##   [3,]  0.0  1.0  0.0
  ##   [4,]  0.0  0.0  1.0
  ##   [5,]  0.7  0.2  0.1
  ##   [6,]  0.4  0.6  0.0

##->  Only the first four observations are crisp.

#*** estimation for uncertain data
fuzdiscr( X )
  ##   > sirt::fuzdiscr( X )
  ##   [1] 0.5772305 0.2499931 0.1727764

#*** estimation pseudo-likelihood
colMeans(X)
  ##   > colMeans(X)
  ##   [1] 0.5166667 0.3000000 0.1833333

##-> Obviously, the treatment uncertainty is different in belief function
##   and in pseudo-likelihood framework.
```

---

gom.em *Discrete (Rasch) Grade of Membership Model*

Description

This function estimates the grade of membership model (Erosheva, Fienberg & Joutard, 2007; also called mixed membership model) by the EM algorithm assuming a discrete membership score distribution. The function is restricted to dichotomous item responses.

Usage

```
gom.em(dat, K=NULL, problevels=NULL, weights=NULL, model="GOM", theta0.k=seq(-5,5,len=15),
    xsi0.k=exp(seq(-6, 3, len=15)), max.increment=0.3, numdiff.parm=1e-4,
```

```
    maxdevchange=1e-6, globconv=1e-4, maxiter=1000, msteps=4, mstepconv=0.001,
    theta_adjust=FALSE, lambda.inits=NULL, lambda.index=NULL, pi.k.inits=NULL,
    newton_raphson=TRUE, optimizer="nlminb", progress=TRUE)

## S3 method for class 'gom'
summary(object, file=NULL, ...)

## S3 method for class 'gom'
anova(object,...)

## S3 method for class 'gom'
logLik(object,...)

## S3 method for class 'gom'
IRT.irfprob(object,...)

## S3 method for class 'gom'
IRT.likelihood(object,...)

## S3 method for class 'gom'
IRT.posterior(object,...)

## S3 method for class 'gom'
IRT.modelfit(object,...)

## S3 method for class 'IRT.modelfit.gom'
summary(object,...)
```

Arguments

`dat`	Data frame with dichotomous responses
`K`	Number of classes (only applies for `model="GOM"`)
`problevels`	Vector containing probability levels for membership functions (only applies for `model="GOM"`). If a specific space of probability levels should be estimated, then a matrix can be supplied (see Example 1, Model 2a).
`weights`	Optional vector of sampling weights
`model`	The type of grade of membership model. The default `"GOM"` is the nonparametric grade of membership model. A parametric multivariate normal representation can be requested by `"GOMnormal"`. The probabilities and membership functions specifications described in Details are called via `"GOMRasch"`.
`theta0.k`	Vector of $\tilde{\theta}_k$ grid (applies only for `model="GOMRasch"`)
`xsi0.k`	Vector of ξ_p grid (applies only for `model="GOMRasch"`)
`max.increment`	Maximum increment
`numdiff.parm`	Numerical differentiation parameter
`maxdevchange`	Convergence criterion for change in relative deviance
`globconv`	Global convergence criterion for parameter change

maxiter	Maximum number of iterations
msteps	Number of iterations within a M step
mstepconv	Convergence criterion within a M step
theta_adjust	Logical indicating whether multivariate normal distribution should be adaptively chosen during the EM algorithm.
lambda.inits	Initial values for item parameters
lambda.index	Optional integer matrix with integers indicating equality constraints among λ item parameters
pi.k.inits	Initial values for distribution parameters
newton_raphson	Logical indicating whether Newton-Raphson should be used for final iterations
optimizer	Type of optimizer. Can be "optim" or "nlminb".
progress	Display iteration progress? Default is TRUE.
object	Object of class gom
file	Optional file name for summary output
...	Further arguments to be passed

Details

The item response model of the grade of membership model (Erosheva, Fienberg & Junker, 2002; Erosheva, Fienberg & Joutard, 2007) with K classes for dichotomous correct responses X_{pi} of person p on item i is as follows (model="GOM")

$$P(X_{pi}=1|g_{p1},\ldots,g_{pK}) = \sum_k \lambda_{ik} g_{pk} \quad , \quad \sum_{k=1}^{K} g_{pk} = 1 \quad , \quad 0 \leq g_{pk} \leq 1$$

In most applications (e.g. Erosheva et al., 2007), the grade of membership function $\{g_{pk}\}$ is assumed to follow a Dirichlet distribution. In our gom.em implementation the membership function is assumed to be discretely represented by a grid $u = (u_1, \ldots, u_L)$ with entries between 0 and 1 (e.g. seq(0,1,length=5) with $L = 5$). The values g_{pk} of the membership function can then only take values in $\{u_1, \ldots, u_L\}$ with the restriction $\sum_k g_{pk} \sum_l \mathbf{1}(g_{pk} = u_l) = 1$. The grid u is specified by using the argument problevels.

The Rasch grade of membership model (model="GOMRasch") poses constraints on probabilities λ_{ik} and membership functions g_{pk}. The membership function of person p is parameterized by a location parameter θ_p and a variability parameter ξ_p. Each class k is represented by a location parameter $\tilde{\theta}_k$. The membership function is defined as

$$g_{pk} \propto \exp\left[-\frac{(\theta_p - \tilde{\theta}_k)^2}{2\xi_p^2}\right]$$

The person parameter θ_p indicates the usual 'ability', while ξ_p describes the individual tendency to change between classes $1, \ldots, K$ and their corresponding locations $\tilde{\theta}_1, \ldots, \tilde{\theta}_K$. The extremal class probabilities λ_{ik} follow the Rasch model

$$\lambda_{ik} = invlogit(\tilde{\theta}_k - b_i) = \frac{\exp(\tilde{\theta}_k - b_i)}{1 + \exp(\tilde{\theta}_k - b_i)}$$

Putting these assumptions together leads to the model equation

$$P(X_{pi}=1|g_{p1},\ldots,g_{pK}) = P(X_{pi}=1|\theta_p,\xi_p) = \sum_k \frac{\exp(\tilde{\theta}_k - b_i)}{1+\exp(\tilde{\theta}_k - b_i)} \cdot \exp\left[-\frac{(\theta_p-\tilde{\theta}_k)^2}{2\xi_p^2}\right]$$

In the extreme case of a very small $\xi_p = \varepsilon > 0$ and $\theta_p = \theta_0$, the Rasch model is obtained

$$P(X_{pi}=1|\theta_p,\xi_p) = P(X_{pi}=1|\theta_0,\varepsilon) = \frac{\exp(\theta_0 - b_i)}{1+\exp(\theta_0 - b_i)}$$

See Erosheva et al. (2002), Erosheva (2005, 2006) or Galyart (2015) for a comparison of grade of membership models with latent trait models and latent class models.

The grade of membership model is also published under the name Bernoulli aspect model, see Bingham, Kaban and Fortelius (2009).

Value

A list with following entries:

`deviance`	Deviance
`ic`	Information criteria
`item`	Data frame with item parameters
`person`	Data frame with person parameters
`EAP.rel`	EAP reliability (only applies for `model="GOMRasch"`)
`MAP`	Maximum aposteriori estimate of the membership function
`EAP`	EAP estimate for individual membership scores
`classdesc`	Descriptives for class membership
`lambda`	Estimated response probabilities λ_{ik}
`se.lambda`	Standard error for estimated response probabilities λ_{ik}
`mu`	Mean of the distribution of (θ_p, ξ_p) (only applies for `model="GOMRasch"`)
`Sigma`	Covariance matrix of (θ_p, ξ_p) (only applies for `model="GOMRasch"`)
`b`	Estimated item difficulties (only applies for `model="GOMRasch"`)
`se.b`	Standard error of estimated difficulties (only applies for `model="GOMRasch"`)
`f.yi.qk`	Individual likelihood
`f.qk.yi`	Individual posterior
`probs`	Array with response probabilities
`n.ik`	Expected counts
`iter`	Number of iterations
`I`	Number of items
`K`	Number of classes
`TP`	Number of discrete integration points for $(g_{p1}, ..., g_{pK})$
`theta.k`	Used grid of membership functions
`...`	Further values

References

Bingham, E., Kaban, A., & Fortelius, M. (2009). The aspect Bernoulli model: multiple causes of presences and absences. *Pattern Analysis and Applications, 12*(1), 55-78.

Erosheva, E. A. (2005). Comparing latent structures of the grade of membership, Rasch, and latent class models. *Psychometrika, 70*, 619-628.

Erosheva, E. A. (2006). *Latent class representation of the grade of membership model*. Seattle: University of Washington.

Erosheva, E. A., Fienberg, S. E., & Junker, B. W. (2002). Alternative statistical models and representations for large sparse multi-dimensional contingency tables. *Annales-Faculte Des Sciences Toulouse Mathematiques, 11*, 485-505.

Erosheva, E. A., Fienberg, S. E., & Joutard, C. (2007). Describing disability through individual-level mixture models for multivariate binary data. *Annals of Applied Statistics, 1*, 502-537.

Galyardt, A. (2015). Interpreting mixed membership models: Implications of Erosheva's representation theorem. In E. M. Airoldi, D. Blei, E. A. Erosheva, & S. E. Fienberg (Eds.). *Handbook of Mixed Membership Models* (pp. 39-65). Chapman & Hall.

See Also

For joint maximum likelihood estimation of the grade of membership model see `gom.jml`.

See also the **mixedMem** package for estimating mixed membership models by a variational EM algorithm.

The C code of Erosheva et al. (2007) can be downloaded from *http://projecteuclid.org/euclid.aoas/1196438029#supplemental*

Code from Manrique-Vallier can be downloaded from *http://pages.iu.edu/~dmanriqu/software.html*.

See *http://users.ics.aalto.fi/ella/publications/aspect_bernoulli.m* for a Matlab implementation of the algorithm in Bingham, Kaban and Fortelius (2009).

Examples

```
#############################################################################
# EXAMPLE 1: PISA data mathematics
#############################################################################

data(data.pisaMath)
dat <- data.pisaMath$data
dat <- dat[, grep("M", colnames(dat)) ]

#***
# Model 1: Discrete GOM with 3 classes and 5 probability levels
problevels <- seq( 0, 1, len=5 )
mod1 <- sirt::gom.em( dat, K=3, problevels, model="GOM")
summary(mod1)

## Not run:
#-- some plots

#* multivariate scatterplot
car::scatterplotMatrix(mod1$EAP, regLine=FALSE, smooth=FALSE, pch=16, cex=.4)
```

```
#* ternary plot
vcd::ternaryplot(mod1$EAP, pch=16, col=1, cex=.3)

#***
# Model 1a: Multivariate normal distribution
problevels <- seq( 0, 1, len=5 )
mod1a <- sirt::gom.em( dat, K=3, theta0.k=seq(-15,15,len=21), model="GOMnormal" )
summary(mod1a)

#***
# Model 2: Discrete GOM with 4 classes and 5 probability levels
problevels <- seq( 0, 1, len=5 )
mod2 <- sirt::gom.em( dat, K=4, problevels,  model="GOM"  )
summary(mod2)

# model comparison
smod1 <- IRT.modelfit(mod1)
smod2 <- IRT.modelfit(mod2)
IRT.compareModels(smod1,smod2)

#***
# Model 2a: Estimate discrete GOM with 4 classes and restricted space of probability levels
#  the 2nd, 4th and 6th class correspond to "intermediate stages"
problevels <- scan()
 1  0  0  0
.5 .5  0  0
 0  1  0  0
 0 .5 .5  0
 0  0  1  0
 0  0 .5 .5
 0  0  0  1

problevels <- matrix( problevels, ncol=4, byrow=TRUE)
mod2a <- sirt::gom.em( dat, K=4, problevels,  model="GOM" )
# probability distribution for latent classes
cbind( mod2a$theta.k, mod2a$pi.k )
  ##        [,1] [,2] [,3] [,4]       [,5]
  ##   [1,]  1.0  0.0  0.0  0.0 0.17214630
  ##   [2,]  0.5  0.5  0.0  0.0 0.04965676
  ##   [3,]  0.0  1.0  0.0  0.0 0.09336660
  ##   [4,]  0.0  0.5  0.5  0.0 0.06555719
  ##   [5,]  0.0  0.0  1.0  0.0 0.27523678
  ##   [6,]  0.0  0.0  0.5  0.5 0.08458620
  ##   [7,]  0.0  0.0  0.0  1.0 0.25945016

## End(Not run)

#***
# Model 3: Rasch GOM
mod3 <- sirt::gom.em( dat, model="GOMRasch", maxiter=20 )
summary(mod3)

#***
```

```
# Model 4: 'Ordinary' Rasch model
mod4 <- sirt::rasch.mml2( dat )
summary(mod4)

## Not run:
#############################################################################
# EXAMPLE 2: Grade of membership model with 2 classes
#############################################################################

#********* DATASET 1 *************
# define an ordinary 2 latent class model
set.seed(8765)
I <- 10
prob.class1 <- stats::runif( I, 0, .35 )
prob.class2 <- stats::runif( I, .70, .95 )
probs <- cbind( prob.class1, prob.class2 )

# define classes
N <- 1000
latent.class <- c( rep( 1, 1/4*N ), rep( 2,3/4*N ) )

# simulate item responses
dat <- matrix( NA, nrow=N, ncol=I )
for (ii in 1:I){
    dat[,ii] <- probs[ ii, latent.class ]
    dat[,ii] <- 1 * ( stats::runif(N) < dat[,ii] )
}
colnames(dat) <- paste0( "I", 1:I)

# Model 1: estimate latent class model
mod1 <- sirt::gom.em(dat, K=2, problevels=c(0,1), model="GOM" )
summary(mod1)
# Model 2: estimate GOM
mod2 <- sirt::gom.em(dat, K=2, problevels=seq(0,1,0.5), model="GOM" )
summary(mod2)
# estimated distribution
cbind( mod2$theta.k, mod2$pi.k )
  ##       [,1] [,2]        [,3]
  ##  [1,]  1.0  0.0 0.243925644
  ##  [2,]  0.5  0.5 0.006534278
  ##  [3,]  0.0  1.0 0.749540078

#********* DATASET 2 *************
# define a 2-class model with graded membership
set.seed(8765)
I <- 10
prob.class1 <- stats::runif( I, 0, .35 )
prob.class2 <- stats::runif( I, .70, .95 )
prob.class3 <- .5*prob.class1+.5*prob.class2  # probabilities for 'fuzzy class'
probs <- cbind( prob.class1, prob.class2, prob.class3)
# define classes
N <- 1000
latent.class <- c( rep(1,round(1/3*N)),rep(2,round(1/2*N)),rep(3,round(1/6*N)))
```

```
# simulate item responses
dat <- matrix( NA, nrow=N, ncol=I )
for (ii in 1:I){
    dat[,ii] <- probs[ ii, latent.class ]
    dat[,ii] <- 1 * ( stats::runif(N) < dat[,ii] )
        }
colnames(dat) <- paste0( "I", 1:I)

#** Model 1: estimate latent class model
mod1 <- sirt::gom.em(dat, K=2, problevels=c(0,1), model="GOM" )
summary(mod1)

#** Model 2: estimate GOM
mod2 <- sirt::gom.em(dat, K=2, problevels=seq(0,1,0.5), model="GOM" )
summary(mod2)
# inspect distribution
cbind( mod2$theta.k, mod2$pi.k )
  ##       [,1] [,2]      [,3]
  ##  [1,]  1.0  0.0 0.3335666
  ##  [2,]  0.5  0.5 0.1810114
  ##  [3,]  0.0  1.0 0.4854220

#***
# Model2m: estimate discrete GOM in mirt
# define latent classes
Theta <- scan( nlines=1)
   1 0   .5 .5    0 1
Theta <- matrix( Theta, nrow=3, ncol=2,byrow=TRUE)
# define mirt model
I <- ncol(dat)
#*** create customized item response function for mirt model
name <- 'gom'
par <- c("a1"=-1, "a2"=1 )
est <- c(TRUE, TRUE)
P.gom <- function(par,Theta,ncat){
    # GOM for two extremal classes
    pext1 <- stats::plogis(par[1])
    pext2 <- stats::plogis(par[2])
    P1 <- Theta[,1]*pext1 + Theta[,2]*pext2
    cbind(1-P1, P1)
}
# create item response function
icc_gom <- mirt::createItem(name, par=par, est=est, P=P.gom)
#** define prior for latent class analysis
lca_prior <- function(Theta,Etable){
  # number of latent Theta classes
  TP <- nrow(Theta)
  # prior in initial iteration
  if ( is.null(Etable) ){ prior <- rep( 1/TP, TP ) }
  # process Etable (this is correct for datasets without missing data)
  if ( ! is.null(Etable) ){
    # sum over correct and incorrect expected responses
    prior <- ( rowSums(Etable[, seq(1,2*I,2)]) + rowSums(Etable[,seq(2,2*I,2)]) )/I
```

```
                }
  prior <- prior / sum(prior)
  return(prior)
}
#*** estimate discrete GOM in mirt package
mod2m <- mirt::mirt(dat, 1, rep( "icc_gom",I), customItems=list("icc_gom"=icc_gom),
           technical=list( customTheta=Theta, customPriorFun=lca_prior)  )
# correct number of estimated parameters
mod2m@nest <- as.integer(sum(mod.pars$est) + nrow(Theta)-1 )
# extract log-likelihood and compute AIC and BIC
mod2m@logLik
( AIC <- -2*mod2m@logLik+2*mod2m@nest )
( BIC <- -2*mod2m@logLik+log(mod2m@Data$N)*mod2m@nest )
# extract coefficients
( cmod2m <- sirt::mirt.wrapper.coef(mod2m) )
# compare estimated distributions
round( cbind( "sirt"=mod2$pi.k, "mirt"=mod2m@Prior[[1]] ), 5 )
  ##           sirt    mirt
  ##   [1,] 0.33357 0.33627
  ##   [2,] 0.18101 0.17789
  ##   [3,] 0.48542 0.48584
# compare estimated item parameters
dfr <- data.frame( "sirt"=mod2$item[,4:5] )
dfr$mirt <- apply(cmod2m$coef[, c("a1", "a2") ], 2, stats::plogis )
round(dfr,4)
  ##      sirt.lam.Cl1 sirt.lam.Cl2 mirt.a1 mirt.a2
  ##   1        0.1157       0.8935  0.1177  0.8934
  ##   2        0.0790       0.8360  0.0804  0.8360
  ##   3        0.0743       0.8165  0.0760  0.8164
  ##   4        0.0398       0.8093  0.0414  0.8094
  ##   5        0.1273       0.7244  0.1289  0.7243
  ##   [...]

################################################################################
# EXAMPLE 3: Lung cancer dataset; using sampling weights
################################################################################

data(data.si08, package="sirt")
dat <- data.si08

#- Latent class model with 3 classes
problevels <- c(0,1)
mod1 <- sirt::gom.em( dat[,1:5], weights=dat$wgt, K=3, problevels=problevels )
summary(mod1)

#- Grade of membership model with discrete distribution
problevels <- seq(0,1,length=5)
mod2 <- sirt::gom.em( dat[,1:5], weights=dat$wgt, K=3, problevels=problevels )
summary(mod2)

#- Grade of membership model with multivariate normal distribution
mod3 <- sirt::gom.em( dat[,1:5], weights=dat$wgt, K=3, theta0.k=10*seq(-1,1,len=11),
            model="GOMnormal", optimizer="nlminb" )
```

```
summary(mod3)

## End(Not run)
```

---

gom.jml *Grade of Membership Model (Joint Maximum Likelihood Estimation)*

Description

This function estimates the grade of membership model employing a joint maximum likelihood estimation method (Erosheva, 2002; p. 23ff.).

Usage

```
gom.jml(dat, K=2, seed=NULL, globconv=0.001, maxdevchange=0.001,
        maxiter=600, min.lambda=0.001, min.g=0.001)
```

Arguments

dat	Data frame of dichotomous item responses
K	Number of classes
seed	Seed value of random number generator. Deterministic starting values are used for the default value NULL.
globconv	Global parameter convergence criterion
maxdevchange	Maximum change in relative deviance
maxiter	Maximum number of iterations
min.lambda	Minimum λ_{ik} parameter to be estimated
min.g	Minimum g_{pk} parameter to be estimated

Details

The item response model of the grade of membership model with K classes for dichotomous correct responses X_{pi} of person p on item i is

$$P(X_{pi}=1|g_{p1},\ldots,g_{pK}) = \sum_k \lambda_{ik} g_{pk} \quad , \quad \sum_k g_{pk} = 1$$

Value

A list with following entries:

lambda	Data frame of item parameters λ_{ik}
g	Data frame of individual membership scores g_{pk}
g.mean	Mean membership scores
gcut	Discretized membership scores

gcut.distr	Distribution of discretized membership scores
K	Number of classes
deviance	Deviance
ic	Information criteria
N	Number of students
score	Person score
iter	Number of iterations
datproc	List with processed data (recoded data, starting values, ...)
...	Further values

References

Erosheva, E. A. (2002). *Grade of membership and latent structure models with application to disability survey data*. PhD thesis, Carnegie Mellon University, Department of Statistics.

See Also

S3 method summary.gom

Examples

```
#############################################################################
# EXAMPLE 1: TIMSS data
#############################################################################

data( data.timss)
dat <- data.timss$data[, grep("M", colnames(data.timss$data) ) ]

# 2 Classes (deterministic starting values)
m2 <- sirt::gom.jml(dat,K=2, maxiter=10 )
summary(m2)

## Not run:
# 3 Classes with fixed seed and maximum number of iterations
m3 <- sirt::gom.jml(dat,K=3, maxiter=50,seed=89)
summary(m3)

## End(Not run)
```

---

greenyang.reliability *Reliability for Dichotomous Item Response Data Using the Method of Green and Yang (2009)*

Description

This function estimates the model-based reliability of dichotomous data using the Green & Yang (2009) method. The underlying factor model is D-dimensional where the dimension D is specified by the argument `nfactors`. The factor solution is subject to the application of the Schmid-Leiman transformation (see Reise, 2012; Reise, Bonifay, & Haviland, 2013; Reise, Moore, & Haviland, 2010).

Usage

```
greenyang.reliability(object.tetra, nfactors)
```

Arguments

`object.tetra`	Object as the output of the function `tetrachoric`, the `fa.parallel.poly` from the **psych** package or the `tetrachoric2` function (from **sirt**). This object can also be created as a list by the user where the tetrachoric correlation must must be in the list entry `rho` and the thresholds must be in the list entry `thresh`.
`nfactors`	Number of factors (dimensions)

Value

A data frame with columns:

`coefficient`	Name of the reliability measure. `omega_1` (Omega) is the reliability estimate for the total score for dichotomous data based on a one-factor model, `omega_t` (Omega Total) is the estimate for a D-dimensional model. For the nested factor model, `omega_h` (Omega Asymptotic) is the reliability of the general factor model, `omega_ha` (Omega Hierarchical Asymptotic) eliminates item-specific variance. The explained common variance (`ECV`) explained by the common factor is based on the D-dimensional but does not take item thresholds into account. The amount of explained variance `ExplVar` is defined as the quotient of the first eigenvalue of the tetrachoric correlation matrix to the sum of all eigenvalues. The statistic `EigenvalRatio` is the ratio of the first and second eigenvalue.
`dimensions`	Number of dimensions
`estimate`	Reliability estimate

Note

This function needs the **psych** package.

References

Green, S. B., & Yang, Y. (2009). Reliability of summed item scores using structural equation modeling: An alternative to coefficient alpha. *Psychometrika, 74*, 155-167.

Reise, S. P. (2012). The rediscovery of bifactor measurement models. *Multivariate Behavioral Research, 47*, 667-696.

Reise, S. P., Bonifay, W. E., & Haviland, M. G. (2013). Scoring and modeling psychological measures in the presence of multidimensionality. *Journal of Personality Assessment, 95*, 129-140.

Reise, S. P., Moore, T. M., & Haviland, M. G. (2010). Bifactor models and rotations: Exploring the extent to which multidimensional data yield univocal scale scores, *Journal of Personality Assessment, 92*, 544-559.

See Also

See `f1d.irt` for estimating the functional unidimensional item response model.

This function uses `reliability.nonlinearSEM`.

See also the `MBESS::ci.reliability` function for estimating reliability for polytomous item responses.

Examples

```
## Not run:
#############################################################################
# EXAMPLE 1: Reliability estimation of Reading dataset data.read
#############################################################################
miceadds::library_install("psych")
set.seed(789)
data( data.read )
dat <- data.read

# calculate matrix of tetrachoric correlations
dat.tetra <- psych::tetrachoric(dat)      # using tetrachoric from psych package
dat.tetra2 <- sirt::tetrachoric2(dat)       # using tetrachoric2 from sirt package

# perform parallel factor analysis
fap <- psych::fa.parallel.poly(dat, n.iter=1 )
  ##   Parallel analysis suggests that the number of factors=3
  ##   and the number of components=2

# parallel factor analysis based on tetrachoric correlation matrix
##       (tetrachoric2)
fap2 <- psych::fa.parallel(dat.tetra2$rho, n.obs=nrow(dat),  n.iter=1 )
  ## Parallel analysis suggests that the number of factors=6
  ## and the number of components=2
  ## Note that in this analysis, uncertainty with respect to thresholds is ignored.

# calculate reliability using a model with 4 factors
greenyang.reliability( object.tetra=dat.tetra, nfactors=4 )
  ##                                          coefficient dimensions estimate
  ## Omega Total (1D)                             omega_1          1    0.771
  ## Omega Total (4D)                             omega_t          4    0.844
  ## Omega Hierarchical (4D)                      omega_h          4    0.360
  ## Omega Hierarchical Asymptotic (4D)           omega_ha         4    0.427
  ## Explained Common Variance (4D)                   ECV          4    0.489
  ## Explained Variance (First Eigenvalue)        ExplVar         NA   35.145
  ## Eigenvalue Ratio (1st to 2nd Eigenvalue) EigenvalRatio        NA    2.121

# calculation of Green-Yang-Reliability based on tetrachoric correlations
#   obtained by tetrachoric2
greenyang.reliability( object.tetra=dat.tetra2, nfactors=4 )
```

```
# The same result will be obtained by using fap as the input
greenyang.reliability( object.tetra=fap, nfactors=4 )
## End(Not run)
```

`invariance.alignment` *Alignment Procedure for Linking under Approximate Invariance*

Description

The function `invariance.alignment` performs alignment under approximate invariance for G groups and I items (Asparouhov & Muthen, 2014; Byrne & van de Vijver, 2017; DeMars, 2020; Finch, 2016; Fischer & Karl, 2019; Flake & McCoach, 2018; Kim et al., 2017; Marsh et al., 2018; Muthen & Asparouhov, 2014, 2018; Pokropek, Davidov & Schmidt, 2019). It is assumed that item loadings and intercepts are previously estimated as a unidimensional factor model under the assumption of a factor with zero mean and a variance of one.

The function `invariance_alignment_constraints` postprocesses the output of the `invariance.alignment` function and estimates item parameters under equality constraints for prespecified absolute values of parameter tolerance.

The function `invariance_alignment_simulate` simulates a one-factor model for multiple groups for given matrices of ν and λ parameters of item intercepts and item slopes (see Example 6).

The function `invariance_alignment_cfa_config` estimates one-factor models separately for each group as a preliminary step for invariance alignment (see Example 6). Sampling weights are accommodated by the argument `weights`. The computed variance matrix `vcov` by this function can be used to obtain standard errors in the `invariance.alignment` function if it is supplied as the argument `vcov`.

Usage

```
invariance.alignment(lambda, nu, wgt=NULL, align.scale=c(1, 1),
   align.pow=c(.5, .5), eps=1e-3, psi0.init=NULL, alpha0.init=NULL, center=FALSE,
   optimizer="optim", fixed=NULL, meth=1, vcov=NULL, eps_grid=seq(0,-10, by=-.5),
    num_deriv=FALSE, ...)

## S3 method for class 'invariance.alignment'
summary(object, digits=3, file=NULL, ...)

invariance_alignment_constraints(model, lambda_parm_tol, nu_parm_tol )

## S3 method for class 'invariance_alignment_constraints'
summary(object, digits=3, file=NULL, ...)

invariance_alignment_simulate(nu, lambda, err_var, mu, sigma, N, output="data",
     groupwise=FALSE, exact=FALSE)

invariance_alignment_cfa_config(dat, group, weights=NULL, model="2PM", verbose=FALSE, ...)
```

Arguments

lambda	A $G \times I$ matrix with item loadings
nu	A $G \times I$ matrix with item intercepts
wgt	A $G \times I$ matrix for weighing groups for each item
align.scale	A vector of length two containing scale parameter a_λ and a_ν (see Details)
align.pow	A vector of length two containing power p_λ and p_ν (see Details)
eps	A parameter in the optimization function
psi0.init	An optional vector of initial ψ_0 parameters
alpha0.init	An optional vector of initial α_0 parameters
center	Logical indicating whether estimated means and standard deviations should be centered.
optimizer	Name of the optimizer chosen for alignment. Options are "optim" (using stats::optim) or "nlminb" (using stats::nlminb).
fixed	Logical indicating whether SD of first group should be fixed to one. If fixed=FALSE, the product of all SDs is set to one. If NULL, then fixed is automatically chosen by default. For many groups, fixed=FALSE is chosen.
meth	Type of method used for optimization function. meth=1 is the default and the optimization function used in Mplus. meth=2 uses logarithmized item loadings in alignment. The choice meth=4 uses the constraint $\prod_g \psi_g = 1$ and adds the penalty $\lambda \sum_g \alpha_g^2$ for a fixed value λ that depends on the weights wgt (similar to Mplus' free method). The choice meth=3 only uses the constraint $\prod_g \psi_g = 1$ (similar to Mplus' FIXED method).
vcov	Variance matrix produced by invariance_alignment_cfa_config for standard error computation. If a matrix is provided, standard errors are computed.
eps_grid	Grid of logarithmized epsilon values in optimization
num_deriv	Logical indicating whether numerical derivatives should be used
object	Object of class invariance.alignment
digits	Number of digits used for rounding
file	Optional file name in which summary should be sunk
...	Further optional arguments to be passed
model	Model of class invariance.alignment. For invariance_alignment_cfa_config: Model type: "2PM" for two-parameter model with unequal loadings and "1PM" with equal loadings and equal residual variances
lambda_parm_tol	Parameter tolerance for λ parameters
nu_parm_tol	Parameter tolerance for ν parameters
err_var	Error variance
mu	Vector of means
sigma	Vector of standard deviations
N	Vector of sample sizes per group

`output`	Specifies output type: `"data"` for dataset and `"suffstat"` for sufficient statistics (i.e., means and covariance matrices)
`groupwise`	Logical indicating whether group-wise output is requested
`exact`	Logical indicating whether distributions should be exactly preserved in simulated data
`dat`	Dataset with items or a list containing sufficient statistics
`group`	Vector containing group indicators
`weights`	Optional vector of sampling weights
`verbose`	Logical indicating whether progress should be printed

Details

For G groups and I items, item loadings λ_{ig0} and intercepts ν_{ig0} are available and have been estimated in a 1-dimensional factor analysis assuming a standardized factor.

The alignment procedure searches means α_{g0} and standard deviations ψ_{g0} using an alignment optimization function F. This function is defined as

$$F = \sum_i \sum_{g_1<g_2} w_{i,g1} w_{i,g2} f_\lambda(\lambda_{ig_1,1} - \lambda_{ig_2,1}) + \sum_i \sum_{g_1<g_2} w_{i,g1} w_{i,g2} f_\nu(\nu_{ig_1,1} - \nu_{ig_2,1})$$

where the aligned item parameters $\lambda_{ig,1}$ and $\nu_{ig,1}$ are defined such that

$$\lambda_{ig,1} = \lambda_{ig0}/\psi_{g0} \qquad \text{and} \qquad \nu_{ig,1} = \nu_{ig0} - \alpha_{g0}\lambda_{ig0}/\psi_{g0}$$

and the optimization functions are defined as

$$f_\lambda(x) = |x/a_\lambda|^{p_\lambda} \approx [(x/a_\lambda)^2 + \varepsilon]^{p_\lambda/2} \qquad \text{and} \qquad f_\nu(x) = |x/a_\nu]^{p_\nu} \approx [(x/a_\nu)^2 + \varepsilon]^{p_\nu/2}$$

using a small $\varepsilon > 0$ (e.g. .001) to obtain a differentiable optimization function. For $p_\nu = 0$ or $p_\lambda = 0$, the optimization function essentially counts the number of different parameter and mimicks a L_0 penalty which is zero iff the argument is zero and one otherwise. It is approximated by

$$f(x) = x^2(x^2 + \varepsilon)^{-1}$$

(O'Neill & Burke, 2023).

For identification reasons, the product $\Pi_g \psi_{g0}$ (`meth`=0,0.5) of all group standard deviations or ψ_1 (`meth`=1,2) is set to one. The mean α_{g0} of the first group is set to zero (`meth`=0.5,1,2) or a penalty function is added to the linking function (`meth`=0).

Note that Asparouhov and Muthen (2014) use $a_\lambda = a_\nu = 1$ (which can be modified in `align.scale`) and $p_\lambda = p_\nu = 0.5$ (which can be modified in `align.pow`). In case of $p_\lambda = 2$, the penalty is approximately $f_\lambda(x) = x^2$, in case of $p_\lambda = 0.5$ it is approximately $f_\lambda(x) = \sqrt{|x|}$. Note that **sirt** used a different parametrization in versions up to 3.5. The p parameters have to be halved for consistency with previous versions (e.g., the Asparouhov & Muthen parametrization corresponds to $p = .25$; see also Fischer & Karl, 2019, for an application of the previous parametrization).

Effect sizes of approximate invariance based on R^2 have been proposed by Asparouhov and Muthen (2014). These are calculated separately for item loading and intercepts, resulting in R^2_λ and R^2_ν measures which are included in the output `es.invariance`. In addition, the average correlation of aligned item parameters among groups (`rbar`) is reported.

Metric invariance means that all aligned item loadings $\lambda_{ig,1}$ are equal across groups and therefore $R^2_\lambda = 1$. *Scalar invariance* means that all aligned item loadings $\lambda_{ig,1}$ and aligned item intercepts $\nu_{ig,1}$ are equal across groups and therefore $R^2_\lambda = 1$ and $R^2_\nu = 1$ (see Vandenberg & Lance, 2000).

Value

A list with following entries

`pars`	Aligned distribution parameters
`itempars.aligned`	Aligned item parameters for all groups
`es.invariance`	Effect sizes of approximate invariance
`lambda.aligned`	Aligned $\lambda_{ig,1}$ parameters
`lambda.resid`	Residuals of $\lambda_{ig,1}$ parameters
`nu.aligned`	Aligned $\nu_{ig,1}$ parameters
`nu.resid`	Residuals of $\nu_{ig,1}$ parameters
`Niter`	Number of iterations for f_λ and f_ν optimization functions
`fopt`	Minimum optimization value
`align.scale`	Used alignment scale parameters
`align.pow`	Used alignment power parameters
`vcov`	Estimated variance matrix of aligned means and standard deviations
`...`	More values

References

Asparouhov, T., & Muthen, B. (2014). Multiple-group factor analysis alignment. *Structural Equation Modeling, 21*(4), 1-14. doi:10.1080/10705511.2014.919210

Byrne, B. M., & van de Vijver, F. J. R. (2017). The maximum likelihood alignment approach to testing for approximate measurement invariance: A paradigmatic cross-cultural application. *Psicothema, 29*(4), 539-551. doi:10.7334/psicothema2017.178

DeMars, C. E. (2020). Alignment as an alternative to anchor purification in DIF analyses. *Structural Equation Modeling, 27*(1), 56-72. doi:10.1080/10705511.2019.1617151

Finch, W. H. (2016). Detection of differential item functioning for more than two groups: A Monte Carlo comparison of methods. *Applied Measurement in Education, 29*,(1), 30-45, doi:10.1080/08957347.2015.1102916

Fischer, R., & Karl, J. A. (2019). A primer to (cross-cultural) multi-group invariance testing possibilities in R. *Frontiers in Psychology | Cultural Psychology, 10*:1507. doi:10.3389/fpsyg.2019.01507

Flake, J. K., & McCoach, D. B. (2018). An investigation of the alignment method with polytomous indicators under conditions of partial measurement invariance. *Structural Equation Modeling, 25*(1), 56-70. doi:10.1080/10705511.2017.1374187

Kim, E. S., Cao, C., Wang, Y., & Nguyen, D. T. (2017). Measurement invariance testing with many groups: A comparison of five approaches. *Structural Equation Modeling, 24*(4), 524-544. doi:10.1080/10705511.2017.1304822

Marsh, H. W., Guo, J., Parker, P. D., Nagengast, B., Asparouhov, T., Muthen, B., & Dicke, T. (2018). What to do when scalar invariance fails: The extended alignment method for multi-group factor analysis comparison of latent means across many groups. *Psychological Methods, 23*(3), 524-545. doi: 10.1037/met0000113

Muthen, B., & Asparouhov, T. (2014). IRT studies of many groups: The alignment method. *Frontiers in Psychology | Quantitative Psychology and Measurement, 5*:978. doi:10.3389/fpsyg.2014.00978

Muthen, B., & Asparouhov, T. (2018). Recent methods for the study of measurement invariance with many groups: Alignment and random effects. *Sociological Methods & Research, 47*(4), 637-664. doi:10.1177/0049124117701488

O'Neill, M., & Burke, K. (2023). Variable selection using a smooth information criterion for distributional regression models. *Statistics and Computing, 33*(3), 71. doi:10.1007/s11222023102048

Pokropek, A., Davidov, E., & Schmidt, P. (2019). A Monte Carlo simulation study to assess the appropriateness of traditional and newer approaches to test for measurement invariance. *Structural Equation Modeling, 26*(5), 724-744. doi:10.1080/10705511.2018.1561293

Vandenberg, R. J., & Lance, C. E. (2000). A review and synthesis of the measurement invariance literature: Suggestions, practices, and recommendations for organizational research. *Organizational Research Methods, 3*, 4-70. doi:10.1177/109442810031002s

See Also

For IRT linking see also `linking.haberman` or `TAM::tam.linking`.

For modeling random item effects for loadings and intercepts see `mcmc.2pno.ml`.

Examples

```
#############################################################################
# EXAMPLE 1: Item parameters cultural activities
#############################################################################

data(data.activity.itempars, package="sirt")
lambda <- data.activity.itempars$lambda
nu <- data.activity.itempars$nu
Ng <-  data.activity.itempars$N
wgt <- matrix( sqrt(Ng), length(Ng), ncol(nu) )

#***
# Model 1: Alignment using a quadratic loss function
mod1 <- sirt::invariance.alignment( lambda, nu, wgt, align.pow=c(2,2) )
summary(mod1)

#****
# Model 2: Different powers for alignment
mod2 <- sirt::invariance.alignment( lambda, nu, wgt,  align.pow=c(.5,1),
              align.scale=c(.95,.95))
summary(mod2)

# compare means from Models 1 and 2
plot( mod1$pars$alpha0, mod2$pars$alpha0, pch=16,
    xlab="M (Model 1)", ylab="M (Model 2)", xlim=c(-.3,.3), ylim=c(-.3,.3) )
lines( c(-1,1), c(-1,1), col="gray")
round( cbind( mod1$pars$alpha0, mod2$pars$alpha0 ), 3 )
round( mod1$nu.resid, 3)
round( mod2$nu.resid,3 )
```

```
# L0 penalty
mod2b <- sirt::invariance.alignment( lambda, nu, wgt,  align.pow=c(0,0),
              align.scale=c(.3,.3))
summary(mod2b)

#****
# Model 3: Low powers for alignment of scale and power
# Note that setting increment.factor larger than 1 seems necessary
mod3 <- sirt::invariance.alignment( lambda, nu, wgt, align.pow=c(.5,.75),
            align.scale=c(.55,.55), psi0.init=mod1$psi0, alpha0.init=mod1$alpha0 )
summary(mod3)

# compare mean and SD estimates of Models 1 and 3
plot( mod1$pars$alpha0, mod3$pars$alpha0, pch=16)
plot( mod1$pars$psi0, mod3$pars$psi0, pch=16)

# compare residuals for Models 1 and 3
# plot lambda
plot( abs(as.vector(mod1$lambda.resid)), abs(as.vector(mod3$lambda.resid)),
      pch=16, xlab="Residuals lambda (Model 1)",
      ylab="Residuals lambda (Model 3)", xlim=c(0,.1), ylim=c(0,.1))
lines( c(-3,3),c(-3,3), col="gray")
# plot nu
plot( abs(as.vector(mod1$nu.resid)), abs(as.vector(mod3$nu.resid)),
      pch=16, xlab="Residuals nu (Model 1)", ylab="Residuals nu (Model 3)",
      xlim=c(0,.4),ylim=c(0,.4))
lines( c(-3,3),c(-3,3), col="gray")

## Not run:
#############################################################################
# EXAMPLE 2: Comparison 4 groups | data.inv4gr
#############################################################################

data(data.inv4gr)
dat <- data.inv4gr
miceadds::library_install("semTools")

model1 <- "
    F=~ I01 + I02 + I03 + I04 + I05 + I06 + I07 + I08 + I09 + I10 + I11
    F ~~ 1*F
    "

res <- semTools::measurementInvariance(model1, std.lv=TRUE, data=dat, group="group")
  ##   Measurement invariance tests:
  ##
  ##   Model 1: configural invariance:
  ##       chisq        df    pvalue       cfi     rmsea       bic
  ##     162.084   176.000     0.766     1.000     0.000 95428.025
  ##
  ##   Model 2: weak invariance (equal loadings):
  ##       chisq        df    pvalue       cfi     rmsea       bic
  ##     519.598   209.000     0.000     0.973     0.039 95511.835
  ##
```

```
  ##   [Model 1 versus model 2]
  ##     delta.chisq      delta.df delta.p.value     delta.cfi
  ##         357.514        33.000         0.000         0.027
  ##
  ##   Model 3: strong invariance (equal loadings + intercepts):
  ##       chisq        df    pvalue       cfi     rmsea       bic
  ##    2197.260   239.000     0.000     0.828     0.091 96940.676
  ##
  ##   [Model 1 versus model 3]
  ##     delta.chisq      delta.df delta.p.value     delta.cfi
  ##        2035.176        63.000         0.000         0.172
  ##
  ##   [Model 2 versus model 3]
  ##     delta.chisq      delta.df delta.p.value     delta.cfi
  ##        1677.662        30.000         0.000         0.144
  ##

# extract item parameters separate group analyses
ipars <- lavaan::parameterEstimates(res$fit.configural)
# extract lambda's: groups are in rows, items in columns
lambda <- matrix( ipars[ ipars$op=="=~", "est"], nrow=4,  byrow=TRUE)
colnames(lambda) <- colnames(dat)[-1]
# extract nu's
nu <- matrix( ipars[ ipars$op=="~1"  & ipars$se !=0, "est" ], nrow=4,  byrow=TRUE)
colnames(nu) <- colnames(dat)[-1]

# Model 1: least squares optimization
mod1 <- sirt::invariance.alignment( lambda=lambda, nu=nu )
summary(mod1)
  ##   Effect Sizes of Approximate Invariance
  ##          loadings intercepts
  ##   R2       0.9826     0.9972
  ##   sqrtU2   0.1319     0.0526
  ##   rbar     0.6237     0.7821
  ##   ----------------------------------------------------------------
  ##   Group Means and Standard Deviations
  ##     alpha0  psi0
  ##   1  0.000 0.965
  ##   2 -0.105 1.098
  ##   3 -0.081 1.011
  ##   4  0.171 0.935

# Model 2: sparse target function
mod2 <- sirt::invariance.alignment( lambda=lambda, nu=nu, align.pow=c(.5,.5) )
summary(mod2)
  ##   Effect Sizes of Approximate Invariance
  ##          loadings intercepts
  ##   R2       0.9824     0.9972
  ##   sqrtU2   0.1327     0.0529
  ##   rbar     0.6237     0.7856
  ##   ----------------------------------------------------------------
  ##   Group Means and Standard Deviations
  ##     alpha0  psi0
```

```
  ##   1 -0.002 0.965
  ##   2 -0.107 1.098
  ##   3 -0.083 1.011
  ##   4  0.170 0.935

#############################################################################
# EXAMPLE 3: European Social Survey data.ess2005
#############################################################################

data(data.ess2005)
lambda <- data.ess2005$lambda
nu <- data.ess2005$nu

# Model 1: least squares optimization
mod1 <- sirt::invariance.alignment( lambda=lambda, nu=nu, align.pow=c(2,2) )
summary(mod1)

# Model 2: sparse target function and definition of scales
mod2 <- sirt::invariance.alignment( lambda=lambda, nu=nu, control=list(trace=2) )
summary(mod2)

#############################################################################
# EXAMPLE 4: Linking with item parameters containing outliers
#############################################################################

# see Help file in linking.robust

# simulate some item difficulties in the Rasch model
I <- 38
set.seed(18785)
itempars <- data.frame("item"=paste0("I",1:I) )
itempars$study1 <- stats::rnorm( I, mean=.3, sd=1.4 )
# simulate DIF effects plus some outliers
bdif <- stats::rnorm(I, mean=.4, sd=.09) +
            (stats::runif(I)>.9 )*rep( 1*c(-1,1)+.4, each=I/2 )
itempars$study2 <- itempars$study1 + bdif
# create input for function invariance.alignment
nu <- t( itempars[,2:3] )
colnames(nu) <- itempars$item
lambda <- 1+0*nu

# linking using least squares optimization
mod1 <- sirt::invariance.alignment( lambda=lambda, nu=nu )
summary(mod1)
  ##   Group Means and Standard Deviations
  ##          alpha0 psi0
  ##   study1 -0.286    1
  ##   study2  0.286    1

# linking using powers of .5
mod2 <- sirt::invariance.alignment( lambda=lambda, nu=nu, align.pow=c(1,1) )
summary(mod2)
  ##   Group Means and Standard Deviations
```

```
  ##          alpha0 psi0
  ##   study1 -0.213    1
  ##   study2  0.213    1

# linking using powers of .25
mod3 <- sirt::invariance.alignment( lambda=lambda, nu=nu, align.pow=c(.5,.5) )
summary(mod3)
  ##   Group Means and Standard Deviations
  ##          alpha0 psi0
  ##   study1 -0.207    1
  ##   study2  0.207    1

#############################################################################
# EXAMPLE 5: Linking gender groups with data.math
#############################################################################

data(data.math)
dat <- data.math$data
dat.male <- dat[ dat$female==0, substring( colnames(dat),1,1)=="M"  ]
dat.female <- dat[ dat$female==1, substring( colnames(dat),1,1)=="M"  ]

#*************************
# Model 1: Linking using the Rasch model
mod1m <- sirt::rasch.mml2( dat.male )
mod1f <- sirt::rasch.mml2( dat.female )

# create objects for invariance.alignment
nu <- rbind( mod1m$item$thresh, mod1f$item$thresh )
colnames(nu) <- mod1m$item$item
rownames(nu) <- c("male", "female")
lambda <- 1+0*nu

# mean of item difficulties
round( rowMeans(nu), 3 )

# Linking using least squares optimization
res1a <- sirt::invariance.alignment( lambda, nu, align.scale=c( .3, .5 ) )
summary(res1a)

# Linking using optimization with absolute value function (pow=.5)
res1b <- sirt::invariance.alignment( lambda, nu, align.scale=c( .3, .5 ),
                align.pow=c(1,1) )
summary(res1b)

#-- compare results with Haberman linking
I <- ncol(dat.male)
itempartable <- data.frame( "study"=rep( c("male", "female"), each=I ) )
itempartable$item <- c( paste0(mod1m$item$item),  paste0(mod1f$item$item) )
itempartable$a <- 1
itempartable$b <- c( mod1m$item$b, mod1f$item$b )
# estimate linking parameters
res1c <- sirt::linking.haberman( itempars=itempartable )
```

```
#-- results of sirt::equating.rasch
x <- itempartable[ 1:I, c("item", "b") ]
y <- itempartable[ I + 1:I, c("item", "b") ]
res1d <- sirt::equating.rasch( x, y )
round( res1d$B.est, 3 )
  ##     Mean.Mean Haebara Stocking.Lord
  ##   1     0.032   0.032         0.029

#*************************
# Model 2: Linking using the 2PL model
I <- ncol(dat.male)
mod2m <- sirt::rasch.mml2( dat.male, est.a=1:I)
mod2f <- sirt::rasch.mml2( dat.female, est.a=1:I)

# create objects for invariance.alignment
nu <- rbind( mod2m$item$thresh, mod2f$item$thresh )
colnames(nu) <- mod2m$item$item
rownames(nu) <- c("male", "female")
lambda <- rbind( mod2m$item$a, mod2f$item$a )
colnames(lambda) <- mod2m$item$item
rownames(lambda) <- c("male", "female")

res2a <- sirt::invariance.alignment( lambda, nu, align.scale=c( .3, .5 ) )
summary(res2a)

res2b <- sirt::invariance.alignment( lambda, nu, align.scale=c( .3, .5 ),
                align.pow=c(1,1) )
summary(res2b)

# compare results with Haberman linking
I <- ncol(dat.male)
itempartable <- data.frame( "study"=rep( c("male", "female"), each=I ) )
itempartable$item <- c( paste0(mod2m$item$item),  paste0(mod2f$item$item ) )
itempartable$a <- c( mod2m$item$a, mod2f$item$a )
itempartable$b <- c( mod2m$item$b, mod2f$item$b )
# estimate linking parameters
res2c <- sirt::linking.haberman( itempars=itempartable )

#############################################################################
# EXAMPLE 6: Data from Asparouhov & Muthen (2014) simulation study
#############################################################################

G <- 3  # number of groups
I <- 5  # number of items
# define lambda and nu parameters
lambda <- matrix(1, nrow=G, ncol=I)
nu <- matrix(0, nrow=G, ncol=I)

# define size of noninvariance
dif <- 1

#- 1st group: N(0,1)
lambda[1,3] <- 1+dif*.4; nu[1,5] <- dif*.5
```

```
#- 2nd group: N(0.3,1.5)
gg <- 2 ; mu <- .3; sigma <- sqrt(1.5)
lambda[gg,5] <- 1-.5*dif; nu[gg,1] <- -.5*dif
nu[gg,] <- nu[gg,] + mu*lambda[gg,]
lambda[gg,] <- lambda[gg,] * sigma

#- 3nd group: N(.8,1.2)
gg <- 3 ; mu <- .8; sigma <- sqrt(1.2)
lambda[gg,4] <- 1-.7*dif; nu[gg,2] <- -.5*dif
nu[gg,] <- nu[gg,] + mu*lambda[gg,]
lambda[gg,] <- lambda[gg,] * sigma

# define alignment scale
align.scale <- c(.2,.4)   # Asparouhov and Muthen use c(1,1)
# define alignment powers
align.pow <- c(.5,.5)   # as in Asparouhov and Muthen

#*** estimate alignment parameters
mod1 <- sirt::invariance.alignment( lambda, nu, eps=.01, optimizer="optim",
            align.scale=align.scale, align.pow=align.pow, center=FALSE )
summary(mod1)

#--- find parameter constraints for prespecified tolerance
cmod1 <- sirt::invariance_alignment_constraints(model=mod1, nu_parm_tol=.4,
            lambda_parm_tol=.2 )
summary(cmod1)

############################################################################
# EXAMPLE 7: Similar to Example 6, but with data simulation and CFA estimation
############################################################################

#--- data simulation

set.seed(65)
G <- 3  # number of groups
I <- 5  # number of items
# define lambda and nu parameters
lambda <- matrix(1, nrow=G, ncol=I)
nu <- matrix(0, nrow=G, ncol=I)
err_var <- matrix(1, nrow=G, ncol=I)

# define size of noninvariance
dif <- 1
#- 1st group: N(0,1)
lambda[1,3] <- 1+dif*.4; nu[1,5] <- dif*.5
#- 2nd group: N(0.3,1.5)
gg <- 2 ;
lambda[gg,5] <- 1-.5*dif; nu[gg,1] <- -.5*dif
#- 3nd group: N(.8,1.2)
gg <- 3
lambda[gg,4] <- 1-.7*dif; nu[gg,2] <- -.5*dif
#- define distributions of groups
```

```
mu <- c(0,.3,.8)
sigma <- sqrt(c(1,1.5,1.2))
N <- rep(1000,3) # sample sizes per group

#* simulate data
dat <- sirt::invariance_alignment_simulate(nu, lambda, err_var, mu, sigma, N)
head(dat)

#--- estimate CFA models
pars <- sirt::invariance_alignment_cfa_config(dat[,-1], group=dat$group)
print(pars)

#--- invariance alignment
# define alignment scale
align.scale <- c(.2,.4)
# define alignment powers
align.pow <- c(.5,.5)
mod1 <- sirt::invariance.alignment( lambda=pars$lambda, nu=pars$nu, eps=.01,
          optimizer="optim", align.scale=align.scale, align.pow=align.pow, center=FALSE)
#* find parameter constraints for prespecified tolerance
cmod1 <- sirt::invariance_alignment_constraints(model=mod1, nu_parm_tol=.4,
            lambda_parm_tol=.2 )
summary(cmod1)

#--- estimate CFA models with sampling weights

#* simulate weights
weights <- stats::runif(sum(N), 0, 2)
#* estimate models
pars2 <- sirt::invariance_alignment_cfa_config(dat[,-1], group=dat$group, weights=weights)
print(pars2$nu)
print(pars$nu)

#--- estimate one-parameter model
pars <- sirt::invariance_alignment_cfa_config(dat[,-1], group=dat$group, model="1PM")
print(pars)

#############################################################################
# EXAMPLE 8: Computation of standard errors
#############################################################################

G <- 3  # number of groups
I <- 5  # number of items
# define lambda and nu parameters
lambda <- matrix(1, nrow=G, ncol=I)
nu <- matrix(0, nrow=G, ncol=I)

# define size of noninvariance
dif <- 1

mu1 <- c(0,.3,.8)
sigma1 <- c(1,1.25,1.1)
```

```
#- 1st group
lambda[1,3] <- 1+dif*.4; nu[1,5] <- dif*.5

#- 2nd group
gg <- 2
lambda[gg,5] <- 1-.5*dif; nu[gg,1] <- -.5*dif

#- 3nd group
gg <- 3
lambda[gg,4] <- 1-.7*dif; nu[gg,2] <- -.5*dif

dat <- sirt::invariance_alignment_simulate(nu=nu, lambda=lambda, err_var=1+0*lambda,
               mu=mu1, sigma=sigma1, N=500, output="data", exact=TRUE)

#* estimate CFA
res <- sirt::invariance_alignment_cfa_config(dat=dat[,-1], group=dat$group )

#- perform invariance alignment
eps <- .001
align.pow <- 0.5*rep(1,2)
lambda <- res$lambda
nu <- res$nu
mod1 <- sirt::invariance.alignment( lambda=lambda, nu=nu, eps=eps, optimizer="optim",
            align.pow=align.pow, meth=meth, vcov=res$vcov)
# variance matrix and standard errors
mod1$vcov
sqrt(diag(mod1$vcov))

#############################################################################
# EXAMPLE 9: Comparison 2 groups for dichotomous data | data.pisaMath
#############################################################################

data(data.pisaMath)
dat <- data.pisaMath$data
library("lavaan")

model1 <- "
    F=~ M192Q01 + M406Q01 + M406Q02 + M423Q01 + M496Q01 + M496Q02 + M564Q01 +
         M564Q02 + M571Q01 + M603Q01 + M603Q02
    "

fit.configural <- lavaan::cfa(model1, data=dat, group="female",
                  ordered=TRUE, std.lv=TRUE, parameterization="theta")
lavaan::summary(fit.configural, standardized=TRUE)

# extract item parameters separate group analyses
ipars <- lavaan::parameterEstimates(fit.configural)
# extract lambda's: groups are in rows, items in columns
lambda <- matrix( ipars[ ipars$op=="=~", "est"], nrow=2,  byrow=TRUE)
colnames(lambda) <- colnames(dat)[6:16]
# extract nu's
nu <- matrix( ipars[ ipars$op=="|" & ipars$se !=0, "est" ], nrow=2,  byrow=TRUE)
colnames(nu) <- colnames(dat)[6:16]
```

```
# Model 1: apply invariance alignment
mod1 <- sirt::invariance.alignment( lambda=lambda, nu=nu )
summary(mod1)

## End(Not run)
```

IRT.mle *Person Parameter Estimation*

Description

Computes the maximum likelihood estimate (MLE), weighted likelihood estimate (WLE) and maximum aposterior estimate (MAP) of ability in unidimensional item response models (Penfield & Bergeron, 2005; Warm, 1989). Item response functions can be defined by the user.

Usage

```
IRT.mle(data, irffct, arg.list, theta=rep(0,nrow(data)), type="MLE",
     mu=0, sigma=1, maxiter=20, maxincr=3, h=0.001, convP=1e-04,
     maxval=9, progress=TRUE)
```

Arguments

data	Data frame with item responses
irffct	User defined item response (see Examples). Arguments must be specified in arg.list. The function must contain theta and ii (item index) as arguments.
theta	Initial ability estimate
arg.list	List of arguments for irffct.
type	Type of ability estimate. It can be "MLE" (the default), "WLE" or "MAP".
mu	Mean of normal prior distribution (for type="MAP")
sigma	Standard deviation of normal prior distribution (for type="MAP")
maxiter	Maximum number of iterations
maxincr	Maximum increment
h	Numerical differentiation parameter
convP	Convergence criterion
maxval	Maximum ability value to be estimated
progress	Logical indicating whether iteration progress should be displayed

Value

Data frame with estimated abilities (est) and its standard error (se).

References

Penfield, R. D., & Bergeron, J. M. (2005). Applying a weighted maximum likelihood latent trait estimator to the generalized partial credit model. *Applied Psychological Measurement, 29*, 218-233.

Warm, T. A. (1989). Weighted likelihood estimation of ability in item response theory. *Psychometrika, 54*, 427-450.

See Also

See also the **PP** package for further person parameter estimation methods.

Examples

```
## Not run:
#############################################################################
# EXAMPLE 1: Generalized partial credit model
#############################################################################

data(data.ratings1)
dat <- data.ratings1

# estimate model
mod1 <- sirt::rm.facets( dat[, paste0( "k",1:5) ], rater=dat$rater,
             pid=dat$idstud, maxiter=15)
# extract dataset and item parameters
data <- mod1$procdata$dat2.NA
a <- mod1$ipars.dat2$a
b <- mod1$ipars.dat2$b
theta0 <- mod1$person$EAP
# define item response function for item ii
calc.pcm <- function( theta, a, b, ii ){
    K <- ncol(b)
    N <- length(theta)
    matrK <- matrix( 0:K, nrow=N, ncol=K+1, byrow=TRUE)
    eta <- a[ii] * theta * matrK - matrix( c(0,b[ii,]), nrow=N, ncol=K+1, byrow=TRUE)
    eta <- exp(eta)
    probs <- eta / rowSums(eta, na.rm=TRUE)
    return(probs)
}
arg.list <- list("a"=a, "b"=b )

# MLE
abil1 <- sirt::IRT.mle( data, irffct=calc.pcm, theta=theta0, arg.list=arg.list )
str(abil1)
# WLE
abil2 <- sirt::IRT.mle( data, irffct=calc.pcm, theta=theta0, arg.list=arg.list, type="WLE")
str(abil2)
# MAP with prior distribution N(.2, 1.3)
abil3 <- sirt::IRT.mle( data, irffct=calc.pcm, theta=theta0, arg.list=arg.list,
             type="MAP", mu=.2, sigma=1.3 )
str(abil3)
```

```
#############################################################################
# EXAMPLE 2: Rasch model
#############################################################################

data(data.read)
dat <- data.read
I <- ncol(dat)

# estimate Rasch model
mod1 <- sirt::rasch.mml2( dat )
summary(mod1)

# define item response function
irffct <- function( theta, b, ii){
    eta <- exp( theta - b[ii] )
    probs <- eta / ( 1 + eta )
    probs <- cbind( 1 - probs, probs )
    return(probs)
}
# initial person parameters and item parameters
theta0 <- mod1$person$EAP
arg.list <- list( "b"=mod1$item$b  )

# estimate WLE
abil <- sirt::IRT.mle( data=dat, irffct=irffct, arg.list=arg.list,
            theta=theta0, type="WLE")
# compare with wle.rasch function
theta <- sirt::wle.rasch( dat, b=mod1$item$b )
cbind( abil[,1], theta$theta, abil[,2], theta$se.theta )

#############################################################################
# EXAMPLE 3: Ramsay quotient model
#############################################################################

data(data.read)
dat <- data.read
I <- ncol(dat)

# estimate Ramsay model
mod1 <- sirt::rasch.mml2( dat, irtmodel="ramsay.qm" )
summary(mod1)
# define item response function
irffct <- function( theta, b, K, ii){
    eta <- exp( theta / b[ii] )
    probs <- eta / ( K[ii] + eta )
    probs <- cbind( 1 - probs, probs )
    return(probs)
}
# initial person parameters and item parameters
theta0 <- exp( mod1$person$EAP )
arg.list <- list( "b"=mod1$item2$b, "K"=mod1$item2$K )
# estimate MLE
res <- sirt::IRT.mle( data=dat, irffct=irffct, arg.list=arg.list, theta=theta0,
```

```
            maxval=20, maxiter=50)

## End(Not run)
```

`isop` *Fit Unidimensional ISOP and ADISOP Model to Dichotomous and Polytomous Item Responses*

Description

Fit the unidimensional isotonic probabilistic model (ISOP; Scheiblechner, 1995, 2007) and the additive istotonic probabilistic model (ADISOP; Scheiblechner, 1999). The `isop.dich` function can be used for dichotomous data while the `isop.poly` function can be applied to polytomous data. Note that for applying the ISOP model for polytomous data it is necessary that all items do have the same number of categories.

Usage

```
isop.dich(dat, score.breaks=NULL, merge.extreme=TRUE,
     conv=.0001, maxit=1000, epsilon=.025, progress=TRUE)

isop.poly( dat, score.breaks=seq(0,1,len=10 ),
     conv=.0001, maxit=1000, epsilon=.025, progress=TRUE )

## S3 method for class 'isop'
summary(object,...)

## S3 method for class 'isop'
plot(x,ask=TRUE,...)
```

Arguments

`dat`	Data frame with dichotomous or polytomous item responses
`score.breaks`	Vector with breaks to define score groups. For dichotomous data, the person score grouping is applied for the mean person score, for polytomous data it is applied to the modified percentile score.
`merge.extreme`	Merge extreme groups with zero and maximum score with succeeding score categories? The default is `TRUE`.
`conv`	Convergence criterion
`maxit`	Maximum number of iterations
`epsilon`	Additive constant to handle cell frequencies of 0 or 1 in `fit.adisop`
`progress`	Display progress?
`object`	Object of class `isop` (generated by `isop.dich` or `isop.poly`)
`x`	Object of class `isop` (generated by `isop.dich` or `isop.poly`)
`ask`	Ask for a new plot?
`...`	Further arguments to be passed

Details

The ISOP model for dichotomous data was firstly proposed by Irtel and Schmalhofer (1982). Consider person groups p (ordered from low to high scores) and items i (ordered from difficult to easy items). Here, $F(p,i)$ denotes the proportion correct for item i in score group p, while n_{pi} denotes the number of persons in group p and on item i. The isotonic probabilistic model (Scheiblechner, 1995) monotonically smooths this distribution function F such that

$$P(X_{pi}=1|p,i)=F^*(p,i)$$

where the two-dimensional distribution function F^* is isotonic in p and i. Model fit is assessed by the square root of weighted squares of deviations

$$Fit=\sqrt{\frac{1}{I}\sum_{p,i} w_{pi}\left(F(p,i)-F^*(p,i)\right)^2}$$

with frequency weights w_{pi} and $\sum_p w_{pi}=1$ for every item i. The additive isotonic model (ADISOP; Scheiblechner, 1999) assumes the existence of person parameters θ_p and item parameters δ_i such that

$$P(X_{pi}=1|p)=g(\theta_p+\delta_i)$$

and g is a nonparametrically estimated isotonic function. The functions `isop.dich` and `isop.poly` uses F^* from the ISOP models and estimates person and item parameters of the ADISOP model. For comparison, `isop.dich` also fits a model with the logistic function g which results in the Rasch model.

For polytomous data, the starting point is the empirical distribution function

$$P(X_i\leq k|p)=F(k;p,i)$$

which is increasing in the argument k (the item categories). The ISOP model is defined to be antitonic in p and i while items are ordered with respect to item P-scores and persons are ordered according to modified percentile scores (Scheiblechner, 2007). The estimated ISOP model results in a distribution function F^*. Using this function, the additive isotonic probabilistic model (ADISOP) aims at estimating a distribution function

$$P(X_i\leq k;p)=F^{**}(k;p,i)=F^{**}(k,\theta_p+\delta_i)$$

which is antitonic in k and in $\theta_p+\delta_i$. Due to this additive relation, the ADISOP scale values are claimed to be measured at interval scale level (Scheiblechner, 1999).

The ADISOP model is compared to the graded response model which is defined by the response equation

$$P(X_i\leq k;p)=g(\theta_p+\delta_i+\gamma_k)$$

where g denotes the logistic function. Estimated parameters are in the value `fit.grm`: person parameters θ_p (`person.sc`), item parameters δ_i (`item.sc`) and category parameters γ_k (`cat.sc`).

The calculation of person and item scores is explained in `isop.scoring`.

For an application of the ISOP and ADISOP model see Scheiblechner and Lutz (2009).

Value

A list with following entries:

`freq.correct`	Used frequency table (distribution function) for dichotomous and polytomous data
`wgt`	Used weights (frequencies)
`prob.saturated`	Frequencies of the saturated model
`prob.isop`	Fitted frequencies of the ISOP model
`prob.adisop`	Fitted frequencies of the ADISOP model
`prob.logistic`	Fitted frequencies of the logistic model (only for `isop.dich`)
`prob.grm`	Fitted frequencies of the graded response model (only for `isop.poly`)
`ll`	List with log-likelihood values
`fit`	Vector of fit statistics
`person`	Data frame of person parameters
`item`	Data frame of item parameters
`p.itemcat`	Frequencies for every item category
`score.itemcat`	Scoring points for every item category
`fit.isop`	Values of fitting the ISOP model (see `fit.isop`)
`fit.isop`	Values of fitting the ADISOP model (see `fit.adisop`)
`fit.logistic`	Values of fitting the logistic model (only for `isop.dich`)
`fit.grm`	Values of fitting the graded response model (only for `isop.poly`)
`...`	Further values

References

Irtel, H., & Schmalhofer, F. (1982). Psychodiagnostik auf Ordinalskalenniveau: Messtheoretische Grundlagen, Modelltest und Parameterschaetzung. *Archiv fuer Psychologie, 134*, 197-218.

Scheiblechner, H. (1995). Isotonic ordinal probabilistic models (ISOP). *Psychometrika, 60*, 281-304.

Scheiblechner, H. (1999). Additive conjoint isotonic probabilistic models (ADISOP). *Psychometrika, 64*, 295-316.

Scheiblechner, H. (2007). A unified nonparametric IRT model for d-dimensional psychological test data (d-ISOP). *Psychometrika, 72*, 43-67.

Scheiblechner, H., & Lutz, R. (2009). Die Konstruktion eines optimalen eindimensionalen Tests mittels nichtparametrischer Testtheorie (NIRT) am Beispiel des MR SOC. *Diagnostica, 55*, 41-54.

See Also

This function uses `isop.scoring`, `fit.isop` and `fit.adisop`.

Tests of the W1 axiom of the ISOP model (Scheiblechner, 1995) can be performed with `isop.test`.

See also the **ISOP** package at *Rforge*: *http://www.rforge.net/ISOP/*.

Install this package using

```
install.packages("ISOP",repos="http://www.rforge.net/")
```

Examples

```
#############################################################################
# EXAMPLE 1: Dataset Reading (dichotomous items)
#############################################################################

data(data.read)
dat <- as.matrix( data.read)
I <- ncol(dat)

# Model 1: ISOP Model (11 score groups)
mod1 <- sirt::isop.dich( dat )
summary(mod1)
plot(mod1)

## Not run:
# Model 2: ISOP Model (5 score groups)
score.breaks <- seq( -.005, 1.005, len=5+1 )
mod2 <- sirt::isop.dich( dat, score.breaks=score.breaks)
summary(mod2)

#############################################################################
# EXAMPLE 2: Dataset PISA mathematics (dichotomous items)
#############################################################################

data(data.pisaMath)
dat <- data.pisaMath$data
dat <- dat[, grep("M", colnames(dat) ) ]

# fit ISOP model
# Note that for this model many iterations are needed
#   to reach convergence for ADISOP
mod1 <- sirt::isop.dich( dat, maxit=4000)
summary(mod1)

## End(Not run)

#############################################################################
# EXAMPLE 3: Dataset Students (polytomous items)
#############################################################################

# Dataset students: scale cultural activities
library(CDM)
data(data.Students, package="CDM")
dat <- stats::na.omit( data.Students[, paste0("act",1:4) ] )

# fit models
mod1 <- sirt::isop.poly( dat )
summary(mod1)
plot(mod1)
```

`isop.scoring` *Scoring Persons and Items in the ISOP Model*

Description

This function does the scoring in the isotonic probabilistic model (Scheiblechner, 1995, 2003, 2007). Person parameters are ordinally scaled but the ISOP model also allows *specific objective* (ordinal) comparisons for persons (Scheiblechner, 1995).

Usage

```
isop.scoring(dat,score.itemcat=NULL)
```

Arguments

`dat`	Data frame with dichotomous or polytomous item responses
`score.itemcat`	Optional data frame with scoring points for every item and every category (see Example 2).

Details

This function extracts the scoring rule of the ISOP model (if `score.itemcat !=NULL`) and calculates the modified percentile score for every person. The score s_{ik} for item i and category k is calculated as

$$s_{ik} = \sum_{j=0}^{k-1} f_{ij} - \sum_{j=k+1}^{K} f_{ij} = P(X_i < k) - P(X_i > k)$$

where f_{ik} is the relative frequency of item i in category k and K is the maximum category. The modified percentile score ρ_p for subject p (`mpsc` in `person`) is defined by

$$\rho_p = \frac{1}{I} \sum_{i=1}^{I} \sum_{j=0}^{K} s_{ik} \mathbf{1}(X_{pi} = k)$$

Note that for dichotomous items, the sum score is a sufficient statistic for ρ_p but this is not the case for polytomous items. The modified percentile score ρ_p ranges between -1 and 1.

The modified item P-score ρ_i (Scheiblechner, 2007, p. 52) is defined by

$$\rho_i = \frac{1}{I-1} \cdot \sum_{j} [P(X_j < X_i) - P(X_j > X_i)]$$

Value

A list with following entries:

`person`	A data frame with person parameters. The modified percentile score ρ_p is denoted by `mpsc`.

`item`	Item statistics and scoring parameters. The item P-scores ρ_i are labeled as `pscore`.
`p.itemcat`	Frequencies for every item category
`score.itemcat`	Scoring points for every item category
`distr.fct`	Empirical distribution function

References

Scheiblechner, H. (1995). Isotonic ordinal probabilistic models (ISOP). *Psychometrika, 60*, 281-304.

Scheiblechner, H. (2003). *Nonparametric IRT: Scoring functions and ordinal parameter estimation of isotonic probabilistic models (ISOP)*. Technical Report, Philipps-Universitaet Marburg.

Scheiblechner, H. (2007). A unified nonparametric IRT model for d-dimensional psychological test data (d-ISOP). *Psychometrika, 72*, 43-67.

See Also

For fitting the ISOP and ADISOP model see `isop.dich` or `fit.isop`.

Examples

```
#############################################################################
# EXAMPLE 1: Dataset Reading
#############################################################################

data( data.read )
dat <- data.read

# Scoring according to the ISOP model
msc <- sirt::isop.scoring( dat )
# plot student scores
boxplot( msc$person$mpsc ~ msc$person$score )

#############################################################################
# EXAMPLE 2: Dataset students from CDM package | polytomous items
#############################################################################

library("CDM")
data( data.Students, package="CDM")
dat <- stats::na.omit(data.Students[, -c(1:2) ])

# Scoring according to the ISOP model
msc <- sirt::isop.scoring( dat )
# plot student scores
boxplot( msc$person$mpsc ~ msc$person$score )

# scoring with known scoring rule for activity items
items <- paste0( "act", 1:5 )
score.itemcat <- msc$score.itemcat
score.itemcat <- score.itemcat[ items, ]
msc2 <- sirt::isop.scoring( dat[,items], score.itemcat=score.itemcat )
```

`isop.test` *Testing the ISOP Model*

Description

This function performs tests of the W1 axiom of the ISOP model (Scheiblechner, 2003). Standard errors of the corresponding $W1_i$ statistics are obtained by Jackknife.

Usage

```
isop.test(data, jackunits=20, weights=rep(1, nrow(data)))

## S3 method for class 'isop.test'
summary(object,...)
```

Arguments

`data`	Data frame with item responses
`jackunits`	A number of Jackknife units (if an integer is provided as the argument value) or a vector in the Jackknife units are already defined.
`weights`	Optional vector of sampling weights
`object`	Object of class `isop.test`
`...`	Further arguments to be passed

Value

A list with following entries

`itemstat`	Data frame with test and item statistics for the W1 axiom. The $W1_i$ statistic is denoted as `est` while `se` is the corresponding standard error of the statistic. The sample size per item is `N` and `M` denotes the item mean.
`Es`	Number of concordances per item
`Ed`	Number of disconcordances per item

The $W1_i$ statistics are printed by the `summary` method.

References

Scheiblechner, H. (2003). Nonparametric IRT: Testing the bi-isotonicity of isotonic probabilistic models (ISOP). *Psychometrika, 68*, 79-96.

See Also

Fit the ISOP model with `isop.dich` or `isop.poly`.

See also the **ISOP** package at *Rforge*: *http://www.rforge.net/ISOP/*.

Examples

```
#############################################################################
# EXAMPLE 1: ISOP model data.Students
#############################################################################

data(data.Students, package="CDM")
dat <- data.Students[, paste0("act",1:5) ]
dat <- dat[1:300, ]    # select first 300 students

# perform the ISOP test
mod <- sirt::isop.test(dat)
summary(mod)
  ## -> W1i statistics
  ##     parm   N     M   est    se      t
  ##   1 test 300    NA 0.430 0.036 11.869
  ##   2 act1 278 0.601 0.451 0.048  9.384
  ##   3 act2 275 0.473 0.473 0.035 13.571
  ##   4 act3 274 0.277 0.352 0.098  3.596
  ##   5 act4 291 1.320 0.381 0.054  7.103
  ##   6 act5 276 0.460 0.475 0.042 11.184
```

---

latent.regression.em.raschtype

Latent Regression Model for the Generalized Logistic Item Response Model and the Linear Model for Normal Responses

---

Description

This function estimates a unidimensional latent regression model if a likelihood is specified, parameters from the generalized item response model (Stukel, 1988) or a mean and a standard error estimate for individual scores is provided as input. Item parameters are treated as fixed in the estimation.

Usage

```
latent.regression.em.raschtype(data=NULL, f.yi.qk=NULL, X,
    weights=rep(1, nrow(X)), beta.init=rep(0,ncol(X)),
    sigma.init=1, b=rep(0,ncol(X)), a=rep(1,length(b)),
    c=rep(0, length(b)), d=rep(1, length(b)), alpha1=0, alpha2=0,
    max.parchange=1e-04, theta.list=seq(-5, 5, len=20),
    maxiter=300, progress=TRUE )

latent.regression.em.normal(y, X, sig.e, weights=rep(1, nrow(X)),
    beta.init=rep(0, ncol(X)), sigma.init=1, max.parchange=1e-04,
    maxiter=300, progress=TRUE)

## S3 method for class 'latent.regression'
summary(object,...)
```

Arguments

data	An $N \times I$ data frame of dichotomous item responses. If no data frame is supplied, then a user can input the individual likelihood f.yi.qk.
f.yi.qk	An optional matrix which contains the individual likelihood. This matrix is produced by rasch.mml2 or rasch.copula2. The use of this argument allows the estimation of the latent regression model independent of the parameters of the used item response model.
X	An $N \times K$ matrix of K covariates in the latent regression model. Note that the intercept (i.e. a vector of ones) must be included in X.
weights	Student weights (optional).
beta.init	Initial regression coefficients (optional).
sigma.init	Initial residual standard deviation (optional).
b	Item difficulties (optional). They must only be provided if the likelihood f.yi.qk is not given as an input.
a	Item discriminations (optional).
c	Guessing parameter (lower asymptotes) (optional).
d	One minus slipping parameter (upper asymptotes) (optional).
alpha1	Upper tail parameter α_1 in the generalized logistic item response model. Default is 0.
alpha2	Lower tail parameter α_2 parameter in the generalized logistic item response model. Default is 0.
max.parchange	Maximum change in regression parameters
theta.list	Grid of person ability where theta is evaluated
maxiter	Maximum number of iterations
progress	An optional logical indicating whether computation progress should be displayed.
y	Individual scores
sig.e	Standard errors for individual scores
object	Object of class latent.regression
...	Further arguments to be passed

Details

In the output *Regression Parameters* the fraction of missing information (fmi) is reported which is the increase of variance in regression parameter estimates because ability is defined as a latent variable. The effective sample size pseudoN.latent corresponds to a sample size when the ability would be available with a reliability of one.

Value

A list with following entries

`iterations`	Number of iterations needed
`maxiter`	Maximal number of iterations
`max.parchange`	Maximum change in parameter estimates
`coef`	Coefficients
`summary.coef`	Summary of regression coefficients
`sigma`	Estimate of residual standard deviation
`vcov.simple`	Covariance parameters of estimated parameters (simplified version)
`vcov.latent`	Covariance parameters of estimated parameters which accounts for latent ability
`post`	Individual posterior distribution
`EAP`	Individual EAP estimates
`SE.EAP`	Standard error estimates of EAP
`explvar`	Explained variance in latent regression
`totalvar`	Total variance in latent regression
`rsquared`	Explained variance R^2 in latent regression

Note

Using the defaults in `a`, `c`, `d`, `alpha1` and `alpha2` corresponds to the Rasch model.

References

Adams, R., & Wu. M. (2007). The mixed-coefficients multinomial logit model: A generalized form of the Rasch model. In M. von Davier & C. H. Carstensen (Eds.). *Multivariate and mixture distribution Rasch models: Extensions and applications* (pp. 57-76). New York: Springer. doi:10.1007/9780387498393_4

Mislevy, R. J. (1991). Randomization-based inference about latent variables from complex samples. *Psychometrika, 56*(2), 177-196. doi:10.1007/BF02294457

Stukel, T. A. (1988). Generalized logistic models. *Journal of the American Statistical Association, 83*(402), 426-431. doi:10.1080/01621459.1988.10478613

See Also

See also `plausible.value.imputation.raschtype` for plausible value imputation of generalized logistic item type models.

Examples

```
#############################################################################
#  EXAMPLE 1: PISA Reading | Rasch model for dichotomous data
#############################################################################

data(data.pisaRead, package="sirt")
```

```
dat <- data.pisaRead$data
items <- grep("R", colnames(dat))
# define matrix of covariates
X <- cbind( 1, dat[, c("female","hisei","migra" ) ] )

#***
# Model 1: Latent regression model in the Rasch model
# estimate Rasch model
mod1 <- sirt::rasch.mml2( dat[,items] )
# latent regression model
lm1 <- sirt::latent.regression.em.raschtype( data=dat[,items ], X=X, b=mod1$item$b )

## Not run:
#***
# Model 2: Latent regression with generalized link function
# estimate alpha parameters for link function
mod2 <- sirt::rasch.mml2( dat[,items], est.alpha=TRUE)
# use model estimated likelihood for latent regression model
lm2 <- sirt::latent.regression.em.raschtype( f.yi.qk=mod2$f.yi.qk,
            X=X, theta.list=mod2$theta.k)

#***
# Model 3: Latent regression model based on Rasch copula model
testlets <- paste( data.pisaRead$item$testlet)
itemclusters <- match( testlets, unique(testlets) )
# estimate Rasch copula model
mod3 <- sirt::rasch.copula2( dat[,items], itemcluster=itemclusters )
# use model estimated likelihood for latent regression model
lm3 <- sirt::latent.regression.em.raschtype( f.yi.qk=mod3$f.yi.qk,
                X=X, theta.list=mod3$theta.k)

############################################################################
# EXAMPLE 2: Simulated data according to the Rasch model
############################################################################

set.seed(899)
I <- 21     # number of items
b <- seq(-2,2, len=I)   # item difficulties
n <- 2000       # number of students

# simulate theta and covariates
theta <- stats::rnorm( n )
x <- .7 * theta + stats::rnorm( n, .5 )
y <- .2 * x+ .3*theta + stats::rnorm( n, .4 )
dfr <- data.frame( theta, 1, x, y )

# simulate Rasch model
dat1 <- sirt::sim.raschtype( theta=theta, b=b )

# estimate latent regression
mod <- sirt::latent.regression.em.raschtype( data=dat1, X=dfr[,-1], b=b )
  ## Regression Parameters
  ##
```

```
  ##        est se.simple     se        t p   beta    fmi N.simple pseudoN.latent
  ## X1 -0.2554    0.0208 0.0248 -10.2853 0 0.0000 0.2972     2000       1411.322
  ## x   0.4113    0.0161 0.0193  21.3037 0 0.4956 0.3052     2000       1411.322
  ## y   0.1715    0.0179 0.0213   8.0438 0 0.1860 0.2972     2000       1411.322
  ##
  ## Residual Variance=0.685
  ## Explained Variance=0.3639
  ## Total Variance=1.049
  ##                 R2=0.3469

# compare with linear model (based on true scores)
summary( stats::lm( theta  ~ x + y, data=dfr ) )
  ## Coefficients:
  ##             Estimate Std. Error t value Pr(>|t|)
  ## (Intercept) -0.27821    0.01984  -14.02   <2e-16 ***
  ## x            0.40747    0.01534   26.56   <2e-16 ***
  ## y            0.18189    0.01704   10.67   <2e-16 ***
  ## ---
  ##
  ## Residual standard error: 0.789 on 1997 degrees of freedom
  ## Multiple R-squared: 0.3713,     Adjusted R-squared: 0.3707

#***********
# define guessing parameters (lower asymptotes) and
# upper asymptotes ( 1 minus slipping parameters)
cI <- rep(.2, I)        # all items get a guessing parameter of .2
cI[ c(7,9) ] <- .25     # 7th and 9th get a guessing parameter of .25
dI <- rep( .95, I )    # upper asymptote of .95
dI[ c(7,11) ] <- 1        # 7th and 9th item have an asymptote of 1

# latent regression model
mod1 <- sirt::latent.regression.em.raschtype( data=dat1, X=dfr[,-1],
           b=b, c=cI, d=dI    )
  ## Regression Parameters
  ##
  ##        est se.simple     se        t p   beta    fmi N.simple pseudoN.latent
  ## X1 -0.7929    0.0243 0.0315 -25.1818 0 0.0000 0.4044     2000       1247.306
  ## x   0.5025    0.0188 0.0241  20.8273 0 0.5093 0.3936     2000       1247.306
  ## y   0.2149    0.0209 0.0266   8.0850 0 0.1960 0.3831     2000       1247.306
  ##
  ## Residual Variance=0.9338
  ## Explained Variance=0.5487
  ## Total Variance=1.4825
  ##                 R2=0.3701

#############################################################################
# EXAMPLE 3: Measurement error in dependent variable
#############################################################################

set.seed(8766)
N <- 4000       # number of persons
X <- stats::rnorm(N)           # independent variable
Z <- stats::rnorm(N)           # independent variable
```

```
y <- .45 * X + .25 * Z + stats::rnorm(N)   # dependent variable true score
sig.e <- stats::runif( N, .5, .6 )       # measurement error standard deviation
yast <- y + stats::rnorm( N, sd=sig.e ) # dependent variable measured with error

#****
# Model 1: Estimation with latent.regression.em.raschtype using
#          individual likelihood
# define theta grid for evaluation of density
theta.list <- mean(yast) + stats::sd(yast) * seq( -5, 5, length=21)
# compute individual likelihood
f.yi.qk <- stats::dnorm( outer( yast, theta.list, "-" ) / sig.e )
f.yi.qk <- f.yi.qk / rowSums(f.yi.qk)
# define predictor matrix
X1 <- as.matrix(data.frame( "intercept"=1, "X"=X, "Z"=Z ))

# latent regression model
res <- sirt::latent.regression.em.raschtype( f.yi.qk=f.yi.qk,
                    X=X1, theta.list=theta.list)
  ##   Regression Parameters
  ##
  ##              est se.simple     se      t      p   beta    fmi N.simple pseudoN.latent
  ##   intercept 0.0112    0.0157 0.0180  0.6225 0.5336 0.0000 0.2345    4000      3061.998
  ##   X        0.4275    0.0157 0.0180 23.7926 0.0000 0.3868 0.2350    4000      3061.998
  ##   Z        0.2314    0.0156 0.0178 12.9868 0.0000 0.2111 0.2349    4000      3061.998
  ##
  ##   Residual Variance=0.9877
  ##   Explained Variance=0.2343
  ##   Total Variance=1.222
  ##                   R2=0.1917

#****
# Model 2: Estimation with latent.regression.em.normal
res2 <- sirt::latent.regression.em.normal( y=yast, sig.e=sig.e, X=X1)
  ##   Regression Parameters
  ##
  ##              est se.simple     se      t      p   beta    fmi N.simple pseudoN.latent
  ##   intercept 0.0112    0.0157 0.0180  0.6225 0.5336 0.0000 0.2345    4000      3062.041
  ##   X        0.4275    0.0157 0.0180 23.7927 0.0000 0.3868 0.2350    4000      3062.041
  ##   Z        0.2314    0.0156 0.0178 12.9870 0.0000 0.2111 0.2349    4000      3062.041
  ##
  ##   Residual Variance=0.9877
  ##   Explained Variance=0.2343
  ##   Total Variance=1.222
  ##                   R2=0.1917

  ## -> Results between Model 1 and Model 2 are identical because they use
  ##    the same input.

#***
# Model 3: Regression model based on true scores y
mod3 <- stats::lm( y ~ X + Z )
summary(mod3)
  ##   Coefficients:
```

```
  ##               Estimate Std. Error t value Pr(>|t|)
  ##   (Intercept)  0.02364    0.01569   1.506    0.132
  ##   X            0.42401    0.01570  27.016   <2e-16 ***
  ##   Z            0.23804    0.01556  15.294   <2e-16 ***
  ##   Residual standard error: 0.9925 on 3997 degrees of freedom
  ##   Multiple R-squared:  0.1923,    Adjusted R-squared:  0.1919
  ##   F-statistic: 475.9 on 2 and 3997 DF,  p-value: < 2.2e-16

#***
# Model 4: Regression model based on observed scores yast
mod4 <- stats::lm( yast ~ X + Z )
summary(mod4)
  ##   Coefficients:
  ##               Estimate Std. Error t value Pr(>|t|)
  ##   (Intercept)  0.01101    0.01797   0.613     0.54
  ##   X            0.42716    0.01797  23.764   <2e-16 ***
  ##   Z            0.23174    0.01783  13.001   <2e-16 ***
  ##   Residual standard error: 1.137 on 3997 degrees of freedom
  ##   Multiple R-squared:  0.1535,    Adjusted R-squared:  0.1531
  ##   F-statistic: 362.4 on 2 and 3997 DF,  p-value: < 2.2e-16

## End(Not run)
```

`lavaan2mirt` *Converting a* `lavaan` *Model into a* `mirt` *Model*

Description

Converts a `lavaan` model into a `mirt` model. Optionally, the model can be estimated with the `mirt::mirt` function (`est.mirt=TRUE`) or just `mirt` syntax is generated (`est.mirt=FALSE`).

Extensions of the `lavaan` syntax include guessing and slipping parameters (operators `?=g1` and `?=s1`) and a shortage operator for item groups (see `__`). See `TAM::lavaanify.IRT` for more details.

Usage

```
lavaan2mirt(dat, lavmodel, est.mirt=TRUE, poly.itemtype="gpcm", ...)
```

Arguments

`dat`	Dataset with item responses
`lavmodel`	Model specified in `lavaan` syntax (see `lavaan::lavaanify`)
`est.mirt`	An optional logical indicating whether the model should be estimated with `mirt::mirt`
`poly.itemtype`	Item type for polytomous data. This can be `gpcm` for the generalized partial credit model or `graded` for the graded response model.
`...`	Further arguments to be passed for estimation in `mirt`

Details

This function uses the `lavaan::lavaanify` (**lavaan**) function.

Only single group models are supported (for now).

Value

A list with following entries

`mirt`	Object generated by `mirt` function if `est.mirt=TRUE`
`mirt.model`	Generated `mirt` model
`mirt.syntax`	Generated `mirt` syntax
`mirt.pars`	Generated parameter specifications in `mirt`
`lavaan.model`	Used `lavaan` model transformed by `lavaanify` function
`dat`	Used dataset. If necessary, only items used in the model are included in the dataset.

See Also

See https://lavaan.ugent.be/ for **lavaan** resources.

See https://groups.google.com/forum/#!forum/lavaan for discussion about the **lavaan** package.

See `mirt.wrapper` for convenience wrapper functions for `mirt::mirt` objects.

See `TAM::lavaanify.IRT` for extensions of `lavaanify`.

See `tam2mirt` for converting fitted objects in the **TAM** package into fitted `mirt::mirt` objects.

Examples

```
## Not run:
#############################################################################
# EXAMPLE 1: Convert some lavaan syntax to mirt syntax for data.read
#############################################################################

library(mirt)
data(data.read)
dat <- data.read

#******************
#*** Model 1: Single factor model
lavmodel <- "
     # omit item C3
     F=~ A1+A2+A3+A4 + C1+C2+C4 + B1+B2+B3+B4
     F ~~ 1*F
            "

# convert syntax and estimate model
res <- sirt::lavaan2mirt( dat,  lavmodel, verbose=TRUE, technical=list(NCYCLES=3) )
```

```
# inspect coefficients
coef(res$mirt)
mirt.wrapper.coef(res$mirt)
# converted mirt model and parameter table
cat(res$mirt.syntax)
res$mirt.pars

#******************
#*** Model 2: Rasch Model with first six items
lavmodel <- "
     F=~ a*A1+a*A2+a*A3+a*A4+a*B1+a*B2
     F ~~ 1*F
          "
# convert syntax and estimate model
res <- sirt::lavaan2mirt( dat,  lavmodel, est.mirt=FALSE)
# converted mirt model
cat(res$mirt.syntax)
# mirt parameter table
res$mirt.pars
# estimate model using generated objects
res2 <- mirt::mirt( res$dat, res$mirt.model, pars=res$mirt.pars )
mirt.wrapper.coef(res2)     # parameter estimates

#******************
#*** Model 3: Bifactor model
lavmodel <- "
     G=~ A1+A2+A3+A4 + B1+B2+B3+B4  + C1+C2+C3+C4
     A=~ A1+A2+A3+A4
     B=~ B1+B2+B3+B4
     C=~ C1+C2+C3+C4
     G ~~ 1*G
     A ~~ 1*A
     B ~~ 1*B
     C ~~ 1*C
          "
res <- sirt::lavaan2mirt( dat,  lavmodel, est.mirt=FALSE )
# mirt syntax and mirt model
cat(res$mirt.syntax)
res$mirt.model
res$mirt.pars

#******************
#*** Model 4: 3-dimensional model with some parameter constraints
lavmodel <- "
     # some equality constraints among loadings
     A=~ a*A1+a*A2+a2*A3+a2*A4
     B=~ B1+B2+b3*B3+B4
     C=~ c*C1+c*C2+c*C3+c*C4
     # some equality constraints among thresholds
     A1 | da*t1
     A3 | da*t1
     B3 | da*t1
     C3 | dg*t1
```

```
     C4 | dg*t1
     # standardized latent variables
     A ~~ 1*A
     B ~~ 1*B
     C ~~ 1*C
     # estimate Cov(A,B) and Cov(A,C)
     A ~~ B
     A ~~ C
     # estimate mean of B
     B ~ 1
           "
res <- sirt::lavaan2mirt( dat,  lavmodel, verbose=TRUE, technical=list(NCYCLES=3) )
# estimated parameters
mirt.wrapper.coef(res$mirt)
# generated mirt syntax
cat(res$mirt.syntax)
# mirt parameter table
mirt::mod2values(res$mirt)

#******************
#*** Model 5: 3-dimensional model with some parameter constraints and
#             parameter fixings
lavmodel <- "
     A=~ a*A1+a*A2+1.3*A3+A4  # set loading of A3 to 1.3
     B=~ B1+1*B2+b3*B3+B4
     C=~ c*C1+C2+c*C3+C4
     A1 | da*t1
     A3 | da*t1
     C4 | dg*t1
     B1 | 0*t1
     B3 | -1.4*t1   # fix item threshold of B3 to -1.4
     A ~~ 1*A
     B ~~ B         # estimate variance of B freely
     C ~~ 1*C
     A ~~ B         # estimate covariance between A and B
     A ~~ .6 * C    # fix covariance to .6
     A ~ .5*1       # set mean of A to .5
     B ~ 1          # estimate mean of B
           "
res <- sirt::lavaan2mirt( dat,  lavmodel, verbose=TRUE, technical=list(NCYCLES=3) )
mirt.wrapper.coef(res$mirt)

#******************
#*** Model 6: 1-dimensional model with guessing and slipping parameters
#******************

lavmodel <- "
     F=~ c*A1+c*A2+1*A3+1.3*A4 + C1__C4 + a*B1+b*B2+b*B3+B4
     # guessing parameters
     A1+A2 ?=guess1*g1
     A3 ?=.25*g1
     B1+C1 ?=g1
     B2__B4 ?=0.10*g1
```

```
     # slipping parameters
     A1+A2+C3 ?=slip1*s1
     A3 ?=.02*s1
     # fix item intercepts
     A1 | 0*t1
     A2 | -.4*t1
     F ~ 1    # estimate mean of F
     F ~~ 1*F   # fix variance of F
            "
# convert syntax and estimate model
res <- sirt::lavaan2mirt( dat,  lavmodel, verbose=TRUE, technical=list(NCYCLES=3) )
# coefficients
mirt.wrapper.coef(res$mirt)
# converted mirt model
cat(res$mirt.syntax)

#############################################################################
# EXAMPLE 2: Convert some lavaan syntax to mirt syntax for
#            longitudinal data data.long
#############################################################################

data(data.long)
dat <- data.long[,-1]

#******************
#*** Model 1: Rasch model for T1
lavmodel <- "
     F=~ 1*I1T1 +1*I2T1+1*I3T1+1*I4T1+1*I5T1+1*I6T1
     F ~~ F
            "
# convert syntax and estimate model
res <- sirt::lavaan2mirt( dat,  lavmodel, verbose=TRUE, technical=list(NCYCLES=20) )
# inspect coefficients
mirt.wrapper.coef(res$mirt)
# converted mirt model
cat(res$mirt.syntax)

#******************
#*** Model 2: Rasch model for two time points
lavmodel <- "
     F1=~ 1*I1T1 +1*I2T1+1*I3T1+1*I4T1+1*I5T1+1*I6T1
     F2=~ 1*I3T2 +1*I4T2+1*I5T2+1*I6T2+1*I7T2+1*I8T2
     F1 ~~ F1
     F1 ~~ F2
     F2 ~~ F2
     # equal item difficulties of same items
     I3T1 | i3*t1
     I3T2 | i3*t1
     I4T1 | i4*t1
     I4T2 | i4*t1
     I5T1 | i5*t1
     I5T2 | i5*t1
     I6T1 | i6*t1
```

```
      I6T2 | i6*t1
      # estimate mean of F1, but fix mean of F2
      F1 ~ 1
      F2 ~ 0*1
            "
# convert syntax and estimate model
res <- sirt::lavaan2mirt( dat,  lavmodel, verbose=TRUE, technical=list(NCYCLES=20) )
# inspect coefficients
mirt.wrapper.coef(res$mirt)
# converted mirt model
cat(res$mirt.syntax)

#-- compare estimation with smirt function
# define Q-matrix
I <- ncol(dat)
Q <- matrix(0,I,2)
Q[1:6,1] <- 1
Q[7:12,2] <- 1
rownames(Q) <- colnames(dat)
colnames(Q) <- c("T1","T2")
# vector with same items
itemnr <- as.numeric( substring( colnames(dat),2,2) )
# fix mean at T2 to zero
mu.fixed <- cbind( 2,0 )
# estimate model in smirt
mod1 <- sirt::smirt(dat, Qmatrix=Q, irtmodel="comp", est.b=itemnr, mu.fixed=mu.fixed )
summary(mod1)

############################################################################
# EXAMPLE 3: Converting lavaan syntax for polytomous data
############################################################################

data(data.big5)
# select some items
items <- c( grep( "O", colnames(data.big5), value=TRUE )[1:6],
            grep( "N", colnames(data.big5), value=TRUE )[1:4] )
#  O3  O8  O13 O18 O23 O28 N1  N6  N11 N16
dat <- data.big5[, items ]
library(psych)
psych::describe(dat)

#******************
#*** Model 1: Partial credit model
lavmodel <- "
      O=~ 1*O3+1*O8+1*O13+1*O18+1*O23+1*O28
      O ~~ O
         "
# estimate model in mirt
res <- sirt::lavaan2mirt( dat, lavmodel, technical=list(NCYCLES=20), verbose=TRUE)
# estimated mirt model
mres <- res$mirt
# mirt syntax
cat(res$mirt.syntax)
```

```
  ##   O=1,2,3,4,5,6
  ##   COV=O*O
# estimated parameters
mirt.wrapper.coef(mres)
# some plots
mirt::itemplot( mres, 3 )   # third item
plot(mres)   # item information
plot(mres,type="trace")  # item category functions

# graded response model with equal slopes
res1 <- sirt::lavaan2mirt( dat, lavmodel, poly.itemtype="graded", technical=list(NCYCLES=20),
              verbose=TRUE )
mirt.wrapper.coef(res1$mirt)

#******************
#*** Model 2: Generalized partial credit model with some constraints
lavmodel <- "
      O=~ O3+O8+O13+a*O18+a*O23+1.2*O28
      O ~ 1   # estimate mean
      O ~~ O  # estimate variance
      # some constraints among thresholds
      O3  | d1*t1
      O13 | d1*t1
      O3  | d2*t2
      O8  | d3*t2
      O28 | (-0.5)*t1
         "
# estimate model in mirt
res <- sirt::lavaan2mirt( dat, lavmodel, technical=list(NCYCLES=5), verbose=TRUE)
# estimated mirt model
mres <- res$mirt
# estimated parameters
mirt.wrapper.coef(mres)

#*** generate syntax for mirt for this model and estimate it in mirt package
# Items: O3  O8  O13 O18 O23 O28
mirtmodel <- mirt::mirt.model( "
             O=1-6
             # a(O18)=a(O23), t1(O3)=t1(O18), t2(O3)=t2(O8)
             CONSTRAIN=(4,5,a1), (1,3,d1), (1,2,d2)
             MEAN=O
             COV=O*O
               ")
# initial table of parameters in mirt
mirt.pars <- mirt::mirt( dat[,1:6], mirtmodel, itemtype="gpcm", pars="values")
# fix slope of item O28 to 1.2
ind <- which( ( mirt.pars$item=="O28" ) & ( mirt.pars$name=="a1") )
mirt.pars[ ind, "est"] <- FALSE
mirt.pars[ ind, "value"] <- 1.2
# fix d1 of item O28 to -0.5
ind <- which( ( mirt.pars$item=="O28" ) & ( mirt.pars$name=="d1") )
mirt.pars[ ind, "est"] <- FALSE
mirt.pars[ ind, "value"] <- -0.5
```

```
# estimate model
res2 <- mirt::mirt( dat[,1:6], mirtmodel, pars=mirt.pars,
             verbose=TRUE, technical=list(NCYCLES=4) )
mirt.wrapper.coef(res2)
plot(res2, type="trace")

## End(Not run)
```

`lc.2raters` *Latent Class Model for Two Exchangeable Raters and One Item*

Description

This function computes a latent class model for ratings on an item based on exchangeable raters (Uebersax & Grove, 1990). Additionally, several measures of rater agreement are computed (see e.g. Gwet, 2010).

Usage

```
lc.2raters(data, conv=0.001, maxiter=1000, progress=TRUE)

## S3 method for class 'lc.2raters'
summary(object,...)
```

Arguments

`data`	Data frame with item responses (must be ordered from 0 to K) and two columns which correspond to ratings of two (exchangeable) raters.
`conv`	Convergence criterion
`maxiter`	Maximum number of iterations
`progress`	An optional logical indicating whether iteration progress should be displayed.
`object`	Object of class `lc.2raters`
`...`	Further arguments to be passed

Details

For two exchangeable raters which provide ratings on an item, a latent class model with $K+1$ classes (if there are $K+1$ item categories $0, ..., K$) is defined. Where $P(X=x, Y=y|c)$ denotes the probability that the first rating is x and the second rating is y given the true but unknown item category (class) c. Ratings are assumed to be locally independent, i.e.

$$P(X=x, Y=y|c) = P(X=x|c) \cdot P(Y=y|c) = p_{x|c} \cdot p_{y|c}$$

Note that $P(X=x|c) = P(Y=x|c) = p_{x|c}$ holds due to the exchangeability of raters. The latent class model estimates true class proportions π_c and conditional item probabilities $p_{x|c}$.

Value

A list with following entries

`classprob.1rater.like`
: Classification probability $P(c|x)$ of latent category c given a manifest rating x (estimated by maximum likelihood)

`classprob.1rater.post`
: Classification probability $P(c|x)$ of latent category c given a manifest rating x (estimated by the posterior distribution)

`classprob.2rater.like`
: Classification probability $P(c|(x,y))$ of latent category c given two manifest ratings x and y (estimated by maximum likelihood)

`classprob.2rater.post`
: Classification probability $P(c|(x,y))$ of latent category c given two manifest ratings x and y (estimated by posterior distribution)

`f.yi.qk`
: Likelihood of each pair of ratings

`f.qk.yi`
: Posterior of each pair of ratings

`probs`
: Item response probabilities $p_{x|c}$

`pi.k`
: Estimated class proportions π_c

`pi.k.obs`
: Observed manifest class proportions

`freq.long`
: Frequency table of ratings in long format

`freq.table`
: Symmetrized frequency table of ratings

`agree.stats`
: Measures of rater agreement. These measures include percentage agreement (`agree0`, `agree1`), Cohen's kappa and weighted Cohen's kappa (`kappa`, `wtd.kappa.linear`), Gwet's AC1 agreement measures (`AC1`; Gwet, 2008, 2010) and Aickin's alpha (`alpha.aickin`; Aickin, 1990).

`data`
: Used dataset

`N.categ`
: Number of categories

References

Aickin, M. (1990). Maximum likelihood estimation of agreement in the constant predictive probability model, and its relation to Cohen's kappa. *Biometrics, 46*, 293-302.

Gwet, K. L. (2008). Computing inter-rater reliability and its variance in the presence of high agreement. *British Journal of Mathematical and Statistical Psychology, 61*, 29-48.

Gwet, K. L. (2010). *Handbook of Inter-Rater Reliability*. Advanced Analytics, Gaithersburg. *http://www.agreestat.com/*

Uebersax, J. S., & Grove, W. M. (1990). Latent class analysis of diagnostic agreement. *Statistics in Medicine, 9*, 559-572.

See Also

See also `rm.facets` and `rm.sdt` for specifying rater models.

See also the **irr** package for measures of rater agreement.

Examples

```
#############################################################################
# EXAMPLE 1: Latent class models for rating datasets data.si05
#############################################################################

data(data.si05)

#*** Model 1: one item with two categories
mod1 <- sirt::lc.2raters( data.si05$Ex1)
summary(mod1)

#*** Model 2: one item with five categories
mod2 <- sirt::lc.2raters( data.si05$Ex2)
summary(mod2)

#*** Model 3: one item with eight categories
mod3 <- sirt::lc.2raters( data.si05$Ex3)
summary(mod3)
```

---

likelihood.adjustment *Adjustment and Approximation of Individual Likelihood Functions*

Description

Approximates individual likelihood functions $L(\boldsymbol{X}_p|\theta)$ by normal distributions (see Mislevy, 1990). Extreme response patterns are handled by adding pseudo-observations of items with extreme item difficulties (see argument `extreme.item`. The individual standard deviations of the likelihood, used in the normal approximation, can be modified by individual adjustment factors which are specified in `adjfac`. In addition, a reliability of the adjusted likelihood can be specified in `target.EAP.rel`.

Usage

```
likelihood.adjustment(likelihood, theta=NULL, prob.theta=NULL,
     adjfac=rep(1, nrow(likelihood)), extreme.item=5, target.EAP.rel=NULL,
     min_tuning=0.2, max_tuning=3, maxiter=100, conv=1e-04,
     trait.normal=TRUE)
```

Arguments

`likelihood`	A matrix containing the individual likelihood $L(\boldsymbol{X}_p|\theta)$ or an object of class `IRT.likelihood`.
`theta`	Optional vector of (unidimensional) θ values
`prob.theta`	Optional vector of probabilities of θ trait distribution
`adjfac`	Vector with individual adjustment factors of the standard deviations of the likelihood
`extreme.item`	Item difficulties of two extreme pseudo items which are added as additional observed data to the likelihood. A large number (e.g. `extreme.item=15`) leaves the likelihood almost unaffected. See also Mislevy (1990).

target.EAP.rel	Target EAP reliability. An additional tuning parameter is estimated which adjusts the likelihood to obtain a pre-specified reliability.
min_tuning	Minimum value of tuning parameter (if ! is.null(target.EAP.rel))
max_tuning	Maximum value of tuning parameter (if ! is.null(target.EAP.rel))
maxiter	Maximum number of iterations (if ! is.null(target.EAP.rel))
conv	Convergence criterion (if ! is.null(target.EAP.rel))
trait.normal	Optional logical indicating whether the trait distribution should be normally distributed (if ! is.null(target.EAP.rel)).

Value

Object of class IRT.likelihood.

References

Mislevy, R. (1990). Scaling procedures. In E. Johnson & R. Zwick (Eds.), *Focusing the new design: The NAEP 1988 technical report* (ETS RR 19-20). Princeton, NJ: Educational Testing Service.

See Also

CDM::IRT.likelihood, TAM::tam.latreg

Examples

```
## Not run:
#############################################################################
# EXAMPLE 1: Adjustment of the likelihood | data.read
#############################################################################

library(CDM)
library(TAM)
data(data.read)
dat <- data.read

# define theta grid
theta.k <- seq(-6,6,len=41)

#*** Model 1: fit Rasch model in TAM
mod1 <- TAM::tam.mml( dat, control=list( nodes=theta.k) )
summary(mod1)

#*** Model 2: fit Rasch copula model
testlets <- substring( colnames(dat), 1, 1 )
mod2 <- sirt::rasch.copula2( dat, itemcluster=testlets, theta.k=theta.k)
summary(mod2)

# model comparison
IRT.compareModels( mod1, mod2 )

# extract EAP reliabilities
```

```
rel1 <- mod1$EAP.rel
rel2 <- mod2$EAP.Rel
# variance inflation factor
vif <- (1-rel2) / (1-rel1)
  ##  > vif
  ##  [1] 1.211644

# extract individual likelihood
like1 <- IRT.likelihood( mod1 )
# adjust likelihood from Model 1 to obtain a target EAP reliability of .599
like1b <- sirt::likelihood.adjustment( like1, target.EAP.rel=.599 )

# compare estimated latent regressions
lmod1a <- TAM::tam.latreg( like1, Y=NULL )
lmod1b <- TAM::tam.latreg( like1b, Y=NULL )
summary(lmod1a)
summary(lmod1b)

## End(Not run)
```

`linking.haberman` *Linking in the 2PL/Generalized Partial Credit Model*

Description

This function does the linking of several studies which are calibrated using the 2PL or the generalized item response model according to Haberman (2009). This method is a generalization of log-mean-mean linking from one study to several studies. The default `a_log=TRUE` logarithmizes item slopes for linking while otherwise an additive regression model is assumed for the original item loadings (see Details; Battauz, 2017)

Usage

```
linking.haberman(itempars, personpars, estimation="OLS", a_trim=Inf, b_trim=Inf,
    lts_prop=.5, a_log=TRUE, conv=1e-05, maxiter=1000, progress=TRUE,
    adjust_main_effects=TRUE, vcov=TRUE)

## S3 method for class 'linking.haberman'
summary(object, digits=3, file=NULL, ...)

linking.haberman.lq(itempars, pow=2, eps=1e-3, a_log=TRUE, use_nu=FALSE,
      est_pow=FALSE, lower_pow=.1, upper_pow=3, method="joint",
      le=FALSE, vcov_list=NULL)

## S3 method for class 'linking.haberman.lq'
summary(object, digits=3, file=NULL, ...)

## prepare 'itempars' argument for linking.haberman()
```

```
linking_haberman_itempars_prepare(b, a=NULL, wgt=NULL)

## conversion of different parameterizations of item parameters
linking_haberman_itempars_convert(itempars=NULL, lambda=NULL, nu=NULL, a=NULL, b=NULL)

## L0 polish precedure minimizing number of interactions in two-way table
L0_polish(x, tol, conv=0.01, maxiter=30, type=1, verbose=TRUE)
```

Arguments

itempars	A data frame with four or five columns. The first four columns contain in the order: study name, item name, a parameter, b parameter. The fifth column is an optional weight for every item and every study.
personpars	A list with vectors (e.g. EAPs or WLEs) or data frames (e.g. plausible values) containing person parameters which should be transformed. If a data frame in each list entry has se or SE (standard error) in a column name, then the corresponding column is only multiplied by A_t. If a column is labeled as pid (person ID), then it is left untransformed.
estimation	Estimation method. Can be "OLS" (ordinary least squares), "BSQ" (bisquare weighted regression), "HUB" (regression using Huber weights), "MED" (median regression), "LTS" (trimmed least squares), "L1" (median polish), "L0" (minimizing number of interactions)
a_trim	Trimming parameter for item slopes a_{it} in bisquare regression (see Details).
b_trim	Trimming parameter for item slopes b_{it} in bisquare regression (see Details).
lts_prop	Proportion of retained observations in "LTS" regression estimation
a_log	Logical indicating whether item slopes should be logarithmized for linking.
conv	Convergence criterion.
maxiter	Maximum number of iterations.
progress	An optional logical indicating whether computational progress should be displayed.
adjust_main_effects	Logical indicating whether all elements in the vector of main effects should be simultaneously adjusted
vcov	Optional indicating whether covariance matrix for linking errors should be computed
pow	Power q
eps	Epsilon value used in differentiable approximating function
use_nu	Logical indicating whether item intercepts instead of item difficulties are used in linking
est_pow	Logical indicating whether power values should be estimated
lower_pow	Lower bound for estimated power
upper_pow	Upper bound for estimated power

method	Estimation method type: "joint" for joint estimation of distribution and item parameters, while "pw1" and "pw2" indicate pairwise estimation using no weights or weights for item frequencies
le	Logical indicating whether linking and standard errors should be computed
vcov_list	List of variance matrices of item parameters
lambda	Matrix containing item loadings
nu	Matrix containing item intercepts
object	Object of class linking.haberman.
digits	Number of digits after decimals for rounding in summary.
file	Optional file name if summary should be sunk into a file.
...	Further arguments to be passed
b	Matrix of item intercepts (items $times$ studies)
a	Matrix of item slopes
wgt	Matrix of weights
x	Matrix
tol	Tolerance value
type	Can be 1 (using Tukey's median polish) or 2 (alternating median regression).
verbose	Logical indicating whether iteration progress should be displayed

Details

For $t = 1, \ldots, T$ studies, item difficulties b_{it} and item slopes a_{it} are available. For dichotomous responses, these parameters are defined by the 2PL response equation

$$logit P(X_{pi} = 1 | \theta_p) = a_i(\theta_p - b_i)$$

while for polytomous responses the generalized partial credit model holds

$$log \frac{P(X_{pi} = k | \theta_p)}{P(X_{pi} = k - 1 | \theta_p)} = a_i(\theta_p - b_i + d_{ik})$$

The parameters $\{a_{it}, b_{it}\}$ of all items and studies are linearly transformed using equations $a_{it} \approx a_i / A_t$ (if a_log=TRUE) or $a_{it} \approx a_i + A_t$ (if a_log=FALSE) and $b_{it} \cdot A_t \approx B_t + b_i$. For identification reasons, we define $A_1 = 1$ and B_1=0.

The optimization function (which is a least squares criterion; see Haberman, 2009) seeks the transformation parameters A_t and B_t with an alternating least squares method (estimation="OLS"). Note that every item i and every study t can be weighted (specified in the fifth column of itempars). Alternatively, a robust regression method based on bisquare weighting (Fox, 2015) can be employed for linking using the argument estimation="BSQ". For example, in the case of item loadings, bisquare weighting is applied to residuals $e_{it} = a_{it} - a_i - A_t$ (where logarithmized or non-logarithmized item loadings are employed) forming weights $w_{it} = [1 - (e_{it}/k)^2]^2$ for $e_{it} < k$ and 0 for $e_{it} \geq k$ where k is the trimming constant which can be estimated or fixed during estimation using arguments a_trim or b_trim. Items in studies with large residuals (i.e., presence differential item functioning) are effectively set to zero in the linking procedure. Alternatively, Huber

weights (`estimation="HUB"`) downweight large residuals by applying $w_{it} = k/|e_{it}|$ for residuals $|e_{it}| > k$. The method `estimation="LTS"` employs trimmed least squares where the proportion of data retained is specified in `lts_prop` with default set to .50.

The method `estimation="MED"` estimates item parameters and linking constants based on alternating median regression. A similar approach is the median polish procedure of Tukey (Tukey, 1977, p. 362ff.; Maronna, Martin & Yohai, 2006, p. 104; see also `stats::medpolish`) implemented in `estimation="L1"` which aims to minimize $\sum_{i,t} |e_{it}|$. For a pre-specified tolerance value t (in `a_trim` or `b_trim`), the approach `estimation="L0"` minimizes the number of interactions (i.e., DIF effects) in the e_{it} effects. In more detail, it minimizes $\sum_{i,t} \#\{|e_{it}| > t\}$ which is computationally conducted by repeatedly applying the median polish procedure in which one cell is omitted (Davies, 2012; Terbeck & Davies, 1998).

Effect sizes of invariance are calculated as R-squared measures of explained item slopes and intercepts after linking in comparison to item parameters across groups (Asparouhov & Muthen, 2014).

The function *linking.haberman.lq* uses the loss function $\rho(x) = |x|^q$. The originally proposed Haberman linking can be obtained with `pow=2` ($q = 2$). The powers can also be estimated (argument `est_pow=TRUE`).

Value

A list with following entries

`transf.pars`	Data frame with transformation parameters A_t and B_t
`transf.personpars`	Data frame with linear transformation functions for person parameters
`joint.itempars`	Estimated joint item parameters a_i and b_i
`a.trans`	Transformed a_{it} parameters
`b.trans`	Transformed b_{it} parameters
`a.orig`	Original a_{it} parameters
`b.orig`	Original b_{it} parameters
`a.resid`	Residual a_{it} parameters (DIF parameters)
`b.resid`	Residual b_{it} parameters (DIF parameters)
`personpars`	Transformed person parameters
`es.invariance`	Effect size measures of invariance, separately for item slopes and intercepts. In the rows, R^2 and $\sqrt{1-R^2}$ are reported.
`es.robust`	Effect size measures of invariance based on robust estimation (if used).
`selitems`	Indices of items which are present in more than one study.
`vcov`	List containing standard, linking and total errors

References

Asparouhov, T., & Muthen, B. (2014). Multiple-group factor analysis alignment. *Structural Equation Modeling, 21*(4), 1-14. doi:10.1080/10705511.2014.919210

Battauz, M. (2017). Multiple equating of separate IRT calibrations. *Psychometrika, 82*(3), 610-636. doi:10.1007/s113360169517x

Davies, P. L. (2012). Interactions in the analysis of variance. *Journal of the American Statistical Association, 107*(500), 1502-1509. doi:10.1080/01621459.2012.726895

Fox, J. (2015). *Applied regression analysis and generalized linear models*. Thousand Oaks: Sage.

Haberman, S. J. (2009). *Linking parameter estimates derived from an item response model through separate calibrations*. ETS Research Report ETS RR-09-40. Princeton, ETS. doi:10.1002/j.2333-8504.2009.tb02197.x

Kolen, M. J., & Brennan, R. L. (2014). *Test equating, scaling, and linking: Methods and practices*. New York: Springer. doi:10.1007/9781493903177

Magis, D., & De Boeck, P. (2012). A robust outlier approach to prevent type I error inflation in differential item functioning. *Educational and Psychological Measurement, 72*(2), 291-311. doi:10.1177/0013164411416975

Maronna, R. A., Martin, R. D., & Yohai, V. J. (2006). *Robust statistics*. West Sussex: Wiley. doi:10.1002/0470010940

Terbeck, W., & Davies, P. L. (1998). Interactions and outliers in the two-way analysis of variance. *Annals of Statistics, 26*(4), 1279-1305. doi: 10.1214/aos/1024691243

Tukey, J. W. (1977). *Exploratory data analysis*. Addison-Wesley.

Weeks, J. P. (2010). **plink**: An R package for linking mixed-format tests using IRT-based methods. Journal of Statistical Software, 35(12), 1-33. doi:10.18637/jss.v035.i12

See Also

See the **plink** package (Weeks, 2010) for a diversity of linking methods.

Mean-mean linking, Stocking-Lord and Haebara linking (see Kolen & Brennan, 2014, for an overview) in the generalized logistic item response model can be conducted with `equating.rasch`. See also `TAM::tam.linking` in the **TAM** package. Haebara linking and a robustified version of it can be found in `linking.haebara`.

The invariance alignment method employs an optimization function based on pairwise loss functions of item parameters (Asparouhov & Muthen, 2014), see `invariance.alignment`.

Examples

```
#############################################################################
# EXAMPLE 1: Item parameters data.pars1.rasch and data.pars1.2pl
#############################################################################

# Model 1: Linking three studies calibrated by the Rasch model
data(data.pars1.rasch)
mod1 <- sirt::linking.haberman( itempars=data.pars1.rasch )
summary(mod1)

# Model 1b: Linking these studies but weigh these studies by
#     proportion weights 3 : 0.5 : 1 (see below).
#     All weights are the same for each item but they could also
#     be item specific.
itempars <- data.pars1.rasch
itempars$wgt <- 1
itempars[ itempars$study=="study1","wgt"] <- 3
```

```
itempars[ itempars$study=="study2","wgt"] <- .5
mod1b <- sirt::linking.haberman( itempars=itempars )
summary(mod1b)

# Model 2: Linking three studies calibrated by the 2PL model
data(data.pars1.2pl)
mod2 <- sirt::linking.haberman( itempars=data.pars1.2pl )
summary(mod2)

# additive model instead of logarithmic model for item slopes
mod2b <- sirt::linking.haberman( itempars=data.pars1.2pl, a_log=FALSE )
summary(mod2b)

## Not run:
#############################################################################
# EXAMPLE 2: Linking longitudinal data
#############################################################################
data(data.long)

#******
# Model 1: Scaling with the 1PL model

# scaling at T1
dat1 <- data.long[, grep("T1", colnames(data.long) ) ]
resT1 <- sirt::rasch.mml2( dat1 )
itempartable1 <- data.frame( "study"="T1", resT1$item[, c("item", "a", "b" ) ] )
# scaling at T2
dat2 <- data.long[, grep("T2", colnames(data.long) ) ]
resT2 <- sirt::rasch.mml2( dat2 )
summary(resT2)
itempartable2 <- data.frame( "study"="T2", resT2$item[, c("item", "a", "b" ) ] )
itempartable <- rbind( itempartable1, itempartable2 )
itempartable[,2] <- substring( itempartable[,2], 1, 2 )
# estimate linking parameters
mod1 <- sirt::linking.haberman( itempars=itempartable )

#******
# Model 2: Scaling with the 2PL model

# scaling at T1
dat1 <- data.long[, grep("T1", colnames(data.long) ) ]
resT1 <- sirt::rasch.mml2( dat1, est.a=1:6)
itempartable1 <- data.frame( "study"="T1", resT1$item[, c("item", "a", "b" ) ] )

# scaling at T2
dat2 <- data.long[, grep("T2", colnames(data.long) ) ]
resT2 <- sirt::rasch.mml2( dat2, est.a=1:6)
summary(resT2)
itempartable2 <- data.frame( "study"="T2", resT2$item[, c("item", "a", "b" ) ] )
itempartable <- rbind( itempartable1, itempartable2 )
itempartable[,2] <- substring( itempartable[,2], 1, 2 )
# estimate linking parameters
mod2 <- sirt::linking.haberman( itempars=itempartable )
```

```
#############################################################################
# EXAMPLE 3: 2 Studies - 1PL and 2PL linking
#############################################################################
set.seed(789)
I <- 20        # number of items
N <- 2000       # number of persons
# define item parameters
b <- seq( -1.5, 1.5, length=I )
# simulate data
dat1 <- sirt::sim.raschtype( stats::rnorm( N, mean=0,sd=1 ), b=b )
dat2 <- sirt::sim.raschtype( stats::rnorm( N, mean=0.5,sd=1.50 ), b=b )

#*** Model 1: 1PL
# 1PL Study 1
mod1 <- sirt::rasch.mml2( dat1, est.a=rep(1,I) )
summary(mod1)
# 1PL Study 2
mod2 <- sirt::rasch.mml2( dat2, est.a=rep(1,I) )
summary(mod2)

# collect item parameters
dfr1 <- data.frame( "study1", mod1$item$item, mod1$item$a, mod1$item$b )
dfr2 <- data.frame( "study2", mod2$item$item, mod2$item$a, mod2$item$b )
colnames(dfr2) <- colnames(dfr1) <- c("study", "item", "a", "b" )
itempars <- rbind( dfr1, dfr2 )

# Haberman linking
linkhab1 <- sirt::linking.haberman(itempars=itempars)
  ## Transformation parameters (Haberman linking)
  ##    study    At     Bt
  ## 1 study1 1.000  0.000
  ## 2 study2 1.465 -0.512
  ##
  ## Linear transformation for item parameters a and b
  ##    study   A_a   A_b    B_b
  ## 1 study1 1.000 1.000  0.000
  ## 2 study2 0.682 1.465 -0.512
  ##
  ## Linear transformation for person parameters theta
  ##    study A_theta B_theta
  ## 1 study1   1.000   0.000
  ## 2 study2   1.465   0.512
  ##
  ## R-Squared Measures of Invariance
  ##        slopes intercepts
  ## R2          1     0.9979
  ## sqrtU2      0     0.0456

#*** Model 2: 2PL
# 2PL Study 1
mod1 <- sirt::rasch.mml2( dat1, est.a=1:I )
summary(mod1)
```

```
# 2PL Study 2
mod2 <- sirt::rasch.mml2( dat2, est.a=1:I )
summary(mod2)

# collect item parameters
dfr1 <- data.frame( "study1", mod1$item$item, mod1$item$a, mod1$item$b )
dfr2 <- data.frame( "study2", mod2$item$item, mod2$item$a, mod2$item$b )
colnames(dfr2) <- colnames(dfr1) <- c("study", "item", "a", "b" )
itempars <- rbind( dfr1, dfr2 )

# Haberman linking
linkhab2 <- sirt::linking.haberman(itempars=itempars)
  ## Transformation parameters (Haberman linking)
  ##    study    At     Bt
  ## 1 study1 1.000  0.000
  ## 2 study2 1.468 -0.515
  ##
  ## Linear transformation for item parameters a and b
  ##    study   A_a   A_b    B_b
  ## 1 study1 1.000 1.000  0.000
  ## 2 study2 0.681 1.468 -0.515
  ##
  ## Linear transformation for person parameters theta
  ##    study A_theta B_theta
  ## 1 study1   1.000   0.000
  ## 2 study2   1.468   0.515
  ##
  ## R-Squared Measures of Invariance
  ##        slopes intercepts
  ## R2     0.9984     0.9980
  ## sqrtU2 0.0397     0.0443

#############################################################################
# EXAMPLE 4: 3 Studies - 1PL and 2PL linking
#############################################################################
set.seed(789)
I <- 20         # number of items
N <- 1500       # number of persons
# define item parameters
b <- seq( -1.5, 1.5, length=I )
# simulate data
dat1 <- sirt::sim.raschtype( stats::rnorm( N, mean=0, sd=1), b=b )
dat2 <- sirt::sim.raschtype( stats::rnorm( N, mean=0.5, sd=1.50), b=b )
dat3 <- sirt::sim.raschtype( stats::rnorm( N, mean=-0.2, sd=0.8), b=b )
# set some items to non-administered
dat3 <- dat3[, -c(1,4) ]
dat2 <- dat2[, -c(1,2,3) ]

#*** Model 1: 1PL in sirt
# 1PL Study 1
mod1 <- sirt::rasch.mml2( dat1, est.a=rep(1,ncol(dat1)) )
summary(mod1)
# 1PL Study 2
```

```
mod2 <- sirt::rasch.mml2( dat2, est.a=rep(1,ncol(dat2)) )
summary(mod2)
# 1PL Study 3
mod3 <- sirt::rasch.mml2( dat3, est.a=rep(1,ncol(dat3)) )
summary(mod3)

# collect item parameters
dfr1 <- data.frame( "study1", mod1$item$item, mod1$item$a, mod1$item$b )
dfr2 <- data.frame( "study2", mod2$item$item, mod2$item$a, mod2$item$b )
dfr3 <- data.frame( "study3", mod3$item$item, mod3$item$a, mod3$item$b )
colnames(dfr3) <- colnames(dfr2) <- colnames(dfr1) <- c("study", "item", "a", "b" )
itempars <- rbind( dfr1, dfr2, dfr3 )

# use person parameters
personpars <- list( mod1$person[, c("EAP","SE.EAP") ], mod2$person[, c("EAP","SE.EAP") ],
    mod3$person[, c("EAP","SE.EAP") ] )

# Haberman linking
linkhab1 <- sirt::linking.haberman(itempars=itempars, personpars=personpars)
# compare item parameters
round( cbind( linkhab1$joint.itempars[,-1], linkhab1$b.trans )[1:5,], 3 )
  ##            aj     bj study1 study2 study3
  ##   I0001 0.998 -1.427 -1.427     NA     NA
  ##   I0002 0.998 -1.290 -1.324     NA -1.256
  ##   I0003 0.998 -1.140 -1.068     NA -1.212
  ##   I0004 0.998 -0.986 -1.003 -0.969     NA
  ##   I0005 0.998 -0.869 -0.809 -0.872 -0.926

# summary of person parameters of second study
round( psych::describe( linkhab1$personpars[[2]] ), 2 )
  ##   var    n mean   sd median trimmed  mad   min  max range  skew kurtosis
  ## EAP      1 1500 0.45 1.36   0.41    0.47 1.52 -2.61 3.25  5.86 -0.08    -0.62
  ## SE.EAP   2 1500 0.57 0.09   0.53    0.56 0.04  0.49 0.84  0.35  1.47     1.56
  ##          se
  ## EAP    0.04
  ## SE.EAP 0.00

#*** Model 2: 2PL in TAM
library(TAM)
# 2PL Study 1
mod1 <- TAM::tam.mml.2pl( resp=dat1, irtmodel="2PL" )
pvmod1 <- TAM::tam.pv(mod1, ntheta=300, normal.approx=TRUE) # draw plausible values
summary(mod1)
# 2PL Study 2
mod2 <- TAM::tam.mml.2pl( resp=dat2, irtmodel="2PL" )
pvmod2 <- TAM::tam.pv(mod2, ntheta=300, normal.approx=TRUE)
summary(mod2)
# 2PL Study 3
mod3 <- TAM::tam.mml.2pl( resp=dat3, irtmodel="2PL" )
pvmod3 <- TAM::tam.pv(mod3, ntheta=300, normal.approx=TRUE)
summary(mod3)

# collect item parameters
```

```
#!!  Note that in TAM the parametrization is a*theta - b while linking.haberman
#!!  needs the parametrization a*(theta-b)
dfr1 <- data.frame( "study1", mod1$item$item, mod1$B[,2,1], mod1$xsi$xsi / mod1$B[,2,1] )
dfr2 <- data.frame( "study2", mod2$item$item, mod2$B[,2,1], mod2$xsi$xsi / mod2$B[,2,1] )
dfr3 <- data.frame( "study3", mod3$item$item, mod3$B[,2,1], mod3$xsi$xsi / mod3$B[,2,1] )
colnames(dfr3) <- colnames(dfr2) <- colnames(dfr1) <- c("study", "item", "a", "b" )
itempars <- rbind( dfr1, dfr2, dfr3 )

# define list containing person parameters
personpars <- list(  pvmod1$pv[,-1], pvmod2$pv[,-1], pvmod3$pv[,-1] )

# Haberman linking
linkhab2 <- sirt::linking.haberman(itempars=itempars,personpars=personpars)
  ##   Linear transformation for person parameters theta
  ##      study A_theta B_theta
  ##   1 study1   1.000   0.000
  ##   2 study2   1.485   0.465
  ##   3 study3   0.786  -0.192

# extract transformed person parameters
personpars.trans <- linkhab2$personpars

#############################################################################
# EXAMPLE 5: Linking with simulated item parameters containing outliers
#############################################################################

# simulate some parameters
I <- 38
set.seed(18785)
b <- stats::rnorm( I, mean=.3, sd=1.4 )
# simulate DIF effects plus some outliers
bdif <- stats::rnorm(I,mean=.4,sd=.09)+( stats::runif(I)>.9 )* rep( 1*c(-1,1)+.4, each=I/2 )
# create item parameter table
itempars <- data.frame( "study"=paste0("study",rep(1:2, each=I)),
                "item"=paste0( "I", 100 + rep(1:I,2) ), "a"=1,
                 "b"=c( b, b + bdif  )  )

#*** Model 1: Haberman linking with least squares regression
mod1 <- sirt::linking.haberman( itempars=itempars )
summary(mod1)

#*** Model 2: Haberman linking with robust bisquare regression with fixed trimming value
mod2 <- sirt::linking.haberman( itempars=itempars, estimation="BSQ", b_trim=.4)
summary(mod2)

#*** Model 2: Haberman linking with robust bisquare regression with estimated trimming value
mod3 <- sirt::linking.haberman( itempars=itempars, estimation="BSQ")
summary(mod3)

## see also Example 3 of ?sirt::robust.linking

#############################################################################
# EXAMPLE 6: Toy example of Magis and De Boeck (2012)
```

```
#############################################################################

# define item parameters from Magis & De Boeck (20212, p. 293)
b1 <- c(1,1,1,1)
b2 <- c(1,1,1,2)
itempars <- data.frame(study=rep(1:2, each=4), item=rep(1:4,2), a=1, b=c(b1,b2) )

#- Least squares regression
mod1 <- sirt::linking.haberman( itempars=itempars, estimation="OLS")
summary(mod1)

#- Bisquare regression with estimated and fixed trimming factors
mod2 <- sirt::linking.haberman( itempars=itempars, estimation="BSQ")
mod2a <- sirt::linking.haberman( itempars=itempars, estimation="BSQ", b_trim=.4)
mod2b <- sirt::linking.haberman( itempars=itempars, estimation="BSQ", b_trim=1.2)
summary(mod2)
summary(mod2a)
summary(mod2b)

#- Least squares trimmed regression
mod3 <- sirt::linking.haberman( itempars=itempars, estimation="LTS")
summary(mod3)

#- median regression
mod4 <- sirt::linking.haberman( itempars=itempars, estimation="MED")
summary(mod4)

#############################################################################
# EXAMPLE 7: Simulated example with directional DIF
#############################################################################

set.seed(98)
I <- 8
mu <- c(-.5, 0, .5)
b <- sample(seq(-1.5,1.5, len=I))
sd_dif <- 0.001
pars <- outer(b, mu, "+") + stats::rnorm(I*3, sd=sd_dif)
ind <- c(1,2); pars[ind,1] <- pars[ind,1] + c(.5,.5)
ind <- c(3,4); pars[ind,2] <- pars[ind,2] + (-1)*c(.6,.6)
ind <- c(5,6); pars[ind,3] <- pars[ind,3] + (-1)*c(1,1)

# median polish (=stats::medpolish())
tmod1 <- sirt:::L1_polish(x=pars)
# L0 polish with tolerance criterion of .3
tmod2 <- sirt::L0_polish(x=pars, tol=.3)

#- prepare itempars input
itempars <- sirt::linking_haberman_itempars_prepare(b=pars)

#- compare different estimation functions for Haberman linking
mod01 <- sirt::linking.haberman(itempars, estimation="L1")
mod02 <- sirt::linking.haberman(itempars, estimation="L0", b_trim=.3)
mod1 <- sirt::linking.haberman(itempars, estimation="OLS")
```

```
mod2 <- sirt::linking.haberman(itempars, estimation="BSQ")
mod2a <- sirt::linking.haberman(itempars, estimation="BSQ", b_trim=.4)
mod3 <- sirt::linking.haberman(itempars, estimation="MED")
mod4 <- sirt::linking.haberman(itempars, estimation="LTS")
mod5 <- sirt::linking.haberman(itempars, estimation="HUB")
mod01$transf.pars
mod02$transf.pars
mod1$transf.pars
mod2$transf.pars
mod2a$transf.pars
mod3$transf.pars
mod4$transf.pars
mod5$transf.pars

#############################################################################
# EXAMPLE 8: Many studies and directional DIF
#############################################################################

set.seed(98)
I <- 10 # number of items
S <- 7  # number of studies
mu <- round( seq(0, 1, len=S))
b <- sample(seq(-1.5,1.5, len=I))
sd_dif <- 0.001
pars0 <- pars <- outer(b, mu, "+") + stats::rnorm(I*S, sd=sd_dif)

# select n_dif items at random per group and set it to dif or -dif
n_dif <- 2
dif <- .6
for (ss in 1:S){
    ind <- sample( 1:I, n_dif )
    pars[ind,ss] <- pars[ind,ss] + dif*sign( runif(1) - .5 )
}

# check DIF
pars - pars0

#* estimate models
itempars <- sirt::linking_haberman_itempars_prepare(b=pars)
mod0 <- sirt::linking.haberman(itempars, estimation="L0", b_trim=.2)
mod1 <- sirt::linking.haberman(itempars, estimation="OLS")
mod2 <- sirt::linking.haberman(itempars, estimation="BSQ")
mod2a <- sirt::linking.haberman(itempars, estimation="BSQ", b_trim=.4)
mod3 <- sirt::linking.haberman(itempars, estimation="MED")
mod3a <- sirt::linking.haberman(itempars, estimation="L1")
mod4 <- sirt::linking.haberman(itempars, estimation="LTS")
mod5 <- sirt::linking.haberman(itempars, estimation="HUB")
mod0$transf.pars
mod1$transf.pars
mod2$transf.pars
mod2a$transf.pars
mod3$transf.pars
mod3a$transf.pars
```

```
mod4$transf.pars
mod5$transf.pars

#* compare results with Haebara linking
mod11 <- sirt::linking.haebara(itempars, dist="L2")
mod12 <- sirt::linking.haebara(itempars, dist="L1")
summary(mod11)
summary(mod12)

############################################################################
# EXAMPLE 9: Haberman linking for polytomous data
############################################################################

#* attach dataset involving two countries
data(data.timssAusTwn.scored, package="TAM")
dat <- data.timssAusTwn.scored
items <- grep("M0", colnames(dat), value=TRUE)

#* separate scaling with the generalized partial credit model (GPCM)
mod2a <- TAM::tam.mml.2pl( dat[dat$IDCNTRY==36,items], irtmodel="GPCM")
mod2b <- TAM::tam.mml.2pl( dat[dat$IDCNTRY==158,items], irtmodel="GPCM")

#* function for extracting item parameters of the GPCM
extract_gpcm_pars <- function(mod, study)
{
    # extract slope parameter
    a <- mod$B[,2,1]
    # maximum score
    K <- rowSums( 1-is.na( mod$AXsi[,-1] ) )
    # extract xsi
    xsi <- mod$xsi
    a1 <- rep( a, K )
    res <- data.frame( study=study, item=rownames(xsi), a=a1, b=xsi[,1] / a1 )
    return(res)
}

itempars1 <- extract_gpcm_pars(mod=mod2a, study="CNT036")
itempars2 <- extract_gpcm_pars(mod=mod2b, study="CNT158")
itempars <- rbind(itempars1, itempars2)

#* apply Haberman linking
lmod1 <- sirt::linking.haberman(itempars=itempars)
lmod1$transf.personpars

## End(Not run)
```

`linking.haebara` *Haebara Linking of the 2PL Model for Multiple Studies*

Description

The function `linking.haebara` is a generalization of Haebara linking of the 2PL model to multiple groups (or multiple studies; see Battauz, 2017, for a similar approach). The optimization estimates transformation parameters for means and standard deviations of the groups and joint item parameters. The function allows two different distance functions `dist="L2"` and `dist="L1"` where the latter is a robustified version of Haebara linking (see Details; He, Cui, & Osterlind, 2015; He & Cui, 2020; Hu, Rogers, & Vukmirovic, 2008).

Usage

```
linking.haebara(itempars, dist="L2", theta=seq(-4,4, length=61),
       optimizer="optim", center=FALSE, eps=1e-3, par_init=NULL, use_rcpp=TRUE,
        pow=2, use_der=TRUE, ...)

## S3 method for class 'linking.haebara'
summary(object, digits=3, file=NULL, ...)
```

Arguments

`itempars`	A data frame with four or five columns. The first four columns contain in the order: study name, item name, a parameter, b parameter. The fifth column is an optional weight for every item and every study. See `linking.haberman` for a function which uses the same argument.
`dist`	Distance function. Options are `"L2"` for squared loss and `"L1"` for absolute value loss.
`theta`	Grid of theta points for 2PL item response functions
`optimizer`	Name of the optimizer chosen for alignment. Options are `"optim"` (using `stats::optim`) or `"nlminb"` (using `stats::nlminb`).
`center`	Logical indicating whether means and standard deviations should be centered after estimation
`eps`	Small value for smooth approximation of the absolute value function
`par_init`	Optional vector of initial parameter estimates
`use_rcpp`	Logical indicating whether **Rcpp** is used for computation
`pow`	Power for method `dist="Lq"`
`use_der`	Logical indicating whether analytical derivative should be used
`object`	Object of class `linking.haabara`.
`digits`	Number of digits after decimals for rounding in `summary`.
`file`	Optional file name if `summary` should be sunk into a file.
`...`	Further arguments to be passed

Details

For $t = 1, \ldots, T$ studies, item difficulties b_{it} and item slopes a_{it} are available. The 2PL item response functions are given by

$$logit P(X_{pi} = 1 | \theta_p) = a_i(\theta_p - b_i)$$

Haebara linking compares the observed item response functions P_{it} based on the equation for the logits $a_{it}(\theta - b_{it})$ and the expected item response functions P_{it}^* based on the equation for the logits $a_i^* \sigma_t(\theta - (b_i - \mu_t)/\sigma_t)$ where the joint item parameters a_i and b_i and means μ_t and standard deviations σ_t are estimated.

Two loss functions are implemented. The quadratic loss of Haebara linking (`dist="L2"`) minimizes

$$f_{opt,L2} = \sum_t \sum_i \int (P_{it}(\theta) - P_{it}^*(\theta))^2 w(\theta)$$

was originally proposed by Haebara. A robustified version (`dist="L1"`) uses the optimization function (He et al., 2015)

$$f_{opt,L1} = \sum_t \sum_i \int |P_{it}(\theta) - P_{it}^*(\theta)| w(\theta)$$

As a further generalization, the follwing distance function (`dist="Lp"`) can be minimized:

$$f_{opt,Lp} = \sum_t \sum_i \int |P_{it}(\theta) - P_{it}^*(\theta)|^p w(\theta)$$

Value

A list with following entries

`pars`	Estimated means and standard deviations (transformation parameters)
`item`	Estimated joint item parameters
`a.orig`	Original a_{it} parameters
`b.orig`	Original b_{it} parameters
`a.resid`	Residual a_{it} parameters (DIF parameters)
`b.resid`	Residual b_{it} parameters (DIF parameters)
`res_optim`	Value of optimization routine

References

Battauz, M. (2017). Multiple equating of separate IRT calibrations. *Psychometrika, 82*, 610-636. doi:10.1007/s113360169517x

He, Y., Cui, Z., & Osterlind, S. J. (2015). New robust scale transformation methods in the presence of outlying common items. *Applied Psychological Measurement, 39*(8), 613-626. doi:10.1177/0146621615587003

He, Y., & Cui, Z. (2020). Evaluating robust scale transformation methods with multiple outlying common items under IRT true score equating. *Applied Psychological Measurement, 44*(4), 296-310. doi:10.1177/0146621619886050

Hu, H., Rogers, W. T., & Vukmirovic, Z. (2008). Investigation of IRT-based equating methods in the presence of outlier common items. *Applied Psychological Measurement, 32*(4), 311-333. doi:10.1177/0146621606292215

See Also

See invariance.alignment and linking.haberman for alternative linking methods in the **sirt** package. See also TAM::tam.linking in the **TAM** package for more linking functionality and the R packages **plink**, **equateIRT**, **equateMultiple** and **SNSequate**.

Examples

```
## Not run:
#############################################################################
# EXAMPLE 1: Robust linking methods in the presence of outliers
#############################################################################

#** simulate data
I <- 10
a <- seq(.9, 1.1, len=I)
b <- seq(-2, 2, len=I)

#- define item parameters
item_names <- paste0("I",100+1:I)
# th=SIG*TH+MU=> logit(p)=a*(SIG*TH+MU-b)=a*SIG*(TH-(-MU)/SIG-b/SIG)
d1 <- data.frame( study="S1", item=item_names, a=a, b=b )
mu <- .5; sigma <- 1.3
d2 <- data.frame( study="S2", item=item_names, a=a*sigma, b=(b-mu)/sigma )
mu <- -.3; sigma <- .7
d3 <- data.frame( study="S3", item=item_names, a=a*sigma, b=(b-mu)/sigma )

#- define DIF effect
# dif <- 0  # no DIF effects
dif <- 1
d2[4,"a"] <- d2[4,"a"] * (1-.8*dif)
d3[5,"b"] <- d3[5,"b"] - 2*dif
itempars <- rbind(d1, d2, d3)

#* Haebara linking non-robust
mod1 <- sirt::linking.haebara( itempars, dist="L2", control=list(trace=2) )
summary(mod1)

#* Haebara linking robust
mod2 <- sirt::linking.haebara( itempars, dist="L1", control=list(trace=2) )
summary(mod2)

#* using initial parameter estimates
par_init <- mod1$res_optim$par
mod2b <- sirt::linking.haebara( itempars, dist="L1", par_init=par_init)
summary(mod2b)

#* power p=.25
mod2c <- sirt::linking.haebara( itempars, dist="Lp", pow=.25, par_init=par_init)
summary(mod2c)

#* Haberman linking non-robust
mod3 <- sirt::linking.haberman(itempars)
```

```
summary(mod3)

#* Haberman linking robust
mod4 <- sirt::linking.haberman(itempars, estimation="BSQ", a_trim=.25, b_trim=.5)
summary(mod4)

#* compare transformation parameters (means and standard deviations)
mod1$pars
mod2$pars
mod3$transf.personpars
mod4$transf.personpars

## End(Not run)
```

`linking.robust` *Robust Linking of Item Intercepts*

Description

This function implements a robust alternative of mean-mean linking which employs trimmed means instead of means. The linking constant is calculated for varying trimming parameters k. The treatment of differential item functioning as outliers and application of robust statistics is discussed in Magis and De Boeck (2011, 2012).

Usage

```
linking.robust(itempars)

## S3 method for class 'linking.robust'
summary(object,...)

## S3 method for class 'linking.robust'
plot(x, ...)
```

Arguments

`itempars`	Data frame of item parameters (item intercepts). The first column contains the item label, the 2nd and 3rd columns item parameters of two studies.
`object`	Object of class `linking.robust`
`x`	Object of class `linking.robust`
`...`	Further arguments to be passed

Value

A list with following entries

`ind.kopt`	Index for optimal scale parameter

kopt	Optimal scale parameter
meanpars.kopt	Linking constant for optimal scale parameter
se.kopt	Standard error for linking constant obtained with optimal scale parameter
meanpars	Linking constant dependent on the scale parameter
se	Standard error of the linking constant dependent on the scale parameter
sd	DIF standard deviation (non-robust estimate)
mad	DIF standard deviation (robust estimate using the MAD measure)
pars	Original item parameters
k.robust	Used vector of scale parameters
I	Number of items
itempars	Used data frame of item parameters

References

Magis, D., & De Boeck, P. (2011). Identification of differential item functioning in multiple-group settings: A multivariate outlier detection approach. *Multivariate Behavioral Research, 46*(5), 733-755. doi:10.1080/00273171.2011.606757

Magis, D., & De Boeck, P. (2012). A robust outlier approach to prevent type I error inflation in differential item functioning. *Educational and Psychological Measurement, 72*(2), 291-311. doi:10.1177/0013164411416975

See Also

Other functions for linking: linking.haberman, equating.rasch

See also the **plink** package.

Examples

```
#############################################################################
# EXAMPLE 1: Linking data.si03
#############################################################################

data(data.si03)
res1 <- sirt::linking.robust( itempars=data.si03 )
summary(res1)
  ##   Number of items=27
  ##   Optimal trimming parameter k=8 |  non-robust parameter k=0
  ##   Linking constant=-0.0345 |  non-robust estimate=-0.056
  ##   Standard error=0.0186 |  non-robust estimate=0.027
  ##   DIF SD: MAD=0.0771 (robust) | SD=0.1405 (non-robust)
plot(res1)

## Not run:
#############################################################################
# EXAMPLE 2: Linking PISA item parameters data.pisaPars
#############################################################################
```

```
data(data.pisaPars)

# Linking with items
res2 <- sirt::linking.robust( data.pisaPars[, c(1,3,4)] )
summary(res2)
  ##   Optimal trimming parameter k=0 |  non-robust parameter k=0
  ##   Linking constant=-0.0883 |  non-robust estimate=-0.0883
  ##   Standard error=0.0297 |  non-robust estimate=0.0297
  ##   DIF SD: MAD=0.1824 (robust) | SD=0.1487 (non-robust)
##  -> no trimming is necessary for reducing the standard error
plot(res2)

#############################################################################
# EXAMPLE 3: Linking with simulated item parameters containing outliers
#############################################################################

# simulate some parameters
I <- 38
set.seed(18785)
itempars <- data.frame("item"=paste0("I",1:I) )
itempars$study1 <- stats::rnorm( I, mean=.3, sd=1.4 )
# simulate DIF effects plus some outliers
bdif <- stats::rnorm(I,mean=.4,sd=.09)+( stats::runif(I)>.9 )* rep( 1*c(-1,1)+.4, each=I/2 )
itempars$study2 <- itempars$study1 + bdif

# robust linking
res <- sirt::linking.robust( itempars )
summary(res)
  ##   Number of items=38
  ##   Optimal trimming parameter k=12 |  non-robust parameter k=0
  ##   Linking constant=-0.4285 |  non-robust estimate=-0.5727
  ##   Standard error=0.0218 |  non-robust estimate=0.0913
  ##   DIF SD: MAD=0.1186 (robust) | SD=0.5628 (non-robust)
## -> substantial differences of estimated linking constants in this case of
##    deviations from normality of item parameters
plot(res)

## End(Not run)
```

---

linking_2groups *Linking Two Groups*

Description

This function performs (robust) Haebara linking or Stocking-Lord for two groups in the 2PL model. There is also an option for simultaneous estimation in which joint item parameters should also be estimated.

Usage

```
linking_2groups(pars, method, type="asymm", pow=2, eps=0.001, simultan=FALSE,
     Theta=seq(-6, 6, len=101), wgt=NULL, par_init=NULL, optimizer="nlminb",
     control_optimizer=list())
```

Arguments

pars	Matrix containing item parameters that must have columns with names a1, b1, a2, and b2.
method	Linking method. Can be SL (Stocking-Lord) or Hae (Haebara).
type	Type of linking function. Can be "asymm" or "symm" for asymmetric or symmetric linking, respectively.
pow	Power used in the loss function. The values should be larger than or equal than zero. The default values is 2.
eps	Tuning parameter in numerical differentiation
simultan	Logical indicating whether joint item parameters should be simultaneously estimated
Theta	Theta grid
wgt	Weights for theta grid
par_init	Initial vector for parameters
optimizer	Chosen optimizer. Can be "nlminb" or "optim".
control_optimizer	Control arguments for optimizer

Value

List with following entries

par	Estimated linking parameters
$...$	More values

Examples

```
## Not run:
#############################################################################
# EXAMPLE 1: data.ex16 from TAM package
#############################################################################

#- extract dataset
data(data.ex16, package="TAM")
dat <- data.ex16
items <- colnames(dat)[-c(1,2)]

# fit grade 1
rdat1 <- TAM::tam_remove_missings( dat[ dat$grade==1, ], items=items )
mod1 <- sirt::rasch.mml2( dat=rdat1$resp[, rdat1$items], est.a=1:length(rdat1$items) )
```

```
# fit grade 2
rdat2 <- TAM::tam_remove_missings( dat[ dat$grade==2, ], items=items )
mod2 <- sirt::rasch.mml2( dat=rdat2$resp[, rdat2$items], est.a=1:length(rdat2$items) )

# merge item parameters of separate scalings
item1 <- mod1$item[, c("item", "a","b") ]
colnames(item1)[2:3] <- c("a1","b1")
item2 <- mod2$item[, c("item", "a","b") ]
colnames(item2)[2:3] <- c("a2","b2")
pars <- merge(x=item1, y=item2, by="item")

# choose theta grid
Theta <- seq(-6,6, len=101)
wgt <- sirt::sirt_dnorm_discrete(x=Theta, mean=0, sd=2)

#- robust Haebara linking with powers 0.5 or 0 and different types
res1 <- sirt::linking_2groups(pars=pars, method="Hae", type="asymm",
              Theta=Theta, wgt=wgt, pow=0.5, eps=0.001 )
res2 <- sirt::linking_2groups(pars=pars, method="Hae", type="symm",
              Theta=Theta, wgt=wgt, pow=0, eps=0.01 )
res1$par  # linking parameter estimate
res2$par

## End(Not run)
```

`locpolycor` *Local Modeling of Thresholds and Polychoric Correlations*

Description

Estimates thresholds and polychoric correlations as a function of a continuous moderator variable x.

Usage

```
locpolycor(y, data.mod, moderator.grid, h=1.1, model_thresh, model_polycor,
     sampling_weights=NULL, kernel="gaussian", eps=1e-10)
```

Arguments

`y`	Matrix with columns referrring to ordinal items
`data.mod`	Values of the moderator variable x
`moderator.grid`	Grid of x values to be used for local estimation of thresholds and polychoric correlations
`h`	Bandwidth factor
`model_thresh`	Model for thresholds: can be `'const'` (constant function) or `'lin'` (linear function)

model_polycor	Model for polychoric correlations: can be 'const' (constant function) or 'lin' (linear function)
sampling_weights	Optional vector of sampling weights
kernel	Used kernel function, see lsem_local_weights
eps	Parameter added in likelihood optimization

Value

A list with entries

thresh_list	Threshold parameters
thresh_stat	Estimated thresholds
polycor_stat	Estimated polychoric correlations
...	...

Examples

```
## Not run:
#############################################################################
# EXAMPLE 1: Two items, moderator on (0,1)
#############################################################################


#*** simulate data

# functions for thresholds
th1_fun <- function(x){ -0.3*(x-2)^2 + .2 }
th2_fun <- function(x){ 0.4*(x+1)^2 - 0.6 }
zh1_fun <- function(x){ 0.3*(x-1) }
# function polychoric correlation
cor_x12 <- function(x){ 0.2+0.1*(x-0.5)+0.09*(x-0.5)^2 }

# simulate moderator
x <- stats::runif(N)

# simulate data
yast <- matrix( NA, nrow=N, ncol=2)
for (nn in 1:N){
    rho12 <- cor_x12(x[nn])
    Sigma <- matrix(0, 2,2)
    Sigma[1,2] <- rho12
    Sigma <- Sigma + t(Sigma)
    diag(Sigma) <- 1
    yast_nn <- MASS::mvrnorm( 1, mu=rep(0,2), Sigma=Sigma )
    yast[nn,] <- yast_nn
}
y <- 0*yast
th1_x <- th1_fun(x)
th2_x <- th2_fun(x)
```

```
zh1_x <- zh1_fun(x)
y[,1] <- 1*( yast[,1] > th1_x ) + 1*( yast[,1] > th2_x )
y[,2] <- 1*( yast[,2] > zh1_x )
colnames(y) <- paste0("I",1:ncol(y))

dat <- data.frame(x=x, y)

#-- local modeling
res <- sirt::locpolycor(y, data.mod=x, moderator.grid=c(0, .25, .5, .75, 1 ), h=2,
                model_thresh="lin", model_polycor="lin")
str(res)

## End(Not run)
```

`lq_fit` *Fit of a L_q Regression Model*

Description

Fits a regression model in the L_q norm (also labeled as the L_p norm). In more detail, the optimization function $\sum_i |y_i - x_i\beta|^p$ is optimized. The nondifferentiable function is approximated by a differentiable approximation, i.e., we use $|x| \approx \sqrt{x^2 + \varepsilon}$. The power p can also be estimated by using `est_pow=TRUE`, see Giacalone, Panarello and Mattera (2018). The algorithm iterates between estimating regression coefficients and the estimation of power values. The estimation of the power based on a vector of residuals `e` can be conducted using the function `lq_fit_estimate_power`.

Using the L_q norm in the regression is equivalent to assuming an expontial power function for residuals (Giacalone et al., 2018). The density function and a simulation function is provided by `dexppow` and `rexppow`, respectively. See also the **normalp** package.

Usage

```
lq_fit(y, X, w=NULL, pow=2, eps=0.001, beta_init=NULL, est_pow=FALSE, optimizer="optim",
   eps_vec=10^seq(0,-10, by=-.5), conv=1e-4, miter=20, lower_pow=.1, upper_pow=5)

lq_fit_estimate_power(e, pow_init=2, lower_pow=.1, upper_pow=10)

dexppow(x, mu=0, sigmap=1, pow=2, log=FALSE)

rexppow(n, mu=0, sigmap=1, pow=2, xbound=100, xdiff=.01)
```

Arguments

`y`	Dependent variable
`X`	Design matrix
`w`	Optional vector of weights
`pow`	Power p in L_q norm- The power $p = 0$ is handled using the loss function $f(e) = e^2/(e^2 + \varepsilon)$.

est_pow	Logical indicating whether power should be estimated
eps	Parameter governing the differentiable approximation
e	Vector of resiuals
pow_init	Initial value of power
beta_init	Initial vector
optimizer	Can be "optim" or "nlminb".
eps_vec	Vector with decreasing ε values used in optimization
conv	Convergence criterion
miter	Maximum number of iterations
lower_pow	Lower bound for estimated power
upper_pow	Upper bound for estimated power
x	Vector
mu	Location parameter
sigmap	Scale parameter
log	Logical indicating whether the logarithm should be provided
n	Sample size
xbound	Lower and upper bound for density approximation
xdiff	Grid width for density approximation

Value

List with following several entries

coefficients	Vector of coefficients
res_optim	Results of optimization
...	More values

References

Giacalone, M., Panarello, D., & Mattera, R. (2018). Multicollinearity in regression: an efficiency comparison between L_p-norm and least squares estimators. *Quality & Quantity, 52*(4), 1831-1859. doi:10.1007/s111350170571y

Examples

```
#############################################################################
# EXAMPLE 1: Small simulated example with fixed power
#############################################################################

set.seed(98)
N <- 300
x1 <- stats::rnorm(N)
x2 <- stats::rnorm(N)
par1 <- c(1,.5,-.7)
```

```
y <- par1[1]+par1[2]*x1+par1[3]*x2 + stats::rnorm(N)
X <- cbind(1,x1,x2)

#- lm function in stats
mod1 <- stats::lm.fit(y=y, x=X)

#- use lq_fit function
mod2 <- sirt::lq_fit( y=y, X=X, pow=2, eps=1e-4)
mod1$coefficients
mod2$coefficients

## Not run:
#############################################################################
# EXAMPLE 2: Example with estimated power values
#############################################################################

#*** simulate regression model with residuals from the exponential power distribution
#*** using a power of .30
set.seed(918)
N <- 2000
X <- cbind( 1, c(rep(1,N), rep(0,N)) )
e <- sirt::rexppow(n=2*N, pow=.3, xdiff=.01, xbound=200)
y <- X %*% c(1,.5) + e

#*** estimate model
mod <- sirt::lq_fit( y=y, X=X, est_pow=TRUE, lower_pow=.1)
mod1 <- stats::lm( y ~ 0 + X )
mod$coefficients
mod$pow
mod1$coefficients

## End(Not run)
```

`lsdm` *Least Squares Distance Method of Cognitive Validation*

Description

This function estimates the least squares distance method of cognitive validation (Dimitrov, 2007; Dimitrov & Atanasov, 2012) which assumes a multiplicative relationship of attribute response probabilities to explain item response probabilities. The argument `distance` allows the estimation of a squared loss function (`distance="L2"`) and an absolute value loss function (`distance="L1"`).

The function also estimates the classical linear logistic test model (LLTM; Fischer, 1973) which assumes a linear relationship for item difficulties in the Rasch model.

Usage

```
lsdm(data, Qmatrix, theta=seq(-3,3,by=.5), wgt_theta=rep(1, length(theta)), distance="L2",
  quant.list=c(0.5,0.65,0.8), b=NULL, a=rep(1,nrow(Qmatrix)), c=rep(0,nrow(Qmatrix)) )
```

```
## S3 method for class 'lsdm'
summary(object, file=NULL, digits=3, ...)

## S3 method for class 'lsdm'
plot(x, ...)
```

Arguments

data	An $I \times L$ matrix of dichotomous item responses. The data consists of I item response functions (parametrically or nonparametrically estimated) which are evaluated at a discrete grid of L theta values (person parameters) and are specified in the argument theta.
Qmatrix	An $I \times K$ matrix where the allocation of items to attributes is coded. Values of zero and one and all values between zero and one are permitted. There must not be any items with only zero Q-matrix entries in a row.
theta	The discrete grid points θ where item response functions are evaluated for doing the LSDM method.
wgt_theta	Optional vector for weights of discrete θ points
quant.list	A vector of quantiles where attribute response functions are evaluated.
distance	Type of distance function for minimizing the discrepancy between observed and expected item response functions. Options are "L2" which is the squared distance (proposed in the original LSDM formulation in Dimitrov, 2007) and the absolute value distance "L1" (see Details).
b	An optional vector of item difficulties. If it is specified, then no data input is necessary.
a	An optional vector of item discriminations.
c	An optional vector of guessing parameters.
object	Object of class lsdm
file	Optional file name for summary output
digits	Number of digits aftert decimal in summary
...	Further arguments to be passed
x	Object of class lsdm

Details

The least squares distance method (LSDM; Dimitrov 2007) is based on the assumption that estimated item response functions $P(X_i = 1|\theta)$ can be decomposed in a multiplicative way (in the implemented conjunctive model):

$$P(X_i = 1|\theta) \approx \prod_{k=1}^{K} [P(A_k = 1|\theta)]^{q_{ik}}$$

where $P(A_k = 1|\theta)$ are attribute response functions and q_{ik} are entries of the Q-matrix. Note that the multiplicative form can be rewritten by taking the logarithm

$$\log P(X_i = 1|\theta) \approx \sum_{k=1}^{K} q_{ik} \log[P(A_k = 1|\theta)]$$

The item and attribute response functions are evaluated on a grid of θ values. Using the definitions of matrices $\boldsymbol{L} = \{\log P(X_i = 1)|\theta)\}$, $\boldsymbol{Q} = \{q_{ik}\}$ and $\boldsymbol{X} = \{\log P(A_k = 1|\theta)\}$, the estimation problem can be formulated as $\boldsymbol{L} \approx \boldsymbol{QX}$. Two different loss functions for minimizing the discrepancy between $\boldsymbol{L}$ and $\boldsymbol{QX}$ are implemented. First, the squared loss function computes the weighted difference $||\boldsymbol{L} - \boldsymbol{QX}||_2 = \sum_i (l_i - \sum_t q_{it} x_{it})^2$ (`distance="L2"`) and has been originally proposed by Dimitrov (2007). Second, the absolute value loss function $||\boldsymbol{L} - \boldsymbol{QX}||_1 = \sum_i |l_i - \sum_t q_{it} x_{it}|$ (`distance="L1"`) is more robust to outliers (i.e., items which show misfit to the assumed multiplicative LSDM formulation).

After fitting the attribute response functions, empirical item-attribute discriminations w_{ik} are calculated as the approximation of the following equation

$$\log P(X_i = 1|\theta) = \sum_{k=1}^{K} w_{ik} q_{ik} \log[P(A_k = 1|\theta)]$$

Value

A list with following entries

`mean.mad.lsdm0`	Mean of MAD statistics for LSDM
`mean.mad.lltm`	Mean of MAD statistics for LLTM
`attr.curves`	Estimated attribute response curves evaluated at `theta`
`attr.pars`	Estimated attribute parameters for LSDM and LLTM
`data.fitted`	LSDM-fitted item response functions evaluated at `theta`
`theta`	Grid of ability distributions at which functions are evaluated
`item`	Item statistics (p value, MAD, ...)
`data`	Estimated or fixed item response functions evaluated at `theta`
`Qmatrix`	Used Q-matrix
`lltm`	Model output of LLTM (`lm` values)
`W`	Matrix with empirical item-attribute discriminations

References

Al-Shamrani, A., & Dimitrov, D. M. (2016). Cognitive diagnostic analysis of reading comprehension items: The case of English proficiency assessment in Saudi Arabia. *International Journal of School and Cognitive Psychology, 4*(3). 1000196. http://dx.doi.org/10.4172/2469-9837.1000196

DiBello, L. V., Roussos, L. A., & Stout, W. F. (2007). Review of cognitively diagnostic assessment and a summary of psychometric models. In C. R. Rao and S. Sinharay (Eds.), *Handbook of Statistics*, Vol. 26 (pp. 979-1030). Amsterdam: Elsevier.

Dimitrov, D. M. (2007). Least squares distance method of cognitive validation and analysis for binary items using their item response theory parameters. *Applied Psychological Measurement, 31*, 367-387. http://dx.doi.org/10.1177/0146621606295199

Dimitrov, D. M., & Atanasov, D. V. (2012). Conjunctive and disjunctive extensions of the least squares distance model of cognitive diagnosis. *Educational and Psychological Measurement, 72*, 120-138. http://dx.doi.org/10.1177/0013164411402324

Dimitrov, D. M., Gerganov, E. N., Greenberg, M., & Atanasov, D. V. (2008). *Analysis of cognitive attributes for mathematics items in the framework of Rasch measurement*. AERA 2008, New York.

Fischer, G. H. (1973). The linear logistic test model as an instrument in educational research. *Acta Psychologica, 37*, 359-374. http://dx.doi.org/10.1016/0001-6918(73)90003-6

Sonnleitner, P. (2008). Using the LLTM to evaluate an item-generating system for reading comprehension. *Psychology Science, 50*, 345-362.

See Also

Get a summary of the LSDM analysis with `summary.lsdm`.

See the **CDM** package for the estimation of related cognitive diagnostic models (DiBello, Roussos & Stout, 2007).

Examples

```
#############################################################################
# EXAMPLE 1: Dataset Fischer (see Dimitrov, 2007)
#############################################################################

# item difficulties
b <- c( 0.171,-1.626,-0.729,0.137,0.037,-0.787,-1.322,-0.216,1.802,
    0.476,1.19,-0.768,0.275,-0.846,0.213,0.306,0.796,0.089,
    0.398,-0.887,0.888,0.953,-1.496,0.905,-0.332,-0.435,0.346,
    -0.182,0.906)
# read Q-matrix
Qmatrix <- c( 1,1,0,1,0,0,0,0,1,0,1,0,0,0,0,0,1,0,0,1,0,0,0,0,
    1,0,1,1,0,0,0,0,1,0,0,1,0,0,0,0,0,1,0,0,1,1,0,0,1,0,1,0,1,0,0,0,
    1,0,1,0,1,1,0,0,1,0,1,1,0,1,0,0,1,0,0,1,0,1,0,0,1,0,1,1,1,0,0,0,
    1,0,0,1,0,0,1,0,1,0,0,1,0,0,1,0,1,0,1,0,0,0,1,0,1,1,0,1,0,1,1,0,
    1,0,1,1,0,0,1,0,1,0,0,1,0,0,0,1,1,0,1,1,0,0,0,1,1,0,0,1,0,0,0,1,
    0,1,0,0,0,1,0,1,1,1,0,1,0,1,0,1,1,0,0,1,0,1,0,0,1,1,0,0,1,0,0,0,
    1,0,0,1,1,0,0,0,1,1,0,1,0,0,0,0,1,0,1,1,0,0,0,0,1,0,1,1,0,1,0,0,
    1,1,0,1,0,0,0,0,1,0,1,1,1,1,0,0 )
Qmatrix <- matrix( Qmatrix, nrow=29, byrow=TRUE )
colnames(Qmatrix) <- paste("A",1:8,sep="")
rownames(Qmatrix) <- paste("Item",1:29,sep="")

#* Model 1: perform a LSDM analysis with defaults
mod1 <- sirt::lsdm( b=b, Qmatrix=Qmatrix )
summary(mod1)
plot(mod1)

#* Model 2: different theta values and weights
theta <- seq(-4,4,len=31)
```

```
wgt_theta <- stats::dnorm(theta)
mod2 <- sirt::lsdm( b=b, Qmatrix=Qmatrix, theta=theta, wgt_theta=wgt_theta )
summary(mod2)

#* Model 3: absolute value distance function
mod3 <- sirt::lsdm( b=b, Qmatrix=Qmatrix, distance="L1" )
summary(mod3)

############################################################################
# EXAMPLE 2: Dataset Henning (see Dimitrov, 2007)
############################################################################

# item difficulties
b <- c(-2.03,-1.29,-1.03,-1.58,0.59,-1.65,2.22,-1.46,2.58,-0.66)
# item slopes
a <- c(0.6,0.81,0.75,0.81,0.62,0.75,0.54,0.65,0.75,0.54)
# define Q-matrix
Qmatrix <- c(1,0,0,0,0,0,1,0,0,0,0,1,0,1,0,0,1,0,0,0,0,1,1,0,0,
    0,0,0,1,0,0,1,0,0,1,0,0,0,1,0,0,0,0,1,1,1,0,1,0,0 )
Qmatrix <- matrix( Qmatrix, nrow=10, byrow=TRUE )
colnames(Qmatrix) <- paste("A",1:5,sep="")
rownames(Qmatrix) <- paste("Item",1:10,sep="")

# LSDM analysis
mod <- sirt::lsdm( b=b, a=a, Qmatrix=Qmatrix )
summary(mod)

## Not run:
############################################################################
# EXAMPLE 3: PISA reading (data.pisaRead)
#    using nonparametrically estimated item response functions
############################################################################

data(data.pisaRead)
# response data
dat <- data.pisaRead$data
dat <- dat[, substring( colnames(dat),1,1)=="R" ]
# define Q-matrix
pars <- data.pisaRead$item
Qmatrix <- data.frame(  "A0"=1*(pars$ItemFormat=="MC" ),
                  "A1"=1*(pars$ItemFormat=="CR" ) )

# start with estimating the 1PL in order to get person parameters
mod <- sirt::rasch.mml2( dat )
theta <- sirt::wle.rasch( dat=dat,b=mod$item$b )$theta
# Nonparametric estimation of item response functions
mod2 <- sirt::np.dich( dat=dat, theta=theta, thetagrid=seq(-3,3,len=100) )

# LSDM analysis
lmod <- sirt::lsdm( data=mod2$estimate, Qmatrix=Qmatrix, theta=mod2$thetagrid)
summary(lmod)
plot(lmod)
```

```
#############################################################################
# EXAMPLE 4: Fraction subtraction dataset
#############################################################################

data( data.fraction1, package="CDM")
data <- data.fraction1$data
q.matrix <- data.fraction1$q.matrix

#****
# Model 1: 2PL estimation
mod1 <- sirt::rasch.mml2( data, est.a=1:nrow(q.matrix) )

# LSDM analysis
lmod1 <- sirt::lsdm( b=mod1$item$b, a=mod1$item$a, Qmatrix=q.matrix )
summary(lmod1)

#****
# Model 2: 1PL estimation
mod2 <- sirt::rasch.mml2(data)

# LSDM analysis
lmod2 <- sirt::lsdm( b=mod1$item$b, Qmatrix=q.matrix )
summary(lmod2)

#############################################################################
# EXAMPLE 5: Dataset LLTM Sonnleitner Reading Comprehension (Sonnleitner, 2008)
#############################################################################

# item difficulties Table 7, p. 355 (Sonnleitner, 2008)
b <- c(-1.0189,1.6754,-1.0842,-.4457,-1.9419,-1.1513,2.0871,2.4874,-1.659,-1.197,-1.2437,
    2.1537,.3301,-.5181,-1.3024,-.8248,-.0278,1.3279,2.1454,-1.55,1.4277,.3301)
b <- b[-21] # remove Item 21

# Q-matrix Table 9, p. 357 (Sonnleitner, 2008)
Qmatrix <- scan()
   1 0 0 0 0 0 0 7 4 0 0 0   0 1 0 0 0 0 0 5 1 0 0 0   1 1 0 1 0 0 0 9 1 0 1 0
   1 1 1 0 0 0 0 5 2 0 1 0   1 1 0 0 1 0 0 7 5 1 1 0   1 1 0 0 0 0 0 7 3 0 0 0
   0 1 0 0 0 0 2 6 1 0 0 0   0 0 0 0 0 0 2 6 1 0 0 0   1 0 0 0 0 0 1 7 4 1 0 0
   0 1 0 0 0 0 0 6 2 1 1 0   0 1 0 0 0 1 0 7 3 1 0 0   0 1 0 0 0 0 0 5 1 0 0 0
   0 0 0 0 0 1 0 4 1 0 0 1   0 0 0 0 0 0 0 6 1 0 1 1   0 0 1 0 0 0 0 6 3 0 1 1
   0 0 0 1 0 0 1 7 5 0 0 1   0 1 0 0 0 0 1 2 2 0 0 1   0 1 1 0 0 0 1 4 1 0 0 1
   0 1 0 0 1 0 0 5 1 0 0 1   0 1 0 0 0 0 1 7 2 0 0 1   0 0 0 0 0 1 0 5 1 0 0 1

Qmatrix <- matrix( as.numeric(Qmatrix), nrow=21, ncol=12, byrow=TRUE )
colnames(Qmatrix) <- scan( what="character", nlines=1)
   pc ic ier inc iui igc ch nro ncro td a t

# divide Q-matrix entries by maximum in each column
Qmatrix <- round(Qmatrix / matrix(apply(Qmatrix,2,max),21,12,byrow=TRUE),3)
# LSDM analysis
mod <- sirt::lsdm( b=b, Qmatrix=Qmatrix )
summary(mod)
```

```
#############################################################################
# EXAMPLE 6: Dataset Dimitrov et al. (2008)
#############################################################################

Qmatrix <- scan()
1 0 0 0 1 1 0 1 1 0 0 0 1 0 0 0 1 1 0 0 1 1 0 1 0 0 1 1 1 0 1 0 0 0 1 0

Qmatrix <- matrix(Qmatrix, ncol=4, byrow=TRUE)
colnames(Qmatrix) <- paste0("A",1:4)
rownames(Qmatrix) <- paste0("I",1:9)

b <- scan()
0.068 1.095 -0.641 -1.129 -0.061 1.218 1.244 -0.648 -1.146

# estimate model
mod <- sirt::lsdm( b=b, Qmatrix=Qmatrix )
summary(mod)
plot(mod)

#############################################################################
# EXAMPLE 7: Dataset Al-Shamrani & Dimitrov et al. (2017)
#############################################################################

I <- 39  # number of items

Qmatrix <- scan()
0 0 0 1 0 0 0 0 1 0 1 0 0 0 0 0 0 0 0 1 0 0 0 0 0 0 1 0 0 0 0 0 1 0 0
0 0 0 0 0 1 1 0 0 0 0 0 0 0 1 0 0 0 0 0 0 0 0 0 0 1 0 1 0 0 0 0 0 0 0 0 0 1 0 0
0 0 0 0 1 0 0 0 0 1 0 0 0 0 1 0 0 0 0 0 0 0 0 1 0 0 0 0 0 0 0 1 0 0 0 0 0 0 0 1 0 0 0
0 0 0 1 0 0 0 0 0 0 1 0 0 0 0 0 0 1 0 0 0 0 0 0 1 0 1 0 0 0 0 0 0 0 0 1 0 0 0 0 0 0
0 0 1 0 0 0 0 0 1 0 0 0 0 0 0 0 1 0 0 0 0 0 0 0 1 0 0 0 0 0 0 1 0 0 0 0 0 0 1 0 0 0 0 0
0 1 0 0 0 0 0 0 1 1 1 0 0 0 0 0 0 0 0 0 0 0 1 0 0 0 0 0 0 1 0 0 0 0 0 0 1 0 0 1 0 0 0
0 0 1 0 0 0 0 0 0 0 0 0 0 1 0

Qmatrix <- matrix(Qmatrix, nrow=I, byrow=TRUE)
colnames(Qmatrix) <- paste0("A",1:7)
rownames(Qmatrix) <- paste0("I",1:I)

pars <- scan()
1.952 0.9833 0.1816 1.1053 0.9631 0.1653 1.3904 1.3208 0.2545 0.7391 1.9367 0.2083 2.0833
1.8627 0.1873 1.4139 1.0107 0.2454 0.8274 0.9913 0.2137 1.0338 -0.0068 0.2368 2.4803
0.7939 0.1997 1.4867 1.1705 0.2541 1.4482 1.4176 0.2889 1.0789 0.8062 0.269 1.6258 1.1739
0.1723 1.5995 1.0936 0.2054 1.1814 1.0909 0.2623 2.0389 1.5023 0.2466 1.3636 1.1485 0.2059
1.8468 1.2755 0.192 1.9461 1.4947 0.2001 1.194 0.0889 0.2275 1.2114 0.8925 0.2367 2.0912
0.5961 0.2036 2.5769 1.3014 0.186 1.4554 1.2529 0.2423 1.4919 0.4763 0.2482 2.6787 1.7069
0.1796 1.5611 1.3991 0.2312 1.4353 0.678 0.1851 0.9127 1.3523 0.2525 0.6886 -0.3652 0.207
0.7039 -0.2494 0.2315 1.3683 0.8953 0.2326 1.4992 0.1025 0.2403 1.0727 0.2591 0.2152
1.3854 1.3802 0.2448 0.7748 0.4304 0.184 1.0218 1.8964 0.1949 1.5773 1.8934 0.2231 0.8631
1.4145 0.2132

pars <- matrix(pars, nrow=I, byrow=TRUE)
colnames(pars) <- c("a","b","c")
rownames(pars) <- paste0("I",1:I)
```

```
pars <- as.data.frame(pars)

#* Model 1: fit LSDM to 3PL curves (as in Al-Shamrani)
mod1 <- sirt::lsdm(b=pars$b, a=pars$a, c=pars$c, Qmatrix=Qmatrix)
summary(mod1)
plot(mod1)

#* Model 2: fit LSDM to 2PL curves
mod2 <- sirt::lsdm(b=pars$b, a=pars$a, Qmatrix=Qmatrix)
summary(mod2)
plot(mod2)

## End(Not run)
```

`lsem.estimate` *Local Structural Equation Models (LSEM)*

Description

Local structural equation models (LSEM) are structural equation models (SEM) which are evaluated for each value of a pre-defined moderator variable (Hildebrandt et al., 2009, 2016). As in nonparametric regression models, observations near a focal point - at which the model is evaluated - obtain higher weights, far distant observations obtain lower weights. The LSEM can be specified by making use of **lavaan** syntax. It is also possible to specify a discretized version of LSEM in which values of the moderator are grouped and a multiple group SEM is specified. The LSEM can be tested by employing a permutation test, see `lsem.permutationTest`.

The function `lsem.MGM.stepfunctions` outputs stepwise functions for a multiple group model evaluated at a grid of focal points of the moderator, specified in `moderator.grid`.

The argument `pseudo_weights` provides an ad hoc solution to estimate an LSEM for any model which can be fitted in **lavaan**.

It is also possible to constrain some of the parameters along the values of the moderator in a joint estimation approach (`est_joint=TRUE`). Parameter names can be specified which are assumed to be invariant (in `par_invariant`). In addition, linear or quadratic constraints can be imposed on parameters (`par_linear` or `par_quadratic`).

Statistical inference in case of joint estimation (but also for separate estimation) can be conducted via bootstrap using the function `lsem.bootstrap`. Bootstrap at the level of a cluster identifier is allowed (argument `cluster`).

Usage

```
lsem.estimate(data, moderator, moderator.grid, lavmodel, type="LSEM", h=1.1, bw=NULL,
    residualize=TRUE, fit_measures=c("rmsea", "cfi", "tli", "gfi", "srmr"),
    standardized=FALSE, standardized_type="std.all", lavaan_fct="sem",
    sufficient_statistics=TRUE, pseudo_weights=0,
   sampling_weights=NULL, loc_linear_smooth=TRUE, est_joint=FALSE, par_invariant=NULL,
    par_linear=NULL, par_quadratic=NULL, partable_joint=NULL, pw_linear=1,
    pw_quadratic=1, pd=TRUE, est_DIF=FALSE, se=NULL, kernel="gaussian",
```

```
    eps=1e-08, verbose=TRUE, ...)

## S3 method for class 'lsem'
summary(object, file=NULL, digits=3, ...)

## S3 method for class 'lsem'
plot(x, parindex=NULL, ask=TRUE, ci=TRUE, lintrend=TRUE,
       parsummary=TRUE, ylim=NULL, xlab=NULL,  ylab=NULL, main=NULL,
       digits=3, ...)

lsem.MGM.stepfunctions( object, moderator.grid )

# compute local weights
lsem_local_weights(data.mod, moderator.grid, h, sampling_weights=NULL, bw=NULL,
     kernel="gaussian", is_imputed=FALSE, Nimp=0, data=NULL, moderator=NULL)

lsem.bootstrap(object, R=100, verbose=TRUE, cluster=NULL,
     repl_design=NULL, repl_factor=NULL, use_starting_values=TRUE,
     n.core=1, cl.type="PSOCK")
```

Arguments

`data`	Data frame or a list of imputed datasets
`moderator`	Variable name of the moderator
`moderator.grid`	Focal points at which the LSEM should be evaluated. If `type="MGM"`, breaks are defined in this vector.
`lavmodel`	Specified SEM in **lavaan**.
`type`	Type of estimated model. The default is `type="LSEM"` which means that a local structural equation model is estimated. A multiple group model with a discretized moderator as the grouping variable can be estimated with `type="MGM"`. In this case, the breaks must be defined in `moderator.grid`.
`h`	Bandwidth factor
`bw`	Optional bandwidth parameter if `h` should not be used
`residualize`	Logical indicating whether a residualization should be applied.
`fit_measures`	Vector with names of fit measures following the labels in **lavaan**
`standardized`	Optional logical indicating whether standardized solution should be included as parameters in the output using the `lavaan::standardizedSolution` function. Standardized parameters are labeled as `std__`.
`standardized_type`	Type of standardization if `standardized=TRUE`. The types are described in `lavaan::standardizedSolu`
`lavaan_fct`	String whether `lavaan::lavaan` (`lavaan_fct="lavaan"`), `lavaan::sem` (`lavaan_fct="sem"`), `lavaan::cfa` (`lavaan_fct="cfa"`) or `lavaan::growth` (`lavaan_fct="growth"`) should be used.
`sufficient_statistics`	Logical whether sufficient statistics of weighted means and covariances should be used for model fitting. This option can be set to `sufficient_statistics=FALSE`

	if the data contain missing values. Note that the option `sufficient_statistics=TRUE` is only valid for (approximate) missing completely at random (MCAR) data. The option can only be used for continuous data.
`pseudo_weights`	Integer defining a target sample size. Local weights are multiplied by a factor which is rounded to integers. This approach is referred as a pseudo weighting approach. For example, using `pseudo_weights=30000` implies that the sum of local weights at each focal point is `30000`.
`sampling_weights`	Optional vector of sampling weights
`loc_linear_smooth`	Logical indicating whether local linear smoothing should be used for computing sufficient statistics for means and covariances. The default is `FALSE`.
`est_joint`	Logical indicating whether LSEM should be estimated in a joint estimation approach. This options only works wih continuous data and sufficient statistics.
`par_invariant`	Vector of invariant parameters
`par_linear`	Vector of parameters with linear function
`par_quadratic`	Vector of parameters with quadratic function
`partable_joint`	User-defined parameter table if joint estimation is used (`est_joint=TRUE`).
`pw_linear`	Number of segments if piecewise linear estimation of parameters is used
`pw_quadratic`	Number of segments if piecewise quadratic estimation of parameters is used
`pd`	Logical indicating whether nearest positive definite covariance matrix should be computed if sufficient statistics are used
`est_DIF`	Logical indicating whether parameters under differential item functioning (DIF) should be additionally computed for invariant item parameters
`se`	Type of standard error used in `lavaan::lavaan`. If `NULL`, the **lavaan** default is used.
`kernel`	Type of kernel function. Can be `"gaussian"`, `"uniform"` or `"epanechnikov"`.
`is_imputed`	Logical indicating whether datasets are imputed
`Nimp`	Number of imputed datasets
`eps`	Minimum number for weights
`verbose`	Optional logical printing information about computation progress.
`object`	Object of class `lsem`
`file`	A file name in which the summary output will be written.
`digits`	Number of digits.
`x`	Object of class `lsem`.
`parindex`	Vector of indices for parameters in plot function.
`ask`	A logical which asks for changing the graphic for each parameter.
`ci`	Logical indicating whether confidence intervals should be plotted.
`lintrend`	Logical indicating whether a linear trend should be plotted.
`parsummary`	Logical indicating whether a parameter summary should be displayed.

ylim	Plot parameter ylim. Can be a list, see Examples.
xlab	Plot parameter xlab. Can be a vector.
ylab	Plot parameter ylab. Can be a vector.
main	Plot parameter main. Can be a vector.
...	Further arguments to be passed to lavaan::sem or lavaan::lavaan.
data.mod	Observed values of the moderator
R	Number of bootstrap samples
cluster	Optional variable name for bootstrap at the level of a cluster identifier
repl_design	Optional matrix containing replication weights for computation of standard errors. Note that sampling weights have to be already included in repl_design.
repl_factor	Replication factor in variance formula for statistical inference, e.g., 0.05 in PISA.
use_starting_values	Logical indicating whether starting values should be used from the original sample
n.core	A scalar indicating the number of cores that should be used.
cl.type	The cluster type. Default value is "PSOCK". Posix machines (Linux, Mac) generally benefit from much faster cluster computation if type is set to type="FORK".

Value

List with following entries

parameters	Data frame with all parameters estimated at focal points of moderator. Bias-corrected estimates under boostrap can be found in the column est_bc.
weights	Data frame with weights at each focal point
parameters_summary	Summary table for estimated parameters
parametersM	Estimated parameters in matrix form. Parameters are in columns and values of the grid of the moderator are in rows.
bw	Used bandwidth
h	Used bandwidth factor
N	Sample size
moderator.density	Estimated frequencies and effective sample size for moderator at focal points
moderator.stat	Descriptive statistics for moderator
moderator	Variable name of moderator
moderator.grid	Used grid of focal points for moderator
moderator.grouped	Data frame with informations about grouping of moderator if type="MGM".
residualized.intercepts	Estimated intercept functions used for residualization.

`lavmodel` Used lavaan model

`data` Used data frame, possibly residualized if `residualize=TRUE`

`model_parameters`
Model parameters in LSEM

`parameters_boot`
Parameter values in each bootstrap sample (for `lsem.bootstrap`)

`fitstats_joint_boot`
Fit statistics in each bootstrap sample (for `lsem.bootstrap`)

`dif_effects` Estimated item parameters under DIF

Author(s)

Alexander Robitzsch, Oliver Luedtke, Andrea Hildebrandt

References

Hildebrandt, A., Luedtke, O., Robitzsch, A., Sommer, C., & Wilhelm, O. (2016). Exploring factor model parameters across continuous variables with local structural equation models. *Multivariate Behavioral Research, 51*(2-3), 257-278. doi:10.1080/00273171.2016.1142856

Hildebrandt, A., Wilhelm, O., & Robitzsch, A. (2009). Complementary and competing factor analytic approaches for the investigation of measurement invariance. *Review of Psychology, 16*, 87-102.

See Also

See `lsem.permutationTest` for conducting a permutation test and `lsem.test` for applying a Wald test to a bootstrapped LSEM model.

Examples

```
## Not run:
#############################################################################
# EXAMPLE 1: data.lsem01 | Age differentiation
#############################################################################

data(data.lsem01, package="sirt")
dat <- data.lsem01

# specify lavaan model
lavmodel <- "
        F=~ v1+v2+v3+v4+v5
        F ~~ 1*F"

# define grid of moderator variable age
moderator.grid <- seq(4,23,1)

#*********************************
#*** Model 1: estimate LSEM with bandwidth 2
mod1 <- sirt::lsem.estimate( dat, moderator="age", moderator.grid=moderator.grid,
              lavmodel=lavmodel, h=2, std.lv=TRUE)
summary(mod1)
```

```
plot(mod1, parindex=1:5)

# perform permutation test for Model 1
pmod1 <- sirt::lsem.permutationTest( mod1, B=10 )
          # only for illustrative purposes the number of permutations B is set
          # to a low number of 10
summary(pmod1)
plot(pmod1, type="global")

#* perform permutation test with parallel computation
pmod1a <- sirt::lsem.permutationTest( mod1, B=10, n.core=3 )
summary(pmod1a)

#** estimate Model 1 based on pseudo weights
mod1b <- sirt::lsem.estimate( dat, moderator="age", moderator.grid=moderator.grid,
               lavmodel=lavmodel, h=2, std.lv=TRUE, pseudo_weights=50 )
summary(mod1b)

#** estimation with sampling weights

# generate random sampling weights
set.seed(987)
weights <- stats::runif(nrow(dat), min=.4, max=3 )
mod1c <- sirt::lsem.estimate( dat, moderator="age", moderator.grid=moderator.grid,
               lavmodel=lavmodel, h=2, sampling_weights=weights)
summary(mod1c)

#*********************************
#*** Model 2: estimate multiple group model with 4 age groups

# define breaks for age groups
moderator.grid <- seq( 3.5, 23.5, len=5) # 4 groups
# estimate model
mod2 <- sirt::lsem.estimate( dat, moderator="age", moderator.grid=moderator.grid,
           lavmodel=lavmodel, type="MGM", std.lv=TRUE)
summary(mod2)

# output step functions
smod2 <- sirt::lsem.MGM.stepfunctions( object=mod2, moderator.grid=seq(4,23,1) )
str(smod2)

#*********************************
#*** Model 3: define standardized loadings as derived variables

# specify lavaan model
lavmodel <- "
        F=~ a1*v1+a2*v2+a3*v3+a4*v4
        v1 ~~ s1*v1
        v2 ~~ s2*v2
        v3 ~~ s3*v3
        v4 ~~ s4*v4
        F ~~ 1*F
        # standardized loadings
```

```
        l1 :=a1 / sqrt(a1^2 + s1 )
        l2 :=a2 / sqrt(a2^2 + s2 )
        l3 :=a3 / sqrt(a3^2 + s3 )
        l4 :=a4 / sqrt(a4^2 + s4 )
        "
# estimate model
mod3 <- sirt::lsem.estimate( dat, moderator="age", moderator.grid=moderator.grid,
               lavmodel=lavmodel, h=2, std.lv=TRUE)
summary(mod3)
plot(mod3)

#*********************************
#*** Model 4: estimate LSEM and automatically include standardized solutions

lavmodel <- "
        F=~ 1*v1+v2+v3+v4
        F ~~ F"
mod4 <- sirt::lsem.estimate( dat, moderator="age", moderator.grid=moderator.grid,
               lavmodel=lavmodel, h=2, standardized=TRUE)
summary(mod4)
# permutation test (use only few permutations for testing purposes)
pmod1 <- sirt::lsem.permutationTest( mod4, B=3 )

#**** compute LSEM local weights
wgt <- sirt::lsem_local_weights(data.mod=dat$age, moderator.grid=moderator.grid,
             h=2)$weights
print(str(weights))

#*********************************
#*** Model 5: invariance parameter constraints and other constraints

lavmodel <- "
        F=~ 1*v1+v2+v3+v4
        F ~~ F"
moderator.grid <- seq(4,23,4)

#- estimate model without constraints
mod5a <- sirt::lsem.estimate( dat, moderator="age", moderator.grid=moderator.grid,
               lavmodel=lavmodel, h=2, standardized=TRUE)
summary(mod5a)
# extract parameter names
mod5a$model_parameters

#- invariance constraints on residual variances
par_invariant <- c("F=~v2","v2~~v2")
mod5b <- sirt::lsem.estimate( dat, moderator="age", moderator.grid=moderator.grid,
               lavmodel=lavmodel, h=2, standardized=TRUE, par_invariant=par_invariant)
summary(mod5b)

#- bootstrap for statistical inference
bmod5b <- sirt::lsem.bootstrap(mod5b, R=100)
# inspect parameter values and standard errors
bmod5b$parameters
```

```
#- bootstrap using parallel computing (i.e., multiple cores)
bmod5ba <- sirt::lsem.bootstrap(mod5b, R=100, n.core=3)

#- user-defined replication design
R <- 100    # bootstrap samples
N <- nrow(dat)
repl_design <- matrix(0, nrow=N, ncol=R)
for (rr in 1:R){
    indices <- sort( sample(1:N, replace=TRUE) )
    repl_design[,rr] <- sapply(1:N, FUN=function(ii){ sum(indices==ii) } )
}
head(repl_design)
bmod5b1 <- sirt::lsem.bootstrap(mod5a, repl_design=repl_design, repl_factor=1/R)

#- compare model mod5b with joint estimation without constraints
mod5c <- sirt::lsem.estimate( dat, moderator="age", moderator.grid=moderator.grid,
               lavmodel=lavmodel, h=2, standardized=TRUE, est_joint=TRUE)
summary(mod5c)

#- linear and quadratic functions
par_invariant <- c("F=~v1","v2~~v2")
par_linear <- c("v1~~v1")
par_quadratic <- c("v4~~v4")

mod5d <- sirt::lsem.estimate( dat1, moderator="age", moderator.grid=moderator.grid,
            lavmodel=lavmodel, h=2, par_invariant=par_invariant, par_linear=par_linear,
            par_quadratic=par_quadratic)
summary(mod5d)

#- user-defined constraints: step functions for parameters

# inspect parameter table (from lavaan) of fitted model
pj <- mod5d$partable_joint
#* modify parameter table for user-defined constraints
# define step function for F=~v1 which is constant on intervals 1:4 and 5:7
pj2 <- pj[ pj$con==1, ]
pj2[ c(5,6), "lhs" ] <- "p1g5"
pj2 <- pj2[ -4, ]
partable_joint <- rbind(pj1, pj2)
# estimate model with constraints
mod5e <- lsem::lsem.estimate( dat1, moderator="age", moderator.grid=moderator.grid,
             lavmodel=lavmodel, h=2, std.lv=TRUE, estimator="ML",
             partable_joint=partable_joint)
summary(mod5e)

#############################################################################
# EXAMPLE 2: data.lsem01 | FIML with missing data
#############################################################################

data(data.lsem01)
dat <- data.lsem01
# induce artifical missing values
```

```
set.seed(98)
dat[ stats::runif(nrow(dat)) < .5, c("v1")] <- NA
dat[ stats::runif(nrow(dat)) < .25, c("v2")] <- NA

# specify lavaan model
lavmodel1 <- "
        F=~ v1+v2+v3+v4+v5
        F ~~ 1*F"

# define grid of moderator variable age
moderator.grid <- seq(4,23,2)

#*** estimate LSEM with FIML
mod1 <- sirt::lsem.estimate( dat, moderator="age", moderator.grid=moderator.grid,
                lavmodel=lavmodel1, h=2, std.lv=TRUE, estimator="ML", missing="fiml")
summary(mod1)

############################################################################
# EXAMPLE 3: data.lsem01 | WLSMV estimation
############################################################################

data(data.lsem01)
dat <- data.lsem01

# create artificial dichotomous data
for (vv in 2:6){
dat[,vv] <- 1*(dat[,vv] > mean(dat[,vv]))
}

# specify lavaan model
lavmodel1 <- "
        F=~ v1+v2+v3+v4+v5
        F ~~ 1*F
        v1 | t1
        v2 | t1
        v3 | t1
        v4 | t1
        v5 | t1
        "

# define grid of moderator variable age
moderator.grid <- seq(4,23,2)

#*** local WLSMV estimation
mod1 <- sirt::lsem.estimate( dat, moderator="age", moderator.grid=moderator.grid,
        lavmodel=lavmodel1, h=2, std.lv=TRUE, estimator="DWLS", ordered=paste0("v",1:5),
          residualize=FALSE, pseudo_weights=10000, parameterization="THETA" )
summary(mod1)

## End(Not run)
```

`lsem.permutationTest` *Permutation Test for a Local Structural Equation Model*

Description

Performs a permutation test for testing the hypothesis that model parameter are independent of a moderator variable (see Hildebrandt, Wilhelm, & Robitzsch, 2009; Hildebrandt, Luedtke, Robitzsch, Sommer, & Wilhelm, 2016).

Usage

```
lsem.permutationTest(lsem.object, B=1000, residualize=TRUE, verbose=TRUE,
     n.core=1, cl.type="PSOCK")

## S3 method for class 'lsem.permutationTest'
summary(object, file=NULL, digits=3, ...)

## S3 method for class 'lsem.permutationTest'
plot(x, type="global", stattype="SD",
    parindex=NULL, sig_add=TRUE, sig_level=0.05, sig_pch=17, nonsig_pch=2,
    sig_cex=1, sig_lab="p value",  stat_lab="Test statistic",
    moderator_lab=NULL, digits=3, title=NULL, parlabels=NULL,
    ask=TRUE, ...)
```

Arguments

`lsem.object`	Fitted object of class `lsem` with `lsem.estimate`
`B`	Number of permutation samples
`residualize`	Optional logical indicating whether residualization of the moderator should be performed for each permutation sample.
`verbose`	Optional logical printing information about computation progress.
`n.core`	A scalar indicating the number of cores that should be used.
`cl.type`	The cluster type. Default value is `"PSOCK"`. Posix machines (Linux, Mac) generally benefit from much faster cluster computation if type is set to `type="FORK"`.
`object`	Object of class `lsem`
`file`	A file name in which the summary output will be written.
`digits`	Number of digits.
`...`	Further arguments to be passed.
`x`	Object of class `lsem`
`type`	Type of the statistic to be plotted. If `type="global"`, a global test will be displayed. If `type="pointwise"` for each value at the focal point (defined in `moderator.grid`) are calculated.
`stattype`	Type of test statistics. Can be `MAD` (mean absolute deviation), `SD` (standard deviation) or `lin_slo` (linear slope).

parindex	Vector of indices of selected parameters.
sig_add	Logical indicating whether significance values (p values) should be displayed.
sig_level	Significance level.
sig_pch	Point symbol for significant values.
nonsig_pch	Point symbol for non-significant values.
sig_cex	Point size for graphic displaying p values
sig_lab	Label for significance value (p value).
stat_lab	Label of y axis for graphic with pointwise test statistic
moderator_lab	Label of the moderator.
title	Title of the plot. Can be a vector.
parlabels	Labels of the parameters. Can be a vector.
ask	A logical which asks for changing the graphic for each parameter.

Value

List with following entries

teststat	Data frame with global test statistics. The statistics are SD, MAD and lin_slo with their corresponding p values.
parameters_pointwise_test	Data frame with pointwise test statistics.
parameters	Original parameters.
parameters	Parameters in permutation samples.
parameters_summary	Original parameter summary.
parameters_summary_M	Mean of each parameter in permutation sample.
parameters_summary_SD	Standard deviation (SD) statistic in permutation slope.
parameters_summary_MAD	Mean absolute deviation (MAD) statistic in permutation sample.
parameters_summary_MAD	Linear slope parameter in permutation sample.
nonconverged_rate	Percentage of permuted dataset in which a LSEM model did not converge

Author(s)

Alexander Robitzsch, Oliver Luedtke, Andrea Hildebrandt

References

Hildebrandt, A., Luedtke, O., Robitzsch, A., Sommer, C., & Wilhelm, O. (2016). Exploring factor model parameters across continuous variables with local structural equation models. *Multivariate Behavioral Research, 51*(2-3), 257-278. doi:10.1080/00273171.2016.1142856

Hildebrandt, A., Wilhelm, O., & Robitzsch, A. (2009). Complementary and competing factor analytic approaches for the investigation of measurement invariance. *Review of Psychology, 16*, 87-102.

See Also

For Examples see lsem.estimate.

---

lsem.test *Test a Local Structural Equation Model Based on Bootstrap*

Description

Performs global and parameter tests for a fitted local structural equation model. The LSEM must have been fitted and bootstrap estimates of the LSEM model must be available for statistical inference. The hypothesis of a constant parameter is tested by means of a Wald test. Moreover, regression functions can be specified and tested if these are specified in the argument models.

Usage

```
lsem.test(mod, bmod, models=NULL)
```

Arguments

mod	Fitted LSEM object
bmod	Fitted LSEM bootstrap object. The argument bmod can also be missing.
models	List of model formulas for named LSEM model parameters

Value

List with following entries

wald_test_global
: Global Wald test for model parameters

test_models
: Output for fitted regression models. The test for parameter heterogeneity is included in chisq_het, while the test of a sufficient fit of a parameter curve is included in chisq_fit.

parameters
: Original model parameters after fitting (i.e., smoothing) a particular parameter using a regression model specified in models.

parameters_boot
: Bootstrapped model parameters after fitting (i.e., smoothing) a particular parameter using a regression model specified in models.

See Also

See also lsem.estimate for estimating LSEM models and lsem.bootstrap for bootstrapping LSEM models.

Examples

```
## Not run:
#############################################################################
# EXAMPLE 1: data.lsem01 | Age differentiation and tested models
#############################################################################

data(data.lsem01, package="sirt")
dat <- data.lsem01

# specify lavaan model
lavmodel <- "
        F=~ v1+v2+v3+v4+v5
        F ~~ 1*F
    "

# define grid of moderator variable age
moderator.grid <- seq(4,23,1)

#-- estimate LSEM with bandwidth 2
mod <- sirt::lsem.estimate( dat, moderator="age", moderator.grid=moderator.grid,
               lavmodel=lavmodel, h=2, std.lv=TRUE)
summary(mod)

#-- bootstrap model
bmod <- sirt::lsem.bootstrap(mod, R=200)

#-- test models
models <- list( "F=~v1"=y ~ m + I(m^2),
                "F=~v2"=y ~ I( splines::bs(m, df=4) ) )
tmod <- sirt::lsem.test(mod=mod, bmod=bmod, models=models)
str(tmod)
sirt::print_digits(wald_test_global, 3)
sirt::print_digits(test_models, 3)

## End(Not run)
```

---

marginal.truescore.reliability

True-Score Reliability for Dichotomous Data

Description

This function computes the marginal true-score reliability for dichotomous data (Dimitrov, 2003; May & Nicewander, 1994) for the four-parameter logistic item response model (see rasch.mml2 for details regarding this IRT model).

Usage

```
marginal.truescore.reliability(b, a=1+0*b,c=0*b,d=1+0*b,
    mean.trait=0, sd.trait=1, theta.k=seq(-6,6,len=200) )
```

Arguments

b	Vector of item difficulties
a	Vector of item discriminations
c	Vector of guessing parameters
d	Vector of upper asymptotes
mean.trait	Mean of trait distribution
sd.trait	Standard deviation of trait distribution
theta.k	Grid at which the trait distribution should be evaluated

Value

A list with following entries:

rel.test	Reliability of the test
item	True score variance (sig2.true, error variance (sig2.error) and item reliability (rel.item). Expected proportions correct are in the column pi.
pi	Average proportion correct for all items and persons
sig2.tau	True score variance σ^2_τ (calculated by the formula in May & Nicewander, 1994)
sig2.error	Error variance σ^2_e

References

Dimitrov, D. (2003). Marginal true-score measures and reliability for binary items as a function of their IRT parameters. *Applied Psychological Measurement, 27*, 440-458.

May, K., & Nicewander, W. A. (1994). Reliability and information functions for percentile ranks. *Journal of Educational Measurement, 31*, 313-325.

See Also

See greenyang.reliability for calculating the reliability for multidimensional measures.

Examples

```
#############################################################################
# EXAMPLE 1: Dimitrov (2003) Table 1 - 2PL model
#############################################################################

# item discriminations
a <- 1.7*c(0.449,0.402,0.232,0.240,0.610,0.551,0.371,0.321,0.403,0.434,0.459,
    0.410,0.302,0.343,0.225,0.215,0.487,0.608,0.341,0.465)
# item difficulties
b <- c( -2.554,-2.161,-1.551,-1.226,-0.127,-0.855,-0.568,-0.277,-0.017,
    0.294,0.532,0.773,1.004,1.250,1.562,1.385,2.312,2.650,2.712,3.000 )

marginal.truescore.reliability( b=b, a=a )
  ##   Reliability=0.606
```

```
#############################################################################
# EXAMPLE 2: Dimitrov (2003) Table 2
#  3PL model: Poetry items (4 items)
#############################################################################

# slopes, difficulties and guessing parameters
a <- 1.7*c(1.169,0.724,0.554,0.706 )
b <- c(0.468,-1.541,-0.042,0.698 )
c <- c(0.159,0.211,0.197,0.177 )

res <- sirt::marginal.truescore.reliability( b=b, a=a, c=c)
  ##   Reliability=0.403
  ##   > round( res$item, 3 )
  ##     item    pi sig2.tau sig2.error rel.item
  ##   1    1 0.463    0.063      0.186    0.252
  ##   2    2 0.855    0.017      0.107    0.135
  ##   3    3 0.605    0.026      0.213    0.107
  ##   4    4 0.459    0.032      0.216    0.130

#############################################################################
# EXAMPLE 3: Reading Data
#############################################################################
data( data.read)

#***
# Model 1: 1PL
mod <- sirt::rasch.mml2( data.read )
marginal.truescore.reliability( b=mod$item$b )
  ##   Reliability=0.653

#***
# Model 2: 2PL
mod <- sirt::rasch.mml2( data.read, est.a=1:12 )
marginal.truescore.reliability( b=mod$item$b, a=mod$item$a)
  ##   Reliability=0.696

## Not run:
# compare results with Cronbach's alpha and McDonald's omega
# posing a 'wrong model' for normally distributed data
library(psych)
psych::omega(dat, nfactors=1)     # 1 factor
  ##  Omega_h for 1 factor is not meaningful, just omega_t
  ##   Omega
  ##   Call: omega(m=dat, nfactors=1)
  ##   Alpha:                 0.69
  ##   G.6:                   0.7
  ##   Omega Hierarchical:    0.66
  ##   Omega H asymptotic:    0.95
  ##   Omega Total            0.69

##! Note that alpha in psych is the standardized one.

## End(Not run)
```

matrixfunctions.sirt *Some Matrix Functions*

Description

Some matrix functions which are written in **Rcpp** for speed reasons.

Usage

```
rowMaxs.sirt(matr)      # rowwise maximum

rowMins.sirt(matr)      # rowwise minimum

rowCumsums.sirt(matr)   # rowwise cumulative sum

colCumsums.sirt(matr)   # columnwise cumulative sum

rowIntervalIndex.sirt(matr,rn) # first index in row nn when matr(nn,zz) > rn(nn)

rowKSmallest.sirt(matr, K, break.ties=TRUE) # k smallest elements in a row
rowKSmallest2.sirt(matr, K )
```

Arguments

matr	A numeric matrix
rn	A vector, usually a random number in applications
K	An integer indicating the number of smallest elements to be extracted
break.ties	A logical which indicates if ties are randomly broken. The default is TRUE.

Details

The function rowIntervalIndex.sirt searches for all rows n the first index i for which matr(n,i) > rn(n) holds.

The functions rowKSmallest.sirt and rowKSmallest2.sirt extract the K smallest entries in a matrix row. For small numbers of K the function rowKSmallest2.sirt is the faster one.

Value

The output of rowMaxs.sirt is a list with the elements maxval (rowwise maximum values) and maxind (rowwise maximum indices). The output of rowMins.sirt contains corresponding minimum values with entries minval and minind.

The output of rowKSmallest.sirt are two matrices: smallval contains the K smallest values whereas smallind contains the K smallest indices.

Author(s)

Alexander Robitzsch

The **Rcpp** code for `rowCumsums.sirt` is copied from code of Romain Francois.

See Also

For other matrix functions see the **matrixStats** package.

Examples

```
##########################################################################
# EXAMPLE 1: a small toy example (I)
##########################################################################
set.seed(789)
N1 <- 10 ; N2 <- 4
M1 <- round( matrix( runif(N1*N2), nrow=N1, ncol=N2), 1 )

rowMaxs.sirt(M1)      # rowwise maximum
rowMins.sirt(M1)      # rowwise minimum
rowCumsums.sirt(M1)   # rowwise cumulative sum

# row index for exceeding a certain threshold value
matr <- M1
matr <- matr / rowSums( matr )
matr <- sirt::rowCumsums.sirt( matr )
rn <- runif(N1)    # generate random numbers
rowIntervalIndex.sirt(matr,rn)

# select the two smallest values
rowKSmallest.sirt(matr=M1, K=2)
rowKSmallest2.sirt(matr=M1, K=2)
```

---

mcmc.2pno *MCMC Estimation of the Two-Parameter Normal Ogive Item Response Model*

Description

This function estimates the Two-Parameter normal ogive item response model by MCMC sampling (Johnson & Albert, 1999, p. 195ff.).

Usage

```
mcmc.2pno(dat, weights=NULL, burnin=500, iter=1000, N.sampvalues=1000,
      progress.iter=50, save.theta=FALSE)
```

Arguments

dat	Data frame with dichotomous item responses
weights	An optional vector with student sample weights
burnin	Number of burnin iterations
iter	Total number of iterations
N.sampvalues	Maximum number of sampled values to save
progress.iter	Display progress every progress.iter-th iteration. If no progress display is wanted, then choose progress.iter larger than iter.
save.theta	Should theta values be saved?

Details

The two-parameter normal ogive item response model with a probit link function is defined by

$$P(X_{pi} = 1|\theta_p) = \Phi(a_i\theta_p - b_i) \quad , \quad \theta_p \sim N(0, 1)$$

Note that in this implementation non-informative priors for the item parameters are chosen (Johnson & Albert, 1999, p. 195ff.).

Value

A list of class mcmc.sirt with following entries:

mcmcobj	Object of class mcmc.list
summary.mcmcobj	Summary of the mcmcobj object. In this summary the Rhat statistic and the mode estimate MAP is included. The variable PercSEratio indicates the proportion of the Monte Carlo standard error in relation to the total standard deviation of the posterior distribution.
burnin	Number of burnin iterations
iter	Total number of iterations
a.chain	Sampled values of a_i parameters
b.chain	Sampled values of b_i parameters
theta.chain	Sampled values of θ_p parameters
deviance.chain	Sampled values of Deviance values
EAP.rel	EAP reliability
person	Data frame with EAP person parameter estimates for θ_p and their corresponding posterior standard deviations
dat	Used data frame
weights	Used student weights
...	Further values

References

Johnson, V. E., & Albert, J. H. (1999). *Ordinal Data Modeling*. New York: Springer.

See Also

S3 methods: summary.mcmc.sirt, plot.mcmc.sirt

For estimating the 2PL model with marginal maximum likelihood see rasch.mml2 or smirt.

A hierarchical version of this model can be estimated with mcmc.2pnoh.

Examples

```
## Not run:
#############################################################################
# EXAMPLE 1: Dataset Reading
#############################################################################
data(data.read)
# estimate 2PNO with MCMC with 3000 iterations and 500 burn-in iterations
mod <- sirt::mcmc.2pno( dat=data.read, iter=3000, burnin=500 )
# plot MCMC chains
plot( mod$mcmcobj, ask=TRUE )
# write sampled chains into codafile
mcmclist2coda( mod$mcmcobj, name="dataread_2pno" )
# summary
summary(mod)

#############################################################################
# EXAMPLE 2
#############################################################################
# simulate data
N <- 1000
I <- 10
b <- seq( -1.5, 1.5, len=I )
a <- rep( c(1,2), I/2 )
theta1 <- stats::rnorm(N)
dat <- sirt::sim.raschtype( theta=theta1, fixed.a=a, b=b )

#***
# Model 1: estimate model without weights
mod1 <- sirt::mcmc.2pno( dat, iter=1500, burnin=500)
mod1$summary.mcmcobj
plot( mod1$mcmcobj, ask=TRUE )

#***
# Model 2: estimate model with weights
# define weights
weights <- c( rep( 5, N/4 ), rep( .2, 3/4*N ) )
mod2 <- sirt::mcmc.2pno( dat, weights=weights, iter=1500, burnin=500)
mod1$summary.mcmcobj

## End(Not run)
```

mcmc.2pno.ml *Random Item Response Model / Multilevel IRT Model*

Description

This function enables the estimation of random item models and multilevel (or hierarchical) IRT models (Chaimongkol, Huffer & Kamata, 2007; Fox & Verhagen, 2010; van den Noortgate, de Boeck & Meulders, 2003; Asparouhov & Muthen, 2012; Muthen & Asparouhov, 2013, 2014). Dichotomous response data is supported using a probit link. Normally distributed responses can also be analyzed. See Details for a description of the implemented item response models.

Usage

```
mcmc.2pno.ml(dat, group, link="logit", est.b.M="h", est.b.Var="n",
    est.a.M="f", est.a.Var="n", burnin=500, iter=1000,
    N.sampvalues=1000, progress.iter=50, prior.sigma2=c(1, 0.4),
    prior.sigma.b=c(1, 1), prior.sigma.a=c(1, 1), prior.omega.b=c(1, 1),
    prior.omega.a=c(1, 0.4), sigma.b.init=.3 )
```

Arguments

dat	Data frame with item responses.
group	Vector of group identifiers (e.g. classes, schools or countries)
link	Link function. Choices are "logit" for dichotomous data and "normal" for data under normal distribution assumptions
est.b.M	Estimation type of b_i parameters: n - non-hierarchical prior distribution, i.e. ω_b is set to a very high value and is not estimated h - hierarchical prior distribution with estimated distribution parameters μ_b and ω_b
est.b.Var	Estimation type of standard deviations of item difficulties b_i. n – no estimation of the item variance, i.e. $\sigma_{b,i}$ is assumed to be zero i – item-specific standard deviation of item difficulties j – a joint standard deviation of all item difficulties is estimated, i.e. $\sigma_{b,1} = \ldots = \sigma_{b,I} = \sigma_b$
est.a.M	Estimation type of a_i parameters: f - no estimation of item slopes, i.e all item slopes a_i are fixed at one n - non-hierarchical prior distribution, i.e. $\omega_a = 0$ h - hierarchical prior distribution with estimated distribution parameter ω_a
est.a.Var	Estimation type of standard deviations of item slopes a_i. n – no estimation of the item variance i – item-specific standard deviation of item slopes j – a joint standard deviation of all item slopes is estimated, i.e. $\sigma_{a,1} = \ldots = \sigma_{a,I} = \sigma_a$
burnin	Number of burnin iterations

iter	Total number of iterations
N.sampvalues	Maximum number of sampled values to save
progress.iter	Display progress every progress.iter-th iteration. If no progress display is wanted, then choose progress.iter larger than iter.
prior.sigma2	Prior for Level 2 standard deviation σ_{L2}
prior.sigma.b	Priors for item difficulty standard deviations $\sigma_{b,i}$
prior.sigma.a	Priors for item difficulty standard deviations $\sigma_{a,i}$
prior.omega.b	Prior for ω_b
prior.omega.a	Prior for ω_a
sigma.b.init	Initial standard deviation for $\sigma_{b,i}$ parameters

Details

For dichotomous item responses (link="logit") of persons p in group j on item i, the probability of a correct response is defined as

$$P(X_{pji}=1|\theta_{pj})=\Phi(a_{ij}\theta_{pj}-b_{ij})$$

The ability θ_{pj} is decomposed into a Level 1 and a Level 2 effect

$$\theta_{pj}=u_j+e_{pj} \quad , \quad u_j \sim N(0,\sigma^2_{L2}) \quad , \quad e_{pj} \sim N(0,\sigma^2_{L1})$$

In a multilevel IRT model (or a random item model), item parameters are allowed to vary across groups:

$$b_{ij} \sim N(b_i,\sigma^2_{b,i}) \quad , \quad a_{ij} \sim N(a_i,\sigma^2_{a,i})$$

In a hierarchical IRT model, a hierarchical distribution of the (main) item parameters is assumed

$$b_i \sim N(\mu_b,\omega^2_b) \quad , \quad a_i \sim N(1,\omega^2_a)$$

Note that for identification purposes, the mean of all item slopes a_i is set to one. Using the arguments est.b.M, est.b.Var, est.a.M and est.a.Var defines which variance components should be estimated.

For normally distributed item responses (link="normal"), the model equations remain the same except the item response model which is now written as

$$X_{pji}=a_{ij}\theta_{pj}-b_{ij}+\varepsilon_{pji} \quad , \quad \varepsilon_{pji} \sim N(0,\sigma^2_{res,i})$$

Value

A list of class mcmc.sirt with following entries:

mcmcobj	Object of class mcmc.list
summary.mcmcobj	Summary of the mcmcobj object. In this summary the Rhat statistic and the mode estimate MAP is included. The variable PercSEratio indicates the proportion of the Monte Carlo standard error in relation to the total standard deviation of the posterior distribution.

`ic`	Information criteria (DIC)
`burnin`	Number of burnin iterations
`iter`	Total number of iterations
`theta.chain`	Sampled values of θ_{pj} parameters
`theta.chain`	Sampled values of u_j parameters
`deviance.chain`	Sampled values of Deviance values
`EAP.rel`	EAP reliability
`person`	Data frame with EAP person parameter estimates for θ_pj and their corresponding posterior standard deviations
`dat`	Used data frame
`...`	Further values

References

Asparouhov, T. & Muthen, B. (2012). General random effect latent variable modeling: Random subjects, items, contexts, and parameters. *http://www.statmodel.com/papers_date.shtml*.

Chaimongkol, S., Huffer, F. W., & Kamata, A. (2007). An explanatory differential item functioning (DIF) model by the WinBUGS 1.4. *Songklanakarin Journal of Science and Technology, 29*, 449-458.

Fox, J.-P., & Verhagen, A.-J. (2010). Random item effects modeling for cross-national survey data. In E. Davidov, P. Schmidt, & J. Billiet (Eds.), *Cross-cultural Analysis: Methods and Applications* (pp. 467-488), London: Routledge Academic.

Muthen, B. & Asparouhov, T. (2013). New methods for the study of measurement invariance with many groups. *http://www.statmodel.com/papers_date.shtml*

Muthen, B. & Asparouhov, T. (2014). Item response modeling in Mplus: A multi-dimensional, multi-level, and multi-timepoint example. In W. Linden & R. Hambleton (2014). *Handbook of item response theory: Models, statistical tools, and applications*. *http://www.statmodel.com/papers_date.shtml*

van den Noortgate, W., De Boeck, P., & Meulders, M. (2003). Cross-classification multilevel logistic models in psychometrics. *Journal of Educational and Behavioral Statistics, 28*, 369-386.

See Also

S3 methods: `summary.mcmc.sirt`, `plot.mcmc.sirt`

For MCMC estimation of three-parameter (testlet) models see `mcmc.3pno.testlet`.

See also the **MLIRT** package (http://www.jean-paulfox.com).

For more flexible estimation of multilevel IRT models see the **MCMCglmm** and **lme4** packages.

Examples

```
## Not run:
#############################################################################
# EXAMPLE 1: Dataset Multilevel data.ml1 - dichotomous items
#############################################################################
data(data.ml1)
```

```
dat <- data.ml1[,-1]
group <- data.ml1$group
# just for a try use a very small number of iterations
burnin <- 50 ; iter <- 100

#***
# Model 1: 1PNO with no cluster item effects
mod1 <- sirt::mcmc.2pno.ml( dat, group, est.b.Var="n", burnin=burnin, iter=iter )
summary(mod1)    # summary
plot(mod1,layout=2,ask=TRUE) # plot results
# write results to coda file
mcmclist2coda( mod1$mcmcobj, name="data.ml1_mod1" )

#***
# Model 2: 1PNO with cluster item effects of item difficulties
mod2 <- sirt::mcmc.2pno.ml( dat, group, est.b.Var="i", burnin=burnin, iter=iter )
summary(mod2)
plot(mod2, ask=TRUE, layout=2 )

#***
# Model 3: 2PNO with cluster item effects of item difficulties but
#          joint item slopes
mod3 <- sirt::mcmc.2pno.ml( dat, group, est.b.Var="i", est.a.M="h",
              burnin=burnin, iter=iter )
summary(mod3)

#***
# Model 4: 2PNO with cluster item effects of item difficulties and
#          cluster item effects with a jointly estimated SD
mod4 <- sirt::mcmc.2pno.ml( dat, group, est.b.Var="i", est.a.M="h",
                est.a.Var="j", burnin=burnin, iter=iter )
summary(mod4)

#############################################################################
# EXAMPLE 2: Dataset Multilevel data.ml2 - polytomous items
#            assuming a normal distribution for polytomous items
#############################################################################
data(data.ml2)
dat <- data.ml2[,-1]
group <- data.ml2$group
# set iterations for all examples (too few!!)
burnin <- 100 ; iter <- 500

#***
# Model 1: no intercept variance, no slopes
mod1 <- sirt::mcmc.2pno.ml( dat=dat, group=group, est.b.Var="n",
             burnin=burnin, iter=iter, link="normal",  progress.iter=20  )
summary(mod1)

#***
# Model 2a: itemwise intercept variance, no slopes
mod2a <- sirt::mcmc.2pno.ml( dat=dat, group=group, est.b.Var="i",
            burnin=burnin, iter=iter,link="normal",  progress.iter=20  )
```

```
summary(mod2a)

#***
# Model 2b: homogeneous intercept variance, no slopes
mod2b <- sirt::mcmc.2pno.ml( dat=dat, group=group, est.b.Var="j",
              burnin=burnin, iter=iter,link="normal",  progress.iter=20  )
summary(mod2b)

#***
# Model 3: intercept variance and slope variances
#          hierarchical item and slope parameters
mod3 <- sirt::mcmc.2pno.ml( dat=dat, group=group,
               est.b.M="h", est.b.Var="i", est.a.M="h", est.a.Var="i",
               burnin=burnin, iter=iter,link="normal",  progress.iter=20  )
summary(mod3)

############################################################################
# EXAMPLE 3: Simulated random effects model | dichotomous items
############################################################################
set.seed(7698)

#*** model parameters
sig2.lev2 <- .3^2   # theta level 2 variance
sig2.lev1 <- .8^2   # theta level 1 variance
G <- 100            # number of groups
n <- 20             # number of persons within a group
I <- 12             # number of items
#*** simuate theta
theta2 <- stats::rnorm( G, sd=sqrt(sig2.lev2) )
theta1 <- stats::rnorm( n*G, sd=sqrt(sig2.lev1) )
theta  <- theta1 + rep( theta2, each=n )
#*** item difficulties
b <- seq( -2, 2, len=I )
#*** define group identifier
group <- 1000 + rep(1:G, each=n )
#*** SD of group specific difficulties for items 3 and 5
sigma.item <- rep(0,I)
sigma.item[c(3,5)] <- 1
#*** simulate group specific item difficulties
b.class <- sapply( sigma.item, FUN=function(sii){ stats::rnorm( G, sd=sii ) } )
b.class <- b.class[ rep( 1:G,each=n ), ]
b <- matrix( b, n*G, I, byrow=TRUE ) + b.class
#*** simulate item responses
m1 <- stats::pnorm( theta - b )
dat <- 1 * ( m1 > matrix( stats::runif( n*G*I ), n*G, I ) )

#*** estimate model
mod <- sirt::mcmc.2pno.ml( dat, group=group, burnin=burnin, iter=iter,
            est.b.M="n", est.b.Var="i", progress.iter=20)
summary(mod)
plot(mod, layout=2, ask=TRUE )

## End(Not run)
```

mcmc.2pnoh *MCMC Estimation of the Hierarchical IRT Model for Criterion-Referenced Measurement*

Description

This function estimates the hierarchical IRT model for criterion-referenced measurement which is based on a two-parameter normal ogive response function (Janssen, Tuerlinckx, Meulders & de Boeck, 2000).

Usage

```
mcmc.2pnoh(dat, itemgroups, prob.mastery=c(.5,.8), weights=NULL,
      burnin=500, iter=1000, N.sampvalues=1000,
      progress.iter=50, prior.variance=c(1,1), save.theta=FALSE)
```

Arguments

dat	Data frame with dichotomous item responses
itemgroups	Vector with characters or integers which define the criterion to which an item is associated.
prob.mastery	Probability levels which define nonmastery, transition and mastery stage (see Details)
weights	An optional vector with student sample weights
burnin	Number of burnin iterations
iter	Total number of iterations
N.sampvalues	Maximum number of sampled values to save
progress.iter	Display progress every progress.iter-th iteration. If no progress display is wanted, then choose progress.iter larger than iter.
prior.variance	Scale parameter of the inverse gamma distribution for the σ^2 and ν^2 item variance parameters
save.theta	Should theta values be saved?

Details

The hierarchical IRT model for criterion-referenced measurement (Janssen et al., 2000) assumes that every item i intends to measure a criterion k. The item response function is defined as

$$P(X_{pik}=1|\theta_p)=\Phi[\alpha_{ik}(\theta_p-\beta_{ik})] \quad , \quad \theta_p \sim N(0,1)$$

Item parameters (α_{ik},β_{ik}) are hierarchically modeled, i.e.

$$\beta_{ik} \sim N(\xi_k,\sigma^2) \quad \text{and} \quad \alpha_{ik} \sim N(\omega_k,\nu^2)$$

In the mcmc.list output object, also the derived parameters $d_{ik} = \alpha_{ik}\beta_{ik}$ and $\tau_k = \xi_k\omega_k$ are calculated. Mastery and nonmastery probabilities are based on a reference item Y_k of criterion k and a response function

$$P(Y_{pk} = 1|\theta_p) = \Phi[\omega_k(\theta_p - \xi_k)] \quad , \quad \theta_p \sim N(0, 1)$$

With known item parameters and person parameters, response probabilities of criterion k are calculated. If a response probability of criterion k is larger than prob.mastery[2], then a student is defined as a master. If this probability is smaller than prob.mastery[1], then a student is a nonmaster. In all other cases, students are in a transition stage.

In the mcmcobj output object, the parameters d[i] are defined by $d_{ik} = \alpha_{ik} \cdot \beta_{ik}$ while tau[k] are defined by $\tau_k = \xi_k \cdot \omega_k$.

Value

A list of class mcmc.sirt with following entries:

mcmcobj	Object of class mcmc.list
summary.mcmcobj	Summary of the mcmcobj object. In this summary the Rhat statistic and the mode estimate MAP is included. The variable PercSEratio indicates the proportion of the Monte Carlo standard error in relation to the total standard deviation of the posterior distribution.
burnin	Number of burnin iterations
iter	Total number of iterations
alpha.chain	Sampled values of α_{ik} parameters
beta.chain	Sampled values of β_{ik} parameters
xi.chain	Sampled values of ξ_k parameters
omega.chain	Sampled values of ω_k parameters
sigma.chain	Sampled values of σ parameter
nu.chain	Sampled values of ν parameter
theta.chain	Sampled values of θ_p parameters
deviance.chain	Sampled values of Deviance values
EAP.rel	EAP reliability
person	Data frame with EAP person parameter estimates for θ_p and their corresponding posterior standard deviations
dat	Used data frame
weights	Used student weights
...	Further values

References

Janssen, R., Tuerlinckx, F., Meulders, M., & De Boeck, P. (2000). A hierarchical IRT model for criterion-referenced measurement. *Journal of Educational and Behavioral Statistics, 25*, 285-306.

See Also

S3 methods: summary.mcmc.sirt, plot.mcmc.sirt

The two-parameter normal ogive model can be estimated with mcmc.2pno.

Examples

```
## Not run:
#############################################################################
# EXAMPLE 1: Simulated data according to Janssen et al. (2000, Table 2)
#############################################################################

N <- 1000
Ik <- c(4,6,8,5,9,6,8,6,5)
xi.k <- c( -.89, -1.13, -1.23, .06, -1.41, -.66, -1.09, .57, -2.44)
omega.k <- c(.98, .91, .76, .74, .71, .80, .79, .82, .54)

# select 4 attributes
K <- 4
Ik <- Ik[1:K] ; xi.k <- xi.k[1:K] ; omega.k <- omega.k[1:K]
sig2 <- 3.02
nu2 <- .09
I <- sum(Ik)
b <- rep( xi.k, Ik ) + stats::rnorm(I, sd=sqrt(sig2) )
a <- rep( omega.k, Ik ) + stats::rnorm(I, sd=sqrt(nu2) )
theta1 <- stats::rnorm(N)
t1 <- rep(1,N)
p1 <- stats::pnorm( outer(t1,a) * ( theta1 - outer(t1,b) ) )
dat <- 1  * ( p1 > stats::runif(N*I)  )
itemgroups <- rep( paste0("A", 1:K ), Ik )

# estimate model
mod <- sirt::mcmc.2pnoh(dat, itemgroups, burnin=200, iter=1000 )
# summary
summary(mod)
# plot
plot(mod$mcmcobj, ask=TRUE)
# write coda files
mcmclist2coda( mod$mcmcobj, name="simul_2pnoh" )

## End(Not run)
```

---

mcmc.3pno.testlet *3PNO Testlet Model*

Description

This function estimates the 3PNO testlet model (Wang, Bradlow & Wainer, 2002, 2007) by Markov Chain Monte Carlo methods (Glas, 2012).

Usage

```
mcmc.3pno.testlet(dat, testlets=rep(NA, ncol(dat)),
   weights=NULL, est.slope=TRUE, est.guess=TRUE, guess.prior=NULL,
   testlet.variance.prior=c(1, 0.2), burnin=500, iter=1000,
  N.sampvalues=1000, progress.iter=50, save.theta=FALSE, save.gamma.testlet=FALSE )
```

Arguments

`dat`	Data frame with dichotomous item responses for N persons and I items
`testlets`	An integer or character vector which indicates the allocation of items to testlets. Same entries corresponds to same testlets. If an entry is `NA`, then this item does not belong to any testlet.
`weights`	An optional vector with student sample weights
`est.slope`	Should item slopes be estimated? The default is `TRUE`.
`est.guess`	Should guessing parameters be estimated? The default is `TRUE`.
`guess.prior`	A vector of length two or a matrix with I items and two columns which defines the beta prior distribution of guessing parameters. The default is a non-informative prior, i.e. the Beta(1,1) distribution.
`testlet.variance.prior`	A vector of length two which defines the (joint) prior for testlet variances assuming an inverse chi-squared distribution. The first entry is the effective sample size of the prior while the second entry defines the prior variance of the testlet. The default of `c(1,.2)` means that the prior sample size is 1 and the prior testlet variance is .2.
`burnin`	Number of burnin iterations
`iter`	Number of iterations
`N.sampvalues`	Maximum number of sampled values to save
`progress.iter`	Display progress every `progress.iter`-th iteration. If no progress display is wanted, then choose `progress.iter` larger than `iter`.
`save.theta`	Logical indicating whether theta values should be saved
`save.gamma.testlet`	Logical indicating whether gamma values should be saved

Details

The testlet response model for person p at item i is defined as

$$P(X_{pi}=1) = c_i + (1-c_i)\Phi(a_i\theta_p + \gamma_{p,t(i)} + b_i) \quad , \quad \theta_p \sim N(0,1), \gamma_{p,t(i)} \sim N(0,\sigma_t^2)$$

In case of `est.slope=FALSE`, all item slopes a_i are set to 1. Then a variance σ^2 of the θ_p distribution is estimated which is called the Rasch testlet model in the literature (Wang & Wilson, 2005).

In case of `est.guess=FALSE`, all guessing parameters c_i are set to 0.

After fitting the testlet model, marginal item parameters are calculated (integrating out testlet effects $\gamma_{p,t(i)}$) according the defining response equation

$$P(X_{pi}=1) = c_i + (1-c_i)\Phi(a_i^*\theta_p + b_i^*)$$

Value

A list of class `mcmc.sirt` with following entries:

`mcmcobj`	Object of class `mcmc.list` containing item parameters (`b_marg` and `a_marg` denote marginal item parameters) and person parameters (if requested)
`summary.mcmcobj`	Summary of the `mcmcobj` object. In this summary the Rhat statistic and the mode estimate MAP is included. The variable `PercSEratio` indicates the proportion of the Monte Carlo standard error in relation to the total standard deviation of the posterior distribution.
`ic`	Information criteria (DIC)
`burnin`	Number of burnin iterations
`iter`	Total number of iterations
`theta.chain`	Sampled values of θ_p parameters
`deviance.chain`	Sampled values of deviance values
`EAP.rel`	EAP reliability
`person`	Data frame with EAP person parameter estimates for θ_p and their corresponding posterior standard deviations and for all testlet effects
`dat`	Used data frame
`weights`	Used student weights
`...`	Further values

References

Glas, C. A. W. (2012). *Estimating and testing the extended testlet model.* LSAC Research Report Series, RR 12-03.

Wainer, H., Bradlow, E. T., & Wang, X. (2007). *Testlet response theory and its applications*. Cambridge: Cambridge University Press.

Wang, W.-C., & Wilson, M. (2005). The Rasch testlet model. *Applied Psychological Measurement, 29*, 126-149.

Wang, X., Bradlow, E. T., & Wainer, H. (2002). A general Bayesian model for testlets: Theory and applications. *Applied Psychological Measurement, 26*, 109-128.

See Also

S3 methods: `summary.mcmc.sirt`, `plot.mcmc.sirt`

Examples

```
## Not run:
#############################################################################
# EXAMPLE 1: Dataset Reading
#############################################################################
data(data.read)
dat <- data.read
```

```
I <- ncol(dat)

# set burnin and total number of iterations here (CHANGE THIS!)
burnin <- 200
iter <- 500

#***
# Model 1: 1PNO model
mod1 <- sirt::mcmc.3pno.testlet( dat,  est.slope=FALSE, est.guess=FALSE,
            burnin=burnin, iter=iter )
summary(mod1)
plot(mod1,ask=TRUE) # plot MCMC chains in coda style
plot(mod1,ask=TRUE, layout=2) # plot MCMC output in different layout

#***
# Model 2: 3PNO model with Beta(5,17) prior for guessing parameters
mod2 <- sirt::mcmc.3pno.testlet( dat,  guess.prior=c(5,17),
               burnin=burnin, iter=iter )
summary(mod2)

#***
# Model 3: Rasch (1PNO) testlet model
testlets <- substring( colnames(dat), 1, 1 )
mod3 <- sirt::mcmc.3pno.testlet( dat,  testlets=testlets,  est.slope=FALSE,
           est.guess=FALSE, burnin=burnin, iter=iter )
summary(mod3)

#***
# Model 4: 3PNO testlet model with (almost) fixed guessing parameters .25
mod4 <- sirt::mcmc.3pno.testlet( dat,  guess.prior=1000*c(25,75), testlets=testlets,
              burnin=burnin, iter=iter )
summary(mod4)
plot(mod4, ask=TRUE, layout=2)

############################################################################
# EXAMPLE 2: Simulated data according to the Rasch testlet model
############################################################################
set.seed(678)

N <- 3000   # number of persons
I <- 4      # number of items per testlet
TT <- 3     # number of testlets

ITT <- I*TT
b <- round( stats::rnorm( ITT, mean=0, sd=1 ), 2 )
sd0 <- 1 # sd trait
sdt <- seq( 0, 2, len=TT ) # sd testlets

# simulate theta
theta <- stats::rnorm( N, sd=sd0 )
# simulate testlets
ut <- matrix(0,nrow=N, ncol=TT )
for (tt in 1:TT){
```

```
    ut[,tt] <- stats::rnorm( N, sd=sdt[tt] )
}
ut <- ut[, rep(1:TT,each=I) ]
# calculate response probability
prob <- matrix( stats::pnorm( theta + ut + matrix( b, nrow=N, ncol=ITT,
            byrow=TRUE ) ), N, ITT)
Y <- (matrix( stats::runif(N*ITT), N, ITT) < prob )*1
colMeans(Y)

# define testlets
testlets <- rep(1:TT, each=I )

burnin <- 300
iter <- 1000

#***
# Model 1: 1PNO model (without testlet structure)
mod1 <- sirt::mcmc.3pno.testlet( dat=Y,  est.slope=FALSE, est.guess=FALSE,
            burnin=burnin, iter=iter, testlets=testlets )
summary(mod1)

summ1 <- mod1$summary.mcmcobj
# compare item parameters
cbind( b, summ1[ grep("b", summ1$parameter ), "Mean" ] )
# Testlet standard deviations
cbind( sdt, summ1[ grep("sigma\.testlet", summ1$parameter ), "Mean" ] )

#***
# Model 2: 1PNO model (without testlet structure)
mod2 <- sirt::mcmc.3pno.testlet( dat=Y,  est.slope=TRUE, est.guess=FALSE,
           burnin=burnin, iter=iter, testlets=testlets )
summary(mod2)

summ2 <- mod2$summary.mcmcobj
# compare item parameters
cbind( b, summ2[ grep("b\[", summ2$parameter ), "Mean" ] )
# item discriminations
cbind( sd0, summ2[ grep("a\[", summ2$parameter ), "Mean" ] )
# Testlet standard deviations
cbind( sdt, summ2[ grep("sigma\.testlet", summ2$parameter ), "Mean" ] )

#############################################################################
# EXAMPLE 3: Simulated data according to the 2PNO testlet model
#############################################################################
set.seed(678)

N <- 3000    # number of persons
I <- 3      # number of items per testlet
TT <- 5    # number of testlets

ITT <- I*TT
b <- round( stats::rnorm( ITT, mean=0, sd=1 ), 2 )
a <- round( stats::runif( ITT, 0.5, 2 ),2)
```

```
sdt <- seq( 0, 2, len=TT ) # sd testlets
sd0 <- 1

# simulate theta
theta <- stats::rnorm( N, sd=sd0 )
# simulate testlets
ut <- matrix(0,nrow=N, ncol=TT )
for (tt in 1:TT){
   ut[,tt] <- stats::rnorm( N, sd=sdt[tt] )
}
ut <- ut[, rep(1:TT,each=I) ]
# calculate response probability
bM <- matrix( b, nrow=N, ncol=ITT, byrow=TRUE )
aM <- matrix( a, nrow=N, ncol=ITT, byrow=TRUE )
prob <- matrix( stats::pnorm( aM*theta + ut + bM ), N, ITT)
Y <- (matrix( stats::runif(N*ITT), N, ITT) < prob )*1
colMeans(Y)

# define testlets
testlets <- rep(1:TT, each=I )

burnin <- 500
iter <- 1500

#***
# Model 1: 2PNO model
mod1 <- sirt::mcmc.3pno.testlet( dat=Y,  est.slope=TRUE, est.guess=FALSE,
             burnin=burnin, iter=iter, testlets=testlets )
summary(mod1)

summ1 <- mod1$summary.mcmcobj
# compare item parameters
cbind( b, summ1[ grep("b\[", summ1$parameter ), "Mean" ] )
# item discriminations
cbind( a, summ1[ grep("a\[", summ1$parameter ), "Mean" ] )
# Testlet standard deviations
cbind( sdt, summ1[ grep("sigma\.testlet", summ1$parameter ), "Mean" ] )

## End(Not run)
```

`mcmc.list.descriptives`

Computation of Descriptive Statistics for a `mcmc.list` *Object*

Description

Computation of descriptive statistics, Rhat convergence statistic and MAP for a `mcmc.list` object. The Rhat statistic is computed by splitting one Monte Carlo chain into three segments of equal length. The MAP is the mode estimate of the posterior distribution which is approximated by the mode of the kernel density estimate.

Usage

```
mcmc.list.descriptives( mcmcobj, quantiles=c(.025,.05,.1,.5,.9,.95,.975) )
```

Arguments

mcmcobj	Object of class mcmc.list
quantiles	Quantiles to be calculated for all parameters

Value

A data frame with descriptive statistics for all parameters in the mcmc.list object.

See Also

See mcmclist2coda for writing an object of class mcmc.list into a coda file (see also the **coda** package).

Examples

```
## Not run:
miceadds::library_install("coda")
miceadds::library_install("R2WinBUGS")

#############################################################################
# EXAMPLE 1: Logistic regression
#############################################################################

#***************************************
# (1) simulate data
set.seed(8765)
N <- 500
x1 <- stats::rnorm(N)
x2 <- stats::rnorm(N)
y <- 1*( stats::plogis( -.6 + .7*x1 + 1.1 *x2 ) > stats::runif(N) )

#***************************************
# (2) estimate logistic regression with glm
mod <- stats::glm( y ~ x1 + x2, family="binomial" )
summary(mod)

#***************************************
# (3) estimate model with rcppbugs package
b <- rcppbugs::mcmc.normal( stats::rnorm(3),mu=0,tau=0.0001)
y.hat <- rcppbugs::deterministic(function(x1,x2,b) {
             stats::plogis( b[1] + b[2]*x1 + b[3]*x2 ) }, x1, x2, b)
y.lik <- rcppbugs::mcmc.bernoulli( y, p=y.hat, observed=TRUE)
m <- rcppbugs::create.model(b, y.hat, y.lik)

#*** estimate model in rcppbugs; 5000 iterations, 1000 burnin iterations
ans <- rcppbugs::run.model(m, iterations=5000, burn=1000, adapt=1000, thin=5)
print(rcppbugs::get.ar(ans))     # get acceptance rate
```

```
print(apply(ans[["b"]],2,mean))  # get means of posterior

#*** convert rcppbugs into mcmclist object
mcmcobj <- data.frame( ans$b  )
colnames(mcmcobj) <- paste0("b",1:3)
mcmcobj <- as.matrix(mcmcobj)
class(mcmcobj) <- "mcmc"
attr(mcmcobj, "mcpar") <- c( 1, nrow(mcmcobj), 1 )
mcmcobj <- coda::as.mcmc.list( mcmcobj )

# plot results
plot(mcmcobj)

# summary
summ1 <-  sirt::mcmc.list.descriptives( mcmcobj )
summ1

## End(Not run)
```

---

mcmc_coef *Some Methods for Objects of Class* mcmc.list

Description

Some methods for objects of class mcmc.list created from the **coda** package.

Usage

```
## coefficients
mcmc_coef(mcmcobj, exclude="deviance")

## covariance matrix
mcmc_vcov(mcmcobj, exclude="deviance")

## confidence interval
mcmc_confint( mcmcobj, parm, level=.95, exclude="deviance" )

## summary function
mcmc_summary( mcmcobj, quantiles=c(.025,.05,.50,.95,.975) )

## plot function
mcmc_plot(mcmcobj, ...)

## inclusion of derived parameters in mcmc object
mcmc_derivedPars( mcmcobj, derivedPars )

## Wald test for parameters
mcmc_WaldTest( mcmcobj, hypotheses )
```

```
## S3 method for class 'mcmc_WaldTest'
summary(object, digits=3, ...)
```

Arguments

mcmcobj	Objects of class mcmc.list as created by coda::mcmc
exclude	Vector of parameters which should be excluded in calculations
parm	Optional vector of parameters
level	Confidence level
quantiles	Vector of quantiles to be computed.
...	Parameters to be passed to mcmc_plot. See LAM::plot.amh for arguments.
derivedPars	List with derived parameters (see examples).
hypotheses	List with hypotheses of the form $g_i(\boldsymbol{\theta}) = 0$.
object	Object of class mcmc_WaldTest.
digits	Number of digits used for rounding.

See Also

coda::mcmc

Examples

```
## Not run:
#############################################################################
# EXAMPLE 1: Logistic regression in rcppbugs package
#############################################################################


#**************************************
# (1) simulate data
set.seed(8765)
N <- 500
x1 <- stats::rnorm(N)
x2 <- stats::rnorm(N)
y <- 1*( stats::plogis( -.6 + .7*x1 + 1.1 *x2 ) > stats::runif(N) )

#**************************************
# (2) estimate logistic regression with glm
mod <- stats::glm( y ~ x1 + x2, family="binomial" )
summary(mod)

#**************************************
# (3) estimate model with rcppbugs package
library(rcppbugs)
b <- rcppbugs::mcmc.normal( stats::rnorm(3),mu=0,tau=0.0001)
y.hat <- rcppbugs::deterministic( function(x1,x2,b){
                stats::plogis( b[1] + b[2]*x1 + b[3]*x2 ) },
                  x1, x2, b)
```

```
y.lik <- rcppbugs::mcmc.bernoulli( y, p=y.hat, observed=TRUE)
model <- rcppbugs::create.model(b, y.hat, y.lik)

#*** estimate model in rcppbugs; 5000 iterations, 1000 burnin iterations
n.burnin <- 500 ; n.iter <- 2000 ; thin <- 2
ans <- rcppbugs::run.model(model, iterations=n.iter, burn=n.burnin, adapt=200, thin=thin)
print(rcppbugs::get.ar(ans)) # get acceptance rate
print(apply(ans[["b"]],2,mean)) # get means of posterior

#*** convert rcppbugs into mcmclist object
mcmcobj <- data.frame( ans$b )
colnames(mcmcobj) <- paste0("b",1:3)
mcmcobj <- as.matrix(mcmcobj)
class(mcmcobj) <- "mcmc"
attr(mcmcobj, "mcpar") <- c( n.burnin+1, n.iter, thin )
mcmcobj <- coda::mcmc( mcmcobj )

# coefficients, variance covariance matrix and confidence interval
mcmc_coef(mcmcobj)
mcmc_vcov(mcmcobj)
mcmc_confint( mcmcobj, level=.90 )

# summary and plot
mcmc_summary(mcmcobj)
mcmc_plot(mcmcobj, ask=TRUE)

# include derived parameters in mcmc object
derivedPars <- list( "diff12"=~ I(b2-b1), "diff13"=~ I(b3-b1) )
mcmcobj2 <- sirt::mcmc_derivedPars(mcmcobj, derivedPars=derivedPars )
mcmc_summary(mcmcobj2)

#*** Wald test for parameters
 # hyp1: b2 - 0.5=0
 # hyp2: b2 * b3=0
hypotheses <- list( "hyp1"=~ I( b2 - .5 ), "hyp2"=~ I( b2*b3 ) )
test1 <- sirt::mcmc_WaldTest( mcmcobj, hypotheses=hypotheses )
summary(test1)

## End(Not run)
```

---

mcmc_Rhat *Computation of the Rhat Statistic from a Single MCMC Chain*

Description

Computes the Rhat statistic from a single MCMC chain.

Usage

```
mcmc_Rhat(mcmc_object, n_splits=3)
```

Arguments

mcmc_object	Object of class mcmc
n_splits	Number of splits for MCMC chain

Value

Numeric vector

Examples

```
## Not run:
#############################################################################
# EXAMPLE 1: Computation Rhat statistic for 2PNO model fitting by MCMC
#############################################################################

data(data.read)

# estimate 2PNO with MCMC with 3000 iterations and 500 burn-in iterations
mod <- sirt::mcmc.2pno( dat=data.read, iter=1000, burnin=100 )
# plot MCMC chains
plot( mod$mcmcobj, ask=TRUE )
# compute Rhat statistics
round( sirt::mcmc_Rhat( mod$mcmcobj[[1]] ), 3 )

## End(Not run)
```

---

mcmclist2coda *Write Coda File from an Object of Class* mcmc.list

---

Description

This function writes a coda file from an object of class mcmc.list. Note that only first entry (i.e. one chain) will be processed.

Usage

```
mcmclist2coda(mcmclist, name, coda.digits=5)
```

Arguments

mcmclist	An object of class mcmc.list.
name	Name of the coda file to be written
coda.digits	Number of digits after decimal in the coda file

Value

The coda file and a corresponding index file are written into the working directory.

Examples

```
## Not run:
#############################################################################
# EXAMPLE 1: MCMC estimation 2PNO dataset Reading
#############################################################################

data(data.read)
# estimate 2PNO with MCMC with 3000 iterations and 500 burn-in iterations
mod <- sirt::mcmc.2pno( dat=data.read, iter=3000, burnin=500 )
# plot MCMC chains
plot( mod$mcmcobj, ask=TRUE )
# write sampled chains into codafile
mcmclist2coda( mod$mcmcobj, name="dataread_2pl" )

## End(Not run)
```

`md.pattern.sirt` *Response Pattern in a Binary Matrix*

Description

Computes different statistics of the response pattern in a binary matrix.

Usage

```
md.pattern.sirt(dat)
```

Arguments

`dat`	A binary data matrix

Value

A list with following entries:

`dat`	Original dataset
`dat.resp1`	Indices for responses of 1's
`dat.resp0`	Indices for responses of 0's
`resp_patt`	Vector of response patterns
`unique_resp_patt`	Unique response patterns
`unique_resp_patt_freq`	Frequencies of unique response patterns
`unique_resp_patt_firstobs`	First observation in original dataset `dat` of a unique response pattern
`freq1`	Frequencies of 1's
`freq0`	Frequencies of 0's
`dat.ordered`	Dataset according to response patterns

See Also

See also the `md.pattern` function in the **mice** package.

Examples

```
#############################################################################
# EXAMPLE 1: Response patterns
#############################################################################
set.seed(7654)
N <- 21         # number of rows
I <- 4          # number of columns
dat <- matrix( 1*( stats::runif(N*I) > .3 ), N, I )
res <- sirt::md.pattern.sirt(dat)
# plot of response patterns
res$dat.ordered
image( z=t(res$dat.ordered), y=1:N, x=1:I, xlab="Items", ylab="Persons")
# 0's are yellow and 1's are red

#############################################################################
# EXAMPLE 2: Item response patterns for dataset data.read
#############################################################################

data(data.read)
dat <- data.read  ; N <- nrow(dat) ; I <- ncol(dat)
# order items according to p values
dat <- dat[, order(colMeans(dat, na.rm=TRUE )) ]
# analyzing response pattern
res <- sirt::md.pattern.sirt(dat)
res$dat.ordered
image( z=t(res$dat.ordered), y=1:N, x=1:I, xlab="Items", ylab="Persons")
```

`mgsem` *Estimation of Multiple-Group Structural Equation Models*

Description

Estimates a multiple-group structural equation model. The function allows arbitrary prior distributions on model parameters and regularized estimation with the SCAD and the LASSO penalty. Moreover, it can also conduct robust moment estimation using the L_p loss function $\rho(x) = |x|^p$ for $p \geq 0$. See Robitzsch (2023) for more details.

Usage

```
mgsem(suffstat, model, data=NULL, group=NULL, weights=NULL, estimator="ML",
     p_me=2, p_pen=1, pen_type="scad", diffpar_pen=NULL, pen_sample_size=TRUE,
     a_scad=3.7, eps_approx=0.001, comp_se=TRUE, se_delta_formula=FALSE,
     prior_list=NULL, hessian=TRUE, fixed_parms=FALSE, cd=FALSE,
    cd_control=list(maxiter=20, tol=5*1e-04, interval_length=0.05, method="exact"),
     partable_start=NULL, num_approx=FALSE, technical=NULL, control=list())
```

Arguments

suffstat	List containing sufficient statistics
model	Model specification, see examples. Can have entries est, index, lower, upper, prior, pen_l2, pen_lp, pen_difflp. Each entry can be defined for model matrices ALPHA, NU, LAM, PHI, and PSI.
data	Optional data frame
group	Optional vector of group identifiers
weights	Optional vector of sampling weights
estimator	Character. Can be either "ML" for maximum likelihood fitting function or "ME" for robust moment estimation.
p_me	Power in L_p loss function for robust moment estimation
p_pen	Power for penalty in regularized estimation. For regular LASSO and SCAD penalty functions, it is $p=1$.
pen_type	Penalty type. Can be either "scad" or "lasso".
diffpar_pen	List containing values of regularization parameters in fused lasso estimation
pen_sample_size	List containing values for sample sizes for regularized estimation
a_scad	Parameter a used in SCAD penalty
eps_approx	Approximation value for nondifferentiable robust moment fitting function or penalty function
comp_se	Logical indicating whether standard errors should be computed
se_delta_formula	Logical indicating whether standard errors should be computed according to the delta formula
prior_list	List containing specifications of the prior distributions
hessian	Logical indicating whether the Hessian matrix should be computed
fixed_parms	Logical indicating whether all model parameters should be fixed
cd	Logical indicating whether coordinate descent should be used for estimation
cd_control	Control parameters for coordinate descent estimation
partable_start	Starting values for parameter estimation
num_approx	Logical indicating whether derivatives should be computed based on numerical differentiation
technical	Parameters used for optimization in sirt_optimizer
control	Control paramaters for optimization

Details

[MORE INFORMATION TO BE ADDED]

Value

A list with following values

`coef`	Coeffients
`vcov`	Variance matrix
`se`	Vector of standard errors
`partable`	Parameter table
`model`	Specified model
`opt_res`	Result from optimization
`opt_value`	Value of fitting function
`residuals`	Residuals of sufficient statistics
`ic`	Information criteria
`technical`	Specifications of optimizer
`suffstat_vcov`	Variance matrix of sufficient statistics
`me_delta_method`	Input and output matrices for delta method if `estimator="ME"`
`data_proc`	Processed data
`case_ll`	Casewise log-likelihood function
`...`	Further values

References

Robitzsch, A. (2023). Model-robust estimation of multiple-group structural equation models. *Algorithms, 16*(4), 210. doi:10.3390/a16040210

Examples

```
## Not run:
#############################################################################
# EXAMPLE 1: Noninvariant item intercepts in a multiple-group SEM
#############################################################################

#---- simulate data
set.seed(65)
G <- 3  # number of groups
I <- 5  # number of items
# define lambda and nu parameters
lambda <- matrix(1, nrow=G, ncol=I)
nu <- matrix(0, nrow=G, ncol=I)
err_var <- matrix(1, nrow=G, ncol=I)

# define extent of noninvariance
dif_int <- .5

#- 1st group: N(0,1)
nu[1,4] <- dif_int
```

```
#- 2nd group: N(0.3,1.5)
gg <- 2 ;
nu[gg,1] <- -dif_int
#- 3nd group: N(.8,1.2)
gg <- 3
nu[gg,2] <- -dif_int
#- define distributions of groups
mu <- c(0,.3,.8)
sigma <- sqrt(c(1,1.5,1.2))
N <- rep(1000,3) # sample sizes per group

exact <- FALSE
suffstat <- sirt::invariance_alignment_simulate(nu, lambda, err_var, mu, sigma, N,
                output="suffstat", groupwise=TRUE, exact=exact)

#---- model specification

# model specifications joint group
est <- list(
        ALPHA=matrix( c(0), ncol=1),
        NU=matrix( 0, nrow=I, ncol=1),
        LAM=matrix(1, nrow=I, ncol=1),
        PHI=matrix(0,nrow=1,ncol=1),
        PSI=diag(rep(1,I))
        )

# parameter index
index <- list(
        ALPHA=0*est$ALPHA,
        NU=1+0*est$NU,
        LAM=1+0*est$LAM,
        PHI=0*est$PHI,
        PSI=diag(1,I)
        )

# lower bounds
lower <- list(
        PSI=diag(rep(0.01,I)), PHI=matrix(0.01,1,1)
        )

#*** joint parameters
group0 <- list(est=est, index=index, lower=lower)

#*** group1
est <- list(
        ALPHA=matrix( c(0), ncol=1),
        NU=matrix( 0, nrow=I, ncol=1),
        LAM=matrix(0, nrow=I, ncol=1),
        PHI=matrix(1,nrow=1,ncol=1)
            )

# parameter index
index <- list(
```

```
        ALPHA=0*est$ALPHA,
        NU=0*est$NU,
        LAM=1*est$LAM,
        PHI=0*est$PHI
        )

group1 <- list(est=est, index=index, lower=lower)

#*** group 2 and group 3

# modify parameter index
index$ALPHA <- 1+0*est$ALPHA
index$PHI <- 1+0*est$PHI
group3 <- group2 <- list(est=est, index=index, lower=lower)

#*** define model
model <- list(group0=group0, group1=group1, group2=group2, group3=group3)

#-- estimate model with ML
res1 <- sirt::mgsem( suffstat=suffstat, model=model2, eps_approx=1e-4, estimator="ML",
                    technical=list(maxiter=500, optimizer="optim"),
                    hessian=FALSE, comp_se=FALSE, control=list(trace=1) )
str(res1)

#-- robust moment estimation with p=0.5

optimizer <- "optim"
technical <- list(maxiter=500, optimizer=optimizer)
eps_approx <- 1e-3

res2 <- sirt::mgsem( suffstat=suffstat, model=res1$model, p_me=0.5,
                    eps_approx=eps_approx, estimator="ME", technical=technical,
                    hessian=FALSE, comp_se=FALSE, control=list(trace=1) )

#---- regularized estimation

nu_lam <- 0.1    # regularization parameter

# redefine model
define_model <- function(model, nu_lam)
{
    pen_lp <- list( NU=nu_lam+0*model$group1$est$NU)
    ee <- "group1"
    for (ee in c("group1","group2","group3"))
    {
        model[[ee]]$index$NU <- 1+0*index$NU
        model[[ee]]$pen_lp <- pen_lp
    }
    return(model)
}

model3 <- define_model(model=model, nu_lam=nu_lam)
pen_type <- "scad"
```

```
res3 <- sirt::mgsem( suffstat=suffstat, model=model3, p_pen=1, pen_type=pen_type,
                    eps_approx=eps_approx, estimator="ML",
                    technical=list(maxiter=500, optimizer="optim"),
                    hessian=FALSE, comp_se=FALSE, control=list(trace=1) )
str(res3)

## End(Not run)
```

`mirt.specify.partable` *Specify or modify a Parameter Table in* **mirt**

Description

Specify or modify a parameter table in **mirt**.

Usage

```
mirt.specify.partable(mirt.partable, parlist, verbose=TRUE)
```

Arguments

`mirt.partable`	Parameter table in **mirt** package
`parlist`	List of parameters which are used for specification in the parameter table. See Examples.
`verbose`	An optional logical indicating whether the some warnings should be printed.

Value

A modified parameter table

Author(s)

Alexander Robitzsch, Phil Chalmers

Examples

```
#############################################################################
# EXAMPLE 1: Modifying a parameter table for single group
#############################################################################

library(mirt)
data(LSAT7,package="mirt")
data <- mirt::expand.table(LSAT7)

mirt.partable <- mirt::mirt(data, 1, pars="values")
colnames(mirt.partable)
## > colnames(mirt.partable) [1] 'group' 'item' 'class' 'name' 'parnum' 'value'
##   'lbound' 'ubound' 'est' 'prior.type' 'prior_1' 'prior_2'
```

```
# specify some values of item parameters
value <- data.frame(d=c(0.7, -1, NA), a1=c(1, 1.2, 1.3), g=c(NA, 0.25, 0.25))
rownames(value) <- c("Item.1", "Item.4", "Item.3")

# fix some item paramters
est1 <- data.frame(d=c(TRUE, NA), a1=c(FALSE, TRUE))
rownames(est1) <- c("Item.4", "Item.3")

# estimate all guessing parameters
est2 <- data.frame(g=rep(TRUE, 5))
rownames(est2) <- colnames(data)

# prior distributions
prior.type <- data.frame(g=rep("norm", 4))
rownames(prior.type) <- c("Item.1", "Item.2", "Item.4", "Item.5")
prior_1 <- data.frame(g=rep(-1.38, 4))
rownames(prior_1) <- c("Item.1", "Item.2", "Item.4", "Item.5")
prior_2 <- data.frame(g=rep(0.5, 4))
rownames(prior_2) <- c("Item.1", "Item.2", "Item.4", "Item.5")

# misspecify some entries
rownames(prior_2)[c(3,2)] <- c("A", "B")
rownames(est1)[2] <- c("B")

# define complete list with parameter specification
parlist <- list(value=value, est=est1, est=est2, prior.type=prior.type,
      prior_1=prior_1, prior_2=prior_2)

# modify parameter table
mirt.specify.partable(mirt.partable, parlist)
```

`mirt.wrapper` *Some Functions for Wrapping with the* **mirt** *Package*

Description

Some functions for wrapping with the **mirt** package.

Usage

```
# extract coefficients
mirt.wrapper.coef(mirt.obj)

# summary output
mirt_summary(object, digits=4, file=NULL, ...)

# extract posterior, likelihood, ...
mirt.wrapper.posterior(mirt.obj, weights=NULL, group=NULL)
```

```
## S3 method for class 'SingleGroupClass'
IRT.likelihood(object, ...)
## S3 method for class 'MultipleGroupClass'
IRT.likelihood(object, ...)
## S3 method for class 'SingleGroupClass'
IRT.posterior(object, ...)
## S3 method for class 'MultipleGroupClass'
IRT.posterior(object, ...)
## S3 method for class 'SingleGroupClass'
IRT.expectedCounts(object, ...)
## S3 method for class 'MultipleGroupClass'
IRT.expectedCounts(object, ...)

# S3 method for extracting item response functions
## S3 method for class 'SingleGroupClass'
IRT.irfprob(object, ...)
## S3 method for class 'MultipleGroupClass'
IRT.irfprob(object, group=1, ...)

# compute factor scores
mirt.wrapper.fscores(mirt.obj, weights=NULL)

# convenience function for itemplot
mirt.wrapper.itemplot( mirt.obj, ask=TRUE, ...)
```

Arguments

mirt.obj	A fitted model in **mirt** package
object	A fitted object in **mirt** package of class SingleGroupClass or MultipleGroupClass.
group	Group index for IRT.irfprob (only applicable for object of class MultipleGroupClass)
digits	Number of digits after decimal used for rounding
file	File name for sinking summary output
weights	Optional vector of student weights
ask	Optional logical indicating whether each new plot should be confirmed.
...	Further arguments to be passed.

Details

The function mirt.wrapper.coef collects all item parameters in a data frame.

The function mirt.wrapper.posterior extracts the individual likelihood, individual likelihood and expected counts. This function does not yet cover the case of multiple groups.

The function mirt.wrapper.fscores computes factor scores EAP, MAP and MLE. The factor scores are computed on the discrete grid of latent traits (contrary to the computation in mirt) as specified in mirt.obj@Theta. This function does also not work for multiple groups.

The function mirt.wrapper.itemplot displays all item plots after each other.

Value

Function `mirt.wrapper.coef` – List with entries

`coef`	Data frame with item parameters
`GroupPars`	Data frame or list with distribution parameters

Function `mirt.wrapper.posterior` – List with entries

`theta.k`	Grid of theta points
`pi.k`	Trait distribution on `theta.k`
`f.yi.qk`	Individual likelihood
`f.qk.yi`	Individual posterior
`n.ik`	Expected counts
`data`	Used dataset

Function `mirt.wrapper.fscores` – List with entries

`person`	Data frame with person parameter estimates (factor scores) EAP, MAP and MLE for all dimensions.
`EAP.rel`	EAP reliabilities

Examples for the mirt Package

1. Latent class analysis (`data.read`, Model 7)
2. Mixed Rasch model (`data.read`, Model 8)
3. Located unidimensional and multidimensional latent class models / Multidimensional latent class IRT models (`data.read`, Model 12; `rasch.mirtlc`, Example 4)
4. Multidimensional IRT model with discrete latent traits (`data.read`, Model 13)
5. DINA model (`data.read`, Model 14; `data.dcm`, **CDM**, Model 1m)
6. Unidimensional IRT model with non-normal distribution (`data.read`, Model 15)
7. Grade of membership model (`gom.em`, Example 2)
8. Rasch copula model (`rasch.copula2`, Example 5)
9. Additive GDINA model (`data.dcm`, **CDM**, Model 6m)
10. Longitudinal Rasch model (`data.long`, Model 3)
11. Normally distributed residuals (`data.big5`, Example 1, Model 5)
12. Nedelsky model (`nedelsky.irf`, Examples 1, 2)
13. Beta item response model (`brm.irf`, Example 1)

See Also

See the **mirt** package manual for more information.

See for the main estimation functions in **mirt**: `mirt::mirt`, `mirt::multipleGroup` and `mirt::bfactor`.

See `mirt::coef-method` for extracting coefficients.

See `mirt::mod2values` for collecting parameter values in a mirt parameter table.

See `lavaan2mirt` for converting `lavaan` syntax to `mirt` syntax.

See `tam2mirt` for converting fitted `tam` models into `mirt` objects.

See also `CDM::IRT.likelihood`, `CDM::IRT.posterior` and `CDM::IRT.irfprob` for general extractor functions.

Examples

```
## Not run:
# A development version can be installed from GitHub
if (FALSE){ # default is set to FALSE, use the installed version
   library(devtools)
   devtools::install_github("philchalmers/mirt")
         }
# now, load mirt
library(mirt)

#############################################################################
# EXAMPLE 1: Extracting item parameters and posterior LSAT data
#############################################################################

data(LSAT7, package="mirt")
data <- mirt::expand.table(LSAT7)

#*** Model 1: 3PL model for item 5 only, other items 2PL
mod1 <- mirt::mirt(data, 1, itemtype=c("2PL","2PL","2PL","2PL","3PL"), verbose=TRUE)
print(mod1)
summary(mod1)
# extracting coefficients
coef(mod1)
mirt.wrapper.coef(mod1)$coef
# summary output
mirt_summary(mod1)
# extract parameter values in mirt
mirt::mod2values(mod1)
# extract posterior
post1 <- sirt::mirt.wrapper.posterior(mod1)
# extract item response functions
probs1 <- IRT.irfprob(mod1)
str(probs1)
# extract individual likelihood
likemod1 <- IRT.likelihood(mod1)
str(likemod1)
# extract individual posterior
postmod1 <- IRT.posterior(mod1)
```

```
str(postmod1)

#*** Model 2: Confirmatory model with two factors
cmodel <- mirt::mirt.model("
        F1=1,4,5
        F2=2,3
        ")
mod2 <- mirt::mirt(data, cmodel, verbose=TRUE)
print(mod2)
summary(mod2)
# extract coefficients
coef(mod2)
mirt.wrapper.coef(mod2)$coef
# extract posterior
post2 <- sirt::mirt.wrapper.posterior(mod2)

############################################################################
# EXAMPLE 2: Extracting item parameters and posterior for differering
#            number of response catagories | Dataset Science
############################################################################

data(Science,package="mirt")
library(psych)
psych::describe(Science)

# modify dataset
dat <- Science
dat[ dat[,1] > 3,1] <- 3
psych::describe(dat)

# estimate generalized partial credit model
mod1 <- mirt::mirt(dat, 1, itemtype="gpcm")
print(mod1)
# extract coefficients
coef(mod1)
mirt.wrapper.coef(mod1)$coef
# extract posterior
post1 <- sirt::mirt.wrapper.posterior(mod1)

############################################################################
# EXAMPLE 3: Multiple group model; simulated dataset from mirt package
############################################################################

#*** simulate data (copy from the multipleGroup manual site in mirt package)
set.seed(1234)
a <- matrix(c(abs( stats::rnorm(5,1,.3)), rep(0,15),abs( stats::rnorm(5,1,.3)),
          rep(0,15),abs( stats::rnorm(5,1,.3))), 15, 3)
d <- matrix( stats::rnorm(15,0,.7),ncol=1)
mu <- c(-.4, -.7, .1)
sigma <- matrix(c(1.21,.297,1.232,.297,.81,.252,1.232,.252,1.96),3,3)
itemtype <- rep("dich", nrow(a))
N <- 1000
dataset1 <- mirt::simdata(a, d, N, itemtype)
```

```
dataset2 <- mirt::simdata(a, d, N, itemtype, mu=mu, sigma=sigma)
dat <- rbind(dataset1, dataset2)
group <- c(rep("D1", N), rep("D2", N))

#group models
model <- mirt::mirt.model("
   F1=1-5
   F2=6-10
   F3=11-15
      ")

# separate analysis
mod_configural <- mirt::multipleGroup(dat, model, group=group, verbose=TRUE)
mirt.wrapper.coef(mod_configural)

# equal slopes (metric invariance)
mod_metric <- mirt::multipleGroup(dat, model, group=group, invariance=c("slopes"),
                verbose=TRUE)
mirt.wrapper.coef(mod_metric)

# equal slopes and intercepts (scalar invariance)
mod_scalar <- mirt::multipleGroup(dat, model, group=group,
          invariance=c("slopes","intercepts","free_means","free_varcov"), verbose=TRUE)
mirt.wrapper.coef(mod_scalar)

# full constraint
mod_fullconstrain <- mirt::multipleGroup(dat, model, group=group,
           invariance=c("slopes", "intercepts", "free_means", "free_var"), verbose=TRUE )
mirt.wrapper.coef(mod_fullconstrain)

################################################################################
# EXAMPLE 4: Nonlinear item response model
################################################################################

data(data.read)
dat <- data.read
# specify mirt model with some interactions
mirtmodel <- mirt.model("
   A=1-4
   B=5-8
   C=9-12
   (A*B)=4,8
   (C*C)=9
   (A*B*C)=12
   " )
# estimate model
res <- mirt::mirt( dat, mirtmodel, verbose=TRUE, technical=list(NCYCLES=3) )
# look at estimated parameters
mirt.wrapper.coef(res)
coef(res)
mirt::mod2values(res)
# model specification
res@model
```

```
#############################################################################
# EXAMPLE 5: Extracting factor scores
#############################################################################

data(data.read)
dat <- data.read
# define lavaan model and convert syntax to mirt
lavmodel <- "
    A=~ a*A1+a*A2+1.3*A3+A4       # set loading of A3 to 1.3
    B=~ B1+1*B2+b3*B3+B4
    C=~ c*C1+C2+c*C3+C4
    A1 | da*t1
    A3 | da*t1
    C4 | dg*t1
    B1 | 0*t1
    B3 | -1.4*t1                 # fix item threshold of B3 to -1.4
    A ~~ B                       # estimate covariance between A and B
    A ~~ .6 * C                  # fix covariance to .6
    B ~~ B                       # estimate variance of B
    A ~ .5*1                     # set mean of A to .5
    B ~ 1                        # estimate mean of B
    "
res <- sirt::lavaan2mirt( dat, lavmodel, verbose=TRUE, technical=list(NCYCLES=3) )
# estimated coefficients
mirt.wrapper.coef(res$mirt)
# extract factor scores
fres <- sirt::mirt.wrapper.fscores(res$mirt)
# look at factor scores
head( round(fres$person,2))
  ##    case   M EAP.Var1 SE.EAP.Var1 EAP.Var2 SE.EAP.Var2 EAP.Var3 SE.EAP.Var3 MLE.Var1
  ##  1    1 0.92     1.26        0.67     1.61        0.60     0.05        0.69     2.65
  ##  2    2 0.58     0.06        0.59     1.14        0.55    -0.80        0.56     0.00
  ##  3    3 0.83     0.86        0.66     1.15        0.55     0.48        0.74     0.53
  ##  4    4 1.00     1.52        0.67     1.57        0.60     0.73        0.76     2.65
  ##  5    5 0.50    -0.13        0.58     0.85        0.48    -0.82        0.55    -0.53
  ##  6    6 0.75     0.41        0.63     1.09        0.54     0.27        0.71     0.00
  ##    MLE.Var2 MLE.Var3 MAP.Var1 MAP.Var2 MAP.Var3
  ##  1     2.65    -0.53     1.06     1.59     0.00
  ##  2     1.06    -1.06     0.00     1.06    -1.06
  ##  3     1.06     2.65     1.06     1.06     0.53
  ##  4     2.65     2.65     1.59     1.59     0.53
  ##  5     0.53    -1.06    -0.53     0.53    -1.06
  ##  6     1.06     2.65     0.53     1.06     0.00
# EAP reliabilities
round(fres$EAP.rel,3)
  ##    Var1  Var2  Var3
  ##   0.574 0.452 0.541

## End(Not run)
```

`mle.pcm.group` *Maximum Likelihood Estimation of Person or Group Parameters in the Generalized Partial Credit Model*

Description

This function estimates person or group parameters in the partial credit model (see Details).

Usage

```
mle.pcm.group(dat, b, a=rep(1, ncol(dat)), group=NULL,
    pid=NULL, adj_eps=0.3, conv=1e-04, maxiter=30)
```

Arguments

`dat`	A numeric $N \times I$ matrix
`b`	Matrix with item thresholds
`a`	Vector of item slopes
`group`	Vector of group identifiers
`pid`	Vector of person identifiers
`adj_eps`	Numeric value which is used in ε adjustment of the likelihood. A value of zero (or a very small $\varepsilon > 0$) corresponds to the usual maximum likelihood estimate.
`conv`	Convergence criterion
`maxiter`	Maximum number of iterations

Details

It is assumed that the generalized partial credit model holds. In case one estimates a person parameter θ_p, the log-likelihood is maximized and the following estimating equation results: (see Penfield & Bergeron, 2005):

$$0 = (\log L)' = \sum_i a_i \cdot [\tilde{x}_{pi} - E(X_{pi}|\theta_p)]$$

where $E(X_{pi}|\theta_p)$ denotes the expected item response conditionally on θ_p.

With the method of ε-adjustment (Bertoli-Barsotti & Punzo, 2012; Bertoli-Barsotti, Lando & Punzo, 2014), the observed item responses x_{pi} are transformed such that no perfect scores arise and bias is reduced. If S_p is the sum score of person p and M_p the maximum score of this person, then the transformed sum scores $\tilde{S}_p$ are

$$\tilde{S}_p = \varepsilon + \frac{M_p - 2\varepsilon}{M_p} S_p$$

However, the adjustment is directly conducted on item responses to also handle the case of the generalized partial credit model with item slope parameters different from 1.

In case one estimates a group parameter θ_g, the following estimating equation is used:

$$0 = (\log L)' = \sum_p \sum_i a_i \cdot [\tilde{x}_{pgi} - E(X_{pgi}|\theta_g)]$$

where persons p are nested within a group g. The ε-adjustment is then performed at the group level, not at the individual level.

Value

A list with following entries:

`person`	Data frame with person or group parameters
`data_adjeps`	Modified dataset according to the ε adjustment.

References

Bertoli-Barsotti, L., & Punzo, A. (2012). Comparison of two bias reduction techniques for the Rasch model. *Electronic Journal of Applied Statistical Analysis, 5*, 360-366.

Bertoli-Barsotti, L., Lando, T., & Punzo, A. (2014). Estimating a Rasch Model via fuzzy empirical probability functions. In D. Vicari, A. Okada, G. Ragozini & C. Weihs (Eds.). *Analysis and Modeling of Complex Data in Behavioral and Social Sciences*, Springer.

Penfield, R. D., & Bergeron, J. M. (2005). Applying a weighted maximum likelihood latent trait estimator to the generalized partial credit model. *Applied Psychological Measurement, 29*, 218-233.

Examples

```
## Not run:
#############################################################################
# EXAMPLE 1: Estimation of a group parameter for only one item per group
#############################################################################

data(data.si01)
dat <- data.si01
# item parameter estimation (partial credit model) in TAM
library(TAM)
mod <- TAM::tam.mml( dat[,2:3], irtmodel="PCM")
# extract item difficulties
b <- matrix( mod$xsi$xsi, nrow=2, byrow=TRUE )
# groupwise estimation
res1 <- sirt::mle.pcm.group( dat[,2:3], b=b, group=dat$idgroup )
# individual estimation
res2 <- sirt::mle.pcm.group( dat[,2:3], b=b  )

#############################################################################
# EXAMPLE 2: Data Reading data.read
#############################################################################

data(data.read)
# estimate Rasch model
mod <- sirt::rasch.mml2( data.read )
score <- rowSums( data.read )
data.read <- data.read[ order(score), ]
score <- score[ order(score) ]
# compare different epsilon-adjustments
res30 <- sirt::mle.pcm.group( data.read, b=matrix( mod$item$b, 12, 1 ),
```

```
               adj_eps=.3 )$person
res10 <- sirt::mle.pcm.group( data.read, b=matrix( mod$item$b, 12, 1 ),
             adj_eps=.1 )$person
res05 <- sirt::mle.pcm.group( data.read, b=matrix( mod$item$b, 12, 1 ),
              adj_eps=.05 )$person
# plot different scorings
plot( score, res05$theta, type="l", xlab="Raw score", ylab=expression(theta[epsilon]),
         main="Scoring with different epsilon-adjustments")
lines( score, res10$theta, col=2, lty=2 )
lines( score, res30$theta, col=4, lty=3 )

## End(Not run)
```

`modelfit.sirt` *Assessing Model Fit and Local Dependence by Comparing Observed and Expected Item Pair Correlations*

Description

This function computes several measures of absolute model fit and local dependence indices for dichotomous item responses which are based on comparing observed and expected frequencies of item pairs (Chen, de la Torre & Zhang, 2013; see `modelfit.cor` for more details).

Usage

```
modelfit.sirt(object)

modelfit.cor.poly( data, probs, theta.k, f.qk.yi)

## S3 method for class 'sirt'
IRT.modelfit(object, mod, ...)
```

Arguments

`object`	An object generated by `rasch.mml2`, `rasch.mirtlc`, `rasch.pml3` (`rasch.pml2`), `smirt`, `R2noharm`, `noharm.sirt`, `gom.em`, `TAM::tam.mml`, `TAM::tam.mml.2pl`, `TAM::tam.fa`, `mirt::mirt`
`data`	Dataset with polytomous item responses
`probs`	Item response probabilities at grid `theta.k`
`theta.k`	Grid of theta vector
`f.qk.yi`	Individual posterior
`mod`	Model name
`...`	Further arguments to be passed

Value

A list with following entries:

`modelfit`	Model fit statistics: `MADcor`: mean of absolute deviations in observed and expected correlations (DiBello et al., 2007) `SRMSR`: standardized mean square root of squared residuals (Maydeu-Olivares, 2013; Maydeu-Olivares & Joe, 2014) `MX2`: Mean of χ^2 statistics of all item pairs (Chen & Thissen, 1997) `MADRESIDCOV`: Mean of absolute deviations of residual covariances (McDonald & Mok, 1995) `MADQ3`: Mean of absolute values of Q_3 statistic (Yen, 1984) `MADaQ3`: Mean of absolute values of centered Q_3 statistic
`itempairs`	Fit of every item pair

Note

The function `modelfit.cor.poly` is just a wrapper to `TAM::tam.modelfit` in the **TAM** package.

References

Chen, W., & Thissen, D. (1997). Local dependence indexes for item pairs using item response theory. *Journal of Educational and Behavioral Statistics, 22*, 265-289.

DiBello, L. V., Roussos, L. A., & Stout, W. F. (2007) Review of cognitively diagnostic assessment and a summary of psychometric models. In C. R. Rao and S. Sinharay (Eds.), *Handbook of Statistics*, Vol. 26 (pp. 979–1030). Amsterdam: Elsevier.

Maydeu-Olivares, A. (2013). Goodness-of-fit assessment of item response theory models (with discussion). *Measurement: Interdisciplinary Research and Perspectives, 11*, 71-137.

Maydeu-Olivares, A., & Joe, H. (2014). Assessing approximate fit in categorical data analysis. *Multivariate Behavioral Research, 49*, 305-328.

McDonald, R. P., & Mok, M. M.-C. (1995). Goodness of fit in item response models. *Multivariate Behavioral Research, 30*, 23-40.

Yen, W. M. (1984). Effects of local item dependence on the fit and equating performance of the three-parameter logistic model. *Applied Psychological Measurement, 8*, 125-145.

See Also

Supported classes: `rasch.mml2`, `rasch.mirtlc`, `rasch.pml3` (`rasch.pml2`), `smirt`, `R2noharm`, `noharm.sirt`, `gom.em`, `TAM::tam.mml`, `TAM::tam.mml.2pl`, `TAM::tam.fa`, `mirt::mirt`

For more details on fit statistics of this function see `CDM::modelfit.cor`.

Examples

```
## Not run:
#############################################################################
# EXAMPLE 1: Reading data
```

```
#############################################################################
data(data.read)
dat <- data.read
I <- ncol(dat)

#*** Model 1: Rasch model
mod1 <- sirt::rasch.mml2(dat)
fmod1 <- sirt::modelfit.sirt( mod1 )
summary(fmod1)

#*** Model 1b: Rasch model in TAM package
library(TAM)
mod1b <- TAM::tam.mml(dat)
fmod1b <- sirt::modelfit.sirt( mod1b )
summary(fmod1b)

#*** Model 2: Rasch model with smoothed distribution
mod2 <- sirt::rasch.mml2( dat, distribution.trait="smooth3" )
fmod2 <- sirt::modelfit.sirt( mod2 )
summary(fmod2 )

#*** Model 3: 2PL model
mod3 <- sirt::rasch.mml2( dat, distribution.trait="normal", est.a=1:I )
fmod3 <- sirt::modelfit.sirt( mod3 )
summary(fmod3 )

#*** Model 3: 2PL model in TAM package
mod3b <- TAM::tam.mml.2pl( dat )
fmod3b <- sirt::modelfit.sirt(mod3b)
summary(fmod3b)
# model fit in TAM package
tmod3b <- TAM::tam.modelfit(mod3b)
summary(tmod3b)
# model fit in mirt package
library(mirt)
mmod3b <- sirt::tam2mirt(mod3b)   # convert to mirt object
mirt::M2(mmod3b$mirt)         # global fit statistic
mirt::residuals( mmod3b$mirt, type="LD")  # local dependence statistics

#*** Model 4: 3PL model with equal guessing parameter
mod4 <- TAM::rasch.mml2( dat, distribution.trait="smooth3", est.a=1:I, est.c=rep(1,I) )
fmod4 <- sirt::modelfit.sirt( mod4 )
summary(fmod4 )

#*** Model 5: Latent class model with 2 classes
mod5 <- sirt::rasch.mirtlc( dat, Nclasses=2 )
fmod5 <- sirt::modelfit.sirt( mod5 )
summary(fmod5 )

#*** Model 6: Rasch latent class model with 3 classes
mod6 <- sirt::rasch.mirtlc( dat, Nclasses=3, modeltype="MLC1", mmliter=100)
fmod6 <- sirt::modelfit.sirt( mod6 )
summary(fmod6 )
```

```
#*** Model 7: PML estimation
mod7 <- sirt::rasch.pml3( dat )
fmod7 <- sirt::modelfit.sirt( mod7 )
summary(fmod7 )

#*** Model 8: PML estimation
#      Modelling error correlations:
#          joint residual correlations for each item cluster
error.corr <- diag(1,ncol(dat))
itemcluster <- rep( 1:4,each=3 )
for ( ii in 1:3){
    ind.ii <- which( itemcluster==ii )
    error.corr[ ind.ii, ind.ii ] <- ii
        }
mod8 <- sirt::rasch.pml3( dat, error.corr=error.corr )
fmod8 <- sirt::modelfit.sirt( mod8 )
summary(fmod8 )

#*** Model 9: 1PL in smirt
Qmatrix <- matrix( 1, nrow=I, ncol=1 )
mod9 <- sirt::smirt( dat, Qmatrix=Qmatrix )
fmod9 <- sirt::modelfit.sirt( mod9 )
summary(fmod9 )

#*** Model 10: 3-dimensional Rasch model in NOHARM
noharm.path <- "c:/NOHARM"
Q <- matrix( 0, nrow=12, ncol=3 )
Q[ cbind(1:12, rep(1:3,each=4) ) ] <- 1
rownames(Q) <- colnames(dat)
colnames(Q) <- c("A","B","C")
# covariance matrix
P.pattern <- matrix( 1, ncol=3, nrow=3 )
P.init <- 0.8+0*P.pattern
diag(P.init) <- 1
# loading matrix
F.pattern <- 0*Q
F.init <- Q
# estimate model
mod10 <- sirt::R2noharm( dat=dat, model.type="CFA", F.pattern=F.pattern,
            F.init=F.init, P.pattern=P.pattern, P.init=P.init,
            writename="ex4e", noharm.path=noharm.path, dec="," )
fmod10 <- sirt::modelfit.sirt( mod10 )
summary(fmod10)

#*** Model 11: Rasch model in mirt package
library(mirt)
mod11 <- mirt::mirt(dat, 1, itemtype="Rasch",verbose=TRUE)
fmod11 <- sirt::modelfit.sirt( mod11 )
summary(fmod11)
# model fit in mirt package
mirt::M2(mod11)
mirt::residuals(mod11)
```

```
## End(Not run)
```

`monoreg.rowwise` *Monotone Regression for Rows or Columns in a Matrix*

Description

Monotone (isotone) regression for rows (`monoreg.rowwise`) or columns (`monoreg.colwise`) in a matrix.

Usage

```
monoreg.rowwise(yM, wM)

monoreg.colwise(yM, wM)
```

Arguments

`yM`	Matrix with dependent variable for the regression. Values are assumed to be sorted.
`wM`	Matrix with weights for every entry in the `yM` matrix.

Value

Matrix with fitted values

Note

This function is used for fitting the ISOP model (see `isop.dich`).

Author(s)

Alexander Robitzsch

The `monoreg` function from the **fdrtool** package is simply extended to handle matrix input.

See Also

See also the `monoreg` function from the **fdrtool** package.

Examples

```
y <- c(22.5, 23.33, 20.83, 24.25 )
w <- c( 3,3,3,2)
# define matrix input
yM <- matrix( 0, nrow=2, ncol=4 )
wM <- yM
yM[1,] <- yM[2,] <- y
wM[1,] <- w
wM[2,] <- c(1,3,4, 3 )

# fit rowwise monotone regression
monoreg.rowwise( yM, wM )
# compare results with monoreg function from fdrtool package
## Not run:
miceadds::library_install("fdrtool")
fdrtool::monoreg(x=yM[1,], w=wM[1,])$yf
fdrtool::monoreg(x=yM[2,], w=wM[2,])$yf

## End(Not run)
```

---

nedelsky-methods *Functions for the Nedelsky Model*

Description

Functions for simulating and estimating the Nedelsky model (Bechger et al., 2003, 2005). `nedelsky.sim` can be used for simulating the model, `nedelsky.irf` computes the item response function and can be used for example when estimating the Nedelsky model in the **mirt** package or using the `xxirt` function in the **sirt** package.

Usage

```
# simulating the Nedelsky model
nedelsky.sim(theta, b, a=NULL, tau=NULL)

# creating latent responses of the Nedelsky model
nedelsky.latresp(K)

# computing the item response function of the Nedelsky model
nedelsky.irf(Theta, K, b, a, tau, combis, thdim=1)
```

Arguments

`theta`	Unidimensional ability (theta)
`b`	Matrix of category difficulties
`a`	Vector of item discriminations
`tau`	Category attractivity parameters τ (see Bechger et al., 2005)

K	(Maximum) Number of distractors of the used multiple choice items
Theta	Theta vector. Note that the Nedelsky model can be only specified as models with between item dimensionality (defined in thdim).
combis	Latent response classes as produced by nedelsky.latresp.
thdim	Theta dimension at which the item loads

Details

Assume that for item i there exists $K+1$ categories $0, 1, ..., K$. The category 0 denotes the correct alternative. The Nedelsky model assumes that a respondent eliminates all distractors which are thought to be incorrect and guesses the solution from the remaining alternatives. This means, that for item i, K latent variables S_{ik} are defined which indicate whether alternative k has been correctly identified as a distractor. By definition, the correct alternative is never been judged as wrong by the respondent.

Formally, the Nedelsky model assumes a 2PL model for eliminating each of the distractors

$$P(S_{ik} = 1|\theta) = invlogit[a_i(\theta - b_{ik})]$$

where θ is the person ability and b_{ik} are distractor difficulties.

The guessing process of the Nedelsky model is defined as

$$P(X_i = j|\theta, S_{i1}, ..., S_{iK}) = \frac{(1 - S_{ij})\tau_{ij}}{\sum_{k=0}^{K}[(1 - S_{ik})\tau_{ik}]}$$

where τ_{ij} are attractivity parameters of alternative j. By definition τ_{i0} is set to 1. By default, all attractivity parameters are set to 1.

References

Bechger, T. M., Maris, G., Verstralen, H. H. F. M., & Verhelst, N. D. (2003). *The Nedelsky model for multiple-choice items*. CITO Research Report, 2003-5.

Bechger, T. M., Maris, G., Verstralen, H. H. F. M., & Verhelst, N. D. (2005). The Nedelsky model for multiple-choice items. In L. van der Ark, M. Croon, & Sijtsma, K. (Eds.). *New developments in categorical data analysis for the social and behavioral sciences*, pp. 187-206. Mahwah, Lawrence Erlbaum.

Examples

```
## Not run:
#############################################################################
# EXAMPLE 1: Simulated data according to the Nedelsky model
#############################################################################

#*** simulate data
set.seed(123)
I <- 20          # number of items
b <- matrix(NA,I,ncol=3)
b[,1] <- -0.5 + stats::runif( I, -.75, .75 )
b[,2] <- -1.5 + stats::runif( I, -.75, .75 )
```

```
b[,3] <- -2.5 + stats::runif( I, -.75, .75 )
K <- 3           # number of distractors
N <- 2000        # number of persons
# apply simulation function
dat <- sirt::nedelsky.sim( theta=stats::rnorm(N,sd=1.2), b=b )

#*** latent response patterns
K <- 3
combis <- sirt::nedelsky.latresp(K=3)

#*** defining the Nedelsky item response function for estimation in mirt
par <- c( 3, rep(-1,K), 1, rep(1,K+1),1)
names(par) <- c("K", paste0("b",1:K), "a", paste0("tau", 0:K),"thdim")
est <- c( FALSE, rep(TRUE,K), rep(FALSE, K+1 + 2 ) )
names(est) <- names(par)
nedelsky.icc <- function( par, Theta, ncat ){
     K <- par[1]
     b <- par[ 1:K + 1]
     a <- par[ K+2]
     tau <- par[1:(K+1) + (K+2) ]
     thdim <- par[ K+2+K+1 +1 ]
     probs <- sirt::nedelsky.irf( Theta, K=K, b=b, a=a, tau=tau, combis,
                    thdim=thdim  )$probs
     return(probs)
}
name <- "nedelsky"
# create item response function
nedelsky.itemfct <- mirt::createItem(name, par=par, est=est, P=nedelsky.icc)

#*** define model in mirt
mirtmodel <- mirt::mirt.model("
           F1=1-20
           COV=F1*F1
           # define some prior distributions
           PRIOR=(1-20,b1,norm,-1,2),(1-20,b2,norm,-1,2),
                   (1-20,b3,norm,-1,2)
        " )

itemtype <- rep("nedelsky", I )
customItems <- list("nedelsky"=nedelsky.itemfct)
# define parameters to be estimated
mod1.pars <- mirt::mirt(dat, mirtmodel, itemtype=itemtype,
                    customItems=customItems, pars="values")
# estimate model
mod1 <- mirt::mirt(dat,mirtmodel, itemtype=itemtype, customItems=customItems,
               pars=mod1.pars, verbose=TRUE  )
# model summaries
print(mod1)
summary(mod1)
mirt.wrapper.coef( mod1 )$coef
mirt.wrapper.itemplot(mod1,ask=TRUE)

#*****************************************************
```

```
# fit Nedelsky model with xxirt function in sirt

# define item class for xxirt
item_nedelsky <- sirt::xxirt_createDiscItem( name="nedelsky", par=par,
                est=est, P=nedelsky.icc,
                prior=c( b1="dnorm", b2="dnorm", b3="dnorm" ),
                prior_par1=c( b1=-1, b2=-1, b3=-1),
                prior_par2=c(b1=2, b2=2, b3=2) )
customItems <- list( item_nedelsky )

#---- definition theta distribution
#** theta grid
Theta <- matrix( seq(-6,6,length=21), ncol=1 )
#** theta distribution
P_Theta1 <- function( par, Theta, G){
    mu <- par[1]
    sigma <- max( par[2], .01 )
    TP <- nrow(Theta)
    pi_Theta <- matrix( 0, nrow=TP, ncol=G)
    pi1 <- dnorm( Theta[,1], mean=mu, sd=sigma )
    pi1 <- pi1 / sum(pi1)
    pi_Theta[,1] <- pi1
    return(pi_Theta)
}
#** create distribution class
par_Theta <- c( "mu"=0, "sigma"=1 )
customTheta <- sirt::xxirt_createThetaDistribution( par=par_Theta, est=c(FALSE,TRUE),
                  P=P_Theta1 )

#-- create parameter table
itemtype <- rep( "nedelsky", I )
partable <- sirt::xxirt_createParTable( dat, itemtype=itemtype, customItems=customItems)

# estimate model
mod2 <- sirt::xxirt( dat=dat, Theta=Theta, partable=partable, customItems=customItems,
                  customTheta=customTheta)
summary(mod2)
# compare sirt::xxirt and mirt::mirt
logLik(mod2)
mod1@Fit$logLik

############################################################################
# EXAMPLE 2: Multiple choice dataset data.si06
############################################################################

data(data.si06)
dat <- data.si06

#*** create latent responses
combis <- sirt::nedelsky.latresp(K)
I <- ncol(dat)
#*** define item response function
K <- 3
```

```
par <- c( 3, rep(-1,K), 1, rep(1,K+1),1)
names(par) <- c("K", paste0("b",1:K), "a", paste0("tau", 0:K),"thdim")
est <- c( FALSE, rep(TRUE,K), rep(FALSE, K+1 + 2 ) )
names(est) <- names(par)
nedelsky.icc <- function( par, Theta, ncat ){
     K <- par[1]
     b <- par[ 1:K + 1]
     a <- par[ K+2]
     tau <- par[1:(K+1) + (K+2) ]
     thdim <- par[ K+2+K+1 +1 ]
     probs <- sirt::nedelsky.irf( Theta, K=K, b=b, a=a, tau=tau, combis,
                    thdim=thdim  )$probs
     return(probs)
}
name <- "nedelsky"
# create item response function
nedelsky.itemfct <- mirt::createItem(name, par=par, est=est, P=nedelsky.icc)

#*** define model in mirt
mirtmodel <- mirt::mirt.model("
           F1=1-14
           COV=F1*F1
           PRIOR=(1-14,b1,norm,-1,2),(1-14,b2,norm,-1,2),
                   (1-14,b3,norm,-1,2)
        " )

itemtype <- rep("nedelsky", I )
customItems <- list("nedelsky"=nedelsky.itemfct)
# define parameters to be estimated
mod1.pars <- mirt::mirt(dat, mirtmodel, itemtype=itemtype,
                   customItems=customItems, pars="values")

#*** estimate model
mod1 <- mirt::mirt(dat,mirtmodel, itemtype=itemtype, customItems=customItems,
               pars=mod1.pars, verbose=TRUE )
#*** summaries
print(mod1)
summary(mod1)
mirt.wrapper.coef( mod1 )$coef
mirt.wrapper.itemplot(mod1,ask=TRUE)

## End(Not run)
```

---

noharm.sirt *NOHARM Model in* R

Description

The function is an R implementation of the normal ogive harmonic analysis robust method (the NOHARM model; McDonald, 1997). Exploratory and confirmatory multidimensional item response

models for dichotomous data using the probit link function can be estimated. Lower asymptotes (guessing parameters) and upper asymptotes (one minus slipping parameters) can be provided as fixed values.

Usage

```
noharm.sirt(dat, pm=NULL, N=NULL, weights=NULL, Fval=NULL, Fpatt=NULL, Pval=NULL,
  Ppatt=NULL, Psival=NULL, Psipatt=NULL, dimensions=NULL, lower=0, upper=1, wgtm=NULL,
  pos.loading=FALSE, pos.variance=FALSE, pos.residcorr=FALSE, maxiter=1000, conv=1e-6,
   optimizer="nlminb", par_lower=NULL, reliability=FALSE, ...)

## S3 method for class 'noharm.sirt'
summary(object, file=NULL, ...)
```

Arguments

dat	Matrix of dichotomous item responses. This matrix may contain missing data (indicated by NA) but missingness is assumed to be missing completely at random (MCAR). Alternatively, a product-moment matrix pm can be used as input.
pm	Optional product-moment matrix
N	Sample size if pm is provided
weights	Optional vector of student weights.
Fval	Initial or fixed values of the loading matrix $\boldsymbol{F}$.
Fpatt	Pattern matrix of the loading matrix $\boldsymbol{F}$. If elements should be estimated, then an entry of 1 must be included in the pattern matrix. Parameters which should be estimated with equality constraints must be indicated by same integers but values largers than 1.
Pval	Initial or fixed values for the covariance matrix $\boldsymbol{P}$.
Ppatt	Pattern matrix for the covariance matrix $\boldsymbol{P}$.
Psival	Initial or fixed values for the matrix of residual correlations $\boldsymbol{\Psi}$.
Psipatt	Pattern matrix for the matrix of residual correlations $\boldsymbol{\Psi}$.
dimensions	Number of dimensions if an exploratory factor analysis should be estimated.
lower	Fixed vector (or numeric) of lower asymptotes c_i.
upper	Fixed vector (or numeric) of upper asymptotes d_i.
wgtm	Matrix with positive entries which indicates by a positive entry which item pairs should be used for estimation.
pos.loading	An optional logical indicating whether all entries in the loading matrix $\boldsymbol{F}$ should be positive
pos.variance	An optional logical indicating whether all variances (i.e. diagonal entries in $\boldsymbol{P}$) should be positive
pos.residcorr	An optional logical indicating whether all entries in the matrix of residual correlations $\boldsymbol{\Psi}$ should be positive
par_lower	Optional vector of lower parameter bounds

`maxiter`	Maximum number of iterations
`conv`	Convergence criterion for parameters
`optimizer`	Optimization function to be used. Can be `"nlminb"` for `stats::nlminb` or `"optim"` for `stats::optim`.
`reliability`	Logical indicating whether reliability should be computed.
`...`	Further arguments to be passed.
`object`	Object of class `noharm.sirt`
`file`	String indicating a file name for summary.

Details

The NOHARM item response model follows the response equation

$$P(X_{pi}=1|\boldsymbol{\theta}_p) = c_i + (d_i - c_i)\Phi(f_{i0} + f_{i1}\theta_{p1} + ... + f_{iD}\theta_{pD})$$

for item responses X_{pi} of person p on item i, $\boldsymbol{F} = (f_{id})$ is a loading matrix and $\boldsymbol{P}$ the covariance matrix of $\boldsymbol{\theta}_p$. The lower asymptotes c_i and upper asymptotes d_i must be provided as fixed values. The response equation can be equivalently written by introducing a latent continuous item response X^*_{pi}

$$X^*_{pi} = f_{i0} + f_{i1}\theta_{p1} + ... + f_{iD}\theta_{pD} + e_{pi}$$

with a standard normally distributed residual e_{pi}. These residuals have a correlation matrix $\boldsymbol{\Psi}$ with ones in the diagonal. In this R implementation of the NOHARM model, correlations between residuals are allowed.

The estimation relies on a Hermite series approximation of the normal ogive item response functions. In more detail, a series expansion

$$\Phi(x) = b_0 + b_1 H_1(x) + b_2 H_2(x) + b_3 H_3(x)$$

is used (McDonald, 1982a). This enables to express cross products $p_{ij} = P(X_i = 1, X_j = 1)$ as a function of unknown model parameters

$$\hat{p}_{ij} = b_{0i}b_{0j} + \sum_{m=1}^{3} b_{mi}b_{mj}\left(\frac{\boldsymbol{f}_i\boldsymbol{P}\boldsymbol{f}_j}{\sqrt{(1+\boldsymbol{f}_i\boldsymbol{P}\boldsymbol{f}_i)(1+\boldsymbol{f}_j\boldsymbol{P}\boldsymbol{f}_j)}}\right)^m$$

where $b_{0i} = p_i = P(X_i = 1) = c_i + (d_i - c_i)\Phi(\tau_i)$, $b_{1i} = (d_i - c_i)\phi(\tau_i)$, $b_{2i} = (d_i - c_i)\tau_i\phi(\tau_i)/\sqrt{2}$, and $b_{3i} = (d_i - c_i)(\tau_i^2 - 1)\phi(\tau_i)/\sqrt{6}$.

The least squares criterion $\sum_{i<j}(p_{ij} - \hat{p}_{ij})^2$ is used for estimating unknown model parameters (McDonald, 1982a, 1982b, 1997).

For derivations of standard errors and fit statistics see Maydeu-Olivares (2001) and Swaminathan and Rogers (2016).

For the statistical properties of the NOHARM approach see Knol and Berger (1991), Finch (2011) or Svetina and Levy (2016).

Value

A list. The most important entries are

`tanaka`	Tanaka fit statistic
`rmsr`	RMSR fit statistic
`N.itempair`	Sample size per item pair
`pm`	Product moment matrix
`wgtm`	Matrix of weights for each item pair
`sumwgtm`	Sum of lower triangle matrix `wgtm`
`lower`	Lower asymptotes
`upper`	Upper asymptotes
`residuals`	Residual matrix from approximation of the `pm` matrix
`final.constants`	Final constants
`factor.cor`	Covariance matrix
`thresholds`	Threshold parameters
`uniquenesses`	Uniquenesses
`loadings`	Matrix of standardized factor loadings (delta parametrization)
`loadings.theta`	Matrix of factor loadings $\boldsymbol{F}$ (theta parametrization)
`residcorr`	Matrix of residual correlations
`Nobs`	Number of observations
`Nitems`	Number of items
`Fpatt`	Pattern loading matrix for $\boldsymbol{F}$
`Ppatt`	Pattern loading matrix for $\boldsymbol{P}$
`Psipatt`	Pattern loading matrix for $\boldsymbol{\Psi}$
`dat`	Used dataset
`dimensions`	Number of dimensions
`iter`	Number of iterations
`Nestpars`	Number of estimated parameters
`chisquare`	Statistic χ^2
`df`	Degrees of freedom
`chisquare_df`	Ratio χ^2/df
`rmsea`	RMSEA statistic
`p.chisquare`	Significance for χ^2 statistic
`omega.rel`	Reliability of the sum score according to Green and Yang (2009)

References

Finch, H. (2011). Multidimensional item response theory parameter estimation with nonsimple structure items. *Applied Psychological Measurement, 35*(1), 67-82. doi:10.1177/0146621610367787

Fraser, C., & McDonald, R. P. (1988). NOHARM: Least squares item factor analysis. *Multivariate Behavioral Research, 23*, 267-269. doi:10.1207/s15327906mbr2302_9

Fraser, C., & McDonald, R. P. (2012). *NOHARM 4 Manual*. http://noharm.niagararesearch.ca/nh4man/nhman.html.

Knol, D. L., & Berger, M. P. (1991). Empirical comparison between factor analysis and multidimensional item response models. *Multivariate Behavioral Research, 26*(3), 457-477. doi:10.1207/s15327906mbr2603_5

Maydeu-Olivares, A. (2001). Multidimensional item response theory modeling of binary data: Large sample properties of NOHARM estimates. *Journal of Educational and Behavioral Statistics, 26*(1), 51-71. doi:10.3102/10769986026001051

McDonald, R. P. (1982a). Linear versus nonlinear models in item response theory. *Applied Psychological Measurement, 6*(4), 379-396. doi:10.1177/014662168200600402

McDonald, R. P. (1982b). *Unidimensional and multidimensional models for item response theory*. I.R.T., C.A.T. conference, Minneapolis, 1982, Proceedings.

McDonald, R. P. (1997). Normal-ogive multidimensional model. In W. van der Linden & R. K. Hambleton (1997): *Handbook of modern item response theory* (pp. 257-269). New York: Springer. doi:10.1007/9781475726916

Svetina, D., & Levy, R. (2016). Dimensionality in compensatory MIRT when complex structure exists: Evaluation of DETECT and NOHARM. *The Journal of Experimental Education, 84*(2), 398-420. doi:10.1080/00220973.2015.1048845

Swaminathan, H., & Rogers, H. J. (2016). Normal-ogive multidimensional models. In W. J. van der Linden (Ed.). *Handbook of item response theory. Volume One: Models* (pp. 167-187). Boca Raton: CRC Press. doi:10.1201/9781315374512

See Also

EAP person parameter estimates can be obtained by `R2noharm.EAP`.

Model fit can be assessed by `modelfit.sirt`.

See `R2noharm` for running the NOHARM software from within R.

See Fraser and McDonald (1988, 2012) for an implementation of the NOHARM model which is available as freeware (http://noharm.niagararesearch.ca/; the link seems to be broken in the meanwhile).

Examples

```
#############################################################################
# EXAMPLE 1: Two-dimensional IRT model with 10 items
#############################################################################

#**** data simulation
set.seed(9776)
N <- 3400 # sample size
```

```
# define difficulties
f0 <- c( .5, .25, -.25, -.5, 0, -.5, -.25, .25, .5, 0 )
I <- length(f0)
# define loadings
f1 <- matrix( 0, I, 2 )
f1[ 1:5,1] <- c(.8,.7,.6,.5, .5)
f1[ 6:10,2] <- c(.8,.7,.6,.5, .5 )
# covariance matrix
Pval <- matrix( c(1,.5,.5,1), 2, 2 )
# simulate theta
library(mvtnorm)
theta <- mvtnorm::rmvnorm(N, mean=c(0,0), sigma=Pval )
# simulate item responses
dat <- matrix( NA, N, I )
for (ii in 1:I){ # ii <- 1
    dat[,ii] <- 1*( stats::pnorm(f0[ii]+theta[,1]*f1[ii,1]+theta[,2]*f1[ii,2])>
                    stats::runif(N) )
        }
colnames(dat) <- paste0("I", 1:I)

#**** Model 1: Two-dimensional CFA with estimated item loadings
# define pattern matrices
Pval <- .3+0*Pval
Ppatt <- 1*(Pval>0)
diag(Ppatt) <- 0
diag(Pval) <- 1
Fval <- .7 * ( f1>0)
Fpatt <- 1 * ( Fval > 0 )
# estimate model
mod1 <- sirt::noharm.sirt( dat=dat, Ppatt=Ppatt, Fpatt=Fpatt, Fval=Fval, Pval=Pval )
summary(mod1)
# EAP ability estimates
pmod1 <- sirt::R2noharm.EAP(mod1, theta.k=seq(-4,4,len=10) )
# model fit
summary( sirt::modelfit.sirt(mod1) )

## Not run:
#*** compare results with NOHARM software
noharm.path <- "c:/NOHARM"   # specify path for noharm software
mod1a <- sirt::R2noharm( dat=dat, model.type="CFA",  F.pattern=Fpatt, F.init=Fval,
             P.pattern=Ppatt, P.init=Pval, writename="r2noharm_example",
             noharm.path=noharm.path, dec="," )
summary(mod1a)

#**** Model 1c: put some equality constraints
Fpatt[ c(1,4),1] <- 3
Fpatt[ cbind( c(3,7), c(1,2)) ] <- 4
mod1c <- sirt::noharm.sirt( dat=dat, Ppatt=Ppatt, Fpatt=Fpatt, Fval=Fval, Pval=Pval)
summary(mod1c)

#**** Model 2: Two-dimensional CFA with correlated residuals
# define pattern matrix for residual correlation
Psipatt <- 0*diag(I)
```

```
Psipatt[1,2] <- 1
Psival <- 0*Psipatt
# estimate model
mod2 <- sirt::noharm.sirt( dat=dat, Ppatt=Ppatt,Fpatt=Fpatt, Fval=Fval, Pval=Pval,
            Psival=Psival, Psipatt=Psipatt )
summary(mod2)

#**** Model 3: Two-dimensional Rasch model
# pattern matrices
Fval <- matrix(0,10,2)
Fval[1:5,1] <- Fval[6:10,2] <- 1
Fpatt <- 0*Fval
Ppatt <- Pval <- matrix(1,2,2)
Pval[1,2] <- Pval[2,1] <- 0
# estimate model
mod3 <- sirt::noharm.sirt( dat=dat, Ppatt=Ppatt,Fpatt=Fpatt, Fval=Fval, Pval=Pval )
summary(mod3)
# model fit
summary( sirt::modelfit.sirt( mod3 ))

#** compare fit with NOHARM
noharm.path <- "c:/NOHARM"
P.pattern <- Ppatt ; P.init <- Pval
F.pattern <- Fpatt ; F.init <- Fval
mod3b <- sirt::R2noharm( dat=dat, model.type="CFA",
             F.pattern=F.pattern, F.init=F.init, P.pattern=P.pattern,
             P.init=P.init, writename="example_sim_2dim_rasch",
             noharm.path=noharm.path, dec="," )
summary(mod3b)

############################################################################
# EXAMPLE 2: data.read
############################################################################

data(data.read)
dat <- data.read
I <- ncol(dat)

#**** Model 1: Unidimensional Rasch model
Fpatt <- matrix( 0, I, 1 )
Fval <- 1 + 0*Fpatt
Ppatt <- Pval <- matrix(1,1,1)
# estimate model
mod1 <- sirt::noharm.sirt( dat=dat, Ppatt=Ppatt,Fpatt=Fpatt, Fval=Fval, Pval=Pval )
summary(mod1)
plot(mod1)    # semPaths plot

#**** Model 2: Rasch model in which item pairs within a testlet are excluded
wgtm <- matrix( 1, I, I )
wgtm[1:4,1:4] <- wgtm[5:8,5:8] <- wgtm[ 9:12, 9:12] <- 0
# estimation
mod2 <- sirt::noharm.sirt(dat=dat, Ppatt=Ppatt,Fpatt=Fpatt, Fval=Fval, Pval=Pval, wgtm=wgtm)
summary(mod2)
```

```
#**** Model 3: Rasch model with correlated residuals
Psipatt <- Psival <- 0*diag(I)
Psipatt[1:4,1:4] <- Psipatt[5:8,5:8] <- Psipatt[ 9:12, 9:12] <- 1
diag(Psipatt) <- 0
Psival <- .6*(Psipatt>0)
# estimation
mod3 <- sirt::noharm.sirt( dat=dat, Ppatt=Ppatt,Fpatt=Fpatt, Fval=Fval, Pval=Pval,
            Psival=Psival, Psipatt=Psipatt )
summary(mod3)
# allow only positive residual correlations
mod3b <- sirt::noharm.sirt( dat=dat, Ppatt=Ppatt, Fpatt=Fpatt, Fval=Fval, Pval=Pval,
            Psival=Psival, Psipatt=Psipatt, pos.residcorr=TRUE)
summary(mod3b)
#* constrain residual correlations
Psipatt[1:4,1:4] <- 2
Psipatt[5:8,5:8] <- 3
Psipatt[ 9:12, 9:12] <- 4
mod3c <- sirt::noharm.sirt( dat=dat, Ppatt=Ppatt, Fpatt=Fpatt, Fval=Fval, Pval=Pval,
            Psival=Psival, Psipatt=Psipatt, pos.residcorr=TRUE)
summary(mod3c)

#**** Model 4: Rasch testlet model
Fval <- Fpatt <- matrix( 0, I, 4 )
Fval[,1] <- Fval[1:4,2] <- Fval[5:8,3] <- Fval[9:12,4 ] <- 1
Ppatt <- Pval <- diag(4)
colnames(Ppatt) <- c("g", "A", "B","C")
Pval <- .5*Pval
# estimation
mod4 <- sirt::noharm.sirt( dat=dat, Ppatt=Ppatt,Fpatt=Fpatt, Fval=Fval, Pval=Pval  )
summary(mod4)
# allow only positive variance entries
mod4b <- sirt::noharm.sirt( dat=dat, Ppatt=Ppatt,Fpatt=Fpatt, Fval=Fval, Pval=Pval,
              pos.variance=TRUE )
summary(mod4b)

#**** Model 5: Bifactor model
Fval <- matrix( 0, I, 4 )
Fval[,1] <- Fval[1:4,2] <- Fval[5:8,3] <- Fval[9:12,4 ] <- .6
Fpatt <- 1 * ( Fval > 0 )
Pval <- diag(4)
Ppatt <- 0*Pval
colnames(Ppatt) <- c("g", "A", "B","C")
# estimation
mod5 <- sirt::noharm.sirt( dat=dat, Ppatt=Ppatt,Fpatt=Fpatt, Fval=Fval, Pval=Pval  )
summary(mod5)
# allow only positive loadings
mod5b <- sirt::noharm.sirt( dat=dat, Ppatt=Ppatt,Fpatt=Fpatt, Fval=Fval, Pval=Pval,
              pos.loading=TRUE )
summary(mod5b)
summary( sirt::modelfit.sirt(mod5b))

#**** Model 6: 3-dimensional Rasch model
```

```
Fval <- matrix( 0, I, 3 )
Fval[1:4,1] <- Fval[5:8,2] <- Fval[9:12,3 ] <- 1
Fpatt <- 0*Fval
Pval <- .6*diag(3)
diag(Pval) <- 1
Ppatt <- 1+0*Pval
colnames(Ppatt) <- c("A", "B","C")
# estimation
mod6 <- sirt::noharm.sirt( dat=dat, Ppatt=Ppatt,Fpatt=Fpatt, Fval=Fval, Pval=Pval  )
summary(mod6)
summary( sirt::modelfit.sirt(mod6) )  # model fit

#**** Model 7: 3-dimensional 2PL model
Fval <- matrix( 0, I, 3 )
Fval[1:4,1] <- Fval[5:8,2] <- Fval[9:12,3 ] <- 1
Fpatt <- Fval
Pval <- .6*diag(3)
diag(Pval) <- 1
Ppatt <- 1+0*Pval
diag(Ppatt) <- 0
colnames(Ppatt) <- c("A", "B","C")
# estimation
mod7 <- sirt::noharm.sirt( dat=dat, Ppatt=Ppatt,Fpatt=Fpatt, Fval=Fval, Pval=Pval  )
summary(mod7)
summary( sirt::modelfit.sirt(mod7) )

#**** Model 8: Exploratory factor analysis with 3 dimensions
# estimation
mod8 <- sirt::noharm.sirt( dat=dat, dimensions=3  )
summary(mod8)

############################################################################
# EXAMPLE 3: Product-moment matrix input, McDonald (1997)
############################################################################

# data from Table 1 of McDonald (1997, p. 266)
pm0 <- "
0.828
0.567 0.658
0.664 0.560 0.772
0.532 0.428 0.501 0.606
0.718 0.567 0.672 0.526 0.843
"
pm <- miceadds::string_to_matrix(x=pm0, as_numeric=TRUE, extend=TRUE)
I <- nrow(pm)
rownames(pm) <- colnames(pm) <- paste0("I", 1:I)

#- Model 1: Unidimensional model
Fval <- matrix(.7, nrow=I, ncol=1)
Fpatt <- 1+0*Fval
Pval <- matrix(1, nrow=1,ncol=1)
Ppatt <- 0*Pval
```

```
mod1 <- sirt::noharm.sirt(pm=pm, N=1000, Fval=Fval, Fpatt=Fpatt, Pval=Pval, Ppatt=Ppatt)
summary(mod1)

#- Model 2: Twodimensional exploratory model
mod2 <- sirt::noharm.sirt(pm=pm, N=1000, dimensions=2)
summary(mod2)

#- Model 3: Unidimensional model with correlated residuals
Psival <- matrix(0, nrow=I, ncol=I)
Psipatt <- 0*Psival
Psipatt[5,1] <- 1

mod3 <- sirt::noharm.sirt(pm=pm, N=1000, Fval=Fval, Fpatt=Fpatt, Pval=Pval, Ppatt=Ppatt,
            Psival=Psival, Psipatt=Psipatt)
summary(mod3)

## End(Not run)
```

`np.dich` *Nonparametric Estimation of Item Response Functions*

Description

This function does nonparametric item response function estimation (Ramsay, 1991).

Usage

```
np.dich(dat, theta, thetagrid, progress=FALSE, bwscale=1.1,
       method="normal")
```

Arguments

`dat`	An $N \times I$ data frame of dichotomous item responses
`theta`	Estimated theta values, for example weighted likelihood estimates from `wle.rasch`
`thetagrid`	A vector of theta values where the nonparametric item response functions shall be evaluated.
`progress`	Display progress?
`bwscale`	The bandwidth parameter h is calculated by the formula $h =$`bwscale`$\cdot N^{-1/5}$
`method`	The default `normal` performs kernel regression with untransformed item responses. The method `binomial` uses nonparametric logistic regression implemented in the **sm** library.

Value

A list with following entries

`dat`	Original data frame

thetagrid	Vector of theta values at which the item response functions are evaluated
theta	Used theta values as person parameter estimates
estimate	Estimated item response functions
...	

References

Ramsay, J. O. (1991). Kernel smoothing approaches to nonparametric item characteristic curve estimation. *Psychometrika, 56*, 611-630.

Examples

```
#############################################################################
# EXAMPLE 1: Reading dataset
#############################################################################
data( data.read )
dat <- data.read

# estimate Rasch model
mod <- sirt::rasch.mml2( dat )
# WLE estimation
wle1 <- sirt::wle.rasch( dat=dat, b=mod$item$b )$theta
# nonparametric function estimation
np1 <- sirt::np.dich( dat=dat, theta=wle1, thetagrid=seq(-2.5, 2.5, len=100 ) )
print( str(np1))
# plot nonparametric item response curves
plot( np1, b=mod$item$b )
```

---

parmsummary_extend *Includes Confidence Interval in Parameter Summary Table*

Description

Includes confidence interval in parameter summary table.

Usage

```
parmsummary_extend(dfr, level=.95, est_label="est", se_label="se",
      df_label="df")
```

Arguments

dfr	Data frame containing parameter summary
level	Significance level
est_label	Label for parameter estimate
se_label	Label for standard error
df_label	Label for degrees of freedom

Value

Extended parameter summary table

See Also

stats::confint

Examples

```
##############################################################################
## EXAMPLE 1: Toy example parameter summary table
##############################################################################

dfr <- data.frame( "parm"=c("b0", "b1" ), "est"=c(0.1, 1.3 ),
                "se"=c(.21, .32) )
print( sirt::parmsummary_extend(dfr), digits=4 )
  ##    parm est   se      t         p lower95 upper95
  ##  1   b0 0.1 0.21 0.4762 6.339e-01 -0.3116  0.5116
  ##  2   b1 1.3 0.32 4.0625 4.855e-05  0.6728  1.9272
```

---

pbivnorm2 *Cumulative Function for the Bivariate Normal Distribution*

Description

This function evaluates the bivariate normal distribution $\Phi_2(x, y; \rho)$ assuming zero means and unit variances. It uses a simple approximation by Cox and Wermuth (1991) with corrected formulas in Hong (1999).

Usage

```
pbivnorm2(x, y, rho)
```

Arguments

x	Vector of x coordinates
y	Vector of y coordinates
rho	Vector of correlations between random normal variates

Value

Vector of probabilities

Note

The function is less precise for correlations near 1 or -1.

References

Cox, D. R., & Wermuth, N. (1991). A simple approximation for bivariate and trivariate normal integrals. *International Statistical Review, 59*(2), 263-269.

Hong, H. P. (1999). An approximation to bivariate and trivariate normal integrals. *Engineering and Environmental Systems, 16*(2), 115-127. doi:10.1080/02630259908970256

See Also

See also the `pbivnorm::pbivnorm` function in the **pbivnorm** package.

Examples

```
library(pbivnorm)
# define input
x <- c(0, 0,  .5, 1, 1  )
y <- c( 0, -.5,  1, 3, .5 )
rho <- c( .2, .8, -.4, .6, .5 )
# compare pbivnorm2 and pbivnorm functions
pbiv2 <- sirt::pbivnorm2( x=x, y=y, rho=rho )
pbiv <- pbivnorm::pbivnorm(  x,  y, rho=rho )
max( abs(pbiv-pbiv2))
  ## [1] 0.0030626
round( cbind( x, y, rho,pbiv, pbiv2 ), 4 )
  ##          x    y  rho   pbiv  pbiv2
  ##   [1,] 0.0  0.0  0.2 0.2820 0.2821
  ##   [2,] 0.0 -0.5  0.8 0.2778 0.2747
  ##   [3,] 0.5  1.0 -0.4 0.5514 0.5514
  ##   [4,] 1.0  3.0  0.6 0.8412 0.8412
  ##   [5,] 1.0  0.5  0.5 0.6303 0.6304
```

`pcm.conversion` *Conversion of the Parameterization of the Partial Credit Model*

Description

Converts a parameterization of the partial credit model (see Details).

Usage

```
pcm.conversion(b)
```

Arguments

`b`	Matrix of item-category-wise intercepts b_{ik} (see Details).

Details

Assume that the input matrix `b` containing parameters b_{ik} is defined according to the following parametrization of the partial credit model

$$P(X_{pi} = k|\theta_p) \propto exp(k\theta_p - b_{ik})$$

if item i possesses K_i categories. The transformed parameterization is defined as

$$b_{ik} = k\delta_i + \sum_{v=1}^{k} \tau_{iv} \quad \text{with} \quad \sum_{k=1}^{K_i} \tau_{ik} = 0$$

The function `pcm.conversion` has the δ and τ parameters as values. The δ parameter is simply $\delta_i = b_{iK_i}/K_i$.

Value

List with the following entries

`delta`	Vector of δ parameters
`tau`	Matrix of τ parameters

Examples

```
## Not run:
#############################################################################
# EXAMPLE 1: Transformation PCM for data.mg
#############################################################################

library(CDM)
data(data.mg,package="CDM")
dat <- data.mg[ 1:1000, paste0("I",1:11) ]

#*** Model 1: estimate partial credit model in parameterization "PCM"
mod1a <- TAM::tam.mml( dat, irtmodel="PCM")
# use parameterization "PCM2"
mod1b <- TAM::tam.mml( dat, irtmodel="PCM2")
summary(mod1a)
summary(mod1b)

# convert parameterization of Model 1a into parameterization of Model 1b
b <- mod1a$item[, c("AXsi_.Cat1","AXsi_.Cat2","AXsi_.Cat3") ]
# compare results
pcm.conversion(b)
mod1b$xsi

## End(Not run)
```

pcm.fit *Item and Person Fit Statistics for the Partial Credit Model*

Description

Computes item and person fit statistics in the partial credit model (Wright & Masters, 1990). The rating scale model is accommodated as a particular partial credit model (see Example 3).

Usage

```
pcm.fit(b, theta, dat)
```

Arguments

b	Matrix with item category parameters (see Examples)
theta	Vector with estimated person parameters
dat	Dataset with item responses

Value

A list with entries

itemfit	Item fit statistics
personfit	Person fit statistics

References

Wright, B. D., & Masters, G. N. (1990). Computation of outfit and infit statistics. *Rasch Measurement Transactions, 3*:4, 84-85.

See Also

See also personfit.stat for person fit statistics for dichotomous item responses. See also the **PerFit** package for further person fit statistics.

Item fit in other R packages: eRm::itemfit, TAM::tam.fit, mirt::itemfit, ltm::item.fit,

Person fit in other R packages: eRm::itemfit, mirt::itemfit, ltm::person.fit,

See pcm.conversion for conversions of different parametrizations of the partial credit model.

Examples

```
## Not run:
#############################################################################
# EXAMPLE 1: Partial credit model
#############################################################################

data(data.Students,package="CDM")
dat <- data.Students
```

```
# select items
items <- c(paste0("sc", 1:4 ), paste0("mj", 1:4 ) )
dat <- dat[,items]
dat <- dat[ rowSums( 1 - is.na(dat) ) > 0, ]

#*** Model 1a: Partial credit model in TAM
# estimate model
mod1a <- TAM::tam.mml( resp=dat )
summary(mod1a)
# estimate person parameters
wle1a <- TAM::tam.wle(mod1a)
# extract item parameters
b1 <- - mod1a$AXsi[, -1 ]
# parametrization in xsi parameters
b2 <- matrix( mod1a$xsi$xsi, ncol=3, byrow=TRUE )
# convert b2 to b1
b1b <- 0*b1
b1b[,1] <- b2[,1]
b1b[,2] <- rowSums( b2[,1:2] )
b1b[,3] <- rowSums( b2[,1:3] )
# assess fit
fit1a <- sirt::pcm.fit(b=b1, theta=wle1a$theta, dat)
fit1a$item

############################################################################
# EXAMPLE 2: Rasch model
############################################################################

data(data.read)
dat <- data.read

#*** Rasch model in TAM
# estimate model
mod <- TAM::tam.mml( resp=dat )
summary(mod)
# estimate person parameters
wle <- TAM::tam.wle(mod)
# extract item parameters
b1 <- - mod$AXsi[, -1 ]
# assess fit
fit1a <- sirt::pcm.fit(b=b1, theta=wle$theta, dat)
fit1a$item

############################################################################
# EXAMPLE 3: Rating scale model
############################################################################

data(data.Students,package="CDM")
dat <- data.Students
items <- paste0("sc", 1:4 )
dat <- dat[,items]
dat <- dat[ rowSums( 1 - is.na(dat) ) > 0, ]
```

```
#*** Model 1: Rating scale model in TAM
# estimate model
mod1 <- tam.mml( resp=dat, irtmodel="RSM")
summary(mod1)
# estimate person parameters
wle1 <- tam.wle(mod1)
# extract item parameters
b1 <- - mod1a$AXsi[, -1 ]
# fit statistic
pcm.fit(b=b1, theta=wle1$theta, dat)

## End(Not run)
```

`person.parameter.rasch.copula` *Person Parameter Estimation of the Rasch Copula Model (Braeken, 2011)*

Description

Ability estimates as maximum likelihood estimates (MLE) are provided by the Rasch copula model.

Usage

```
person.parameter.rasch.copula(raschcopula.object, numdiff.parm=0.001,
    conv.parm=0.001, maxiter=20, stepwidth=1,
    print.summary=TRUE, ...)
```

Arguments

`raschcopula.object`	Object which is generated by the `rasch.copula2` function.
`numdiff.parm`	Parameter h for numerical differentiation
`conv.parm`	Convergence criterion
`maxiter`	Maximum number of iterations
`stepwidth`	Maximal increment in iterations
`print.summary`	Print summary?
`...`	Further arguments to be passed

Value

A list with following entries

`person`	Estimated person parameters
`se.inflat`	Inflation of individual standard errors due to local dependence
`theta.table`	Ability estimates for each unique response pattern

`pattern.in.data`
: Item response pattern

`summary.theta.table`
: Summary statistics of person parameter estimates

See Also

See `rasch.copula2` for estimating Rasch copula models.

Examples

```
#############################################################################
# EXAMPLE 1: Reading Data
#############################################################################

data(data.read)
dat <- data.read

# define item cluster
itemcluster <- rep( 1:3, each=4 )
mod1 <- sirt::rasch.copula2( dat, itemcluster=itemcluster )
summary(mod1)

# person parameter estimation under the Rasch copula model
pmod1 <- sirt::person.parameter.rasch.copula(raschcopula.object=mod1 )
## Mean percentage standard error inflation
##   missing.pattern Mperc.seinflat
## 1               1           6.35

## Not run:
#############################################################################
# EXAMPLE 2: 12 items nested within 3 item clusters (testlets)
#   Cluster 1 -> Items 1-4; Cluster 2 -> Items 6-9;  Cluster 3 -> Items 10-12
#############################################################################

set.seed(967)
I <- 12                             # number of items
n <- 450                            # number of persons
b <- seq(-2,2, len=I)               # item difficulties
b <- sample(b)                      # sample item difficulties
theta <- stats::rnorm( n, sd=1 ) # person abilities
# itemcluster
itemcluster <- rep(0,I)
itemcluster[ 1:4 ] <- 1
itemcluster[ 6:9 ] <- 2
itemcluster[ 10:12 ] <- 3
# residual correlations
rho <- c( .35, .25, .30 )

# simulate data
dat <- sirt::sim.rasch.dep( theta, b, itemcluster, rho )
colnames(dat) <- paste("I", seq(1,ncol(dat)), sep="")
```

```
# estimate Rasch copula model
mod1 <- sirt::rasch.copula2( dat, itemcluster=itemcluster )
summary(mod1)

# person parameter estimation under the Rasch copula model
pmod1 <- sirt::person.parameter.rasch.copula(raschcopula.object=mod1 )
  ## Mean percentage standard error inflation
  ##   missing.pattern Mperc.seinflat
  ## 1               1          10.48

## End(Not run)
```

`personfit.stat` *Person Fit Statistics for the Rasch Model*

Description

This function collects some person fit statistics for the Rasch model (Karabatsos, 2003; Meijer & Sijtsma, 2001).

Usage

```
personfit.stat(dat, abil, b)
```

Arguments

`dat`	An $N \times I$ data frame of dichotomous item responses
`abil`	An ability estimate, e.g. the WLE
`b`	Estimated item difficulty

Value

A data frame with following columns (see Meijer & Sijtsma 2001 for a review of different person fit statistics):

`case`	Case index
`abil`	Ability estimate `abil`
`mean`	Person mean of correctly solved items
`caution`	Caution index
`depend`	Dependability index
`ECI1`	$ECI1$
`ECI2`	$ECI2$
`ECI3`	$ECI3$
`ECI4`	$ECI4$

ECI5	$ECI5$
ECI6	$ECI6$
l0	Fit statistic l_0
lz	Fit statistic l_z
outfit	Person outfit statistic
infit	Person infit statistic
rpbis	Point biserial correlation of item responses and item p values
rpbis.itemdiff	Point biserial correlation of item responses and item difficulties b
U3	Fit statistic U_3

References

Karabatsos, G. (2003). Comparing the aberrant response detection performance of thirty-six person-fit statistics. *Applied Measurement in Education, 16*, 277-298.

Meijer, R. R., & Sijtsma, K. (2001). Methodology review: Evaluating person fit. *Applied Psychological Measurement, 25*, 107-135.

See Also

See pcm.fit for person fit in the partial credit model.

See the **irtProb** and **PerFit** packages for person fit statistics and person response curves and functions included in other packages: mirt::personfit, eRm::personfit and ltm::person.fit.

Examples

```
#############################################################################
# EXAMPLE 1: Person fit Reading Data
#############################################################################

data(data.read)
dat <- data.read

# estimate Rasch model
mod <- sirt::rasch.mml2( dat )
# WLE
wle1 <- sirt::wle.rasch( dat,b=mod$item$b )$theta
b <- mod$item$b # item difficulty

# evaluate person fit
pf1 <- sirt::personfit.stat( dat=dat, abil=wle1, b=b)

## Not run:
# dimensional analysis of person fit statistics
x0 <- stats::na.omit(pf1[, -c(1:3) ] )
stats::factanal( x=x0, factors=2, rotation="promax" )
  ## Loadings:
  ##               Factor1 Factor2
  ## caution         0.914
```

```
## depend          0.293   0.750
## ECI1            0.869   0.160
## ECI2            0.869   0.162
## ECI3            1.011
## ECI4            1.159  -0.269
## ECI5            1.012
## ECI6            0.879   0.130
## l0              0.409  -1.255
## lz             -0.504  -0.529
## outfit          0.297   0.702
## infit           0.362   0.695
## rpbis          -1.014
## rpbis.itemdiff  1.032
## U3              0.735   0.309
##
## Factor Correlations:
##         Factor1 Factor2
## Factor1   1.000  -0.727
## Factor2  -0.727   1.000
##

## End(Not run)
```

---

pgenlogis *Calculation of Probabilities and Moments for the Generalized Logistic Item Response Model*

Description

Calculation of probabilities and moments for the generalized logistic item response model (Stukel, 1988).

Usage

```
pgenlogis(x, alpha1=0, alpha2=0)

genlogis.moments(alpha1, alpha2)
```

Arguments

x	Vector
alpha1	Upper tail parameter α_1 in the generalized logistic item response model. The default is 0.
alpha2	Lower tail parameter α_2 parameter in the generalized logistic item response model. The default is 0.

Details

The class of generalized logistic link functions contain the most important link functions using the specifications (Stukel, 1988):

- logistic link function L:

$$L(x) \approx G_{(\alpha_1=0,\alpha_2=0)}[x]$$

- probit link function Φ:

$$\Phi(x) \approx G_{(\alpha_1=0.165,\alpha_2=0.165)}[1.47x]$$

- loglog link function H:

$$H(x) \approx G_{(\alpha_1=-0.037,\alpha_2=0.62)}[-0.39 + 1.20x - 0.007x^2]$$

- cloglog link function H:

$$H(x) \approx G_{(\alpha_1=0.62,\alpha_2=-0.037)}[0.54 + 1.64x + 0.28x^2 + 0.046x^3]$$

Value

Vector of probabilities or moments

References

Stukel, T. A. (1988). Generalized logistic models. *Journal of the American Statistical Association, 83*(402), 426-431. doi:10.1080/01621459.1988.10478613

Examples

```
sirt::pgenlogis( x=c(-.3, 0, .25, 1 ), alpha1=0, alpha2=.6 )
  ##   [1] 0.4185580 0.5000000 0.5621765 0.7310586

#############################################################################
# compare link functions
x <- seq( -3,3, .1 )

#***
# logistic link
y <- sirt::pgenlogis( x, alpha1=0, alpha2=0 )
plot( x, stats::plogis(x), type="l", main="Logistic Link", lwd=2)
points( x, y, pch=1, col=2 )

#***
# probit link
round( sirt::genlogis.moments( alpha1=.165, alpha2=.165 ), 3 )
  ##       M    SD   Var
  ##   0.000 1.472 2.167
# SD of generalized logistic link function is 1.472
y <- sirt::pgenlogis( x * 1.47, alpha1=.165, alpha2=.165 )
plot( x, stats::pnorm(x), type="l", main="Probit Link", lwd=2)
points( x, y, pch=1, col=2 )
```

```
#***
# loglog link
y <- sirt::pgenlogis( -.39 + 1.20*x -.007*x^2, alpha1=-.037, alpha2=.62 )
plot( x, exp( - exp( -x ) ), type="l", main="Loglog Link", lwd=2,
    ylab="loglog(x)=exp(-exp(-x))" )
points( x, y, pch=17, col=2 )

#***
# cloglog link
y <- sirt::pgenlogis( .54+1.64*x +.28*x^2 + .046*x^3, alpha1=.062, alpha2=-.037 )
plot( x, 1-exp( - exp(x) ), type="l", main="Cloglog Link", lwd=2,
    ylab="loglog(x)=1-exp(-exp(x))" )
points( x, y, pch=17, col=2 )
```

`plausible.value.imputation.raschtype` *Plausible Value Imputation in Generalized Logistic Item Response Model*

Description

This function performs unidimensional plausible value imputation (Adams & Wu, 2007; Mislevy, 1991).

Usage

```
plausible.value.imputation.raschtype(data=NULL, f.yi.qk=NULL, X,
   Z=NULL, beta0=rep(0, ncol(X)), sig0=1, b=rep(1, ncol(X)),
   a=rep(1, length(b)), c=rep(0, length(b)), d=1+0*b,
   alpha1=0, alpha2=0, theta.list=seq(-5, 5, len=50),
   cluster=NULL, iter, burnin, nplausible=1, printprogress=TRUE)
```

Arguments

`data`	An $N \times I$ data frame of dichotomous responses
`f.yi.qk`	An optional matrix which contains the individual likelihood. This matrix is produced by `rasch.mml2` or `rasch.copula2`. The use of this argument allows the estimation of the latent regression model independent of the parameters of the used item response model.
`X`	A matrix of individual covariates for the latent regression of θ on X
`Z`	A matrix of individual covariates for the regression of individual residual variances on Z
`beta0`	Initial vector of regression coefficients
`sig0`	Initial vector of coefficients for the variance heterogeneity model
`b`	Vector of item difficulties. It must not be provided if the individual likelihood `f.yi.qk` is specified.

a	Optional vector of item slopes
c	Optional vector of lower item asymptotes
d	Optional vector of upper item asymptotes
alpha1	Parameter α_1 in generalized item response model
alpha2	Parameter α_2 in generalized item response model
theta.list	Vector of theta values at which the ability distribution should be evaluated
cluster	Cluster identifier (e.g. schools or classes) for including theta means in the plausible imputation.
iter	Number of iterations
burnin	Number of burn-in iterations for plausible value imputation
nplausible	Number of plausible values
printprogress	A logical indicated whether iteration progress should be displayed at the console.

Details

Plausible values are drawn from the latent regression model with heterogeneous variances:

$$\theta_p = X_p\beta + \epsilon_p \quad , \quad \epsilon_p \sim N(0, \sigma_p^2) \quad , \quad \log(\sigma_p) = Z_p\gamma + \nu_p$$

Value

A list with following entries:

coefs.X	Sampled regression coefficients for covariates X
coefs.Z	Sampled coefficients for modeling variance heterogeneity for covariates Z
pvdraws	Matrix with drawn plausible values
posterior	Posterior distribution from last iteration
EAP	Individual EAP estimate
SE.EAP	Standard error of the EAP estimate
pv.indexes	Index of iterations for which plausible values were drawn

References

Adams, R., & Wu. M. (2007). The mixed-coefficients multinomial logit model: A generalized form of the Rasch model. In M. von Davier & C. H. Carstensen: *Multivariate and Mixture Distribution Rasch Models: Extensions and Applications* (pp. 57-76). New York: Springer.

Mislevy, R. J. (1991). Randomization-based inference about latent variables from complex samples. *Psychometrika, 56*, 177-196.

See Also

For estimating the latent regression model see latent.regression.em.raschtype.

Examples

```
#############################################################################
# EXAMPLE 1: Rasch model with covariates
#############################################################################

set.seed(899)
I <- 21     # number of items
b <- seq(-2,2, len=I)   # item difficulties
n <- 2000       # number of students

# simulate theta and covariates
theta <- stats::rnorm( n )
x <- .7 * theta + stats::rnorm( n, .5 )
y <- .2 * x+ .3*theta + stats::rnorm( n, .4 )
dfr <- data.frame( theta, 1, x, y )

# simulate Rasch model
dat1 <- sirt::sim.raschtype( theta=theta, b=b )

# Plausible value draws
pv1 <- sirt::plausible.value.imputation.raschtype(data=dat1, X=dfr[,-1], b=b,
            nplausible=3, iter=10, burnin=5)
# estimate linear regression based on first plausible value
mod1 <- stats::lm( pv1$pvdraws[,1] ~ x+y )
summary(mod1)
  ##               Estimate Std. Error t value Pr(>|t|)
  ##   (Intercept) -0.27755    0.02121  -13.09   <2e-16 ***
  ##   x            0.40483    0.01640   24.69   <2e-16 ***
  ##   y            0.20307    0.01822   11.15   <2e-16 ***

# true regression estimate
summary( stats::lm( theta ~ x + y ) )
  ## Coefficients:
  ##             Estimate Std. Error t value Pr(>|t|)
  ## (Intercept) -0.27821    0.01984  -14.02   <2e-16 ***
  ## x            0.40747    0.01534   26.56   <2e-16 ***
  ## y            0.18189    0.01704   10.67   <2e-16 ***

## Not run:
#############################################################################
# EXAMPLE 2: Classical test theory, homogeneous regression variance
#############################################################################

set.seed(899)
n <- 3000       # number of students
x <- round( stats::runif( n, 0,1 ) )
y <- stats::rnorm(n)
# simulate true score theta
theta <- .4*x + .5 * y + stats::rnorm(n)
# simulate observed score by adding measurement error
sig.e <- rep( sqrt(.40), n )
theta_obs <- theta + stats::rnorm( n, sd=sig.e)
```

```
# define theta grid for evaluation of density
theta.list <- mean(theta_obs) + stats::sd(theta_obs) * seq( - 5, 5, length=21)
# compute individual likelihood
f.yi.qk <- stats::dnorm( outer( theta_obs, theta.list, "-" ) / sig.e )
f.yi.qk <- f.yi.qk / rowSums(f.yi.qk)
# define covariates
X <- cbind( 1, x, y )
# draw plausible values
mod2 <- sirt::plausible.value.imputation.raschtype( f.yi.qk=f.yi.qk,
                  theta.list=theta.list, X=X, iter=10, burnin=5)

# linear regression
mod1 <- stats::lm( mod2$pvdraws[,1] ~ x+y )
summary(mod1)
  ##             Estimate Std. Error t value Pr(>|t|)
  ## (Intercept) -0.01393    0.02655  -0.525      0.6
  ## x            0.35686    0.03739   9.544   <2e-16 ***
  ## y            0.53759    0.01872  28.718   <2e-16 ***

# true regression model
summary( stats::lm( theta ~ x + y ) )
  ##             Estimate Std. Error t value Pr(>|t|)
  ## (Intercept) 0.002931   0.026171   0.112    0.911
  ## x           0.359954   0.036864   9.764   <2e-16 ***
  ## y           0.509073   0.018456  27.584   <2e-16 ***

#############################################################################
# EXAMPLE 3: Classical test theory, heterogeneous regression variance
#############################################################################

set.seed(899)
n <- 5000       # number of students
x <- round( stats::runif( n, 0,1 ) )
y <- stats::rnorm(n)
# simulate true score theta
theta <- .4*x + .5 * y + stats::rnorm(n) * ( 1 - .4 * x )
# simulate observed score by adding measurement error
sig.e <- rep( sqrt(.40), n )
theta_obs <- theta + stats::rnorm( n, sd=sig.e)

# define theta grid for evaluation of density
theta.list <- mean(theta_obs) + stats::sd(theta_obs) * seq( - 5, 5, length=21)
# compute individual likelihood
f.yi.qk <- stats::dnorm( outer( theta_obs, theta.list, "-" ) / sig.e )
f.yi.qk <- f.yi.qk / rowSums(f.yi.qk)
# define covariates
X <- cbind( 1, x, y )
# draw plausible values (assuming variance homogeneity)
mod3a <- sirt::plausible.value.imputation.raschtype( f.yi.qk=f.yi.qk,
                  theta.list=theta.list, X=X, iter=10, burnin=5)
# draw plausible values (assuming variance heterogeneity)
#  -> include predictor Z
```

```
mod3b <- sirt::plausible.value.imputation.raschtype( f.yi.qk=f.yi.qk,
                  theta.list=theta.list, X=X, Z=X, iter=10, burnin=5)

# investigate variance of theta conditional on x
res3 <- sapply( 0:1, FUN=function(vv){
        c( stats::var(theta[x==vv]), stats::var(mod3b$pvdraw[x==vv,1]),
              stats::var(mod3a$pvdraw[x==vv,1]))})
rownames(res3) <- c("true", "pv(hetero)", "pv(homog)" )
colnames(res3) <- c("x=0","x=1")
  ## > round( res3, 2 )
  ##             x=0  x=1
  ## true       1.30 0.58
  ## pv(hetero) 1.29 0.55
  ## pv(homog)  1.06 0.77
## -> assuming heteroscedastic variances recovers true conditional variance

## End(Not run)
```

`plot.mcmc.sirt` *Plot Function for Objects of Class* `mcmc.sirt`

Description

Plot function for objects of class `mcmc.sirt`. These objects are generated by: `mcmc.2pno`, `mcmc.2pnoh`, `mcmc.3pno.testlet`, `mcmc.2pno.ml`

Usage

```
## S3 method for class 'mcmc.sirt'
plot( x, layout=1, conflevel=0.9, round.summ=3,
   lag.max=.1, col.smooth="red", lwd.smooth=2, col.ci="orange",
   cex.summ=1, ask=FALSE, ...)
```

Arguments

`x`	Object of class `mcmc.sirt`
`layout`	Layout type. `layout=1` is the standard coda plot output, `layout=2` gives a slightly different display.
`conflevel`	Confidence level (only applies to `layout=2`)
`round.summ`	Number of digits to be rounded in summary (only applies to `layout=2`)
`lag.max`	Maximum lag for autocorrelation plot (only applies to `layout=2`). The default of .1 means that it is set to 1/10 of the number of iterations.
`col.smooth`	Color of smooth trend in traceplot (only applies to `layout=2`)
`lwd.smooth`	Line type of smooth trend in traceplot (only applies to `layout=2`)
`col.ci`	Color for displaying confidence interval (only applies to `layout=2`)
`cex.summ`	Cex size for descriptive summary (only applies to `layout=2`)
`ask`	Ask for a new plot (only applies to `layout=2`)
`...`	Further arguments to be passed

See Also

mcmc.2pno, mcmc.2pnoh, mcmc.3pno.testlet, mcmc.2pno.ml

---

plot.np.dich *Plot Method for Object of Class* np.dich

Description

This function plots nonparametric item response functions estimated with dich.np.

Usage

```
## S3 method for class 'np.dich'
plot(x, b, infit=NULL, outfit=NULL,
    nsize=100, askplot=TRUE, progress=TRUE, bands=FALSE,
    plot.b=FALSE, shade=FALSE, shadecol="burlywood1", ...)
```

Arguments

x	Object of class np.dich
b	Estimated item difficulty (threshold)
infit	Infit (optional)
outfit	Outfit (optional)
nsize	XXX
askplot	Ask for new plot?
progress	Display progress?
bands	Draw confidence bands?
plot.b	Plot difficulty parameter?
shade	Shade curves?
shadecol	Shade color
...	Further arguments to be passed

See Also

For examples see np.dich.

polychoric2 *Polychoric Correlation*

Description

This function estimates the polychoric correlation coefficient using maximum likelihood estimation (Olsson, 1979).

Usage

```
polychoric2(dat, maxiter=100, cor.smooth=TRUE, use_pbv=1, conv=1e-10,
      rho_init=NULL, weights=NULL)

## exported Rcpp function
sirt_rcpp_polychoric2( dat, maxK, maxiter, use_pbv, conv, rho_init, weights)
```

Arguments

dat	A dataset with integer values $0, 1, \ldots, K$
maxiter	Maximum number of iterations
cor.smooth	An optional logical indicating whether the polychoric correlation matrix should be smooth to ensure positive definiteness.
use_pbv	Integer indicating whether the **pbv** package is used for computation of bivariate normal distribution. `0` stands for the simplest approximation in **sirt** (Cox & Wermuth, 1991, as implemented in `polychoric2`) while versions `1` and `2` uses the algorithm of **pbv** (the first one copied into the **sirt** package, the second one linking Rcpp code to **pbv**.)
conv	Convergence criterion
rho_init	Optional matrix of initial values for polychoric correlations
weights	Optional vector of sampling weights
maxK	Maximum number of categories

Value

A list with following entries

tau	Matrix of thresholds
rho	Polychoric correlation matrix
Nobs	Sample size for every item pair
maxcat	Maximum number of categories per item

References

Cox, D. R., & Wermuth, N. (1991). A simple approximation for bivariate and trivariate normal integrals. *International Statistical Review, 59*(2), 263-269.

Olsson, U. (1979). Maximum likelihood estimation of the polychoric correlation coefficient. *Psychometrika, 44*(4), 443-460. doi:10.1007/BF02296207

See Also

See the `psych::polychoric` function in the **psych** package.

For estimating tetrachoric correlations see `tetrachoric2`.

Examples

```
##############################################################################
# EXAMPLE 1: data.Students | activity scale
##############################################################################

data(data.Students, package="CDM")
dat <- data.Students[, paste0("act", 1:5 ) ]

# tetrachoric correlation from psych package
library(psych)
t0 <- psych::polychoric(dat)$rho
# Olsson method (maximum likelihood estimation)
t1 <- sirt::polychoric2(dat)$rho
# maximum absolute difference
max( abs( t0 - t1 ) )
  ##   [1] 0.004102429
```

---

prior_model_parse *Parsing a Prior Model*

Description

Parses a string specifying a prior model which is needed for the `prior` argument in `LAM::amh`

Usage

```
prior_model_parse(prior_model)
```

Arguments

`prior_model`	String specifying the prior conforming to R syntax.

Value

List with specified prior distributions for parameters as needed for the `prior` argument in `LAM::amh`

See Also

LAM::amh

Examples

```
#############################################################################
# EXAMPLE 1: Toy example prior distributions
#############################################################################

#*** define prior model as a string
prior_model <- "
  # prior distributions means
  mu1 ~ dnorm( NA, mean=0, sd=1 )
  mu2 ~ dnorm(NA)       # mean T2 and T3
  # prior distribution standard deviation
  sig1 ~ dunif(NA,0, max=10)
      "

#*** convert priors into a list
res <- sirt::prior_model_parse( prior_model )
str(res)
  ##  List of 3
  ##   $ mu1 :List of 2
  ##    ..$ : chr "dnorm"
  ##    ..$ :List of 3
  ##    .. ..$ NA  : num NA
  ##    .. ..$ mean: num 0
  ##    .. ..$ sd  : num 1
  ##   $ mu2 :List of 2
  ##    ..$ : chr "dnorm"
  ##    ..$ :List of 1
  ##    .. ..$ : num NA
  ##   $ sig1:List of 2
  ##    ..$ : chr "dunif"
  ##    ..$ :List of 3
  ##    .. ..$ NA : num NA
  ##    .. ..$ NA : num 0
  ##    .. ..$ max: num 10
```

---

prmse.subscores.scales

Proportional Reduction of Mean Squared Error (PRMSE) for Subscale Scores

---

Description

This function estimates the proportional reduction of mean squared error (PRMSE) according to Haberman (Haberman 2008; Haberman, Sinharay & Puhan, 2008; see Meijer et al. 2017 for an overview).

Usage

```
prmse.subscores.scales(data, subscale)
```

Arguments

data	An $N \times I$ data frame of item responses
subscale	Vector of labels corresponding to subscales

Value

Matrix with columns corresponding to subscales
The symbol X denotes the subscale and Z the whole scale (see also in the Examples section for the structure of this matrix).

References

Haberman, S. J. (2008). When can subscores have value? *Journal of Educational and Behavioral Statistics, 33*, 204-229.

Haberman, S., Sinharay, S., & Puhan, G. (2008). Reporting subscores for institutions. *British Journal of Mathematical and Statistical Psychology, 62*, 79-95.

Meijer, R. R., Boeve, A. J., Tendeiro, J. N., Bosker, R. J., & Albers, C. J. (2017). The use of subscores in higher education: When is this useful?. *Frontiers in Psychology | Educational Psychology, 8*.

See Also

See the **subscore** package for computing subscores and the PRMSE measures, especially `subscore::CTTsub`.

Examples

```
#############################################################################
# EXAMPLE 1: PRMSE Reading data data.read
#############################################################################

data( data.read )
p1 <- sirt::prmse.subscores.scales(data=data.read,
        subscale=substring( colnames(data.read), 1,1 ) )
print( p1, digits=3 )
  ##                A       B       C
  ## N          328.000 328.000 328.000
  ## nX           4.000   4.000   4.000
  ## M.X          2.616   2.811   3.253
  ## Var.X        1.381   1.059   1.107
  ## SD.X         1.175   1.029   1.052
  ## alpha.X      0.545   0.381   0.640
  ## [...]
  ## nZ          12.000  12.000  12.000
  ## M.Z          8.680   8.680   8.680
  ## Var.Z        5.668   5.668   5.668
  ## SD.Z         2.381   2.381   2.381
```

```
  ## alpha.Z     0.677   0.677   0.677
  ## [...]
  ## cor.TX_Z    0.799   0.835   0.684
  ## rmse.X      0.585   0.500   0.505
  ## rmse.Z      0.522   0.350   0.614
  ## rmse.XZ     0.495   0.350   0.478
  ## prmse.X     0.545   0.381   0.640
  ## prmse.Z     0.638   0.697   0.468
  ## prmse.XZ    0.674   0.697   0.677
#-> Scales A and B do not have lower RMSE,
#   but for scale C the RMSE is smaller than the RMSE of a
#   prediction based on a whole scale.
```

---

prob.guttman *Probabilistic Guttman Model*

Description

This function estimates the probabilistic Guttman model which is a special case of an ordered latent trait model (Hanson, 2000; Proctor, 1970).

Usage

```
prob.guttman(dat, pid=NULL, guess.equal=FALSE,  slip.equal=FALSE,
    itemlevel=NULL, conv1=0.001, glob.conv=0.001, mmliter=500)

## S3 method for class 'prob.guttman'
summary(object,...)

## S3 method for class 'prob.guttman'
anova(object,...)

## S3 method for class 'prob.guttman'
logLik(object,...)

## S3 method for class 'prob.guttman'
IRT.irfprob(object,...)

## S3 method for class 'prob.guttman'
IRT.likelihood(object,...)

## S3 method for class 'prob.guttman'
IRT.posterior(object,...)
```

Arguments

dat	An $N \times I$ data frame of dichotomous item responses
pid	Optional vector of person identifiers

guess.equal	Should the same guessing parameters for all the items estimated?
slip.equal	Should the same slipping parameters for all the items estimated?
itemlevel	A vector of item levels of the Guttman scale for each item. If there are K different item levels, then the Guttman scale possesses K ordered trait values.
conv1	Convergence criterion for item parameters
glob.conv	Global convergence criterion for the deviance
mmliter	Maximum number of iterations
object	Object of class prob.guttman
...	Further arguments to be passed

Value

An object of class prob.guttman

person	Estimated person parameters
item	Estimated item parameters
theta.k	Ability levels
trait	Estimated trait distribution
ic	Information criteria
deviance	Deviance
iter	Number of iterations
itemdesign	Specified allocation of items to trait levels

References

Hanson, B. (2000). *IRT parameter estimation using the EM algorithm.* Technical Report.

Proctor, C. H. (1970). A probabilistic formulation and statistical analysis for Guttman scaling. *Psychometrika, 35*, 73-78.

Examples

```
#############################################################################
# EXAMPLE 1: Dataset Reading
#############################################################################
data(data.read)
dat <- data.read

#***
# Model 1: estimate probabilistic Guttman model
mod1 <- sirt::prob.guttman( dat )
summary(mod1)

#***
# Model 2: probabilistic Guttman model with equal guessing and slipping parameters
mod2 <- sirt::prob.guttman( dat, guess.equal=TRUE, slip.equal=TRUE)
summary(mod2)
```

```
#***
# Model 3: Guttman model with three a priori specified item levels
itemlevel <- rep(1,12)
itemlevel[ c(2,5,8,10,12) ] <- 2
itemlevel[ c(3,4,6) ] <- 3
mod3 <- sirt::prob.guttman( dat, itemlevel=itemlevel )
summary(mod3)

## Not run:
#***
# Model3m: estimate Model 3 in mirt

library(mirt)
# define four ordered latent classes
Theta <- scan(nlines=1)
   0 0 0    1 0 0   1 1 0   1 1 1
Theta <- matrix( Theta, nrow=4, ncol=3,byrow=TRUE)

# define mirt model
I <- ncol(dat)  # I=12
mirtmodel <- mirt::mirt.model("
        # specify factors for each item level
        C1=1,7,9,11
        C2=2,5,8,10,12
        C3=3,4,6
        ")
# get initial parameter values
mod.pars <- mirt::mirt(dat, model=mirtmodel,  pars="values")
# redefine initial parameter values
mod.pars[ mod.pars$name=="d","value" ]  <- -1
mod.pars[ mod.pars$name %in% paste0("a",1:3) & mod.pars$est,"value" ]  <- 2
mod.pars
# define prior for latent class analysis
lca_prior <- function(Theta,Etable){
  # number of latent Theta classes
  TP <- nrow(Theta)
  # prior in initial iteration
  if ( is.null(Etable) ){ prior <- rep( 1/TP, TP ) }
  # process Etable (this is correct for datasets without missing data)
  if ( ! is.null(Etable) ){
    # sum over correct and incorrect expected responses
    prior <- ( rowSums(Etable[, seq(1,2*I,2)]) + rowSums(Etable[,seq(2,2*I,2)]) )/I
                }
  prior <- prior / sum(prior)
  return(prior)
}
# estimate model in mirt
mod3m <- mirt::mirt(dat, mirtmodel, pars=mod.pars, verbose=TRUE,
            technical=list( customTheta=Theta, customPriorFun=lca_prior) )
# correct number of estimated parameters
mod3m@nest <- as.integer(sum(mod.pars$est) + nrow(Theta)-1 )
# extract log-likelihood and compute AIC and BIC
```

```
mod3m@logLik
( AIC <- -2*mod3m@logLik+2*mod3m@nest )
( BIC <- -2*mod3m@logLik+log(mod3m@Data$N)*mod3m@nest )
# compare with information criteria from prob.guttman
mod3$ic
# model fit in mirt
mirt::M2(mod3m)
# extract coefficients
( cmod3m <- sirt::mirt.wrapper.coef(mod3m) )
# compare estimated distributions
round( cbind( "sirt"=mod3$trait$prob, "mirt"=mod3m@Prior[[1]] ), 5 )
  ##           sirt    mirt
  ##   [1,] 0.13709 0.13765
  ##   [2,] 0.30266 0.30303
  ##   [3,] 0.15239 0.15085
  ##   [4,] 0.40786 0.40846
# compare estimated item parameters
ipars <- data.frame( "guess.sirt"=mod3$item$guess,
                     "guess.mirt"=plogis( cmod3m$coef$d ) )
ipars$slip.sirt <- mod3$item$slip
ipars$slip.mirt <- 1-plogis( rowSums(cmod3m$coef[, c("a1","a2","a3","d") ] ) )
round( ipars, 4 )
  ##      guess.sirt guess.mirt slip.sirt slip.mirt
  ##   1      0.7810     0.7804    0.1383    0.1382
  ##   2      0.4513     0.4517    0.0373    0.0368
  ##   3      0.3203     0.3200    0.0747    0.0751
  ##   4      0.3009     0.3007    0.3082    0.3087
  ##   5      0.5776     0.5779    0.1800    0.1798
  ##   6      0.3758     0.3759    0.3047    0.3051
  ##   7      0.7262     0.7259    0.0625    0.0623
  ##   [...]

#***
# Model 4: Monotone item response function estimated in mirt

# define four ordered latent classes
Theta <- scan(nlines=1)
   0 0 0    1 0 0   1 1 0   1 1 1
Theta <- matrix( Theta, nrow=4, ncol=3,byrow=TRUE)

# define mirt model
I <- ncol(dat)  # I=12
mirtmodel <- mirt::mirt.model("
        # specify factors for each item level
        C1=1-12
        C2=1-12
        C3=1-12
        ")
# get initial parameter values
mod.pars <- mirt::mirt(dat, model=mirtmodel,  pars="values")
# redefine initial parameter values
mod.pars[ mod.pars$name=="d","value" ]  <- -1
mod.pars[ mod.pars$name %in% paste0("a",1:3) & mod.pars$est,"value" ]  <- .6
```

```
# set lower bound to zero ton ensure monotonicity
mod.pars[ mod.pars$name %in% paste0("a",1:3),"lbound" ]  <- 0
mod.pars
# estimate model in mirt
mod4 <- mirt::mirt(dat, mirtmodel, pars=mod.pars, verbose=TRUE,
            technical=list( customTheta=Theta, customPriorFun=lca_prior) )
# correct number of estimated parameters
mod4@nest <- as.integer(sum(mod.pars$est) + nrow(Theta)-1 )
# extract coefficients
cmod4 <- sirt::mirt.wrapper.coef(mod4)
cmod4
# compute item response functions
cmod4c <- cmod4$coef[, c("d", "a1", "a2", "a3" ) ]
probs4 <- t( apply( cmod4c, 1, FUN=function(ll){
                plogis(cumsum(as.numeric(ll))) } ) )
matplot( 1:4,  t(probs4), type="b", pch=1:I)

## End(Not run)
```

Q3 *Estimation of the Q_3 Statistic (Yen, 1984)*

Description

This function estimates the Q_3 statistic according to Yen (1984). The statistic Q_3 is calculated for every item pair (i, j) which is the correlation between item residuals after fitting the Rasch model.

Usage

```
Q3(dat, theta, b, progress=TRUE)
```

Arguments

dat	An $N \times I$ data frame of dichotomous item responses
theta	Vector of length N of person parameter estimates (e.g. obtained from wle.rasch)
b	Vector of length I (e.g. obtained from rasch.mml2)
progress	Should iteration progress be displayed?

Value

A list with following entries

q3.matrix	An $I \times I$ matrix of Q_3 statistics
q3.long	Just the q3.matrix in long matrix format where every row corresponds to an item pair
expected	An $N \times I$ matrix of expected probabilities by the Rasch model
residual	An $N \times I$ matrix of residuals obtained after fitting the Rasch model
Q3.stat	Vector with descriptive statistics of Q_3

References

Yen, W. M. (1984). Effects of local item dependence on the fit and equating performance of the three-parameter logistic model. *Applied Psychological Measurement, 8*, 125-145.

See Also

For the estimation of the average Q_3 statistic within testlets see `Q3.testlet`.

For modeling testlet effects see `mcmc.3pno.testlet`.

For handling local dependencies in IRT models see `rasch.copula2`, `rasch.pml3` or `rasch.pairwise.itemcluster`.

Examples

```
#############################################################################
# EXAMPLE 1: data.read. The 12 items are arranged in 4 testlets
#############################################################################
data(data.read)

# estimate the Rasch model
mod <- sirt::rasch.mml2( data.read)
# estmate WLEs
mod.wle <- sirt::wle.rasch( dat=data.read, b=mod$item$b )
# calculate Yen's Q3 statistic
mod.q3 <- sirt::Q3( dat=data.read, theta=mod.wle$theta, b=mod$item$b )
  ##   Yen's Q3 Statistic based on an estimated theta score
  ##   *** 12 Items | 66 item pairs
  ##   *** Q3 Descriptives
  ##        M     SD    Min    10%    25%    50%    75%    90%    Max
  ##   -0.085  0.110 -0.261 -0.194 -0.152 -0.107 -0.051  0.041  0.412

# plot Q3 statistics
I <- ncol(data.read)
image( 1:I, 1:I, mod.q3$q3.matrix, col=gray( 1 - (0:32)/32),
        xlab="Item", ylab="Item")
abline(v=c(5,9)) # borders for testlets
abline(h=c(5,9))

## Not run:
# obtain Q3 statistic from modelfit.sirt function which is based on the
# posterior distribution of theta and not on observed values
fitmod <- sirt::modelfit.sirt( mod )
# extract Q3 statistic
q3stat <- fitmod$itempairs$Q3
  ##  > summary(q3stat)
  ##      Min.  1st Qu.   Median     Mean  3rd Qu.     Max.
  ##  -0.21760 -0.11590 -0.07280 -0.05545 -0.01220  0.44710
  ##  > sd(q3stat)
  ##  [1] 0.1101451

## End(Not run)
```

`Q3.testlet` *Q_3 Statistic of Yen (1984) for Testlets*

Description

This function calculates the average Q_3 statistic (Yen, 1984) within and between testlets.

Usage

```
Q3.testlet(q3.res, testlet.matrix, progress=TRUE)
```

Arguments

`q3.res`	An object generated by `Q3`
`testlet.matrix`	A matrix with two columns. The first column contains names of the testlets and the second names of the items. See the examples for the definition of such matrices.
`progress`	Logical indicating whether computation progress should be displayed.

Value

A list with following entries

`testlet.q3`	Data frame with average Q_3 statistics within testlets
`testlet.q3.korr`	Matrix of average Q_3 statistics within and between testlets

References

Yen, W. M. (1984). Effects of local item dependence on the fit and equating performance of the three-parameter logistic model. *Applied Psychological Measurement, 8*, 125-145.

See Also

For estimating all Q_3 statistics between item pairs use `Q3`.

Examples

```
#############################################################################
# EXAMPLE 1: data.read. The 12 items are arranged in 4 testlets
#############################################################################
data(data.read)

# estimate the Rasch model
mod <- sirt::rasch.mml2( data.read)
mod$item

# estmate WLEs
```

```
mod.wle <- sirt::wle.rasch( dat=data.read, b=mod$item$b )

# Yen's Q3 statistic
mod.q3 <- sirt::Q3( dat=data.read, theta=mod.wle$theta, b=mod$item$b )

# Yen's Q3 statistic with testlets
items <- colnames(data.read)
testlet.matrix <- cbind( substring(  items,1,1), items )
mod.testletq3 <- sirt::Q3.testlet( q3.res=mod.q3,testlet.matrix=testlet.matrix)
mod.testletq3
```

`qmc.nodes` *Calculation of Quasi Monte Carlo Integration Points*

Description

This function calculates integration nodes based on the multivariate normal distribution with zero mean vector and identity covariance matrix. See Pan and Thompson (2007) and Gonzales et al. (2006) for details.

Usage

```
qmc.nodes(snodes, ndim)
```

Arguments

`snodes`	Number of integration nodes
`ndim`	Number of dimensions

Value

`theta`	A matrix of integration points

Note

This function uses the `sfsmisc::QUnif` function from the **sfsmisc** package.

References

Gonzalez, J., Tuerlinckx, F., De Boeck, P., & Cools, R. (2006). Numerical integration in logistic-normal models. *Computational Statistics & Data Analysis, 51*, 1535-1548.

Pan, J., & Thompson, R. (2007). Quasi-Monte Carlo estimation in generalized linear mixed models. *Computational Statistics & Data Analysis, 51*, 5765-5775.

Examples

```
## some toy examples

# 5 nodes on one dimension
qmc.nodes( snodes=5, ndim=1 )
  ##            [,1]
  ## [1,]  0.0000000
  ## [2,] -0.3863753
  ## [3,]  0.8409238
  ## [4,] -0.8426682
  ## [5,]  0.3850568

# 7 nodes on two dimensions
qmc.nodes( snodes=7, ndim=2 )
  ##             [,1]        [,2]
  ## [1,]  0.00000000 -0.43072730
  ## [2,] -0.38637529  0.79736332
  ## [3,]  0.84092380 -1.73230641
  ## [4,] -0.84266815 -0.03840544
  ## [5,]  0.38505683  1.51466109
  ## [6,] -0.00122394 -0.86704605
  ## [7,]  1.35539115  0.33491073
```

R2conquest *Running ConQuest From Within* R

Description

The function R2conquest runs the IRT software ConQuest (Wu, Adams, Wilson & Haldane, 2007) from within R.

Other functions are utility functions for reading item parameters, plausible values or person-item maps.

Usage

```
R2conquest(dat, path.conquest, conquest.name="console", converge=0.001,
    deviancechange=1e-04, iter=800, nodes=20, minnode=-6, maxnode=6,
   show.conquestoutput=FALSE, name="rasch", pid=1:(nrow(dat)), wgt=NULL, X=NULL,
    set.constraints=NULL, model="item", regression=NULL,
   itemcodes=seq(0,max(dat,na.rm=TRUE)), constraints=NULL, digits=5, onlysyntax=FALSE,
    qmatrix=NULL, import.regression=NULL, anchor.regression=NULL,
    anchor.covariance=NULL, pv=TRUE, designmatrix=NULL, only.calibration=FALSE,
    init_parameters=NULL, n_plausible=10,  persons.elim=TRUE, est.wle=TRUE,
    save.bat=TRUE, use.bat=FALSE, read.output=TRUE, ignore.pid=FALSE)

## S3 method for class 'R2conquest'
summary(object, ...)
```

```
# read all terms in a show file or only some terms
read.show(showfile)
read.show.term(showfile, term)

# read regression parameters in a show file
read.show.regression(showfile)

# read unidimensional plausible values form a pv file
read.pv(pvfile, npv=5)
# read multidimensional plausible values
read.multidimpv(pvfile, ndim, npv=5)

# read person-item map
read.pimap(showfile)
```

Arguments

dat	Data frame of item responses
path.conquest	Directory where the ConQuest executable file is located
conquest.name	Name of the ConQuest executable.
converge	Maximal change in parameters
deviancechange	Maximal change in deviance
iter	Maximum number of iterations
nodes	Number of nodes for integration
minnode	Minimum value of discrete grid of θ nodes
maxnode	Maximum value of discrete grid of θ nodes
show.conquestoutput	Show ConQuest run log file on console?
name	Name of the output files. The default is 'rasch'.
pid	Person identifier
wgt	Vector of person weights
X	Matrix of covariates for the latent regression model (e.g. gender, socioeconomic status, ..) or for the item design (e.g. raters, booklets, ...)
set.constraints	This is the set.constraints in ConQuest. It can be "cases" (constraint for persons), "items" or "none"
model	Definition model statement. It can be for example "item+item*step" or "item+booklet+rater"
regression	The ConQuest regression statement (for example "gender+status")
itemcodes	Vector of valid codes for item responses. E.g. for partial credit data with at most 3 points it must be c(0,1,2,3).
constraints	Matrix of item parameter constraints. 1st column: Item names, 2nd column: Item parameters. It only works correctly for dichotomous data.
digits	Number of digits for covariates in the latent regression model

onlysyntax	Should only be ConQuest syntax generated?
qmatrix	Matrix of item loadings on dimensions in a multidimensional IRT model
import.regression	Name of an file with initial covariance parameters (follow the ConQuest specification rules!)
anchor.regression	Name of an file with anchored regression parameters
anchor.covariance	Name of an file with anchored covariance parameters (follow the ConQuest specification rules!)
pv	Draw plausible values?
designmatrix	Design matrix for item parameters (see the ConQuest manual)
only.calibration	Estimate only item parameters and not person parameters (no WLEs or plausible values are estimated)?
init_parameters	Name of an file with initial item parameters (follow the ConQuest specification rules!)
n_plausible	Number of plausible values
persons.elim	Eliminate persons with only missing item responses?
est.wle	Estimate weighted likelihood estimate?
save.bat	Save bat file?
use.bat	Run ConQuest from within R due a direct call via the system command (use.bat=FALSE) or via a system call of a bat file in the working directory (use.bat=TRUE)
read.output	Should ConQuest output files be processed? Default is TRUE.
ignore.pid	Logical indicating whether person identifiers (pid) should be processed in ConQuest input syntax.
object	Object of class R2conquest
showfile	A ConQuest show file (shw file)
term	Name of the term to be extracted in the show file
pvfile	File with plausible values
ndim	Number of dimensions
npv	Number of plausible values
...	Further arguments to be passed

Details

Consult the ConQuest manual (Wu et al., 2007) for specification details.

Value

A list with several entries

`item`	Data frame with item parameters and item statistics
`person`	Data frame with person parameters
`shw.itemparameter`	ConQuest output table for item parameters
`shw.regrparameter`	ConQuest output table for regression parameters
`...`	More values

References

Wu, M. L., Adams, R. J., Wilson, M. R. & Haldane, S. (2007). *ACER ConQuest Version 2.0*. Mulgrave. https://shop.acer.edu.au/acer-shop/group/CON3.

See Also

See also the **eat** package for elaborate functionality of using ConQuest from within R. See also the **conquestr** package for another R wrapper to the ConQuest software (at least version 4 of ConQuest has to be installed).

See also the **TAM** package for similar (and even extended) functionality for specifying item response models.

Examples

```
## Not run:
# define ConQuest path
path.conquest <- "C:/Conquest/"

#############################################################################
# EXAMPLE 1: Dichotomous data (data.pisaMath)
#############################################################################
library(sirt)
data(data.pisaMath)
dat <- data.pisaMath$data

# select items
items <- colnames(dat)[ which( substring( colnames(dat), 1, 1)=="M" ) ]

#***
# Model 11: Rasch model
mod11 <- sirt::R2conquest(dat=dat[,items], path.conquest=path.conquest,
             pid=dat$idstud, name="mod11")
summary(mod11)
# read show file
shw11 <- sirt::read.show( "mod11.shw" )
# read person-item map
pi11 <- sirt::read.pimap(showfile="mod11.shw")
```

```
#***
# Model 12: Rasch model with fixed item difficulties (from Model 1)
mod12 <- sirt::R2conquest(dat=dat[,items], path.conquest=path.conquest,
             pid=dat$idstud, constraints=mod11$item[, c("item","itemdiff")],
             name="mod12")
summary(mod12)

#***
# Model 13: Latent regression model with predictors female, hisei and migra
mod13a <- sirt::R2conquest(dat=dat[,items], path.conquest=path.conquest,
             pid=dat$idstud, X=dat[, c("female", "hisei", "migra") ],
             name="mod13a")
summary(mod13a)

# latent regression with a subset of predictors
mod13b <- sirt::R2conquest(dat=dat[,items], path.conquest=path.conquest,
             pid=dat$idstud, X=dat[, c("female", "hisei", "migra") ],
             regression="hisei migra", name="mod13b")

#***
# Model 14: Differential item functioning (female)
mod14 <- sirt::R2conquest(dat=dat[,items], path.conquest=path.conquest,
             pid=dat$idstud, X=dat[, c("female"), drop=FALSE],
             model="item+female+item*female",  regression="",  name="mod14")

############################################################################
# EXAMPLE 2: Polytomous data (data.Students)
############################################################################
library(CDM)
data(data.Students)
dat <- data.Students

# select items
items <- grep.vec( "act", colnames(dat) )$x

#***
# Model 21: Partial credit model
mod21 <- sirt::R2conquest(dat=dat[,items], path.conquest=path.conquest,
              model="item+item*step",  name="mod21")

#***
# Model 22: Rating scale model
mod22 <- sirt::R2conquest(dat=dat[,items], path.conquest=path.conquest,
              model="item+step", name="mod22")

#***
# Model 23: Multidimensional model
items <- grep.vec( c("act", "sc" ), colnames(dat),  "OR" )$x
qmatrix <- matrix( 0, nrow=length(items), 2 )
qmatrix[1:5,1] <- 1
qmatrix[6:9,2] <- 1
mod23 <- sirt::R2conquest(dat=dat[,items], path.conquest=path.conquest,
```

```
            model="item+item*step", qmatrix=qmatrix, name="mod23")

#############################################################################
# EXAMPLE 3: Multi facet models (data.ratings1)
#############################################################################
library(sirt)
data(data.ratings1)
dat <- data.ratings1

items <- paste0("k",1:5)

# use numeric rater ID's
raters <- as.numeric( substring( paste( dat$rater ), 3 ) )

#***
# Model 31: Rater model 'item+item*step+rater'
mod31 <- sirt::R2conquest(dat=dat[,items], path.conquest=path.conquest,
              itemcodes=0:3, model="item+item*step+rater",
              pid=dat$idstud, X=data.frame("rater"=raters),
              regression="", name="mod31")

#***
# Model 32: Rater model 'item+item*step+rater+item*rater'
mod32 <- sirt::R2conquest(dat=dat[,items], path.conquest=path.conquest,
              model="item+item*step+rater+item*rater",
              pid=dat$idstud, X=data.frame("rater"=raters),
              regression="", name="mod32")

## End(Not run)
```

R2noharm *Estimation of a NOHARM Analysis from within* R

Description

This function enables the estimation of a NOHARM analysis (Fraser & McDonald, 1988; McDonald, 1982a, 1982b, 1997) from within R. NOHARM estimates a compensatory multidimensional factor analysis for dichotomous response data. Arguments of this function strictly follow the rules of the NOHARM manual (see Fraser & McDonald, 2012; Lee & Lee, 2016).

Usage

```
R2noharm(dat=NULL,pm=NULL, n=NULL, model.type, weights=NULL, dimensions=NULL,
      guesses=NULL, noharm.path, F.pattern=NULL, F.init=NULL,
      P.pattern=NULL, P.init=NULL, digits.pm=4, writename=NULL,
      display.fit=5,  dec=".", display=TRUE)

## S3 method for class 'R2noharm'
summary(object, logfile=NULL, ...)
```

Arguments

dat	An $N \times I$ data frame of item responses for N subjects and I items
pm	A matrix or a vector containing product-moment correlations
n	Sample size. This value must only be included if pm is provided.
model.type	Can be "EFA" (exploratory factor analysis) or "CFA" (confirmatory factor analysis).
weights	Optional vector of student weights
dimensions	Number of dimensions in exploratory factor analysis
guesses	An optional vector of fixed guessing parameters of length I. In case of the default NULL, all guessing parameters are set to zero.
noharm.path	Local path where the NOHARM 4 command line 64-bit version is located.
F.pattern	Pattern matrix for F ($I \times D$)
F.init	Initial matrix for F ($I \times D$)
P.pattern	Pattern matrix for P ($D \times D$)
P.init	Initial matrix for P ($D \times D$)
digits.pm	Number of digits after decimal separator which are used for estimation
writename	Name for NOHARM input and output files
display.fit	How many digits (after decimal separator) should be used for printing results on the R console?
dec	Decimal separator (". " or ",")
display	Display output?
object	Object of class R2noharm
logfile	File name if the summary should be sunk into a file
...	Further arguments to be passed

Details

NOHARM estimates a multidimensional compensatory item response model with the probit link function Φ. For item responses X_{pi} of person p on item i the model equation is defined as

$$P(X_{pi} = 1|\boldsymbol{\theta}_p) = c_i + (1 - c_i)\Phi(f_{i0} + f_{i1}\theta_{p1} + ... + f_{iD}\theta_{pD})$$

where $F = (f_{id})$ is a loading matrix and P the covariance matrix of $\boldsymbol{\theta}_p$. The guessing parameters c_i must be provided as fixed values.

For the definition of F and P matrices, please consult the NOHARM manual.

This function needs the 64-bit command line version which can be downloaded from (some links may be broken in the meantime)

http://noharm.niagararesearch.ca/nh4cldl.html
https://noharm.software.informer.com/4.0/
https://cehs.unl.edu/edpsych/software-urls-and-other-interesting-sites/

Value

A list with following entries

`tanaka`	Tanaka index
`rmsr`	RMSR statistic
`N.itempair`	Sample sizes of pairwise item observations
`pm`	Product moment matrix
`weights`	Used student weights
`guesses`	Fixed guessing parameters
`residuals`	Residual covariance matrix
`final.constants`	Vector of final constants
`thresholds`	Threshold parameters
`uniquenesses`	Item uniquenesses
`loadings.theta`	Matrix of loadings in theta parametrization (common factor parametrization)
`factor.cor`	Covariance matrix of factors
`difficulties`	Item difficulties (for unidimensional models)
`discriminations`	Item discriminations (for unidimensional models)
`loadings`	Loading matrix (latent trait parametrization)
`model.type`	Used model type
`Nobs`	Number of observations
`Nitems`	Number of items
`modtype`	Model type according to the NOHARM specification (see NOHARM manual)
`F.init`	Initial loading matrix for F
`F.pattern`	Pattern loading matrix for F
`P.init`	Initial covariance matrix for P
`P.pattern`	Pattern covariance matrix for P
`dat`	Original data frame
`systime`	System time
`noharm.path`	Used NOHARM directory
`digits.pm`	Number of digits in product moment matrix
`dec`	Used decimal symbol
`display.fit`	Number of digits for fit display
`dimensions`	Number of dimensions
`chisquare`	Statistic χ^2
`Nestpars`	Number of estimated parameters
`df`	Degrees of freedom
`chisquare_df`	Ratio χ^2/df
`rmsea`	RMSEA statistic
`p.chisquare`	Significance for χ^2 statistic

Note

Possible errors often occur due to wrong dec specification.

References

Fraser, C., & McDonald, R. P. (1988). NOHARM: Least squares item factor analysis. *Multivariate Behavioral Research, 23*, 267-269. https://doi.org/10.1207/s15327906mbr2302_9

Fraser, C., & McDonald, R. P. (2012). *NOHARM 4 Manual*. http://noharm.niagararesearch.ca/nh4man/nhman.html.

Lee, J. J., & Lee, M. K. (2016). An overview of the normal ogive harmonic analysis robust method (NOHARM) approach to item response theory. *Tutorials in Quantitative Methods for Psychology, 12*(1), 1-8. https://doi.org/10.20982/tqmp.12.1.p001

McDonald, R. P. (1982a). Linear versus nonlinear models in item response theory. *Applied Psychological Measurement, 6*(4), 379-396. doi:10.1177/014662168200600402

McDonald, R. P. (1982b). *Unidimensional and multidimensional models for item response theory*. I.R.T., C.A.T. conference, Minneapolis, 1982, Proceedings.

McDonald, R. P. (1997). Normal-ogive multidimensional model. In W. van der Linden & R. K. Hambleton (1997): *Handbook of modern item response theory* (pp. 257-269). New York: Springer. http://dx.doi.org/10.1007/978-1-4757-2691-6

See Also

For estimating standard errors see R2noharm.jackknife.

For EAP person parameter estimates see R2noharm.EAP.

For an R implementation of the NOHARM model see noharm.sirt.

Examples

```
## Not run:
#############################################################################
# EXAMPLE 1: Data data.noharm18 with 18 items
#############################################################################

# load data
data(data.noharm18)
dat <- data.noharm18
I <- ncol(dat) # number of items

# locate noharm.path
noharm.path <- "c:/NOHARM"

#*****************************************
# Model 1: 1-dimensional Rasch model (1-PL model)

# estimate one factor variance
P.pattern <- matrix( 1, ncol=1, nrow=1 )
P.init <- P.pattern
# fix all entries in the loading matrix to 1
```

```
F.pattern <- matrix( 0, nrow=I, ncol=1 )
F.init <- 1 + 0*F.pattern       #
# estimate model
mod <- sirt::R2noharm( dat=dat, model.type="CFA",
           F.pattern=F.pattern, F.init=F.init, P.pattern=P.pattern,
           P.init=P.init, writename="ex1__1dim_1pl",
       noharm.path=noharm.path, dec="," )
# summary
summary(mod, logfile="ex1__1dim_1pl__SUMMARY")
# jackknife
jmod <- sirt::R2noharm.jackknife( mod, jackunits=20 )
summary(jmod, logfile="ex1__1dim_1pl__JACKKNIFE")
# compute factor scores (EAPs)
emod <- sirt::R2noharm.EAP(mod)

#*****-----
# Model 1b: Include student weights in estimation
N <- nrow(dat)
weights <- stats::runif( N, 1, 5 )
mod1b <- sirt::R2noharm( dat=dat, model.type="CFA",  weights=weights,
            F.pattern=F.pattern, F.init=F.init, P.pattern=P.pattern,
            P.init=P.init, writename="ex1__1dim_1pl_w",
            noharm.path=noharm.path, dec="," )
summary(mod1b)

#**************************************
# Model 2: 1-dimensional 2PL Model

# set trait variance equal to 1
P.pattern <- matrix( 0, ncol=1, nrow=1 )
P.init <- 1+0*P.pattern
# loading matrix
F.pattern <- matrix( 1, nrow=I, ncol=1 )
F.init <- 1 + 0*F.pattern

mod <- sirt::R2noharm( dat=dat, model.type="CFA",
            F.pattern=F.pattern, F.init=F.init, P.pattern=P.pattern,
            P.init=P.init, writename="ex2__1dim_2pl",
            noharm.path=noharm.path, dec="," )

summary(mod)
jmod <- sirt::R2noharm.jackknife( mod, jackunits=20 )
summary(jmod)

#**************************************
# Model 3: 1-dimensional 3PL Model with fixed guessing parameters

# set trait variance equal to 1
P.pattern <- matrix( 0, ncol=1, nrow=1 )
P.init <- 1+0*P.pattern
# loading matrix
F.pattern <- matrix( 1, nrow=I, ncol=1 )
F.init <- 1 + 0*F.pattern       #
```

```
# fix guessing parameters equal to .2 (for all items)
guesses <- rep( .1, I )

mod <- sirt::R2noharm( dat=dat, model.type="CFA",
          F.pattern=F.pattern, F.init=F.init, P.pattern=P.pattern,
          P.init=P.init, guesses=guesses,
          writename="ex3__1dim_3pl", noharm.path=noharm.path, dec="," )
summary(mod)
jmod <- sirt::R2noharm.jackknife( mod, jackunits=20 )
summary(jmod)

#****************************************
# Model 4: 3-dimensional Rasch model

# estimate one factor variance
P.pattern <- matrix( 1, ncol=3, nrow=3 )
P.init <- .8*P.pattern
diag(P.init) <- 1
# fix all entries in the loading matrix to 1
F.init <- F.pattern <- matrix( 0, nrow=I, ncol=3 )
F.init[1:6,1] <- 1
F.init[7:12,2] <- 1
F.init[13:18,3] <- 1

mod <- sirt::R2noharm( dat=dat, model.type="CFA",
          F.pattern=F.pattern, F.init=F.init, P.pattern=P.pattern,
          P.init=P.init, writename="ex4__3dim_1pl",
          noharm.path=noharm.path, dec="," )
# write output from R console in a file
summary(mod, logfile="ex4__3dim_1pl__SUMMARY.Rout")

jmod <- sirt::R2noharm.jackknife( mod, jackunits=20 )
summary(jmod)

# extract factor scores
emod <- sirt::R2noharm.EAP(mod)

#****************************************
# Model 5: 3-dimensional 2PL model

# estimate one factor variance
P.pattern <- matrix( 1, ncol=3, nrow=3 )
P.init <- .8*P.pattern
diag(P.init) <- 0
# fix all entries in the loading matrix to 1
F.pattern <- matrix( 0, nrow=I, ncol=3 )
F.pattern[1:6,1] <- 1
F.pattern[7:12,2] <- 1
F.pattern[13:18,3] <- 1
F.init <- F.pattern

mod <- sirt::R2noharm( dat=dat, model.type="CFA",
          F.pattern=F.pattern, F.init=F.init, P.pattern=P.pattern,
```

```
          P.init=P.init, writename="ex5__3dim_2pl",
          noharm.path=noharm.path, dec="," )
summary(mod)
# use 50 jackknife units with 4 persons within a unit
jmod <- sirt::R2noharm.jackknife( mod, jackunits=seq( 1:50, each=4 ) )
summary(jmod)

#*************************************
# Model 6: Exploratory Factor Analysis with 3 factors

mod <- sirt::R2noharm( dat=dat, model.type="EFA",  dimensions=3,
           writename="ex6__3dim_efa", noharm.path=noharm.path,dec=",")
summary(mod)

jmod <- sirt::R2noharm.jackknife( mod, jackunits=20 )

#############################################################################
# EXAMPLE 2: NOHARM manual Example A
#############################################################################

# See NOHARM manual: http://noharm.niagararesearch.ca/nh4man/nhman.html
# The following text and data is copied from this manual.
#
# In the first example, we demonstrate how to prepare the input for a 2-dimensional
# model using exploratory analysis. Data from a 9 item test were collected from
# 200 students and the 9x9 product-moment matrix of the responses was computed.
#
# Our hypothesis is for a 2-dimensional model with no guessing,
# i.e., all guesses are equal to zero. However, because we are unsure of any
# particular pattern for matrix F, we wish to prescribe an exploratory analysis, i.e.,
# set EX=1. Also, we will content ourselves with letting the program supply all
# initial values.
#
# We would like both the sample product-moment matrix and the residual matrix to
# be included in the output.

# scan product-moment matrix copied from the NOHARM manual
pm <- scan()
     0.8967
     0.2278 0.2356
     0.6857 0.2061 0.7459
     0.8146 0.2310 0.6873 0.8905
     0.4505 0.1147 0.3729 0.4443 0.5000
     0.7860 0.2080 0.6542 0.7791 0.4624 0.8723
     0.2614 0.0612 0.2140 0.2554 0.1914 0.2800 0.2907
     0.7549 0.1878 0.6236 0.7465 0.4505 0.7590 0.2756 0.8442
     0.6191 0.1588 0.5131 0.6116 0.3845 0.6302 0.2454 0.6129 0.6879

ex2 <- sirt::R2noharm( pm=pm, n=200, model.type="EFA", dimensions=2,
         noharm.path=noharm.path, writename="ex2_noharmExA", dec=",")
summary(ex2)

#############################################################################
```

```
# EXAMPLE 3: NOHARM manual Example B
#############################################################################

# See NOHARM manual: http://noharm.niagararesearch.ca/nh4man/nhman.html
# The following text and data is copied from this manual.

# Suppose we have the product-moment matrix of data from 125 students on 9 items.
# Our hypothesis is for 2 dimensions with simple structure. In this case,
# items 1 to 5 have coefficients of theta which are to be estimated for one
# latent trait but are to be fixed at zero for the other one.
# For the latent trait for which items 1 to 5 have zero coefficients,
# items 6 to 9 have coefficients which are to be estimated. For the other
# latent trait, items 6 to 9 will have zero coefficients.
# We also wish to estimate the correlation between the latent traits,
# so we prescribe P as a 2x2 correlation matrix.
#
# Our hypothesis prescribes that there was no guessing involved, i.e.,
# all guesses are equal to zero. For demonstration purposes,
# let us not have the program print out the sample product-moment matrix.
# Also let us not supply any starting values but, rather, use the defaults
# supplied by the program.

pm <- scan()
    0.930
    0.762 0.797
    0.541 0.496 0.560
    0.352 0.321 0.261 0.366
    0.205 0.181 0.149 0.110 0.214
    0.858 0.747 0.521 0.336 0.203 0.918
    0.773 0.667 0.465 0.308 0.184 0.775 0.820
    0.547 0.474 0.347 0.233 0.132 0.563 0.524 0.579
    0.329 0.290 0.190 0.140 0.087 0.333 0.308 0.252 0.348

I <- 9    # number of items
# define loading matrix
F.pattern <- matrix(0,I,2)
F.pattern[1:5,1] <- 1
F.pattern[6:9,2] <- 1
F.init <- F.pattern
# define covariance matrix
P.pattern <- matrix(1,2,2)
diag(P.pattern) <- 0
P.init <- 1+P.pattern

ex3 <- sirt::R2noharm( pm=pm, n=125,, model.type="CFA",
           F.pattern=F.pattern, F.init=F.init, P.pattern=P.pattern,
           P.init=P.init, writename="ex3_noharmExB",
           noharm.path=noharm.path, dec="," )
summary(ex3)

#############################################################################
# EXAMPLE 4: NOHARM manual Example C
#############################################################################
```

```
data(data.noharmExC)
# See NOHARM manual: http://noharm.niagararesearch.ca/nh4man/nhman.html
# The following text and data is copied from this manual.

# In this example, suppose that from 300 respondents we have item
# responses scored dichotomously, 1 or 0, for 8 items.
#
# Our hypothesis is for a unidimensional model where all eight items
# have coefficients of theta which are to be estimated.
# Suppose that since the items were multiple choice with 5 options each,
# we set the fixed guesses all to 0.2 (not necessarily good reasoning!)
#
# Let's supply initial values for the coefficients of theta (F matrix)
# as .75 for items 1 to 4 and .6 for items 5 to 8.

I <- 8
guesses <- rep(.2,I)
F.pattern <- matrix(1,I,1)
F.init <- F.pattern
F.init[1:4,1] <- .75
F.init[5:8,1] <- .6
P.pattern <- matrix(0,1,1)
P.init <- 1 + 0 * P.pattern

ex4 <- sirt::R2noharm( dat=data.noharmExC,, model.type="CFA",
           guesses=guesses, F.pattern=F.pattern, F.init=F.init,
           P.pattern=P.pattern, P.init=P.init, writename="ex3_noharmExC",
           noharm.path=noharm.path, dec="," )
summary(ex4)

# modify F pattern matrix
# f11=f51 (since both have equal pattern values of 2),
# f21=f61 (since both have equal pattern values of 3),
# f31=f71 (since both have equal pattern values of 4),
# f41=f81 (since both have equal pattern values of 5).
F.pattern[ c(1,5) ] <- 2
F.pattern[ c(2,6) ] <- 3
F.pattern[ c(3,7) ] <- 4
F.pattern[ c(4,8) ] <- 5
F.init <- .5+0*F.init

ex4a <- sirt::R2noharm( dat=data.noharmExC,, model.type="CFA",
           guesses=guesses, F.pattern=F.pattern, F.init=F.init,
           P.pattern=P.pattern, P.init=P.init, writename="ex3_noharmExC1",
           noharm.path=noharm.path, dec="," )
summary(ex4a)

## End(Not run)
```

R2noharm.EAP *EAP Factor Score Estimation*

Description

This function performs EAP factor score estimation of an item response model estimated with NOHARM.

Usage

```
R2noharm.EAP(noharmobj, theta.k=seq(-6, 6, len=21), print.output=TRUE)
```

Arguments

noharmobj	Object of class R2noharm or noharm.sirt
theta.k	Vector of discretized theta values on which the posterior is evaluated. This vector applies to all dimensions.
print.output	An optional logical indicating whether output should be displayed at the console

Value

A list with following entries

person	Data frame of person parameter EAP estimates and their corresponding standard errors
theta	Grid of multidimensional theta values where the posterior is evaluated.
posterior	Individual posterior distribution evaluated at theta
like	Individual likelihood
EAP.rel	EAP reliabilities of all dimensions
probs	Item response probabilities evaluated at theta

See Also

For examples see R2noharm and noharm.sirt.

R2noharm.jackknife *Jackknife Estimation of NOHARM Analysis*

Description

This function performs a jackknife estimation of NOHARM analysis to get standard errors based on a replication method (see Christoffersson, 1977).

Usage

```
R2noharm.jackknife(object, jackunits=NULL)

## S3 method for class 'R2noharm.jackknife'
summary(object, logfile=NULL, ...)
```

Arguments

object	Object of class R2noharm
jackunits	A vector of integers or a number. If it is a number, then it refers to the number of jackknife units. If it is a vector of integers, then this vector defines the allocation of persons jackknife units. Integers corresponds to row indexes in the data set.
logfile	File name if the summary should be sunk into a file
...	Further arguments to be passed

Value

A list of lists with following entries:

partable	Data frame with parameters
se.pars	List of estimated standard errors for all parameter estimates: tanaka.stat, rmsr.stat, rmsea.stat, chisquare_df.stat, thresholds.stat, final.constants.stat, uniquenesses.stat, factor.cor.stat, loadings.stat, loadings.theta.stat
jackknife.pars	List with obtained results by jackknifing for all parameters: j.tanaka, j.rmsr, rmsea, chisquare_df, j.pm, j.thresholds, j.factor.cor, j.loadings, j.loadings.theta
u.jacknunits	Unique jackknife elements

References

Christoffersson, A. (1977). Two-step weighted least squares factor analysis of dichotomized variables. *Psychometrika, 42*, 433-438.

See Also

R2noharm

---

rasch.copula2 *Multidimensional IRT Copula Model*

Description

This function handles local dependence by specifying copulas for residuals in multidimensional item response models for dichotomous item responses (Braeken, 2011; Braeken, Tuerlinckx & de Boeck, 2007; Schroeders, Robitzsch & Schipolowski, 2014). Estimation is allowed for item difficulties, item slopes and a generalized logistic link function (Stukel, 1988).

The function rasch.copula3 allows the estimation of multidimensional models while rasch.copula2 only handles unidimensional models.

Usage

```
rasch.copula2(dat, itemcluster, weights=NULL, copula.type="bound.mixt",
    progress=TRUE, mmliter=1000, delta=NULL,
    theta.k=seq(-4, 4, len=21), alpha1=0, alpha2=0,
    numdiff.parm=1e-06,  est.b=seq(1, ncol(dat)),
    est.a=rep(1, ncol(dat)), est.delta=NULL, b.init=NULL, a.init=NULL,
    est.alpha=FALSE, glob.conv=0.0001, alpha.conv=1e-04, conv1=0.001,
    dev.crit=.2, increment.factor=1.01)

rasch.copula3(dat, itemcluster, dims=NULL, copula.type="bound.mixt",
    progress=TRUE, mmliter=1000, delta=NULL,
    theta.k=seq(-4, 4, len=21), alpha1=0, alpha2=0,
    numdiff.parm=1e-06,  est.b=seq(1, ncol(dat)),
    est.a=rep(1, ncol(dat)), est.delta=NULL, b.init=NULL, a.init=NULL,
    est.alpha=FALSE, glob.conv=0.0001, alpha.conv=1e-04, conv1=0.001,
    dev.crit=.2, rho.init=.5, increment.factor=1.01)

## S3 method for class 'rasch.copula2'
summary(object, file=NULL, digits=3, ...)
## S3 method for class 'rasch.copula3'
summary(object, file=NULL, digits=3, ...)

## S3 method for class 'rasch.copula2'
anova(object,...)
## S3 method for class 'rasch.copula3'
anova(object,...)

## S3 method for class 'rasch.copula2'
logLik(object,...)
## S3 method for class 'rasch.copula3'
logLik(object,...)

## S3 method for class 'rasch.copula2'
IRT.likelihood(object,...)
## S3 method for class 'rasch.copula3'
IRT.likelihood(object,...)

## S3 method for class 'rasch.copula2'
IRT.posterior(object,...)
## S3 method for class 'rasch.copula3'
IRT.posterior(object,...)
```

Arguments

dat	An $N \times I$ data frame. Cases with only missing responses are removed from the analysis.
itemcluster	An integer vector of length I (number of items). Items with the same integers define a joint item cluster of (positively) locally dependent items. Values of

	zero indicate that the corresponding item is not included in any item cluster of dependent responses.
weights	Optional vector of sampling weights
dims	A vector indicating to which dimension an item is allocated. The default is that all items load on the first dimension.
copula.type	A character or a vector containing one of the following copula types: bound.mixt (boundary mixture copula), cook.johnson (Cook-Johnson copula) or frank (Frank copula) (see Braeken, 2011). The vector copula.type must match the number of different itemclusters. For every itemcluster, a different copula type may be specified (see Examples).
progress	Print progress? Default is TRUE.
mmliter	Maximum number of iterations.
delta	An optional vector of starting values for the dependency parameter delta.
theta.k	Discretized trait distribution
alpha1	alpha1 parameter in the generalized logistic item response model (Stukel, 1988). The default is 0 which leads together with alpha2=0 to the logistic link function.
alpha2	alpha2 parameter in the generalized logistic item response model
numdiff.parm	Parameter for numerical differentiation
est.b	Integer vector of item difficulties to be estimated
est.a	Integer vector of item discriminations to be estimated
est.delta	Integer vector of length length(itemcluster). Nonzero integers correspond to delta parameters which are estimated. Equal integers indicate parameter equality constraints.
b.init	Initial b parameters
a.init	Initial a parameters
est.alpha	Should both alpha parameters be estimated? Default is FALSE.
glob.conv	Convergence criterion for all parameters
alpha.conv	Maximal change in alpha parameters for convergence
conv1	Maximal change in item parameters for convergence
dev.crit	Maximal change in the deviance. Default is .2.
rho.init	Initial value for off-diagonal elements in correlation matrix
increment.factor	A numeric value larger than one which controls the size of increments in iterations. To stabilize convergence, choose values 1.05 or 1.1 in some situations.
object	Object of class rasch.copula2 or rasch.copula3
file	Optional file name for summary output
digits	Number of digits after decimal in summary output
...	Further arguments to be passed

Value

A list with following entries

`N.itemclusters`	Number of item clusters
`item`	Estimated item parameters
`iter`	Number of iterations
`dev`	Deviance
`delta`	Estimated dependency parameters δ
`b`	Estimated item difficulties
`a`	Estimated item slopes
`mu`	Mean
`sigma`	Standard deviation
`alpha1`	Parameter α_1 in the generalized item response model
`alpha2`	Parameter α_2 in the generalized item response model
`ic`	Information criteria
`theta.k`	Discretized ability distribution
`pi.k`	Fixed θ distribution
`deviance`	Deviance
`pattern`	Item response patterns with frequencies and posterior distribution
`person`	Data frame with person parameters
`datalist`	List of generated data frames during estimation
`EAP.rel`	Reliability of the EAP
`copula.type`	Type of copula
`summary.delta`	Summary for estimated δ parameters
`f.qk.yi`	Individual posterior
`f.yi.qk`	Individual likelihood
`...`	Further values

References

Braeken, J. (2011). A boundary mixture approach to violations of conditional independence. *Psychometrika, 76*(1), 57-76. doi:10.1007/s1133601091904

Braeken, J., Kuppens, P., De Boeck, P., & Tuerlinckx, F. (2013). Contextualized personality questionnaires: A case for copulas in structural equation models for categorical data. *Multivariate Behavioral Research, 48*(6), 845-870. doi:10.1080/00273171.2013.827965

Braeken, J., & Tuerlinckx, F. (2009). Investigating latent constructs with item response models: A MATLAB IRTm toolbox. *Behavior Research Methods, 41*(4), 1127-1137.

Braeken, J., Tuerlinckx, F., & De Boeck, P. (2007). Copula functions for residual dependency. *Psychometrika, 72*(3), 393-411. doi:10.1007/s1133600790054

Schroeders, U., Robitzsch, A., & Schipolowski, S. (2014). A comparison of different psychometric approaches to modeling testlet structures: An example with C-tests. *Journal of Educational Measurement, 51*(4), 400-418. doi:10.1111/jedm.12054

Stukel, T. A. (1988). Generalized logistic models. *Journal of the American Statistical Association, 83*(402), 426-431. doi:10.1080/01621459.1988.10478613

See Also

For a summary see `summary.rasch.copula2`.

For simulating locally dependent item responses see `sim.rasch.dep`.

Person parameters estimates are obtained by `person.parameter.rasch.copula`.

See `rasch.mml2` for the generalized logistic link function.

See also Braeken and Tuerlinckx (2009) for alternative (and more expanded) copula models implemented in the MATLAB software. See `https://ppw.kuleuven.be/okp/software/irtm/`.

See Braeken, Kuppens, De Boeck and Tuerlinckx (2013) for an extension of the copula modeling approach to polytomous data.

Examples

```
#############################################################################
# EXAMPLE 1: Reading Data
#############################################################################

data(data.read)
dat <- data.read

# define item clusters
itemcluster <- rep( 1:3, each=4 )

# estimate Copula model
mod1 <- sirt::rasch.copula2( dat=dat, itemcluster=itemcluster)

## Not run:
# estimate Rasch model
mod2 <- sirt::rasch.copula2( dat=dat, itemcluster=itemcluster,
        delta=rep(0,3), est.delta=rep(0,3) )
summary(mod1)
summary(mod2)

# estimate copula 2PL model
I <- ncol(dat)
mod3 <- sirt::rasch.copula2( dat=dat, itemcluster=itemcluster, est.a=1:I,
                increment.factor=1.05)
summary(mod3)

#############################################################################
# EXAMPLE 2: 11 items nested within 2 item clusters (testlets)
#    with 2 resp. 3 dependent and 6 independent items
#############################################################################
```

```
set.seed(5698)
I <- 11                             # number of items
n <- 3000                           # number of persons
b <- seq(-2,2, len=I)               # item difficulties
theta <- stats::rnorm( n, sd=1 ) # person abilities
# define item clusters
itemcluster <- rep(0,I)
itemcluster[ c(3,5 )] <- 1
itemcluster[c(2,4,9)] <- 2
# residual correlations
rho <- c( .7, .5 )

# simulate data
dat <- sirt::sim.rasch.dep( theta, b, itemcluster, rho )
colnames(dat) <- paste("I", seq(1,ncol(dat)), sep="")

# estimate Rasch copula model
mod1 <- sirt::rasch.copula2( dat, itemcluster=itemcluster )
summary(mod1)

# both item clusters have Cook-Johnson copula as dependency
mod1c <- sirt::rasch.copula2( dat, itemcluster=itemcluster,
            copula.type="cook.johnson")
summary(mod1c)

# first item boundary mixture and second item Cook-Johnson copula
mod1d <- sirt::rasch.copula2( dat, itemcluster=itemcluster,
            copula.type=c( "bound.mixt", "cook.johnson" ) )
summary(mod1d)

# compare result with Rasch model estimation in rasch.copula2
# delta must be set to zero
mod2 <- sirt::rasch.copula2( dat, itemcluster=itemcluster, delta=c(0,0),
            est.delta=c(0,0) )
summary(mod2)

#############################################################################
# EXAMPLE 3: 12 items nested within 3 item clusters (testlets)
#   Cluster 1 -> Items 1-4; Cluster 2 -> Items 6-9;  Cluster 3 -> Items 10-12
#############################################################################

set.seed(967)
I <- 12                             # number of items
n <- 450                            # number of persons
b <- seq(-2,2, len=I)               # item difficulties
b <- sample(b)                      # sample item difficulties
theta <- stats::rnorm( n, sd=1 ) # person abilities
# itemcluster
itemcluster <- rep(0,I)
itemcluster[ 1:4 ] <- 1
itemcluster[ 6:9 ] <- 2
itemcluster[ 10:12 ] <- 3
# residual correlations
```

```
rho <- c( .35, .25, .30 )

# simulate data
dat <- sirt::sim.rasch.dep( theta, b, itemcluster, rho )
colnames(dat) <- paste("I", seq(1,ncol(dat)), sep="")

# estimate Rasch copula model
mod1 <- sirt::rasch.copula2( dat, itemcluster=itemcluster )
summary(mod1)

# person parameter estimation assuming the Rasch copula model
pmod1 <- sirt::person.parameter.rasch.copula(raschcopula.object=mod1 )

# Rasch model estimation
mod2 <- sirt::rasch.copula2( dat, itemcluster=itemcluster,
             delta=rep(0,3), est.delta=rep(0,3) )
summary(mod1)
summary(mod2)

############################################################################
# EXAMPLE 4: Two-dimensional copula model
############################################################################

set.seed(5698)
I <- 9
n <- 1500                           # number of persons
b <- seq(-2,2, len=I)               # item difficulties
theta0 <- stats::rnorm( n, sd=sqrt( .6 ) )

#*** Dimension 1
theta <- theta0 + stats::rnorm( n, sd=sqrt( .4 ) )   # person abilities
# itemcluster
itemcluster <- rep(0,I)
itemcluster[ c(3,5 )] <- 1
itemcluster[c(2,4,9)] <- 2
itemcluster1 <- itemcluster
# residual correlations
rho <- c( .7, .5 )
# simulate data
dat <- sirt::sim.rasch.dep( theta, b, itemcluster, rho )
colnames(dat) <- paste("A", seq(1,ncol(dat)), sep="")
dat1 <- dat
# estimate model of dimension 1
mod0a <- sirt::rasch.copula2( dat1, itemcluster=itemcluster1)
summary(mod0a)

#*** Dimension 2
theta <- theta0 + stats::rnorm( n, sd=sqrt( .8 ) )        # person abilities
# itemcluster
itemcluster <- rep(0,I)
itemcluster[ c(3,7,8 )] <- 1
itemcluster[c(4,6)] <- 2
itemcluster2 <- itemcluster
```

```
# residual correlations
rho <- c( .2, .4 )
# simulate data
dat <- sirt::sim.rasch.dep( theta, b, itemcluster, rho )
colnames(dat) <- paste("B", seq(1,ncol(dat)), sep="")
dat2 <- dat
# estimate model of dimension 2
mod0b <- sirt::rasch.copula2( dat2, itemcluster=itemcluster2)
summary(mod0b)

# both dimensions
dat <- cbind( dat1, dat2 )
itemcluster2 <- ifelse( itemcluster2 > 0, itemcluster2 + 2, 0 )
itemcluster <- c( itemcluster1, itemcluster2 )
dims <- rep( 1:2, each=I)

# estimate two-dimensional copula model
mod1 <- sirt::rasch.copula3( dat, itemcluster=itemcluster, dims=dims, est.a=dims,
            theta.k=seq(-5,5,len=15) )
summary(mod1)

#############################################################################
# EXAMPLE 5: Subset of data Example 2
#############################################################################

set.seed(5698)
I <- 11                             # number of items
n <- 3000                           # number of persons
b <- seq(-2,2, len=I)               # item difficulties
theta <- stats::rnorm( n, sd=1.3 )  # person abilities
# define item clusters
itemcluster <- rep(0,I)
itemcluster[ c(3,5)] <- 1
itemcluster[c(2,4,9)] <- 2
# residual correlations
rho <- c( .7, .5 )
# simulate data
dat <- sirt::sim.rasch.dep( theta, b, itemcluster, rho )
colnames(dat) <- paste("I", seq(1,ncol(dat)), sep="")

# select subdataset with only one dependent item cluster
item.sel <- scan( what="character", nlines=1 )
    I1 I6 I7 I8 I10 I11 I3 I5
dat1 <- dat[,item.sel]

#******************
#*** Model 1a: estimate Copula model in sirt
itemcluster <- rep(0,8)
itemcluster[c(7,8)] <- 1
mod1a <- sirt::rasch.copula2( dat3, itemcluster=itemcluster )
summary(mod1a)

#******************
```

```
#*** Model 1b: estimate Copula model in mirt
library(mirt)
#*** redefine dataset for estimation in mirt
dat2 <- dat1[, itemcluster==0 ]
dat2 <- as.data.frame(dat2)
# combine items 3 and 5
dat2$C35 <- dat1[,"I3"] + 2*dat1[,"I5"]
table( dat2$C35, paste0( dat1[,"I3"],dat1[,"I5"]) )
#* define mirt model
mirtmodel <- mirt::mirt.model("
      F=1-7
      CONSTRAIN=(1-7,a1)
      " )
#-- Copula function with two dependent items
# define item category function for pseudo-items like C35
P.copula2 <- function(par,Theta, ncat){
     b1 <- par[1]
     b2 <- par[2]
     a1 <- par[3]
     ldelta <- par[4]
     P1 <- stats::plogis( a1*(Theta - b1 ) )
     P2 <- stats::plogis( a1*(Theta - b2 ) )
     Q1 <- 1-P1
     Q2 <- 1-P2
     # define vector-wise minimum function
     minf2 <- function( x1, x2 ){
         ifelse( x1 < x2, x1, x2 )
                                 }
     # distribution under independence
     F00 <- Q1*Q2
     F10 <- Q1*Q2 + P1*Q2
     F01 <- Q1*Q2 + Q1*P2
     F11 <- 1+0*Q1
     F_ind <- c(F00,F10,F01,F11)
     # distribution under maximal dependence
     F00 <- minf2(Q1,Q2)
     F10 <- Q2               #=minf2(1,Q2)
     F01 <- Q1               #=minf2(Q1,1)
     F11 <- 1+0*Q1           #=minf2(1,1)
     F_dep <- c(F00,F10,F01,F11)
     # compute mixture distribution
     delta <- stats::plogis(ldelta)
     F_tot <- (1-delta)*F_ind + delta * F_dep
     # recalculate probabilities of mixture distribution
     L1 <- length(Q1)
     v1 <- 1:L1
     F00 <- F_tot[v1]
     F10 <- F_tot[v1+L1]
     F01 <- F_tot[v1+2*L1]
     F11 <- F_tot[v1+3*L1]
     P00 <- F00
     P10 <- F10 - F00
     P01 <- F01 - F00
```

```
     P11 <- 1 - F10 - F01 + F00
     prob_tot <- c( P00, P10, P01, P11 )
     return(prob_tot)
        }
# create item
copula2 <- mirt::createItem(name="copula2", par=c(b1=0, b2=0.2, a1=1, ldelta=0),
               est=c(TRUE,TRUE,TRUE,TRUE), P=P.copula2,
               lbound=c(-Inf,-Inf,0,-Inf), ubound=c(Inf,Inf,Inf,Inf) )
# define item types
itemtype <- c( rep("2PL",6), "copula2" )
customItems <- list("copula2"=copula2)
# parameter table
mod.pars <- mirt::mirt(dat2, 1, itemtype=itemtype,
               customItems=customItems, pars='values')
# estimate model
mod1b <- mirt::mirt(dat2, mirtmodel, itemtype=itemtype, customItems=customItems,
               verbose=TRUE, pars=mod.pars,
               technical=list(customTheta=as.matrix(seq(-4,4,len=21)) ) )
# estimated coefficients
cmod <- sirt::mirt.wrapper.coef(mod)$coef

# compare common item discrimination
round( c("sirt"=mod1a$item$a[1], "mirt"=cmod$a1[1] ), 4 )
  ##     sirt   mirt
  ##   1.2845 1.2862
# compare delta parameter
round( c("sirt"=mod1a$item$delta[7], "mirt"=stats::plogis( cmod$ldelta[7] ) ), 4 )
  ##     sirt   mirt
  ##   0.6298 0.6297
# compare thresholds a*b
dfr <- cbind( "sirt"=mod1a$item$thresh,
              "mirt"=c(- cmod$d[-7],cmod$b1[7]*cmod$a1[1], cmod$b2[7]*cmod$a1[1]))
round(dfr,4)
  ##           sirt    mirt
  ##   [1,] -1.9236 -1.9231
  ##   [2,] -0.0565 -0.0562
  ##   [3,]  0.3993  0.3996
  ##   [4,]  0.8058  0.8061
  ##   [5,]  1.5293  1.5295
  ##   [6,]  1.9569  1.9572
  ##   [7,] -1.1414 -1.1404
  ##   [8,] -0.4005 -0.3996

## End(Not run)
```

Description

This function performs the eigenvector approach to estimate item parameters which is based on a pairwise estimation approach (Garner & Engelhard, 2002). No assumption about person parameters is required for item parameter estimation. Statistical inference is performed by Jackknifing. If a group identifier is provided, tests for differential item functioning are performed.

Usage

```
rasch.evm.pcm(dat, jackunits=20, weights=NULL, pid=NULL,
    group=NULL, powB=2, adj_eps=0.3, progress=TRUE )

## S3 method for class 'rasch.evm.pcm'
summary(object, digits=3, file=NULL, ...)

## S3 method for class 'rasch.evm.pcm'
coef(object,...)

## S3 method for class 'rasch.evm.pcm'
vcov(object,...)
```

Arguments

dat	Data frame with dichotomous or polytomous item responses
jackunits	A number of Jackknife units (if an integer is provided as the argument value) or a vector in which the Jackknife units are already defined.
weights	Optional vector of sample weights
pid	Optional vector of person identifiers
group	Optional vector of group identifiers. In this case, item parameters are group wise estimated and tests for differential item functioning are performed.
powB	Power created in B matrix which is the basis of parameter estimation
adj_eps	Adjustment parameter for person parameter estimation (see mle.pcm.group)
progress	An optional logical indicating whether progress should be displayed
object	Object of class rasch.evm.pcm
digits	Number of digits after decimals for rounding in summary.
file	Optional file name if summary should be sunk into a file.
...	Further arguments to be passed

Value

A list with following entries

item	Data frame with item parameters. The item parameter estimate is denoted by est while a Jackknife bias-corrected estimate is est_jack. The Jackknife standard error is se.
b	Item threshold parameters

person	Data frame with person parameters obtained (MLE)
B	Paired comparison matrix
D	Transformed paired comparison matrix
coef	Vector of estimated coefficients
vcov	Covariance matrix of estimated item parameters
JJ	Number of jackknife units
JJadj	Reduced number of jackknife units
powB	Used power of comparison matrix B
maxK	Maximum number of categories per item
G	Number of groups
desc	Some descriptives
difstats	Statistics for differential item functioning if group is provided as an argument

References

Choppin, B. (1985). A fully conditional estimation procedure for Rasch Model parameters. *Evaluation in Education, 9*, 29-42.

Garner, M., & Engelhard, G. J. (2002). An eigenvector method for estimating item parameters of the dichotomous and polytomous Rasch models. *Journal of Applied Measurement, 3*, 107-128.

Wang, J., & Engelhard, G. (2014). A pairwise algorithm in R for rater-mediated assessments. *Rasch Measurement Transactions, 28*(1), 1457-1459.

See Also

See the **pairwise** package for the alternative row averaging approach of Choppin (1985) and Wang and Engelhard (2014) for an alternative R implementation.

Examples

```
#############################################################################
# EXAMPLE 1: Dataset Liking for Science
#############################################################################

data(data.liking.science)
dat <- data.liking.science

# estimate partial credit model using 10 Jackknife units
mod1 <- sirt::rasch.evm.pcm( dat, jackunits=10 )
summary(mod1)

## Not run:
# compare results with TAM
library(TAM)
mod2 <- TAM::tam.mml( dat )
r1 <- mod2$xsi$xsi
r1 <- r1 - mean(r1)
# item parameters are similar
```

```
dfr <- data.frame( "b_TAM"=r1, mod1$item[,c( "est","est_jack") ] )
round( dfr, 3 )
  ##      b_TAM    est est_jack
  ##  1  -2.496 -2.599   -2.511
  ##  2   0.687  0.824    1.030
  ##  3  -0.871 -0.975   -0.943
  ##  4  -0.360 -0.320   -0.131
  ##  5  -0.833 -0.970   -0.856
  ##  6   1.298  1.617    1.444
  ##  7   0.476  0.465    0.646
  ##  8   2.808  3.194    3.439
  ##  9   1.611  1.460    1.433
  ##  10  2.396  1.230    1.095
  ##  [...]

# partial credit model in eRm package
miceadds::library_install("eRm")
mod3 <- eRm::PCM(X=dat)
summary(mod3)
eRm::plotINFO(mod3)      # plot item and test information
eRm::plotICC(mod3)       # plot ICCs
eRm::plotPImap(mod3)     # plot person-item maps

#############################################################################
# EXAMPLE 2: Garner and Engelhard (2002) toy example dichotomous data
#############################################################################

dat <- scan()
   1 0 1 1   1 1 0 0   1 0 0 0   0 1 1 1   1 1 1 0
   1 1 0 1   1 1 1 1   1 0 1 0   1 1 1 1   1 1 0 0

dat <- matrix( dat, 10, 4, byrow=TRUE)
colnames(dat) <- paste0("I", 1:4 )

# estimate Rasch model with no jackknifing
mod1 <- sirt::rasch.evm.pcm( dat, jackunits=0 )

# paired comparison matrix
mod1$B
  ##          I1_Cat1 I2_Cat1 I3_Cat1 I4_Cat1
  ##  I1_Cat1       0       3       4       5
  ##  I2_Cat1       1       0       3       3
  ##  I3_Cat1       1       2       0       2
  ##  I4_Cat1       1       1       1       0

#############################################################################
# EXAMPLE 3: Garner and Engelhard (2002) toy example polytomous data
#############################################################################

dat <- scan()
   2 2 1 1 1   2 1 2 0 0   1 0 0 0 0   0 1 1 2 0   1 2 2 1 1
   2 2 0 2 1   2 2 1 1 0   1 0 1 0 0   2 1 2 2 2   2 1 0 0 1
```

```
dat <- matrix( dat, 10, 5, byrow=TRUE)
colnames(dat) <- paste0("I", 1:5 )

# estimate partial credit model with no jackknifing
mod1 <- sirt::rasch.evm.pcm( dat, jackunits=0, powB=3 )

# paired comparison matrix
mod1$B
 ##        I1_Cat1 I1_Cat2 I2_Cat1 I2_Cat2 I3_Cat1 I3_Cat2 I4_Cat1 I4_Cat2 I5_Cat1 I5_Cat2
 ##  I1_Cat1       0       0       2       0       1       1       2       1       2       1
 ##  I1_Cat2       0       0       0       3       2       2       2       2       2       3
 ##  I2_Cat1       1       0       0       0       1       1       2       0       2       1
 ##  I2_Cat2       0       1       0       0       1       2       0       3       1       3
 ##  I3_Cat1       1       1       1       1       0       0       1       2       3       1
 ##  I3_Cat2       0       1       0       2       0       0       1       1       1       1
 ##  I4_Cat1       0       1       0       0       0       2       0       0       1       2
 ##  I4_Cat2       1       0       0       2       1       1       0       0       1       1
 ##  I5_Cat1       0       1       0       1       2       1       1       2       0       0
 ##  I5_Cat2       0       0       0       1       0       0       0       0       0       0

#############################################################################
# EXAMPLE 4: Partial credit model for dataset data.mg from CDM package
#############################################################################

library(CDM)
data(data.mg,package="CDM")
dat <- data.mg[, paste0("I",1:11) ]

#*** Model 1: estimate partial credit model
mod1 <- sirt::rasch.evm.pcm( dat )
# item parameters
round( mod1$b, 3 )
 ##        Cat1   Cat2  Cat3
 ##  I1  -1.537     NA    NA
 ##  I2  -2.360     NA    NA
 ##  I3  -0.574     NA    NA
 ##  I4  -0.971 -2.086    NA
 ##  I5  -0.104  0.201    NA
 ##  I6   0.470  0.806    NA
 ##  I7  -1.027  0.756 1.969
 ##  I8   0.897     NA    NA
 ##  I9   0.766     NA    NA
 ##  I10  0.069     NA    NA
 ##  I11 -1.122  1.159 2.689

#*** Model 2: estimate PCM with pairwise package
miceadds::library_install("pairwise")
mod2 <- pairwise::pair(daten=dat)
summary(mod2)
plot(mod2)
# compute standard errors
semod2 <- pairwise::pairSE(daten=dat,  nsample=20)
semod2
```

```
#############################################################################
# EXAMPLE 5: Differential item functioning for dataset data.mg
#############################################################################

library(CDM)
data(data.mg,package="CDM")
dat <- data.mg[ data.mg$group %in% c(2,3,11), ]
# define items
items <- paste0("I",1:11)
# estimate model
mod1 <- sirt::rasch.evm.pcm( dat[,items], weights=dat$weight, group=dat$group )
summary(mod1)

#############################################################################
# EXAMPLE 6: Differential item functioning for Rasch model
#############################################################################

# simulate some data
set.seed(9776)
N <- 1000    # number of persons
I <- 10        # number of items
# simulate data for first group
b <- seq(-1.5,1.5,len=I)
dat1 <- sirt::sim.raschtype( stats::rnorm(N), b )
# simulate data for second group
b1 <- b
b1[4] <- b1[4] + .5 # introduce DIF for fourth item
dat2 <- sirt::sim.raschtype( stats::rnorm(N,mean=.3), b1 )
dat <- rbind(dat1, dat2 )
group <- rep( 1:2, each=N )
# estimate model
mod1 <- sirt::rasch.evm.pcm( dat, group=group )
summary(mod1)

## End(Not run)
```

`rasch.jml` *Joint Maximum Likelihood (JML) Estimation of the Rasch Model*

Description

This function estimates the Rasch model using joint maximum likelihood estimation (Lincare, 1994). The PROX algorithm (Lincare, 1994) is used for the generation of starting values of item parameters.

Usage

```
rasch.jml(dat, method="MLE", b.init=NULL, constraints=NULL, weights=NULL,
   center="persons", glob.conv=10^(-6), conv1=1e-05, conv2=0.001, progress=TRUE,
```

```
    bsteps=4, thetasteps=2, wle.adj=0, jmliter=100, prox=TRUE,
    proxiter=30, proxconv=0.01, dp=NULL, theta.init=NULL, calc.fit=TRUE,
    prior_sd=NULL)

## S3 method for class 'rasch.jml'
summary(object, digits=3, ...)
```

Arguments

dat	An $N \times I$ data frame of dichotomous item responses where N indicates the number of persons and I the number of items
method	Method for estimating person parameters during JML iterations. MLE is maximum likelihood estimation (where person with perfect scores are deleted from analysis). WLE uses weighted likelihood estimation (Warm, 1989) for person parameter estimation. Default is MLE.
b.init	Initial values of item difficulties
constraints	Optional matrix or data.frame with two columns. First column is an integer of item indexes or item names (colnames(dat)) which shall be fixed during estimation. The second column is the corresponding item difficulty.
weights	Person sample weights. Default is NULL, i.e. all persons in the sample are equally weighted.
center	Character indicator whether persons ("persons"), items ("items") should be centered or ("none") should be conducted.
glob.conv	Global convergence criterion with respect to the log-likelihood function
conv1	Convergence criterion for estimation of item parameters
conv2	Convergence criterion for estimation of person parameters
progress	Display progress? Default is TRUE
bsteps	Number of steps for b parameter estimation
thetasteps	Number of steps for theta parameter estimation
wle.adj	Score adjustment for WLE estimation
jmliter	Number of maximal iterations during JML estimation
prox	Should the PROX algorithm (see rasch.prox) be used as initial estimations? Default is TRUE.
proxiter	Number of maximal PROX iterations
proxconv	Convergence criterion for PROX iterations
dp	Object created from data preparation function (.data.prep) which could be created in earlier JML runs. Default is NULL.
theta.init	Initial person parameter estimate
calc.fit	Should itemfit being calculated?
prior_sd	Optional value for standard deviation of prior distribution for ability values if penalized JML should be utilized
object	Object of class rasch.jml
digits	Number of digits used for rounding
...	Further arguments to be passed

Details

The estimation is known to have a bias in item parameters for a fixed (finite) number of items. In literature (Lincare, 1994), a simple bias correction formula is proposed and included in the value `item$itemdiff.correction` in this function. If I denotes the number of items, then the correction factor is $\frac{I-1}{I}$.

Value

A list with following entries

`item`	Estimated item parameters
`person`	Estimated person parameters
`method`	Person parameter estimation method
`dat`	Original data frame
`deviance`	Deviance
`data.proc`	Processed data frames excluding persons with extreme scores
`dp`	Value of data preparation (it is used in the function `rasch.jml.jackknife1`)

References

Linacre, J. M. (1994). *Many-Facet Rasch Measurement*. Chicago: MESA Press.

Warm, T. A. (1989). Weighted likelihood estimation of ability in the item response theory. *Psychometrika, 54*, 427-450.

See Also

Get a summary with `summary.rasch.jml`.

See `rasch.prox` for the PROX algorithm as initial iterations.

For a bias correction of the JML method try `rasch.jml.jackknife1`.

JML estimation can also be conducted with the **TAM** (`TAM::tam.jml`) and **immer** (`immer::immer_jml`) packages.

See also marginal maximum likelihood estimation with `rasch.mml2` or the R package **ltm**.

Examples

```
#############################################################################
# EXAMPLE 1: Simulated data from the Rasch model
#############################################################################

set.seed(789)
N <- 500    # number of persons
I <- 11     # number of items
b <- seq( -2, 2, length=I )
dat <- sirt::sim.raschtype( stats::rnorm( N, mean=.5 ), b )
colnames(dat) <- paste( "I", 1:I, sep="")

# JML estimation of the Rasch model (centering persons)
```

```
mod1 <- sirt::rasch.jml( dat )
summary(mod1)

# JML estimation of the Rasch model (centering items)
mod1b <- sirt::rasch.jml( dat, center="items" )
summary(mod1b)

# MML estimation with rasch.mml2 function
mod2 <- sirt::rasch.mml2( dat )
summary(mod2)

# Pairwise method of Fischer
mod3 <- sirt::rasch.pairwise( dat )
summary(mod3)

# JML estimation in TAM
## Not run:
library(TAM)
mod4 <- TAM::tam.jml( resp=dat )

#******
# item parameter constraints in JML estimation
# fix item difficulties: b[4]=-.76 and b[6]=.10
constraints <- matrix( cbind( 4, -.76,
                              6, .10 ),
                  ncol=2, byrow=TRUE )
mod6 <- sirt::rasch.jml( dat, constraints=constraints )
summary(mod6)
  # For constrained item parameters, it this not obvious
  # how to calculate a 'right correction' of item parameter bias

## End(Not run)
```

`rasch.jml.biascorr` *Bias Correction of Item Parameters for Joint Maximum Likelihood Estimation in the Rasch model*

Description

This function computes an analytical bias correction for the Rasch model according to the method of Arellano and Hahn (2007).

Usage

```
rasch.jml.biascorr(jmlobj,itemfac=NULL)
```

Arguments

`jmlobj`	An object which is the output of the `rasch.jml` function
`itemfac`	Number of items which are used for bias correction. By default it is the average number of item responses per person.

Value

A list with following entries

`b.biascorr`	Matrix of item difficulty estimates. The column `b.analytcorr1` contains item difficulties by analytical bias correction of Method 1 in Arellano and Hahn (2007) whereas `b.analytcorr2` corresponds to Method 2.
`b.bias1`	Estimated bias by Method 1
`b.bias2`	Estimated bias by Method 2
`itemfac`	Number of items which are used as the factor for bias correction

References

Arellano, M., & Hahn, J. (2007). Understanding bias in nonlinear panel models: Some recent developments. In R. Blundell, W. Newey & T. Persson (Eds.): *Advances in Economics and Econometrics, Ninth World Congress*, Cambridge University Press.

See Also

See `rasch.jml.jackknife1` for bias correction based on Jackknife.

See also the **bife** R package for analytical bias corrections.

Examples

```
#############################################################################
# EXAMPLE 1: Dataset Reading
#############################################################################
data(data.read)
dat <- data( data.read )

# estimate Rasch model
mod <- sirt::rasch.jml( data.read  )

# JML with analytical bias correction
res1 <- sirt::rasch.jml.biascorr( jmlobj=mod  )
print( res1$b.biascorr, digits=3 )
  ##        b.JML b.JMLcorr b.analytcorr1 b.analytcorr2
  ##   1  -2.0086   -1.8412        -1.908        -1.922
  ##   2  -1.1121   -1.0194        -1.078        -1.088
  ##   3  -0.0718   -0.0658        -0.150        -0.127
  ##   4   0.5457    0.5002         0.393         0.431
  ##   5  -0.9504   -0.8712        -0.937        -0.936
  ##  [...]
```

`rasch.jml.jackknife1` *Jackknifing the IRT Model Estimated by Joint Maximum Likelihood (JML)*

Description

Jackknife estimation is an alternative to other ad hoc proposed methods for bias correction (Hahn & Newey, 2004).

Usage

```
rasch.jml.jackknife1(jmlobj)
```

Arguments

`jmlobj`	Output of `rasch.jml`

Details

Note that items are used for jackknifing (Hahn & Newey, 2004). By default, all I items in the data frame are used as jackknife units.

Value

A list with following entries

`item` A data frame with item parameters

- `b.JML`: Item difficulty from JML estimation
- `b.JMLcorr`: Item difficulty from JML estimation by applying the correction factor $(I-1)/I$
- `b.jack`: Item difficulty from Jackknife estimation
- `b.jackse`: Standard error of Jackknife estimation for item difficulties. Note that this parameter refer to the standard error with respect to item sampling
- `b.JMLse`: Standard error for item difficulties obtained from JML estimation

`jack.itemdiff` A matrix containing all item difficulties obtained by Jackknife

References

Hahn, J., & Newey, W. (2004). Jackknife and analytical bias reduction for nonlinear panel models. *Econometrica, 72*, 1295-1319.

See Also

For JML estimation `rasch.jml`.

For analytical bias correction methods see `rasch.jml.biascorr`.

Examples

```
## Not run:
#############################################################################
# EXAMPLE 1: Simulated data from the Rasch model
#############################################################################
set.seed(7655)
N <- 5000    # number of persons
I <- 11      # number of items
b <- seq( -2, 2, length=I )
dat <- sirt::sim.raschtype( rnorm( N ), b )
colnames(dat) <- paste( "I", 1:I, sep="")

# estimate the Rasch model with JML
mod <- sirt::rasch.jml(dat)
summary(mod)

# re-estimate the Rasch model using Jackknife
mod2 <- sirt::rasch.jml.jackknife1( mod )
  ##
  ##   Joint Maximum Likelihood Estimation
  ##   Jackknife Estimation
  ##   11 Jackknife Units are used
  ##   |--------------------PROGRESS--------------------|
  ##   |-------------------------------------------------|
  ##
  ##          N     p  b.JML b.JMLcorr b.jack b.jackse b.JMLse
  ##   I1  4929 0.853 -2.345    -2.131 -2.078    0.079   0.045
  ##   I2  4929 0.786 -1.749    -1.590 -1.541    0.075   0.039
  ##   I3  4929 0.723 -1.298    -1.180 -1.144    0.065   0.036
  ##   I4  4929 0.657 -0.887    -0.806 -0.782    0.059   0.035
  ##   I5  4929 0.576 -0.420    -0.382 -0.367    0.055   0.033
  ##   I6  4929 0.492  0.041     0.038  0.043    0.054   0.033
  ##   I7  4929 0.409  0.502     0.457  0.447    0.056   0.034
  ##   I8  4929 0.333  0.939     0.854  0.842    0.058   0.035
  ##   I9  4929 0.264  1.383     1.257  1.229    0.065   0.037
  ##   I10 4929 0.210  1.778     1.617  1.578    0.071   0.040
  ##   I11 4929 0.154  2.266     2.060  2.011    0.077   0.044
#-> Item parameters obtained by jackknife seem to be acceptable.

## End(Not run)
```

`rasch.mirtlc` *Multidimensional Latent Class 1PL and 2PL Model*

Description

This function estimates the multidimensional latent class Rasch (1PL) and 2PL model (Bartolucci, 2007; Bartolucci, Montanari & Pandolfi, 2012) for dichotomous data which emerges from the original latent class model (Goodman, 1974) and a multidimensional IRT model.

Usage

```
rasch.mirtlc(dat, Nclasses=NULL, modeltype="LC", dimensions=NULL,
    group=NULL, weights=rep(1,nrow(dat)), theta.k=NULL, ref.item=NULL,
    distribution.trait=FALSE,  range.b=c(-8,8), range.a=c(.2, 6 ),
    progress=TRUE, glob.conv=10^(-5), conv1=10^(-5), mmliter=1000,
    mstep.maxit=3, seed=0, nstarts=1, fac.iter=.35)

## S3 method for class 'rasch.mirtlc'
summary(object,...)

## S3 method for class 'rasch.mirtlc'
anova(object,...)

## S3 method for class 'rasch.mirtlc'
logLik(object,...)

## S3 method for class 'rasch.mirtlc'
IRT.irfprob(object,...)

## S3 method for class 'rasch.mirtlc'
IRT.likelihood(object,...)

## S3 method for class 'rasch.mirtlc'
IRT.posterior(object,...)

## S3 method for class 'rasch.mirtlc'
IRT.modelfit(object,...)

## S3 method for class 'IRT.modelfit.rasch.mirtlc'
summary(object,...)
```

Arguments

dat	An $N \times I$ data frame
Nclasses	Number of latent classes. If the trait vector (or matrix) theta.k is specified, then Nclasses is set to the dimension of theta.k.
modeltype	Modeltype. LC is the latent class model of Goodman (1974). MLC1 is the multidimensional latent class Rasch model with item discrimination parameter of 1. MLC2 allows for the estimation of item discriminations.
dimensions	Vector of dimension integers which allocate items to dimensions.
group	A group identifier for multiple group estimation
weights	Vector of sample weights
theta.k	A grid of theta values can be specified if theta should not be estimated. In the one-dimensional case, it must be a vector, in the D-dimensional case it must be a matrix of dimension D.
ref.item	An optional vector of integers which indicate the items whose intercept and slope are fixed at 0 and 1, respectively.

`distribution.trait`
: A type of the assumed theta distribution can be specified. One alternative is `normal` for the normal distribution assumption. The options `smooth2`, `smooth3` and `smooth4` use the log-linear smoothing of Xu and von Davier (2008) to smooth the distribution up to two, three or four moments, respectively. This function only works in unidimensional models.
If a different string is provided as an input (e.g. `no`), then no smoothing is conducted.

`range.b`
: Range of item difficulties which are allowed for estimation

`range.a`
: Range of item slopes which are allowed for estimation

`progress`
: Display progress? Default is `TRUE`.

`glob.conv`
: Global relative deviance convergence criterion

`conv1`
: Item parameter convergence criterion

`mmliter`
: Maximum number of iterations

`mstep.maxit`
: Maximum number of iterations within an M step

`seed`
: Set random seed for latent class estimation. A seed can be specified. If the seed is negative, then the function will generate a random seed.

`nstarts`
: If a positive integer is provided, then a `nstarts` starts with different starting values are conducted.

`fac.iter`
: A parameter between 0 and 1 to control the maximum increment in each iteration. The larger the parameter the more increments will become smaller from iteration to iteration.

`object`
: Object of class `rasch.mirtlc`

`...`
: Further arguments to be passed

Details

The multidimensional latent class Rasch model (Bartolucci, 2007) is an item response model which combines ideas from latent class analysis and item response models with continuous variables. With `modeltype="MLC2"` the following D-dimensional item response model is estimated

$$logit P(X_{pi}=1|\theta_p) = a_i \theta_{pcd} - b_i$$

Besides the item thresholds b_i and item slopes a_i, for a prespecified number of latent classes $c = 1, \ldots, C$ a set of C D-dimensional $\{\theta_{cd}\}_{cd}$ vectors are estimated. These vectors represent the locations of latent classes. If the user provides a grid of theta distribution `theta.k` as an argument in `rasch.mirtlc`, then the ability distribution is fixed.

In the unidimensional Rasch model with I items, $(I+1)/2$ (if I odd) or $I/2+1$ (if I even) trait location parameters are identified (see De Leeuw & Verhelst, 1986; Lindsay et al., 1991; for a review see Formann, 2007).

Value

A list with following entries

`pjk`
: Item probabilities evaluated at discretized ability distribution

`rprobs`	Item response probabilities like in `pjk`, but for each item category
`pi.k`	Estimated trait distribution
`theta.k`	Discretized ability distribution
`item`	Estimated item parameters
`trait`	Estimated ability distribution (`theta.k` and `pi.k`)
`mean.trait`	Estimated mean of ability distribution
`sd.trait`	Estimated standard deviation of ability distribution
`skewness.trait`	Estimated skewness of ability distribution
`cor.trait`	Estimated correlation between abilities (only applies for multidimensional models)
`ic`	Information criteria
`D`	Number of dimensions
`G`	Number of groups
`deviance`	Deviance
`ll`	Log-likelihood
`Nclasses`	Number of classes
`modeltype`	Used model type
`estep.res`	Result from E step: `f.qk.yi` is the individual posterior, `f.yi.qk` is the individual likelihood
`dat`	Original data frame
`devL`	Vector of deviances if multiple random starts were conducted
`seedL`	Vector of seed if multiple random starts were conducted
`iter`	Number of iterations

Note

For the estimation of latent class models, rerunning the model with different starting values (different random seeds) is recommended.

References

Bartolucci, F. (2007). A class of multidimensional IRT models for testing unidimensionality and clustering items. *Psychometrika, 72*(2), 141-157. doi:10.1007/s1133600513769

Bartolucci, F., Montanari, G. E., & Pandolfi, S. (2012). Dimensionality of the latent structure and item selection via latent class multidimensional IRT models. *Psychometrika, 77*(4), 782-802. doi:10.1007/s1133601292780

De Leeuw, J., & Verhelst, N. (1986). Maximum likelihood estimation in generalized Rasch models. *Journal of Educational and Behavioral Statistics, 11*(3), 183-196. doi:10.3102/10769986011003183

Formann, A. K. (2007). (Almost) Equivalence between conditional and mixture maximum likelihood estimates for some models of the Rasch type. In M. von Davier & C. H. Carstensen: *Multivariate and Mixture Distribution Rasch Models* (pp. 177-189). Springer: New York. doi:10.1007/9780387498393_11

Goodman, L. A. (1974). Exploratory latent structure analysis using both identifiable and unidentifiable models. *Biometrika, 61*(2), 215-231. doi:10.1093/biomet/61.2.215

Lindsay, B., Clogg, C. C., & Grego, J. (1991). Semiparametric estimation in the Rasch model and related exponential response models, including a simple latent class model for item analysis. *Journal of the American Statistical Association, 86*(413), 96-107. doi:10.1080/01621459.1991.10475008

Xu, X., & von Davier, M. (2008). *Fitting the structured general diagnostic model to NAEP data*. ETS Research Report ETS RR-08-27. Princeton, ETS. doi:10.1002/j.23338504.2008.tb02113.x

See Also

See also the `CDM::gdm` function in the **CDM** package.

For an assessment of global model fit see `modelfit.sirt`.

The estimation of the multidimensional latent class item response model for polytomous data can be conducted in the **MultiLCIRT** package. Latent class analysis can be carried out with **poLCA** and **randomLCA** packages.

Examples

```
#############################################################################
# EXAMPLE 1: Reading data
#############################################################################
data( data.read )
dat <- data.read

#***************
# latent class models

# latent class model with 1 class
mod1 <- sirt::rasch.mirtlc( dat, Nclasses=1 )
summary(mod1)

# latent class model with 2 classes
mod2 <- sirt::rasch.mirtlc( dat, Nclasses=2 )
summary(mod2)

## Not run:
# latent class model with 3 classes
mod3 <- sirt::rasch.mirtlc( dat, Nclasses=3, seed=- 30)
summary(mod3)

# extract individual likelihood
lmod3 <- IRT.likelihood(mod3)
str(lmod3)
# extract likelihood value
logLik(mod3)
# extract item response functions
IRT.irfprob(mod3)

# compare models 1, 2 and 3
anova(mod2,mod3)
```

```
IRT.compareModels(mod1,mod2,mod3)
# avsolute and relative model fit
smod2 <- IRT.modelfit(mod2)
smod3 <- IRT.modelfit(mod3)
summary(smod2)
IRT.compareModels(smod2,smod3)

# latent class model with 4 classes and 3 starts with different seeds
mod4 <- sirt::rasch.mirtlc( dat, Nclasses=4,seed=-30,  nstarts=3 )
# display different solutions
sort(mod4$devL)
summary(mod4)

# latent class multiple group model
# define group identifier
group <- rep( 1, nrow(dat))
group[ 1:150 ] <- 2
mod5 <- sirt::rasch.mirtlc( dat, Nclasses=3, group=group )
summary(mod5)

#*************
# Unidimensional IRT models with ordered trait

# 1PL model with 3 classes
mod11 <- sirt::rasch.mirtlc( dat, Nclasses=3, modeltype="MLC1", mmliter=30)
summary(mod11)

# 1PL model with 11 classes
mod12 <- sirt::rasch.mirtlc( dat, Nclasses=11,modeltype="MLC1", mmliter=30)
summary(mod12)

# 1PL model with 11 classes and fixed specified theta values
mod13 <- sirt::rasch.mirtlc( dat,  modeltype="MLC1",
             theta.k=seq( -4, 4, len=11 ), mmliter=100)
summary(mod13)

# 1PL model with fixed theta values and normal distribution
mod14 <- sirt::rasch.mirtlc( dat,  modeltype="MLC1", mmliter=30,
             theta.k=seq( -4, 4, len=11 ), distribution.trait="normal")
summary(mod14)

# 1PL model with a smoothed trait distribution (up to 3 moments)
mod15 <- sirt::rasch.mirtlc( dat,  modeltype="MLC1", mmliter=30,
             theta.k=seq( -4, 4, len=11 ),  distribution.trait="smooth3")
summary(mod15)

# 2PL with 3 classes
mod16 <- sirt::rasch.mirtlc( dat, Nclasses=3, modeltype="MLC2", mmliter=30 )
summary(mod16)

# 2PL with fixed theta and smoothed distribution
mod17 <- sirt::rasch.mirtlc( dat, theta.k=seq(-4,4,len=12), mmliter=30,
             modeltype="MLC2", distribution.trait="smooth4"  )
```

```
summary(mod17)

# 1PL multiple group model with 8 classes
# define group identifier
group <- rep( 1, nrow(dat))
group[ 1:150 ] <- 2
mod21 <- sirt::rasch.mirtlc( dat, Nclasses=8, modeltype="MLC1", group=group )
summary(mod21)

#***************
# multidimensional latent class IRT models

# define vector of dimensions
dimensions <- rep( 1:3, each=4 )

# 3-dimensional model with 8 classes and seed 145
mod31 <- sirt::rasch.mirtlc( dat, Nclasses=8, mmliter=30,
             modeltype="MLC1", seed=145, dimensions=dimensions )
summary(mod31)

# try the model above with different starting values
mod31s <- sirt::rasch.mirtlc( dat, Nclasses=8,
             modeltype="MLC1", seed=-30, nstarts=30, dimensions=dimensions )
summary(mod31s)

# estimation with fixed theta vectors
#=> 4^3=216 classes
theta.k <- seq(-4, 4, len=6 )
theta.k <- as.matrix( expand.grid( theta.k, theta.k, theta.k ) )
mod32 <- sirt::rasch.mirtlc( dat,  dimensions=dimensions,
              theta.k=theta.k, modeltype="MLC1"  )
summary(mod32)

# 3-dimensional 2PL model
mod33 <- sirt::rasch.mirtlc( dat, dimensions=dimensions, theta.k=theta.k, modeltype="MLC2")
summary(mod33)

#############################################################################
# EXAMPLE 2: Skew trait distribution
#############################################################################
set.seed(789)
N <- 1000   # number of persons
I <- 20     # number of items
theta <- sqrt( exp( stats::rnorm( N ) ) )
theta <- theta - mean(theta )
# calculate skewness of theta distribution
mean( theta^3 ) / stats::sd(theta)^3
# simulate item responses
dat <- sirt::sim.raschtype( theta, b=seq(-2,2,len=I ) )

# normal distribution
mod1 <- sirt::rasch.mirtlc( dat, theta.k=seq(-4,4,len=15), modeltype="MLC1",
              distribution.trait="normal", mmliter=30)
```

```
# allow for skew distribution with smoothed distribution
mod2 <- sirt::rasch.mirtlc( dat, theta.k=seq(-4,4,len=15), modeltype="MLC1",
               distribution.trait="smooth3", mmliter=30)

# nonparametric distribution
mod3 <- sirt::rasch.mirtlc( dat, theta.k=seq(-4,4,len=15), modeltype="MLC1", mmliter=30)

summary(mod1)
summary(mod2)
summary(mod3)

#############################################################################
# EXAMPLE 3: Stouffer-Toby dataset data.si02 with 5 items
#############################################################################

data(dat.si02)
dat <- data.si02$data
weights <- data.si02$weights   # extract weights

# Model 1: 2 classes Rasch model
mod1 <- sirt::rasch.mirtlc( dat, Nclasses=2, modeltype="MLC1", weights=weights,
                ref.item=4, nstarts=5)
summary(mod1)

# Model 2: 3 classes Rasch model: not all parameters are identified
mod2 <- sirt::rasch.mirtlc( dat, Nclasses=3, modeltype="MLC1", weights=weights,
               ref.item=4, nstarts=5)
summary(mod2)

# Model 3: Latent class model with 2 classes
mod3 <- sirt::rasch.mirtlc( dat, Nclasses=2, modeltype="LC", weights=weights, nstarts=5)
summary(mod3)

# Model 4: Rasch model with normal distribution
mod4 <- sirt::rasch.mirtlc( dat,  modeltype="MLC1", weights=weights,
            theta.k=seq( -6, 6, len=21 ), distribution.trait="normal", ref.item=4)
summary(mod4)

## End(Not run)

#############################################################################
# EXAMPLE 4: 5 classes, 3 dimensions and 27 items
#############################################################################

set.seed(979)
I <- 9
N <- 5000
b <- seq( - 1.5, 1.5, len=I)
b <- rep(b,3)
# define class locations
theta.k <- c(-3.0, -4.1, -2.8, 1.7, 2.3, 1.8,
   0.2, 0.4, -0.1,   2.6, 0.1, -0.9, -1.1,-0.7, 0.9 )
```

```
Nclasses <- 5
theta.k0 <- theta.k <- matrix( theta.k, Nclasses, 3, byrow=TRUE )
pi.k <- c(.20,.25,.25,.10,.15)
theta <- theta.k[ rep( 1:Nclasses, round(N*pi.k) ), ]
dimensions <- rep( 1:3, each=I)
# simulate item responses
dat <- matrix( NA, nrow=N, ncol=I*3)
for (ii in 1:(3*I) ){
    dat[,ii] <- 1 * ( stats::runif(N) < stats::plogis( theta[,dimensions[ii]] - b[ii]))
}
colnames(dat) <- paste0( rep( LETTERS[1:3], each=I ), 1:(3*I) )

# estimate model
mod1 <- sirt::rasch.mirtlc( dat, Nclasses=Nclasses, dimensions=dimensions,
             modeltype="MLC1", ref.item=c(5,14,23), glob.conv=.0005, conv1=.0005)

round( cbind( mod1$theta.k, mod1$pi.k ), 3 )
  ##          [,1]   [,2]   [,3]  [,4]
  ##   [1,] -2.776 -3.791 -2.667 0.250
  ##   [2,] -0.989 -0.605  0.957 0.151
  ##   [3,]  0.332  0.418 -0.046 0.246
  ##   [4,]  2.601  0.171 -0.854 0.101
  ##   [5,]  1.791  2.330  1.844 0.252
cbind( theta.k, pi.k )
  ##                        pi.k
  ##   [1,] -3.0 -4.1 -2.8 0.20
  ##   [2,]  1.7  2.3  1.8 0.25
  ##   [3,]  0.2  0.4 -0.1 0.25
  ##   [4,]  2.6  0.1 -0.9 0.10
  ##   [5,] -1.1 -0.7  0.9 0.15

# plot class locations
plot( 1:3, mod1$theta.k[1,], xlim=c(1,3), ylim=c(-5,3), col=1, pch=1, type="n",
    axes=FALSE, xlab="Dimension", ylab="Location")
axis(1, 1:3 ) ;  axis(2) ; axis(4)
for (cc in 1:Nclasses){ # cc <- 1
    lines(1:3, mod1$theta.k[cc,], col=cc, lty=cc )
    points(1:3, mod1$theta.k[cc,], col=cc,  pch=cc )
}

## Not run:
#------
# estimate model with gdm function in CDM package
library(CDM)
# define Q-matrix
Qmatrix <- matrix(0,3*I,3)
Qmatrix[ cbind( 1:(3*I), rep(1:3, each=I) ) ] <- 1

set.seed(9176)
# random starting values for theta locations
theta.k <- matrix( 2*stats::rnorm(5*3), 5, 3 )
colnames(theta.k) <- c("Dim1","Dim2","Dim3")
```

```
# try possibly different starting values

# estimate model in CDM
b.constraint  <- cbind( c(5,14,23), 1, 0 )
mod2 <- CDM::gdm( dat, theta.k=theta.k, b.constraint=b.constraint, skillspace="est",
               irtmodel="1PL",  Qmatrix=Qmatrix)
summary(mod2)

#------
# estimate model with MultiLCIRT package
miceadds::library_install("MultiLCIRT")

# define matrix to allocate each item to one dimension
multi1 <- matrix( 1:(3*I), nrow=3, byrow=TRUE )
# define reference items in item-dimension allocation matrix
multi1[ 1, c(1,5)  ] <- c(5,1)
multi1[ 2, c(10,14) - 9  ] <- c(14,9)
multi1[ 3, c(19,23) - 18 ] <- c(23,19)

# Rasch model with 5 latent classes (random start: start=1)
mod3 <- MultiLCIRT::est_multi_poly(S=dat,k=5,       # k=5 ability levels
                start=1,link=1,multi=multi1,tol=10^-5,
                output=TRUE, disp=TRUE, fort=TRUE)
# estimated location points and class probabilities in MultiLCIRT
cbind( t( mod3$Th ), mod3$piv )
# compare results with rasch.mirtlc
cbind( mod1$theta.k, mod1$pi.k )
# simulated data parameters
cbind( theta.k, pi.k )

#----
# estimate model with cutomized input in mirt
library(mirt)
#-- define Theta design matrix for 5 classes
Theta <- diag(5)
Theta <- cbind( Theta, Theta, Theta )
r1 <- rownames(Theta) <- paste0("C",1:5)
colnames(Theta) <- c( paste0(r1, "D1"), paste0(r1, "D2"), paste0(r1, "D3") )
  ##      C1D1 C2D1 C3D1 C4D1 C5D1 C1D2 C2D2 C3D2 C4D2 C5D2 C1D3 C2D3 C3D3 C4D3 C5D3
  ##   C1    1    0    0    0    0    1    0    0    0    0    1    0    0    0    0
  ##   C2    0    1    0    0    0    0    1    0    0    0    0    1    0    0    0
  ##   C3    0    0    1    0    0    0    0    1    0    0    0    0    1    0    0
  ##   C4    0    0    0    1    0    0    0    0    1    0    0    0    0    1    0
  ##   C5    0    0    0    0    1    0    0    0    0    1    0    0    0    0    1
#-- define mirt model
I <- ncol(dat)  # I=27
mirtmodel <- mirt::mirt.model("
        C1D1=1-9 \n C2D1=1-9 \n  C3D1=1-9 \n  C4D1=1-9  \n  C5D1=1-9
        C1D2=10-18 \n C2D2=10-18 \n  C3D2=10-18 \n  C4D2=10-18  \n  C5D2=10-18
        C1D3=19-27 \n C2D3=19-27 \n  C3D3=19-27 \n  C4D3=19-27  \n  C5D3=19-27
        CONSTRAIN=(1-9,a1),(1-9,a2),(1-9,a3),(1-9,a4),(1-9,a5),
                    (10-18,a6),(10-18,a7),(10-18,a8),(10-18,a9),(10-18,a10),
                    (19-27,a11),(19-27,a12),(19-27,a13),(19-27,a14),(19-27,a15)
```

```
               ")
#-- get initial parameter values
mod.pars <- mirt::mirt(dat, model=mirtmodel,  pars="values")
#-- redefine initial parameter values
# set all d parameters initially to zero
ind <- which( ( mod.pars$name=="d" ) )
mod.pars[ ind,"value" ]  <- 0
# fix item difficulties of reference items to zero
mod.pars[ ind[ c(5,14,23) ], "est"] <- FALSE
mod.pars[ind,]
# initial item parameters of cluster locations (a1,...,a15)
ind <- which( ( mod.pars$name %in% paste0("a", c(1,6,11) ) ) & ( mod.pars$est ) )
mod.pars[ind,"value"] <- -2
ind <- which( ( mod.pars$name %in% paste0("a", c(1,6,11)+1 ) ) & ( mod.pars$est ) )
mod.pars[ind,"value"] <- -1
ind <- which( ( mod.pars$name %in% paste0("a", c(1,6,11)+2 ) ) & ( mod.pars$est ) )
mod.pars[ind,"value"] <- 0
ind <- which( ( mod.pars$name %in% paste0("a", c(1,6,11)+3 ) ) & ( mod.pars$est ) )
mod.pars[ind,"value"] <- 1
ind <- which( ( mod.pars$name %in% paste0("a", c(1,6,11)+4 ) ) & ( mod.pars$est ) )
mod.pars[ind,"value"] <- 0
#-- define prior for latent class analysis
lca_prior <- function(Theta,Etable){
  TP <- nrow(Theta)
  if ( is.null(Etable) ){ prior <- rep( 1/TP, TP ) }
  if ( ! is.null(Etable) ){
    prior <- ( rowSums(Etable[, seq(1,2*I,2)]) + rowSums(Etable[,seq(2,2*I,2)]) )/I
  }
  prior <- prior / sum(prior)
  return(prior)
}

#-- estimate model in mirt
mod4 <- mirt::mirt(dat, mirtmodel, pars=mod.pars, verbose=TRUE,
              technical=list( customTheta=Theta, customPriorFun=lca_prior,
                    MAXQUAD=1E20) )
# correct number of estimated parameters
mod4@nest <- as.integer(sum(mod.pars$est) + nrow(Theta)-1 )
# extract coefficients
# source.all(pfsirt)
cmod4 <- sirt::mirt.wrapper.coef(mod4)

# estimated item difficulties
dfr <- data.frame( "sim"=b, "mirt"=-cmod4$coef$d, "sirt"=mod1$item$thresh )
round( dfr, 4 )
  ##         sim    mirt    sirt
  ##   1  -1.500 -1.3782 -1.3382
  ##   2  -1.125 -1.0059 -0.9774
  ##   3  -0.750 -0.6157 -0.6016
  ##   4  -0.375 -0.2099 -0.2060
  ##   5   0.000  0.0000  0.0000
  ##   6   0.375  0.5085  0.4984
  ##   7   0.750  0.8661  0.8504
```

```
  ##   8   1.125  1.3079  1.2847
  ##   9   1.500  1.5891  1.5620
  ##   [...]

#-- reordering estimated latent clusters to make solutions comparable
#* extract estimated cluster locations from sirt
order.sirt <- c(1,5,3,4,2)  # sort(order.sirt)
round(mod1$trait[,1:3],3)
dfr <- data.frame( "sim"=theta.k, mod1$trait[order.sirt,1:3] )
colnames(dfr)[4:6] <- paste0("sirt",1:3)
#* extract estimated cluster locations from mirt
c4 <- cmod4$coef[, paste0("a",1:15) ]
c4 <- apply( c4,2, FUN=function(ll){ ll[ ll!=0 ][1] } )
trait.loc <- matrix(c4,5,3)
order.mirt <- c(1,4,3,5,2)  # sort(order.mirt)
dfr <- cbind( dfr, trait.loc[ order.mirt, ] )
colnames(dfr)[7:9] <- paste0("mirt",1:3)
# compare estimated cluster locations
round(dfr,3)
  ##     sim.1 sim.2 sim.3  sirt1  sirt2  sirt3  mirt1  mirt2  mirt3
  ##   1  -3.0  -4.1  -2.8 -2.776 -3.791 -2.667 -2.856 -4.023 -2.741
  ##   5   1.7   2.3   1.8  1.791  2.330  1.844  1.817  2.373  1.869
  ##   3   0.2   0.4  -0.1  0.332  0.418 -0.046  0.349  0.421 -0.051
  ##   4   2.6   0.1  -0.9  2.601  0.171 -0.854  2.695  0.166 -0.876
  ##   2  -1.1  -0.7   0.9 -0.989 -0.605  0.957 -1.009 -0.618  0.962
#* compare estimated cluster sizes
dfr <- data.frame( "sim"=pi.k, "sirt"=mod1$pi.k[order.sirt,1],
            "mirt"=mod4@Prior[[1]][ order.mirt] )
round(dfr,4)
  ##      sim   sirt   mirt
  ##   1 0.20 0.2502 0.2500
  ##   2 0.25 0.2522 0.2511
  ##   3 0.25 0.2458 0.2494
  ##   4 0.10 0.1011 0.0986
  ##   5 0.15 0.1507 0.1509

############################################################################
# EXAMPLE 5: Dataset data.si04 from Bartolucci et al. (2012)
############################################################################

data(data.si04)

# define reference items
ref.item <- c(7,17,25,44,64)
dimensions <- data.si04$itempars$dim

# estimate a Rasch latent class with 9 classes
mod1 <- sirt::rasch.mirtlc( data.si04$data, Nclasses=9, dimensions=dimensions,
             modeltype="MLC1", ref.item=ref.item, glob.conv=.005, conv1=.005,
             nstarts=1, mmliter=200 )

# compare estimated distribution with simulated distribution
round( cbind( mod1$theta.k, mod1$pi.k ), 4 ) # estimated
```

```
##            [,1]    [,2]    [,3]    [,4]    [,5]   [,6]
##    [1,] -3.6043 -5.1323 -5.3022 -6.8255 -4.3611 0.1341
##    [2,]  0.2083 -2.7422 -2.8754 -5.3416 -2.5085 0.1573
##    [3,] -2.8641 -4.0272 -5.0580 -0.0340 -0.9113 0.1163
##    [4,] -0.3575 -2.0081 -1.7431  1.2992 -0.1616 0.0751
##    [5,]  2.9329  0.3662 -1.6516 -3.0284  0.1844 0.1285
##    [6,]  1.5092 -2.0461 -4.3093  1.0481  1.0806 0.1094
##    [7,]  3.9899  3.1955 -4.0010  1.8879  2.2988 0.1460
##    [8,]  4.3062  0.7080 -1.2324  1.4351  2.0893 0.1332
##    [9,]  5.0855  4.1214 -0.9141  2.2744  1.5314 0.0000

round(d2,4) # simulated
##         class      A      B      C      D      E     pi
##    [1,]     1 -3.832 -5.399 -5.793 -7.042 -4.511 0.1323
##    [2,]     2 -2.899 -4.217 -5.310 -0.055 -0.915 0.1162
##    [3,]     3 -0.376 -2.137 -1.847  1.273 -0.078 0.0752
##    [4,]     4  0.208 -2.934 -3.011 -5.526 -2.511 0.1583
##    [5,]     5  1.536 -2.137 -4.606  1.045  1.143 0.1092
##    [6,]     6  2.042 -0.573 -0.404 -4.331 -1.044 0.0471
##    [7,]     7  3.853  0.841 -2.993 -2.746  0.803 0.0822
##    [8,]     8  4.204  3.296 -4.328  1.892  2.419 0.1453
##    [9,]     9  4.466  0.700 -1.334  1.439  2.161 0.1343

## End(Not run)
```

`rasch.mml2` *Estimation of the Generalized Logistic Item Response Model, Ramsay's Quotient Model, Nonparametric Item Response Model, Pseudo-Likelihood Estimation and a Missing Data Item Response Model*

Description

This function employs marginal maximum likelihood estimation of item response models for dichotomous data. First, the Rasch type model (generalized item response model) can be estimated. The generalized logistic link function (Stukel, 1988) can be estimated or fixed for conducting IRT with different link functions than the logistic one. The Four-Parameter logistic item response model is a special case of this model (Loken & Rulison, 2010). Second, Ramsay's quotient model (Ramsay, 1989) can be estimated by specifying `irtmodel="ramsay.qm"`. Third, quite general item response functions can be estimated in a nonparametric framework (Rossi, Wang & Ramsay, 2002). Fourth, pseudo-likelihood estimation for fractional item responses can be conducted for Rasch type models. Fifth, a simple two-dimensional missing data item response model (`irtmodel='missing1'`; Mislevy & Wu, 1996) can be estimated.

See Details for more explanations.

Usage

```
rasch.mml2( dat, theta.k=seq(-6,6,len=21), group=NULL, weights=NULL,
   constraints=NULL, glob.conv=10^(-5), parm.conv=10^(-4), mitermax=4,
   mmliter=1000, progress=TRUE,  fixed.a=rep(1,ncol(dat)),
```

```
    fixed.c=rep(0,ncol(dat)), fixed.d=rep(1,ncol(dat)),
    fixed.K=rep(3,ncol(dat)), b.init=NULL, est.a=NULL, est.b=NULL,
    est.c=NULL, est.d=NULL, min.b=-99, max.b=99, min.a=-99, max.a=99,
   min.c=0, max.c=1, min.d=0, max.d=1, prior.b=NULL, prior.a=NULL, prior.c=NULL,
    prior.d=NULL, est.K=NULL, min.K=1, max.K=20, min.delta=-20, max.delta=20,
  beta.init=NULL, min.beta=-8, pid=1:(nrow(dat)), trait.weights=NULL, center.trait=TRUE,
    center.b=FALSE, alpha1=0, alpha2=0,est.alpha=FALSE, equal.alpha=FALSE,
    designmatrix=NULL, alpha.conv=parm.conv, numdiff.parm=0.00001,
    numdiff.alpha.parm=numdiff.parm, distribution.trait="normal", Qmatrix=NULL,
    variance.fixed=NULL, variance.init=NULL,
    mu.fixed=cbind(seq(1,ncol(Qmatrix)),rep(0,ncol(Qmatrix))),
    irtmodel="raschtype", npformula=NULL, npirt.monotone=TRUE,
    use.freqpatt=is.null(group), delta.miss=0, est.delta=rep(NA,ncol(dat)),
    nimps=0, ... )

## S3 method for class 'rasch.mml'
summary(object, file=NULL, ...)

## S3 method for class 'rasch.mml'
plot(x, items=NULL, xlim=NULL, main=NULL, ...)

## S3 method for class 'rasch.mml'
anova(object,...)

## S3 method for class 'rasch.mml'
logLik(object,...)

## S3 method for class 'rasch.mml'
IRT.irfprob(object,...)

## S3 method for class 'rasch.mml'
IRT.likelihood(object,...)

## S3 method for class 'rasch.mml'
IRT.posterior(object,...)

## S3 method for class 'rasch.mml'
IRT.modelfit(object,...)

## S3 method for class 'rasch.mml'
IRT.expectedCounts(object,...)

## S3 method for class 'IRT.modelfit.rasch.mml'
summary(object,...)
```

Arguments

dat	An $N \times I$ data frame of dichotomous item responses. For the missing data item response model (`irtmodel='missing1'`), code item

	responses by 9 which should be treated by the missing data model. Other missing responses can be coded by NA.
theta.k	Optional vector of discretized theta values. For multidimensional IRT models with D dimensions, it is a matrix with D columns.
group	Vector of integers with group identifiers in multiple group estimation. The multiple group does not work for irtmodel="missing1".
weights	Optional vector of person weights (sample weights).
constraints	Constraints on b parameters (item difficulties). It must be a matrix with two columns: the first column contains item names, the second column fixed parameter values.
glob.conv	Convergence criterion for deviance
parm.conv	Convergence criterion for item parameters
mitermax	Maximum number of iterations in M step. This argument does only apply for the estimation of the b parameters.
mmliter	Maximum number of iterations
progress	Should progress be displayed at the console?
fixed.a	Fixed or initial a parameters
fixed.c	Fixed or initial c parameters
fixed.d	Fixed or initial d parameters
fixed.K	Fixed or initial K parameters in Ramsay's quotient model.
b.init	Initial b parameters
est.a	Vector of integers which indicate which a parameters should be estimated. Equal integers correspond to the same estimated parameters.
est.b	Vector of integers which indicate which b parameters should be estimated. Equal integers correspond to the same estimated parameters.
est.c	Vector of integers which indicate which c parameters should be estimated. Equal integers correspond to the same estimated parameters.
est.d	Vector of integers which indicate which d parameters should be estimated. Equal integers correspond to the same estimated parameters.
min.b	Minimal b parameter to be estimated
max.b	Maximal b parameter to be estimated
min.a	Minimal a parameter to be estimated
max.a	Maximal a parameter to be estimated
min.c	Minimal c parameter to be estimated
max.c	Maximal c parameter to be estimated
min.d	Minimal d parameter to be estimated
max.d	Maximal d parameter to be estimated
prior.b	Optional prior distribution for b parameters: $N(\mu, \sigma)$. Input is a vector of length two with parameters μ and σ.

`prior.a` Optional prior distribution for a parameters: $N(\mu, \sigma)$. Input is a vector of length two with parameters μ and σ.

`prior.c` Optional prior distribution for c parameters: $Beta(a, b)$. Input is a vector of length two with parameters a and b.

`prior.d` Optional prior distribution for d parameters: $Beta(a, b)$. Input is a vector of length two with parameters a and b.

`est.K` Vector of integers which indicate which K parameters should be estimated. Equal integers correspond to the same estimated parameters.

`min.K` Minimal K parameter to be estimated

`max.K` Maximal K parameter to be estimated

`min.delta` Minimal $delta.miss$ parameter to be estimated

`max.delta` Maximal $delta.miss$ parameter to be estimated

`beta.init` Optional vector of initial β parameters

`min.beta` Minimum β parameter to be estimated.

`pid` Optional vector of person identifiers

`trait.weights` Optional vector of trait weights for a fixing the trait distribution.

`center.trait` Should the trait distribution be centered

`center.b` An optional logical indicating whether b parameters should be centered at each dimension

`alpha1` Fixed or initial α_1 parameter

`alpha2` Fixed or initial α_2 parameter

`est.alpha` Should α parameters be estimated?

`equal.alpha` Estimate α parameters under the assumption $\alpha_1 = \alpha_2$?

`designmatrix` Design matrix for item difficulties b to estimate linear logistic test models

`alpha.conv` Convergence criterion for α parameter

`numdiff.parm` Parameter for numerical differentiation

`numdiff.alpha.parm` Parameter for numerical differentiation for α parameter

`distribution.trait` Assumed trait distribution. The default is the normal distribution (`"normal"`). Log-linear smoothing of the trait distribution is also possible (`"smooth2"`, `"smooth3"` or `"smooth4"` for smoothing up to 2, 3 or 4 moments, respectively).

`Qmatrix` The Q-matrix

`variance.fixed` Matrix for fixing covariance matrix (See Examples)

`variance.init` Optional initial covariance matrix

`mu.fixed` Matrix for fixing mean vector (See Examples)

`irtmodel` Specify estimable IRT models: `raschtype` (Rasch type model), `ramsay.qm` (Ramsay's quotient model), `npirt` (Nonparametric item response model). If `npirt` is used as the argument for `irtmodel`, the argument `npformula` specifies different item response functions in the R formula framework (like `"y~I(theta^2)"`; see Examples). For estimating the missing data item response model, use `irtmodel='missing1'`.

npformula	A string or a vector which contains R formula objects for specifying the item response function. For example, "y~theta" is the specification of the 2PL model (see Details). If irtmodel="npirt" and npformula is not specified, then an unrestricted item response functions on the grid of θ values is estimated.
npirt.monotone	Should nonparametrically estimated item response functions be monotone? The default is TRUE. This function applies only to irtmodel='npirt' and npformula=NULL.
use.freqpatt	A logical if frequencies of pattern should be used or not. The default is is.null(group). This means that for single group analyses, frequency patterns are used but not for multiple groups. If data processing times are large, then use.freqpatt=FALSE is recommended.
delta.miss	Missingness parameter δ quantifying the meaning of responding to an item between the two extremes of ignoring missing responses and setting all missing responses to incorrect
est.delta	Vector with indices indicating the δ parameters to be estimated if irtmodel="missing1".
nimps	Number of imputed datasets of item responses
object	Object of class rasch.mml
x	Object of class rasch.mml
items	Vector of integer or item names which should be plotted
xlim	Specification for xlim in plot
main	Title of the plot
file	Optional file name for summary output
...	Further arguments to be passed

Details

The item response function of the generalized item response model (irtmodel="raschtype"; Stukel, 1988) can be written as

$$P(X_{pi}=1|\theta_{pd}) = c_i + (d_i - c_i) g_{\alpha_1,\alpha_2}[a_i(\theta_{pd} - b_i)]$$

where g is the generalized logistic link function depending on parameters α_1 and α_2.

For the most important link functions the specifications are (Stukel, 1988):

logistic link function: $\alpha_1 = 0$ and $\alpha_2 = 0$
probit link function: $\alpha_1 = 0.165$ and $\alpha_2 = 0.165$
loglog link function: $\alpha_1 = -0.037$ and $\alpha_2 = 0.62$
cloglog link function: $\alpha_1 = 0.62$ and $\alpha_2 = -0.037$

See pgenlogis for exact transformation formulas of the mentioned link functions.

A D-dimensional model can also be specified but only allows for between item dimensionality (one item loads on one and only dimension). Setting $c_i = 0$, $d_i = 1$ and $a_i = 1$ for all items i, an additive item response model

$$P(X_{pi}=1|\theta_p) = g_{\alpha_1,\alpha_2}(\theta_p - b_i)$$

is estimated.

Ramsay's quotient model (`irtmodel="qm.ramsay"`) uses the item response function

$$P(X_{pi}=1|\theta_p)=\frac{\exp(\theta_p/b_i)}{K_i+\exp(\theta_p/b_i)}$$

Quite general unidimensional item response models can be estimated in a nonparametric framework (`irtmodel="npirt"`). The response functions are a linear combination of transformed θ values

$$logit[P(X_{pi}=1|\theta_p)]=Y_\theta\beta$$

Where Y_θ is a design matrix of θ and β are item parameters to be estimated. The formula $Y_\theta\beta$ can be specified in the R formula framework (see Example 3, Model 3c).

Pseudo-likelihood estimation can be conducted for fractional item response data as input (i.e. some item response x_{pi} do have values between 0 and 1). Then the pseudo-likelihood L_p for person p is defined as

$$L_p=\prod_i P_i(\theta_p)^{x_{pi}}[1-P_i(\theta_p)]^{(1-x_{pi})}$$

Note that for dichotomous responses this term corresponds to the ordinary likelihood. See Example 7.

A special two-dimensional missing data item response model (`irtmodel="missing1"`) is implemented according to Mislevy and Wu (1996). Besides an unidimensional ability θ_p, an individual response propensity ξ_p is proposed. We define item responses X_{pi} and response indicators R_{pi} indicating whether item responses X_{pi} are observed or not. Denoting the logistic function by Ψ, the item response model for ability is defined as

$$P(X_{pi}=1|\theta_p,\xi_p)=P(X_{pi}=1|\theta_p)=\Psi(a_i(\theta_p-b_i))$$

We also define a measurement model for response indicators R_{pi} which depends on the item response X_{pi} itself:

$$P(R_{pi}=1|X_{pi}=k,\theta_p,\xi_p)=P(R_{pi}=1|X_{pi}=k,\xi_p)=\Psi\left[\xi_p-\beta_i-k\delta_i\right] \quad \text{for} \quad k=0,1$$

If $\delta_i=0$, then the probability of responding to an item is independent of the incompletely observed item X_{pi} which is an item response model with nonignorable missings (Holman & Glas, 2005; see also Pohl, Graefe & Rose, 2014). If δ_i is a large negative number (e.g. $\delta=-100$), then it follows $P(R_{pi}=1|X_{pi}=1,\theta_p,\xi_p)=1$ and as a consequence it holds that $P(X_{pi}=1|R_{pi}=0,\theta_p,\xi_p)=0$, which is equivalent to treating all missing item responses as incorrect. The missingness parameter δ can be specified by the user and studied as a sensitivity analysis under different missing not at random assumptions or can be estimated by choosing `est.delta=TRUE`.

Value

A list with following entries

`dat`	Original data frame
`item`	Estimated item parameters in the generalized item response model
`item2`	Estimated item parameters for Ramsay's quotient model
`trait.distr`	Discretized ability distribution points and probabilities
`mean.trait`	Estimated mean vector

sd.trait	Estimated standard deviations
skewness.trait	Estimated skewnesses
deviance	Deviance
pjk	Estimated probabilities of item correct evaluated at theta.k
rprobs	Item response probabilities like in pjk, but slightly extended to accommodate all categories
person	Person parameter estimates: mode (MAP) and mean (EAP) of the posterior distribution
pid	Person identifier
ability.est.pattern	Response pattern estimates
f.qk.yi	Individual posterior distribution
f.yi.qk	Individual likelihood
fixed.a	Estimated a parameters
fixed.c	Estimated c parameters
G	Number of groups
alpha1	Estimated α_1 parameter in generalized logistic item response model
alpha2	Estimated α_2 parameter in generalized logistic item response model
se.b	Standard error of b parameter in generalized logistic model or Ramsay's quotient model
se.a	Standard error of a parameter in generalized logistic model
se.c	Standard error of c parameter in generalized logistic model
se.d	Standard error of d parameter in generalized logistic model
se.alpha	Standard error of α parameter in generalized logistic model
se.K	Standard error of K parameter in Ramsay's quotient model
iter	Number of iterations
reliability	EAP reliability
irtmodel	Type of estimated item response model
D	Number of dimensions
mu	Mean vector (for multidimensional models)
Sigma.cov	Covariance matrix (for multdimensional models)
theta.k	Grid of discretized ability distributions
trait.weights	Fixed vector of probabilities for the ability distribution
pi.k	Trait distribution
ic	Information criteria
esttype	Estimation type: ll (Log-Likelihood), pseudoll (Pseudo-Log-Likelihood)
...	

Note

Multiple group estimation is not possible for Ramsay's quotient model and multdimensional models.

References

Holman, R., & Glas, C. A. (2005). Modelling non-ignorable missing-data mechanisms with item response theory models. *British Journal of Mathematical and Statistical Psychology, 58*(1), 1-17. doi:10.1348/000711005X47168

Loken, E., & Rulison, K. L. (2010). Estimation of a four-parameter item response theory model. *British Journal of Mathematical and Statistical Psychology, 63*(3), 509-525. doi:10.1348/000711009X474502

Mislevy, R. J., & Wu, P. K. (1996). *Missing responses and IRT ability estimation: Omits, choice, time Limits, and adaptive testing*. ETS Research Report ETS RR-96-30. Princeton, ETS. doi:10.1002/j.23338504.1996.tb01708.x

Pohl, S., Graefe, L., & Rose, N. (2014). Dealing with omitted and not-reached items in competence tests evaluating approaches accounting for missing responses in item response theory models. *Educational and Psychological Measurement, 74*(3), 423-452. doi:10.1177/0013164413504926

Ramsay, J. O. (1989). A comparison of three simple test theory models. *Psychometrika, 54*, 487-499. doi:10.1007/BF02294631

Rossi, N., Wang, X., & Ramsay, J. O. (2002). Nonparametric item response function estimates with the EM algorithm. *Journal of Educational and Behavioral Statistics, 27*(3), 291-317. doi:10.3102/10769986027003291

Stukel, T. A. (1988). Generalized logistic models. *Journal of the American Statistical Association, 83*(402), 426-431. doi:10.1080/01621459.1988.10478613

van der Maas, H. J. L., Molenaar, D., Maris, G., Kievit, R. A., & Borsboom, D. (2011). Cognitive psychology meets psychometric theory: On the relation between process models for decision making and latent variable models for individual differences. *Psychological Review, 118*(2), 339-356. doi: 10.1037/a0022749

See Also

Simulate the generalized logistic Rasch model with `sim.raschtype`.

Simulate Ramsay's quotient model with `sim.qm.ramsay`.

Simulate locally dependent item response data using `sim.rasch.dep`.

For an assessment of global model fit see `modelfit.sirt`.

See `CDM::itemfit.sx2` for item fit statistics.

Examples

```
#############################################################################
# EXAMPLE 1: Reading dataset
#############################################################################

library(CDM)
data(data.read)
dat <- data.read
```

```
I <- ncol(dat) # number of items

# Rasch model
mod1 <- sirt::rasch.mml2( dat )
summary(mod1)
plot( mod1 )    # plot all items
# title 'Rasch model', display curves from -3 to 3 only for items 1, 5 and 8
plot(mod1, main="Rasch model Items 1, 5 and 8", xlim=c(-3,3), items=c(1,5,8) )

# Rasch model with constraints on item difficulties
# set item parameters of A1 and C3 equal to -2
constraints <- data.frame( c("A1","C3"), c(-2,-2) )
mod1a <- sirt::rasch.mml2( dat, constraints=constraints)
summary(mod1a)

# estimate equal item parameters for 1st and 11th item
est.b <- 1:I
est.b[11] <- 1
mod1b <- sirt::rasch.mml2( dat, est.b=est.b )
summary(mod1b)

# estimate Rasch model with skew trait distribution
mod1c <- sirt::rasch.mml2( dat, distribution.trait="smooth3")
summary(mod1c)

# 2PL model
mod2 <- sirt::rasch.mml2( dat, est.a=1:I )
summary(mod2)
plot(mod2)    # plot 2PL item response curves

# extract individual likelihood
llmod2 <- IRT.likelihood(mod2)
str(llmod2)

## Not run:
library(CDM)
# model comparisons
CDM::IRT.compareModels(mod1, mod1c, mod2 )
anova(mod1,mod2)

# assess model fit
smod1 <- IRT.modelfit(mod1)
smod2 <- IRT.modelfit(mod2)
IRT.compareModels(smod1, smod2)

# set some bounds for a and b parameters
mod2a <- sirt::rasch.mml2( dat, est.a=1:I, min.a=.7, max.a=2, min.b=-2 )
summary(mod2a)

# 3PL model
mod3 <- sirt::rasch.mml2( dat, est.a=1:I, est.c=1:I,
              mmliter=400 # maximal 400 iterations
                 )
```

```
summary(mod3)

# 3PL model with fixed guessing paramters of .25 and equal slopes
mod4 <- sirt::rasch.mml2( dat, fixed.c=rep( .25, I )   )
summary(mod4)

# 3PL model with equal guessing paramters for all items
mod5 <- sirt::rasch.mml2( dat, est.c=rep(1, I )   )
summary(mod5)

# difficulty + guessing model
mod6 <- sirt::rasch.mml2( dat, est.c=1:I   )
summary(mod6)

# 4PL model
mod7 <- sirt::rasch.mml2( dat, est.a=1:I, est.c=1:I, est.d=1:I,
            min.d=.95, max.c=.25)
        # set minimal d and maximal c parameter to .95 and .25
summary(mod7)

# 4PL model with prior distributions
mod7b <- sirt::rasch.mml2( dat, est.a=1:I, est.c=1:I, est.d=1:I, prior.a=c(1,2),
            prior.c=c(5,17), prior.d=c(20,2) )
summary(mod7b)

# constrained 4PL model
# equal slope, guessing and slipping parameters
mod8 <- sirt::rasch.mml2( dat,est.c=rep(1,I), est.d=rep(1,I) )
summary(mod8)

# estimation of an item response model with an
# uniform theta distribution
theta.k <- seq( 0.01, .99, len=20 )
trait.weights <- rep( 1/length(theta.k), length(theta.k) )
mod9 <- sirt::rasch.mml2( dat, theta.k=theta.k, trait.weights=trait.weights,
              normal.trait=FALSE, est.a=1:12  )
summary(mod9)

#############################################################################
# EXAMPLE 2: Longitudinal data
#############################################################################

data(data.long)
dat <- data.long[,-1]

# define Q loading matrix
Qmatrix <- matrix( 0, 12, 2 )
Qmatrix[1:6,1] <- 1 # T1 items
Qmatrix[7:12,2] <- 1    # T2 items

# define restrictions on item difficulties
est.b <- c(1,2,3,4,5,6,   3,4,5,6,7,8)
mu.fixed <- cbind(1,0)
```

```
    # set first mean to 0 for identification reasons

# Model 1: 2-dimensional Rasch model
mod1 <- sirt::rasch.mml2( dat, Qmatrix=Qmatrix, miterstep=4,
            est.b=est.b,  mu.fixed=mu.fixed, mmliter=30 )
summary(mod1)
plot(mod1)
##     Plot function is only applicable for unidimensional models

## End(Not run)

#############################################################################
# EXAMPLE 3: One group, estimation of alpha parameter in the generalized logistic model
#############################################################################

# simulate theta values
set.seed(786)
N <- 1000                  # number of persons
theta <- stats::rnorm( N, sd=1.5 ) # N persons with SD 1.5
b <- seq( -2, 2, len=15)

# simulate data
dat <- sirt::sim.raschtype( theta=theta, b=b, alpha1=0, alpha2=-0.3 )

#  estimating alpha parameters
mod1 <- sirt::rasch.mml2( dat, est.alpha=TRUE, mmliter=30 )
summary(mod1)
plot(mod1)

## Not run:
# fixed alpha parameters
mod1b <- sirt::rasch.mml2( dat, est.alpha=FALSE, alpha1=0, alpha2=-.3 )
summary(mod1b)

# estimation with equal alpha parameters
mod1c <- sirt::rasch.mml2( dat, est.alpha=TRUE, equal.alpha=TRUE )
summary(mod1c)

# Ramsay QM
mod2a <- sirt::rasch.mml2( dat, irtmodel="ramsay.qm" )
summary(mod2a)

## End(Not run)

# Ramsay QM with estimated K parameters
mod2b <- sirt::rasch.mml2( dat, irtmodel="ramsay.qm", est.K=1:15, mmliter=30)
summary(mod2b)
plot(mod2b)

## Not run:
# nonparametric estimation of monotone item response curves
mod3a <- sirt::rasch.mml2( dat, irtmodel="npirt", mmliter=100,
            theta.k=seq( -3, 3, len=10) ) # evaluations at 10 theta grid points
```

```
# nonparametric ICC of first 4 items
round( t(mod3a$pjk)[1:4,], 3 )
summary(mod3a)
plot(mod3a)

# nonparametric IRT estimation without monotonicity assumption
mod3b <- sirt::rasch.mml2( dat, irtmodel="npirt", mmliter=10,
            theta.k=seq( -3, 3, len=10), npirt.monotone=FALSE)
plot(mod3b)

# B-Spline estimation of ICCs
library(splines)
mod3c <- sirt::rasch.mml2( dat, irtmodel="npirt",
             npformula="y~bs(theta,df=3)", theta.k=seq(-3,3,len=15) )
summary(mod3c)
round( t(mod3c$pjk)[1:6,], 3 )
plot(mod3c)

# estimation of quadratic item response functions: ~ theta + I( theta^2)
mod3d <- sirt::rasch.mml2( dat, irtmodel="npirt",
             npformula="y~theta + I(theta^2)" )
summary(mod3d)
plot(mod3d)

# estimation of a stepwise ICC function
# ICCs are constant on the theta domains: [-Inf,-1], [-1,1], [1,Inf]
mod3e <- sirt::rasch.mml2( dat, irtmodel="npirt",
             npformula="y~I(theta>-1 )+I(theta>1)" )
summary(mod3e)
plot(mod3e, xlim=c(-2.5,2.5) )

# 2PL model
mod4 <- sirt::rasch.mml2( dat,  est.a=1:15)
summary(mod4)

#############################################################################
# EXAMPLE 4: Two groups, estimation of generalized logistic model
#############################################################################

# simulate generalized logistic Rasch model in two groups
set.seed(8765)
N1 <- 1000     # N1=1000 persons in group 1
N2 <- 500      # N2=500 persons in group 2
dat1 <- sirt::sim.raschtype( theta=stats::rnorm( N1, sd=1.5 ), b=b,
            alpha1=-0.3, alpha2=0)
dat2 <- sirt::sim.raschtype( theta=stats::rnorm( N2, mean=-.5, sd=.75),
            b=b, alpha1=-0.3, alpha2=0)
dat1 <- rbind( dat1, dat2 )
group <- c( rep(1,N1), rep(2,N2))

mod1 <-  sirt::rasch.mml2( dat1, parm.conv=.0001, group=group, est.alpha=TRUE )
summary(mod1)
```

```
#############################################################################
# EXAMPLE 5: Multidimensional model
#############################################################################

#***
# (1) simulate data
set.seed(785)
library(mvtnorm)
N <- 500
theta <- mvtnorm::rmvnorm( N,mean=c(0,0), sigma=matrix( c(1.45,.5,.5,1.7), 2, 2 ))
I <- 10
# 10 items load on the first dimension
p1 <- stats::plogis( outer( theta[,1], seq( -2, 2, len=I ), "-" ) )
resp1 <- 1 * ( p1 > matrix( stats::runif( N*I ), nrow=N, ncol=I ) )
# 10 items load on the second dimension
p1 <- stats::plogis( outer( theta[,2], seq( -2, 2, len=I ), "-" ) )
resp2 <- 1 * ( p1 > matrix( stats::runif( N*I ), nrow=N, ncol=I ) )
#Combine the two sets of items into one response matrix
resp <- cbind(resp1,resp2)
colnames(resp) <- paste("I", 1:(2*I), sep="")
dat <- resp

# define Q-matrix
Qmatrix <- matrix( 0, 2*I, 2 )
Qmatrix[1:I,1] <- 1
Qmatrix[1:I+I,2] <- 1

#***
# (2) estimation of models
# 2-dimensional Rasch model
mod1 <- sirt::rasch.mml2( dat, Qmatrix=Qmatrix )
summary(mod1)

# 2-dimensional 2PL model
mod2 <- sirt::rasch.mml2( dat, Qmatrix=Qmatrix, est.a=1:(2*I) )
summary(mod2)

# estimation with some fixed variances and covariances
# set variance of 1st dimension to 1 and
#  covariance to zero
variance.fixed <- matrix( cbind(c(1,1), c(1,2), c(1,0)),
             byrow=FALSE, ncol=3 )
mod3 <- sirt::rasch.mml2( dat, Qmatrix=Qmatrix, variance.fixed=variance.fixed )
summary(mod3)

# constraints on item difficulties
#  useful for example in longitudinal linking
est.b <- c( 1:I, 1:I )
    # equal indices correspond to equally estimated item parameters
mu.fixed <- cbind( 1, 0 )
mod4 <- sirt::rasch.mml2( dat, Qmatrix=Qmatrix, est.b=est.b, mu.fixed=mu.fixed )
summary(mod4)
```

```
#############################################################################
# EXAMPLE 6: Two booklets with same items but with item context effects.
# Therefore, item slopes and item difficulties are assumed to be shifted in the
# second design group.
#############################################################################

#***
# simulate data
set.seed(987)
I <- 10     # number of items
# define person design groups 1 and 2
n1 <- 700
n2 <- 1500
# item difficulties group 1
b1 <- seq(-1.5,1.5,length=I)
# item slopes group 1
a1 <- rep(1, I)
# simulate data group 1
dat1 <- sirt::sim.raschtype( stats::rnorm(n1), b=b1, fixed.a=a1 )
colnames(dat1) <- paste0("I", 1:I, "des1" )
# group 2
b2 <- b1 - .15
a2 <- 1.1*a1
# Item parameters are slightly transformed in the second group
# compared to the first group. This indicates possible item context effects.

# simulate data group 2
dat2 <- sirt::sim.raschtype( stats::rnorm(n2), b=b2, fixed.a=a2 )
colnames(dat2) <- paste0("I", 1:I, "des2" )
# define joint dataset
dat <- matrix( NA, nrow=n1+n2, ncol=2*I)
colnames(dat) <- c( colnames(dat1), colnames(dat2) )
dat[ 1:n1, 1:I ] <- dat1
dat[ n1 + 1:n2, I + 1:I ] <- dat2
# define group identifier
group <- c( rep(1,n1), rep(2,n2) )

#***
# Model 1: Rasch model two groups
itemindex <- rep( 1:I, 2 )
mod1 <- sirt::rasch.mml2( dat, group=group, est.b=itemindex )
summary(mod1)

#***
# Model 2: two item slope groups and designmatrix for intercepts
designmatrix <- matrix( 0, 2*I, I+1)
designmatrix[ ( 1:I )+ I,1:I] <- designmatrix[1:I,1:I] <- diag(I)
designmatrix[ ( 1:I )+ I,I+1] <- 1
mod2 <- sirt::rasch.mml2( dat, est.a=rep(1:2,each=I), designmatrix=designmatrix )
summary(mod2)

#############################################################################
# EXAMPLE 7: PIRLS dataset with missing responses
```

```
#############################################################################

data(data.pirlsmissing)
items <- grep( "R31", colnames(data.pirlsmissing), value=TRUE )
I <- length(items)
dat <- data.pirlsmissing

#****
# Model 1: recode missing responses as missing (missing are ignorable)

# data recoding
dat1 <- dat
dat1[ dat1==9 ] <- NA
# estimate Rasch model
mod1 <- sirt::rasch.mml2( dat1[,items], weights=dat$studwgt, group=dat$country )
summary(mod1)
##   Mean=0 0.341 -0.134 0.219
##   SD=1.142 1.166 1.197 0.959

#****
# Model 2: recode missing responses as wrong

# data recoding
dat2 <- dat
dat2[ dat2==9 ] <- 0
# estimate Rasch model
mod2 <- sirt::rasch.mml2( dat2[,items], weights=dat$studwgt, group=dat$country )
summary(mod2)
  ##   Mean=0 0.413 -0.172 0.446
  ##   SD=1.199 1.263 1.32 0.996

#****
# Model 3: recode missing responses as rho * P_i( theta ) and
#          apply pseudo-log-likelihood estimation
# Missing item responses are predicted by the model implied probability
# P_i( theta ) where theta is the ability estimate when ignoring missings (Model 1)
# and rho is an adjustment parameter. rho=0 is equivalent to Model 2 (treating
# missing as wrong) and rho=1 is equivalent to Model 1 (treating missing as ignorable).

# data recoding
dat3 <- dat
# simulate theta estimate from posterior distribution
theta <- stats::rnorm( nrow(dat3), mean=mod1$person$EAP, sd=mod1$person$SE.EAP )
rho <- .3   # define a rho parameter value of .3
for (ii in items){
    ind <- which( dat[,ii]==9 )
    dat3[ind,ii] <- rho*stats::plogis( theta[ind] - mod1$item$b[ which( items==ii ) ] )
                }

# estimate Rasch model
mod3 <- sirt::rasch.mml2( dat3[,items], weights=dat$studwgt, group=dat$country )
summary(mod3)
  ##   Mean=0 0.392 -0.153 0.38
```

```
  ##   SD=1.154 1.209 1.246 0.973

#****
# Model 4: simulate missing responses as rho * P_i( theta )
# The definition is the same as in Model 3. But it is now assumed
# that the missing responses are 'latent responses'.
set.seed(789)

# data recoding
dat4 <- dat
# simulate theta estimate from posterior distribution
theta <- stats::rnorm( nrow(dat4), mean=mod1$person$EAP, sd=mod1$person$SE.EAP )
rho <- .3   # define a rho parameter value of .3
for (ii in items){
    ind <- which( dat[,ii]==9 )
    p3 <- rho*stats::plogis( theta[ind] - mod1$item$b[ which( items==ii ) ] )
    dat4[ ind, ii ] <- 1*( stats::runif( length(ind), 0, 1 ) < p3)
                }

# estimate Rasch model
mod4 <- sirt::rasch.mml2( dat4[,items], weights=dat$studwgt, group=dat$country )
summary(mod4)
  ##   Mean=0 0.396 -0.156 0.382
  ##   SD=1.16 1.216 1.253 0.979

#****
# Model 5: recode missing responses for multiple choice items with four alternatives
#          to 1/4 and apply pseudo-log-likelihood estimation.
#          Missings for constructed response items are treated as incorrect.

# data recoding
dat5 <- dat
items_mc <- items[ substring( items, 7,7)=="M" ]
items_cr <- items[ substring( items, 7,7)=="C" ]
for (ii in items_mc){
    ind <- which( dat[,ii]==9 )
    dat5[ind,ii] <- 1/4
                }
for (ii in items_cr){
    ind <- which( dat[,ii]==9 )
    dat5[ind,ii] <- 0
                }

# estimate Rasch model
mod5 <- sirt::rasch.mml2( dat5[,items], weights=dat$studwgt, group=dat$country )
summary(mod5)
  ##   Mean=0 0.411 -0.165 0.435
  ##   SD=1.19 1.245 1.293 0.995

#*** For the following analyses, we ignore sample weights and the
#    country grouping.
data(data.pirlsmissing)
items <- grep( "R31", colnames(data.pirlsmissing), value=TRUE )
```

```
dat <- data.pirlsmissing
dat1 <- dat
dat1[ dat1==9 ] <- 0

#*** Model 6: estimate item difficulties assuming incorrect missing data treatment
mod6 <- sirt::rasch.mml2( dat1[,items], mmliter=50 )
summary(mod6)

#*** Model 7: reestimate model with constrained item difficulties
I <- length(items)
constraints <- cbind( 1:I, mod6$item$b )
mod7 <- sirt::rasch.mml2( dat1[,items], constraints=constraints)
summary(mod7)

#*** Model 8: score all missings responses as missing items
dat2 <- dat[,items]
dat2[ dat2==9 ] <- NA
mod8 <- sirt::rasch.mml2( dat2, constraints=constraints, mu.fixed=NULL )
summary(mod8)

#*** Model 9: estimate missing data model 'missing1' assuming a missingness
#       parameter delta.miss of zero
dat2 <-  dat[,items]    # note that missing item responses must be defined by 9
mod9 <- sirt::rasch.mml2( dat2, constraints=constraints, irtmodel="missing1",
            theta.k=seq(-5,5,len=10), delta.miss=0, mitermax=4, mu.fixed=NULL )
summary(mod9)

#*** Model 10: estimate missing data model with a large negative missing delta parameter
#=> This model is equivalent to treating missing responses as wrong
mod10 <- sirt::rasch.mml2( dat2, constraints=constraints, irtmodel="missing1",
             theta.k=seq(-5, 5, len=10), delta.miss=-10, mitermax=4, mmliter=200,
             mu.fixed=NULL )
summary(mod10)

#*** Model 11: choose a missingness delta parameter of -1
mod11 <- sirt::rasch.mml2( dat2, constraints=constraints, irtmodel="missing1",
             theta.k=seq(-5, 5, len=10), delta.miss=-1, mitermax=4,
             mmliter=200, mu.fixed=NULL )
summary(mod11)

#*** Model 12: estimate joint delta parameter
mod12 <- sirt::rasch.mml2( dat2, irtmodel="missing1", mu.fixed=cbind( c(1,2), 0 ),
             theta.k=seq(-8, 8, len=10), delta.miss=0, mitermax=4,
             mmliter=30, est.delta=rep(1,I)  )
summary(mod12)

#*** Model 13: estimate delta parameter in item groups defined by item format
est.delta <- 1 + 1 * ( substring( colnames(dat2),7,7 )=="M" )
mod13 <- sirt::rasch.mml2( dat2, irtmodel="missing1", mu.fixed=cbind( c(1,2), 0 ),
             theta.k=seq(-8, 8, len=10), delta.miss=0, mitermax=4,
             mmliter=30, est.delta=est.delta  )
summary(mod13)
```

```
#*** Model 14: estimate item specific delta parameter
mod14 <- sirt::rasch.mml2( dat2, irtmodel="missing1", mu.fixed=cbind( c(1,2), 0 ),
             theta.k=seq(-8, 8, len=10), delta.miss=0, mitermax=4,
             mmliter=30, est.delta=1:I  )
summary(mod14)

############################################################################
# EXAMPLE 8: Comparison of different models for polytomous data
############################################################################

data(data.Students, package="CDM")
head(data.Students)
dat <- data.Students[, paste0("act",1:5) ]
I <- ncol(dat)

#*************************************************
#*** Model 1: Partial Credit Model (PCM)

#*** Model 1a: PCM in TAM
mod1a <- TAM::tam.mml( dat )
summary(mod1a)

#*** Model 1b: PCM in sirt
mod1b <- sirt::rm.facets( dat )
summary(mod1b)

#*** Model 1c: PCM in mirt
mod1c <- mirt::mirt( dat, 1, itemtype=rep("Rasch",I), verbose=TRUE )
print(mod1c)

#*************************************************
#*** Model 2: Sequential Model (SM): Equal Loadings

#*** Model 2a: SM in sirt
dat1 <- CDM::sequential.items(dat)
resp <- dat1$dat.expand
iteminfo <- dat1$iteminfo
# fit model
mod2a <- sirt::rasch.mml2( resp )
summary(mod2a)

#*************************************************
#*** Model 3: Sequential Model (SM): Different Loadings

#*** Model 3a: SM in sirt
mod3a <- sirt::rasch.mml2( resp, est.a=iteminfo$itemindex )
summary(mod3a)

#*************************************************
#*** Model 4: Generalized partial credit model (GPCM)

#*** Model 4a: GPCM in TAM
mod4a <- TAM::tam.mml.2pl( dat, irtmodel="GPCM")
```

```
summary(mod4a)

#*************************************************
#*** Model 5: Graded response model (GRM)

#*** Model 5a: GRM in mirt
mod5a <- mirt::mirt( dat, 1, itemtype=rep("graded",I), verbose=TRUE)
print(mod5a)

# model comparison
logLik(mod1a);logLik(mod1b);mod1c@logLik  # PCM
logLik(mod2a)   # SM (Rasch)
logLik(mod3a)   # SM (GPCM)
logLik(mod4a)   # GPCM
mod5a@logLik    # GRM

## End(Not run)
```

`rasch.pairwise` *Pairwise Estimation Method of the Rasch Model*

Description

This function estimates the Rasch model with a minimum chi square estimation method (cited in Fischer, 2007, p. 544) which is a pairwise conditional likelihood estimation approach.

Usage

```
rasch.pairwise(dat, weights=NULL, conv=1e-04, maxiter=3000, progress=TRUE,
        b.init=NULL, zerosum=FALSE, power=1, direct_optim=TRUE)

## S3 method for class 'rasch.pairwise'
summary(object, digits=3, file=NULL, ...)
```

Arguments

`dat`	An $N \times I$ data frame of dichotomous item responses
`weights`	Optional vector of sampling weights
`conv`	Convergence criterion
`maxiter`	Maximum number of iterations
`progress`	Display iteration progress?
`b.init`	An optional vector of length I of item difficulties
`zerosum`	Optional logical indicating whether item difficulties should be centered in each iteration. The default is that no centering is conducted.
`power`	Power used for computing pairwise response probabilities like in row averaging approach

direct_optim	Logical indicating whether least squares criterion funcion should be minimized with stats::nlminb
object	Object of class rasch.pairwise
digits	Number of digits after decimal for rounding
file	Optional file name for summary output
...	Further arguments to be passed

Value

An object of class rasch.pairwise with following entries

b	Item difficulties
eps	Exponentiated item difficulties, i.e. eps=exp(-b)
iter	Number of iterations
conv	Convergence criterion
dat	Original data frame
freq.ij	Frequency table of all item pairs
item	Summary table of item parameters

References

Fischer, G. H. (2007). Rasch models. In C. R. Rao and S. Sinharay (Eds.), *Handbook of Statistics*, Vol. 26 (pp. 515-585). Amsterdam: Elsevier.

See Also

See summary.rasch.pairwise for a summary.

A slightly different implementation of this conditional pairwise method is implemented in rasch.pairwise.itemcluster.

Pairwise marginal likelihood estimation (also labeled as pseudolikelihood estimation) can be conducted with rasch.pml3.

Examples

```
#############################################################################
# EXAMPLE 1: Reading data set | pairwise estimation Rasch model
#############################################################################

data(data.read)
dat <- data.read

#*** Model 1: no constraint on item difficulties
mod1 <- sirt::rasch.pairwise(dat)
summary(mod1)

#*** Model 2: sum constraint on item difficulties
mod2 <- sirt::rasch.pairwise(dat, zerosum=TRUE)
```

```
summary(mod2)

## Not run:
#** obtain standard errors by bootstrap
mod2$item$b   # extract item difficulties

# Bootstrap of item difficulties
boot_pw <- function(data, indices ){
    dd <- data[ indices, ] # bootstrap of indices
    mod <- sirt::rasch.pairwise( dat=dd, zerosum=TRUE, progress=FALSE)
    return(mod$item$b)
}
set.seed(986)
library(boot)
bmod2 <- boot::boot(data=dat, statistic=boot_pw, R=999 )
print(bmod2)
summary(bmod2)
# quantiles for bootstrap sample (and confidence interval)
apply(bmod2$t, 2, stats::quantile, probs=c(.025, .5, .975) )

## End(Not run)
```

`rasch.pairwise.itemcluster`

Pairwise Estimation of the Rasch Model for Locally Dependent Items

---

Description

This function uses pairwise conditional likelihood estimation for estimating item parameters in the Rasch model.

Usage

```
rasch.pairwise.itemcluster(dat, itemcluster=NULL, b.fixed=NULL, weights=NULL,
    conv=1e-05, maxiter=3000, progress=TRUE, b.init=NULL, zerosum=FALSE)
```

Arguments

`dat`	An $N \times I$ data frame. Missing responses are allowed and must be recoded as `NA`.
`itemcluster`	Optional integer vector of itemcluster (see Examples). Different integers correspond to different item clusters. No item cluster is set as default.
`b.fixed`	Matrix for fixing item parameters. The first columns contains the item (number or name), the second column the parameter to be fixed.
`weights`	Optional Vector of sampling weights
`conv`	Convergence criterion in maximal absolute parameter change
`maxiter`	Maximal number of iterations

progress	A logical which displays progress. Default is TRUE.
b.init	Vector of initial item difficulty estimates. Default is NULL.
zerosum	Optional logical indicating whether item difficulties should be centered in each iteration. The default is that no centering is conducted.

Details

This is an adaptation of the algorithm of van der Linden and Eggen (1986). Only item pairs of different item clusters are taken into account for item difficulty estimation. Therefore, the problem of locally dependent items within each itemcluster is (almost) eliminated (see Examples below) because contributions of local dependencies do not appear in the pairwise likelihood terms. In detail, the estimation rests on observed frequency tables of items i and j and therefore on conditional probabilities

$$\frac{P(X_i = x, X_j = y)}{P(X_i + X_j = 1)} \quad \text{with} \quad x, y = 0, 1 \quad \text{and} \quad x + y = 1$$

If for some item pair (i, j) a higher positive (or negative) correlation is expected (i.e. deviation from local dependence), then this pair is removed from estimation. Clearly, there is a loss in precision but item parameters can be less biased.

Value

Object of class rasch.pairwise with elements

b	Vector of item difficulties
item	Data frame of item parameters (N, p and item difficulty)

Note

No standard errors are provided by this function. Use resampling methods for conducting statistical inference.

Formulas for asymptotic standard errors of this pairwise estimation method are described in Zwinderman (1995).

References

van der Linden, W. J., & Eggen, T. J. H. M. (1986). *An empirical Bayes approach to item banking*. Research Report 86-6, University of Twente.

Zwinderman, A. H. (1995). Pairwise parameter estimation in Rasch models. *Applied Psychological Measurement, 19*, 369-375.

See Also

rasch.pairwise, summary.rasch.pairwise,

Pairwise marginal likelihood estimation (also labeled as pseudolikelihood estimation) can be conducted with rasch.pml3.

Other estimation methods are implemented in rasch.copula2 or rasch.mml2.

For simulation of locally dependent data see sim.rasch.dep.

Examples

```
############################################################################
# EXAMPLE 1: Example with locally dependent items
#      12 Items: Cluster 1 -> Items 1,...,4
#                Cluster 2 -> Items 6,...,9
#                Cluster 3 -> Items 10,11,12
############################################################################

set.seed(7896)
I <- 12                             # number of items
n <- 5000                           # number of persons
b <- seq(-2,2, len=I)               # item difficulties
bsamp <- b <- sample(b)             # sample item difficulties
theta <- stats::rnorm( n, sd=1 ) # person abilities
# itemcluster
itemcluster <- rep(0,I)
itemcluster[ 1:4 ] <- 1
itemcluster[ 6:9 ] <- 2
itemcluster[ 10:12 ] <- 3
# residual correlations
rho <- c( .55, .25, .45 )

# simulate data
dat <- sirt::sim.rasch.dep( theta, b, itemcluster, rho )
colnames(dat) <- paste("I", seq(1,ncol(dat)), sep="")

# estimation with pairwise Rasch model
mod3 <- sirt::rasch.pairwise( dat )
summary(mod3)

# use item cluster in rasch pairwise estimation
mod <- sirt::rasch.pairwise.itemcluster( dat=dat, itemcluster=itemcluster )
summary(mod)

## Not run:
# Rasch MML estimation
mod4 <- sirt::rasch.mml2( dat )
summary(mod4)

# Rasch Copula estimation
mod5 <- sirt::rasch.copula2( dat, itemcluster=itemcluster )
summary(mod5)

# compare different item parameter estimates
M1 <- cbind( "true.b"=bsamp, "b.rasch"=mod4$item$b, "b.rasch.copula"=mod5$item$thresh,
         "b.rasch.pairwise"=mod3$b, "b.rasch.pairwise.cluster"=mod$b )
# center item difficulties
M1 <- scale( M1, scale=FALSE )
round( M1, 3 )
round( apply( M1, 2, stats::sd ), 3 )

#  Below the output of the example is presented.
```

```
# The rasch.pairwise.itemcluster is pretty close to the estimate in the Rasch copula model.

  ##   > round( M1, 3 )
  ##       true.b b.rasch b.rasch.copula b.rasch.pairwise b.rasch.pairwise.cluster
  ##   I1   0.545   0.561          0.526            0.628                    0.524
  ##   I2  -0.182  -0.168         -0.174           -0.121                   -0.156
  ##   I3  -0.909  -0.957         -0.867           -0.971                   -0.899
  ##   I4  -1.636  -1.726         -1.625           -1.765                   -1.611
  ##   I5   1.636   1.751          1.648            1.694                    1.649
  ##   I6   0.909   0.892          0.836            0.898                    0.827
  ##   I7  -2.000  -2.134         -2.020           -2.051                   -2.000
  ##   I8  -1.273  -1.355         -1.252           -1.303                   -1.271
  ##   I9  -0.545  -0.637         -0.589           -0.581                   -0.598
  ##   I10  1.273   1.378          1.252            1.308                    1.276
  ##   I11  0.182   0.241          0.226            0.109                    0.232
  ##   I12  2.000   2.155          2.039            2.154                    2.026
  ##   > round( apply( M1, 2, sd ), 3 )
  ##                     true.b                  b.rasch           b.rasch.copula
  ##                      1.311                    1.398                    1.310
  ##      b.rasch.pairwise    b.rasch.pairwise.cluster
  ##                 1.373                       1.310

# set item parameters of first item to 0 and of second item to -0.7
b.fixed <- cbind( c(1,2), c(0,-.7) )
mod5 <- sirt::rasch.pairwise.itemcluster( dat=dat, b.fixed=b.fixed,
            itemcluster=itemcluster )
# difference between estimations 'mod' and 'mod5'
dfr <- cbind( mod5$item$b, mod$item$b )
plot( mod5$item$b, mod$item$b, pch=16)
apply( dfr, 1, diff)

## End(Not run)
```

`rasch.pml3` *Pairwise Marginal Likelihood Estimation for the Probit Rasch Model*

Description

This function estimates unidimensional 1PL and 2PL models with the probit link using pairwise marginal maximum likelihood estimation (PMML; Renard, Molenberghs & Geys, 2004). Item pairs within an itemcluster can be excluded from the pairwise likelihood (argument `itemcluster`). The other alternative is to model a residual error structure with itemclusters (argument `error.corr`).

Usage

```
rasch.pml3(dat, est.b=seq(1, ncol(dat)), est.a=rep(0,ncol(dat)),
   est.sigma=TRUE, itemcluster=NULL, weight=rep(1, nrow(dat)), numdiff.parm=0.001,
   b.init=NULL, a.init=NULL,  sigma.init=NULL, error.corr=0*diag( 1, ncol(dat) ),
   err.constraintM=NULL, err.constraintV=NULL, glob.conv=10^(-6), conv1=10^(-4),
    pmliter=300, progress=TRUE, use.maxincrement=TRUE )
```

```
## S3 method for class 'rasch.pml'
summary(object,...)
```

Arguments

dat	An $N \times I$ data frame of dichotomous item responses
est.b	Vector of integers of length I. Same integers mean that the corresponding items do have the same item difficulty b. Entries of 0 mean fixing item parameters to values specified in b.init.
est.a	Vector of integers of length I. Same integers mean that the corresponding items do have the same item slope a. Entries of 0 mean fixing item parameters to values specified in a.init.
est.sigma	Should sigma (the trait standard deviation) be estimated? The default is TRUE.
itemcluster	Optional vector of length I of integers which indicates itemclusters. Same integers correspond to the same itemcluster. An entry of 0 correspond to an item which is not included in any itemcluster.
weight	Optional vector of person weights
numdiff.parm	Step parameter for numerical differentiation
b.init	Initial or fixed item difficulty
a.init	Initial or fixed item slopes
sigma.init	Initial or fixed trait standard deviation
error.corr	An optional $I \times I$ integer matrix which defines the estimation of residual correlations. Entries of zero indicate that the corresponding residual correlation should not be estimated. Integers which differ from zero indicate correlations to be estimated. All entries with an equal integer are estimated by the same residual correlation. The default of error.corr is a diagonal matrix which means that no residual correlation is estimated. If error.corr deviates from this default, then the argument itemcluster is set to NULL. If some error correlations are estimated, then no itempairs in itemcluster can be excluded from the pairwise modeling.
err.constraintM	An optional $P \times L$ matrix where P denotes the number of item pairs in pseudolikelihood estimation and L is the number of linear constraints for residual correlations (see Details).
err.constraintV	An optional $L \times 1$ matrix with specified values for linear constraints on residual correlations (see Details).
glob.conv	Global convergence criterion
conv1	Convergence criterion for model parameters
pmliter	Maximum number of iterations
progress	Display progress?
use.maxincrement	Optional logical whether increments in slope parameters should be controlled in size in iterations. The default is TRUE.

object	Object of class rasch.pml
...	Further arguments to be passed

Details

The probit item response model can be estimated with this function:

$$P(X_{pi}=1|\theta_p)=\Phi(a_i\theta_p-b_i) \quad , \quad \theta_p \sim N(0,\sigma^2)$$

where Φ denotes the normal distribution function. This model can also be expressed as a latent variable model which assumes a latent response tendency X^*_{pi} which is equal to 1 if $X_{pi} > -b_i$ and otherwise zero. If ϵ_{pi} is standard normally distributed, then

$$X^*_{pi}=a_i\theta_p-b_i+\epsilon_{pi}$$

An arbitrary pattern of residual correlations between ϵ_{pi} and ϵ_{pj} for item pairs i and j can be imposed using the error.corr argument.

Linear constraints $Me=v$ on residual correlations $e=Cov(\epsilon_{pi},\epsilon_{pj})_{ij}$ (in a vectorized form) can be specified using the arguments err.constraintM (matrix M) and err.constraintV (vector v). The estimation is described in Neuhaus (1996).

For the pseudo likelihood information criterion (PLIC) see Stanford and Raftery (2002).

Value

A list with following entries:

item	Data frame with estimated item parameters
iter	Number of iterations
deviance	Pseudolikelihood multiplied by minus 2
b	Estimated item difficulties
sigma	Estimated standard deviation
dat	Original dataset
ic	Data frame with information criteria (sample size, number of estimated parameters, pseudolikelihood information criterion PLIC)
link	Used link function (only probit is permitted)
itempairs	Estimated statistics of item pairs
error.corr	Estimated error correlation matrix
eps.corr	Vectorized error correlation matrix
omega.rel	Reliability of the sum score according to Green and Yang (2009). If some item pairs are excluded in the estimation, the residual correlation for these item pairs is assumed to be zero.
...	

Note

This function needs the **combinat** library.

References

Green, S. B., & Yang, Y. (2009). Reliability of summed item scores using structural equation modeling: An alternative to coefficient alpha. *Psychometrika, 74*, 155-167.

Neuhaus, W. (1996). Optimal estimation under linear constraints. *Astin Bulletin, 26*, 233-245.

Renard, D., Molenberghs, G., & Geys, H. (2004). A pairwise likelihood approach to estimation in multilevel probit models. *Computational Statistics & Data Analysis, 44*, 649-667.

Stanford, D. C., & Raftery, A. E. (2002). Approximate Bayes factors for image segmentation: The pseudolikelihood information criterion (PLIC). *IEEE Transactions on Pattern Analysis and Machine Intelligence, 24*, 1517-1520.

See Also

Get a summary of `rasch.pml3` with `summary.rasch.pml`.

For simulation of locally dependent items see `sim.rasch.dep`.

For pairwise conditional likelihood estimation see `rasch.pairwise` or `rasch.pairwise.itemcluster`.

For an assessment of global model fit see `modelfit.sirt`.

Examples

```
############################################################################
# EXAMPLE 1: Reading data set
############################################################################

data(data.read)
dat <- data.read

#******
# Model 1: Rasch model with PML estimation
mod1 <- sirt::rasch.pml3( dat )
summary(mod1)

#******
# Model 2: Excluding item pairs with local dependence
#          from bivariate composite likelihood
itemcluster <- rep( 1:3, each=4)
mod2 <- sirt::rasch.pml3( dat, itemcluster=itemcluster )
summary(mod2)

## Not run:
#*****
# Model 3: Modelling error correlations:
#          joint residual correlations for each itemcluster
error.corr <- diag(1,ncol(dat))
for ( ii in 1:3){
    ind.ii <- which( itemcluster==ii )
    error.corr[ ind.ii, ind.ii ] <- ii
        }
# estimate the model with error correlations
mod3 <- sirt::rasch.pml3( dat, error.corr=error.corr )
```

```
summary(mod3)

#****
# Model 4: model separate residual correlations
I <- ncol(error.corr)
error.corr1 <- matrix( 1:(I*I), ncol=I )
error.corr <- error.corr1 * ( error.corr > 0 )
# estimate the model with error correlations
mod4 <- sirt::rasch.pml3( dat, error.corr=error.corr )
summary(mod4)

#****
# Model 5:  assume equal item difficulties:
# b_1=b_7 and b_2=b_12
# fix item difficulty of the 6th item to .1
est.b <- 1:I
est.b[7] <- 1; est.b[12] <- 2 ; est.b[6] <- 0
b.init <- rep( 0, I ) ; b.init[6] <- .1
mod5 <- sirt::rasch.pml3( dat, est.b=est.b, b.init=b.init)
summary(mod5)

#****
# Model 6: estimate three item slope groups
est.a <- rep(1:3, each=4 )
mod6 <- sirt::rasch.pml3( dat, est.a=est.a, est.sigma=0)
summary(mod6)

############################################################################
# EXAMPLE 2: PISA reading
############################################################################

data(data.pisaRead)
dat <- data.pisaRead$data

# select items
dat <- dat[, substring(colnames(dat),1,1)=="R" ]

#******
# Model 1: Rasch model with PML estimation
mod1 <- sirt::rasch.pml3( as.matrix(dat) )
  ## Trait SD (Logit Link) : 1.419

#******
# Model 2: Model correlations within testlets
error.corr <- diag(1,ncol(dat))
testlets <- paste( data.pisaRead$item$testlet )
itemcluster <- match( testlets, unique(testlets ) )
for ( ii in 1:(length(unique(testlets))) ){
    ind.ii <- which( itemcluster==ii )
    error.corr[ ind.ii, ind.ii ] <- ii
        }
# estimate the model with error correlations
mod2 <- sirt::rasch.pml3( dat, error.corr=error.corr )
```

```
  ## Trait SD (Logit Link) : 1.384

#****
# Model 3: model separate residual correlations
I <- ncol(error.corr)
error.corr1 <- matrix( 1:(I*I), ncol=I )
error.corr <- error.corr1 * ( error.corr > 0 )
# estimate the model with error correlations
mod3 <- sirt::rasch.pml3( dat, error.corr=error.corr )
  ## Trait SD (Logit Link) : 1.384

############################################################################
# EXAMPLE 3: 10 locally independent items
############################################################################

#**********
# simulate some data
set.seed(554)
N <- 500    # persons
I <- 10        # items
theta <- stats::rnorm(N,sd=1.3 )    # trait SD of 1.3
b <- seq(-2, 2, length=I) # item difficulties

# simulate data from the Rasch model
dat <- sirt::sim.raschtype( theta=theta, b=b )

# estimation with rasch.pml and probit link
mod1 <- sirt::rasch.pml3( dat )
summary(mod1)

# estimation with rasch.mml2 function
mod2 <- sirt::rasch.mml2( dat )

# estimate item parameters for groups with five item parameters each
est.b <- rep( 1:(I/2), each=2 )
mod3 <- sirt::rasch.pml3( dat, est.b=est.b )
summary(mod3)

# compare parameter estimates
summary(mod1)
summary(mod2)
summary(mod3)

############################################################################
# EXAMPLE 4: 11 items and 2 item clusters with 2 and 3 items
############################################################################

set.seed(5698)
I <- 11                             # number of items
n <- 5000                           # number of persons
b <- seq(-2,2, len=I)               # item difficulties
theta <- stats::rnorm( n, sd=1 ) # person abilities
# itemcluster
```

```
itemcluster <- rep(0,I)
itemcluster[c(3,5)] <- 1
itemcluster[c(2,4,9)] <- 2
# residual correlations
rho <- c( .7, .5 )

# simulate data (under the logit link)
dat <- sirt::sim.rasch.dep( theta, b, itemcluster, rho )
colnames(dat) <- paste("I", seq(1,ncol(dat)), sep="")

#***
# Model 1: estimation using the Rasch model (with probit link)
mod1 <- sirt::rasch.pml3( dat )
#***
# Model 2: estimation when pairs of locally dependent items are eliminated
mod2 <- sirt::rasch.pml3( dat, itemcluster=itemcluster)

#***
# Model 3: Positive correlations within testlets
est.corrs <- diag( 1, I )
est.corrs[ c(3,5), c(3,5) ] <- 2
est.corrs[ c(2,4,9), c(2,4,9) ] <- 3
mod3 <- sirt::rasch.pml3( dat, error.corr=est.corrs )

#***
# Model 4: Negative correlations between testlets
est.corrs <- diag( 1, I )
est.corrs[ c(3,5), c(2,4,9) ] <- 2
est.corrs[ c(2,4,9), c(3,5) ] <- 2
mod4 <- sirt::rasch.pml3( dat, error.corr=est.corrs )

#***
# Model 5: sum constraint of zero within and between testlets
est.corrs <- matrix( 1:(I*I),  I, I )
cluster2 <- c(2,4,9)
est.corrs[ setdiff( 1:I, c(cluster2)),  ] <- 0
est.corrs[, setdiff( 1:I, c(cluster2))  ] <- 0
# define an error constraint matrix
itempairs0 <- mod4$itempairs
IP <- nrow(itempairs0)
err.constraint <- matrix( 0, IP, 1 )
err.constraint[ ( itempairs0$item1 %in% cluster2 )
       & ( itempairs0$item2 %in% cluster2 ), 1 ] <- 1
# set sum of error covariances to 1.2
err.constraintV <- matrix(3*.4,1,1)

mod5 <- sirt::rasch.pml3( dat, error.corr=est.corrs,
         err.constraintM=err.constraint, err.constraintV=err.constraintV)

#****
# Model 6: Constraint on sum of all correlations
est.corrs <- matrix( 1:(I*I),  I, I )
# define an error constraint matrix
```

```
itempairs0 <- mod4$itempairs
IP <- nrow(itempairs0)
# define two side conditions
err.constraint <- matrix( 0, IP, 2 )
err.constraintV <- matrix( 0, 2, 1)
# sum of all correlations is zero
err.constraint[, 1 ] <- 1
err.constraintV[1,1] <- 0
# sum of items cluster c(1,2,3) is 0
cluster2 <- c(1,2,3)
err.constraint[ ( itempairs0$item1 %in%  cluster2 )
       & ( itempairs0$item2 %in% cluster2 ), 2 ] <- 1
err.constraintV[2,1] <- 0

mod6 <- sirt::rasch.pml3( dat, error.corr=est.corrs,
    err.constraintM=err.constraint,  err.constraintV=err.constraintV)
summary(mod6)

#############################################################################
# EXAMPLE 5: 10 Items: Cluster 1 -> Items 1,2
#         Cluster 2 -> Items 3,4,5;   Cluster 3 -> Items 7,8,9
#############################################################################

set.seed(7650)
I <- 10                             # number of items
n <- 5000                           # number of persons
b <- seq(-2,2, len=I)               # item difficulties
bsamp <- b <- sample(b)             # sample item difficulties
theta <- stats::rnorm( n, sd=1 ) # person abilities
# define itemcluster
itemcluster <- rep(0,I)
itemcluster[ 1:2 ] <- 1
itemcluster[ 3:5 ] <- 2
itemcluster[ 7:9 ] <- 3
# define residual correlations
rho <- c( .55, .35, .45)

# simulate data
dat <- sirt::sim.rasch.dep( theta, b, itemcluster, rho )
colnames(dat) <- paste("I", seq(1,ncol(dat)), sep="")

#***
# Model 1: residual correlation (equal within item clusters)
# define a matrix of integers for estimating error correlations
error.corr <- diag(1,ncol(dat))
for ( ii in 1:3){
    ind.ii <- which( itemcluster==ii )
    error.corr[ ind.ii, ind.ii ] <- ii
        }
# estimate the model
mod1 <- sirt::rasch.pml3( dat, error.corr=error.corr )

#***
```

```
# Model 2: residual correlation (different within item clusters)
# define again a matrix of integers for estimating error correlations
error.corr <- diag(1,ncol(dat))
for ( ii in 1:3){
    ind.ii <- which( itemcluster==ii )
    error.corr[ ind.ii, ind.ii ] <- ii
        }
I <- ncol(error.corr)
error.corr1 <- matrix( 1:(I*I), ncol=I )
error.corr <- error.corr1 * ( error.corr > 0 )
# estimate the model
mod2 <- sirt::rasch.pml3( dat, error.corr=error.corr )

#***
# Model 3: eliminate item pairs within itemclusters for PML estimation
mod3 <- sirt::rasch.pml3( dat, itemcluster=itemcluster )

#***
# Model 4: Rasch model ignoring dependency
mod4 <- sirt::rasch.pml3( dat )

# compare different models
summary(mod1)
summary(mod2)
summary(mod3)
summary(mod4)

## End(Not run)
```

`rasch.prox` *PROX Estimation Method for the Rasch Model*

Description

This function estimates the Rasch model using the PROX algorithm (cited in Wright & Stone, 1999).

Usage

```
rasch.prox(dat, dat.resp=1 - is.na(dat), freq=rep(1,nrow(dat)),
    conv=0.001, maxiter=30, progress=FALSE)
```

Arguments

`dat`	An $N \times I$ data frame of dichotomous response data. `NA`s are not allowed and must be indicated by zero entries in the response indicator matrix `dat.resp`.
`dat.resp`	An $N \times I$ indicator data frame of nonmissing item responses.
`freq`	A vector of frequencies (or weights) of all rows in data frame `dat`.
`conv`	Convergence criterion for item parameters

maxiter	Maximum number of iterations
progress	Display progress?

Value

A list with following entries

b	Estimated item difficulties
theta	Estimated person abilities
iter	Number of iterations
sigma.i	Item standard deviations
sigma.n	Person standard deviations

References

Wright, B., & Stone, W. (1999). *Measurement Essentials*. Wilmington: Wide Range.

Examples

```
#############################################################################
# EXAMPLE 1: PROX data.read
#############################################################################

data(data.read)
mod <- sirt::rasch.prox( data.read )
mod$b       # item difficulties
```

---

rasch.va *Estimation of the Rasch Model with Variational Approximation*

Description

This function estimates the Rasch model by the estimation method of variational approximation (Rijmen & Vomlel, 2008).

Usage

```
rasch.va(dat, globconv=0.001, maxiter=1000)
```

Arguments

dat	Data frame with dichotomous item responses
globconv	Convergence criterion for item parameters
maxiter	Maximal number of iterations

Value

A list with following entries:

`sig`	Standard deviation of the trait
`item`	Data frame with item parameters
`xsi.ij`	Data frame with variational parameters ξ_{ij}
`mu.i`	Vector with individual means μ_i
`sigma2.i`	Vector with individual variances σ_i^2

References

Rijmen, F., & Vomlel, J. (2008). Assessing the performance of variational methods for mixed logistic regression models. *Journal of Statistical Computation and Simulation, 78*, 765-779.

Examples

```
#############################################################################
# EXAMPLE 1: Rasch model
#############################################################################
set.seed(8706)
N <- 5000
I <- 20
dat <- sirt::sim.raschtype( stats::rnorm(N,sd=1.3), b=seq(-2,2,len=I) )

# estimation via variational approximation
mod1 <- sirt::rasch.va(dat)

# estimation via marginal maximum likelihood
mod2 <- sirt::rasch.mml2(dat)

# estmation via joint maximum likelihood
mod3 <- sirt::rasch.jml(dat)

# compare sigma
round( c( mod1$sig, mod2$sd.trait ), 3 )
## [1] 1.222 1.314

# compare b
round( cbind( mod1$item$b, mod2$item$b, mod3$item$itemdiff), 3 )
##         [,1]   [,2]   [,3]
##  [1,] -1.898 -1.967 -2.090
##  [2,] -1.776 -1.841 -1.954
##  [3,] -1.561 -1.618 -1.715
##  [4,] -1.326 -1.375 -1.455
##  [5,] -1.121 -1.163 -1.228
```

`reliability.nonlinearSEM` *Estimation of Reliability for Confirmatory Factor Analyses Based on Dichotomous Data*

Description

This function estimates a model based reliability using confirmatory factor analysis (Green & Yang, 2009).

Usage

```
reliability.nonlinearSEM(facloadings, thresh, resid.cov=NULL, cor.factors=NULL)
```

Arguments

`facloadings`	Matrix of factor loadings
`thresh`	Vector of thresholds
`resid.cov`	Matrix of residual covariances
`cor.factors`	Optional matrix of covariances (correlations) between factors. The default is a diagonal matrix with variances of 1.

Value

A list. The reliability is the list element `omega.rel`

Note

This function needs the **mvtnorm** package.

References

Green, S. B., & Yang, Y. (2009). Reliability of summed item scores using structural equation modeling: An alternative to coefficient alpha. *Psychometrika, 74*, 155-167.

See Also

This function is used in `greenyang.reliability`.

Examples

```
#############################################################################
# EXAMPLE 1: Reading data set
#############################################################################
data(data.read)
dat <- data.read
I <- ncol(dat)
```

```
# define item clusters
itemcluster <- rep( 1:3, each=4)
error.corr <- diag(1,ncol(dat))
for ( ii in 1:3){
    ind.ii <- which( itemcluster==ii )
    error.corr[ ind.ii, ind.ii ] <- ii
        }
# estimate the model with error correlations
mod1 <- sirt::rasch.pml3( dat, error.corr=error.corr)
summary(mod1)

# extract item parameters
thresh <- - matrix( mod1$item$a * mod1$item$b, I, 1 )
A <- matrix( mod1$item$a * mod1$item$sigma, I, 1 )
# extract estimated correlation matrix
corM <- mod1$eps.corrM
# compute standardized factor loadings
facA <- 1 / sqrt( A^2 + 1 )
resvar <- 1 - facA^2
covM <- outer( sqrt(resvar[,1]), sqrt(resvar[,1] ) ) * corM
facloadings <- A *facA

# estimate reliability
rel1 <- sirt::reliability.nonlinearSEM( facloadings=facloadings, thresh=thresh,
          resid.cov=covM)
rel1$omega.rel
```

`resp_groupwise` *Creates Group-Wise Item Response Dataset*

Description

Creates group-wise item response dataset.

Usage

```
resp_groupwise(resp, group, items_group)
```

Arguments

`resp`	Dataset with item responses
`group`	Vector of group identifiers
`items_group`	List containing vectors of groups for each item which should be made group-specific

Value

Dataset

Examples

```
## Not run:
#############################################################################
# EXAMPLE 1: Toy dataset
#############################################################################

library(CDM)
library(TAM)

data(data.ex11, package="TAM")
dat <- data.ex11
dat[ dat==9 ] <- 0
resp <- dat[,-1]

# group labels
booklets <- sort( unique(paste(dat$booklet)))

#- fit initial model
mod0 <- TAM::tam.mml( resp, group=dat$booklet)
summary(mod0)

# fit statistics
fmod <- IRT.RMSD(mod)
stat <- abs(fmod$MD[,-1])
stat[ is.na( fmod$RMSD[,2:4] ) ] <- NA
thresh <- .01
round(stat,3)
# define list define groups for group-specific items
items_group <- apply( stat, 1, FUN=function(ll){
                v1 <- booklets[ which( ll > thresh ) ]
                v1[ ! is.na(v1) ]  } )

#- create extended response dataset
dat2 <- sirt::resp_groupwise(resp=resp, group=paste(dat$booklet), items_group=items_group)
colSums( ! is.na(dat2) )

#- fit model for extended response dataset
mod2 <- TAM::tam.mml( dat2, group=dat$booklet)
summary(mod2)

## End(Not run)
```

`rinvgamma2` *Inverse Gamma Distribution in Prior Sample Size Parameterization*

Description

Random draws and density of inverse gamma distribution parameterized in prior sample size `n0` and prior variance `var0` (see Gelman et al., 2014).

Usage

```
rinvgamma2(n, n0, var0)

dinvgamma2(x, n0, var0)
```

Arguments

n	Number of draws for inverse gamma distribution
n0	Prior sample size
var0	Prior variance
x	Vector with numeric values for density evaluation

Value

A vector containing random draws or density values

References

Gelman, A., Carlin, J. B., Stern, H. S., Dunson, D. B., Vehtari, A., & Rubin, D. B. (2014). *Bayesian data analysis* (Vol. 3). Boca Raton, FL, USA: Chapman & Hall/CRC.

See Also

MCMCpack::rinvgamma, stats::rgamma, MCMCpack::dinvgamma, stats::dgamma

Examples

```
############################################################################
# EXAMPLE 1: Inverse gamma distribution
############################################################################

# prior sample size of 100 and prior variance of 1.5
n0 <- 100
var0 <- 1.5

# 100 random draws
y1 <- sirt::rinvgamma2( n=100, n0, var0 )
summary(y1)
graphics::hist(y1)

# density y at grid x
x <- seq( 0, 2, len=100 )
y <- sirt::dinvgamma2( x, n0, var0 )
graphics::plot( x, y, type="l")
```

rm.facets *Rater Facets Models with Item/Rater Intercepts and Slopes*

Description

This function estimates the unidimensional rater facets model (Lincare, 1994) and an extension to slopes (see Details; Robitzsch & Steinfeld, 2018). The estimation is conducted by an EM algorithm employing marginal maximum likelihood.

Usage

```
rm.facets(dat, pid=NULL, rater=NULL, Qmatrix=NULL, theta.k=seq(-9, 9, len=30),
    est.b.rater=TRUE, est.a.item=FALSE, est.a.rater=FALSE, rater_item_int=FALSE,
     est.mean=FALSE, tau.item.fixed=NULL, a.item.fixed=NULL, b.rater.fixed=NULL,
   a.rater.fixed=NULL, b.rater.center=2, a.rater.center=2, a.item.center=2, a_lower=.05,
     a_upper=10, reference_rater=NULL, max.b.increment=1, numdiff.parm=0.00001,
     maxdevchange=0.1, globconv=0.001, maxiter=1000, msteps=4, mstepconv=0.001,
     PEM=FALSE, PEM_itermax=maxiter)

## S3 method for class 'rm.facets'
summary(object, file=NULL, ...)

## S3 method for class 'rm.facets'
anova(object,...)

## S3 method for class 'rm.facets'
logLik(object,...)

## S3 method for class 'rm.facets'
IRT.irfprob(object,...)

## S3 method for class 'rm.facets'
IRT.factor.scores(object, type="EAP", ...)

## S3 method for class 'rm.facets'
IRT.likelihood(object,...)

## S3 method for class 'rm.facets'
IRT.posterior(object,...)

## S3 method for class 'rm.facets'
IRT.modelfit(object,...)

## S3 method for class 'IRT.modelfit.rm.facets'
summary(object, ...)

## function for processing data
```

```
rm_proc_data( dat, pid, rater, rater_item_int=FALSE, reference_rater=NULL )
```

Arguments

dat	Original data frame. Ratings on variables must be in rows, i.e. every row corresponds to a person-rater combination.
pid	Person identifier.
rater	Rater identifier
Qmatrix	An optional Q-matrix. If this matrix is not provided, then by default the ordinary scoring of categories (from 0 to the maximum score of K) is used.
theta.k	A grid of theta values for the ability distribution.
est.b.rater	Should the rater severities b_r be estimated?
est.a.item	Should the item slopes a_i be estimated?
est.a.rater	Should the rater slopes a_r be estimated?
rater_item_int	Logical indicating whether rater-item-interactions should be modeled.
est.mean	Optional logical indicating whether the mean of the trait distribution should be estimated.
tau.item.fixed	Matrix with fixed τ parameters. Non-fixed parameters must be declared by NA values.
a.item.fixed	Vector with fixed item discriminations
b.rater.fixed	Vector with fixed rater intercept parameters
a.rater.fixed	Vector with fixed rater discrimination parameters
b.rater.center	Centering method for rater intercept parameters. The value 0 corresponds to no centering, the values 1 and 2 to different methods to ensure that they sum to zero.
a.rater.center	Centering method for rater discrimination parameters. The value 0 corresponds to no centering, the values 1 and 2 to different methods to ensure that their product equals one.
a.item.center	Centering method for item discrimination parameters. The value 0 corresponds to no centering, the values 1 and 2 to different methods to ensure that their product equals one.
a_lower	Lower bound for a parameters
a_upper	Upper bound for a parameters
reference_rater	Identifier for rater as a reference rater for which a fixed rater mean of 0 and a fixed rater slope of 1 is assumed.
max.b.increment	Maximum increment of item parameters during estimation
numdiff.parm	Numerical differentiation step width
maxdevchange	Maximum relative deviance change as a convergence criterion
globconv	Maximum parameter change

maxiter	Maximum number of iterations
msteps	Maximum number of iterations during an M step
mstepconv	Convergence criterion in an M step
PEM	Logical indicating whether the P-EM acceleration should be applied (Berlinet & Roland, 2012).
PEM_itermax	Number of iterations in which the P-EM method should be applied.
object	Object of class rm.facets
file	Optional file name in which summary should be written.
type	Factor score estimation method. Factor score types "EAP", "MLE" and "WLE" are supported.
...	Further arguments to be passed

Details

This function models ratings X_{pri} for person p, rater r and item i and category k (see also Robitzsch & Steinfeld, 2018; Uto & Ueno, 2010; Wu, 2017)

$$P(X_{pri}=k|\theta_p) \propto \exp(a_i a_r q_{ik} \theta_p - q_{ik} b_r - \tau_{ik}) \quad , \quad \theta_p \sim N(0, \sigma^2)$$

By default, the scores in the Q matrix are $q_{ik}=k$. Item slopes a_i and rater slopes a_r are standardized such that their product equals one, i.e. $\prod_i a_i = \prod_r a_r = 1$.

Value

A list with following entries:

deviance	Deviance
ic	Information criteria and number of parameters
item	Data frame with item parameters
rater	Data frame with rater parameters
person	Data frame with person parameters: EAP and corresponding standard errors
EAP.rel	EAP reliability
mu	Mean of the trait distribution
sigma	Standard deviation of the trait distribution
theta.k	Grid of theta values
pi.k	Fitted distribution at theta.k values
tau.item	Item parameters τ_{ik}
se.tau.item	Standard error of item parameters τ_{ik}
a.item	Item slopes a_i
se.a.item	Standard error of item slopes a_i
delta.item	Delta item parameter. See pcm.conversion.
b.rater	Rater severity parameter b_r

`se.b.rater`	Standard error of rater severity parameter b_r
`a.rater`	Rater slope parameter a_r
`se.a.rater`	Standard error of rater slope parameter a_r
`f.yi.qk`	Individual likelihood
`f.qk.yi`	Individual posterior distribution
`probs`	Item probabilities at grid `theta.k`
`n.ik`	Expected counts
`maxK`	Maximum number of categories
`procdata`	Processed data
`iter`	Number of iterations
`ipars.dat2`	Item parameters for expanded dataset `dat2`
`...`	Further values

Note

If the trait standard deviation `sigma` strongly differs from 1, then a user should investigate the sensitivity of results using different theta integration points `theta.k`.

References

Berlinet, A. F., & Roland, C. (2012). Acceleration of the EM algorithm: P-EM versus epsilon algorithm. *Computational Statistics & Data Analysis, 56*(12), 4122-4137.

Linacre, J. M. (1994). *Many-Facet Rasch Measurement*. Chicago: MESA Press.

Robitzsch, A., & Steinfeld, J. (2018). Item response models for human ratings: Overview, estimation methods, and implementation in R. *Psychological Test and Assessment Modeling, 60*(1), 101-139.

Uto, M., & Ueno, M. (2016). Item response theory for peer assessment. *IEEE Transactions on Learning Technologies, 9*(2), 157-170.

Wu, M. (2017). Some IRT-based analyses for interpreting rater effects. *Psychological Test and Assessment Modeling, 59*(4), 453-470.

See Also

See also the **TAM** package for the estimation of more complicated facet models.

See `rm.sdt` for estimating a hierarchical rater model.

Examples

```
#############################################################################
# EXAMPLE 1: Partial Credit Model and Generalized partial credit model
#                  5 items and 1 rater
#############################################################################
data(data.ratings1)
dat <- data.ratings1
```

```
# select rater db01
dat <- dat[ paste(dat$rater)=="db01", ]

#****  Model 1: Partial Credit Model
mod1 <- sirt::rm.facets( dat[, paste0( "k",1:5) ], pid=dat$idstud )

#****  Model 2: Generalized Partial Credit Model
mod2 <- sirt::rm.facets( dat[, paste0( "k",1:5) ],  pid=dat$idstud, est.a.item=TRUE)

summary(mod1)
summary(mod2)

## Not run:
#############################################################################
# EXAMPLE 2: Facets Model: 5 items, 7 raters
#############################################################################

data(data.ratings1)
dat <- data.ratings1

#****  Model 1: Partial Credit Model: no rater effects
mod1 <- sirt::rm.facets( dat[, paste0( "k",1:5) ], rater=dat$rater,
             pid=dat$idstud, est.b.rater=FALSE )

#****  Model 2: Partial Credit Model: intercept rater effects
mod2 <- sirt::rm.facets( dat[, paste0( "k",1:5) ], rater=dat$rater, pid=dat$idstud)

# extract individual likelihood
lmod1 <- IRT.likelihood(mod1)
str(lmod1)
# likelihood value
logLik(mod1)
# extract item response functions
pmod1 <- IRT.irfprob(mod1)
str(pmod1)
# model comparison
anova(mod1,mod2)
# absolute and relative model fit
smod1 <- IRT.modelfit(mod1)
summary(smod1)
smod2 <- IRT.modelfit(mod2)
summary(smod2)
IRT.compareModels( smod1, smod2 )
# extract factor scores (EAP is the default)
IRT.factor.scores(mod2)
# extract WLEs
IRT.factor.scores(mod2, type="WLE")

#****  Model 2a: compare results with TAM package
#   Results should be similar to Model 2
library(TAM)
mod2a <- TAM::tam.mml.mfr( resp=dat[, paste0( "k",1:5) ],
             facets=dat[, "rater", drop=FALSE],
```

```
            pid=dat$pid, formulaA=~ item*step + rater )

#****  Model 2b: Partial Credit Model: some fixed parameters
# fix rater parameters for raters 1, 4 and 5
b.rater.fixed <- rep(NA,7)
b.rater.fixed[ c(1,4,5) ] <- c(1,-.8,0)  # fixed parameters
# fix item parameters of first and second item
tau.item.fixed <- round( mod2$tau.item, 1 )    # use parameters from mod2
tau.item.fixed[ 3:5, ] <- NA    # free item parameters of items 3, 4 and 5
mod2b <- sirt::rm.facets( dat[, paste0( "k",1:5) ], rater=dat$rater,
            b.rater.fixed=b.rater.fixed, tau.item.fixed=tau.item.fixed,
            est.mean=TRUE, pid=dat$idstud)
summary(mod2b)

#****  Model 3: estimated rater slopes
mod3 <- sirt::rm.facets( dat[, paste0( "k",1:5) ], rater=dat$rater,
           est.a.rater=TRUE)

#****  Model 4: estimated item slopes
mod4 <- sirt::rm.facets( dat[, paste0( "k",1:5) ], rater=dat$rater,
            pid=dat$idstud, est.a.item=TRUE)

#****  Model 5: estimated rater and item slopes
mod5 <- sirt::rm.facets( dat[, paste0( "k",1:5) ], rater=dat$rater,
            pid=dat$idstud, est.a.rater=TRUE, est.a.item=TRUE)
summary(mod1)
summary(mod2)
summary(mod2a)
summary(mod3)
summary(mod4)
summary(mod5)

#****  Model 5a: Some fixed parameters in Model 5
# fix rater b parameters for raters 1, 4 and 5
b.rater.fixed <- rep(NA,7)
b.rater.fixed[ c(1,4,5) ] <- c(1,-.8,0)
# fix rater a parameters for first four raters
a.rater.fixed <- rep(NA,7)
a.rater.fixed[ c(1,2,3,4) ] <- c(1.1,0.9,.85,1)
# fix item b parameters of first item
tau.item.fixed <- matrix( NA, nrow=5, ncol=3 )
tau.item.fixed[ 1, ] <- c(-2,-1.5, 1 )
# fix item a parameters
a.item.fixed <- rep(NA,5)
a.item.fixed[ 1:4 ] <- 1
# estimate model
mod5a <- sirt::rm.facets( dat[, paste0( "k",1:5) ], rater=dat$rater,
            pid=dat$idstud, est.a.rater=TRUE, est.a.item=TRUE,
            tau.item.fixed=tau.item.fixed, b.rater.fixed=b.rater.fixed,
            a.rater.fixed=a.rater.fixed, a.item.fixed=a.item.fixed,
            est.mean=TRUE)
summary(mod5a)
```

```
#****  Model 6: Estimate rater model with reference rater 'db03'
mod6 <- sirt::rm.facets( dat[, paste0( "k",1:5) ], rater=dat$rater, est.a.item=TRUE,
             est.a.rater=TRUE, pid=dat$idstud, reference_rater="db03" )
summary(mod6)

#**** Model 7: Modelling rater-item-interactions
mod7 <- sirt::rm.facets( dat[, paste0( "k",1:5) ], rater=dat$rater, est.a.item=FALSE,
             est.a.rater=TRUE, pid=dat$idstud, reference_rater="db03",
             rater_item_int=TRUE)
summary(mod7)

## End(Not run)
```

`rm.sdt` *Hierarchical Rater Model Based on Signal Detection Theory (HRM-SDT)*

Description

This function estimates a version of the hierarchical rater model (HRM) based on signal detection theory (HRM-SDT; DeCarlo, 2005; DeCarlo, Kim & Johnson, 2011; Robitzsch & Steinfeld, 2018). The model is estimated by means of an EM algorithm adapted from multilevel latent class analysis (Vermunt, 2008).

Usage

```
rm.sdt(dat, pid, rater, Qmatrix=NULL, theta.k=seq(-9, 9, len=30),
   est.a.item=FALSE, est.c.rater="n", est.d.rater="n", est.mean=FALSE, est.sigma=TRUE,
    skillspace="normal", tau.item.fixed=NULL, a.item.fixed=NULL,
    d.min=0.5, d.max=100, d.start=3, c.start=NULL, tau.start=NULL, sd.start=1,
    d.prior=c(3,100), c.prior=c(3,100), tau.prior=c(0,1000), a.prior=c(1,100),
    link_item="GPCM", max.increment=1, numdiff.parm=0.00001, maxdevchange=0.1,
   globconv=.001, maxiter=1000, msteps=4, mstepconv=0.001, optimizer="nlminb" )

## S3 method for class 'rm.sdt'
summary(object, file=NULL, ...)

## S3 method for class 'rm.sdt'
plot(x, ask=TRUE, ...)

## S3 method for class 'rm.sdt'
anova(object,...)

## S3 method for class 'rm.sdt'
logLik(object,...)

## S3 method for class 'rm.sdt'
IRT.factor.scores(object, type="EAP", ...)
```

```
## S3 method for class 'rm.sdt'
IRT.irfprob(object,...)

## S3 method for class 'rm.sdt'
IRT.likelihood(object,...)

## S3 method for class 'rm.sdt'
IRT.posterior(object,...)

## S3 method for class 'rm.sdt'
IRT.modelfit(object,...)

## S3 method for class 'IRT.modelfit.rm.sdt'
summary(object,...)
```

Arguments

`dat`	Original data frame. Ratings on variables must be in rows, i.e. every row corresponds to a person-rater combination.
`pid`	Person identifier.
`rater`	Rater identifier.
`Qmatrix`	An optional Q-matrix. If this matrix is not provided, then by default the ordinary scoring of categories (from 0 to the maximum score of K) is used.
`theta.k`	A grid of theta values for the ability distribution.
`est.a.item`	Should item parameters a_i be estimated?
`est.c.rater`	Type of estimation for item-rater parameters c_{ir} in the signal detection model. Options are `'n'` (no estimation), `'e'` (set all parameters equal to each other), `'i'` (itemwise estimation), `'r'` (rater wise estimation) and `'a'` (all parameters are estimated independently from each other).
`est.d.rater`	Type of estimation of d parameters. Options are the same as in `est.c.rater`.
`est.mean`	Optional logical indicating whether the mean of the trait distribution should be estimated.
`est.sigma`	Optional logical indicating whether the standard deviation of the trait distribution should be estimated.
`skillspace`	Specified θ distribution type. It can be `"normal"` or `"discrete"`. In the latter case, all probabilities of the distribution are separately estimated.
`tau.item.fixed`	Optional matrix with three columns specifying fixed τ parameters. The first two columns denote item and category indices, the third the fixed value. See Example 3.
`a.item.fixed`	Optional matrix with two columns specifying fixed a parameters. First column: Item index. Second column: Fixed a parameter.
`d.min`	Minimal d parameter to be estimated
`d.max`	Maximal d parameter to be estimated

d.start	Starting value(s) of d parameters
c.start	Starting values of c parameters
tau.start	Starting values of τ parameters
sd.start	Starting value for trait standard deviation
d.prior	Normal prior $N(M, S^2)$ for d parameters
c.prior	Normal prior for c parameters. The prior for parameter c_{irk} is defined as $M \cdot (k - 0.5)$ where M is c.prior[1].
tau.prior	Normal prior for τ parameters
a.prior	Normal prior for a parameters
link_item	Type of item response function for latent responses. Can be "GPCM" for the generalized partial credit model or "GRM" for the graded response model.
max.increment	Maximum increment of item parameters during estimation
numdiff.parm	Numerical differentiation step width
maxdevchange	Maximum relative deviance change as a convergence criterion
globconv	Maximum parameter change
maxiter	Maximum number of iterations
msteps	Maximum number of iterations during an M step
mstepconv	Convergence criterion in an M step
optimizer	Choice of optimization function in M-step for item parameters. Options are "nlminb" for stats::nlminb and "optim" for stats::optim.
object	Object of class rm.sdt
file	Optional file name in which summary should be written.
x	Object of class rm.sdt
ask	Optional logical indicating whether a new plot should be asked for.
type	Factor score estimation method. Up to now, only type="EAP" is supported.
...	Further arguments to be passed

Details

The specification of the model follows DeCarlo et al. (2011). The second level models the ideal rating (latent response) $\eta = 0, ..., K$ of person p on item i. The option link_item='GPCM' follows the generalized partial credit model

$$P(\eta_{pi} = \eta|\theta_p) \propto exp(a_i q_{i\eta} \theta_p - \tau_{i\eta})$$

. The option link_item='GRM' employs the graded response model

$$P(\eta_{pi} = \eta|\theta_p) = \Psi(\tau_{i,\eta+1} - a_i\theta_p) - \Psi(\tau_{i,\eta} - a_i\theta_p)$$

At the first level, the ratings X_{pir} for person p on item i and rater r are modeled as a signal detection model

$$P(X_{pir} \leq k|\eta_{pi}) = G(c_{irk} - d_{ir}\eta_{pi})$$

where G is the logistic distribution function and the categories are $k = 1, \ldots, K+1$. Note that the item response model can be equivalently written as

$$P(X_{pir} \geq k | \eta_{pi}) = G(d_{ir}\eta_{pi} - c_{irk})$$

The thresholds c_{irk} can be further restricted to $c_{irk} = c_k$ (`est.c.rater='e'`), $c_{irk} = c_{ik}$ (`est.c.rater='i'`) or $c_{irk} = c_{ir}$ (`est.c.rater='r'`). The same holds for rater precision parameters d_{ir}.

Value

A list with following entries:

`deviance`	Deviance
`ic`	Information criteria and number of parameters
`item`	Data frame with item parameters. The columns `N` and `M` denote the number of observed ratings and the observed mean of all ratings, respectively. In addition to item parameters τ_{ik} and a_i, the mean for the latent response (`latM`) is computed as $E(\eta_i) = \sum_p P(\theta_p) q_{ik} P(\eta_i = k \mid \theta_p)$ which provides an item parameter at the original metric of ratings. The latent standard deviation (`latSD`) is computed in the same manner.
`rater`	Data frame with rater parameters. Transformed c parameters (`c_x.trans`) are computed as $c_{irk}/(d_{ir})$.
`person`	Data frame with person parameters: EAP and corresponding standard errors
`EAP.rel`	EAP reliability
`EAP.rel`	EAP reliability
`mu`	Mean of the trait distribution
`sigma`	Standard deviation of the trait distribution
`tau.item`	Item parameters τ_{ik}
`se.tau.item`	Standard error of item parameters τ_{ik}
`a.item`	Item slopes a_i
`se.a.item`	Standard error of item slopes a_i
`c.rater`	Rater parameters c_{irk}
`se.c.rater`	Standard error of rater severity parameter c_{irk}
`d.rater`	Rater slope parameter d_{ir}
`se.d.rater`	Standard error of rater slope parameter d_{ir}
`f.yi.qk`	Individual likelihood
`f.qk.yi`	Individual posterior distribution
`probs`	Item probabilities at grid `theta.k`. Note that these probabilities are calculated on the pseudo items $i \times r$, i.e. the interaction of item and rater.
`prob.item`	Probabilities $P(\eta_i = \eta \mid \theta)$ of latent item responses evaluated at theta grid θ_p.
`n.ik`	Expected counts
`pi.k`	Estimated trait distribution $P(\theta_p)$.
`maxK`	Maximum number of categories
`procdata`	Processed data
`iter`	Number of iterations
`...`	Further values

References

DeCarlo, L. T. (2005). A model of rater behavior in essay grading based on signal detection theory. *Journal of Educational Measurement, 42*, 53-76.

DeCarlo, L. T. (2010). *Studies of a latent-class signal-detection model for constructed response scoring II: Incomplete and hierarchical designs*. ETS Research Report ETS RR-10-08. Princeton NJ: ETS.

DeCarlo, T., Kim, Y., & Johnson, M. S. (2011). A hierarchical rater model for constructed responses, with a signal detection rater model. *Journal of Educational Measurement, 48*, 333-356.

Robitzsch, A., & Steinfeld, J. (2018). Item response models for human ratings: Overview, estimation methods, and implementation in R. *Psychological Test and Assessment Modeling, 60*(1), 101-139.

Vermunt, J. K. (2008). Latent class and finite mixture models for multilevel data sets. *Statistical Methods in Medical Research, 17*, 33-51.

See Also

The facets rater model can be estimated with `rm.facets`.

Examples

```
#############################################################################
# EXAMPLE 1: Hierarchical rater model (HRM-SDT) data.ratings1
#############################################################################
data(data.ratings1)
dat <- data.ratings1

## Not run:
# Model 1: Partial Credit Model: no rater effects
mod1 <- sirt::rm.sdt( dat[, paste0( "k",1:5) ], rater=dat$rater,
            pid=dat$idstud, est.c.rater="n", d.start=100,  est.d.rater="n" )
summary(mod1)

# Model 2: Generalized Partial Credit Model: no rater effects
mod2 <- sirt::rm.sdt( dat[, paste0( "k",1:5) ], rater=dat$rater,
            pid=dat$idstud, est.c.rater="n", est.d.rater="n",
            est.a.item=TRUE, d.start=100)
summary(mod2)

# Model 3: Equal effects in SDT
mod3 <- sirt::rm.sdt( dat[, paste0( "k",1:5) ], rater=dat$rater,
            pid=dat$idstud, est.c.rater="e", est.d.rater="e")
summary(mod3)

# Model 4: Rater effects in SDT
mod4 <- sirt::rm.sdt( dat[, paste0( "k",1:5) ], rater=dat$rater,
            pid=dat$idstud, est.c.rater="r", est.d.rater="r")
summary(mod4)

#############################################################################
# EXAMPLE 2: HRM-SDT data.ratings3
```

```
#############################################################################

data(data.ratings3)
dat <- data.ratings3
dat <- dat[ dat$rater < 814, ]
psych::describe(dat)

# Model 1: item- and rater-specific effects
mod1 <- sirt::rm.sdt( dat[, paste0( "crit",c(2:4)) ], rater=dat$rater,
            pid=dat$idstud, est.c.rater="a", est.d.rater="a" )
summary(mod1)
plot(mod1)

# Model 2: Differing number of categories per variable
mod2 <- sirt::rm.sdt( dat[, paste0( "crit",c(2:4,6)) ], rater=dat$rater,
            pid=dat$idstud, est.c.rater="a", est.d.rater="a")
summary(mod2)
plot(mod2)

#############################################################################
# EXAMPLE 3: Hierarchical rater model with discrete skill spaces
#############################################################################

data(data.ratings3)
dat <- data.ratings3
dat <- dat[ dat$rater < 814, ]
psych::describe(dat)

# Model 1: Discrete theta skill space with values of 0,1,2 and 3
mod1 <- sirt::rm.sdt( dat[, paste0( "crit",c(2:4)) ], theta.k=0:3, rater=dat$rater,
            pid=dat$idstud, est.c.rater="a", est.d.rater="a", skillspace="discrete" )
summary(mod1)
plot(mod1)

# Model 2: Modelling of one item by using a discrete skill space and
#          fixed item parameters

# fixed tau and a parameters
tau.item.fixed <- cbind( 1, 1:3,  100*cumsum( c( 0.5, 1.5, 2.5)) )
a.item.fixed <- cbind( 1, 100 )
# fit HRM-SDT
mod2 <- sirt::rm.sdt( dat[, "crit2", drop=FALSE], theta.k=0:3, rater=dat$rater,
            tau.item.fixed=tau.item.fixed,a.item.fixed=a.item.fixed, pid=dat$idstud,
            est.c.rater="a", est.d.rater="a", skillspace="discrete" )
summary(mod2)
plot(mod2)

## End(Not run)
```

---

rmvn *Simulation of a Multivariate Normal Distribution with Exact Moments*

Description

Simulates a dataset from a multivariate or univariate normal distribution that exactly fulfils the specified mean vector and the covariance matrix.

Usage

```
# multivariate normal distribution
rmvn(N, mu, Sigma, exact=TRUE)

# univariate normal distribution
ruvn(N, mean=0, sd=1, exact=TRUE)
```

Arguments

N	Sample size
mu	Mean vector
Sigma	Covariance matrix
exact	Logical indicating whether mu and Sigma should be exactly reproduced.
mean	Numeric value for mean
sd	Numeric value for standard deviation

Value

A dataframe or a vector

See Also

mvtnorm::rmvnorm, mgcv::rmvn

Examples

```
############################################################################
# EXAMPLE 1: Simulate multivariate normal data
############################################################################

# define covariance matrix and mean vector
rho <- .8
Sigma <- matrix(rho,3,3)
diag(Sigma) <- 1
mu <- c(0,.5,1)

#* simulate data
set.seed(87)
dat <- sirt::rmvn(N=200, mu=mu, Sigma=Sigma)
#* check means and covariances
stats::cov.wt(dat, method="ML")

## Not run:
############################################################################
```

```
# EXAMPLE 2: Simulate univariate normal data
#############################################################################

#* simulate data
x <- sirt::ruvn(N=20, mean=.5, sd=1.2, exact=TRUE)
# check results
stats::var(x)
sirt:::sirt_var(x)

## End(Not run)
```

---

scale_group_means *Scaling of Group Means and Standard Deviations*

Description

Scales a vector of means and standard deviations containing group values.

Usage

```
scale_group_means(M, SD, probs=NULL, M_target=0, SD_target=1)

## predict method
predict_scale_group_means(object, M, SD)
```

Arguments

M	Vector of means
SD	Vector of standard deviations
probs	Optional vector containing probabilities
M_target	Target value for mean
SD_target	Target value for standard deviation
object	Fitted object from scale_group_means

Value

List with entries

M1	total mean
SD1	total standard deviation
M_z	standardized means
SD_z	standardized standard deviations
M_trafo	transformed means
SD_trafo	transformed standard deviations

Examples

```
#############################################################################
# EXAMPLE 1: Toy example
#############################################################################

M <- c(-.03, .18, -.23, -.15, .29)
SD <- c(.97, 1.13, .77, 1.05, 1.17)
sirt::scale_group_means(M=M, SD=SD)
```

`sia.sirt` *Statistical Implicative Analysis (SIA)*

Description

This function is a simplified implementation of statistical implicative analysis (Gras & Kuntz, 2008) which aims at deriving implications $X_i \rightarrow X_j$. This means that solving item i implies solving item j.

Usage

```
sia.sirt(dat, significance=0.85)
```

Arguments

`dat`	Data frame with dichotomous item responses
`significance`	Minimum implicative probability for inclusion of an arrow in the graph. The probability can be interpreted as a kind of significance level, i.e. higher probabilities indicate more probable implications.

Details

The test statistic for selection an implicative relation follows Gras and Kuntz (2008). Transitive arrows (implications) are removed from the graph. If some implications are symmetric, then only the more probable implication will be retained.

Value

A list with following entries

`adj.matrix`	Adjacency matrix of the graph. Transitive and symmetric implications (arrows) have been removed.
`adj.pot`	Adjacency matrix including all powers, i.e. all direct and indirect paths from item i to item j.
`adj.matrix.trans`	Adjacency matrix including transitive arrows.
`desc`	List with descriptive statistics of the graph.

`desc.item`	Descriptive statistics for each item.
`impl.int`	Implication intensity (probability) as the basis for deciding the significance of an arrow
`impl.t`	Corresponding t values of `impl.int`
`impl.significance`	Corresponding p values (significancies) of `impl.int`
`conf.loev`	Confidence according to Loevinger (see Gras & Kuntz, 2008). This values are just conditional probabilities $P(X_j = 1 \mid X_i = 1)$.
`graph.matr`	Matrix containing all arrows. Can be used for example for the **Rgraphviz** package.
`graph.edges`	Vector containing all edges of the graph, e.g. for the **Rgraphviz** package.
`igraph.matr`	Matrix containing all arrows for the **igraph** package.
`igraph.obj`	An object of the graph for the **igraph** package.

Note

For an implementation of statistical implicative analysis in the C.H.I.C. (Classification Hierarchique, Implicative et Cohesitive) software.

See https://ardm.eu/partenaires/logiciel-danalyse-de-donnees-c-h-i-c/.

References

Gras, R., & Kuntz, P. (2008). An overview of the statistical implicative analysis (SIA) development. In R. Gras, E. Suzuki, F. Guillet, & F. Spagnolo (Eds.). *Statistical Implicative Analysis* (pp. 11-40). Springer, Berlin Heidelberg.

See Also

See also the **IsingFit** package for calculating a graph for dichotomous item responses using the Ising model.

Examples

```
#############################################################################
# EXAMPLE 1: SIA for data.read
#############################################################################

data(data.read)
dat <- data.read

res <- sirt::sia.sirt(dat, significance=.85 )

#*** plot results with igraph package
library(igraph)
plot( res$igraph.obj ) #, vertex.shape="rectangle", vertex.size=30 )

## Not run:
#*** plot results with qgraph package
```

```
miceadds::library_install(qgraph)
qgraph::qgraph( res$adj.matrix )

#*** plot results with Rgraphviz package
# Rgraphviz can only be obtained from Bioconductor
# If it should be downloaded, select TRUE for the following lines
if (FALSE){
     source("http://bioconductor.org/biocLite.R")
     biocLite("Rgraphviz")
           }
# define graph
grmatrix <- res$graph.matr
res.graph <- new("graphNEL", nodes=res$graph.edges, edgemode="directed")
# add edges
RR <- nrow(grmatrix)
for (rr in 1:RR){
    res.graph <- Rgraphviz::addEdge(grmatrix[rr,1], grmatrix[rr,2], res.graph, 1)
                    }
# define cex sizes and shapes
V <- length(res$graph.edges)
size2 <- rep(16,V)
shape2 <- rep("rectangle", V )
names(shape2) <- names(size2) <- res$graph.edges
# plot graph
Rgraphviz::plot( res.graph, nodeAttrs=list("fontsize"=size2, "shape"=shape2) )

## End(Not run)
```

`sim.qm.ramsay` *Simulate from Ramsay's Quotient Model*

Description

This function simulates dichotomous item response data according to Ramsay's quotient model (Ramsay, 1989).

Usage

```
sim.qm.ramsay(theta, b, K)
```

Arguments

`theta`	Vector of of length N person parameters (must be positive!)
`b`	Vector of length I of item difficulties (must be positive)
`K`	Vector of length I of guessing parameters (must be positive)

Details

Ramsay's quotient model (Ramsay, 1989) is defined by the equation

$$P(X_{pi}=1|\theta_p) = \frac{\exp(\theta_p/b_i)}{K_i + \exp(\theta_p/b_i)}$$

Value

An $N \times I$ data frame with dichotomous item responses.

References

Ramsay, J. O. (1989). A comparison of three simple test theory models. *Psychometrika, 54*, 487-499.

van der Maas, H. J. L., Molenaar, D., Maris, G., Kievit, R. A., & Borsboom, D. (2011). Cognitive psychology meets psychometric theory: On the relation between process models for decision making and latent variable models for individual differences. *Psychological Review, 318*, 339-356.

See Also

See `rasch.mml2` for estimating Ramsay's quotient model.

See `sim.raschtype` for simulating response data from the generalized logistic item response model.

Examples

```
#############################################################################
# EXAMPLE 1: Estimate Ramsay Quotient Model with rasch.mml2
#############################################################################

set.seed(657)
# simulate data according to the Ramsay model
N <- 1000       # persons
I <- 11         # items
theta <- exp( stats::rnorm( N ) )  # person ability
b <- exp( seq(-2,2,len=I))  # item difficulty
K <- rep( 3, I )           # K parameter (=> guessing)

# apply simulation function
dat <- sirt::sim.qm.ramsay( theta, b, K )

#***
# analysis
mmliter <- 50       # maximum number of iterations
I <- ncol(dat)
fixed.K <- rep( 3, I )

# Ramsay QM with fixed K parameter (K=3 in fixed.K specification)
mod1 <- sirt::rasch.mml2( dat, mmliter=mmliter, irtmodel="ramsay.qm",
              fixed.K=fixed.K )
summary(mod1)
```

```
# Ramsay QM with joint estimated K parameters
mod2 <- sirt::rasch.mml2( dat, mmliter=mmliter, irtmodel="ramsay.qm",
             est.K=rep(1,I)  )
summary(mod2)

## Not run:
# Ramsay QM with itemwise estimated K parameters
mod3 <- sirt::rasch.mml2( dat, mmliter=mmliter, irtmodel="ramsay.qm",
              est.K=1:I  )
summary(mod3)

# Rasch model
mod4 <- sirt::rasch.mml2( dat )
summary(mod4)

# generalized logistic model
mod5 <- sirt::rasch.mml2( dat, est.alpha=TRUE, mmliter=mmliter)
summary(mod5)

# 2PL model
mod6 <- sirt::rasch.mml2( dat, est.a=rep(1,I) )
summary(mod6)

# Difficulty + Guessing (b+c) Model
mod7 <- sirt::rasch.mml2( dat, est.c=rep(1,I) )
summary(mod7)

# estimate separate guessing (c) parameters
mod8 <- sirt::rasch.mml2( dat, est.c=1:I  )
summary(mod8)

#*** estimate Model 1 with user defined function in mirt package

# create user defined function for Ramsay's quotient model
name <- 'ramsayqm'
par <- c("K"=3, "b"=1 )
est <- c(TRUE, TRUE)
P.ramsay <- function(par,Theta){
     eps <- .01
     K <- par[1]
     b <- par[2]
     num <- exp( exp( Theta[,1] ) / b )
     denom <- K + num
     P1 <- num / denom
     P1 <- eps + ( 1 - 2*eps ) * P1
     cbind(1-P1, P1)
}

# create item response function
ramsayqm <- mirt::createItem(name, par=par, est=est, P=P.ramsay)
# define parameters to be estimated
mod1m.pars <- mirt::mirt(dat, 1, rep( "ramsayqm",I),
                  customItems=list("ramsayqm"=ramsayqm), pars="values")
```

```
mod1m.pars[ mod1m.pars$name=="K", "est" ] <- FALSE
# define Theta design matrix
Theta <- matrix( seq(-3,3,len=10), ncol=1)
# estimate model
mod1m <- mirt::mirt(dat, 1, rep( "ramsayqm",I), customItems=list("ramsayqm"=ramsayqm),
               pars=mod1m.pars, verbose=TRUE,
               technical=list( customTheta=Theta, NCYCLES=50)
                )
print(mod1m)
summary(mod1m)
cmod1m <- sirt::mirt.wrapper.coef( mod1m )$coef
# compare simulated and estimated values
dfr <- cbind( b, cmod1m$b, exp(mod1$item$b ) )
colnames(dfr) <- c("simulated", "mirt", "sirt_rasch.mml2")
round( dfr, 2 )
  ##      simulated mirt sirt_rasch.mml2
  ## [1,]      0.14 0.11            0.11
  ## [2,]      0.20 0.17            0.18
  ## [3,]      0.30 0.27            0.29
  ## [4,]      0.45 0.42            0.43
  ## [5,]      0.67 0.65            0.67
  ## [6,]      1.00 1.00            1.01
  ## [7,]      1.49 1.53            1.54
  ## [8,]      2.23 2.21            2.21
  ## [9,]      3.32 3.00            2.98
  ##[10,]      4.95 5.22            5.09
  ##[11,]      7.39 5.62            5.51

## End(Not run)
```

`sim.rasch.dep` *Simulation of the Rasch Model with Locally Dependent Responses*

Description

This function simulates dichotomous item responses where for some itemclusters residual correlations can be defined.

Usage

```
sim.rasch.dep(theta, b, itemcluster, rho)
```

Arguments

`theta`	Vector of person abilities of length N
`b`	Vector of item difficulties of length I
`itemcluster`	Vector of integers (including 0) of length I. Different integers correspond to different itemclusters.
`rho`	Vector of residual correlations. The length of vector must be equal to the number of itemclusters.

Value

An $N \times I$ data frame of dichotomous item responses.

Note

The specification of the simulation models follows a marginal interpretation of the latent trait. Local dependencies are only interpreted as nuisance and not of substantive interest. If local dependencies should be substantively interpreted, a testlet model seems preferable (see `mcmc.3pno.testlet`).

See Also

To simulate the generalized logistic item response model see `sim.raschtype`. Ramsay's quotient model can be simulated using `sim.qm.ramsay`.

Marginal item reponse models for locally dependent item responses can be estimated with `rasch.copula2`, `rasch.pairwise` or `rasch.pairwise.itemcluster`.

Examples

```
#############################################################################
# EXAMPLE 1: 11 Items: 2 itemclusters with 2 resp. 3 dependent items
#             and 6 independent items
#############################################################################

set.seed(7654)
I <- 11                             # number of items
n <- 1500                           # number of persons
b <- seq(-2,2, len=I)               # item difficulties
theta <- stats::rnorm( n, sd=1 )        # person abilities
# itemcluster
itemcluster <- rep(0,I)
itemcluster[ c(3,5)] <- 1
itemcluster[c(2,4,9)] <- 2
# residual correlations
rho <- c( .7, .5 )

# simulate data
dat <- sirt::sim.rasch.dep( theta, b, itemcluster, rho )
colnames(dat) <- paste("I", seq(1,ncol(dat)), sep="")

# estimate Rasch copula model
mod1 <- sirt::rasch.copula2( dat, itemcluster=itemcluster )
summary(mod1)

# compare result with Rasch model estimation in rasch.copula
# delta must be set to zero
mod2 <- sirt::rasch.copula2( dat, itemcluster=itemcluster, delta=c(0,0),
            est.delta=c(0,0)  )
summary(mod2)

# estimate Rasch model with rasch.mml2 function
mod3 <- sirt::rasch.mml2( dat )
```

```
summary(mod3)

## Not run:
#############################################################################
# EXAMPLE 2: 12 Items: Cluster 1 -> Items 1,...,4;
#       Cluster 2 -> Items 6,...,9; Cluster 3 -> Items 10,11,12
#############################################################################

set.seed(7896)
I <- 12                             # number of items
n <- 450                            # number of persons
b <- seq(-2,2, len=I)               # item difficulties
b <- sample(b)                      # sample item difficulties
theta <- stats::rnorm( n, sd=1 )        # person abilities
# itemcluster
itemcluster <- rep(0,I)
itemcluster[ 1:4 ] <- 1
itemcluster[ 6:9 ] <- 2
itemcluster[ 10:12 ] <- 3
# residual correlations
rho <- c( .55, .25, .45 )

# simulate data
dat <- sirt::sim.rasch.dep( theta, b, itemcluster, rho )
colnames(dat) <- paste("I", seq(1,ncol(dat)), sep="")

# estimate Rasch copula model
mod1 <- sirt::rasch.copula2( dat, itemcluster=itemcluster, numdiff.parm=.001 )
summary(mod1)

# Rasch model estimation
mod2 <- sirt::rasch.copula2( dat, itemcluster=itemcluster,
            delta=rep(0,3), est.delta=rep(0,3) )
summary(mod2)

# estimation with pairwise Rasch model
mod3 <- sirt::rasch.pairwise( dat )
summary(mod3)

## End(Not run)
```

`sim.raschtype` *Simulate from Generalized Logistic Item Response Model*

Description

This function simulates dichotomous item responses from a generalized logistic item response model (Stukel, 1988). The four-parameter logistic item response model (Loken & Rulison, 2010) is a special case. See `rasch.mml2` for more details.

Usage

```
sim.raschtype(theta, b, alpha1=0, alpha2=0, fixed.a=NULL,
    fixed.c=NULL, fixed.d=NULL)
```

Arguments

theta	Unidimensional ability vector θ
b	Vector of item difficulties b
alpha1	Parameter α_1 in generalized logistic link function
alpha2	Parameter α_2 in generalized logistic link function
fixed.a	Vector of item slopes a
fixed.c	Vector of lower item asymptotes c
fixed.d	Vector of lower item asymptotes d

Details

The class of generalized logistic link functions contain the most important link functions using the specifications (Stukel, 1988):

logistic link function: $\alpha_1 = 0$ and $\alpha_2 = 0$
probit link function: $\alpha_1 = 0.165$ and $\alpha_2 = 0.165$
loglog link function: $\alpha_1 = -0.037$ and $\alpha_2 = 0.62$
cloglog link function: $\alpha_1 = 0.62$ and $\alpha_2 = -0.037$

See pgenlogis for exact transformation formulas of the mentioned link functions.

Value

Data frame with simulated item responses

References

Loken, E., & Rulison, K. L. (2010). Estimation of a four-parameter item response theory model. *British Journal of Mathematical and Statistical Psychology, 63*, 509-525.

Stukel, T. A. (1988). Generalized logistic models. *Journal of the American Statistical Association, 83*, 426-431.

See Also

rasch.mml2, pgenlogis

Examples

```
#############################################################################
## EXAMPLE 1: Simulation of data from a Rasch model (alpha_1=alpha_2=0)
#############################################################################

set.seed(9765)
```

```
N <- 500    # number of persons
I <- 11     # number of items
b <- seq( -2, 2, length=I )
dat <- sirt::sim.raschtype( stats::rnorm( N ), b )
colnames(dat) <- paste0( "I", 1:I )
```

`sirt-defunct` *Defunct* **sirt** *Functions*

Description

These functions have been removed or replaced in the **sirt** package.

Usage

```
rasch.conquest(...)
rasch.pml2(...)
testlet.yen.q3(...)
yen.q3(...)
```

Arguments

`...`	Arguments to be passed.

Details

The `rasch.conquest` function has been replaced by `R2conquest`.

The `rasch.pml2` function has been superseded by `rasch.pml3`.

The `testlet.yen.q3` function has been replaced by `Q3.testlet`.

The `yen.q3` function has been replaced by `Q3`.

`sirt-utilities` *Utility Functions in* **sirt**

Description

Utility functions in **sirt**.

Usage

```
# bounds entries in a vector
bounds_parameters( pars, lower=NULL, upper=NULL)

# improper density function which always returns a value of 1
dimproper(x)

# generalized inverse of a symmetric function
ginverse_sym(A, eps=1E-8)
# hard thresholding function
hard_thresholding(x, lambda)
# soft thresholding function
soft_thresholding(x, lambda)

# power function x^a, like in Cpp
pow(x, a)
# trace of a matrix
tracemat(A)

#** matrix functions
sirt_matrix2(x, nrow)   # matrix() function with byrow=TRUE
sirt_colMeans(x, na.rm=TRUE)
sirt_colSDs(x, na.rm=TRUE)
sirt_colMins(x, na.rm=TRUE)
sirt_colMaxs(x, na.rm=TRUE)
sirt_colMedians(x, na.rm=TRUE)

#* normalize vector to have sum of one
sirt_sum_norm(x, na.rm=TRUE)
#* discrete normal distribution
sirt_dnorm_discrete(x, mean=0, sd=1, ...)

# plyr::rbind.fill implementation in sirt
sirt_rbind_fill(x, y)

# Fisher-z transformation, see psych::fisherz
sirt_fisherz(rho)
# inverse Fisher-z transformation, see psych::fisherz2r
sirt_antifisherz(z)

# smooth approximation of the absolute value function
sirt_abs_smooth(x, deriv=0, eps=1e-4)

# permutations with replacement
sirt_permutations(r,v)
 #-> is equivalent to gtools::permutations(n=length(v), r=D, v=v, repeats.allowed=TRUE)

# attach all elements in a list in a specified environment
```

```
sirt_attach_list_elements(x, envir)

# switch between stats::optim and stats::nlminb
sirt_optimizer(optimizer, par, fn, grad=NULL, method="L-BFGS-B", hessian=TRUE,
                   control=list(), ...)

# print objects in a summary
sirt_summary_print_objects(obji, from=NULL, to=NULL, digits=3, rownames_null=TRUE,
      grep_string=NULL)
# print package version and R session
sirt_summary_print_package_rsession(pack)
# print package version
sirt_summary_print_package(pack)
# print R session
sirt_summary_print_rsession()
# print call
sirt_summary_print_call(CALL)

# print a data frame x with fixed numbers of digits after the decimal
print_digits(x, digits=NULL)

# discrete inverse function
sirt_rcpp_discrete_inverse(x0, y0, y)

# move variables in a data frame
move_variables_df(x, after_var, move_vars)
```

Arguments

pars	Numeric vector
lower	Numeric vector
upper	Numeric vector
x	Numeric vector or a matrix or a list
eps	Numerical. Shrinkage parameter of eigenvalue in ginverse_sym
a	Numeric vector
lambda	Numeric value
A	Matrix
nrow	Integer
na.rm	Logical
mean	Numeric
sd	Numeric
y	Matrix
rho	Numeric
deriv	Integer indicating the order of derivative

z	Numeric
r	Integer
v	Vector
envir	Environment
optimizer	Can be one of the following optimizers: optim, nlminb, bobyqa (from the **minqa** packlage), Rvmmin (from the **optimx** package) or nloptr (from the **nloptr** package using the argument opts$algorithm="NLOPT_LD_MMA").
par	Initial parameter
fn	Function
grad	Gradient function
method	Optimization method
hessian	Logical
control	Control list for R optimizers
...	Further arguments to be passed
obji	Data frame
from	Integer
to	Integer
digits	Integer
rownames_null	Logical
grep_string	String
pack	Package name
CALL	Call statement
x0	Vector
y0	Vector
after_var	String indicating variable name after which variable specified variables in move_vars should be moved
move_vars	Variables which should be moved after after_var

Examples

```
############################################################################
## EXAMPLE 1: Trace of a matrix
############################################################################

set.seed(86)
A <- matrix( stats::runif(4), 2,2 )
tracemat(A)
sum(diag(A))    #=sirt::tracemat(A)

############################################################################
## EXAMPLE 2: Power function
############################################################################
```

```
x <- 2.3
a <- 1.7
pow(x=x,a=a)
x^a            #=sirt::pow(x,a)

#############################################################################
## EXAMPLE 3: Soft and hard thresholding function (e.g. in LASSO estimation)
#############################################################################

x <- seq(-2, 2, length=100)
y <- sirt::soft_thresholding( x, lambda=.5)
graphics::plot( x, y, type="l")

z <- sirt::hard_thresholding( x, lambda=.5)
graphics::lines( x, z, lty=2, col=2)

#############################################################################
## EXAMPLE 4: Bounds on parameters
#############################################################################

pars <- c(.721, .346)
bounds_parameters( pars=pars, lower=c(-Inf, .5), upper=c(Inf,1) )

#############################################################################
## EXAMPLE 5: Smooth approximation of absolute value function
#############################################################################

x <- seq(-1,1,len=100)
graphics::plot(x, abs(x), lwd=2, col=1, lty=1, type="l", ylim=c(-1,1) )
# smooth approximation
tt <- 2
graphics::lines(x, sirt::sirt_abs_smooth(x), lty=tt, col=tt, lwd=2)
# first derivative
tt <- 3
graphics::lines(x, sirt::sirt_abs_smooth(x, deriv=1), lty=tt, col=tt, lwd=2)
# second derivative
tt <- 4
graphics::lines(x, sirt::sirt_abs_smooth(x, deriv=2), lty=tt, col=tt, lwd=2)

# analytic computation of first and second derivative
stats::deriv( ~ sqrt(x^2 + eps), namevec="x", hessian=TRUE )

## Not run:
#############################################################################
## EXAMPLE 6: Permutations with replacement
#############################################################################

D <- 4
v <- 0:1
sirt::sirt_permutations(r=D, v=v)
gtools::permutations(n=length(v), r=D, v=v, repeats.allowed=TRUE)

## End(Not run)
```

`sirt_eigenvalues` *First Eigenvalues of a Symmetric Matrix*

Description

This function computes the first D eigenvalues and eigenvectors of a symmetric positive definite matrices. The eigenvalues are computed by the Rayleigh quotient method (Lange, 2010, p. 120).

Usage

```
sirt_eigenvalues( X, D, maxit=200, conv=10^(-6) )
```

Arguments

`X`	Symmetric matrix
`D`	Number of eigenvalues to be estimated
`maxit`	Maximum number of iterations
`conv`	Convergence criterion

Value

A list with following entries:

`d`	Vector of eigenvalues
`u`	Matrix with eigenvectors in columns

References

Lange, K. (2010). *Numerical Analysis for Statisticians*. New York: Springer.

Examples

```
Sigma <- diag(1,3)
Sigma[ lower.tri(Sigma) ] <- Sigma[ upper.tri(Sigma) ] <- c(.4,.6,.8 )
sirt::sirt_eigenvalues(X=Sigma, D=2 )
# compare with svd function
svd(Sigma)
```

smirt *Multidimensional Noncompensatory, Compensatory and Partially Compensatory Item Response Model*

Description

This function estimates the noncompensatory and compensatory multidimensional item response model (Bolt & Lall, 2003; Reckase, 2009) as well as the partially compensatory item response model (Spray et al., 1990) for dichotomous data.

Usage

```
smirt(dat, Qmatrix, irtmodel="noncomp", est.b=NULL, est.a=NULL,
     est.c=NULL, est.d=NULL, est.mu.i=NULL, b.init=NULL, a.init=NULL,
     c.init=NULL, d.init=NULL, mu.i.init=NULL, Sigma.init=NULL,
     b.lower=-Inf, b.upper=Inf, a.lower=-Inf, a.upper=Inf,
     c.lower=-Inf, c.upper=Inf, d.lower=-Inf, d.upper=Inf,
     theta.k=seq(-6,6,len=20), theta.kDES=NULL,
     qmcnodes=0, mu.fixed=NULL, variance.fixed=NULL,  est.corr=FALSE,
     max.increment=1, increment.factor=1, numdiff.parm=0.0001,
     maxdevchange=0.1, globconv=0.001, maxiter=1000, msteps=4,
     mstepconv=0.001)

## S3 method for class 'smirt'
summary(object,...)

## S3 method for class 'smirt'
anova(object,...)

## S3 method for class 'smirt'
logLik(object,...)

## S3 method for class 'smirt'
IRT.irfprob(object,...)

## S3 method for class 'smirt'
IRT.likelihood(object,...)

## S3 method for class 'smirt'
IRT.posterior(object,...)

## S3 method for class 'smirt'
IRT.modelfit(object,...)

## S3 method for class 'IRT.modelfit.smirt'
summary(object,...)
```

Arguments

dat	Data frame with dichotomous item responses
Qmatrix	The Q-matrix which specifies the loadings to be estimated
irtmodel	The item response model. Options are the noncompensatory model ("noncomp"), the compensatory model ("comp") and the partially compensatory model ("partcomp"). See Details for more explanations.
est.b	An integer matrix (if irtmodel="noncomp") or integer vector (if irtmodel="comp") for b parameters to be estimated
est.a	An integer matrix for a parameters to be estimated. If est.a="2PL", then all item loadings will be estimated and the variances are set to one (and therefore est.corr=TRUE).
est.c	An integer vector for c parameters to be estimated
est.d	An integer vector for d parameters to be estimated
est.mu.i	An integer vector for μ_i parameters to be estimated
b.init	Initial b coefficients. For irtmodel="noncomp" it must be a matrix, for irtmodel="comp" it is a vector.
a.init	Initial a coefficients arranged in a matrix
c.init	Initial c coefficients
d.init	Initial d coefficients
mu.i.init	Initial d coefficients
Sigma.init	Initial covariance matrix Σ
b.lower	Lower bound for b parameter
b.upper	Upper bound for b parameter
a.lower	Lower bound for a parameter
a.upper	Upper bound for a parameter
c.lower	Lower bound for c parameter
c.upper	Upper bound for c parameter
d.lower	Lower bound for d parameter
d.upper	Upper bound for d parameter
theta.k	Vector of discretized trait distribution. This vector is expanded in all dimensions by using the base::expand.grid function. If a user specifies a design matrix theta.kDES of transformed $\boldsymbol{\theta}_p$ values (see Details and Examples), then theta.k must be a matrix, too.
theta.kDES	An optional design matrix. This matrix will differ from the ordinary theta grid in case of nonlinear item response models.
qmcnodes	Number of integration nodes for quasi Monte Carlo integration (see Pan & Thompson, 2007; Gonzales et al., 2006). Integration points are obtained by using the function qmc.nodes. Note that when using quasi Monte Carlo nodes, no theta design matrix theta.kDES can be specified. See Example 1, Model 11.
mu.fixed	Matrix with fixed entries in the mean vector. By default, all means are set to zero.

`variance.fixed` Matrix (with rows and three columns) with fixed entries in the covariance matrix (see Examples). The entry c_{kd} of the covariance between dimensions k and d is set to c_0 iff `variance.fixed` has a row with a k in the first column, a d in the second column and the value c_0 in the third column.

`est.corr` Should only a correlation matrix instead of a covariance matrix be estimated?

`max.increment` Maximum increment

`increment.factor`
A value (larger than one) which defines the extent of the decrease of the maximum increment of item parameters in every iteration. The maximum increment in iteration `iter` is defined as `max.increment*increment.factor^(-iter)` where `max.increment=1`. Using a value larger than 1 helps to reach convergence in some non-converging analyses (use values of 1.01, 1.02 or even 1.05). See also Example 1 Model 2a.

`numdiff.parm` Numerical differentiation parameter

`maxdevchange` Convergence criterion for change in relative deviance

`globconv` Global convergence criterion for parameter change

`maxiter` Maximum number of iterations

`msteps` Number of iterations within a M step

`mstepconv` Convergence criterion within a M step

`object` Object of class `smirt`

`...` Further arguments to be passed

Details

The noncompensatory item response model (`irtmodel="noncomp"`; e.g. Bolt & Lall, 2003) is defined as

$$P(X_{pi}=1|\boldsymbol{\theta}_p) = c_i + (d_i - c_i) \prod_l invlogit(a_{il} q_{il} \theta_{pl} - b_{il})$$

where i, p, l denote items, persons and dimensions respectively.

The compensatory item response model (`irtmodel="comp"`) is defined by

$$P(X_{pi}=1|\boldsymbol{\theta}_p) = c_i + (d_i - c_i) invlogit(\sum_l a_{il} q_{il} \theta_{pl} - b_i)$$

Using a design matrix `theta.kDES` the model can be made even more general in a model which is linear in item parameters

$$P(X_{pi}=1|\boldsymbol{\theta}_p) = c_i + (d_i - c_i) invlogit(\sum_l a_{il} q_{il} t_l(\boldsymbol{\theta_p}) - b_i)$$

with known functions t_l of the trait vector $\boldsymbol{\theta}_p$. Fixed values of the functions t_l are specified in the $\boldsymbol{\theta}_p$ design matrix `theta.kDES`.

The partially compensatory item response model (`irtmodel="partcomp"`) is defined by

$$P(X_{pi}=1|\boldsymbol{\theta}_p) = c_i + (d_i - c_i) \frac{\exp\left(\sum_l (a_{il} q_{il} \theta_{pl} - b_{il})\right)}{\mu_i \prod_l (1+\exp(a_{il} q_{il} \theta_{pl} - b_{il})) + (1-\mu_i)(1+\exp\left(\sum_l (a_{il} q_{il} \theta_{pl} - b_{il})\right))}$$

with item parameters μ_i indicating the degree of compensatory. $\mu_i = 1$ indicates a noncompensatory model while $\mu_i = 0$ indicates a (fully) compensatory model.

The models are estimated by an EM algorithm employing marginal maximum likelihood.

Value

A list with following entries:

deviance	Deviance
ic	Information criteria
item	Data frame with item parameters
person	Data frame with person parameters. It includes the person mean of all item responses (M; percentage correct of all non-missing items), the EAP estimate and its corresponding standard error for all dimensions (EAP and SE.EAP) and the maximum likelihood estimate as well as the mode of the posterior distribution (MLE and MAP).
EAP.rel	EAP reliability
mean.trait	Means of trait
sd.trait	Standard deviations of trait
Sigma	Trait covariance matrix
cor.trait	Trait correlation matrix
b	Matrix (vector) of b parameters
se.b	Matrix (vector) of standard errors b parameters
a	Matrix of a parameters
se.a	Matrix of standard errors of a parameters
c	Vector of c parameters
se.c	Vector of standard errors of c parameters
d	Vector of d parameters
se.d	Vector of standard errors of d parameters
mu.i	Vector of μ_i parameters
se.mu.i	Vector of standard errors of μ_i parameters
f.yi.qk	Individual likelihood
f.qk.yi	Individual posterior
probs	Probabilities of item response functions evaluated at theta.k
n.ik	Expected counts
iter	Number of iterations
dat2	Processed data set
dat2.resp	Data set of response indicators
I	Number of items
D	Number of dimensions
K	Maximum item response score
theta.k	Used theta integration grid
pi.k	Distribution function evaluated at theta.k
irtmodel	Used IRT model
Qmatrix	Used Q-matrix

References

Bolt, D. M., & Lall, V. F. (2003). Estimation of compensatory and noncompensatory multidimensional item response models using Markov chain Monte Carlo. *Applied Psychological Measurement, 27*, 395-414.

Gonzalez, J., Tuerlinckx, F., De Boeck, P., & Cools, R. (2006). Numerical integration in logistic-normal models. *Computational Statistics & Data Analysis, 51*, 1535-1548.

Pan, J., & Thompson, R. (2007). Quasi-Monte Carlo estimation in generalized linear mixed models. *Computational Statistics & Data Analysis, 51*, 5765-5775.

Reckase, M. (2009). *Multidimensional item response theory*. New York: Springer. doi:10.1007/9780387899763

Spray, J. A., Davey, T. C., Reckase, M. D., Ackerman, T. A., & Carlson, J. E. (1990). *Comparison of two logistic multidimensional item response theory models*. ACT Research Report No. ACT-RR-ONR-90-8.

See Also

See the `mirt::mirt` and `itemtype="partcomp"` for estimating noncompensatory item response models using the **mirt** package. See also `mirt::mixedmirt`.

Other multidimensional IRT models can also be estimated with `rasch.mml2` and `rasch.mirtlc`.

See `itemfit.sx2` (**CDM**) for item fit statistics.

See also the **mirt** and **TAM** packages for estimation of compensatory multidimensional item response models.

Examples

```
#############################################################################
## EXAMPLE 1: Noncompensatory and compensatory IRT models
#############################################################################
set.seed(997)

# (1) simulate data from a two-dimensional noncompensatory
#     item response model
#   -> increase number of iterations in all models!

N <- 1000    # number of persons
I <- 10        # number of items
theta0 <- rnorm( N, sd=1 )
theta1 <- theta0 + rnorm(N, sd=.7 )
theta2 <- theta0 + rnorm(N, sd=.7 )
Q <- matrix( 1, nrow=I,ncol=2 )
Q[ 1:(I/2), 2 ] <- 0
Q[ I,1] <- 0
b <- matrix( rnorm( I*2 ), I, 2 )
a <- matrix( 1, I, 2 )

# simulate data
prob <- dat <- matrix(0, nrow=N, ncol=I )
for (ii in 1:I){
```

```
prob[,ii] <- ( stats::plogis( theta1 - b[ii,1]  ) )^Q[ii,1]
prob[,ii] <- prob[,ii] * ( stats::plogis( theta2 - b[ii,2]  ) )^Q[ii,2]
            }
dat[ prob > matrix( stats::runif( N*I),N,I) ] <- 1
colnames(dat) <- paste0("I",1:I)

#***
# Model 1: Noncompensatory 1PL model
mod1 <- sirt::smirt(dat, Qmatrix=Q, maxiter=10 ) # change number of iterations
summary(mod1)

## Not run:
#***
# Model 2: Noncompensatory 2PL model
mod2 <- sirt::smirt(dat,Qmatrix=Q, est.a="2PL", maxiter=15 )
summary(mod2)

# Model 2a: avoid convergence problems with increment.factor
mod2a <- sirt::smirt(dat,Qmatrix=Q, est.a="2PL", maxiter=30, increment.factor=1.03)
summary(mod2a)

#***
# Model 3: some fixed c and d parameters different from zero or one
c.init <- rep(0,I)
c.init[ c(3,7)] <- .2
d.init <- rep(1,I)
d.init[c(4,8)] <- .95
mod3 <- sirt::smirt( dat, Qmatrix=Q, c.init=c.init, d.init=d.init )
summary(mod3)

#***
# Model 4: some estimated c and d parameters (in parameter groups)
est.c <- c.init <- rep(0,I)
c.estpars <- c(3,6,7)
c.init[ c.estpars ] <- .2
est.c[c.estpars] <- 1
est.d <- rep(0,I)
d.init <- rep(1,I)
d.estpars <- c(6,9)
d.init[ d.estpars ] <- .95
est.d[ d.estpars ] <- d.estpars   # different d parameters
mod4 <- sirt::smirt(dat,Qmatrix=Q, est.c=est.c, c.init=c.init,
            est.d=est.d, d.init=d.init  )
summary(mod4)

#***
# Model 5: Unidimensional 1PL model
Qmatrix <- matrix( 1, nrow=I, ncol=1 )
mod5 <- sirt::smirt( dat, Qmatrix=Qmatrix )
summary(mod5)

#***
# Model 6: Unidimensional 2PL model
```

```
mod6 <- sirt::smirt( dat, Qmatrix=Qmatrix, est.a="2PL" )
summary(mod6)

#***
# Model 7: Compensatory model with between item dimensionality
# Note that the data is simulated under the noncompensatory condition
# Therefore Model 7 should have a worse model fit than Model 1
Q1 <- Q
Q1[ 6:10, 1] <- 0
mod7 <- sirt::smirt(dat,Qmatrix=Q1, irtmodel="comp", maxiter=30)
summary(mod7)

#***
# Model 8: Compensatory model with within item dimensionality
#         assuming zero correlation between dimensions
variance.fixed <- as.matrix( cbind( 1,2,0) )
# set the covariance between the first and second dimension to zero
mod8 <- sirt::smirt(dat,Qmatrix=Q, irtmodel="comp", variance.fixed=variance.fixed,
            maxiter=30)
summary(mod8)

#***
# Model 8b: 2PL model with starting values for a and b parameters
b.init <- rep(0,10)  # set all item difficulties initially to zero
# b.init <- NULL
a.init <- Q       # initialize a.init with Q-matrix
# provide starting values for slopes of first three items on Dimension 1
a.init[1:3,1] <- c( .55, .32, 1.3)

mod8b <- sirt::smirt(dat,Qmatrix=Q, irtmodel="comp", variance.fixed=variance.fixed,
              b.init=b.init, a.init=a.init, maxiter=20, est.a="2PL" )
summary(mod8b)

#***
# Model 9: Unidimensional model with quadratic item response functions
# define theta
theta.k <- seq( -6, 6, len=15 )
theta.k <- as.matrix( theta.k, ncol=1 )
# define design matrix
theta.kDES <- cbind( theta.k[,1], theta.k[,1]^2 )
# define Q-matrix
Qmatrix <- matrix( 0, I, 2 )
Qmatrix[,1] <- 1
Qmatrix[ c(3,6,7), 2 ] <- 1
colnames(Qmatrix) <- c("F1", "F1sq" )
# estimate model
mod9 <- sirt::smirt(dat,Qmatrix=Qmatrix, maxiter=50, irtmodel="comp",
           theta.k=theta.k, theta.kDES=theta.kDES, est.a="2PL" )
summary(mod9)

#***
# Model 10: Two-dimensional item response model with latent interaction
#           between dimensions
```

```
theta.k <- seq( - 6, 6, len=15 )
theta.k <- expand.grid( theta.k, theta.k )    # expand theta to 2 dimensions
# define design matrix
theta.kDES <- cbind( theta.k, theta.k[,1]*theta.k[,2] )
# define Q-matrix
Qmatrix <- matrix( 0, I, 3 )
Qmatrix[,1] <- 1
Qmatrix[ 6:10, c(2,3) ] <- 1
colnames(Qmatrix) <- c("F1", "F2", "F1iF2" )
# estimate model
mod10 <- sirt::smirt(dat,Qmatrix=Qmatrix,irtmodel="comp", theta.k=theta.k,
            theta.kDES=theta.kDES, est.a="2PL" )
summary(mod10)

#****
# Model 11: Example Quasi Monte Carlo integration
Qmatrix <- matrix( 1, I, 1 )
mod11 <- sirt::smirt( dat, irtmodel="comp", Qmatrix=Qmatrix, qmcnodes=1000 )
summary(mod11)

############################################################################
## EXAMPLE 2: Dataset Reading data.read
##            Multidimensional models for dichotomous data
############################################################################

data(data.read)
dat <- data.read
I <- ncol(dat)    # number of items

#***
# Model 1: 3-dimensional 2PL model

# define Q-matrix
Qmatrix <- matrix(0,nrow=I,ncol=3)
Qmatrix[1:4,1] <- 1
Qmatrix[5:8,2] <- 1
Qmatrix[9:12,3] <- 1

# estimate model
mod1 <- sirt::smirt( dat, Qmatrix=Qmatrix, irtmodel="comp", est.a="2PL",
            qmcnodes=1000, maxiter=20)
summary(mod1)

#***
# Model 2: 3-dimensional Rasch model
mod2 <- sirt::smirt( dat, Qmatrix=Qmatrix, irtmodel="comp",
              qmcnodes=1000, maxiter=20)
summary(mod2)

#***
# Model 3: 3-dimensional 2PL model with uncorrelated dimensions
# fix entries in variance matrix
variance.fixed <- cbind( c(1,1,2), c(2,3,3), 0 )
```

```
# set the following covariances to zero: cov[1,2]=cov[1,3]=cov[2,3]=0

# estimate model
mod3 <- sirt::smirt( dat, Qmatrix=Qmatrix, irtmodel="comp", est.a="2PL",
             variance.fixed=variance.fixed, qmcnodes=1000, maxiter=20)
summary(mod3)

#***
# Model 4: Bifactor model with one general factor (g) and
#          uncorrelated specific factors

# define a new Q-matrix
Qmatrix1 <- cbind( 1, Qmatrix )
# uncorrelated factors
variance.fixed <- cbind( c(1,1,1,2,2,3), c(2,3,4,3,4,4), 0 )
# The first dimension refers to the general factors while the other
# dimensions refer to the specific factors.
# The specification means that:
# Cov[1,2]=Cov[1,3]=Cov[1,4]=Cov[2,3]=Cov[2,4]=Cov[3,4]=0

# estimate model
mod4 <- sirt::smirt( dat, Qmatrix=Qmatrix1, irtmodel="comp", est.a="2PL",
             variance.fixed=variance.fixed, qmcnodes=1000, maxiter=20)
summary(mod4)

#############################################################################
## EXAMPLE 3: Partially compensatory model
#############################################################################

#**** simulate data
set.seed(7656)
I <- 10         # number of items
N <- 2000        # number of subjects
Q <- matrix( 0, 3*I,2)  # Q-matrix
Q[1:I,1] <- 1
Q[1:I + I,2] <- 1
Q[1:I + 2*I,1:2] <- 1
b <- matrix( stats::runif( 3*I *2, -2, 2 ), nrow=3*I, 2 )
b <- b*Q
b <- round( b, 2 )
mui <- rep(0,3*I)
mui[ seq(2*I+1, 3*I) ] <- 0.65
# generate data
dat <- matrix( NA, N, 3*I )
colnames(dat) <- paste0("It", 1:(3*I) )
# simulate item responses
library(mvtnorm)
theta <- mvtnorm::rmvnorm(N, mean=c(0,0), sigma=matrix( c( 1.2, .6,.6,1.6),2, 2 ) )
for (ii in 1:(3*I)){
    # define probability
    tmp1 <- exp( theta[,1] * Q[ii,1] - b[ii,1] +  theta[,2] * Q[ii,2] - b[ii,2] )
    # non-compensatory model
    nco1 <- ( 1 + exp( theta[,1] * Q[ii,1] - b[ii,1] ) ) *
```

```
                ( 1 + exp( theta[,2] * Q[ii,2] - b[ii,2] ) )
    co1 <- ( 1 + tmp1 )
    p1 <- tmp1 / ( mui[ii] * nco1 + ( 1 - mui[ii] )*co1 )
    dat[,ii] <- 1 * ( stats::runif(N) < p1 )
}

#*** Model 1: Joint mu.i parameter for all items
est.mu.i <- rep(0,3*I)
est.mu.i[ seq(2*I+1,3*I)] <- 1
mod1 <- sirt::smirt( dat, Qmatrix=Q, irtmodel="partcomp", est.mu.i=est.mu.i)
summary(mod1)

#*** Model 2: Separate mu.i parameter for all items
est.mu.i[ seq(2*I+1,3*I)] <- 1:I
mod2 <- sirt::smirt( dat, Qmatrix=Q, irtmodel="partcomp", est.mu.i=est.mu.i)
summary(mod2)

## End(Not run)
```

`stratified.cronbach.alpha`
Stratified Cronbach's Alpha

Description

This function computes the stratified Cronbach's Alpha for composite scales (Cronbach, Schoenemann & McKie, 1965; He, 2010; Meyer, 2010).

Usage

```
stratified.cronbach.alpha(data, itemstrata=NULL)
```

Arguments

`data`	An $N \times I$ data frame
`itemstrata`	A matrix with two columns defining the item stratification. The first column contains the item names, the second column the item stratification label (these can be integers). The default `NULL` does only compute Cronbach's Alpha for the whole scale.

References

Cronbach, L. J., Schoenemann, P., & McKie, D. (1965). Alpha coefficient for stratified-parallel tests. *Educational and Psychological Measurement, 25*, 291-312. doi:10.1177/001316446502500201

He, Q. (2010). *Estimating the reliability of composite scores*. Ofqual/10/4703. Coventry: The Office of Qualifications and Examinations Regulation.

Meyer, P. (2010). *Reliability*. Cambridge: Oxford University Press.

Examples

```
#############################################################################
# EXAMPLE 1: data.read
#############################################################################

data(data.read, package="sirt")
dat <- data.read
I <- ncol(dat)

# apply function without defining item strata
sirt::stratified.cronbach.alpha( data.read  )

# define item strata
itemstrata <- cbind( colnames(dat), substring( colnames(dat), 1,1 ) )
sirt::stratified.cronbach.alpha( dat, itemstrata=itemstrata )
  ##   scale  I alpha mean.tot var.tot alpha.stratified
  ## 1 total 12 0.677    8.680   5.668            0.703
  ## 2     A  4 0.545    2.616   1.381               NA
  ## 3     B  4 0.381    2.811   1.059               NA
  ## 4     C  4 0.640    3.253   1.107               NA

## Not run:
#**************************
# reliability analysis in psych package
library(psych)
# Cronbach's alpha and item discriminations
psych::alpha(dat)
# McDonald's omega
psych::omega(dat, nfactors=1)     # 1 factor
  ##   Alpha:                 0.69
  ##   Omega Total            0.69
##=> Note that alpha in this function is the standardized Cronbach's
##     alpha, i.e. alpha computed for standardized variables.
psych::omega(dat, nfactors=2)     # 2 factors
  ##   Omega Total            0.72
psych::omega(dat, nfactors=3)     # 3 factors
  ##   Omega Total            0.74

## End(Not run)
```

`summary.mcmc.sirt` *Summary Method for Objects of Class* `mcmc.sirt`

Description

S3 method to summarize objects of class `mcmc.sirt`. This object is generated by following functions: `mcmc.2pno`, `mcmc.2pnoh`, `mcmc.3pno.testlet`, `mcmc.2pno.ml`

Usage

```
## S3 method for class 'mcmc.sirt'
summary(object,digits=3, file=NULL, ...)
```

Arguments

object	Object of class mcmc.sirt
digits	Number of digits after decimal
file	Optional file name to which summary output is written
...	Further arguments to be passed

See Also

mcmc.2pno, mcmc.2pnoh, mcmc.3pno.testlet, mcmc.2pno.ml

---

tam2mirt *Converting a fitted* TAM *Object into a* mirt *Object*

Description

Converts a fitted TAM object into a mirt object. As a by-product, lavaan syntax is generated which can be used with lavaan2mirt for re-estimating the model in the **mirt** package. Up to now, only single group models are supported. There must not exist background covariates (no latent regression models!).

Usage

```
tam2mirt(tamobj)
```

Arguments

tamobj	Object of class TAM::tam.mml

Value

A list with following entries

mirt	Object generated by mirt function if est.mirt=TRUE
mirt.model	Generated mirt model
mirt.syntax	Generated mirt syntax
mirt.pars	Generated parameter specifications in mirt
lavaan.model	Used lavaan model transformed by lavaanify function
dat	Used dataset. If necessary, only items used in the model are included in the dataset.
lavaan.syntax.fixed	Generated lavaan syntax with fixed parameter estimates.
lavaan.syntax.freed	Generated lavaan syntax with freed parameters for estimation.

See Also

See `mirt.wrapper` for convenience wrapper functions for `mirt` objects.

See `lavaan2mirt` for converting `lavaan` syntax to `mirt` syntax.

Examples

```
## Not run:
library(TAM)
library(mirt)

#############################################################################
# EXAMPLE 1: Estimations in TAM for data.read dataset
#############################################################################

data(data.read)
dat <- data.read

#*************************************
#*** Model 1: Rasch model
#*************************************

# estimation in TAM package
mod <- TAM::tam.mml( dat )
summary(mod)
# conversion to mirt
res <- sirt::tam2mirt(mod)
# generated lavaan syntax
cat(res$lavaan.syntax.fixed)
cat(res$lavaan.syntax.freed)
# extract object of class mirt
mres <- res$mirt
# print and parameter values
print(mres)
mirt::mod2values(mres)
# model fit
mirt::M2(mres)
# residual statistics
mirt::residuals(mres, type="Q3")
mirt::residuals(mres, type="LD")
# item fit
mirt::itemfit(mres)
# person fit
mirt::personfit(mres)
# compute several types of factor scores (quite slow)
f1 <- mirt::fscores(mres, method='WLE',response.pattern=dat[1:10,])
     # method=MAP and EAP also possible
# item plot
mirt::itemplot(mres,"A3")    # item A3
mirt::itemplot(mres,4)       # fourth item
# some more plots
plot(mres,type="info")
plot(mres,type="score")
```

```
plot(mres,type="trace")
# compare estimates with estimated Rasch model in mirt
mres1 <- mirt::mirt(dat,1,"Rasch" )
print(mres1)
mirt.wrapper.coef(mres1)

#*************************************
#*** Model 2: 2PL model
#*************************************

# estimation in TAM
mod <- TAM::tam.mml.2pl( dat )
summary(mod)
# conversion to mirt
res <- sirt::tam2mirt(mod)
mres <- res$mirt
# lavaan syntax
cat(res$lavaan.syntax.fixed)
cat(res$lavaan.syntax.freed)
# parameter estimates
print(mres)
mod2values(mres)
mres@nest   # number of estimated parameters
# some plots
plot(mres,type="info")
plot(mres,type="score")
plot(mres,type="trace")
# model fit
mirt::M2(mres)
# residual statistics
mirt::residuals(mres, type="Q3")
mirt::residuals(mres, type="LD")
# item fit
mirt::itemfit(mres)

#*************************************
#*** Model 3: 3-dimensional Rasch model
#*************************************

# define Q-matrix
Q <- matrix( 0, nrow=12, ncol=3 )
Q[ cbind(1:12, rep(1:3,each=4) ) ] <- 1
rownames(Q) <- colnames(dat)
colnames(Q) <- c("A","B","C")
# estimation in TAM
mod <- TAM::tam.mml( resp=dat, Q=Q, control=list(snodes=1000,maxiter=30) )
summary(mod)
# mirt conversion
res <- sirt::tam2mirt(mod)
mres <- res$mirt
# mirt syntax
cat(res$mirt.syntax)
  ##   Dim01=1,2,3,4
```

```
  ##   Dim02=5,6,7,8
  ##   Dim03=9,10,11,12
  ##   COV=Dim01*Dim01,Dim02*Dim02,Dim03*Dim03,Dim01*Dim02,Dim01*Dim03,Dim02*Dim03
  ##   MEAN=Dim01,Dim02,Dim03
# lavaan syntax
cat(res$lavaan.syntax.freed)
  ##   Dim01=~ 1*A1+1*A2+1*A3+1*A4
  ##   Dim02=~ 1*B1+1*B2+1*B3+1*B4
  ##   Dim03=~ 1*C1+1*C2+1*C3+1*C4
  ##   A1 | t1_1*t1
  ##   A2 | t1_2*t1
  ##   A3 | t1_3*t1
  ##   A4 | t1_4*t1
  ##   B1 | t1_5*t1
  ##   B2 | t1_6*t1
  ##   B3 | t1_7*t1
  ##   B4 | t1_8*t1
  ##   C1 | t1_9*t1
  ##   C2 | t1_10*t1
  ##   C3 | t1_11*t1
  ##   C4 | t1_12*t1
  ##   Dim01 ~ 0*1
  ##   Dim02 ~ 0*1
  ##   Dim03 ~ 0*1
  ##   Dim01 ~~ Cov_11*Dim01
  ##   Dim02 ~~ Cov_22*Dim02
  ##   Dim03 ~~ Cov_33*Dim03
  ##   Dim01 ~~ Cov_12*Dim02
  ##   Dim01 ~~ Cov_13*Dim03
  ##   Dim02 ~~ Cov_23*Dim03
# model fit
mirt::M2(mres)
# residual statistics
residuals(mres,type="LD")
# item fit
mirt::itemfit(mres)

#************************************
#*** Model 4: 3-dimensional 2PL model
#************************************

# estimation in TAM
mod <- TAM::tam.mml.2pl( resp=dat, Q=Q, control=list(snodes=1000,maxiter=30) )
summary(mod)
# mirt conversion
res <- sirt::tam2mirt(mod)
mres <- res$mirt
# generated lavaan syntax
cat(res$lavaan.syntax.fixed)
cat(res$lavaan.syntax.freed)
# write lavaan syntax on disk
  sink( "mod4_lav_freed.txt", split=TRUE )
cat(res$lavaan.syntax.freed)
```

```
  sink()
# some statistics from mirt
print(mres)
summary(mres)
mirt::M2(mres)
mirt::residuals(mres)
mirt::itemfit(mres)

# estimate mirt model by using the generated lavaan syntax with freed parameters
res2 <- sirt::lavaan2mirt( dat, res$lavaan.syntax.freed,
            technical=list(NCYCLES=3), verbose=TRUE)
                 # use only few cycles for illustrational purposes
mirt.wrapper.coef(res2$mirt)
summary(res2$mirt)
print(res2$mirt)

#############################################################################
# EXAMPLE 4: mirt conversions for polytomous dataset data.big5
#############################################################################

data(data.big5)
# select some items
items <- c( grep( "O", colnames(data.big5), value=TRUE )[1:6],
     grep( "N", colnames(data.big5), value=TRUE )[1:4] )
# O3 O8 O13 O18 O23 O28 N1 N6 N11 N16
dat <- data.big5[, items ]
library(psych)
psych::describe(dat)

library(TAM)
#******************
#*** Model 1: Partial credit model in TAM
mod1 <- TAM::tam.mml( dat[,1:6] )
summary(mod1)
# convert to mirt object
mmod1 <- sirt::tam2mirt( mod1 )
rmod1 <- mmod1$mirt
# coefficients in mirt
coef(rmod1)
mirt.wrapper.coef(rmod1)
# model fit
mirt::M2(rmod1)
# item fit
mirt::itemfit(rmod1)
# plots
plot(rmod1,type="trace")
plot(rmod1, type="trace", which.items=1:4 )
mirt::itemplot(rmod1,"O3")

#******************
#*** Model 2: Generalized partial credit model in TAM
mod2 <- TAM::tam.mml.2pl( dat[,1:6], irtmodel="GPCM" )
summary(mod2)
```

```
# convert to mirt object
mmod2 <- sirt::tam2mirt( mod2 )
rmod2 <- mmod2$mirt
# coefficients in mirt
mirt.wrapper.coef(rmod2)
# model fit
mirt::M2(rmod2)
# item fit
mirt::itemfit(rmod2)

## End(Not run)
```

`testlet.marginalized` *Marginal Item Parameters from a Testlet (Bifactor) Model*

Description

This function computes marginal item parameters of a general factor if item parameters from a testlet (bifactor) model are provided as an input (see Details).

Usage

```
testlet.marginalized(tam.fa.obj=NULL,a1=NULL, d1=NULL, testlet=NULL,
      a.testlet=NULL, var.testlet=NULL)
```

Arguments

`tam.fa.obj`	Optional object of class `tam.fa` generated by `TAM::tam.fa` from the **TAM** package.
`a1`	Vector of item discriminations of general factor
`d1`	Vector of item intercepts of general factor
`testlet`	Integer vector of testlet (bifactor) identifiers (must be integers between 1 to T).
`a.testlet`	Vector of testlet (bifactor) item discriminations
`var.testlet`	Vector of testlet (bifactor) variances

Details

A testlet (bifactor) model is assumed to be estimated:

$$P(X_{pit}=1|\theta_p, u_{pt}) = invlogit(a_{i1}\theta_p + a_t u_{pt} - d_i)$$

with $Var(u_{pt}) = \sigma_t^2$. This multidimensional item response model with locally independent items is equivalent to a unidimensional IRT model with locally dependent items (Ip, 2010). Marginal item parameters a_i^* and d_i^* are obtained according to the response equation

$$P(X_{pit}=1|\theta_p^*) = invlogit(a_i^*\theta_p^* - d_i^*)$$

Calculation details can be found in Ip (2010).

Value

A data frame containing all input item parameters and marginal item intercept d_i^* (`d1_marg`) and marginal item slope a_i^* (`a1_marg`).

References

Ip, E. H. (2010). Empirically indistinguishable multidimensional IRT and locally dependent unidimensional item response models. *British Journal of Mathematical and Statistical Psychology, 63*, 395-416.

See Also

For estimating a testlet (bifactor) model see `TAM::tam.fa`.

Examples

```
#############################################################################
# EXAMPLE 1: Small numeric example for Rasch testlet model
#############################################################################

# Rasch testlet model with 9 items contained into 3 testlets
# the third testlet has essentially no dependence and therefore
# no testlet variance
testlet <- rep( 1:3, each=3 )
a1 <- rep(1, 9 )   # item slopes first dimension
d1 <- rep( c(-1.25,0,1.5), 3 ) # item intercepts
a.testlet <- rep( 1, 9 )  # item slopes testlets
var.testlet <- c( .8, .2, 0 )  # testlet variances

# apply function
res <- sirt::testlet.marginalized( a1=a1, d1=d1, testlet=testlet,
            a.testlet=a.testlet, var.testlet=var.testlet )
round( res, 2 )
  ##    item testlet a1    d1 a.testlet var.testlet a1_marg d1_marg
  ##  1    1       1  1 -1.25         1         0.8    0.89   -1.11
  ##  2    2       1  1  0.00         1         0.8    0.89    0.00
  ##  3    3       1  1  1.50         1         0.8    0.89    1.33
  ##  4    4       2  1 -1.25         1         0.2    0.97   -1.21
  ##  5    5       2  1  0.00         1         0.2    0.97    0.00
  ##  6    6       2  1  1.50         1         0.2    0.97    1.45
  ##  7    7       3  1 -1.25         1         0.0    1.00   -1.25
  ##  8    8       3  1  0.00         1         0.0    1.00    0.00
  ##  9    9       3  1  1.50         1         0.0    1.00    1.50

## Not run:
#############################################################################
# EXAMPLE 2: Dataset reading
#############################################################################

library(TAM)
data(data.read)
resp <- data.read
```

```
maxiter <-  100

# Model 1: Rasch testlet model with 3 testlets
dims <- substring( colnames(resp),1,1 )  # define dimensions
mod1 <- TAM::tam.fa( resp=resp, irtmodel="bifactor1", dims=dims,
               control=list(maxiter=maxiter) )
# marginal item parameters
res1 <- sirt::testlet.marginalized( mod1 )

#***
# Model 2: estimate bifactor model but assume that items 3 and 5 do not load on
#           specific factors
dims1 <- dims
dims1[c(3,5)] <- NA
mod2 <- TAM::tam.fa( resp=resp, irtmodel="bifactor2", dims=dims1,
              control=list(maxiter=maxiter) )
res2 <- sirt::testlet.marginalized( mod2 )
res2

## End(Not run)
```

`tetrachoric2` *Tetrachoric Correlation Matrix*

Description

This function estimates a tetrachoric correlation matrix according to the maximum likelihood estimation of Olsson (Olsson, 1979; `method="Ol"`), the Tucker method (Method 2 of Froemel, 1971; `method="Tu"`) and Divgi (1979, `method="Di"`). In addition, an alternative non-iterative approximation of Bonett and Price (2005; `method="Bo"`) is provided.

Usage

```
tetrachoric2(dat, method="Ol", delta=0.007, maxit=1000000, cor.smooth=TRUE,
   progress=TRUE)
```

Arguments

`dat`	A data frame of dichotomous response
`method`	Computation method for calculating the tetrachoric correlation. The ML method is `method="Ol"` (which is the default), the Tucker method is `method="Tu"`, the Divgi method is `method="Di"` the method of Bonett and Price (2005) is `method="Bo"`.
`delta`	The step parameter. It is set by default to 2^{-7} which is approximately .007.
`maxit`	Maximum number of iterations.
`cor.smooth`	Should smoothing of the tetrachoric correlation matrix be performed to ensure positive definiteness? Choosing `cor.smooth=TRUE`, the function `cor.smooth` from the **psych** package is used for obtaining a positive definite tetrachoric correlation matrix.

progress Display progress? Default is TRUE.

Value

A list with following entries

tau Item thresholds

rho Tetrachoric correlation matrix

Author(s)

Alexander Robitzsch

The code is adapted from an R script of Cengiz Zopluoglu. See *http://sites.education.miami.edu/zopluoglu/software-programs/*.

References

Bonett, D. G., & Price, R. M. (2005). Inferential methods for the tetrachoric correlation coefficient. *Journal of Educational and Behavioral Statistics, 30*(2), 213-225. doi:10.3102/10769986030002213

Divgi, D. R. (1979). Calculation of the tetrachoric correlation coefficient. *Psychometrika, 44*(2), 169-172. doi:10.1007/BF02293968

Froemel, E. C. (1971). A comparison of computer routines for the calculation of the tetrachoric correlation coefficient. *Psychometrika, 36*(2), 165-174. doi:10.1007/BF02291396

Olsson, U. (1979). Maximum likelihood estimation of the polychoric correlation coefficient. *Psychometrika, 44*(4), 443-460. doi:10.1007/BF02296207

See Also

See also the psych::tetrachoric function in the **psych** package and the function irtoys::tet in the **irtoys** package.

See polychoric2 for estimating polychoric correlations.

Examples

```
#############################################################################
# EXAMPLE 1: data.read
#############################################################################

data(data.read)

# tetrachoric correlation from psych package
library(psych)
t0 <- psych::tetrachoric( data.read )$rho
# Olsson method (maximum likelihood estimation)
t1 <- sirt::tetrachoric2( data.read )$rho
# Divgi method
t2 <- sirt::tetrachoric2( data.read, method="Di"  )$rho
# Tucker method
t3 <- sirt::tetrachoric2( data.read, method="Tu" )$rho
```

```
# Bonett method
t4 <- sirt::tetrachoric2( data.read, method="Bo" )$rho

# maximum absolute deviation ML method
max( abs( t0 - t1 ) )
  ##   [1] 0.008224986
# mean absolute deviation Divgi method
max( abs( t0 - t2 ) )
  ##   [1] 0.1766688
# mean absolute deviation Tucker method
max( abs( t0 - t3 ) )
  ##   [1] 0.1766292
# mean absolute deviation Bonett method
max( abs( t0 - t4 ) )
  ##   [1] 0.05695522
```

`truescore.irt` *Conversion of Trait Scores θ into True Scores $\tau(\theta)$*

Description

This function computes the true score $\tau = \tau(\theta) = \sum_{i=1}^{I} P_i(\theta)$ in a unidimensional item response model with I items. In addition, it also transforms conditional standard errors if they are provided.

Usage

```
truescore.irt(A, B, c=NULL, d=NULL, theta=seq(-3, 3, len=21),
    error=NULL, pid=NULL, h=0.001)
```

Arguments

`A`	Matrix or vector of item slopes. See Examples for polytomous responses.
`B`	Matrix or vector of item intercepts. Note that the entries in `B` refer to item intercepts and not to item difficulties.
`c`	Optional vector of guessing parameters
`d`	Optional vector of slipping parameters
`theta`	Vector of trait values
`error`	Optional vector of standard errors of trait
`pid`	Optional vector of person identifiers
`h`	Numerical differentiation parameter

Details

In addition, the function $\pi(\theta) = \frac{1}{I} \cdot \tau(\theta)$ of the expected percent score is approximated by a logistic function

$$\pi(\theta) \approx l + (u - l) \cdot invlogit(a\theta + b)$$

Value

A data frame with following columns:

`truescore`	True scores $\tau = \tau(\theta)$
`truescore.error`	Standard errors of true scores
`percscore`	Expected correct scores which is τ divided by the maximum true score
`percscore.error`	Standard errors of expected correct scores
`lower`	The l parameter
`upper`	The u parameter
`a`	The a parameter
`b`	The b parameter

Examples

```
#############################################################################
# EXAMPLE 1: Dataset with mixed dichotomous and polytomous responses
#############################################################################

data(data.mixed1)
dat <- data.mixed1

#****
# Model 1: Partial credit model
# estimate model with TAM package
library(TAM)
mod1 <- TAM::tam.mml( dat )
# estimate person parameter estimates
wmod1 <- TAM::tam.wle( mod1 )
wmod1 <- wmod1[ order(wmod1$theta), ]
# extract item parameters
A <- mod1$B[,-1,1]
B <- mod1$AXsi[,-1]
# person parameters and standard errors
theta <- wmod1$theta
error <- wmod1$error

# estimate true score transformation
dfr <- sirt::truescore.irt( A=A, B=B, theta=theta, error=error )

# plot different person parameter estimates and standard errors
par(mfrow=c(2,2))
plot( theta, dfr$truescore, pch=16, cex=.6, xlab=expression(theta), type="l",
    ylab=expression(paste( tau, "(",theta, ")" )), main="True Score Transformation" )
plot( theta, dfr$percscore, pch=16, cex=.6, xlab=expression(theta), type="l",
    ylab=expression(paste( pi, "(",theta, ")" )), main="Percent Score Transformation" )
points( theta, dfr$lower + (dfr$upper-dfr$lower)*
                stats::plogis(dfr$a*theta+dfr$b), col=2, lty=2)
plot( theta, error, pch=16, cex=.6, xlab=expression(theta), type="l",
```

```
    ylab=expression(paste("SE(",theta, ")" )), main="Standard Error Theta" )
plot( dfr$truescore, dfr$truescore.error, pch=16, cex=.6, xlab=expression(tau),
    ylab=expression(paste("SE(",tau, ")" ) ), main="Standard Error True Score Tau",
    type="l")
par(mfrow=c(1,1))

## Not run:
#****
# Model 2: Generalized partial credit model
mod2 <- TAM::tam.mml.2pl( dat, irtmodel="GPCM")
# estimate person parameter estimates
wmod2 <- TAM::tam.wle( mod2 )
# extract item parameters
A <- mod2$B[,-1,1]
B <- mod2$AXsi[,-1]
# person parameters and standard errors
theta <- wmod2$theta
error <- wmod2$error
# estimate true score transformation
dfr <- sirt::truescore.irt( A=A, B=B, theta=theta, error=error )

############################################################################
# EXAMPLE 2: Dataset Reading data.read
############################################################################
data(data.read)

#****
# Model 1: estimate difficulty + guessing model
mod1 <- sirt::rasch.mml2( data.read, fixed.c=rep(.25,12) )
mod1$person <- mod1$person[ order( mod1$person$EAP), ]
# person parameters and standard errors
theta <- mod1$person$EAP
error <- mod1$person$SE.EAP
A <- rep(1,12)
B <- - mod1$item$b
c <- rep(.25,12)
# estimate true score transformation
dfr <- sirt::truescore.irt( A=A, B=B, theta=theta, error=error,c=c)

plot( theta, dfr$percscore, pch=16, cex=.6, xlab=expression(theta), type="l",
    ylab=expression(paste( pi, "(",theta, ")" )), main="Percent Score Transformation" )
points( theta, dfr$lower + (dfr$upper-dfr$lower)*
            stats::plogis(dfr$a*theta+dfr$b), col=2, lty=2)

#****
# Model 2: Rasch model
mod2 <- sirt::rasch.mml2( data.read  )
# person parameters and standard errors
theta <- mod2$person$EAP
error <- mod2$person$SE.EAP
A <- rep(1,12)
B <- - mod2$item$b
# estimate true score transformation
```

```
dfr <- sirt::truescore.irt( A=A, B=B, theta=theta, error=error )

## End(Not run)
```

`unidim.test.csn` *Test for Unidimensionality of CSN*

Description

This function tests whether item covariances given the sum score are non-positive (CSN; see Junker 1993), i.e. for items i and j it holds that

$$Cov(X_i, X_j|X^+) \leq 0$$

Note that this function only works for dichotomous data.

Usage

```
unidim.test.csn(dat, RR=400, prop.perm=0.75, progress=TRUE)
```

Arguments

`dat`	Data frame with dichotomous item responses. All persons with (some) missing responses are removed.
`RR`	Number of permutations used for statistical testing
`prop.perm`	A positive value indicating the amount of permutation in an existing permuted data set
`progress`	An optional logical indicating whether computation progress should be displayed

Details

For each item pair (i, j) and a each sum score group k a conditional covariance $r(i, j|k)$ is calculated. Then, the test statistic for CSN is

$$h = \sum_{k=1}^{I-1} \frac{n_k}{n} \max_{i,j} r(i, j|k)$$

where n_k is the number of persons in score group k. "'Large values"' of h are not in agreement with the null hypothesis of non-positivity of conditional covariances.

The distribution of the test statistic h under the null hypothesis is empirically obtained by column wise permutation of items within all score groups. In the population, this procedure corresponds to conditional covariances of zero. See de Gooijer and Yuan (2011) for more details.

Value

A list with following entries

`stat`	Value of the statistic
`stat_perm`	Distribution of statistic under H_0 of permuted dataset
`p`	The corresponding p value of the statistic
`H0_quantiles`	Quantiles of the statistic under permutation (the null hypothesis H_0)

References

De Gooijer, J. G., & Yuan, A. (2011). Some exact tests for manifest properties of latent trait models. *Computational Statistics and Data Analysis, 55*, 34-44.

Junker, B.W. (1993). Conditional association, essential independence, and monotone unidimensional item response models. *Annals of Statistics, 21*, 1359-1378.

Examples

```
#############################################################################
# EXAMPLE 1: Dataset data.read
#############################################################################

data(data.read)
dat <- data.read
set.seed(778)
res <- sirt::unidim.test.csn( dat )
  ##  CSN Statistic=0.04737, p=0.02

## Not run:
#############################################################################
# EXAMPLE 2: CSN statistic for two-dimensional simulated data
#############################################################################

set.seed(775)
N <- 2000
I <- 30   # number of items
rho <- .60   # correlation between 2 dimensions
t0 <- stats::rnorm(N)
t1 <- sqrt(rho)*t0 + sqrt(1-rho)*stats::rnorm(N)
t2 <- sqrt(rho)*t0 + sqrt(1-rho)*stats::rnorm(N)
dat1 <- sirt::sim.raschtype(t1, b=seq(-1.5,1.5,length=I/2) )
dat2 <- sirt::sim.raschtype(t2, b=seq(-1.5,1.5,length=I/2) )
dat <- as.matrix(cbind( dat1, dat2) )
res <- sirt::unidim.test.csn( dat )
  ##  CSN Statistic=0.06056, p=0.02

## End(Not run)
```

wle.rasch *Weighted Likelihood Estimation of Person Abilities*

Description

This function computes weighted likelihood estimates for dichotomous responses based on the Rasch model (Warm, 1989).

Usage

```
wle.rasch(dat, dat.resp=NULL, b, itemweights=1 + 0 * b,
    theta=rep(0, nrow(dat)), conv=0.001, maxit=200,
    wle.adj=0, progress=FALSE)
```

Arguments

dat	An $N \times I$ data frame of dichotomous item responses
dat.resp	Optional data frame with dichotomous response indicators
b	Vector of length I with fixed item difficulties
itemweights	Optional vector of fixed item discriminations
theta	Optional vector of initial person parameter estimates
conv	Convergence criterion
maxit	Maximal number of iterations
wle.adj	Constant for WLE adjustment
progress	Display progress?

Value

A list with following entries

theta	Estimated weighted likelihood estimate
dat.resp	Data frame with dichotomous response indicators. A one indicates an observed response, a zero a missing response. See also dat.resp in the list of arguments of this function.
p.ia	Matrix with expected item response, i.e. the probabilities $P(X_{pi} = 1 \vert \theta_p) = invlogit(\theta_p - b_i)$.
wle	WLE reliability (Adams, 2005)

References

Adams, R. J. (2005). Reliability as a measurement design effect. *Studies in Educational Evaluation, 31*, 162-172.

Warm, T. A. (1989). Weighted likelihood estimation of ability in item response theory. *Psychometrika, 54*, 427-450.

See Also

For standard errors of weighted likelihood estimates estimated via jackknife see `wle.rasch.jackknife`.

For a joint estimation of item and person parameters see the joint maximum likelihood estimation method in `rasch.jml`.

Examples

```
#############################################################################
# EXAMPLE 1: Dataset Reading
#############################################################################
data(data.read)

# estimate the Rasch model
mod <- sirt::rasch.mml2(data.read)
mod$item

# estmate WLEs
mod.wle <- sirt::wle.rasch( dat=data.read, b=mod$item$b )
```

`wle.rasch.jackknife` *Standard Error Estimation of WLE by Jackknifing*

Description

This function calculates standard errors of WLEs (Warm, 1989) for stratified item designs and item designs with testlets for the Rasch model.

Usage

```
wle.rasch.jackknife(dat, b, itemweights=1 + 0 * b, pid=NULL,
    testlet=NULL, stratum=NULL, size.itempop=NULL)
```

Arguments

`dat`	An $N \times I$ data frame of item responses
`b`	Vector of item difficulties
`itemweights`	Weights for items, i.e. fixed item discriminations
`pid`	Person identifier
`testlet`	A vector of length I which defines which item belongs to which testlet. If some items does not belong to any testlet, then define separate testlet labels for these single items.
`stratum`	Item stratum
`size.itempop`	Number of items in an item stratum of the finite item population.

Details

The idea of Jackknife in item response models can be found in Wainer and Wright (1980).

Value

A list with following entries:

`wle`	Data frame with some estimated statistics. The column `wle` is the WLE and `wle.jackse` its corresponding standard error estimated by jackknife.
`wle.rel`	WLE reliability (Adams, 2005)

References

Adams, R. J. (2005). Reliability as a measurement design effect. *Studies in Educational Evaluation, 31*(2-3), 162-172. doi:10.1016/j.stueduc.2005.05.008

Gershunskaya, J., Jiang, J., & Lahiri, P. (2009). Resampling methods in surveys. In D. Pfeffermann and C.R. Rao (Eds.). *Handbook of Statistics 29B; Sample Surveys: Inference and Analysis* (pp. 121-151). Amsterdam: North Holland. doi:10.1016/S01697161(09)002284

Wainer, H., & Wright, B. D. (1980). Robust estimation of ability in the Rasch model. *Psychometrika, 45*(3), 373-391. doi:10.1007/BF02293910

Warm, T. A. (1989). Weighted likelihood estimation of ability in item response theory. *Psychometrika, 54*(3), 427-450. doi:10.1007/BF02294627

See Also

`wle.rasch`

Examples

```
#############################################################################
# EXAMPLE 1: Dataset Reading
#############################################################################
data(data.read)
dat <- data.read

# estimation of the Rasch model
res <- sirt::rasch.mml2( dat, parm.conv=.001)

# WLE estimation
wle1 <- sirt::wle.rasch(dat, b=res$item$thresh )

# simple jackknife WLE estimation
wle2 <- sirt::wle.rasch.jackknife(dat, b=res$item$thresh )
  ## WLE Reliability=0.651

# SE(WLE) for testlets A, B and C
wle3 <- sirt::wle.rasch.jackknife(dat, b=res$item$thresh,
           testlet=substring( colnames(dat),1,1) )
  ## WLE Reliability=0.572

# SE(WLE) for item strata A,B, C
wle4 <- sirt::wle.rasch.jackknife(dat, b=res$item$thresh,
             stratum=substring( colnames(dat),1,1) )
  ## WLE Reliability=0.683
```

```
# SE (WLE) for finite item strata
# A (10 items), B (7 items), C (4 items -> no sampling error)
# in every stratum 4 items were sampled
size.itempop <- c(10,7,4)
names(size.itempop) <- c("A","B","C")
wle5 <- sirt::wle.rasch.jackknife(dat, b=res$item$thresh,
             stratum=substring( colnames(dat),1,1),
             size.itempop=size.itempop )
  ## Stratum  A (Mean) Correction Factor 0.6
  ## Stratum  B (Mean) Correction Factor 0.42857
  ## Stratum  C (Mean) Correction Factor 0
  ## WLE Reliability=0.876

# compare different estimated standard errors
a2 <- stats::aggregate( wle2$wle$wle.jackse, list( wle2$wle$wle), mean )
colnames(a2) <- c("wle", "se.simple")
a2$se.testlet <- stats::aggregate( wle3$wle$wle.jackse, list( wle3$wle$wle), mean )[,2]
a2$se.strata <- stats::aggregate( wle4$wle$wle.jackse, list( wle4$wle$wle), mean )[,2]
a2$se.finitepop.strata <- stats::aggregate( wle5$wle$wle.jackse,
    list( wle5$wle$wle), mean )[,2]
round( a2, 3 )
  ## > round( a2, 3 )
  ##       wle se.simple se.testlet se.strata se.finitepop.strata
  ## 1  -5.085     0.440      0.649     0.331               0.138
  ## 2  -3.114     0.865      1.519     0.632               0.379
  ## 3  -2.585     0.790      0.849     0.751               0.495
  ## 4  -2.133     0.715      1.177     0.546               0.319
  ## 5  -1.721     0.597      0.767     0.527               0.317
  ## 6  -1.330     0.633      0.623     0.617               0.377
  ## 7  -0.942     0.631      0.643     0.604               0.365
  ## 8  -0.541     0.655      0.678     0.617               0.384
  ## 9  -0.104     0.671      0.646     0.659               0.434
  ## 10  0.406     0.771      0.706     0.751               0.461
  ## 11  1.080     1.118      0.893     1.076               0.630
  ## 12  2.332     0.400      0.631     0.272               0.195
```

`xxirt` *User Defined Item Response Model*

Description

Estimates a user defined item response model. Both, item response functions and latent trait distributions can be specified by the user (see Details). By default, the EM algorithm is used for estimation. The number of maximum EM iterations can be defined with the argument `maxit`. The `xxirt` function also allows Newton-Raphson optimization by specifying values of maximum number of iterations in `maxit_nr` larger than zero. Typically, a small initial number of EM iterations should be chosen to obtain reasonable starting values.

Usage

```
xxirt(dat, Theta=NULL, itemtype=NULL, customItems=NULL, partable=NULL,
       customTheta=NULL, group=NULL, weights=NULL, globconv=1e-06, conv=1e-04,
     maxit=1000, mstep_iter=4, mstep_reltol=1e-06, maxit_nr=0, optimizer_nr="nlminb",
     estimator="ML", control_nr=list(trace=1), h=1E-4, use_grad=TRUE, verbose=TRUE,
       penalty_fun_item=NULL, np_fun_item=NULL, penalty_fun_theta=NULL,
       np_fun_theta=NULL, pml_args=NULL, verbose_index=NULL,
       cv_kfold=0, cv_maxit=10)

## S3 method for class 'xxirt'
summary(object, digits=3, file=NULL, ...)

## S3 method for class 'xxirt'
print(x, ...)

## S3 method for class 'xxirt'
anova(object,...)

## S3 method for class 'xxirt'
coef(object,...)

## S3 method for class 'xxirt'
logLik(object,...)

## S3 method for class 'xxirt'
vcov(object,...)

## S3 method for class 'xxirt'
confint(object, parm, level=.95, ... )

## S3 method for class 'xxirt'
IRT.expectedCounts(object,...)

## S3 method for class 'xxirt'
IRT.factor.scores(object, type="EAP", ...)

## S3 method for class 'xxirt'
IRT.irfprob(object,...)

## S3 method for class 'xxirt'
IRT.likelihood(object,...)

## S3 method for class 'xxirt'
IRT.posterior(object,...)

## S3 method for class 'xxirt'
IRT.modelfit(object,...)
```

```
## S3 method for class 'IRT.modelfit.xxirt'
summary(object,...)

## S3 method for class 'xxirt'
IRT.se(object,...)

# computes Hessian matrix
xxirt_hessian(object, h=1e-4, use_shortcut=TRUE)

#- sandwich estimate for pairwise maximum likelihood estimation
xxirt_sandwich_pml(object, h=1e-4)
```

Arguments

dat	Data frame with item responses
Theta	Matrix with θ grid vector of latent trait
itemtype	Vector of item types
customItems	List containing types of item response functions created by xxirt_createDiscItem.
partable	Item parameter table which is initially created by xxirt_createParTable and which can be modified by xxirt_modifyParTable.
customTheta	User defined θ distribution created by xxirt_createThetaDistribution.
group	Optional vector of group indicators
weights	Optional vector of person weights
globconv	Convergence criterion for relative change in deviance
conv	Convergence criterion for absolute change in parameters
maxit	Maximum number of iterations in the EM algorithm
mstep_iter	Maximum number of iterations in M-step
mstep_reltol	Convergence criterion in M-step
maxit_nr	Number of Newton-Raphson iterations after EM algorithm
optimizer_nr	Type of optimizer for Newton-Raphson optimization. Alternatives are "optim" or "nlminb" or other options of sirt_optimizer.
estimator	Marginal maximum likelihood ("ML") or pairwise maximum likelihood ("PML")
control_nr	Argument control for optimizer.
h	Numerical differentiation parameter
use_grad	Logical indicating whether the gradient should be supplied to stats::optim
verbose	Logical indicating whether iteration progress should be displayed
penalty_fun_item	Optional penalty function used in regularized estimation. Used as a function of x (vector of item parameters)
np_fun_item	Function that counts the number of item parameters in regularized estimation. Used as a function of x (vector of item parameters)

penalty_fun_theta	Optional penalty function used in regularized estimation. Used as a function of x (vector of theta parameters)
np_fun_theta	Function that counts the number of theta parameters in regularized estimation. Used as a function of x (vector of theta parameters)
object	Object of class xxirt
digits	Number of digits to be rounded
file	Optional file name to which summary output is written
parm	Optional vector of parameters
level	Confidence level
pml_args	Weight matrices for estimator="PML"
verbose_index	Logical indicating whether item index should be printed in estimation output
cv_kfold	Number of k folds in cross validation. The default is 0 (no cross-validation)
cv_maxit	Maximum number of iterations for each cross-validation sample
x	Object of class xxirt
type	Type of person parameter estimate. Currently, only EAP is implemented.
use_shortcut	Logical indicating whether a shortcut in the computation should be utilized
...	Further arguments to be passed

Details

Item response functions can be specified as functions of unknown parameters $\boldsymbol{\delta}_i$ such that $P(X_i = x|\boldsymbol{\theta}) = f_i(x|\boldsymbol{\theta};\boldsymbol{\delta}_i)$ The item response model is estimated under the assumption of local stochastic independence of items. Equality constraints of item parameters $\boldsymbol{\delta}_i$ among items are allowed.

The probability distribution $P(\boldsymbol{\theta})$ are specified as functions of an unknown parameter vector $\boldsymbol{\gamma}$.

A penalty function for item parameters can be specified in penalty_fun_item. The penalty function should be differentiable and a non-differentiable function (e.g., the absolute value function) should be approximated by a differentiable function.

Value

List with following entries

partable	Item parameter table
par_items	Vector with estimated item parameters
par_items_summary	Data frame with item parameters
par_items_bounds	Data frame with summary on bounds of estimated item parameters
par_Theta	Vector with estimated parameters of theta distribution
Theta	Matrix with $\boldsymbol{\theta}$ grid
probs_items	Item response functions

probs_Theta	Theta distribution
deviance	Deviance
loglik	Log likelihood value
ic	Information criteria
item_list	List with item functions
customItems	Used customized item response functions
customTheta	Used customized theta distribution
cv_loglike	Cross-validated log-likelihood value (if cv_kfold>0)
p.xi.aj	Individual likelihood
p.aj.xi	Individual posterior
ll_case	Case-wise log-likelihood values
n.ik	Array of expected counts
EAP	EAP person parameter estimates
dat	Used dataset with item responses
dat_resp	Dataset with response indicators
weights	Vector of person weights
G	Number of groups
group	Integer vector of group indicators
group_orig	Vector of original group_identifiers
ncat	Number of categories per item
converged	Logical whether model has converged
iter	Number of iterations needed

See Also

See the mirt::createItem and mirt::mirt functions in the **mirt** package for similar functionality.

Examples

```
## Not run:
#############################################################################
## EXAMPLE 1: Unidimensional item response functions
#############################################################################

data(data.read)
dat <- data.read

#------ Definition of item response functions

#*** IRF 2PL
P_2PL <- function( par, Theta, ncat){
    a <- par[1]
    b <- par[2]
    TP <- nrow(Theta)
```

```
    P <- matrix( NA, nrow=TP, ncol=ncat)
    P[,1] <- 1
    for (cc in 2:ncat){
        P[,cc] <- exp( (cc-1) * a * Theta[,1] - b )
    }
    P <- P / rowSums(P)
    return(P)
}

#*** IRF 1PL
P_1PL <- function( par, Theta, ncat){
    b <- par[1]
    TP <- nrow(Theta)
    P <- matrix( NA, nrow=TP, ncol=ncat)
    P[,1] <- 1
    for (cc in 2:ncat){
        P[,cc] <- exp( (cc-1) * Theta[,1] - b )
    }
    P <- P / rowSums(P)
    return(P)
}

#** created item classes of 1PL and 2PL models
par <- c( "a"=1, "b"=0 )
# define some slightly informative prior of 2PL
item_2PL <- sirt::xxirt_createDiscItem( name="2PL", par=par, est=c(TRUE,TRUE),
               P=P_2PL, prior=c(a="dlnorm"), prior_par1=c( a=0 ),
               prior_par2=c(a=5) )
item_1PL <- sirt::xxirt_createDiscItem( name="1PL", par=par[2], est=c(TRUE),
               P=P_1PL )
customItems <- list( item_1PL,  item_2PL )

#---- definition theta distribution

#** theta grid
Theta <- matrix( seq(-6,6,length=21), ncol=1 )

#** theta distribution
P_Theta1 <- function( par, Theta, G){
    mu <- par[1]
    sigma <- max( par[2], .01 )
    TP <- nrow(Theta)
    pi_Theta <- matrix( 0, nrow=TP, ncol=G)
    pi1 <- dnorm( Theta[,1], mean=mu, sd=sigma )
    pi1 <- pi1 / sum(pi1)
    pi_Theta[,1] <- pi1
    return(pi_Theta)
}
#** create distribution class
par_Theta <- c( "mu"=0, "sigma"=1 )
customTheta  <- sirt::xxirt_createThetaDistribution( par=par_Theta, est=c(FALSE,TRUE),
                     P=P_Theta1 )
```

```
#*****************************************************************************
#******* Model 1: Rasch model

#-- create parameter table
itemtype <- rep( "1PL", 12 )
partable <- sirt::xxirt_createParTable( dat, itemtype=itemtype,
                        customItems=customItems )

# estimate model
mod1 <- sirt::xxirt( dat=dat, Theta=Theta, partable=partable,
                  customItems=customItems, customTheta=customTheta)
summary(mod1)

# estimate Rasch model by providing starting values
partable1 <- sirt::xxirt_modifyParTable( partable, parname="b",
                  value=- stats::qlogis( colMeans(dat) ) )
# estimate model again
mod1b <- sirt::xxirt( dat=dat, Theta=Theta, partable=partable1,
                  customItems=customItems, customTheta=customTheta )
summary(mod1b)

# extract coefficients, covariance matrix and standard errors
coef(mod1b)
vcov(mod1b)
IRT.se(mod1b)

#** start with EM and finalize with Newton-Raphson algorithm
mod1c <- sirt::xxirt( dat=dat, Theta=Theta, partable=partable,
                  customItems=customItems, customTheta=customTheta,
                  maxit=20, maxit_nr=300)
summary(mod1c)

#*****************************************************************************
#******* Model 2: 2PL Model with three groups of item discriminations

#-- create parameter table
itemtype <- rep( "2PL", 12 )
partable <- sirt::xxirt_createParTable( dat, itemtype=itemtype, customItems=customItems)
# modify parameter table: set constraints for item groups A, B and C
partable1 <- sirt::xxirt_modifyParTable(partable, item=paste0("A",1:4),
                        parname="a", parindex=111)
partable1 <- sirt::xxirt_modifyParTable(partable1, item=paste0("B",1:4),
                        parname="a", parindex=112)
partable1 <- sirt::xxirt_modifyParTable(partable1, item=paste0("C",1:4),
                        parname="a", parindex=113)
# delete prior distributions
partable1 <- sirt::xxirt_modifyParTable(partable1, parname="a", prior=NA)

#-- fix sigma to 1
customTheta1 <- customTheta
customTheta1$est <- c("mu"=FALSE,"sigma"=FALSE )

# estimate model
```

```
mod2 <- sirt::xxirt( dat=dat, Theta=Theta, partable=partable1,
                  customItems=customItems, customTheta=customTheta1 )
summary(mod2)

#*****************************************************************************
#******* Model 3: Cloglog link function

#*** IRF cloglog
P_1N <- function( par, Theta, ncat){
    b <- par
    TP <- nrow(Theta)
    P <- matrix( NA, nrow=TP, ncol=ncat)
    P[,2] <- 1 - exp( - exp( Theta - b ) )
    P[,1] <- 1 - P[,2]
    return(P)
}
par <- c("b"=0)
item_1N <- sirt::xxirt_createDiscItem( name="1N", par=par, est=c(TRUE),
                    P=P_1N )
customItems <- list( item_1N )
itemtype <- rep( "1N", I )
partable <- sirt::xxirt_createParTable( dat[,items], itemtype=itemtype,
                     customItems=customItems )
partable <- sirt::xxirt_modifyParTable( partable=partable, parname="b",
                 value=- stats::qnorm( colMeans(dat[,items] )) )

#*** estimate model
mod3 <- sirt::xxirt( dat=dat, Theta=Theta, partable=partable, customItems=customItems,
                customTheta=customTheta )
summary(mod3)
IRT.compareModels(mod1,mod3)

#*****************************************************************************
#******* Model 4: Latent class model

K <- 3 # number of classes
Theta <- diag(K)

#*** Theta distribution
P_Theta1 <- function( par, Theta, G  ){
    logitprobs <- par[1:(K-1)]
    l1 <- exp( c( logitprobs, 0 ) )
    probs <- matrix( l1/sum(l1), ncol=1)
    return(probs)
}

par_Theta <- stats::qlogis( rep( 1/K, K-1 ) )
names(par_Theta) <- paste0("pi",1:(K-1) )
customTheta  <- sirt::xxirt_createThetaDistribution( par=par_Theta,
                     est=rep(TRUE,K-1), P=P_Theta1)

#*** IRF latent class
P_lc <- function( par, Theta, ncat){
```

```
    b <- par
    TP <- nrow(Theta)
    P <- matrix( NA, nrow=TP, ncol=ncat)
    P[,1] <- 1
    for (cc in 2:ncat){
        P[,cc] <- exp( Theta %*% b )
    }
    P <- P / rowSums(P)
    return(P)
}
par <- seq( -1.5, 1.5, length=K )
names(par) <- paste0("b",1:K)
item_lc <- sirt::xxirt_createDiscItem( name="LC", par=par,
                est=rep(TRUE,K), P=P_lc )
customItems <- list( item_lc )

# create parameter table
itemtype <- rep( "LC", 12 )
partable <- sirt::xxirt_createParTable( dat, itemtype=itemtype, customItems=customItems)
partable

#*** estimate model
mod4 <- sirt::xxirt( dat=dat, Theta=Theta, partable=partable, customItems=customItems,
              customTheta=customTheta)
summary(mod4)
# class probabilities
mod4$probs_Theta
# item response functions
imod4 <- IRT.irfprob( mod5 )
round( imod4[,2,], 3 )

#############################################################################
#******* Model 5: Ordered latent class model

K <- 3 # number of classes
Theta <- diag(K)
Theta <- apply( Theta, 1, cumsum )

#*** Theta distribution
P_Theta1 <- function( par, Theta, G  ){
    logitprobs <- par[1:(K-1)]
    l1 <- exp( c( logitprobs, 0 ) )
    probs <- matrix( l1/sum(l1), ncol=1)
    return(probs)
}
par_Theta <- stats::qlogis( rep( 1/K, K-1 ) )
names(par_Theta) <- paste0("pi",1:(K-1) )
customTheta  <- sirt::xxirt_createThetaDistribution( par=par_Theta,
                est=rep(TRUE,K-1), P=P_Theta1  )

#*** IRF ordered latent class
P_olc <- function( par, Theta, ncat){
    b <- par
```

```
    TP <- nrow(Theta)
    P <- matrix( NA, nrow=TP, ncol=ncat)
    P[,1] <- 1
    for (cc in 2:ncat){
        P[,cc] <- exp( Theta %*% b )
    }
    P <- P / rowSums(P)
    return(P)
}

par <- c( -1, rep( .5,, length=K-1 ) )
names(par) <- paste0("b",1:K)
item_olc <- sirt::xxirt_createDiscItem( name="OLC", par=par, est=rep(TRUE,K),
                    P=P_olc, lower=c( -Inf, 0, 0 ) )
customItems <- list( item_olc )
itemtype <- rep( "OLC", 12 )
partable <- sirt::xxirt_createParTable( dat, itemtype=itemtype, customItems=customItems)
partable

#*** estimate model
mod5 <- sirt::xxirt( dat=dat, Theta=Theta, partable=partable, customItems=customItems,
               customTheta=customTheta )
summary(mod5)
# estimated item response functions
imod5 <- IRT.irfprob( mod5 )
round( imod5[,2,], 3 )

############################################################################
## EXAMPLE 2: Multiple group models with xxirt
############################################################################

data(data.math)
dat <- data.math$data
items <- grep( "M[A-Z]", colnames(dat), value=TRUE )
I <- length(items)

Theta <- matrix( seq(-8,8,len=31), ncol=1 )

#*************************************************************************
#******* Model 1: Rasch model, single group

#*** Theta distribution
P_Theta1 <- function( par, Theta, G  ){
    mu <- par[1]
    sigma <- max( par[2], .01 )
    p1 <- stats::dnorm( Theta[,1], mean=mu, sd=sigma)
    p1 <- p1 / sum(p1)
    probs <- matrix( p1, ncol=1)
    return(probs)
}

par_Theta <- c(0,1)
names(par_Theta) <- c("mu","sigma")
```

```
customTheta  <- sirt::xxirt_createThetaDistribution( par=par_Theta,
                  est=c(FALSE,TRUE), P=P_Theta1  )
customTheta

#*** IRF 1PL logit
P_1PL <- function( par, Theta, ncat){
    b <- par
    TP <- nrow(Theta)
    P <- matrix( NA, nrow=TP, ncol=ncat)
    P[,2] <- plogis( Theta - b )
    P[,1] <- 1 - P[,2]
    return(P)
}
par <- c("b"=0)
item_1PL <- sirt::xxirt_createDiscItem( name="1PL", par=par, est=c(TRUE), P=P_1PL)
customItems <- list( item_1PL )

itemtype <- rep( "1PL", I )
partable <- sirt::xxirt_createParTable( dat[,items], itemtype=itemtype,
                      customItems=customItems )
partable <- sirt::xxirt_modifyParTable( partable=partable, parname="b",
                  value=- stats::qlogis( colMeans(dat[,items] )) )

#*** estimate model
mod1 <- sirt::xxirt( dat=dat[,items], Theta=Theta, partable=partable,
                customItems=customItems, customTheta=customTheta )
summary(mod1)

#############################################################################
#******* Model 2: Rasch model, multiple groups

#*** Theta distribution
P_Theta2 <- function( par, Theta, G  ){
    mu1 <- par[1]
    mu2 <- par[2]
    sigma1 <- max( par[3], .01 )
    sigma2 <- max( par[4], .01 )
    TP <- nrow(Theta)
    probs <- matrix( NA, nrow=TP, ncol=G)
    p1 <- stats::dnorm( Theta[,1], mean=mu1, sd=sigma1)
    probs[,1] <- p1 / sum(p1)
    p1 <- stats::dnorm( Theta[,1], mean=mu2, sd=sigma2)
    probs[,2] <- p1 / sum(p1)
    return(probs)
}
par_Theta <- c(0,0,1,1)
names(par_Theta) <- c("mu1","mu2","sigma1","sigma2")
customTheta2  <- sirt::xxirt_createThetaDistribution( par=par_Theta,
                    est=c(FALSE,TRUE,TRUE,TRUE), P=P_Theta2  )
print(customTheta2)

#*** estimate model
mod2 <- sirt::xxirt( dat=dat[,items], group=dat$female, Theta=Theta, partable=partable,
```

```
          customItems=customItems, customTheta=customTheta2, maxit=40)
summary(mod2)
IRT.compareModels(mod1, mod2)

#*** compare results with TAM package
library(TAM)
mod2b <- TAM::tam.mml( resp=dat[,items], group=dat$female )
summary(mod2b)
IRT.compareModels(mod1, mod2, mod2b)

#############################################################################
## EXAMPLE 3: Regularized 2PL model
#############################################################################

data(data.read, package="sirt")
dat <- data.read

#------ Definition of item response functions

#*** IRF 2PL
P_2PL <- function( par, Theta, ncat){
    a <- par[1]
    b <- par[2]
    TP <- nrow(Theta)
    P <- matrix( NA, nrow=TP, ncol=ncat)
    P[,1] <- 1
    for (cc in 2:ncat){
        P[,cc] <- exp( (cc-1) * a * Theta[,1] - b )
    }
    P <- P / rowSums(P)
    return(P)
}

#** created item classes of 1PL and 2PL models
par <- c( "a"=1, "b"=0 )
# define some slightly informative prior of 2PL
item_2PL <- sirt::xxirt_createDiscItem( name="2PL", par=par, est=c(TRUE,TRUE),
               P=P_2PL, prior=c(a="dlnorm"), prior_par1=c( a=0 ),
               prior_par2=c(a=5) )
customItems <- list( item_2PL )

#---- definition theta distribution

#** theta grid
Theta <- matrix( seq(-6,6,length=21), ncol=1 )

#** theta distribution
P_Theta1 <- function( par, Theta, G){
    mu <- par[1]
    sigma <- max( par[2], .01 )
    TP <- nrow(Theta)
    pi_Theta <- matrix( 0, nrow=TP, ncol=G)
    pi1 <- dnorm( Theta[,1], mean=mu, sd=sigma )
```

```
    pi1 <- pi1 / sum(pi1)
    pi_Theta[,1] <- pi1
    return(pi_Theta)
}
#** create distribution class
par_Theta <- c( "mu"=0, "sigma"=1 )
customTheta  <- sirt::xxirt_createThetaDistribution( par=par_Theta, est=c(FALSE,FALSE),
                      P=P_Theta1 )

#*****************************************************************************
#******* Model 1: 2PL model

itemtype <- rep( "2PL", 12 )
partable <- sirt::xxirt_createParTable( dat, itemtype=itemtype,
                       customItems=customItems )

mod1 <- sirt::xxirt( dat=dat, Theta=Theta, partable=partable,
                   customItems=customItems, customTheta=customTheta)
summary(mod1)

#*****************************************************************************
#******* Model 2: Regularized 2PL model with regularization on item loadings

# define regularized estimation of item loadings
parindex <- partable[ partable$parname=="a","parindex"]

#** penalty is defined by -N*lambda*sum_i (a_i-1)^2
N <- nrow(dat)
lambda <- .02
penalty_fun_item <- function(x)
{
    val <- N*lambda*sum( ( x[parindex]-1)^2)
    return(val)
}
# estimate standard deviation
customTheta1  <- sirt::xxirt_createThetaDistribution( par=par_Theta, est=c(FALSE,TRUE),
                      P=P_Theta1 )
mod2 <- sirt::xxirt( dat=dat, Theta=Theta, partable=partable,
                   customItems=customItems, customTheta=customTheta1,
                   penalty_fun_item=penalty_fun_item)
summary(mod2)

#############################################################################
## EXAMPLE 4: 2PL mixture model
#############################################################################

#*** simulate data
set.seed(123)
N <- 4000   # number of persons
I <- 15     # number of items
prop <- .25 # mixture proportion for second class

# discriminations and difficulties in first class
```

```
a1 <- rep(1,I)
b1 <- seq(-2,2,len=I)
# distribution in second class
mu2 <- 1
sigma2 <- 1.2
# compute parameters with constraint N(0,1) in second class
# a*(sigma*theta+mu-b)=a*sigma*(theta-(b-mu)/sigma)
#=> a2=a*sigma and b2=(b-mu)/sigma
a2 <- a1
a2[c(2,4,6,8)] <- 0.2  # some items with different discriminations
a2 <- a2*sigma2
b2 <- b1
b2[1:5] <- 1   # first 5 item with different difficulties
b2 <- (b2-mu2)/sigma2
dat1 <- sirt::sim.raschtype(theta=stats::rnorm(N*(1-prop)), b=b1, fixed.a=a1)
dat2 <- sirt::sim.raschtype(theta=stats::rnorm(N*prop), b=b2, fixed.a=a2)
dat <- rbind(dat1, dat2)

#**** model specification

#*** define theta distribution
TP <- 21
theta <- seq(-6,6,length=TP)
# stack theta vectors below each others=> 2 latent classes
Theta <- matrix( c(theta, theta ), ncol=1 )
# distribution of theta (i.e., N(0,1))
w_theta <- dnorm(theta)
w_theta <- w_theta / sum(w_theta)

P_Theta1 <- function( par, Theta, G){
    p2_logis <- par[1]
    p2 <- stats::plogis( p2_logis )
    p1 <- 1-p2
    pi_Theta <- c( p1*w_theta, p2*w_theta)
    pi_Theta <- matrix(pi_Theta, ncol=1)
    return(pi_Theta)
}

par_Theta <- c( p2_logis=qlogis(.25))
customTheta  <- sirt::xxirt_createThetaDistribution( par=par_Theta, est=c(TRUE),
                      P=P_Theta1)

# IRF for 2-class mixture 2PL model
par <- c(a1=1, a2=1, b1=0, b2=.5)

P_2PLmix <- function( par, Theta, ncat)
{
    a1 <- par[1]
    a2 <- par[2]
    b1 <- par[3]
    b2 <- par[4]
    P <- matrix( NA, nrow=2*TP, ncol=ncat)
    TP <- nrow(Theta)/2
```

```
    P1 <- stats::plogis( a1*(Theta[1:TP,1]-b1) )
    P2 <- stats::plogis( a2*(Theta[TP+1:(2*TP),1]-b2) )
    P[,2] <- c(P1, P2)
    P[,1] <- 1-P[,2]
    return(P)
}

# define some slightly informative prior of 2PL
item_2PLmix <- sirt::xxirt_createDiscItem( name="2PLmix", par=par,
               est=c(TRUE,TRUE,TRUE,TRUE), P=P_2PLmix )
customItems <- list( item_2PLmix )

#*****************************************************************************
#******* Model 1: 2PL mixture model

itemtype <- rep( "2PLmix", I )
partable <- sirt::xxirt_createParTable( dat, itemtype=itemtype,
                        customItems=customItems )
mod1 <- sirt::xxirt( dat=dat, Theta=Theta, partable=partable,
                  customItems=customItems, customTheta=customTheta)
summary(mod1)

#############################################################################
## EXAMPLE 5: Partial credit model with MML and PML
#############################################################################

data(data.gpcm, package="TAM")
dat <- data.gpcm

# recode data and include some missings
dat[ dat[,1]==3, 1] <- 2
dat[ 1, c(1,2) ] <- NA
dat[2,3] <- NA

#------ Definition of item response functions
#*** IRF 2PL
P_2PL <- function( par, Theta, ncat)
{
    b <- par
    TP <- nrow(Theta)
    P <- matrix( NA, nrow=TP, ncol=ncat)
    P[,1] <- 1
    for (cc in 2:ncat){
        P[,cc] <- exp( Theta[,1] - b[cc-1] )
    }
    P <- P / rowSums(P)
    return(P)
}

P_PCM2 <- function( par, Theta, ncat=3)
{
    P <- P_2PL(par=par, Theta=Theta, ncat=ncat)
    return(P)
```

```
}

P_PCM3 <- function( par, Theta, ncat=4)
{
    P <- P_2PL(par=par, Theta=Theta, ncat=ncat)
    return(P)
}

# define some slightly informative prior of 2PL
par <- c( b1=-1, b2=1 )
NP <- length(par)
item_PCM2 <- sirt::xxirt_createDiscItem( name="PCM2", par=par, est=rep(TRUE,NP),
               P=P_PCM2 )
par <- c( b1=-1, b2=0, b3=1 ) ; NP <- length(par)
item_PCM3 <- sirt::xxirt_createDiscItem( name="PCM3", par=par, est=rep(TRUE,NP),
               P=P_PCM3 )

customItems <- list( item_PCM2,  item_PCM3 )

#---- definition theta distribution
#** theta grid
Theta <- matrix( seq(-6,6,length=21), ncol=1 )

#** theta distribution
P_Theta1 <- function( par, Theta, G){
    mu <- par[1]
    sigma <- max( par[2], .01 )
    TP <- nrow(Theta)
    pi_Theta <- matrix( 0, nrow=TP, ncol=G)
    pi1 <- dnorm( Theta[,1], mean=mu, sd=sigma )
    pi1 <- pi1 / sum(pi1)
    pi_Theta[,1] <- pi1
    return(pi_Theta)
}
#** create distribution class
par_Theta <- c( "mu"=0, "sigma"=1 )
customTheta  <- sirt::xxirt_createThetaDistribution( par=par_Theta, est=c(FALSE,TRUE),
                      P=P_Theta1 )

#-- create parameter table
itemtype <- c("PCM2", "PCM3", "PCM3")
partable <- sirt::xxirt_createParTable( dat, itemtype=itemtype,
                       customItems=customItems )

#***** Model 1: MML
mod1 <- sirt::xxirt( dat=dat, Theta=Theta, partable=partable,
                  customItems=customItems, customTheta=customTheta)
summary(mod1)

#***** Model 2: PML
I <- ncol(dat)
W1 <- rep(1,I)
W2 <- 1-diag(I)
```

```
W2[3,2] <- 0
W2[ upper.tri(W2)] <- 0
pml_args <- list(W1=W1/sum(W1), W2=W2/sum(W2) )

mod2 <- sirt::xxirt( dat=dat, Theta=Theta, partable=partable,
                  customItems=customItems, customTheta=mod1$customTheta,
                  estimator="PML", pml_args=pml_args)

# variance matrix
smod2 <- sirt::xxirt_sandwich_pml(object=mod2)
smod2


#############################################################################
## EXAMPLE 6: Person covariates for item parameters and trait distribution
#############################################################################

#-- simulate data
set.seed(2025)
N <- 2000
I <- 10
b <- c(0, seq(-2,2,len=I-1))
b1 <- b
b1[1] <- 1
dat1 <- sirt::sim.raschtype( stats::rnorm(N, mean=0, sd=1), b=b )
dat2 <- sirt::sim.raschtype( stats::rnorm(N, mean=1, sd=1.5), b=b1 )
dat <- data.frame( group=rep( c(1,2), each=N), rbind(dat1, dat2))

#*****************************************************************************
#***** Model 1: two-group Rasch model

#*** IRF 1PL
P_1PL <- function( par, Theta, ncat){
    b <- par[1]
    TP <- nrow(Theta)
    P <- matrix( NA, nrow=TP, ncol=ncat)
    P[,1] <- 1
    for (cc in 2:ncat){
        P[,cc] <- exp( (cc-1) * Theta[,1] - b )
    }
    P <- P / rowSums(P)
    return(P)
}

#** create item classes of 1PL and 2PL models
par <- c( b=0 )
item_1PL <- sirt::xxirt_createDiscItem( name="1PL", par=par, est=c(TRUE), P=P_1PL )
customItems <- list( item_1PL )

#---- definition theta distribution

#** theta grid
Theta <- matrix( seq(-6,6,length=21), ncol=1 )
```

```
#** theta distribution
P_Theta1 <- function( par, Theta, G)
{
    mu1 <- par[1]
    sigma1 <- max( par[2], .01 )
    mu2 <- par[3]
    sigma2 <- max( par[4], .01 )
    TP <- nrow(Theta)
    pi_Theta <- matrix( 0, nrow=TP, ncol=G)
    pi1 <- dnorm( Theta[,1], mean=mu1, sd=sigma1 )
    pi1 <- pi1 / sum(pi1)
    pi_Theta[,1] <- pi1
    pi1 <- dnorm( Theta[,1], mean=mu2, sd=sigma2 )
    pi1 <- pi1 / sum(pi1)
    pi_Theta[,2] <- pi1
    return(pi_Theta)
}
#** create distribution class
par_Theta <- c( "mu1"=0, "sigma1"=1, "mu2"=0, "sigma2"=1 )
customTheta  <- sirt::xxirt_createThetaDistribution( par=par_Theta,
                      est=c(FALSE,TRUE,TRUE,TRUE), P=P_Theta1 )

#-- create parameter table
itemtype <- rep( "1PL", I )
partable <- sirt::xxirt_createParTable( dat[,-1], itemtype=itemtype,
                       customItems=customItems )

# estimate model
mod1 <- sirt::xxirt( dat=dat[,-1], Theta=Theta, partable=partable, group=dat$group,
                  customItems=customItems, customTheta=customTheta)
summary(mod1)

#*****************************************************************************
#***** Model 2: Rasch model with person covariates in trait distribution

#- matrix with person covariates
X <- dat,"group", drop=FALSE]

#** theta distribution
P_Theta2 <- function( par, Theta, G, X)
{
    mu1 <- par[1]
    sigma1 <- max( par[2], .01 )
    mu2 <- par[3]
    sigma2 <- max( par[4], .01 )
    TP <- nrow(Theta)
    N <- nrow(X)
    pi_Theta <- matrix( 0, nrow=TP, ncol=N)
    mu <- par[ 2*(X[,1]-1)+1 ]
    sigma <- par[ 2*(X[,1]-1)+2 ]
    for (tt in 1:TP){
        pi_Theta[tt,] <- stats::dnorm(Theta[tt,1], mean=mu, sd=sigma)
```

```
    }
    cp <- sirt::sirt_matrix2( colSums(pi_Theta), nrow=TP)
    pi_Theta <- pi_Theta / ( cp + 1e-80 )
    return(pi_Theta)
}

par_Theta2 <- mod1$customTheta$par

customTheta2  <- sirt::xxirt_createThetaDistribution( par=par_Theta2,
                      est=c(FALSE,TRUE,TRUE,TRUE),
                      P=P_Theta2, X=X, lower=c(-10,0.01, -10, 0.01) )

partable2 <- mod1$partable

mod2 <- sirt::xxirt( dat=dat[,-1], Theta=Theta, partable=partable2,
                  customItems=customItems, customTheta=customTheta2)
summary(mod2)

#*****************************************************************************
#***** Model 3: Rasch model with person covariates in trait distribution and
#*****          item parameters

#*** IRF 1PL
P_1PL <- function( par, Theta, ncat, X)
{
    TP <- nrow(Theta)
    N <- nrow(X)
    P <- array( 0, dim=c(TP,ncat,N) )
    efficient <- TRUE
    if (! efficient ){
        bM <- sirt::sirt_matrix2( par[ X[,1] ], nrow=TP)
        P1 <- stats::plogis(Theta[,1] - bM )
    } else {
        h1 <- exp(-Theta[,1])
        h2 <- sirt::sirt_matrix2( exp(par[ X[,1] ]), nrow=TP)
        P1 <- 1/ ( 1+h1*h2 )
    }
    P[,2,] <- P1
    P[,1,] <- 1 - P[,2,]
    return(P)
}

#** create item classes of 1PL and 2PL models
par <- c( b1=0, b2=-1 )
item_1PL <- sirt::xxirt_createDiscItem( name="1PL", par=par, est=c(TRUE,TRUE),
                           P=P_1PL, X=X )

customItems <- list( item_1PL )

#-- create parameter table
itemtype <- rep( "1PL", I )
partable2 <- sirt::xxirt_createParTable( dat[,-1], itemtype=itemtype,
                       customItems=customItems )
```

```
#-- distribution parameters
customTheta2b <- mod2$customTheta
customTheta2b$par[3] <- 0      # fix mu2 to 0
customTheta2b$est <- c(FALSE,TRUE,FALSE,TRUE)

# estimate model
mod3 <- sirt::xxirt( dat=resp, Theta=Theta, partable=partable2,
                  customItems=customItems, customTheta=customTheta2b, mstep_iter=2)
summary(mod3)


## End(Not run)
```

---

xxirt_createParTable *Create Item Response Functions and Item Parameter Table*

Description

Create item response functions and item parameter table

Usage

```
xxirt_createDiscItem( name, par, est, P, lower=-Inf, upper=Inf,
     prior=NULL, prior_par1=NULL, prior_par2=NULL, X=NULL)

xxirt_createParTable(dat, itemtype, customItems=NULL)

xxirt_modifyParTable( partable, parname, item=NULL, value=NULL,
     est=NULL, parlabel=NULL, parindex=NULL, lower=NULL,
     upper=NULL, prior=NULL, prior_par1=NULL, prior_par2=NULL )
```

Arguments

name	Type of item response function
par	Named vector of starting values of item parameters
est	Logical vector indicating which parameters should be estimated
P	Item response function
lower	Lower bounds
upper	Upper bounds
prior	Prior distribution
prior_par1	First parameter prior distribution
prior_par2	Second parameter prior distribution
X	optional matrix of person covariates
dat	Data frame with item responses

itemtype	Vector of item types
customItems	List with item objects created by xxirt_createDiscItem
partable	Item parameter table
parname	Parameter name
item	Item
value	Value of item parameter
parindex	Parameter index
parlabel	Item parameter label

See Also

xxirt

See mirt::createItem for similar functionality.

Examples

```
#############################################################################
## EXAMPLE 1: Definition of item response functions
#############################################################################

data(data.read)
dat <- data.read

#------ Definition of item response functions
#*** IRF 2PL
P_2PL <- function( par, Theta, ncat){
    a <- par[1]
    b <- par[2]
    TP <- nrow(Theta)
    P <- matrix( NA, nrow=TP, ncol=ncat)
    P[,1] <- 1
    for (cc in 2:ncat){
        P[,cc] <- exp( (cc-1) * a * Theta[,1] - b )
    }
    P <- P / rowSums(P)
    return(P)
}

#*** IRF 1PL
P_1PL <- function( par, Theta, ncat){
    b <- par[1]
    TP <- nrow(Theta)
    par0 <- c(1,b)
    P <- P_2PL( par=par0, Theta=Theta, ncat=ncat)
    return(P)
}

#** created item classes of 1PL and 2PL models
par <- c( "a"=1, "b"=0 )
```

```
# define some slightly informative prior of 2PL
item_2PL <- sirt::xxirt_createDiscItem( name="2PL", par=par, est=c(TRUE,TRUE),
                P=P_2PL, prior=c( a="dlnorm"), prior_par1=c(a=0),
                prior_par2=c(a=5) )
item_1PL <- sirt::xxirt_createDiscItem( name="1PL", par=par[2], est=c(TRUE),
                P=P_1PL )
# list of item classes in customItems
customItems <- list( item_1PL,  item_2PL )

#-- create parameter table
itemtype <- rep( "1PL", 12 )
partable <- sirt::xxirt_createParTable(dat, itemtype=itemtype, customItems=customItems)
# privide starting values
partable1 <- sirt::xxirt_modifyParTable( partable, parname="b",
                   value=- stats::qlogis( colMeans(dat) ) )
# equality constraint of parameters and definition of lower bounds
partable1 <- sirt::xxirt_modifyParTable( partable1, item=c("A1","A2"),
                parname="b", parindex=110, lower=-1, value=0)
print(partable1)
```

`xxirt_createThetaDistribution` *Creates a User Defined Theta Distribution*

Description

Creates a user defined theta distribution.

Usage

```
xxirt_createThetaDistribution(par, est, P, prior=NULL, prior_par1=NULL,
       prior_par2=NULL, lower=NULL, upper=NULL, X=NULL)
```

Arguments

`par`	Parameter vector with starting values
`est`	Vector of logicals indicating which parameters should be estimated
`P`	Distribution function for $\boldsymbol{\theta}$
`prior`	Prior distribution
`prior_par1`	First parameter of prior distribution
`prior_par2`	Second parameter of prior distribution
`lower`	Lower bounds for parameters
`upper`	Upper bounds for parameters
`X`	optional matrix of person covariates

See Also

xxirt

Examples

```
#############################################################################
## EXAMPLE 1: Definition of theta distribution
#############################################################################

#** theta grid
Theta <- matrix( seq(-10,10,length=31), ncol=1 )

#** theta distribution
P_Theta1 <- function( par, Theta, G){
    mu <- par[1]
    sigma <- max( par[2], .01 )
    TP <- nrow(Theta)
    pi_Theta <- matrix( 0, nrow=TP, ncol=G)
    pi1 <- stats::dnorm( Theta[,1], mean=mu, sd=sigma )
    pi1 <- pi1 / sum(pi1)
    pi_Theta[,1] <- pi1
    return(pi_Theta)
                }
#** create distribution class
par_Theta <- c( "mu"=0, "sigma"=1 )
customTheta  <- sirt::xxirt_createThetaDistribution( par=par_Theta,
                      est=c(FALSE,TRUE), P=P_Theta1 )
```

Index

∗ **package**
sirt-package, 5

anova.gom *(gom.em)*, 141
anova.prob.guttman *(prob.guttman)*, 319
anova.rasch.copula2 *(rasch.copula2)*, 342
anova.rasch.copula3 *(rasch.copula2)*, 342
anova.rasch.mirtlc *(rasch.mirtlc)*, 362
anova.rasch.mml *(rasch.mml2)*, 374
anova.rm.facets *(rm.facets)*, 412
anova.rm.sdt *(rm.sdt)*, 418
anova.smirt *(smirt)*, 441
anova.xxirt *(xxirt)*, 469
automatic.recode, 10

base::expand.grid, *442*
bounds_parameters *(sirt-utilities)*, 435
brm-Methods, 12
brm.irf, *271*
brm.irf *(brm-Methods)*, 12
brm.sim *(brm-Methods)*, 12
btm, 16
btm_sim *(btm)*, 16

categorize, 21
ccov.np, 22, *28*, *111*
CDM::gdm, *366*
CDM::IRT.irfprob, *272*
CDM::IRT.likelihood, *193*, *272*
CDM::IRT.posterior, *272*
CDM::itemfit.sx2, *381*
CDM::modelfit.cor, *279*
cfa_meas_inv, 24
class.accuracy.rasch, 26
coda::mcmc, *259*
coef.rasch.evm.pcm *(rasch.evm.pcm)*, 351
coef.xxirt *(xxirt)*, 469
colCumsums.sirt *(matrixfunctions.sirt)*, 240
conf.detect, *7*, *23*, 27, *112*, *130*
confint.xxirt *(xxirt)*, 469

data.activity.itempars, 32
data.befki, 33
data.befki_resp *(data.befki)*, 33
data.big5, 34, *271*
data.bs, 39
data.bs07a *(data.bs)*, 39
data.dcm, *271*
data.eid, 41
data.ess2005, 49
data.g308, 50
data.inv4gr, 52
data.liking.science, 53
data.long, 54, *271*
data.lsem, 58
data.lsem01 *(data.lsem)*, 58
data.lsem02 *(data.lsem)*, 58
data.lsem03 *(data.lsem)*, 58
data.math, 59
data.mcdonald, 61
data.mixed1, 64
data.ml, 65
data.ml1 *(data.ml)*, 65
data.ml2 *(data.ml)*, 65
data.noharm, 66
data.noharm18 *(data.noharm)*, 66
data.noharmExC *(data.noharm)*, 66
data.pars1.2pl *(data.pars1.rasch)*, 67
data.pars1.rasch, 67
data.pirlsmissing, 68
data.pisa2006Read, 69
data.pisaMath, 69
data.pisaPars, 70
data.pisaRead, 71
data.pw, 72
data.pw01 *(data.pw)*, 72
data.ratings, 72
data.ratings1 *(data.ratings)*, 72
data.ratings2 *(data.ratings)*, 72

data.ratings3 (data.ratings), 72
data.raw1, 73
data.read, 74, *271*
data.reck, 94
data.reck21 (data.reck), 94
data.reck61DAT1 (data.reck), 94
data.reck61DAT2 (data.reck), 94
data.reck73C1a (data.reck), 94
data.reck73C1b (data.reck), 94
data.reck75C2 (data.reck), 94
data.reck78ExA (data.reck), 94
data.reck79ExB (data.reck), 94
data.si01 (data.sirt), 100
data.si02 (data.sirt), 100
data.si03 (data.sirt), 100
data.si04 (data.sirt), 100
data.si05 (data.sirt), 100
data.si06 (data.sirt), 100
data.si07 (data.sirt), 100
data.si08 (data.sirt), 100
data.si09 (data.sirt), 100
data.si10 (data.sirt), 100
data.sirt, 100
data.timss, 105
data.timss07.G8.RUS, 106
data.trees, 107
data.wide2long, 109
decategorize (categorize), 21
detect.index, 111
dexppow (lq_fit), 216
dif.logistic.regression, 112, *117, 118*
dif.strata.variance, *113*, 116
dif.variance, *113*, 117
dimproper (sirt-utilities), 435
dinvgamma2 (rinvgamma2), 410
dirichlet.mle, 118
dirichlet.simul, *119*, 120
dmlavaan, 122

eigenvalues.manymatrices, 124
equating.rasch, *7*, 125, *128*, *198*, *211*
equating.rasch.jackknife, *126*, 127
expl.detect, *23*, *27*, *29*, 128

f1d.irt, *7*, 130, *153*
fit.adisop, *170*, *172*
fit.adisop (fit.isop), 133
fit.isop, 133, *172*, *175*
fuzcluster, 135

fuzdiscr, *136*, 138

genlogis.moments (pgenlogis), 307
ginverse_sym (sirt-utilities), 435
gom.em, *6*, 141, *271*, *278*, *279*
gom.jml, *145*, 150
greenyang.reliability, *7*, *131*, 151, *238*, *408*

hard_thresholding (sirt-utilities), 435

invariance.alignment, *7*, *126*, 154, *198*, *209*
invariance_alignment_cfa_config (invariance.alignment), 154
invariance_alignment_constraints (invariance.alignment), 154
invariance_alignment_simulate (invariance.alignment), 154
IRT.expectedCounts.MultipleGroupClass (mirt.wrapper), 269
IRT.expectedCounts.rasch.mml (rasch.mml2), 374
IRT.expectedCounts.SingleGroupClass (mirt.wrapper), 269
IRT.expectedCounts.xxirt (xxirt), 469
IRT.factor.scores.rm.facets (rm.facets), 412
IRT.factor.scores.rm.sdt (rm.sdt), 418
IRT.factor.scores.xxirt (xxirt), 469
IRT.irfprob.gom (gom.em), 141
IRT.irfprob.MultipleGroupClass (mirt.wrapper), 269
IRT.irfprob.prob.guttman (prob.guttman), 319
IRT.irfprob.rasch.mirtlc (rasch.mirtlc), 362
IRT.irfprob.rasch.mml (rasch.mml2), 374
IRT.irfprob.rm.facets (rm.facets), 412
IRT.irfprob.rm.sdt (rm.sdt), 418
IRT.irfprob.SingleGroupClass (mirt.wrapper), 269
IRT.irfprob.smirt (smirt), 441
IRT.irfprob.xxirt (xxirt), 469
IRT.likelihood.gom (gom.em), 141
IRT.likelihood.MultipleGroupClass (mirt.wrapper), 269
IRT.likelihood.prob.guttman (prob.guttman), 319

IRT.likelihood.rasch.copula2 (rasch.copula2), 342
IRT.likelihood.rasch.copula3 (rasch.copula2), 342
IRT.likelihood.rasch.mirtlc (rasch.mirtlc), 362
IRT.likelihood.rasch.mml (rasch.mml2), 374
IRT.likelihood.rm.facets (rm.facets), 412
IRT.likelihood.rm.sdt (rm.sdt), 418
IRT.likelihood.SingleGroupClass (mirt.wrapper), 269
IRT.likelihood.smirt (smirt), 441
IRT.likelihood.xxirt (xxirt), 469
IRT.mle, 167
IRT.modelfit.gom (gom.em), 141
IRT.modelfit.rasch.mirtlc (rasch.mirtlc), 362
IRT.modelfit.rasch.mml (rasch.mml2), 374
IRT.modelfit.rm.facets (rm.facets), 412
IRT.modelfit.rm.sdt (rm.sdt), 418
IRT.modelfit.sirt (modelfit.sirt), 278
IRT.modelfit.smirt (smirt), 441
IRT.modelfit.xxirt (xxirt), 469
IRT.posterior.gom (gom.em), 141
IRT.posterior.MultipleGroupClass (mirt.wrapper), 269
IRT.posterior.prob.guttman (prob.guttman), 319
IRT.posterior.rasch.copula2 (rasch.copula2), 342
IRT.posterior.rasch.copula3 (rasch.copula2), 342
IRT.posterior.rasch.mirtlc (rasch.mirtlc), 362
IRT.posterior.rasch.mml (rasch.mml2), 374
IRT.posterior.rm.facets (rm.facets), 412
IRT.posterior.rm.sdt (rm.sdt), 418
IRT.posterior.SingleGroupClass (mirt.wrapper), 269
IRT.posterior.smirt (smirt), 441
IRT.posterior.xxirt (xxirt), 469
IRT.se.xxirt (xxirt), 469
isop, 170
isop.dich, *7*, *134*, *175*, *176*, *282*
isop.poly, *7*, *176*
isop.scoring, *7*, *171*, *172*, 174
isop.test, *172*, 176
itemfit.sx2, *445*

L0_polish (linking.haberman), 194
latent.regression.em.normal (latent.regression.em.raschtype), 177
latent.regression.em.raschtype, 177, *310*
lavaan2mirt, 183, *272*, *452*, *453*
lavaan::cfa, *226*
lavaan::growth, *226*
lavaan::lavaan, *226*, *228*
lavaan::lavaanify, *183*, *184*
lavaan::sem, *226*, *228*
lavaan::standardizedSolution, *226*
lc.2raters, *6*, 190
likelihood.adjustment, 192
linking.haberman, *7*, *67*, *126*, *158*, 194, *207*, *209*, *211*
linking.haebara, *198*, 206
linking.robust, *7*, *126*, 210
linking_2groups, 212
linking_haberman_itempars_convert (linking.haberman), 194
linking_haberman_itempars_prepare (linking.haberman), 194
locpolycor, 214
logLik.gom (gom.em), 141
logLik.prob.guttman (prob.guttman), 319
logLik.rasch.copula2 (rasch.copula2), 342
logLik.rasch.copula3 (rasch.copula2), 342
logLik.rasch.mirtlc (rasch.mirtlc), 362
logLik.rasch.mml (rasch.mml2), 374
logLik.rm.facets (rm.facets), 412
logLik.rm.sdt (rm.sdt), 418
logLik.smirt (smirt), 441
logLik.xxirt (xxirt), 469
lq_fit, 216
lq_fit_estimate_power (lq_fit), 216
lsdm, *7*, 218
lsem.bootstrap, *236*
lsem.bootstrap (lsem.estimate), 225
lsem.estimate, *7*, 225, *234*, *236*
lsem.MGM.stepfunctions (lsem.estimate), 225

lsem.permutationTest, *225*, *229*, 234
lsem.test, *229*, 236
lsem_local_weights, *215*
lsem_local_weights *(*lsem.estimate*)*, 225

marginal.truescore.reliability, *7*, 237
matrixfunctions.sirt, 240
mcmc.2pno, *6*, 241, *251*, *313, 314*, *451, 452*
mcmc.2pno.ml, *6, 7*, *65*, *158*, 244, *313, 314*, *451, 452*
mcmc.2pnoh, *7*, *243*, 249, *313, 314*, *451, 452*
mcmc.3pno.testlet, *7*, *246*, 251, *313, 314*, *324*, *432*, *451, 452*
mcmc.list.descriptives, 256
mcmc_coef, 258
mcmc_confint *(*mcmc_coef*)*, 258
mcmc_derivedPars *(*mcmc_coef*)*, 258
mcmc_plot *(*mcmc_coef*)*, 258
mcmc_Rhat, 260
mcmc_summary *(*mcmc_coef*)*, 258
mcmc_vcov *(*mcmc_coef*)*, 258
mcmc_WaldTest *(*mcmc_coef*)*, 258
mcmclist2coda, *257*, 261
md.pattern.sirt, 262
mgsem, 263
mirt, *183*, *453*
mirt.specify.partable, 268
mirt.wrapper, *184*, 269, *453*
mirt::bfactor, *272*
mirt::createItem, *473*, *489*
mirt::itemfit, *301*
mirt::mirt, *183, 184*, *272*, *278, 279*, *445*, *473*
mirt::mixedmirt, *445*
mirt::mod2values, *272*
mirt::multipleGroup, *272*
mirt::personfit, *306*
mirt_summary *(*mirt.wrapper*)*, 269
mle.pcm.group, 276, *352*
modelfit.cor, *278*
modelfit.cor.poly *(*modelfit.sirt*)*, 278
modelfit.sirt, 278, *291*, *366*, *381*, *400*
monoreg.colwise *(*monoreg.rowwise*)*, 282
monoreg.rowwise, 282
move_variables_df *(*sirt-utilities*)*, 435

nedelsky-methods, 283
nedelsky.irf, *271*
nedelsky.irf *(*nedelsky-methods*)*, 283
nedelsky.latresp *(*nedelsky-methods*)*, 283
nedelsky.sim *(*nedelsky-methods*)*, 283
noharm.sirt, *7*, *278, 279*, 287, *335*, *341*
np.dich, *6*, 296, *314*

parmsummary_extend, 297
pbivnorm2, 298
pbivnorm::pbivnorm, *299*
pcm.conversion, 299, *301*, *414*
pcm.fit, 301, *306*
person.parameter.rasch.copula, 303, *346*
personfit.stat, *7*, 305
pgenlogis, 307, *378*, *434*
plausible.value.imputation.raschtype, *179*, 309
plot.isop *(*isop*)*, 170
plot.linking.robust *(*linking.robust*)*, 210
plot.lsdm *(*lsdm*)*, 218
plot.lsem *(*lsem.estimate*)*, 225
plot.lsem.permutationTest *(*lsem.permutationTest*)*, 234
plot.mcmc.sirt, *243*, *246*, *251*, *253*, 313
plot.np.dich, 314
plot.rasch.mml *(*rasch.mml2*)*, 374
plot.rm.sdt *(*rm.sdt*)*, 418
polychoric2, 315, *315*, *460*
pow *(*sirt-utilities*)*, 435
predict.btm *(*btm*)*, 16
predict_scale_group_means *(*scale_group_means*)*, 425
print.xxirt *(*xxirt*)*, 469
print_digits *(*sirt-utilities*)*, 435
prior_model_parse, 316
prmse.subscores.scales, 317
prob.guttman, *7*, 319
psych::polychoric, *316*

Q3, 323, *325*, *435*
Q3.testlet, *324*, 325, *435*
qmc.nodes, 326, *442*

R2conquest, 327, *435*
R2noharm, *7*, *66*, *278, 279*, *291*, 332, *341, 342*
R2noharm.EAP, *291*, *335*, 340
R2noharm.jackknife, *335*, 341
rasch.conquest *(*sirt-defunct*)*, 435
rasch.copula2, *178*, *271*, *304*, *309*, *324*, 342, *395*, *432*
rasch.copula3, *6*

rasch.copula3 *(rasch.copula2)*, 342
rasch.evm.pcm, *6*, *113*, 351
rasch.jml, *6*, 356, *359*, *361*, *467*
rasch.jml.biascorr, *6*, 359, *361*
rasch.jml.jackknife1, *6*, *358*, *360*, 361
rasch.mirtlc, *6*, *101*, *271*, *278, 279*, 362, *445*
rasch.mml2, *6*, *178*, *237*, *243*, *278, 279*, *309*, *323*, *346*, *358*, 374, *395*, *429*, *433, 434*, *445*
rasch.pairwise, *6*, 392, *395*, *400*, *432*
rasch.pairwise.itemcluster, *6*, *324*, *393*, 394, *400*, *432*
rasch.pml2, *278, 279*
rasch.pml2 *(sirt-defunct)*, 435
rasch.pml3, *6*, *278, 279*, *324*, *393*, *395*, 397, *435*
rasch.prox, *357, 358*, 405
rasch.va, *7*, 406
read.multidimpv *(R2conquest)*, 327
read.pimap *(R2conquest)*, 327
read.pv *(R2conquest)*, 327
read.show *(R2conquest)*, 327
reliability.nonlinearSEM, *153*, 408
resp_groupwise, 409
rexppow *(lq_fit)*, 216
rinvgamma2, 410
rm.facets, *6*, *191*, 412, *422*
rm.sdt, *6*, *191*, *415*, 418
rm_proc_data *(rm.facets)*, 412
rmvn, 423
rowCumsums.sirt *(matrixfunctions.sirt)*, 240
rowIntervalIndex.sirt *(matrixfunctions.sirt)*, 240
rowKSmallest.sirt *(matrixfunctions.sirt)*, 240
rowKSmallest2.sirt *(matrixfunctions.sirt)*, 240
rowMaxs.sirt *(matrixfunctions.sirt)*, 240
rowMins.sirt *(matrixfunctions.sirt)*, 240
ruvn *(rmvn)*, 423

scale_group_means, 425
sfsmisc::QUnif, *326*
sia.sirt, 426
sim.qm.ramsay, *381*, 428, *432*
sim.rasch.dep, *346*, *381*, *395*, *400*, 431
sim.raschtype, *381*, *429*, *432*, 433
sirt *(sirt-package)*, 5
sirt-defunct, 435
sirt-package, 5
sirt-utilities, 435
sirt::invariance.alignment, *25*
sirt_abs_smooth *(sirt-utilities)*, 435
sirt_antifisherz *(sirt-utilities)*, 435
sirt_attach_list_elements *(sirt-utilities)*, 435
sirt_colMaxs *(sirt-utilities)*, 435
sirt_colMeans *(sirt-utilities)*, 435
sirt_colMedians *(sirt-utilities)*, 435
sirt_colMins *(sirt-utilities)*, 435
sirt_colSDs *(sirt-utilities)*, 435
sirt_dnorm_discrete *(sirt-utilities)*, 435
sirt_eigenvalues, 440
sirt_fisherz *(sirt-utilities)*, 435
sirt_matrix2 *(sirt-utilities)*, 435
sirt_optimizer, *471*
sirt_optimizer *(sirt-utilities)*, 435
sirt_permutations *(sirt-utilities)*, 435
sirt_rbind_fill *(sirt-utilities)*, 435
sirt_rcpp_discrete_inverse *(sirt-utilities)*, 435
sirt_rcpp_polychoric2 *(polychoric2)*, 315
sirt_sum_norm *(sirt-utilities)*, 435
sirt_summary_print_call *(sirt-utilities)*, 435
sirt_summary_print_objects *(sirt-utilities)*, 435
sirt_summary_print_package *(sirt-utilities)*, 435
sirt_summary_print_package_rsession *(sirt-utilities)*, 435
sirt_summary_print_rsession *(sirt-utilities)*, 435
smirt, *6*, *243*, *278, 279*, 441
soft_thresholding *(sirt-utilities)*, 435
stats::confint, *298*
stats::dgamma, *411*
stats::hclust, *129*
stats::medpolish, *197*
stats::nlminb, *155*, *207*, *289*, *393*, *420*
stats::optim, *155*, *207*, *289*, *420*, *471*
stats::rgamma, *411*
stratified.cronbach.alpha, 450
summary.btm *(btm)*, 16
summary.conf.detect *(conf.detect)*, 27

summary.fuzcluster (fuzcluster), 135
summary.gom, *151*
summary.gom (gom.em), 141
summary.invariance.alignment (invariance.alignment), 154
summary.invariance_alignment_constraints (invariance.alignment), 154
summary.IRT.modelfit.gom (gom.em), 141
summary.IRT.modelfit.rasch.mirtlc (rasch.mirtlc), 362
summary.IRT.modelfit.rasch.mml (rasch.mml2), 374
summary.IRT.modelfit.rm.facets (rm.facets), 412
summary.IRT.modelfit.rm.sdt (rm.sdt), 418
summary.IRT.modelfit.smirt (smirt), 441
summary.IRT.modelfit.xxirt (xxirt), 469
summary.isop (isop), 170
summary.isop.test (isop.test), 176
summary.latent.regression (latent.regression.em.raschtype), 177
summary.lc.2raters (lc.2raters), 190
summary.linking.haberman (linking.haberman), 194
summary.linking.haebara (linking.haebara), 206
summary.linking.robust (linking.robust), 210
summary.lsdm, *221*
summary.lsdm (lsdm), 218
summary.lsem (lsem.estimate), 225
summary.lsem.permutationTest (lsem.permutationTest), 234
summary.mcmc.sirt, *243*, *246*, *251*, *253*, 451
summary.mcmc_WaldTest (mcmc_coef), 258
summary.noharm.sirt (noharm.sirt), 287
summary.prob.guttman (prob.guttman), 319
summary.R2conquest (R2conquest), 327
summary.R2noharm (R2noharm), 332
summary.R2noharm.jackknife (R2noharm.jackknife), 341
summary.rasch.copula2, *346*
summary.rasch.copula2 (rasch.copula2), 342
summary.rasch.copula3 (rasch.copula2), 342
summary.rasch.evm.pcm (rasch.evm.pcm), 351
summary.rasch.jml, *358*
summary.rasch.jml (rasch.jml), 356
summary.rasch.mirtlc (rasch.mirtlc), 362
summary.rasch.mml (rasch.mml2), 374
summary.rasch.pairwise, *393*, *395*
summary.rasch.pairwise (rasch.pairwise), 392
summary.rasch.pml, *400*
summary.rasch.pml (rasch.pml3), 397
summary.rm.facets (rm.facets), 412
summary.rm.sdt (rm.sdt), 418
summary.smirt (smirt), 441
summary.xxirt (xxirt), 469

tam2mirt, *184*, *272*, 452
TAM::lavaanify.IRT, *183, 184*
TAM::tam.fa, *131*, *278, 279*, *457, 458*
TAM::tam.fit, *301*
TAM::tam.jml, *358*
TAM::tam.latreg, *193*
TAM::tam.linking, *158*, *198*
TAM::tam.mml, *278, 279*, *452*
TAM::tam.mml.2pl, *278, 279*
TAM::tam.mml.3pl, *13*
TAM::tam.modelfit, *279*
testlet.marginalized, 457
testlet.yen.q3 (sirt-defunct), 435
tetrachoric2, *131*, *316*, 459
tracemat (sirt-utilities), 435
truescore.irt, 461

unidim.test.csn, 464

vcov.rasch.evm.pcm (rasch.evm.pcm), 351
vcov.xxirt (xxirt), 469

wle.rasch, *296*, *323*, 466, *468*
wle.rasch.jackknife, *7*, 467, *467*

xxirt, *283*, 469, *489*, *491*
xxirt_createDiscItem, *471*
xxirt_createDiscItem (xxirt_createParTable), 488
xxirt_createParTable, *471*, 488
xxirt_createThetaDistribution, *471*, 490
xxirt_hessian (xxirt), 469
xxirt_modifyParTable, *471*

xxirt_modifyParTable
(xxirt_createParTable), 488
xxirt_sandwich_pml (xxirt), 469

yen.q3 (sirt-defunct), 435