Package: spinebil (via r-universe)

October 28, 2026

Type Package

Title Investigating New Projection Pursuit Index Functions

Version 1.0.6

Description Projection pursuit is used to find interesting low-dimensional projections of high-dimensional data by optimizing an index over all possible projections. The 'spinebil' package contains methods to evaluate the performance of projection pursuit index functions using tour methods. A paper describing the methods can be found at <doi:10.1007/s00180-020-00954-8>.

License GPL-3

Encoding UTF-8

URL https://uschilaa.github.io/spinebil/index.html

BugReports https://github.com/uschiLaa/spinebil/issues

Depends R (>= 4.1.0)

Imports tourr, ggplot2, tibble, stats, dplyr, tidyr, tictoc, cassowaryr, rlang, readr

Suggests minerva, purrr, furrr, future, quarto, knitr

VignetteBuilder quarto

Config/roxygen2/version 8.0.0

NeedsCompilation no

Author Ursula Laa [aut] (ORCID: <https://orcid.org/0000-0002-0249-6439>), Dianne Cook [aut] (ORCID: <https://orcid.org/0000-0002-3813-7155>), Tina Rashid Jafari [aut, cre] (ORCID: <https://orcid.org/0009-0008-3605-5341>)

Maintainer Tina Rashid Jafari <tina.rashidjafari@gmail.com>

Repository https://cran.r-universe.dev

Date/Publication 2026-10-28 10:00:02 UTC

RemoteUrl https://github.com/cran/spinebil

RemoteRef HEAD

RemoteSha a0d3380706f171ab934344b87ed5b211d771a270

Contents

basis_matrix . . . 2
basis_vector . . . 3
compare_smoothing . . . 3
data_gen . . . 4
distance_dist . . . 5
distance_to_sp . . . 6
get_index_mean . . . 6
get_trace . . . 7
jitter_angle . . . 8
jitter_points . . . 8
noise_gen . . . 9
pipe_data . . . 10
plot_rotation . . . 10
plot_smoothing_comparison . . . 11
plot_trace . . . 11
ppi_mean . . . 12
ppi_noise_grid . . . 12
ppi_noise_threshold . . . 15
ppi_samplesize_effect . . . 16
ppi_scale . . . 17
profile_rotation . . . 19
scag_index . . . 19
sin_data . . . 20
spiral_data . . . 21
squint_angle_estimate . . . 22
time_sequence . . . 23

Index **24**

`basis_matrix` *Generate 2-d basis in directions i, j in n dimensions (i,j <= n)*

Description

Generate 2-d basis in directions i, j in n dimensions (i,j <= n)

Usage

```
basis_matrix(i, j, n)
```

Arguments

i	first basis direction
j	second basis direction
n	number of dimensions

Value

basis matrix

---

basis_vector *Generate basis vector in direction i in n dimensions (i <= n)*

Description

Generate basis vector in direction i in n dimensions (i <= n)

Usage

```
basis_vector(i, n)
```

Arguments

i	selected direction
n	number of dimensions

Value

basis vector

---

compare_smoothing *Compare traces with different smoothing options.*

Description

Compare traces with different smoothing options.

Usage

```
compare_smoothing(d, tPath, idx, alphaV = c(0.01, 0.05, 0.1), n = 10)
```

Arguments

d	Data matrix
tPath	Interpolated tour path (as list of projections)
idx	Index function
alphaV	Jitter amounts to compare (for jittering angle or points)
n	Number of evaluations entering mean value calculation

Value

Table of mean index values

Examples

```
d <- as.matrix(spiral_data(30, 3))
tPath <- tourr::save_history(d, max_bases=2)
tPath <- as.list(tourr::interpolate(tPath, 0.3))
idx <- scag_index("stringy")
compS <- compare_smoothing(d, tPath, idx, alphaV = c(0.01, 0.05), n=2)
plot_smoothing_comparison(compS)
```

---

data_gen *Generate Synthetic Data with Various Structures*

Description

Generates either:

- Structured (x, y) scatter data (linear, sine, circle, etc.), or
- A matrix of scaled orthogonal polynomial features.

Usage

```
data_gen(type = "all", n = 500, degree = NULL, seed = NULL)
```

Arguments

type	Character string. Options: • "polynomial" for orthogonal polynomial features • "linear", "sine", "circle", "cluster", "snake", "outliers", "sparse", "clumpy", "skewed", "striated", "concave", "monotonic", "doughnut", or "all" to generate all scatter structures.
n	Integer. Number of samples to generate. Default is 500.
degree	Integer. Degree of polynomial features (only for type = "polynomial").
seed	Optional integer. Sets random seed for reproducibility.

Value

- If `type = "polynomial"`, returns a matrix (`n` x `degree`).
- Otherwise a tibble with columns:
- `x`: Numeric vector of x-values
- `y`: Numeric vector of y-values
- `structure`: Character name of the structure type

Examples

```
data_gen("linear", n = 200)
data_gen("polynomial", degree = 4, n = 200)
data_gen("all", n = 200)
```

`distance_dist` *Collecting all pairwise distances between input planes.*

Description

The distribution of all pairwise distances is useful to understand the optimisation in a guided tour, to compare e.g. different optimisation methods or different number of noise dimensions.

Usage

```
distance_dist(planes, nn = FALSE)
```

Arguments

`planes`	Input planes (e.g. result of guided tour)
`nn`	Set true to only consider nearest neighbour distances (dummy, not yet implemented)

Value

numeric vector containing all distances

Examples

```
planes1 <- purrr::rerun(10, tourr::basis_random(5))
planes2 <- purrr::rerun(10, tourr::basis_random(10))
d1 <- distance_dist(planes1)
d2 <- distance_dist(planes2)
d <- tibble::tibble(dist=c(d1, d2), dim=c(rep(5,length(d1)),rep(10,length(d2))))
ggplot2::ggplot(d) + ggplot2::geom_boxplot(ggplot2::aes(factor(dim), dist))
```

distance_to_sp *Collecting distances between input planes and input special plane.*

Description

If the optimal view is known, we can use the distance between a given plane and the optimal one as a proxy to diagnose the performance of the guided tour.

Usage

```
distance_to_sp(planes, special_plane)
```

Arguments

planes	Input planes (e.g. result of guided tour)
special_plane	Plane defining the optimal view

Value

numeric vector containing all distances

Examples

```
planes <- purrr::rerun(10, tourr::basis_random(5))
special_plane <- basis_matrix(1,2,5)
d <- distance_to_sp(planes, special_plane)
plot(d)
```

get_index_mean *Evaluate mean index value over n jittered views.*

Description

Evaluate mean index value over n jittered views.

Usage

```
get_index_mean(proj, d, alpha, idx, method = "jitter_angle", n = 10)
```

Arguments

proj	Original projection plane
d	Data matrix
alpha	Jitter amount (for jittering angle or points)
idx	Index function
method	Select between "jitterAngle" (default) and "jitterPoints" (otherwise we return original index value)
n	Number of evaluations entering mean value calculation

Value

Mean index value

`get_trace` *Tracing the index over an interpolated planned tour path.*

Description

Tracing is used to test if the index value varies smoothly over an interpolated tour path. The index value is calculated for the data d in each projection in the interpolated sequence. Note that all index functions must take the data in 2-d matrix format and return the index value.

Usage

```
get_trace(d, m, index_list, index_labels)
```

Arguments

`d`	data
`m`	list of projection matrices for the planned tour
`index_list`	list of index functions to calculate for each entry
`index_labels`	labels used in the output

Value

index values for each interpolation step

Examples

```
d <- spiral_data(100, 4)
m <- list(basis_matrix(1,2,4), basis_matrix(3,4,4))
index_list <- list(tourr::holes(), tourr::cmass())
index_labels <- c("holes", "cmass")
trace <- get_trace(d, m, index_list, index_labels)
plot_trace(trace)
```

jitter_angle *Re-evaluate index after jittering the projection by an angle alpha.*

Description

Re-evaluate index after jittering the projection by an angle alpha.

Usage

```
jitter_angle(proj, d, alpha, idx)
```

Arguments

proj	Original projection plane
d	Data matrix
alpha	Jitter angle
idx	Index function

Value

New index value

jitter_points *Re-evaluate index after jittering all points by an amount alpha.*

Description

Re-evaluate index after jittering all points by an amount alpha.

Usage

```
jitter_points(proj_data, alpha, idx)
```

Arguments

proj_data	Original projected data points
alpha	Jitter amount (passed into the jitter() function)
idx	Index function

Value

New index value

noise_gen *Generate Synthetic Noise*

Description

Generate Synthetic Noise

Usage

```
noise_gen(n = 500, type = "gaussian", level = 0.01, seed = NULL)
```

Arguments

n	Integer. Number samples to generate. Default is 500.
type	Character string specifying the type of noise to generate. Supported types: • "gaussian": Standard normal distribution. • "uniform": Uniform distribution between -level and +level. • "lognormal": Log-normal distribution. • "t_distributed": Heavy-tailed t-distribution with 3 degrees of freedom. • "cauchy": Extremely heavy-tailed Cauchy distribution. • "beta_noise": Beta distribution shifted and scaled to [-level, level]. • "exponential": Positive-only exponential distribution. • "microstructure": Oscillatory sinusoidal pattern with additive Gaussian noise.
level	Numeric. Controls the scale (standard deviation, range, or spread) of the noise. Default is 0.01.
seed	Optional integer. Sets a random seed for reproducibility.

Value

A tibble with two columns:

- value: Numeric vector of generated noise samples.
- type: Character string indicating the type of noise.

Examples

```
# Gaussian noise with small scale
noise_gen(500, type = "gaussian", level = 0.05)

# Heavy-tailed noise
noise_gen(500, type = "t_distributed", level = 0.1)
```

pipe_data *Generating a sample of points on a pipe*

Description

Points are drawn from a uniform distribution between -1 and 1, the pipe structure is generated by rejecting points if they are not on a circle with radius 1 and thickness t in the last two parameters.

Usage

```
pipe_data(n, p, t = 0.1)
```

Arguments

n	number of sample points to generate
p	sample dimensionality
t	thickness of circle, default=0.1

Value

sample points in tibble format

Examples

```
pipe_data(100, 4)
pipe_data(100, 2, 0.5)
```

plot_rotation *Plot rotation traces of indexes obtained with profileRotation.*

Description

Plot rotation traces of indexes obtained with profileRotation.

Usage

```
plot_rotation(res_mat)
```

Arguments

res_mat	data (result of profileRotation)

Value

ggplot visualisation of the tracing data

plot_smoothing_comparison

Plot the comparison of smoothing methods.

Description

Plotting method for the results of compareSmoothing. The results are mapped by facetting over values of alpha and mapping the method (jitter_angle, jitter_points, no_smoothing) to linestyle and color (black dashed, black dotted, red solid). By default legend drawing is turned off, but can be turned on via the lPos argument, e.g. setting to "bottom" for legend below the plot.

Usage

```
plot_smoothing_comparison(sm_mat, lPos = "none")
```

Arguments

sm_mat	Result from compare_smoothing
lPos	Legend position passed to ggplot2 (default is none for no legend shown)

Value

ggplot visualisation of the comparison

plot_trace

Plot traces of indexes obtained with get_trace.

Description

Plot traces of indexes obtained with get_trace.

Usage

```
plot_trace(res_mat, rescY = TRUE)
```

Arguments

res_mat	data (result of get_trace)
rescY	bool to fix y axis range to [0,1]

Value

ggplot visualisation of the tracing data

ppi_mean *Simulate and Summarize Projection Pursuit Index (PPI) Values*

Description

Simulate and Summarize Projection Pursuit Index (PPI) Values

Usage

```
ppi_mean(data, index_fun, n_sim = 100, n_obs = 300)
```

Arguments

data	A data frame or matrix. Must have at least two columns.
index_fun	A function taking two numeric vectors (x, y) and returning a scalar index.
n_sim	Integer. Number of simulations. Default is 100.
n_obs	Integer. Number of observations to sample in each simulation. Default is 300.

Value

A tibble with:

- var_i, var_j: Names of variable pairs
- mean_index: Mean index value over simulations

Examples

```
data <- as.data.frame(data_gen(type = "polynomial", degree = 2))
ppi_mean(data, scag_index("stringy"), n_sim = 10)
```

ppi_noise_grid *Estimate Noise Thresholds Across Sample Sizes*

Description

Simulates two-dimensional noise data over a sequence of sample sizes and estimates the 95th percentile of one or more projection pursuit index functions under the noise distribution.

Usage

```
ppi_noise_grid(
  index_funs,
  n_sim,
  n_start,
  n_end,
  step = 25,
  settings = list(default = list()),
  seed = 1028,
  workers = 1,
  output_file = NULL,
  index_args = list(),
  noise_fun = NULL,
  save_raw = FALSE,
  raw_output_file = "raw_noise_values.csv",
  ...
)
```

Arguments

index_funs	An index function or a list of index functions. Each index function should take two numeric vectors as its first two arguments, for example `function(x, y) ...`.
n_sim	Number of noise simulations to run for each sample size.
n_start	Smallest sample size.
n_end	Largest sample size.
step	Step size between sample sizes. Default is 25.
settings	A named list of settings. Each setting should be a list of arguments passed to the index functions. Default is `list(default = list())`.
seed	Random seed used for reproducibility. Default is 1028.
workers	Number of parallel workers to use. Default is 1.
output_file	Optional file path for saving the summarized 95th percentile results as a CSV file. If NULL, results are not written to disk.
index_args	Optional named list of index-specific arguments. Each element should have the same name as an index in index_funs.
noise_fun	Optional function for generating noise data. The function should take the current sample size as input and return a numeric object with at least two columns. If NULL, independent Gaussian noise is used.
save_raw	Logical. If TRUE, saves the raw simulated index values before calculating the 95th percentile. Default is FALSE.
raw_output_file	File path for saving raw simulated values when `save_raw = TRUE`. Default is `"raw_noise_values.csv"`.
...	Additional arguments passed to all index functions.

Details

The default noise generator produces two independent standard normal variables. Users can provide their own noise generator through `noise_fun`. This is useful for comparing the behaviour of an index under different null distributions, such as uniform noise, heavy-tailed noise, or correlated noise.

If `output_file` is supplied, the summarized results are saved after each sample size. If `save_raw = TRUE`, the raw simulation results are also saved before summarisation.

Value

A tibble with one row for each sample size, setting, and index. The output contains:

sample_size The sample size used in the simulation.

setting The setting name.

index The index name.

p95 The estimated 95th percentile of the simulated noise values.

n_valid The number of non-missing index values.

n_sim The number of simulations requested.

Examples

```
## Not run:
# Estimate the 95th percentile for stringy05 under Gaussian noise
res <- ppi_noise_grid(
  index_funs = cassowaryr::sc_stringy05,
  n_sim = 100,
  n_start = 50,
  n_end = 150,
  step = 25
)

 Named list of index functions
res_named <- ppi_noise_grid(
  index_funs = list(
    stringy05 = cassowaryr::sc_stringy05,
    skinny = cassowaryr::sc_skinny
  ),
  n_sim = 100,
  n_start = 50,
  n_end = 150,
  step = 25
)

Custom uniform noise
uniform_noise <- function(n) {
  cbind(
    runif(n, -1, 1),
    runif(n, -1, 1)
  )
```

```
}

res_uniform <- ppi_noise_grid(
  index_funs = list(stringy05 = cassowaryr::sc_stringy05),
  n_sim = 100,
  n_start = 50,
  n_end = 150,
  noise_fun = uniform_noise
)

## End(Not run)
```

`ppi_noise_threshold` *Estimate the 95th Percentile of a Projection Pursuit Index Under Noise*

Description

This function estimates the 95th percentile of a projection pursuit index under synthetic noise data.

Usage

```
ppi_noise_threshold(
  index_fun,
  n_sim = 100,
  n_obs = 500,
  noise_type = "gaussian",
  noise_level = 0.01,
  seed = NULL
)
```

Arguments

`index_fun`	A function that takes either a 2-column matrix or two numeric vectors and returns a scalar index.
`n_sim`	Integer. Number of index evaluations to simulate. Default is 100.
`n_obs`	Integer. Number of observations per noise sample. Default is 500.
`noise_type`	Character. Type of noise to use (e.g., "gaussian", "t_distributed", etc.). Default is "gaussian".
`noise_level`	Numeric. Controls the scale/spread of the generated noise. Default is 0.01.
`seed`	Optional integer. Random seed for reproducibility.

Value

A single numeric value: the estimated 95th percentile of the index under noise.

Examples

```
ppi_noise_threshold(
  index_fun = scag_index("stringy"),
  noise_type = "cauchy",
  noise_level = 0.1,
  n_sim = 10,
  n_obs = 100
)
```

`ppi_samplesize_effect` *Simulate Effect of Sample Size on a Projection Pursuit Index*

Description

For a given index function, simulates how the index behaves across a range of sample sizes. By default, standard bivariate Gaussian noise is used, but the user may instead supply a 2-column dataset to sample from.

Usage

```
ppi_samplesize_effect(
  index_fun,
  sample_sizes = 100,
  n_sim = 100,
  data = NULL,
  csv_file = NULL,
  index_args = list(),
  workers = 1
)
```

Arguments

`index_fun`	A function returning a numeric scalar index. It may accept either a 2-column matrix/data frame, or two numeric vectors (`x`, `y`).
`sample_sizes`	Numeric vector (e.g., 100, c(50,100,200), seq(30,200,5)). Default is 100.
`n_sim`	Integer. Number of simulations per sample size.
`data`	Optional 2-column data frame, tibble, or matrix to sample from. If `NULL`, standard bivariate Gaussian noise is used.
`csv_file`	Optional file path to save results as CSV.
`index_args`	A named list of additional arguments passed to `index_fun`.
`workers`	Integer. Number of parallel workers to use. Default is 1.

Value

A tibble with:

- `sample_size`: sample size used for each simulation block
- `percentile95`: 95th percentile of the index values over simulations

Examples

```
## Not run:
ppi_samplesize_effect(
  cassowaryr::sc_stringy,
  sample_sizes = c(100, 300),
  n_sim = 3,
  index_args = list(binner = "hex"),
  workers = 2
)

ppi_samplesize_effect(
  cassowaryr::sc_skinny,
  sample_sizes = c(100, 300),
  n_sim = 3,
  data = data_gen("polynomial", degree = 2),
  workers = 2
)

## End(Not run)
```

---

ppi_scale *Simulate and Compare Index Scale on Structured vs Noisy Data*

Description

Performs simulations to compute a projection pursuit index on structured (sampled) data and on random noise, allowing a comparison of index scale across contexts.

Usage

```
ppi_scale(
  data,
  index_fun,
  noise_fun = NULL,
  n_sim = 100,
  n_obs = 500,
  index_args = list(),
  seed = NULL,
  workers = 1
)
```

Arguments

data	A data frame or tibble with at least two numeric columns.
index_fun	A function returning a numeric scalar index. It may accept either a 2-column matrix/data frame, or two numeric vectors (x, y).
noise_fun	Optional function for generating noise data. It should take n_obs as input and return a 2-column matrix or data frame. By default, standard bivariate Gaussian noise is used.
n_sim	Integer. Number of simulations. Default is 100.
n_obs	Integer. Number of observations per simulation. Default is 500.
index_args	A named list of additional arguments passed to index_fun.
seed	Optional integer seed for reproducibility.
workers	Integer. Number of parallel workers to use. Default is 1.

Value

A tibble with columns:

- simulation: simulation number
- var_i, var_j: variable names
- var_pair: pair name as a string
- sigma: "structure" for structured data, "noise" for noisy data
- index: index value returned by index_fun

Examples

```
ppi_scale(
  data_gen("polynomial", degree = 3),
  cassowaryr::sc_stringy,
  n_sim = 2,
  index_args = list(binner = "hex"),
  workers = 2
)

ppi_scale(
  data_gen("polynomial", degree = 3),
  scag_index("stringy"),
  n_sim = 2
)
```

`profile_rotation` *Test rotation invariance of index functions for selected 2-d data set.*

Description

Ideally a projection pursuit index should be roation invariant, we test this explicitly by profiling the index while rotating a distribution.

Usage

```
profile_rotation(d, index_list, index_labels, n = 200)
```

Arguments

`d`	data (2 column matrix containing distribution to be rotated)
`index_list`	list of index functions to calculate for each entry
`index_labels`	labels used in the output
`n`	number of steps in the rotation (default = 200)

Value

index values for each rotation step

Examples

```
d <- as.matrix(sin_data(30, 2))
index_list <- list(tourr::holes(), scag_index("stringy"), mine_indexE("MIC"))
index_labels <- c("holes", "stringy", "mic")
pRot <- profile_rotation(d, index_list, index_labels, n = 50)
plot_rotation(pRot)
```

`scag_index` *Matching index functions to the required format.*

Description

These are convenicence functions that format scagnostics and mine index functions for direct use with the guided tour or other functionalities in this package.

Usage

```
scag_index(index_name)

mine_index(index_name)

mine_indexE(index_name)

holesR()

cmassR()
```

Arguments

index_name	Index name to select from group of indexes.

Value

function taking 2-d data matrix and returning the index value

Functions

- `scag_index()`: Scagnostics index from cassowaryr package
- `mine_index()`: MINE index from minerva package
- `mine_indexE()`: MINE index from minerva package (updated estimator)
- `holesR()`: rescaling the tourr holes index
- `cmassR()`: rescaling the tourr cmass index

---

sin_data *Generating sine wave sample*

Description

n-1 points are drawn from a normal distribution with mean=0, sd=1, the points in the final direction are calculated as the sine of the values of direction n-1 with additional jittering controled by the jitter factor f.

Usage

```
sin_data(n, p, f = 1)
```

Arguments

n	number of sample points to generate
p	sample dimensionality
f	jitter factor, default=1

Value

sample points in tibble format

Examples

```
sin_data(100, 4)
sin_data(100, 2, 200)
```

---

spiral_data *Generating spiral sample*

Description

n-2 points are drawn from a normal distribution with mean=0, sd=1, the points in the final two direction are sampled along a spiral by samping the angle from a normal distribution with mean=0, sd=2*pi (absolute values are used to fix the orientation of the spiral).

Usage

```
spiral_data(n, p)
```

Arguments

n	number of sample points to generate
p	sample dimensionality

Value

sample points in matrix format

Examples

```
spiral_data(100, 4)
```

`squint_angle_estimate` *Estimating squint angle of 2-d structure in high-d dataset under selected index.*

Description

We estimate the squint angle by interpolating from a random starting plane towards the optimal view until the index value of the selected index function is above the selected cutoff. Since this depends on the direction, this is repeated with n randomly selected planes giving a distribution representative of the squint angle.

Usage

```
squint_angle_estimate(
  data,
  indexF,
  cutoff,
  structure_plane,
  n = 100,
  step_size = 0.01
)
```

Arguments

`data`	Input data
`indexF`	Index function
`cutoff`	Threshold index value above which we assume the structure to be visible
`structure_plane`	Plane defining the optimal view
`n`	Number of random starting planes (default = 100)
`step_size`	Interpolation step size fixing the accuracy (default = 0.01)

Value

numeric vector containing all squint angle estimates

Examples

```
data <- spiral_data(50, 4)
indexF <- scag_index("stringy")
cutoff <- 0.7
structure_plane <- basis_matrix(3,4,4)
squint_angle_estimate(data, indexF, cutoff, structure_plane, n=1)
```

`time_sequence` *Time each index evaluation for projections in the tour path.*

Description

Index evaluation timing may depend on the data distribution, we evaluate the computing time for a set of different projections to get an overview of the distribution of computing times.

Usage

```
time_sequence(d, t, idx, pmax)
```

Arguments

`d`	Input data in matrix format
`t`	List of projection matrices (e.g. interpolated tour path)
`idx`	Index function
`pmax`	Maximum number of projections to evaluate (cut t if longer than pmax)

Value

numeric vector containing all distances

Examples

```
d <- as.matrix(spiral_data(500, 4))
t <- purrr::map(1:10, ~ tourr::basis_random(4))
idx <- scag_index("stringy")
time_sequence(d, t, idx, 10)
```

Index

basis_matrix, 2
basis_vector, 3

cmassR *(*scag_index*)*, 19
compare_smoothing, 3

data_gen, 4
distance_dist, 5
distance_to_sp, 6

get_index_mean, 6
get_trace, 7, *11*

holesR *(*scag_index*)*, 19

jitter_angle, 8
jitter_points, 8

mine_index *(*scag_index*)*, 19
mine_indexE *(*scag_index*)*, 19

noise_gen, 9

pipe_data, 10
plot_rotation, 10
plot_smoothing_comparison, 11
plot_trace, 11
ppi_mean, 12
ppi_noise_grid, 12
ppi_noise_threshold, 15
ppi_samplesize_effect, 16
ppi_scale, 17
profile_rotation, 19

scag_index, 19
sin_data, 20
spiral_data, 21
squint_angle_estimate, 22

time_sequence, 23