

Package: standartox (via r-universe)

May 26, 2026

Version 0.0.2

Date 2022-08-08

Title Ecotoxicological Information from the Standartox Database

Maintainer Andreas Scharmüller <andschar@protonmail.com>

Description The <<http://standartox.uni-landau.de>> database offers cleaned, harmonized and aggregated ecotoxicological test data, which can be used for assessing effects and risks of chemical concentrations found in the environment.

Depends R (>= 3.5.0)

Imports stats, httr (>= 1.4.1), jsonlite (>= 1.6.1), fst (>= 0.9.4), data.table (>= 1.13.0)

License MIT + file LICENSE

URL <https://github.com/andschar/standartox>

BugReports <https://github.com/andschar/standartox/issues>

RoxygenNote 7.1.2

Encoding UTF-8

NeedsCompilation no

Author Andreas Scharmüller [aut, cre]
(<<https://orcid.org/0000-0002-9290-3965>>)

Repository <https://cran.r-universe.dev>

Date/Publication 2022-08-08 10:00:02 UTC

RemoteUrl <https://github.com/cran/standartox>

RemoteRef HEAD

RemoteSha a9e3f3265f89190eb8330f10289b4101595bc3ad

Contents

| | |
|-------------|---|
| stx_catalog | 2 |
| stx_chem | 2 |
| stx_query | 3 |
| stx_taxa | 5 |

Index**6**

| | |
|-------------|------------------------------|
| stx_catalog | <i>Retrieve data catalog</i> |
|-------------|------------------------------|

Description

Retrieve a data catalog for all variables (and their values) that can be retrieved with stx_query()

Usage

```
stx_catalog(vers = NULL)
```

Arguments

| | |
|------|--|
| vers | integer; Choose the version of the EPA Ecotox on which Standartox is based on. NULL (default) accesses the most recent version |
|------|--|

Value

Returns a list of data.frames containing information on data base variables

Author(s)

Andreas Scharm Mueller <andschar@protonmail.com>

Examples

```
# might fail if API is not available  
stx_catalog()
```

| | |
|----------|-------------------------------|
| stx_chem | <i>Retrieve chemical data</i> |
|----------|-------------------------------|

Description

Retrieve data on all chemicals in Standartox.

Usage

```
stx_chem()
```

Value

Returns a data.table containing information on chemicals in Standartox.

Author(s)

Andreas Scharmueller <andschar@protonmail.com>

Examples

```
# might fail if API is not available
stx_chem()
```

stx_query

Retrieve Standartox toxicity values

Description

Retrieve toxicity values from the Standartox data base <http://standartox.uni-landau.de/>.

Usage

```
stx_query(
  cas = NULL,
  concentration_unit = NULL,
  concentration_type = NULL,
  duration = NULL,
  endpoint = c("XX50", "NOEX", "LOEX"),
  effect = NULL,
  exposure = NULL,
  chemical_role = NULL,
  chemical_class = NULL,
  taxa = NULL,
  ecotox_grp = NULL,
  trophic_lvl = NULL,
  habitat = NULL,
  region = NULL,
  vers = NULL,
  ...
)
```

Arguments

cas character, integer; Limit data base query to specific CAS numbers, multiple entries possible (e.g. 1071-83-6, 1071836), NULL (default).

concentration_unit character; Limit data base query to specific concentration units (e.g. ug/l - default).

| | |
|--------------------|---|
| concentration_type | character; Limit data base query to specific concentration types, can be one of NULL (default), 'active ingredient', 'formulation', 'total', 'not reported', 'unionized', 'dissolved', 'labile'. See https://cfpub.epa.gov/ecotox/pdf/codeappendix.pdf p.4. |
| duration | integer vector of length two; Limit data base query to specific test durations (hours) (e.g. c(24, 48)). NULL (default). |
| endpoint | character; Choose endpoint type, must be one of 'XX50' (default), 'NOEX', 'LOEX'. |
| effect | character; Limit data base query to specific effect groups, multiple entries possible (e.g. 'Mortality', 'Intoxication', 'Growth'). See https://cfpub.epa.gov/ecotox/pdf/codeappendix.pdf p.95. NULL (default). |
| exposure | character; Choose exposure type, (e.g. aquatic, environmental, diet). NULL (default). |
| chemical_role | character; Limit data base query to specific chemical roles (e.g. insecticide), multiple entries possible. NULL (default). |
| chemical_class | character; Limit data base query to specific chemical classes (e.g. neonicotinoid), multiple entries possible. NULL (default). |
| taxa | character; Limit data base query to specific taxa, multiple entries possible. NULL (default). |
| ecotox_grp | character; Convenience grouping of organisms in ecotoxicology, must be one of NULL (default), 'invertebrate', 'fish', 'plant_land', 'macrophyte', 'algae'. |
| trophic_lvl | character; Trophic level of organism, must be one of NULL (default), 'autotroph', 'heterotroph'. |
| habitat | character; Limit data base query to specific organism habitats, can be one of NULL (default) 'marine', 'brackish', 'freshwater', 'terrestrial'. |
| region | character; Limit data base query to organisms occurring in specific regions, can be one of NULL (default) 'africa', 'america_north', 'america_south', 'asia', 'europe', 'oceania'. |
| vers | integer; Choose the version of the EPA Ecotox on which Standartox is based on. NULL (default) accesses the most recent version. |
| ... | currently not used |

Value

Returns a list of three data.tables (filtered data base query results, aggregated data base query results, meta information)

Author(s)

Andreas Scharmueller <andschar@protonmail.com>

Examples

```
# might fail if API is not available
stx_query('1071-83-6')
stx_query(cas = '1071-83-6',
          duration = c(48, 120),
          concentration_unit = 'ug/l')
stx_query(cas = '1071-83-6',
          duration = c(48, 120),
          concentration_unit = 'ug/l',
          endpoint = 'XX50')
```

| | |
|----------|---------------------------|
| stx_taxa | <i>Retrieve taxa data</i> |
|----------|---------------------------|

Description

Retrieve data on all taxa in Standartox.

Usage

```
stx_taxa()
```

Value

Returns a data.table containing information on taxa in Standartox.

Author(s)

Andreas Scharm Mueller <andschar@protonmail.com>

Examples

```
# might fail if API is not available
stx_taxa()
```

Index

stx_catalog, [2](#)
stx_chem, [2](#)
stx_query, [3](#)
stx_taxa, [5](#)