

# Package: sundialr (via r-universe)

July 3, 2024

**Type** Package

**Title** An Interface to 'SUNDIALS' Ordinary Differential Equation (ODE) Solvers

**Version** 0.1.4.2

**Maintainer** Satyaprakash Nayak <satyaprakash.nayak@gmail.com>

**URL** <https://github.com/sn248/sundialr>

**BugReports** <https://github.com/sn248/sundialr/issues>

**Description** Provides a way to call the functions in 'SUNDIALS' C ODE solving library (<https://computing.llnl.gov/projects/sundials>). Currently the serial version of ODE solver, 'CVODE', sensitivity calculator 'CVODES' and differential algebraic solver 'IDA' from the 'SUNDIALS' library are implemented. The package requires ODE to be written as an 'R' or 'Rcpp' function and does not require the 'SUNDIALS' library to be installed on the local machine.

**License** BSD\_3\_clause + file LICENSE

**Copyright** file COPYRIGHTS

**Imports** Rcpp (>= 1.0.12)

**LinkingTo** Rcpp, RcppArmadillo

**RoxygenNote** 7.3.1

**Suggests** knitr, rmarkdown, testthat

**SystemRequirements** GNU make

**NeedsCompilation** yes

**VignetteBuilder** knitr

**Author** Satyaprakash Nayak [aut, cre, cph]  
(<https://orcid.org/0000-0001-7225-1317>), Lawrence Livermore National Security [cph], Southern Methodist University [cph]

**Repository** CRAN

**Date/Publication** 2024-07-02 06:10:02 UTC

## Contents

cvode . . . . .	2
cvodes . . . . .	4
cvsolve . . . . .	6
ida . . . . .	7
<b>Index</b>	<b>9</b>

---

cvode	<i>cvode</i>
-------	--------------

---

### Description

CVODE solver to solve stiff ODEs

### Usage

```
cvode(
  time_vector,
  IC,
  input_function,
  Parameters,
  reltolerance = 1e-04,
  abstolerance = 1e-04
)
```

### Arguments

time_vector	time vector
IC	Initial Conditions
input_function	Right Hand Side function of ODEs
Parameters	Parameters input to ODEs
reltolerance	Relative Tolerance (a scalar, default value = 1e-04)
abstolerance	Absolute Tolerance (a scalar or vector with length equal to ydot (dy/dx), default = 1e-04)

### Value

A data frame. First column is the time-vector, the other columns are values of y in order they are provided.

**Examples**

```

# Example of solving a set of ODEs with cvode function
# ODEs described by an R function
ODE_R <- function(t, y, p){

  # vector containing the right hand side gradients
  ydot = vector(mode = "numeric", length = length(y))

  # R indices start from 1
  ydot[1] = -p[1]*y[1] + p[2]*y[2]*y[3]
  ydot[2] = p[1]*y[1] - p[2]*y[2]*y[3] - p[3]*y[2]*y[2]
  ydot[3] = p[3]*y[2]*y[2]

  # ydot[1] = -0.04 * y[1] + 10000 * y[2] * y[3]
  # ydot[3] = 30000000 * y[2] * y[2]
  # ydot[2] = -ydot[1] - ydot[3]

  ydot

}

# ODEs can also be described using Rcpp
Rcpp::sourceCpp(code = '

#include <Rcpp.h>
using namespace Rcpp;

// ODE functions defined using Rcpp
// [[Rcpp::export]]
NumericVector ODE_Rcpp (double t, NumericVector y, NumericVector p){

  // Initialize ydot filled with zeros
  NumericVector ydot(y.length());

  ydot[0] = -p[0]*y[0] + p[1]*y[1]*y[2];
  ydot[1] = p[0]*y[0] - p[1]*y[1]*y[2] - p[2]*y[1]*y[1];
  ydot[2] = p[2]*y[1]*y[1];

  return ydot;

}')

# R code to generate time vector, IC and solve the equations
time_vec <- c(0.0, 0.4, 4.0, 40.0, 4E2, 4E3, 4E4, 4E5, 4E6, 4E7, 4E8, 4E9, 4E10)
IC <- c(1,0,0)
params <- c(0.04, 10000, 30000000)
reltol <- 1e-04
abstol <- c(1e-8,1e-14,1e-6)

## Solving the ODEs using cvode function

```

```
df1 <- ccode(time_vec, IC, ODE_R , params, reltol, abstol)      ## using R
df2 <- ccode(time_vec, IC, ODE_Rcpp , params, reltol, abstol)  ## using Rcpp

## Check that both solutions are identical
# identical(df1, df2)
```

---

 cvodes

*cvodes*


---

## Description

CVODES solver to solve ODEs and calculate sensitivities

## Usage

```
cvodes(
  time_vector,
  IC,
  input_function,
  Parameters,
  reltolerance = 1e-04,
  abstolerance = 1e-04,
  SensType = "STG",
  ErrCon = "F"
)
```

## Arguments

time_vector	time vector
IC	Initial Conditions
input_function	Right Hand Side function of ODEs
Parameters	Parameters input to ODEs
reltolerance	Relative Tolerance (a scalar, default value = 1e-04)
abstolerance	Absolute Tolerance (a scalar or vector with length equal to ydot, default = 1e-04)
SensType	Sensitivity Type - allowed values are Staggered (default)", "STG" (for Staggered) or "SIM" (for Simultaneous)
ErrCon	Error Control - allowed values are TRUE or FALSE (default)

## Value

A data frame. First column is the time-vector, the next  $y * p$  columns are sensitivities of  $y_1$  w.r.t all parameters, then  $y_2$  w.r.t all parameters etc.  $y$  is the state vector,  $p$  is the parameter vector

**Examples**

```

# Example of solving a set sensitivity equations for ODEs with cvodes function
# ODEs described by an R function
ODE_R <- function(t, y, p){

  # vector containing the right hand side gradients
  ydot = vector(mode = "numeric", length = length(y))

  # R indices start from 1
  ydot[1] = -p[1]*y[1] + p[2]*y[2]*y[3]
  ydot[2] = p[1]*y[1] - p[2]*y[2]*y[3] - p[3]*y[2]*y[2]
  ydot[3] = p[3]*y[2]*y[2]

  # ydot[1] = -0.04 * y[1] + 10000 * y[2] * y[3]
  # ydot[3] = 30000000 * y[2] * y[2]
  # ydot[2] = -ydot[1] - ydot[3]

  ydot

}

# ODEs can also be described using Rcpp
Rcpp::sourceCpp(code = '

#include <Rcpp.h>
using namespace Rcpp;

// ODE functions defined using Rcpp
// [[Rcpp::export]]
NumericVector ODE_Rcpp (double t, NumericVector y, NumericVector p){

// Initialize ydot filled with zeros
NumericVector ydot(y.length());

ydot[0] = -p[0]*y[0] + p[1]*y[1]*y[2];
ydot[1] = p[0]*y[0] - p[1]*y[1]*y[2] - p[2]*y[1]*y[1];
ydot[2] = p[2]*y[1]*y[1];

return ydot;

}')
```

```

# R code to generate time vector, IC and solve the equations
time_vec <- c(0.0, 0.4, 4.0, 40.0, 4E2, 4E3, 4E4, 4E5, 4E6, 4E7, 4E8, 4E9, 4E10)
IC <- c(1,0,0)
params <- c(0.04, 10000, 30000000)
reltol <- 1e-04
abstol <- c(1e-8,1e-14,1e-6)

## Solving the ODEs and Sensitivities using cvodes function

```

```
df1 <- cvodes(time_vec, IC, ODE_R , params, reltol, abstol,"STG",FALSE)      ## using R
df2 <- cvodes(time_vec, IC, ODE_Rcpp , params, reltol, abstol,"STG",FALSE)  ## using Rcpp

## Check that both solutions are identical
# identical(df1, df2)
```

---

cvsolve

*cvsolve*


---

## Description

CVSOLVE solver to solve stiff ODEs with discontinuities

## Usage

```
cvsolve(
  time_vector,
  IC,
  input_function,
  Parameters,
  Events = NULL,
  reltolerance = 1e-04,
  abstolerance = 1e-04
)
```

## Arguments

time_vector	time vector
IC	Initial Conditions
input_function	Right Hand Side function of ODEs
Parameters	Parameters input to ODEs
Events	Discontinuities in the solution (a DataFrame, default value is NULL)
reltolerance	Relative Tolerance (a scalar, default value = 1e-04)
abstolerance	Absolute Tolerance (a scalar or vector with length equal to ydot, default = 1e-04)

## Value

A data frame. First column is the time-vector, the other columns are values of  $y$  in order they are provided.

**Examples**

```

# Example of solving a set of ODEs with multiple discontinuities using cvsolve
# A simple One dimensional equation,  $y = -0.1 * y$ 
# ODEs described by an R function
ODE_R <- function(t, y, p){

  # vector containing the right hand side gradients
  ydot = vector(mode = "numeric", length = length(y))

  # R indices start from 1
  ydot[1] = -p[1]*y[1]

  ydot

}

# R code to generate time vector, IC and solve the equations
TSAMP <- seq(from = 0, to = 100, by = 0.1)      # sampling time points
IC <- c(1)
params <- c(0.1)

# A dataset describing the dosing at times at which additions to y[1] are to be done
# Names of the columns don't matter, but they MUST be in the order of state index,
# times and Values at discontinuity.
TDOSE <- data.frame(ID = 1, TIMES = c(0, 10, 20, 30, 40, 50), VAL = 100)
df1 <- cvsolve(TSAMP, c(1), ODE_R, params)      # solving without any discontinuity
df2 <- cvsolve(TSAMP, c(1), ODE_R, params, TDOSE) # solving with discontinuity

```

---

ida

---

ida

---

**Description**

IDA solver to solve stiff DAEs

**Usage**

```

ida(
  time_vector,
  IC,
  IRes,
  input_function,
  Parameters,
  reltolerance = 1e-04,
  abstolerance = 1e-04
)

```

**Arguments**

time_vector	time vector
IC	Initial Value of y
IRes	Initial Value of ydot
input_function	Right Hand Side function of DAEs
Parameters	Parameters input to ODEs
reltolerance	Relative Tolerance (a scalar, default value = 1e-04)
abstolerance	Absolute Tolerance (a scalar or vector with length equal to ydot, default = 1e-04)

**Value**

A data frame. First column is the time-vector, the other columns are values of y in order they are provided.



# Index

cvode, [2](#)  
cvodes, [4](#)  
cvsolve, [6](#)  
  
ida, [7](#)