

# survSNP: Power and Sample Size Calculations for SNP Association Studies with Censored Time to Event Outcomes

Kouros Owzar      Zhiguo Li      Nancy Cox      Sin-Ho Jung  
Chanhee Yi

October 11, 2024

## 1 Introduction

This vignette serves as a tutorial for using the `survSNP` extension package for conducting power and sample size calculations for SNP association studies with censored time to event outcomes. We begin by loading the package.

```
library(survSNP)

## Loading required package: survival
## Loading required package: Rcpp
## Loading required package: lattice
## Loading required package: foreach
## Loading required package: xtable
```

## 2 Example 1

In this example, we conduct power calculations for a SNP for which the relative allelic frequency for the risk allele  $B$  is  $q = 0.1$ . The validation data set is assumed to consist of  $n = 500$  patients. The event rate (e.g., death rate) is assumed to be  $\rho = 0.75$  (i.e., 375 events among 500 patients). We hypothesize an effect size (genotype hazard ratio)  $\Delta = 1.25$ .

Finally, we assume that the median in the population is 1 unit of time (i.e.,  $P(\tilde{T} > t) = 0.5$ ). To find the asymptotic power, at the two-sided  $\alpha = 0.05$  level, the `sim.snp.expsurv.power` function is used.

```
res1<-sim.snp.expsurv.power(1.25, n=500, raf=0.1, erate=0.75,
                           pilm=0.5, lm=1, B=0,
                           model="additive",test="additive",alpha=0.05)
```

Below, we show some of the relevant columns from the output.

```
res1[,c("n", "GHR", "erate", "raf", "B", "alpha", "pow0", "pow", "powB")]

##           n  GHR erate raf B alpha      pow0 pow powB
## power 500 1.25  0.75 0.1 0  0.05 0.4706994 NA  NA
```

The asymptotic power, at the two-sided  $\alpha = 0.05$  level, is 0.47. Note that we are assuming that the median for the survival function in the population is 1 unit of time (that is why we have set `pilm=0.5` and `lm=1`). If we had desired to set power the study based on a population whose 0.7 quantile is say 2 units of time, we would have set `pilm=0.7` and `lm=2`. The current version of the package supports power calculations for additive models.

By default, the asymptotic power based on the approximate asymptotic variance formula is computed. The corresponding column name is `pow0` in the output shown above. The asymptotic power based on the exact variance formula (column `pow`) or the empirical power (column `powB`) can be computed by setting the arguments `exactvar=TRUE` or `B=b` where `b` is a positive integer. Be sure to set a random number generation seed when calculating the empirical or the asymptotic power based on the exact variance formula to get reproducible results. We illustrate these features next. This example is based on  $B = 10000$  simulation replicates.

```
set.seed(123)
res1b<-sim.snp.expsurv.power(1.25, n=500, raf=0.25, erate=0.75,
                             pilm=0.5, lm=1,
                             exactvar=TRUE,B=10000,
                             model="additive",test="additive",alpha=0.05)
```

The results are shown below.

```
res1b[,c("n", "GHR", "erate", "raf", "B", "alpha", "pow0", "pow", "powB")]

##           n  GHR erate raf      B alpha      pow0      pow  powB
## power 500 1.25  0.75 0.25 10000 0.05 0.749999 0.769836 0.7556
```

### 3 Example 2

For power calculations for SNP association studies with censored outcomes, it is generally desired to vary the effect size, sample size, event rate and the relative minor allele frequency. These are denoted by the variable names `GHRs`, `ns`, `rafs` and `erates` in this example.

```
GHRs<-seq(1.05,1.5,by=0.05)
ns<-c(100,500,700)
rafs<-c(0.1,0.3,0.5)
erates<-c(0.5,0.7,0.9)
```

The function `survSNP.power.table` can be used to generate power calculations for this combination of parameters. This is a wrapper function for `sim.snp.expsurv.power`.

```
res2<-survSNP.power.table(GHRs,ns,rafs,erates,
                           pilm=0.5,lm=1,
                           model="additive",test="additive",
                           alpha=0.05)
```

We print selected columns from the first three rows of the previous object next.

```
res2[1:3,c("n","GHR","erate","raf","pow0","pow","powB")]

##           n  GHR  erate  raf      pow0  pow  powB
## power    100 1.05   0.5 0.1 0.05719290  NA   NA
## power1   100 1.05   0.7 0.1 0.05819468  NA   NA
## power2   100 1.05   0.9 0.1 0.05917498  NA   NA
```

Next, we will consider illustrating the previous set of results using the `lattice` package. The power is illustrated in Figure 1. A revised version of this illustration limiting the presentation to  $n = 100$  and displaying the type I error rate  $\alpha$  is shown in Figure 2.

### 4 Example 3

We can also use the `xtable` package to summarize the results in a table. For this illustration, we consider a subset of the rows from Example 2.

```
cols<-c("n","GHR","erate","raf","pow0")
res3<-subset(res2,GHR==1.25&raf==0.3&n==500,select=cols)
res3
```

```
##           n  GHR  erate raf      pow0
## power314  500  1.25   0.5 0.3 0.6407236
## power1114 500  1.25   0.7 0.3 0.7694030
## power2114 500  1.25   0.9 0.3 0.8515087
```

The corresponding table generated by `xtable` is shown in Table 1.

```
print(xtable(res3,digits=c(0,0,1,1,1,3)),
      include.rownames=FALSE,floating=FALSE)
```

n	GHR	erate	raf	pow0
500	1.2	0.5	0.3	0.641
500	1.2	0.7	0.3	0.769
500	1.2	0.9	0.3	0.852

Table 1: Tabular summary of the results from Example 2

## 5 Miscellaneous

The function `survSNP.power.table` is a straightforward implementation of nested `foreach` loops. In order to maintain reproducibility of the randomly generated simulations, the loops are executed sequentially. A vignette in the `doRNG` package provides simple examples of how the code could be modified to run in parallel, while maintaining reproducible random number generation <https://cran.r-project.org/web/packages/doRNG/vignettes/doRNG.pdf>. [The `doRNG` package itself is not required to implement this functionality]. Note that some consideration should be given as to which parameter(s) to parallelize across, in order to maximize use of available processing cores and minimize I/O overhead.

The `tikzDevice` and `latticeExtra` packages can be used to considerably refine the illustrations. The software development repository provides some examples [bitbucket.org/kowzar/survsnp/](http://bitbucket.org/kowzar/survsnp/).

The session information for this vignette is provided in Table 2

```

KEY=paste("q=", levels(factor(res2$raf)), sep="")
KEY<-list(lines=list(col=1:length(KEY), lty=1:length(KEY)),
          text=list(labels=paste("q=", levels(factor(res2$raf)), sep=""),
                    column=3))
print(xyplot(pow0~GHR|factor(erate)*factor(n), group=factor(raf),
            data=res2, type="l", lty=KEY$lines$lty, col=KEY$lines$col,
            key=KEY,
            xlab="Genotype Hazard Ratio", ylab="Power"))

```




Figure 1: Power Illustration for Example 1.

```

print(xyplot(pow0~GHR|factor(erate),group=factor(raf),
  data=subset(res2,n==ns[1]),
  type="l",lty=KEY$lines$lty,col=KEY$lines$col,
  key=KEY,
  xlab="Genotype Hazard Ratio",ylab="Power",
  sub=paste("n=",ns[1],", alpha=",round(unique(res2$alpha),2))))

```




Figure 2: Power Illustration for Example 1 (restricted to  $n = 100$ ).

- R version 4.4.1 (2024-06-14), x86\_64-pc-linux-gnu
- Locale: LC\_CTYPE=en\_US.UTF-8, LC\_NUMERIC=C, LC\_TIME=en\_US.UTF-8, LC\_COLLATE=C, LC\_MONETARY=en\_US.UTF-8, LC\_MESSAGES=en\_US.UTF-8, LC\_PAPER=en\_US.UTF-8, LC\_NAME=C, LC\_ADDRESS=C, LC\_TELEPHONE=C, LC\_MEASUREMENT=en\_US.UTF-8, LC\_IDENTIFICATION=C
- Time zone: Etc/UTC
- TZcode source: system (glibc)
- Running under: Ubuntu 24.04.1 LTS
- Matrix products: default
- BLAS: /usr/lib/x86\_64-linux-gnu/openblas-pthread/libblas.so.3
- LAPACK:  
/usr/lib/x86\_64-linux-gnu/openblas-pthread/libopenblas-p0.3.26.so ;  
LAPACK version3.12.0
- Base packages: base, datasets, grDevices, graphics, methods, stats, utils
- Other packages: Rcpp 1.0.13, foreach 1.5.2, lattice 0.22-6, survSNP 0.26, survival 3.7-0, xtable 1.8-4
- Loaded via a namespace (and not attached): Matrix 1.7-0, buildtools 1.0.0, codetools 0.2-20, compiler 4.4.1, evaluate 1.0.1, grid 4.4.1, highr 0.11, iterators 1.0.14, knitr 1.48, maketools 1.3.1, splines 4.4.1, sys 3.4.3, tools 4.4.1, xfun 0.48

Table 2: Session Information