

Package: svymargins (via r-universe)

July 6, 2026

Title Predictive Margins for Survey Analyses

Version 0.1.0

Author Tommi Härkänen [aut, cre]

Maintainer Tommi Härkänen <tommi.harkanen@thl.fi>

Depends R (>= 4.2.0)

Description Predictive margins like in the 'Stata' procedure 'margins'. This package is based on the `survey::svypredmean()` function. Supported regression analyses are based on `survey::svyglm()` and `svyVGAM::svy_vglm()` functions (for multinomial logistic regression models).

License GPL (>= 3)

Encoding UTF-8

Imports plyr, dplyr, stringr, survey, tidyselect, VGAM

Suggests knitr, rmarkdown, svyVGAM

VignetteBuilder knitr

Config/roxygen2/version 8.0.0

NeedsCompilation no

Repository <https://cran.r-universe.dev>

Date/Publication 2026-07-06 14:30:02 UTC

RemoteUrl <https://github.com/cran/svymargins>

RemoteRef HEAD

RemoteSha 6db19887a9f56213dfd7d13c98c0a4fe7f5e8a16

Contents

<code>asymm_ci</code>	2
<code>scenarios2group</code>	3
<code>svymargins</code>	4
<code>svymargins.default</code>	4
<code>svymargins.svy_vglm</code>	5
<code>svymargins.svyglm</code>	6

asymm_ci	<i>Helper function to convert symmetric probability scale confidence intervals into asymmetric</i>
----------	--

Description

Helper function to convert symmetric probability scale confidence intervals into asymmetric

Usage

```
asymm_ci(x, ci.level = 0.95)
```

Arguments

`x` Matrix with two columns as returned by `confint` function.

`ci.level` Default 0.95 for 95% confidence intervals.
The transformation is based on the logit transformation and the delta method.

Value

Matrix with two columns as returned by `confint` function.

Examples

```
library(survey)
library(dplyr)
library(svyVGAM)
n <- 1000
# Generate data:
set.seed(1234)
d <- data.frame(sex=factor(sample(c("M", "F"), n, replace=TRUE)),
               education=factor(sample(c("low", "middle", "high"), n, replace=TRUE)))
d <- d |>
  mutate(age=runif(n, 0, 40) + as.numeric(education) * 20,
         pr1=1,
         pr2=exp(-3 + 0.5 * as.numeric(education) + 0.05 * age),
         pr3=exp(1 + -0.5 * as.numeric(education) + 0.02 * age)) |>
  rowwise() |>
  mutate(y=which(rmultinom(1, 1, c(pr1, pr2, pr3))[,1] == 1)) |>
  ungroup() |>
  mutate(y=factor(y, levels=1:3, labels=LETTERS[1:3]))
# Create survey design:
my.svy <- svydesign(~ 1, weights=~ 1, data=d)
# Run regression analysis:
res <- svy_vglm(y ~ education + age + sex, family=multinomial(refLevel=1), design=my.svy)
# Define margins as a named list:
target.l <- list(null=list(),
                educ=list("education"),
```

```

      age=list(age=seq(40,70,10)),
      educ_age=list("education", age=seq(40,70,10)))
# Calculate predictive margins:
marg <- svymargins(res, groupfactor=target.l, y.lev=2)
confint(marg)
confint(marg) |> asymm_ci()

```

scenarios2group	<i>Specify constraints for selected covariates for predicted margins</i>
-----------------	--

Description

Specify constraints for selected covariates for predicted margins

Usage

```
scenarios2group(scenarios, dat)
```

Arguments

scenarios	A (named) list of scenarios based on factor and/or continuous covariates.
dat	A dataframe containing the covariates.

Details

All combinations of the specified covariates are returned as a dataframe. If the list contains more than one element, then the dataframes based on the elements are returned, and binded together. if scenarios is a named list, then the returned dataframe has column group_id containing the list names.

Value

A dataframe containing the combinations of the specified covariates.

Examples

```

n <- 1000
d <- data.frame(sex=factor(sample(c("M", "F"), n, replace=TRUE)),
               age=runif(20, 100, n),
               education=factor(sample(c("low", "middle", "high"), n, replace=TRUE)),
               y=rnorm(n))
target.l <- list(null=list(), educ=list("education"), age=list(age=seq(40,70,10)),
                educ_age=list("education", age=seq(40,70,10)))
scenarios2group(target.l, d)

```

svymargins	<i>Generic function for svymargins</i>
------------	--

Description

Generic function for svymargins

Usage

```
svymargins(adjustmodel, ...)
```

Arguments

adjustmodel	A regression analysis result object.
...	Other arguments See other methods for different regression analyses.

Value

As svypredmeans, an object of class svystat with the predictive marginal means and their covariance matrix. Additional attribute: groups, which contains dataframe with the groupfactor variable values, and the estimated margins and standard errors.

svymargins.default	<i>The default method for svymargins</i>
--------------------	--

Description

The default method for svymargins

Usage

```
## Default S3 method:  
svymargins(adjustmodel, ...)
```

Arguments

adjustmodel	A regression analysis result object.
...	Other arguments Executed for regression analyses, which have not been implemented.

Value

An error message.

See Also

svymargins.svyglm, svymargins.svy_vglm

svymargins.svy_vglm *Predictive margins for multinomial logistic regression model*

Description

Predictive margins for multinomial logistic regression model

Usage

```
## S3 method for class 'svy_vglm'
svymargins(adjustmodel, ..., groupfactor, y.lev = NULL, subs = NULL)
```

Arguments

adjustmodel	Result of regression analysis object from the survey::svyglm function.
...	Currently unused.
groupfactor	Specification of the margins: Character vector of factor variable names or a list. See details and examples.
y.lev	Output category (name or number of level) for which margins are calculated.
subs	Character string specifying a subset, e.g. "age < 50 & year == 2015".

Details

groupfactor is a list specifying several margins specifications. The list can contain one or more lists. A list can contain the names of factor covariates (as character strings) and/or continuous covariates as named vectors containing the desired values at which to calculate the margins.

Value

As svypredmeans, an object of class svystat with the predictive marginal means and their covariance matrix. Additional attribute: groups, which contains dataframe with the groupfactor variable values, and the estimated margins and standard errors. The result of svymargins is named based on the groupfactor, but if there are duplicates, then the result is unnamed.

Examples

```
library(survey)
library(dplyr)
library(svyVGAM)
n <- 1000
# Generate data:
set.seed(1234)
d <- data.frame(sex=factor(sample(c("M", "F"), n, replace=TRUE)),
                education=factor(sample(c("low", "middle", "high"), n, replace=TRUE)))
```

```
d <- d |>
  mutate(age=runif(n, 0, 40) + as.numeric(education) * 20,
         pr1=1,
         pr2=exp(-3 + 0.5 * as.numeric(education) + 0.05 * age),
         pr3=exp(1 + -0.5 * as.numeric(education) + 0.02 * age)) |>
  rowwise() |>
  mutate(y=which(rmultinom(1, 1, c(pr1, pr2, pr3))[,1] == 1)) |>
  ungroup() |>
  mutate(y=factor(y, levels=1:3, labels=LETTERS[1:3]))
# Create survey design:
my.svy <- svydesign(~ 1, weights=~ 1, data=d)
# Run regression analysis:
res <- svy_vglm(y ~ education + age + sex, family=multinomial(refLevel=1), design=my.svy)
# Define margins as a named list:
target.l <- list(null=list(),
                educ=list("education"),
                age=list(age=seq(40,70,10)),
                educ_age=list("education", age=seq(40,70,10)))
# Calculate predictive margins:
svymargins(res, groupfactor=target.l, y.lev=2)
# Get the output table containing the covariate information from "groups" attribute:
attr(svymargins(res, groupfactor=target.l, y.lev="B"), "groups")
```

svymargins.svyglm	<i>Mimics the margins procedure of Stata for GLM estimated with survey::svyglm</i>
-------------------	--

Description

Based on the survey::svypredmeans function, but is more flexible. No restrictions with interactions. Implements also subsets with the subs argument.

Usage

```
## S3 method for class 'svyglm'
svymargins(adjustmodel, ..., groupfactor, y.lev = NULL, subs = NULL)
```

Arguments

adjustmodel	Result of regression analysis object from the survey::svyglm function.
...	Currently unused.
groupfactor	Specification of the margins: Character vector of factor variable names or a list. See details and examples.
y.lev	Not currently used in svyglm models.
subs	Character string specifying a subset, e.g. "age < 50 & year == 2015".

Details

groupfactor is a list specifying several margins specifications. The list can contain one or more lists. A list can contain the names of factor covariates (as

character strings) and/or continuous covariates as named vectors containing the desired values at which to calculate the margins.

Value

As svypredmeans, an object of class svystat with the predictive marginal means and their covariance matrix. Additional attribute: groups, which contains dataframe with the groupfactor variable values, and the estimated margins and standard errors. The result of svymargins is named based on the groupfactor, but if there are duplicates, then the result is unnamed.

Examples

```
library(survey)
library(dplyr)
n <- 1000
# Generate data:
set.seed(1234)
d <- data.frame(sex=factor(sample(c("M", "F"), n, replace=TRUE)),
                education=factor(sample(c("low", "middle", "high"), n, replace=TRUE)))
d <- d |> mutate(age=runif(n, 0, 40) + as.numeric(education) * 20,
                y=rnorm(n, sd=5) + as.numeric(education) + 0.05 * age)
# Create survey design:
my.svy <- svydesign(~ 1, weights=~ 1, data=d)
# Run regression analysis:
res <- svyglm(y ~ education + age + sex, design=my.svy)
# Define margins as a named list:
target.l <- list(null=list(),
                educ=list("education"),
                age=list(age=seq(40,70,10)),
                educ_age=list("education", age=seq(40,70,10)))
# Calculate predictive margins:
svymargins(res, groupfactor=target.l)
# Get the output table containing the covariate information from "groups" attribute:
attr(svymargins(res, groupfactor=target.l), "groups")
```

Index

`asymm_ci`, [2](#)

`scenarios2group`, [3](#)

`svymargins`, [4](#)

`svymargins.default`, [4](#)

`svymargins.svy_vglm`, [5](#)

`svymargins.svyglm`, [6](#)