Package: sysbreak (via r-universe)

October 31, 2026

Title Structural Breaks in a System of Equations

Version 1.1.0

Maintainer Zhongjun Qu <qu@bu.edu>

Description Methods for detecting, estimating, and conducting inference on multiple structural breaks in a linear system of equations, such as multivariate linear regressions, seemingly unrelated regressions, vector autoregressions, and network vector autoregressions. Breaks can occur in the regression coefficients, the covariance matrix of the errors, or both, and can be restricted to a subset of the coefficients. The main function, sysbreak(), returns the number of breaks detected and confidence intervals for the break dates and for the regression coefficients. A separate function ordbreak() estimates ordered breaks, in which a break in one subset of equations occurs before a break in another. Specialized functions for vector autoregressions varbreak() and network vector autoregressions netbreak() are also provided. Reference: Qu, Z., and Perron, P. (2007). 'Estimating and Testing Structural Changes in Multivariate Regressions.' Econometrica, 75(2), 459-502.

License GPL (>= 3)

Depends R (>= 4.3.0)

Suggests knitr, rmarkdown, testthat (>= 3.0.0)

VignetteBuilder knitr

Encoding UTF-8

NeedsCompilation no

RoxygenNote 7.3.2

Imports graphics, grDevices, MASS, stats, utils

Config/testthat/edition 3

LazyData true

Author Zhongjun Qu [aut, cre], Cheolju Kim [aut], Pierre Perron [aut]

Repository https://cran.r-universe.dev

Date/Publication 2026-10-31 17:50:35 UTC

RemoteUrl https://github.com/cran/sysbreak

RemoteRef HEAD

RemoteSha e3d2591fdee06ca256e6a4ed38b29c08f3e15613

Contents

brtype . . . 2
data1 . . . 3
data2 . . . 4
dynobreak . . . 5
dyspill . . . 6
housing . . . 8
inflation . . . 9
netbreak . . . 9
netsim . . . 13
ordbreak . . . 14
ordcheck . . . 16
plot.sysbreak . . . 17
summary.sysbreak . . . 18
sysbreak . . . 19
sysbreak-methods . . . 22
varbreak . . . 24

Index **28**

`brtype` *Methods to Examine What Changes at Each Break Date*

Description

For each estimated break date, tests whether the volatilities, the correlations and the regression coefficients differ between the two regimes on either side of it.

Usage

```
brtype(fit)
```

Arguments

`fit`	A result from `sysbreak`, `varbreak` or `netbreak` with at least one break.

Details

The volatility statistic is a two-sample Hotelling (1931) statistic on the squared residuals. The correlation statistic is the Jennrich (1970) test for equal correlation matrices, which assumes normal errors. The coefficient statistic is a Wald test for equal coefficients; it covers only the coefficients allowed to change, and is `NA` when no coefficient is allowed to change. Each test compares the two regimes adjacent to a break and treats the break dates as known.

The coefficient test holds the error covariance constant across regimes, even when `fit` allows it to break (`brv = TRUE`). Estimating the covariance separately in each regime would make the test oversized in samples of typical length; the constant covariance tends to make it conservative when the volatility does change.

Value

A data frame with one row per break: `breaks`, the break date as a row of the data; the statistics `volatility`, `correlation` and `coefficients`; and their p-values `volatility_p`, `correlation_p` and `coefficients_p`. The degrees of freedom are n, $n(n-1)/2$ and the number of coefficients allowed to change.

References

Hotelling, H. (1931). The generalization of Student's ratio. *The Annals of Mathematical Statistics*, 2(3), 360-378.

Jennrich, R. I. (1970). An asymptotic chi-square test for the equality of two correlation matrices. *Journal of the American Statistical Association*, 65, 904-912.

Examples

```
set.seed(11)
bigt <- 120
x <- rnorm(bigt)
y1 <- 1 + 0.4 * x + rnorm(bigt, sd = 0.3)
y2 <- -0.5 + 0.2 * x + rnorm(bigt, sd = 0.3)
y1[61:120] <- y1[61:120] + 1.2 - 0.6 * x[61:120]
dat <- data.frame(y1 = y1, y2 = y2, x = x)

fit <- sysbreak(cbind(y1, y2) ~ x, data = dat, m = 2, trim = 0.2)
brtype(fit)
```

---

data1 *GAUSS/MATLAB Example Data 1*

Description

Example data used by the original GAUSS/MATLAB `mbreak2` script. In this package the corresponding procedure is `sysbreak`.

Usage

```
data1
```

Format

A numeric matrix with 150 rows and 5 columns. Columns 1 and 2 are dependent variables, and columns 3 through 5 are regressors.

Source

Qu, Z., and Perron, P. (2007). Estimating and testing structural changes in multivariate regressions. *Econometrica*, 75(2), 459-502.

---

data2 *GAUSS/MATLAB Example Data 2*

Description

Example data used by the original GAUSS/MATLAB `obreak2` script for the ordered-break procedure.

Usage

```
data2
```

Format

A numeric matrix with 100 rows and 5 columns. Columns 1 and 2 are dependent variables, and columns 3 through 5 are regressors.

Source

Qu, Z., and Perron, P. (2007). Estimating and testing structural changes in multivariate regressions. *Econometrica*, 75(2), 459-502.

dynobreak *Diebold-Yilmaz Spillover Measures Without Breaks*

Description

Fits a VAR by OLS on the whole sample and computes the generalized spillover measures of `dyspill()`, for comparison with the measures of a model with breaks.

Usage

```
dynobreak(y, lags, h, intercept = TRUE)
```

Arguments

`y`	Numeric matrix, one column per variable.
`lags`	Positive integer number of lags.
`h`	Positive integer forecast horizon.
`intercept`	Logical; include an intercept.

Value

A list with the row-normalized generalized `fevd`, the total spillover index `total`, and the directional vectors `from`, `to` and `net`. The covariance divides by the number of observations.

Examples

```
set.seed(1)
bigt <- 120
a <- matrix(c(0.2, 0.4, 0.4, 0.2), 2)
y <- matrix(0, bigt, 2)
colnames(y) <- c("y1", "y2")
for (tt in 2:bigt) {
  y[tt, ] <- a %*% y[tt - 1, ] + rnorm(2, sd = 0.3)
}

sp <- dynobreak(y, lags = 1, h = 10)
sp$total
sp$net
```

`dyspill` *Diebold-Yilmaz Generalized Spillover Measures*

Description

Computes horizon-specific spillover measures from a fitted structural-break VAR model. The forecast-error variance decomposition uses generalized shocks and is therefore invariant to variable ordering.

Usage

```
dyspill(fit, h = 10, boot = 0, seed = NULL)
```

Arguments

`fit`	A fitted object returned by `varbreak()` or `netbreak()`.
`h`	Positive integer for forecast horizon.
`boot`	Number of bootstrap replications for standard errors and confidence intervals; `0` for none. Available for `varbreak()` and `netbreak()` fits.
`seed`	Optional seed for the bootstrapping. The seed of the calling session is restored on exit.

Details

For a regime-specific VAR,

$$y_t = c_r + \sum_{\ell=1}^{p} A_{\ell,r} y_{t-\ell} + u_t, \qquad E(u_t u_t') = \Sigma_r,$$

let $\Psi_{0,r} = I$ and

$$\Psi_{s,r} = \sum_{\ell=1}^{\min(p,s)} A_{\ell,r} \Psi_{s-\ell,r}.$$

The generalized variance share from shock j to variable i is

$$\theta^g_{ij}(H) = \frac{\sigma_{jj}^{-1} \sum_{s=0}^{H-1} (e_i' \Psi_s \Sigma e_j)^2}{\sum_{s=0}^{H-1} e_i' \Psi_s \Sigma \Psi_s' e_i}.$$

Rows are normalized to sum to one before spillover statistics are formed. For variable i, `from` is the contribution received from all other shocks, `to` is the contribution transmitted to all other variables, and `net` = `to` - `from`; a positive net value identifies a net transmitter. The total spillover index is the average off-diagonal contribution, expressed in percent.

The benchmark puts every lag matrix to zero and keeps Σ_r. The measures then depend on the error correlations only; comparing them with the fitted ones shows how much of the spillover comes from the dynamics. With two variables the benchmark total is $100\rho^2/(1+\rho^2)$.

The bootstrap is a recursive residual bootstrap within each regime: the residuals of the regime are resampled, the series is rebuilt from the fitted VAR of the regime, the model is refitted at the same break dates in the same way as `fit`, and the measures are recomputed. The break dates are treated as known. The intervals are percentile intervals, since the draws are skewed in small samples. Draws in which a refitted VAR is not stable are dropped.

Value

An object of class `"dyspill"` containing:

`horizon` The forecast horizon `h`.

`model` The source model type.

`variables` Names of the endogenous variables.

`break_grid` A data frame with one row per regime: the `regime` number; its first and last observation, `start` and `end`, counted in the estimation sample (which omits the first `lags` observations); and the coefficient and covariance regimes it belongs to, `coef_regime` and `cov_regime`.

`regimes` A list with one entry per regime. Each entry contains:

- `input_rows`: the first and last row of the data in the regime.
- `spectral_radius`: the largest modulus of the eigenvalues of the companion matrix of the VAR; the VAR is stable when it is below one.
- `fevd`: the generalized forecast-error variance decomposition, with rows normalized to sum to one.
- `total`: the total spillover index.
- `from`, `to` and `net`: the directional spillovers of each variable.
- `net_pairwise`: the matrix of net pairwise spillovers.
- `benchmark_total` and `benchmark_net`: `total` and `net` recomputed with all lag coefficients set to zero, so that they reflect the error correlations only (see Details).
- With `boot > 0`: the bootstrap standard errors `total_se` and `net_se`, and the percentile intervals `total_ci` and `net_ci`.

`boot` Returned only when `boot > 0`. A list with:

- `replications`: the number of bootstrap replications.
- `level`: the coverage probability of the intervals, taken from `ci_level` of the fit.
- `total`: the bootstrap draws of the total index, a matrix with one row per replication and one column per regime.
- `net`: the bootstrap draws of the net spillovers, an array of replications by variables by regimes.
- `differences`: a data frame with one row per pair of regimes, giving the `difference` in the total index (the later regime minus the earlier one), its bootstrap standard error `se`, and the percentile interval `lower` and `upper`.
- `dropped`: the number of draws dropped in each regime because the refitted VAR was not stable.

References

Diebold, F. X., and Yilmaz, K. (2012). Better to give than to receive: Predictive directional measurement of volatility spillovers. *International Journal of Forecasting*, 28(1), 57–66.

Examples

```
set.seed(1)
bigt <- 120
y <- matrix(0, bigt, 2)
colnames(y) <- c("y1", "y2")
for (tt in 2:bigt) {
  a <- if (tt > 60) matrix(c(0.2, 0.6, 0.6, 0.2), 2) else diag(0.2, 2)
  y[tt, ] <- a %*% y[tt - 1, ] + rnorm(2, sd = 0.3)
}

fit <- varbreak(y, lags = 1, m = 1, trim = 0.2)
dyspill(fit, h = 10, boot = 99, seed = 1)
```

---

housing *U.S. House Prices and the Macroeconomy*

Description

Quarterly data for the house price application of Ahamada and Diaz Sanchez (2013), 1959:Q4 to 2009:Q3.

Usage

```
housing
```

Format

A data frame with 200 rows and 6 columns:

date Quarter, such as `"1960:Q1"`.

dGDP Log difference of real GDP.

dC Log difference of real personal consumption expenditures.

dHP Log difference of the real home price index.

FFR Federal funds rate, in percent, first month of the quarter.

dI Change in `FFR`.

Source

FRED series GDPC1, PCEC, CPIAUCSL and FEDFUNDS, and the Shiller nominal home price index, seasonally adjusted by log-STL. Consumption and home prices are deflated by CPIAUCSL.

References

Ahamada, I., and Diaz Sanchez, J. L. (2013). A retrospective analysis of the house price macro-relationship in the United States. *International Journal of Central Banking*, 9(4), 153-174.

inflation *International Inflation*

Description

Monthly consumer price inflation for the G7 countries and the euro area, 1973:04 to 2007:12, from Bataa, Osborn, Sensier and van Dijk (2013).

Usage

```
inflation
```

Format

A data frame with 417 rows and 9 columns: `date`, such as `"1973:04"`, followed by inflation for `Canada`, `EuroArea`, `France`, `Germany`, `Italy`, `Japan`, `UK` and `US`. Inflation is $100 \times \Delta \log$ of the consumer price index, adjusted for outliers and seasonality by the authors.

Source

The replication files of Bataa et al. (2013).

References

Bataa, E., Osborn, D. R., Sensier, M., and van Dijk, D. (2013). Structural breaks in the international dynamics of inflation. *Review of Economics and Statistics*, 95(2), 646-659.

netbreak *Structural Breaks in a network VAR*

Description

Estimates structural breaks in a VAR whose coefficients are restricted by a fixed network matrix. With one lag, the model is

$$y_t = \mu_j + (\alpha_{1,j} W + \beta_{1,j} I) y_{t-1} + u_t,$$

for observations in regime j. With multiple lags, the model is

$$y_t = \mu_j + \sum_{\ell=1}^{p} (\alpha_{\ell,j} W + \beta_{\ell,j} I) y_{t-\ell} + u_t.$$

Usage

```
netbreak(y, W, lags, m, intercept = TRUE,
  coef_breaks = "all", row_normalize = FALSE,
  test_level = 0.05, ci_level = 0.95,
  trim = 0.15, verbose = FALSE, brv = FALSE,
  robust = c("none", "hc", "hac"), hetq = FALSE, prewhit = FALSE,
  restart = c("none", "brbp", "brbp_residual"),
  restart_B = 10, restart_verbose = FALSE, h = NULL)
```

Arguments

y	Numeric matrix/data frame with one column per network node.
W	Numeric square network matrix. Row i gives the weights used to form the network lag for equation i.
lags	Positive integer, number of lags.
m	The maximum number of breaks allowed.
intercept	Logical. If TRUE, include equation-specific intercepts μ_i.
coef_breaks	Parameters allowed to change across regimes. The parameters are one intercept per node, mu:<node>; the network coefficients α_ℓ, named network_lag1, network_lag2, and so on; and the own-lag coefficients β_ℓ, named own_lag1, own_lag2, and so on. The default "all" lets every parameter change. "none" or NULL holds them all constant, which requires brv = TRUE so that the disturbance covariance matrix can change; otherwise the code will return an error message. For anything in between, supply a character vector of parameter names or of these groups: • "intercepts", or "mu": all μ_i. • "network": all α_ℓ. • "own": all β_ℓ. • "dynamic": every lag coefficient, network and own. • "lag1", "lag2", ...: α_ℓ and β_ℓ at that lag. • "alpha1", "beta1", ...: α_ℓ or β_ℓ on its own. Entries are case-insensitive and may be combined, as in c("intercepts", "network_lag1").
row_normalize	Logical. If TRUE, row-normalize W; rows with zero row sums are left as zero rows.
test_level	Significance level used for selecting the number of breaks. One of 0.10, 0.05, 0.025 or 0.01. WDmax decides whether there is any break; if it is not significant the procedure stops and no break is reported. Otherwise the sequential tests of l against $l + 1$ breaks are applied from one break upwards, stopping at the first insignificant test or at m.
ci_level	Coverage probability of the reported confidence intervals for the break dates. Either 0.95 or 0.90.
trim	Trimming parameter. The minimum segment length is h = round(trim * nrow(y)). We recommend $h \geq 3(n + k)$, where n is the number of equations and k the number of regressors per equation, and a larger value for larger systems. A warning is issued if $h < 3(n + k)$.

verbose — Logical. If TRUE, print additional progress information from the testing and estimation.

brv — Logical. If TRUE, allow the disturbance covariance matrix to change across regimes.

robust — Inference for the coefficient-break tests, the coefficient standard errors and the break-date confidence intervals. "none" gives Gaussian quasi-likelihood-ratio tests, valid when the errors are serially uncorrelated and conditionally homoskedastic. "hc" gives the robust SupF statistic of Qu and Perron (2007, eq. 20) with a heteroskedasticity-consistent covariance estimate without autocovariance terms, valid when the errors are a martingale difference sequence. "hac" uses instead the quadratic spectral kernel with the automatic bandwidth of Andrews (1991), allowing for serial correlation. With enough lags the VAR errors are serially uncorrelated, and "hc" suffices for the tests and standard errors; with brv = TRUE and conditionally heteroskedastic errors of the ARCH type, the confidence intervals require "hac".

hetq — Logical. If TRUE, allow regressor moments to vary across regimes when computing confidence intervals for break dates.

prewhit — Logical. If TRUE, prewhiten the scores by a VAR(1) before the HAC estimation (Andrews and Monahan, 1992). Used only when robust = "hac".

restart — A bootstrap restarting procedure to check and improve convergence. It applies only when some coefficients are held constant; otherwise it is ignored with a warning. Set to "none" to turn it off, "brbp" for resampling bootstrap restarts, or "brbp_residual" for residual-based restarts.

restart_B — Integer, number of restart values used when restart != "none".

restart_verbose — Logical. If TRUE, print restart progress.

h — Optional positive integer for forecast horizon. If supplied, attach Diebold–Yilmaz generalized spillover measures in spillover.

Details

The interpretation of testing$statistic depends on robust.

- robust = "none" gives the SupLR statistic. The code can test the parameters specified by coef_breaks, the disturbance covariance when brv = TRUE, or both.
- robust = "hc" or "hac" gives the robust SupF statistic, for the parameters only, because the covariance-break critical values are case dependent under heteroskedasticity or serial correlation; it assumes a constant error covariance. With brv = TRUE, the estimates, standard errors and confidence intervals account for the covariance breaks; under "hc" the intervals further require errors without ARCH-type dependence.

Value

An object of class c("netbreak", "sysbreak") containing:

spec — A summary of the setup, including the sample size bigt, the number of equations n, the total number of NVAR parameters per regime q, the arguments m, lags, intercept, row_normalize,

`trim`, `brv`, `robust`, `hetq`, `prewhit`, `test_level` and `ci_level`, the network matrix `W`, the equation and parameter names, the retained input rows `y_rows` after discarding the lags, and a record of the `coef_breaks` selector.

`testing` The tests, reported at `test_level`: `statistic`, testing no break against k breaks for every $k = 1, \ldots, m$, with its `critical_values`; `statistic_type`, `"SupLR"` or `"SupF"`, and `NA` when a requested robust test is unavailable; `wdmax` and `wdmax_critical_values`; the `sequential` tests of l against $l + 1$ breaks, each containing `l`, a `statistic` and its `critical_values`; and the number of `changing_parameters`, which includes the changing covariance parameters when `robust = "none"`.

`br_selected` The outcome of the break-number determination at `test_level`: the selected number of `breaks`, the WDmax statistic with its critical value and significance flag, and the `sequential` steps taken. `breaks` is `0` when WDmax is not significant, and `NA` when the tests are unavailable for the requested specification.

`estimation` The estimates related to the selected number of breaks: estimated `breaks`; their confidence intervals `ci_breaks`; `coefficients` by regimes and their confidence intervals; disturbance `covariance` matrices. This component is `NULL` when no break is detected, in which case only `testing` and `br_selected` are informative.

`spillover` When `h` is supplied and at least one break is selected, regime-specific Diebold–Yilmaz generalized spillover measures returned by `dyspill`.

`y` The responses used in estimation, rows `spec$y_rows` of `y`.

Note that `m` is the *maximum* number of breaks allowed. Testing output is reported for every value from 1 through `m`, while `estimation` corresponds to the number of breaks selected by the procedure under `test_level`. Parameters excluded by `coef_breaks` are repeated across regime blocks. The optional `spillover` component is omitted when `h = NULL`. The fit has `print()`, `summary()`, `plot()` and the accessors in `sysbreak-methods`.

References

Andrews, D. W. K. (1991). Heteroskedasticity and autocorrelation consistent covariance matrix estimation. *Econometrica*, 59(3), 817–858.

Andrews, D. W. K., and Monahan, J. C. (1992). An improved heteroskedasticity and autocorrelation consistent covariance matrix estimator. *Econometrica*, 60(4), 953–966.

Zhu, X., Pan, R., Li, G., Liu, Y., and Wang, H. (2017). Network vector autoregression. *The Annals of Statistics*, 45(3), 1096–1123.

Qu, Z., and Perron, P. (2007). Estimating and testing structural changes in multivariate regressions. *Econometrica*, 75(2), 459–502.

Examples

```
set.seed(5)
bigt <- 80
W <- matrix(c(0, 1, 1, 0), 2, 2, byrow = TRUE)
y <- matrix(0, bigt, 2)
colnames(y) <- c("y1", "y2")
for (tt in 2:bigt) {
  alpha <- if (tt <= 40) 0.05 else 0.75
```

```
  beta <- 0.1
  y[tt, ] <- alpha * as.numeric(W %*% y[tt - 1, ]) +
    beta * y[tt - 1, ] + rnorm(2, sd = 0.2)
}

fit <- netbreak(
  y = y, W = W, lags = 1, m = 1,
  coef_breaks = c("network", "own"),
  trim = 0.2
)
fit$estimation$breaks
```

`netsim` *Simulated Network VAR*

Description

One draw from Scenario 1 of Han and Lee (2024): a network VAR for 20 nodes over 300 periods, with breaks after periods 100 and 200.

Usage

```
netsim
```

Format

A list with two components:

y A 300 by 20 matrix of observations, with columns `node1` to `node20`.

W The 20 by 20 row-normalized network matrix. Entry (i, l) is $1/n_i$ if node i follows node l and 0 otherwise, where n_i is the number of nodes that i follows.

Details

In regime j,

$$y_{it} = V_i'\gamma_j + \sum_{\ell} \alpha_{\ell,j}(Wy_{t-\ell})_i + \sum_{\ell} \beta_{\ell,j} y_{i,t-\ell} + e_{it}, \qquad e_{it} \sim N(0, 0.1^2).$$

Regime 1 has one lag, with $\alpha = -0.10$ and $\beta = 0.20$. Regimes 2 and 3 have two lags, with $\alpha = (0.20, -0.22)$, $\beta = (-0.12, 0.40)$ and $\alpha = (-0.12, 0.10)$, $\beta = (0.25, -0.40)$. The covariates V_i are fixed, so $V_i'\gamma_j$ is a node intercept that changes across regimes. The in-degrees of the network follow a power law, as in Zhu et al. (2017).

Source

Simulated with `set.seed(1)` following Han and Lee (2024).

References

Han, Y., and Lee, T. C. M. (2024). Structural break detection in non-stationary network vector autoregression models. *IEEE Transactions on Network Science and Engineering*, 11(5), 4134-4145.

Zhu, X., Pan, R., Li, G., Liu, Y., and Wang, H. (2017). Network vector autoregression. *The Annals of Statistics*, 45(3), 1096-1123.

`ordbreak` *Ordered Structural Breaks in a System of Equations*

Description

Estimation of a multiple-equation system in which the coefficients of one group of equations change before those of another group. The two break dates are estimated jointly and are not restricted to coincide.

Usage

```
ordbreak(set1, set2, data,
  coef_breaks1 = "all", coef_breaks2 = "all",
  trim = 0.2, hetq = TRUE, max_break_gap = NULL,
  test_level = 0.05, ci_level = 0.95,
  confidence_intervals = FALSE,
  ci_grid_radius = 20, ci_replications = 5000, ci_step = 1000,
  ci_grid_step = 0.02, ci_seed = NULL, ci_verbose = FALSE,
  tol = 1e-8, max_iter = 1000)
```

Arguments

`set1`	The equations whose coefficients change at the first date. A formula such as `y1 ~ x1 + x2` for a single equation, or `list(y1 ~ x1 + x2, y2 ~ x2 + x3)` for several. The number of regressors may differ across equations. An intercept is added to each equation unless the formula indicates otherwise.
`set2`	The equations whose coefficients change at the second date, written in the same way as `set1`. Each equation of the system belongs to exactly one of the two sets.
`data`	Data frame used to evaluate the formulas.
`coef_breaks1`	An expression for which coefficients of `set1` are allowed to change at the first date. The default `"all"` allows all of them to change. Otherwise supply a list of formulas, one per equation of `set1`, where the left-hand side should specify the equation and the right-hand side selects the coefficients of that equation that may change: • `y1 ~ x1`: the intercept and the coefficient on `x1` change. • `y1 ~ x1 - 1`: the coefficient on `x1` only. • `y1 ~ 0`: no coefficient of that equation changes. Coefficients left out are held constant across both dates. At least one coefficient of `set1` must be allowed to change.

`coef_breaks2` The same, for `set2` and the second date.

`trim` Trimming parameter, which must lie in $(0, 0.5)$. The minimum segment length is `floor(trim * nrow(data))`.

`hetq` Logical. If `TRUE`, allow regressor moments to vary across regimes when computing confidence intervals for break dates.

`max_break_gap` Truncation used when computing the test statistic. If `NULL`, `floor(sqrt(T))` is used, as in the original GAUSS program.

`test_level` Significance level at which the critical value is reported. One of `0.10`, `0.05`, `0.025` or `0.01`.

`ci_level` Coverage probability of the reported confidence intervals for the break dates. Either `0.95` or `0.90`.

`confidence_intervals`
Logical. If `TRUE`, simulate confidence intervals for the two break dates. This is the expensive part of the procedure and is therefore off by default.

`ci_grid_radius` Half-width of the grid on which the limiting distribution is simulated.

`ci_replications`
Number of simulation replications.

`ci_step` Number of steps used to discretize each Brownian motion.

`ci_grid_step` Spacing of the simulation grid.

`ci_seed` Optional seed for the simulation. The seed of the calling session is restored on exit.

`ci_verbose` Logical. If `TRUE`, print simulation progress.

`tol` Convergence tolerance of the feasible GLS iterations.

`max_iter` Maximum number of feasible GLS iterations.

Details

The coefficients are stacked equation by equation in the order the formulas are given, so those of `set1` occupy the leading `q1` positions and those of `set2` the remaining `q2`. `ordcheck` reports this layout without estimating anything, which is worth doing before a long run.

The test is that of Qu and Perron (2007, Section 6.4) for locally ordered breaks. The test for globally ordered breaks in their Section 6.5, whose limiting distribution differs, is not implemented.

Value

An object of class `"ordbreak"` containing:

`spec` The setup: the sample size `bigt`, the number of equations `n`, the minimum segment length `h`, the number of coefficients in each set `q1` and `q2`, the number of equations in the first set `n1`, the names of the coefficients allowed to change at each date, `changing1` and `changing2`, the arguments `trim`, `hetq` and `trun`, the input formulas split into `set1` and `set2`, the equation and coefficient names, the retained data rows `y_rows` after discarding missing values, and the selection matrix `S`.

`testing` The SupLR statistic for ordered breaks, `sup_lr_ordered`, its `critical_values` at `test_level`, the pair `truncated_breaks` the statistic is computed at, and the log-likelihoods `H1like` and `H0like` it is built from. The critical value is indexed by the number of coefficients allowed to change, not by the total number of coefficients.

`estimation` The estimated `breaks`, given as rows of `data`; the coefficients `beta1` and `beta2` of the two regimes; the `residuals` of the model at the estimated breaks, one column per equation; and the coefficient shifts `delta1` and `delta2` occurring at the two dates; and `ci_breaks`, a two by two matrix when `confidence_intervals = TRUE` and `NULL` otherwise, also given as rows of `data`. Its rows are the two break dates and its columns the lower and upper bounds at `ci_level`.

Note that the ordering is imposed rather than tested. The equations in `set1` are taken to break first, so exchanging the two sets specifies a different model. Both specifications are tested against the same no-break null, and their values of `sup_lr_ordered` can be compared.

References

Qu, Z., and Perron, P. (2007). Estimating and testing structural changes in multivariate regressions. *Econometrica*, 75(2), 459–502.

Examples

```
set.seed(13)
bigt <- 60
x1 <- rnorm(bigt)
x2 <- rnorm(bigt)
y1 <- 1 + 0.5 * x1 + rnorm(bigt, sd = 0.3)
y2 <- 1 + 0.5 * x2 + rnorm(bigt, sd = 0.3)
y1[21:bigt] <- y1[21:bigt] + 1.5 * x1[21:bigt]
y2[36:bigt] <- y2[36:bigt] - 1.5 * x2[36:bigt]
dat <- data.frame(y1 = y1, y2 = y2, x1 = x1, x2 = x2)

fit <- ordbreak(y1 ~ x1, y2 ~ x2, data = dat, trim = 0.2)
fit$estimation$breaks
```

`ordcheck` *Coefficient Layout of an Ordered-Break Specification*

Description

Reports the coefficients of an ordered-break model, which set of equations they belongs to, and which of them are allowed to change, without estimating anything.

Usage

```
ordcheck(set1, set2, data, coef_breaks1 = "all", coef_breaks2 = "all")
```

Arguments

set1	The equations whose coefficients change at the first date, written as in ordbreak.
set2	The equations whose coefficients change at the second date.
data	Data frame used to evaluate the formulas.
coef_breaks1	Which coefficients of set1 are allowed to change at the first date. See ordbreak.
coef_breaks2	The same, for set2 and the second date.

Value

The layout is printed: one row per coefficient, giving its position in the coefficient vector, its name, the set it belongs to, whether it is allowed to change, and the date at which it changes.

Examples

```
set.seed(13)
dat <- data.frame(y1 = rnorm(40), y2 = rnorm(40),
                  x1 = rnorm(40), x2 = rnorm(40))

ordcheck(y1 ~ x1 + x2, y2 ~ x1 + x2, data = dat,
        coef_breaks1 = list(y1 ~ x1))
```

---

plot.sysbreak *Plot a Structural-Break Fit*

Description

Plots each series with the estimated break dates (dashed lines), their confidence intervals (shaded) and, optionally, the fitted values of the regime-specific model.

Usage

```
## S3 method for class 'sysbreak'
plot(x, which = NULL, dates = NULL, fitted = TRUE, ...)
```

Arguments

x	A fit returned by sysbreak, varbreak or netbreak.
which	Series to plot, as indices or names. By default all series, or the first four when there are more.
dates	Optional vector with one entry per row of the data passed to the fitting function, including the initial lags of a VAR and any rows dropped for missing values; the observation in row r is placed at dates[r]. Numeric values or dates are used as the horizontal axis; character values, such as "1983:Q1", are used as labels for the axis.

fitted	Logical. If TRUE, add the fitted values.
...	Graphical parameters. type, col, lwd, lty and pch apply to the plotted series; main and ylab may be vectors with one entry per panel; the others, such as xlab, ylim or las, are passed to plot() when each panel is set up.

Value

x, invisibly.

See Also

sysbreak-methods, summary.sysbreak

Examples

```
set.seed(11)
bigt <- 40
x <- rnorm(bigt)
y1 <- 1 + 0.4 * x + rnorm(bigt, sd = 0.3)
y2 <- -0.5 + 0.2 * x + rnorm(bigt, sd = 0.3)
y1[21:40] <- y1[21:40] + 1.2 - 0.6 * x[21:40]
y2[21:40] <- y2[21:40] - 0.8 + 0.4 * x[21:40]
dat <- data.frame(y1 = y1, y2 = y2, x = x)
fit <- sysbreak(cbind(y1, y2) ~ x, dat, m = 1, trim = 0.3)
plot(fit)
```

---

summary.sysbreak *Summarize a Structural-Break Fit*

Description

A report of a fit returned by sysbreak, varbreak or netbreak: the break number, the break dates with their confidence intervals, and a coefficient table for each regime. print() of the fit gives the full output.

Usage

```
## S3 method for class 'sysbreak'
summary(object, ...)

## S3 method for class 'summary.sysbreak'
print(x, digits = max(3L, getOption("digits") - 3L), ...)
```

Arguments

object	A fit returned by sysbreak(), varbreak() or netbreak().
...	Not used.
x	An object returned by summary().
digits	Number of significant digits in the coefficient tables.

Value

An object of class `"summary.sysbreak"`, a list with the `model` type, the numbers of equations `n` and observations `bigt`, the `tests` for the break-number decision, the number of breaks `selected`, and, when at least one break is selected, the break dates with their confidence intervals (`breaks`), the rows of the data in each regime (`regimes`) and the coefficient tables (`coefficients`): estimate, standard error, z value and two-sided p-value, one table per regime, treating the break dates as known.

See Also

`sysbreak-methods`, `plot.sysbreak`

Examples

```
set.seed(11)
bigt <- 40
x <- rnorm(bigt)
y1 <- 1 + 0.4 * x + rnorm(bigt, sd = 0.3)
y2 <- -0.5 + 0.2 * x + rnorm(bigt, sd = 0.3)
y1[21:40] <- y1[21:40] + 1.2 - 0.6 * x[21:40]
y2[21:40] <- y2[21:40] - 0.8 + 0.4 * x[21:40]
dat <- data.frame(y1 = y1, y2 = y2, x = x)
fit <- sysbreak(cbind(y1, y2) ~ x, dat, m = 1, trim = 0.3)
summary(fit)
```

`sysbreak` *Structural Breaks in a System of Equations*

Description

Estimation of a multiple-equation system affected by structural breaks in the regression coefficients and/or the variance covariance matrix of the residuals.

Usage

```
sysbreak(model, data = NULL, m, coef_breaks = "all",
  test_level = 0.05, ci_level = 0.95,
  trim = 0.15, verbose = FALSE, brv = FALSE,
  robust = c("none", "hc", "hac"), hetq = FALSE, prewhit = FALSE,
  restart = c("none", "brbp", "brbp_residual"),
  restart_B = 10, restart_verbose = FALSE)
```

Arguments

model	A formula such as `cbind(y1, y2) ~ x1 + x2` for a system with common regressors across equations, or `list(y1 ~ x1 + x2, y2 ~ x2 + x3)` for a system allowing different regressors across equations. The number of regressors may differ across equations, e.g., `list(y1 ~ x1 + x2, y2 ~ x3)` An intercept is added to each equation unless the formula indicates otherwise.
data	Data frame used to evaluate `model`.
m	Integer, the maximum number of breaks allowed when testing for breaks.
coef_breaks	An expression for which regression coefficients are allowed to change across regimes. The default `"all"` allows all regression coefficients to change. `"none"` or `NULL` restrictions all coefficients to be constant. \ This case requires setting `brv = TRUE`, so that the disturbance covariance matrix\ can change; otherwise the code will return an error message. For in between, supply a list of formulas, one per equation, where left-hand side should specify the equation and the right-hand side selects the coefficients of that equation that may change: • `y1 ~ x1, y2 ~ x2`: the coefficient on `x1` in the first equation and the coefficient on `x2` in the second equation can change. • `y1 ~ 1, y2 ~ x2+ x4`: the intercept in the first equation and the two slope coefficients in the second equation. • `y1 ~ 1 + x1, y2~0`: the intercept and `x1` in the first equation, and no coefficient in the second equation.
test_level	Significance level used to select the number of breaks. One of `0.10`, `0.05`, `0.025` or `0.01`. The double-maximum tests decide whether there is any break; if WDmax is not significant the procedure stops and no break is reported. Otherwise the sequential tests of l against $l + 1$ breaks are applied from one break upwards, stopping at the first insignificant test or at `m`.
ci_level	Coverage probability of the reported confidence intervals for the break dates. Either `0.95` or `0.90`.
trim	Trimming parameter. The minimum segment length is `h = round(trim * nrow(y))`. We recommend $h \geq 3(n + k)$, where n is the number of equations and k the number of regressors per equation, and a larger value for larger systems. A warning is issued if $h < 3(n + k)$.
verbose	Logical. If `TRUE`, print additional information from the estimation.
brv	Logical. If `TRUE`, allow the covariance matrix of the residuals to change across regimes.
robust	Inference for the coefficient-break tests, the coefficient standard errors and the break-date confidence intervals. `"none"` gives Gaussian quasi-likelihood-ratio tests, valid when the errors are serially uncorrelated and conditionally homoskedastic. `"hc"` gives the robust SupF statistic of Qu and Perron (2007, eq. 20) with a heteroskedasticity-consistent covariance estimate without autocovariance terms, valid when the errors are a martingale difference sequence. `"hac"` uses instead the quadratic spectral kernel with the automatic bandwidth of Andrews (1991), allowing for serial correlation.
hetq	Logical. If `TRUE`, allow regressor moments to vary across regimes when computing confidence intervals for break dates.

prewhit Logical. If TRUE, prewhiten the scores by a VAR(1) before the HAC estimation (Andrews and Monahan, 1992). Used only when robust = "hac".

restart A bootstrap restarting procedure to check and improve convergence. It applies only when some coefficients are held constant; otherwise it is ignored with a warning. Set to "none" to turn it off, "brbp" for resampling bootstrap restarts, or "brbp_residual" for residual-based restarts.

restart_B Number of restarting values used when restart != "none"; 10 is recommended.

restart_verbose
Logical. If TRUE, print restart progress.

Details

The interpretation of testing$statistic depends on robust.

- robust = "none" gives the SupLR statistic. The code can test the coefficients specified by coef_breaks, the disturbance covariance when brv = TRUE, or both.
- robust = "hc" or "hac" gives the robust SupF statistic, for the coefficients only, because the covariance-break critical values are case dependent under heteroskedasticity or serial correlation; it assumes a constant error covariance. With brv = TRUE, the estimates, standard errors and confidence intervals account for the covariance breaks; under "hc" the intervals further require errors without ARCH-type dependence.

Value

An object of class "sysbreak" containing:

spec A summary of the setup, including the sample size bigt, the number of equations n, the total number of regression coefficients per regime q, the arguments m, trim, brv, robust, hetq, prewhit, test_level and ci_level, the input formula or formulas, the equation and coefficient names, the retained data rows y_rows after discarding missing values, and a record of the coef_breaks selector.

testing The tests, reported at test_level: statistic, testing no break against k breaks for every $k = 1, \ldots, m$, with its critical_values; statistic_type, "SupLR" or "SupF", and NA when a requested robust test is unavailable; wdmax and wdmax_critical_values; the sequential tests of l against $l + 1$ breaks, each containing l, a statistic and its critical_values; and the number of changing_parameters, which includes the changing covariance parameters when robust = "none".

br_selected The outcome of the break-number determination at test_level: the selected number of breaks, the WDmax statistic with its critical value and significance flag, and the sequential steps taken. breaks is 0 when WDmax is not significant, and NA when the tests are unavailable for the requested specification.

estimation The estimates related to the selected number of breaks: estimated breaks; their confidence intervals ci_breaks; coefficients by regimes and their confidence intervals; disturbance covariance matrices. This component is NULL when no break is detected, in which case only testing and br_selected are informative.

y The responses used in estimation, rows spec$y_rows of data.

Note that `m` is the *maximum* number of breaks allowed. Testing output is reported for every value from 1 through `m`, while `estimation` corresponds to the number of breaks selected by the procedure under `test_level`. The fit has `print()`, `summary()`, `plot()` and the accessors in `sysbreak-methods`.

References

Andrews, D. W. K. (1991). Heteroskedasticity and autocorrelation consistent covariance matrix estimation. *Econometrica*, 59(3), 817–858.

Andrews, D. W. K., and Monahan, J. C. (1992). An improved heteroskedasticity and autocorrelation consistent covariance matrix estimator. *Econometrica*, 60(4), 953–966.

Bai, J., and Perron, P. (1998). Estimating and testing linear models with multiple structural changes. *Econometrica*, 66(1), 47–78.

Qu, Z., and Perron, P. (2007). Estimating and testing structural changes in multivariate regressions. *Econometrica*, 75(2), 459–502.

Examples

```
set.seed(11)
bigt <- 40
x <- rnorm(bigt)
y1 <- 1 + 0.4 * x + rnorm(bigt, sd = 0.3)
y2 <- -0.5 + 0.2 * x + rnorm(bigt, sd = 0.3)
y1[21:40] <- y1[21:40] + 1.2 - 0.6 * x[21:40]
y2[21:40] <- y2[21:40] - 0.8 + 0.4 * x[21:40]
dat <- data.frame(y1 = y1, y2 = y2, x = x)

fit <- sysbreak(cbind(y1, y2) ~ x, data = dat, m = 1, trim = 0.2)
fit$estimation$breaks
```

---

sysbreak-methods *Methods for Displaying Structural-Break Fits*

Description

Fits returned by `sysbreak`, `varbreak` and `netbreak`. All refer to the estimates at the selected number of breaks.

Usage

```
## S3 method for class 'sysbreak'
coef(object, ...)

## S3 method for class 'sysbreak'
vcov(object, ...)

## S3 method for class 'sysbreak'
```

```
confint(object, parm, level = NULL, type = c("breaks", "coef"), ...)

## S3 method for class 'sysbreak'
residuals(object, ...)

## S3 method for class 'sysbreak'
fitted(object, ...)

## S3 method for class 'sysbreak'
nobs(object, ...)
```

Arguments

`object`	A fit returned by `sysbreak()`, `varbreak()` or `netbreak()`.
`...`	Not used.
`parm`	Breaks (`type = "breaks"`) or coefficients (`type = "coef"`) to report, as indices or row names.
`level`	Coverage probability. By default the `ci_level` of the fit, the level of the intervals shown by `print()` and `summary()`. For break dates either `0.95` or `0.90`, the two levels computed at estimation; for coefficients any value in $(0, 1)$.
`type`	`"breaks"` for the break dates or `"coef"` for the regression coefficients.

Value

`coef` A named vector of the regime coefficients: all coefficients of regime 1, then those of regime 2, and so on. Each name joins the regime and the coefficient label used by `summary()`, as in `"regime1:y1:x"` (equation `y1`, regressor `x`) or `"regime2:mu:node3"` for `netbreak`. Coefficients held constant by `coef_breaks` are repeated in every regime.

`vcov` The covariance matrix of `coef()`, with rows and columns in the same order and with the same names. When `coef_breaks` holds coefficients constant, the matrix is singular, since the repeated entries of a constant coefficient are perfectly correlated.

`confint` For `type = "breaks"`, a matrix with one row per break: the lower bound, the estimated break date and the upper bound. For `type = "coef"`, the lower and upper bounds of confidence intervals, estimate $\pm$ normal quantile times standard error, treating the break dates as known.

`residuals`, `fitted` Matrices with one column per equation and one row per observation; the row names are the rows of the data (`spec$y_rows`).

`nobs` The number of observations used.

When no break is selected the regime estimates are not computed, and all but `nobs` stop with an error.

See Also

`summary.sysbreak`, `plot.sysbreak`

Examples

```
set.seed(11)
bigt <- 40
x <- rnorm(bigt)
y1 <- 1 + 0.4 * x + rnorm(bigt, sd = 0.3)
y2 <- -0.5 + 0.2 * x + rnorm(bigt, sd = 0.3)
y1[21:40] <- y1[21:40] + 1.2 - 0.6 * x[21:40]
y2[21:40] <- y2[21:40] - 0.8 + 0.4 * x[21:40]
dat <- data.frame(y1 = y1, y2 = y2, x = x)
fit <- sysbreak(cbind(y1, y2) ~ x, dat, m = 1, trim = 0.3)

coef(fit)
confint(fit)
confint(fit, level = 0.90)
confint(fit, type = "coef")
head(residuals(fit))
nobs(fit)
```

---

varbreak *Structural Breaks in a VAR*

Description

Estimation of a VAR affected by structural breaks in the regression coefficients and/or the variance covariance matrix of the residuals.

Usage

```
varbreak(y, lags, m, intercept = TRUE, coef_breaks = "all",
  test_level = 0.05, ci_level = 0.95,
  trim = 0.15, verbose = FALSE, brv = FALSE,
  robust = c("none", "hc", "hac"), hetq = FALSE, prewhit = FALSE,
  restart = c("none", "brbp", "brbp_residual"),
  restart_B = 10, restart_verbose = FALSE, h = NULL)
```

Arguments

y	Numeric response matrix with one column per variable.
lags	Positive integer, number of lags.
m	Integer, maximum number of breaks allowed.
intercept	Logical. If TRUE, include an intercept in the regressors matrix.
coef_breaks	Coefficient-break selector, applied after the VAR lag matrix is built. The default "all" lets all VAR coefficients change. Use "none" or NULL for no coefficient changes, for which brv = TRUE is required so that the covariance matrix of the residuals can change. Use a list such as list(y1 ~ ., y2 ~ 0) to restrict breaks to selected regression coefficients.

`test_level` Significance level used for selecting the number of breaks. One of `0.10`, `0.05`, `0.025` or `0.01`. WDmax decides whether there is any break; if it is not significant the procedure stops and no break is reported. Otherwise the sequential tests of l against $l + 1$ breaks are applied from one break upwards, stopping at the first insignificant test or at `m`.

`ci_level` Coverage probability of the reported confidence intervals for the break dates. Either `0.95` or `0.90`.

`trim` Trimming parameter. The minimum segment length is `h = round(trim * nrow(y))`. We recommend $h \geq 3(n + k)$, where n is the number of equations and k the number of regressors per equation, and a larger value for larger systems. A warning is issued if $h < 3(n + k)$.

`verbose` Logical. If `TRUE`, print additional progress information from the testing and estimation.

`brv` Logical. If `TRUE`, allow the disturbance covariance matrix to change across regimes.

`robust` Inference for the coefficient-break tests, the coefficient standard errors and the break-date confidence intervals. `"none"` gives Gaussian quasi-likelihood-ratio tests, valid when the errors are serially uncorrelated and conditionally homoskedastic. `"hc"` gives the robust SupF statistic of Qu and Perron (2007, eq. 20) with a heteroskedasticity-consistent covariance estimate without autocovariance terms, valid when the errors are a martingale difference sequence. `"hac"` uses instead the quadratic spectral kernel with the automatic bandwidth of Andrews (1991), allowing for serial correlation. With enough lags the VAR errors are serially uncorrelated, and `"hc"` suffices for the tests and standard errors; with `brv = TRUE` and conditionally heteroskedastic errors of the ARCH type, the confidence intervals require `"hac"`.

`hetq` Logical. If `TRUE`, allow regressor moments to vary across regimes when computing confidence intervals for break dates.

`prewhit` Logical. If `TRUE`, prewhiten the scores by a VAR(1) before the HAC estimation (Andrews and Monahan, 1992). Used only when `robust = "hac"`.

`restart` A bootstrap restarting procedure to check and improve convergence. It applies only when some coefficients are held constant; otherwise it is ignored with a warning. Set to `"none"` to turn it off, `"brbp"` for resampling bootstrap restarts, or `"brbp_residual"` for residual-based restarts.

`restart_B` Integer, number of restart values used when `restart != "none"`.

`restart_verbose` Logical. If `TRUE`, print restart progress.

`h` Optional positive integer for forecast horizon. If supplied, attach Diebold–Yilmaz generalized spillover measures in `spillover`.

Details

The interpretation of `testing$statistic` depends on `robust`.

- `robust = "none"` gives the SupLR statistic. The code can test the coefficients specified by `coef_breaks`, the disturbance covariance when `brv = TRUE`, or both.

- `robust = "hc"` or `"hac"` gives the robust SupF statistic, for the coefficients only, because the covariance-break critical values are case dependent under heteroskedasticity or serial correlation; it assumes a constant error covariance. With `brv = TRUE`, the estimates, standard errors and confidence intervals account for the covariance breaks; under `"hc"` the intervals further require errors without ARCH-type dependence.

Value

An object of class `c("varbreak", "sysbreak")` containing:

`spec` A summary of the setup, including the sample size `bigt`, the number of equations `n`, the total number of coefficients per regime `q`, the arguments `m`, `lags`, `intercept`, `trim`, `brv`, `robust`, `hetq`, `prewhit`, `test_level` and `ci_level`, the equation and coefficient names, the retained input rows `y_rows` after discarding the lags, and the `coef_breaks` selector.

`testing` The tests, reported at `test_level`: `statistic`, testing no break against k breaks for every $k = 1, \ldots, m$, with its `critical_values`; `statistic_type`, `"SupLR"` or `"SupF"`, and `NA` when a requested robust test is unavailable; `wdmax` and `wdmax_critical_values`; the `sequential` tests of l against $l + 1$ breaks, each containing `l`, a `statistic` and its `critical_values`; and the number of `changing_parameters`, which includes the changing covariance parameters when `robust = "none"`.

`br_selected` The outcome of the break-number determination at `test_level`: the selected number of `breaks`, the WDmax statistic with its critical value and significance flag, and the `sequential` steps taken. `breaks` is `0` when WDmax is not significant, and `NA` when the tests are unavailable for the requested specification.

`estimation` The estimates related to the selected number of breaks: estimated `breaks`; their confidence intervals `ci_breaks`; `coefficients` by regimes and their confidence intervals; disturbance `covariance` matrices. This component is `NULL` when no break is detected, in which case only `testing` and `br_selected` are informative.

`spillover` When `h` is supplied and at least one break is selected, regime-specific Diebold–Yilmaz generalized spillover measures returned by `dyspill`.

`y` The responses used in estimation, rows `spec$y_rows` of `y`.

Note that `m` is the *maximum* number of breaks allowed. Testing output is reported for every value from 1 through `m`, while `estimation` corresponds to the number of breaks selected by the procedure under `test_level`. The optional `spillover` component is omitted when `h = NULL`. The fit has `print()`, `summary()`, `plot()` and the accessors in `sysbreak-methods`.

References

Andrews, D. W. K. (1991). Heteroskedasticity and autocorrelation consistent covariance matrix estimation. *Econometrica*, 59(3), 817–858.

Andrews, D. W. K., and Monahan, J. C. (1992). An improved heteroskedasticity and autocorrelation consistent covariance matrix estimator. *Econometrica*, 60(4), 953–966.

Bai, J., and Perron, P. (1998). Estimating and testing linear models with multiple structural changes. *Econometrica*, 66(1), 47–78.

Qu, Z., and Perron, P. (2007). Estimating and testing structural changes in multivariate regressions. *Econometrica*, 75(2), 459–502.

Examples

```
set.seed(12)
bigt <- 45
y <- matrix(0, bigt, 2)
for (tt in 2:bigt) {
  shift <- if (tt > 24) c(0.8, -0.6) else c(0, 0)
  y[tt, ] <- shift +
    c(0.3 * y[tt - 1, 1], -0.2 * y[tt - 1, 2]) +
    rnorm(2, sd = 0.3)
}

fit <- varbreak(y, lags = 1, m = 1, trim = 0.2)
fit$estimation$breaks
```

Index

∗ **datasets**
    data1, 3
    data2, 4
    housing, 8
    inflation, 9
    netsim, 13

brtype, 2

coef.sysbreak *(*sysbreak-methods*)*, 22
confint.sysbreak *(*sysbreak-methods*)*, 22

data1, 3
data2, 4
dynobreak, 5
dyspill, 6, *12*, *26*

fitted.sysbreak *(*sysbreak-methods*)*, 22

housing, 8

inflation, 9

netbreak, *2*, 9, *17, 18*, *22*
netsim, 13
nobs.sysbreak *(*sysbreak-methods*)*, 22

ordbreak, 14, *17*
ordcheck, *15*, 16

plot(), *12*, *22*, *26*
plot.sysbreak, 17, *19*, *23*
print.summary.sysbreak
        *(*summary.sysbreak*)*, 18

residuals.sysbreak *(*sysbreak-methods*)*,
        22

summary(), *12*, *22*, *26*
summary.sysbreak, 18, *18*, *23*
sysbreak, *2*, *3*, *17, 18*, 19, *22*
sysbreak-methods, 22

varbreak, *2*, *17, 18*, *22*, 24
vcov.sysbreak *(*sysbreak-methods*)*, 22