

Package: tcv (via r-universe)

May 24, 2026

Type Package

Title Determining the Number of Factors in Poisson Factor Models via Thinning Cross-Validation

Version 0.1.0

Date 2025-09-01

Description Implements methods for selecting the number of factors in Poisson factor models, with a primary focus on Thinning Cross-Validation (TCV). The TCV method is based on the 'data thinning' technique, which probabilistically partitions each count observation into training and test sets while preserving the underlying factor structure. The Poisson factor model is then fit on the training set, and model selection is performed by comparing predictive performance on the test set. This toolkit is designed for researchers working with high-dimensional count data in fields such as genomics, text mining, and social sciences. The data thinning methodology is detailed in Dharamshi et al. (2025) [doi:10.1080/01621459.2024.2353948](https://doi.org/10.1080/01621459.2024.2353948) and Wang et al. (2025) [doi:10.1080/01621459.2025.2546577](https://doi.org/10.1080/01621459.2025.2546577).

License GPL (>= 3)

Encoding UTF-8

Imports stats, GFM, countsplit, irlba

LinkingTo Rcpp, RcppArmadillo

Suggests knitr, rmarkdown, testthat (>= 3.0.0)

SystemRequirements C++17

RoxygenNote 7.3.2

URL <https://github.com/Wangzhijingwzj/tcv>

BugReports <https://github.com/Wangzhijingwzj/tcv/issues>

NeedsCompilation yes

Author Zhijing Wang [aut, cre], Heng Peng [aut], Peirong Xu [aut]

Maintainer Zhijing Wang <wangzhijing@sjtu.edu.cn>

Repository https://cran.r-universe.dev

Date/Publication 2025-09-23 07:40:02 UTC

RemoteUrl https://github.com/cran/tcv

RemoteRef HEAD

RemoteSha cc9e2cc3622dbc1a5b784220e936f8f0b69eb66b

Contents

add_identifiability	2
chooseFacNumber_ratio	3
multiDT	4
Index	6

add_identifiability *Enforce Identifiability Constraints on Factor Model Components*

Description

Post-processes the factor scores (H), loadings (B), and intercept (mu) to ensure a unique solution by applying SVD-based rotation. This typically enforces orthogonality constraints.

Usage

```
add_identifiability(H, B, mu)
```

Arguments

H	A numeric matrix of factor scores (n x q).
B	A numeric matrix of factor loadings (p x q).
mu	A numeric vector for the intercept/mean term.

Value

A list containing the transformed H, B, and mu that satisfy identifiability constraints.

chooseFacNumber_ratio *Estimating the Number of Factor by Eigenvalue Ratio of Natural Parameter Matrix in Generalized Factor Model.*

Description

Estimating the Number of Factor by Eigenvalue Ratio of Natural Parameter Matrix in Generalized Factor Model.

Usage

```
chooseFacNumber_ratio(
  XList,
  types,
  q_set = 1:5,
  select_method = c("SVR", "IC"),
  offset = FALSE,
  dc_eps = 1e-04,
  maxIter = 30,
  verbose = FALSE,
  parallelList = NULL
)
```

Arguments

XList	A list that containing an n by p matrix, where n is the number of samples, p is the number of features.
types	The type of data. In Poisson factor models, the type is "poisson".
q_set	The maximum number of factors for conducting ratio methods. Default as 5.
select_method	The methods to conduct GFM. Default as AM.
offset	Default as FALSE.
dc_eps	The tolerance for convergence. Default as 1e-4.
maxIter	The maximum iteration times. Default as 30.
verbose	Default as FALSE
parallelList	Whether to use parallel. Default as NULL.

Value

The number of factors estimated by ratio methods.

multiDT

Perform Thinning Cross-Validation to Select Factor Number

Description

This function implements a K-fold cross-validation scheme based on data thinning (count splitting) to determine the optimal number of factors for a Poisson matrix factorization model.

Usage

```
multiDT(x, K = 5, rmax = 8)
```

Arguments

x	A numeric matrix of count data (n x p).
K	An integer, the number of folds for cross-validation. Default is 5.
rmax	An integer, the maximum number of factors to test. Default is 8.

Value

A list containing two elements: - TCV: A numeric vector of total cross-validation error for each number of factors. - TICV: A numeric vector of the natural logarithm of TCV.

Examples

```
# 1. Set parameters for data generation
# Use smaller dimensions for a quick example
n <- 50 # Number of samples
p <- 30 # Number of features
true_q <- 2 # True number of factors

# 2. Generate data from a Poisson factor model
set.seed(123) # For reproducibility

# Factor matrix (scores)
FF <- matrix(rnorm(n * true_q), nrow = n, ncol = true_q)

# Loading matrix
BB <- matrix(runif(p * true_q, min = -1, max = 1), nrow = p, ncol = true_q)

# Intercept term
a <- runif(p, min = 0, max = 1)

# Enforce identifiability for a unique generating model
FF0 <- add_identifiability(FF, BB, a)$H
BB0 <- add_identifiability(FF, BB, a)$B
alpha <- add_identifiability(FF, BB, a)$mu

# Calculate the mean matrix (lambda) with some noise
```

```
lambda <- exp(FF0 %*% t(BB0) + rep(1, n) %*% t(alpha) + matrix(rnorm(n*p, 0, 0.5), n, p))

# Generate the final count data matrix 'x'
x <- matrix(rpois(n * p, lambda = as.vector(lambda)), nrow = n, ncol = p)

# 3. Run multiDT to find the best number of factors
# Use small K and rmax for a quick example run
cv_results <- multiDT(x, K = 2, rmax = 4)

# 4. Print results and select the best 'r' based on the minimum TCV
print(cv_results$TCV)
best_r <- which.min(cv_results$TCV)
```

Index

`add_identifiability`, 2
`chooseFacNumber_ratio`, 3
`multiDT`, 4