

Package: tergo (via r-universe)

February 5, 2025

Title Style Your Code Fast

Version 0.1.8

Description Provides a set of functions that allow users for styling their R code according to the 'tidyverse' style guide. The package uses a native Rust implementation to ensure the highest performance. Learn more about 'tergo' at <https://rtergo.pagacz.io>.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.2

Config/rextendr/version 0.3.1

SystemRequirements Cargo (Rust's package manager), rustc

NeedsCompilation yes

Biarch true

Depends R (>= 4.1.0)

Suggests rextendr (== 0.3.1), roxygen2, rstudioapi (>= 0.7), devtools, pkgdown, desc, knitr, rmarkdown

URL <https://rtergo.pagacz.io>, <https://github.com/kpagacz/tergo>

BugReports <https://github.com/kpagacz/tergo/issues>

VignetteBuilder knitr

Author Konrad Pagacz [aut, cre], Maciej Nasinski [ctb], The authors of the dependency Rust crates [ctb] (see inst/AUTHORS file for details)

Maintainer Konrad Pagacz <konrad.pagacz@gmail.com>

Repository CRAN

Date/Publication 2025-02-05 09:20:02 UTC

Contents

get_default_config	2
style	3
style_file	4
style_pkg	4
style_text	6
Index	7

get_default_config	<i>Get the default configuration</i>
--------------------	--------------------------------------

Description

This configuration is used by the styling functions if no value is provided for the configuration keys. It can also serve as the base for you custom configuration.

Usage

```
get_default_config()
```

Details

The configuration values:

- indent - the number of spaces to use for indentation.
- line_length - the maximum number of characters in a line.
- embracing_op_no_nl - whether to allow a newline after an embracing operator.
- allow_nl_after_assignment - whether to allow a newline after an assignment operator.
- space_before_complex_rhs_in_formula - whether to add a space before a complex right-hand side in a formula.
- strip_suffix_whitespace_in_function_defs - whether to strip suffix whitespace in function definitions.
- function_line_breaks - the type of line breaks in function definitions when arguments do not fit. Possible values are: hanging, double, single.
- insert_newline_in_quote_call - whether to insert a newline in calls to quote.

Value

list with the default configuration

Examples

```
config <- get_default_config()
print(config)

# Make the indent 4 spaces
config$indent <- 4

# Make the maximum line length 80 characters
config$line_length <- 80
```

style	<i>Style a package</i>
-------	------------------------

Description

Style a package

Usage

```
style(config_file = "tergo.toml", configuration = list(), ...)
```

Arguments

`config_file` (character) The path to the configuration file. Default "tergo.toml".
`configuration` (list) Configuration for formatting. Default `list()`.
... additional parameters to `style_pkg()`

Details

Configuration is read from a file named `tergo.toml` in the root of the package. The precedence of the configuration is (from the highest to lowest):

1. The configuration passed to the function.
2. The configuration file.

To see possible configuration options, see `get_default_config()`.

Value

No return value, called for side effects.

Examples

```
style()
style(config_file = "tergo.toml", configuration = list())
```

style_file

Style a file

Description

Style a file

Usage

```
style_file(file, configuration = list())
```

Arguments

file (character) the file to format
configuration (list) Configuration for formatting. Default list().

Details

To see possible configuration options, see [get_default_config\(\)](#).

Value

No return value, called for side effects.

Examples

```
tmp <- tempfile()
file_conn <- file(tmp)
writeLines(c("function(){}", "A<-7"), file_conn)
close(file_conn)
style_file(file = tmp, configuration = list())
unlink(tmp)
```

style_pkg*Style a package*

Description

Style a package

Usage

```
style_pkg(  
  path = ".",  
  config_file = "tergo.toml",  
  configuration = list(),  
  force = FALSE,  
  extensions = c(".R", ".r"),  
  verbose = interactive()  
)
```

Arguments

path	(character) The path to the package. Default ".".
config_file	(character) The path to the configuration file. Default "tergo.toml".
configuration	(list) Configuration for formatting. Default list().
force	(logical(1)) Whether to format the files even if no package was found. TRUE - format the .R and .r files found in the directory (recursive). FALSE exit without formatting anything. Default FALSE.
extensions	(character) The extensions of the files to format. Default c(".R", ".r").
verbose	(logical(1)) Whether per file status and run statistics should be printed. Default interactive().

Details

Configuration is read from a file named `tergo.toml` in the root of the package. The precedence of the configuration is (from the highest to lowest):

1. The configuration passed to the function.
2. The configuration file.

To see possible configuration options, see [get_default_config\(\)](#).

Value

No return values, called for side effects.

Examples

```
style_pkg()  
style_pkg(path = "./tergo", config_file = "custom_tergo.toml", verbose = TRUE)
```

`style_text`*Style text*

Description

Style text

Usage

```
style_text(text, configuration = list())
```

Arguments`text` (character) the text to style`configuration` (list) Configuration for formatting. Default `list()`.**Details**

This function is vectorized. To see possible configuration options, see [get_default_config\(\)](#).

Value

(character) the text formatted as R code

Examples

```
code <- "function(){}"  
style_text(code)
```

```
code <- c("function(){}", "A<-7")  
style_text(code)
```

Index

`get_default_config`, [2](#)
`get_default_config()`, [3-6](#)

`style`, [3](#)
`style_file`, [4](#)
`style_pkg`, [4](#)
`style_pkg()`, [3](#)
`style_text`, [6](#)