Package: tesseract (via r-universe)

October 12, 2026

Type Package

Title Open Source OCR Engine

Version 5.3.1

Description Bindings to 'Tesseract': a powerful optical character recognition (OCR) engine that supports over 100 languages. The engine is highly configurable in order to tune the detection algorithms and obtain the best possible results.

License Apache License 2.0

URL https://docs.ropensci.org/tesseract/
https://ropensci.r-universe.dev/tesseract

BugReports https://github.com/ropensci/tesseract/issues

SystemRequirements Tesseract >= 3.03 (libtesseract-dev / tesseract-devel) and Leptonica (libleptonica-dev / leptonica-devel). On Debian you need to install the English training data separately (tesseract-ocr-eng)

Imports Rcpp (>= 0.12.12), pdftools (>= 1.5), curl, rappdirs, digest

LinkingTo Rcpp

RoxygenNote 7.3.3

Suggests magick (>= 1.7), spelling, knitr, tibble, rmarkdown

Encoding UTF-8

VignetteBuilder knitr

Language en-US

NeedsCompilation yes

Author Jeroen Ooms [aut, cre] (ORCID: <https://orcid.org/0000-0002-4035-0289>)

Maintainer Jeroen Ooms <jeroenooms@gmail.com>

Config/pak/sysreqs libleptonica-dev libtesseract-dev tesseract-ocr-eng

Repository https://cran.r-universe.dev

Date/Publication 2026-09-12 09:40:02 UTC

RemoteUrl https://github.com/cran/tesseract

RemoteRef HEAD

RemoteSha 6a9b239c6f2011d8c138584bf1782b5d59e1d8ee

Contents

ocr 2
tesseract 3
tesseract_download 4

Index **6**

`ocr` *Tesseract OCR*

Description

Extract text from an image. Requires that you have training data for the language you are reading. Works best for images with high contrast, little noise and horizontal text. See tesseract wiki and our package vignette for image preprocessing tips.

Usage

```
ocr(image, engine = tesseract("eng"), HOCR = FALSE)

ocr_data(image, engine = tesseract("eng"))
```

Arguments

`image`	file path, url, or raw vector to image (png, tiff, jpeg, etc)
`engine`	a tesseract engine created with `tesseract()`. Alternatively a language string which will be passed to `tesseract()`.
`HOCR`	if `TRUE` return results as HOCR xml instead of plain text

Details

The `ocr()` function returns plain text by default, or hOCR text if hOCR is set to `TRUE`. The `ocr_data()` function returns a data frame with a confidence rate and bounding box for each word in the text.

References

Tesseract: Improving Quality

See Also

Other tesseract: `tesseract()`, `tesseract_download()`

Examples

```
text <- ocr("https://jeroen.github.io/images/testocr.png")
cat(text)

xml <- ocr("https://jeroen.github.io/images/testocr.png", HOCR = TRUE)
cat(xml)

df <- ocr_data("https://jeroen.github.io/images/testocr.png")
print(df)

# Full roundtrip test: render PDF to image and OCR it back to text
curl::curl_download("https://cran.r-project.org/doc/manuals/r-release/R-intro.pdf", "R-intro.pdf")
orig <- pdftools::pdf_text("R-intro.pdf")[1]

# Render pdf to png image
img_file <- pdftools::pdf_convert("R-intro.pdf", format = 'tiff', pages = 1, dpi = 400)
unlink("R-intro.pdf")

# Extract text from png image
text <- ocr(img_file)
unlink(img_file)
cat(text)


engine <- tesseract(options = list(tessedit_char_whitelist = "0123456789"))
```

---

tesseract *Tesseract Engine*

Description

Create an OCR engine for a given language and control parameters. This can be used by the ocr and ocr_data functions to recognize text.

Usage

```
tesseract(
  language = "eng",
  datapath = NULL,
  configs = NULL,
  options = NULL,
  cache = TRUE
)

tesseract_params(filter = "")

tesseract_info()
```

Arguments

language	string with language for training data. Usually defaults to eng
datapath	path with the training data for this language. Default uses the system library.
configs	character vector with files, each containing one or more parameter values. These config files can exist in the current directory or one of the standard tesseract config files that live in the tessdata directory. See details.
options	a named list with tesseract parameters. See details.
cache	speed things up by caching engines
filter	only list parameters containing a particular string

Details

Tesseract control parameters can be set either via a named list in the `options` parameter, or in a `config` file text file which contains the parameter name followed by a space and then the value, one per line. Use `tesseract_params()` to list or find parameters. Note that that some parameters are only supported in certain versions of libtesseract, and that invalid parameters can sometimes cause libtesseract to crash.

See Also

Other tesseract: `ocr()`, `tesseract_download()`

Examples

```
tesseract_params('debug')
```

---

tesseract_download *Tesseract Training Data*

Description

Helper function to download training data from the official tessdata repository. On Linux, the fast training data can be installed directly with yum or apt-get.

Usage

```
tesseract_download(
  lang,
  datapath = NULL,
  model = c("fast", "best"),
  progress = interactive()
)
```

Arguments

`lang`	three letter code for language, see tessdata repository.
`datapath`	destination directory where to download store the file
`model`	either `fast` or `best` is currently supported. The latter downloads more accurate (but slower) trained models for Tesseract 4.0 or higher
`progress`	print progress while downloading

Details

Tesseract uses training data to perform OCR. Most systems default to English training data. To improve OCR performance for other languages you can to install the training data from your distribution. For example to install the spanish training data:

- tesseract-ocr-spa (Debian, Ubuntu)
- `tesseract-langpack-spa` (Fedora, EPEL)

On Windows and MacOS you can install languages using the tesseract_download function which downloads training data directly from github and stores it in a the path on disk given by the `TESSDATA_PREFIX` variable.

References

tesseract wiki: training data

See Also

Other tesseract: `ocr()`, `tesseract()`

Examples

```
## Not run:
if(is.na(match("fra", tesseract_info()$available)))
  tesseract_download("fra", model = 'best')
french <- tesseract("fra")
text <- ocr("https://jeroen.github.io/images/french_text.png", engine = french)
cat(text)

## End(Not run)
```

Index

∗ **tesseract**
ocr, 2
tesseract, 3
tesseract_download, 4

ocr, 2, *3–5*
ocr_data, *3*
ocr_data *(*ocr*)*, 2

tessdata *(*tesseract_download*)*, 4
tesseract, *2*, 3, *5*
tesseract(), *2*
tesseract_download, *2*, 4, *4, 5*
tesseract_info *(*tesseract*)*, 3
tesseract_params *(*tesseract*)*, 3
tesseract_params(), *4*