Package: theeuh (via r-universe)

October 14, 2026

Title Write Spaces to Korean Sentences

Version 0.1.5

Description Restores spacing in Korean sentences using a bundled neural network model and 'ONNX Runtime' <https://onnxruntime.ai/> through 'churon'. Inference runs locally without a web service or automatic downloads.

License GPL (>= 3)

Encoding UTF-8

RoxygenNote 7.3.3

URL https://github.com/mrchypark/theeuh, https://mrchypark.github.io/theeuh/

BugReports https://github.com/mrchypark/theeuh/issues

Depends R (>= 4.0.0)

Imports churon (>= 0.1.13)

SystemRequirements ONNX Runtime (>= 1.28.0, optional at runtime)

Suggests covr, testthat (>= 3.2.0)

Config/testthat/edition 3

NeedsCompilation no

Author Chanyub Park [aut, cre] (ORCID: <https://orcid.org/0000-0001-6474-2570>), Heewon Jeon [aut] (Author of KoSpacing code and bundled model assets)

Maintainer Chanyub Park <mrchypark@gmail.com>

Repository https://cran.r-universe.dev

Date/Publication 2026-10-14 11:10:02 UTC

RemoteUrl https://github.com/cran/theeuh

RemoteRef HEAD

RemoteSha 9d603d7e60392a79942152bdac3d62dabbabaffe

Contents

space 2

Index **3**

`space` *Write spaces to Korean sentences.*

Description

Write spaces to Korean sentences.

Usage

```
space(ko_sents)
```

Arguments

`ko_sents`	A character vector of Korean sentences. Missing values are preserved. Sentences longer than 198 characters are truncated with a warning.

Details

The bundled model is loaded on the first non-empty, non-missing sentence. ONNX Runtime must be configured first; see `churon::install_onnx_runtime()`. No runtime is downloaded automatically. On supported non-Windows runtimes, telemetry is disabled during model initialization. If another package initializes ONNX Runtime first, set `ORT_DISABLE_TELEMETRY=1` before starting R to disable telemetry globally.

Value

Sentences with restored spacing: a character string for one sentence, or an unnamed list of character strings for multiple sentences. An empty character vector returns `list()`.

Examples

```
if (churon::check_onnx_runtime_available()) {
  space("\uC774\uC81C\uCEE4\uBC0B\uD558\uBA74")
}
```

Index

churon::install_onnx_runtime(), *2*

space, 2